

(12) **United States Patent**  
**Black et al.**

(10) **Patent No.:** **US 10,251,345 B2**  
(45) **Date of Patent:** **\*Apr. 9, 2019**

(54) **HANDHELD APPARATUS AND METHOD FOR TRIMMING A PLANT**

(71) Applicant: **Easy Trim LLC**, Broomfield, CO (US)

(72) Inventors: **Joseph Black**, Broomfield, CO (US);  
**Michael Cross**, Broomfield, CO (US)

(73) Assignee: **Easy Trim LLC**, Broomfield, CO (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 8 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/115,888**

(22) PCT Filed: **Feb. 4, 2015**

(86) PCT No.: **PCT/US2015/014485**

§ 371 (c)(1),

(2) Date: **Aug. 1, 2016**

(87) PCT Pub. No.: **WO2015/120067**

PCT Pub. Date: **Aug. 13, 2015**

(65) **Prior Publication Data**

US 2017/0188523 A1 Jul. 6, 2017

#### Related U.S. Application Data

(60) Provisional application No. 61/937,061, filed on Feb. 7, 2014.

(51) **Int. Cl.**

**A01G 3/08** (2006.01)

**A01G 3/053** (2006.01)

(52) **U.S. Cl.**

CPC ..... **A01G 3/08** (2013.01); **A01G 3/0535** (2013.01)

(58) **Field of Classification Search**

CPC .... A01D 46/005; A01D 46/247; A01D 46/24;  
A01G 3/037; A01G 3/053; A01G 3/0535;  
A01G 3/08

(Continued)

(56) **References Cited**

#### U.S. PATENT DOCUMENTS

1,723,151 A 8/1929 Goodwin  
3,165,880 A \* 1/1965 Buie, Jr. .... A01D 46/24  
56/336

(Continued)

#### FOREIGN PATENT DOCUMENTS

JP 08-033425 A 2/1996  
WO 00/08915 A1 2/2000  
WO 2013/090779 A1 6/2013

#### OTHER PUBLICATIONS

Photos of relevant Arrdvark Bud Trimmer from YouTube video clip entitled "Arrdvark Bud Trimmer", 4 pages, uploaded on Mar. 17, 2012 by Ian Fergie at <https://www.youtube.com/watch?v=xP0Z6qic8rg>.

(Continued)



*Primary Examiner* — Robert E Pezzuto

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(57) **ABSTRACT**

The present application provides a handheld plant trimming apparatus. The handheld plant trimming apparatus, in one aspect, includes a wand having a longitudinal axis. The wand includes a wand inlet tube defining a void and an elongate slot, an outlet port having a through bore parallel to the wand longitudinal axis and an outlet bore where the outlet bore is in fluid communication with the void, and a handle. A cutting element is contained in the wand inlet tube and coupled to a motor to provide rotative force to the cutting element. A drum is in fluid communication with the

(Continued)



wand and a vacuum pulls plant parts that are cut by the cutting element from the wand to the drum.

24 Claims, 11 Drawing Sheets

(58) Field of Classification Search

USPC ..... 56/328.1, 332–336, 327.1  
See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS


3,420,046 A \* 1/1969 Johnson ..... A01D 46/005  
406/52  
3,507,107 A \* 4/1970 Mccutcheon ..... A01D 46/253  
56/336  
3,564,826 A \* 2/1971 Middleton, Jr. .... A01D 46/005  
56/328.1  
3,732,858 A 5/1973 Banko  
3,945,375 A 3/1976 Banko  
3,969,878 A \* 7/1976 Morganeier ..... A01D 46/005  
56/328.1  
4,357,790 A \* 11/1982 Tyros ..... A01D 46/253  
56/328.1  
4,519,193 A \* 5/1985 Yoshida ..... A01D 46/24  
348/89  
4,558,561 A \* 12/1985 Mendenhall ..... A01D 46/005  
56/327.1  
4,598,710 A 7/1986 Kleinberg et al.

4,964,472 A 10/1990 Cleworth  
5,005,347 A \* 4/1991 Kedem ..... A01D 46/253  
56/328.1  
5,176,628 A 1/1993 Charles et al.  
5,588,289 A 12/1996 Wilson  
5,685,838 A 11/1997 Peters et al.  
5,862,595 A 1/1999 Keane  
6,743,245 B2 6/2004 Lobdell  
6,751,871 B2 6/2004 Furnish  
6,886,258 B2 5/2005 Swanson  
7,107,887 B2 9/2006 Whited  
7,500,343 B2 \* 3/2009 Hsia ..... A01D 46/253  
56/332  
D618,253 S 6/2010 Wilson et al.  
7,810,305 B2 \* 10/2010 Macidull ..... A01D 46/247  
56/333  
8,161,652 B2 4/2012 Delfini et al.  
8,251,917 B2 8/2012 Almazan  
8,298,253 B2 10/2012 Charles  
8,430,824 B2 4/2013 Videbaek et al.  
8,690,793 B2 4/2014 Ranpura et al.  
8,914,981 B1 12/2014 Paez  
9,078,640 B1 7/2015 An  
9,258,943 B1 2/2016 Ruger  
2008/0189870 A1 8/2008 Dayton et al.  
2012/0279193 A1 11/2012 Mosman

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/US2015/014485 dated Apr. 28, 2015, 11 pages.

\* cited by examiner



**FIG. 1**




FIG. 2






FIG. 3







**FIG. 4**



**FIG. 5**




**FIG. 6**




**FIG. 7**







**FIG. 8**




**FIG. 9**




**FIG. 10**




**FIG. 11**




**FIG. 12**




**FIG. 13**



**FIG. 14**



**FIG. 15**



**FIG. 16**



## 1

**HANDHELD APPARATUS AND METHOD  
FOR TRIMMING A PLANT****CROSS-REFERENCE TO RELATED PATENT  
APPLICATIONS**

The present application claims priority to U.S. Provisional Patent Application Ser. No. 61/937,061, filed Feb. 7, 2014, titled HANDHELD APPARATUS AND METHOD FOR TRIMMING A PLANT, the disclosure of which is incorporated herein by reference as if set out in full.

**BACKGROUND**

Small volume agricultural crops need to be harvested similar to a higher volume or a mass produced volume of crops. Unfortunately, most of the harvesting tools are not viable or economical for the harvesting of certain spices and herbs, such as for example, rosemary, mint, oregano, basil, cilantro, medicinal herbs, and the like. It is often necessary to hand trim with a scissor (or pick) the flowers and plants associated with these crops, especially when smaller volumes are produced.

Hand trimming crops often involves using a scissor to cut, rather than tear, portions of the plant while manipulating the crops. This is a labor intensive process that can become manually taxing over time as more product is handled and trimmed. To facilitate the process, many tools and devices have been developed to automatically trim plants, for example, separating the leaves from the stems. One particularly effective automatic plant trimmer is described in International Patent Application WO 2013/090779, filed Dec. 14, 2012, titled PLANT TRIMMING APPARATUS AND METHODS OF USING THE SAME, the disclosure of which is incorporated herein as if set out in full. WO 2013/090779 provides a relatively large container and a series of grates, blades, and fans to trim the product. A unique bagging system allows the constituent components of the plants being harvested to be separated. The plant trimmer of WO 2013/090779 is not a hand trimming device, however.

Automatic trimmers, such as the above described automatic trimmer, are often expensive and more effective at higher volumes of plant harvesting. While the above described plant trimmer is effective, hand trimming of plants is still gentler on the plants and more cost effective for lower volumes.

Accordingly, there is a need for a handheld automatic trimmer that is more cost effective for harvesting plants.

**SUMMARY**

This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary, and the foregoing Background, is not intended to identify key aspects or essential aspects of the claimed subject matter. Moreover, this Summary is not intended for use as an aid in determining the scope of the claimed subject matter.

The technology of the present application provides a handheld plant trimming apparatus. The handheld plant trimming apparatus, in one aspect, includes a wand having a longitudinal axis. The wand includes a wand inlet tube defining a void and an elongate slot, an outlet port having a through bore parallel to the wand longitudinal axis and an outlet bore where the outlet bore is in fluid communication with the void, and a handle. A cutting element is contained

## 2

in the wand inlet tube and coupled to a motor to provide rotative force to the cutting element. A drum is in fluid communication with the wand and a vacuum pulls plant parts that are cut by the cutting element from the wand to the drum.

These and other aspects of the present system and method will be apparent after consideration of the Detailed Description and Figures herein.

**DRAWINGS**

Non-limiting and non-exhaustive embodiments of the present invention, including the preferred embodiment, are described with reference to the following figures, wherein like reference numerals refer to like parts throughout the various views unless otherwise specified.

FIG. 1 depicts a functional block diagram of an automatic plant trimming system consistent with the technology of the present application.

FIG. 2 depicts the wand of the automatic plant trimming system of FIG. 1.

FIG. 3 depicts a cross section view of the wand of FIG. 2.

FIG. 4 depicts a perspective view of a portion of the wand of FIG. 2.

FIG. 5 depicts a perspective view of a cutting element consistent with the technology of the present application.

FIG. 6 depicts a perspective view of a driver hub consistent with the technology of the present application.

FIG. 7 depicts a perspective view of the driver hub coupled to the cutting element consistent with the technology of the present application.

FIG. 8 depicts a perspective view of an idle hub consistent with the technology of the present application.

FIG. 9 depicts a perspective view of the idle hub coupled to the cutting element consistent with the technology of the present application.

FIG. 10 depicts a perspective view of the cutting element slidably received in a portion of the wand consistent with the technology of the present application.

FIG. 11 depicts a perspective view of a bearing coupled to the idle hub consistent with the technology of the present application.

FIG. 12 depicts a perspective view of a drive and a portion of the wand consistent with the technology of the present application.

FIG. 13 depicts a perspective view of a filtration system consistent with the technology of the present application.

FIG. 14 depicts an alternative outlet port consistent with the technology of the present application.

FIG. 15 depicts a portion of the outlet port of FIG. 14.

FIG. 16 depicts an alternative configuration of a portion of the wand and the cutting element consistent with the technology of the present application.

**DETAILED DESCRIPTION**

Embodiments of the technology of the present application are described more fully below with reference to the accompanying figures, which form a part hereof and show, by way of illustration, specific exemplary embodiments. These embodiments are disclosed in sufficient detail to enable those skilled in the art to practice the technology disclosed herein. However, embodiments may be implemented in many different forms and should not be construed as being limited to the embodiments set forth herein. The following detailed description is, therefore, not to be taken in a limiting



sense. Moreover, the technology of the present application will be described with relation to exemplary embodiments. The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any embodiment described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other embodiments. Additionally, unless specifically identified otherwise, all embodiments described herein should be considered exemplary. As mentioned above, hand trimming as is allowed by the technology of the present application is gentler on plants than industrial or large plant trimming apparatuses in the normal course. The hand trimming technology of the present application advantageously also allows for the harvested material to be hang dried prior to curing rather than using drying racks prior to curing, which some growers prefer.

FIG. 1 shows an automatic handheld plant trimming system 100. The automatic handheld plant trimming system 100 includes a wand 102, a motor 104 (which may have an external power source 105 such as a wall socket to grid power or a battery pack as shown), and a vacuum 106, which is shown as a conventional wet/dry vacuum, but could be any conventional suction pump. The motor 104 is connected to the wand 102 via a drive 108. The drive 108 is shown as a flexible cable to facilitate the movement of the handheld wand 102. In operation, the rotation of the motor causes the drive 108 to rotate.

The motor 104 may be a variable speed motor with a speed controller 107. The speed controller 107 optionally is coupled to the vacuum 106 via cable 101 as well to allow coordination between the wand 102 speed and the vacuum 106 speed as will be explained further below. The vacuum 106 may be provided with a separate variable speed drive as a matter of design choice. The wand 102 has a port 110 to which a flexible conduit 112 is attached. The flexible conduit 112 is coupled to the port 110 on a first end 114 and the vacuum 106 inlet port 116 on a second end 118 opposite the first end. The vacuum 106 also has a discharge with a filtration system as will be explained further below. The flexible conduit 112 may be coupled to one or both of the wand 102 or the drive 108 using one or more ties 111. The ties may comprise twist ties, VELCRO® hook and loop ties, or the like. Coupling the flexible conduit 112 in this manner facilitates operation of the device. Moreover, the flexible conduit 112 and a wand handle 202 of the wand 102 may be coupled in a manner to form a loop 120 construct similar to, for example, a saber grip. The vacuum 106 may be provided with a separate variable speed drive and motor as a matter of design choice. The automatic handheld plant trimming system 100 may be provided with a female socket to receive a male plug such that the vacuum 106 motor and controller may be powered from the system power supply (whether a battery pack, generator, or wall socket).

With reference now to FIG. 2, the wand 102 is shown in more detail. The wand 102 includes the aforementioned wand handle 202, an outlet port 204, and a wand inlet tube 206. The wand 102 may comprise a single monolithic unit or may be modular. The wand 102 forms a generally cylindrical tube having a wand axis 208 extending longitudinally from a wand tip 201 to a wand base 203. The outlet port 204 has a port axis 210 generally perpendicular to the wand axis 208. While the outlet port 204 is shown roughly centered on the wand 102 between the wand handle 202 and the wand inlet tube 206, the outlet port could be located in alternative locations. Additionally, the outlet port 204 could be located at a base 203 of the wand handle 202 and arranged such that the port axis 210 is parallel to the wand axis 208.

The port axis 210 is currently shown perpendicular to the wand axis 208. As mentioned, the port axis 210 being parallel (or offset by zero degrees) to the wand axis 208 is possible, and would facilitate movement of product. Reducing the angle of the port axis 210 to wand axis 208 to less than about forty-five degrees facilitates movement of product. In some embodiments, the angle should be less than about twenty degrees. Of course, any angle between zero and ninety is possible.

FIG. 3 shows a cross section of the wand 102. The wand 102 houses a hollow, cylindrical cutting element 302 (best seen in FIG. 5), which is shown as a pair of helically shaped blades 304 each having a leading edge cutting surface 306. While shown as helically shaped, the cutting elements 302 may be any curved shape. The wand inlet tube 206 has an elongated slot 308 that has a cutting edge 310. The elongated slot 308 allows plant product access to the cutting area where the cutting surface 306 and the cutting edge 310 meet. The cutting element 302 has an outer diameter about equal to the inner diameter of the wand inlet tube 206 to minimize any gap between the cutting surface 306 and the cutting edge 310. The helical shape of the blades 304 in part simulate a scissor motion comparable to handheld scissors for trimming. As will be explained further below, the vacuum 106 provides a suction force at the elongated slot 308 through the flexible conduit 112 and wand outlet port 204. The suction force helps draw and stand the plant product in the elongated slot 308 such that the cutting surface 306 forces the plant product against the cutting edge 310 to provide a cut or shearing force, similar to a scissor, to slice rather than tear the plant product, which minimizes damage to the plant product.

With reference to FIGS. 4-12, the parts of the wand 102 will be described in some detail. The parts will be described in connection with the assembly of a modular wand 102. However, the wand 102, or certain component parts explained herein, may be a monolithic unit or units in certain embodiments. First, the outlet port 204 is coupled to the wand inlet tube 206. The wand inlet tube 206 has an outer diameter  $D_1$ . The outlet port 206 comprises a through bore 402 generally collinear with the wand axis 208. The through bore 402 has an inner diameter  $D_2$  slightly larger than the outer diameter  $D_1$  to allow the wand inlet tube 206 to be slidably received in the through bore 402. As shown, a portion first thread 401 on the wand inlet tube 206 extends beyond the outlet port 204. The wand inlet tube 206 has a second thread 403 arranged on the opposite side of the wand inlet tube 206 from the first thread 401. The threads will be further explained below. The outlet port 206 has an outlet bore 404 (see FIG. 3) that is shown substantially perpendicular to the through bore 402. The outlet bore 404 is shown substantially cylindrical, but could have alternative shapes to facilitate movement of the plant material from the wand 102 into the flexible conduit 112. One of many possible outlet ports have an alternative outlet bore as shown in FIG. 14.

The wand inlet tube 206 and the outlet port 204 may be frictionally engaged. Alternatively, the connection may be a snap fit connection. In still other embodiments, the outlet bore 204 may include a locking bore 406 or bores 406 capable of receiving a set screw 408 or set screws 408s that is/are receivable in an aligned, threaded bore 410 or bores on the wand inlet tube 206. Alternatively, the set screw 408 may abut the outer surface of the wand inlet tube 206 rather than engage an aligned bore. The set screw 408 may be tightened using an Allen wrench 409 as shown. Of course, the set screw could be replaced by a pin, rivet, or the like.



## 5

The cutting element **302** is next prepared for insertion into the wand inlet tube **206** such that the cutting element **302** is rotatably coupled to the wand **102**. The cutting element **302** has a proximal end (or bottom) **502** and a distal end (or top) **504**. The orientation of the proximal end **502** and the distal end **504** ensures that the cutting surface **306** will move across the elongated slot **308** in a clockwise direction. Notice, the cutting surface **306** could be oriented such that the cutting surface **306** moves across the elongated slot **308** in a counter-clockwise direction. In still other embodiments, both the leading edge **506** and the trailing edge **508** may be formed into cutting surfaces **306** such that the orientation or rotation of the cutting element **302** is not overly relevant for performance.

As shown in FIG. 6, a driver hub **602** has a bottom disc **604** and a drive shaft **606**. The drive shaft **606** has a groove **610**. The groove **610** includes a central hole and a radially extending slot or channel. The slot may extend from a surface **608** of the drive shaft **606** internal to the central hole of the groove. The groove **610** extends from a proximal end **612** of the driver hub towards, but not completely, to the distal end **614** of the shaft **606**. The groove **610** acts as a keyway for the drive **108** as will be explained further below. The bottom disc **604** has a pin bore **616** to receive a pin **618**. The bottom disc **604** of the drive hub **602** is inserted into the proximal end **502** (or bottom) of the cutting element **302** until the pin **618** seats against divots **702** (FIG. 5) in the proximal end **502** of the cutting element **302** as shown in FIG. 7.

The distal end **504** of the cutting element **302** receives an idle hub **802** as shown in FIG. 8. The idle hub **802** comprises a top disc **804** and an alignment shaft **806**. The alignment shaft has a central alignment bore **808**. The top disc **804** has a pin bore **810** to receive a pin **812**. The top disc **804** of the idle hub is inserted into the distal end **504** (or top) of the cutting element **302** until the pin **812** seats against divots **902** (FIG. 5) in the distal end **504** of the cutting elements as shown in FIG. 9. As can be appreciated, the driver hub **602** and the idle hub **802** are similar in construction and how they are coupled to the cutting element.

The cutting element **302**, with the driver hub **602** and the idle hub **802**, is received in the outlet port **204** and the wand inlet tube **206** as shown in FIG. 10. A bearing **1002** is coupled to the driver hub **602** by sliding a bearing **1002** over the drive shaft **606** of the driver hub **602** as shown in FIG. 10. Similarly, a bearing **1002** is coupled to the idle hub **802** by sliding a bearing **1002** over the alignment shaft **806** (FIG. 11). With reference back to FIGS. 2 and 3, housings **1102**<sub>1,2</sub> are threaded onto the threads **403** and **401** of the wand inlet tube **206**. The housing **1102**<sub>1</sub> proximate the idle hub **802** has a blind hole **1104**. One of the bearings **1002** fits in the blind hole **1104** and allows the cutting element to rotate with respect to the housing **1102**<sub>1</sub>. The housing **1102**<sub>2</sub> has a through bore with a countersunk shoulder **1106** (see FIG. 3) on which the bearing **1002** rests to allow the cutting element **302** and driver hub **602** to rotate with respect to the housing **1102**<sub>2</sub>.

The motor **104** and the driver hub **602** are coupled using the drive **108**. The drive **108**, which is shown as a flexible cable, is threaded through the wand handle **202** as shown in FIG. 12. The drive **108** terminates in a rotor **1202** having a protrusion **1204**. The protrusion **1204**, or key, engages the groove **610**, or keyway, in a frictional arrangement. As can be appreciated, when the motor **104** is turned on, the motor rotation is transmitted through the drive **108** to the rotor **1202**. The protrusion **1204**, which is engaged with the groove **610**, rotates with the rotor **1202**. Correspondingly,

## 6

the driver hub **602** rotates. The pin **618** traversing the pin bore **616** rotates with the driver hub **602**. The pin **618** are engaged with the detents **702** of the cutting element **302**, which in turn cause the cutting element to rotate in the wand **102**. The wand handle **202** is threaded onto the threads **401** on the wand inlet tube **206**.

As can be appreciated, because the diameter of the cutting element **302** is approximately equal to the inner diameter of the wand inlet tube **206**, the cutting element **302** is provided hollow to allow for movement of the plant parts after trimming. Essentially, the vacuum **106** causes a suction that draws the plant part from the elongated slot **308**, past the cutting element **302** into a void **301** internal to the cutting element **302** and wand inlet tube **206**. The suction further causes the plant parts to travel down the void towards the outlet port **204** and through the flexible conduit **112** to the vacuum. While the diameter of the cutting element **302** is shown as approximately equal to the inner diameter of the wand inlet tube **206**, the diameter of the wand inlet tube **206** may be larger, which will be explained further below. The cutting surface **306** of the cutting element **302** generally passes in close proximity to the cutting edge **310** of slot **308** in the of the wand inlet tube **206**. If the designed in such a manner, generally the cutting element **302** and the wand inlet tube **206** are offset providing space between the cutting element **302** and an inner wall of the wand inlet tube **206** at a location opposite the slot **308**, which allows product to be moved laterally along the handle **202** outside of the cutting element **302**.

The plant parts travel the flexible conduit **112** to the inlet of the vacuum **106**. The vacuum **106** may contain a filtration system similar to a conventional wet/dry vacuum, for example. In such a case, the plant parts enter the drum **121** of the vacuum **106**. A filter (not specifically shown but generally known in the art) is coupled to the outlet of the vacuum **106** to prevent solids of a certain particle size from exiting the vacuum **106** such that the plant parts (all of them over the predefined particle size) are collected in a cavity of the drum **121**. As can be appreciated, however, each of the different parts of a plant may have a different use or value. Thus, it may be beneficial to provide an alternative filter bag collection system **1300** at either the inlet or outlet of the vacuum to separate the plant parts. While more or less filter/collectors are possible, FIG. 13 illustrates an exemplary filtration system comprising filter bags **1302**, **1304**, and **1306**. The filter bags **1302**, **1304**, and **1306** are described with respect to being attached to the outlet of the vacuum **106**. The filter bag collection system **1300** may be attached to a tube extending from the outlet port by a hook and loop cinch belt, string, cord, or the like as well as other fastening means. The first filter bag **1302** has a first filter mesh **1303**. The first filter mesh **1303** is the largest mesh opening. The second filter bag **1304** has a second filter mesh **1305** and is located between the first filter bag **1302** and the third filter bag **1306** in this exemplary embodiment. The second filter mesh **1305** may have medium mesh openings (as compared to the first filter bag **1302** and the third filter bag **1306**). The third filter bag **1306** has the smallest filter mesh **1307**. The particles not retained by the third filter bag **1306** may be exhausted or blocked by other upstream filters. From the outside in, because the filter bag collection system **1300** is coupled to the outlet, the third filter bag is contained in the second filter bag that is contained in the first filter bag. The first, second, and third filter bags may include support structure to inhibit the bags from collapsing due to the suction of the vacuum. Alternatively, the filter bag collection system **1300** may be coupled to the inlet of the vacuum **106**.



We reference now to FIGS. 14 and 15, an alternative outlet port 1400 is provided. As mentioned above, outlet port 204 provides a generally “T”-shaped junction or right angle connection to the wand inlet tube 206. The outlet port 1400 rather than a “T”-shape comprises an elongated shape with a wand inlet tube 206 receiving portion 1402, which would comprise a bore 1404 shaped to receive the wand inlet tube 206. The outlet port 1400 further comprises a funnel portion 1406 that tapers from the receiving portion 1402 to a discharge 1408. The funnel portion 1406 would converge to a generally circular opening 1410 to receive the flexible conduit 112 similar to the embodiments described above. As shown in FIG. 15, the receiving portion 1402 would have an elongated inlet 1412 to the funnel portion 1406. The funnel portion 1406 would guide the plant parts to the circular opening 1410 at the discharge into the flexible conduit 112.

As shown and described above, the outer diameter of the cutting element 302 is approximately equal to the inner diameter of the wand inlet tube 206. The size of the cutting element 302 is controlled to provide as close a fit between the cutting surface 306 and the cutting edge 310 to cut the plants without, or at least with limited, tearing. However, other than where the cutting surface 306 passes the cutting edge 310, the cutting element 302 and the inner surface of the wand inlet tube 206 do not necessarily need to be in close relation. With reference to FIG. 16, an alternative wand inlet tube 1600 is shown in cross section. The wand inlet tube 1600 contains a longitudinal axis 1602 at the geometric center of the wand inlet tube 1600 in this exemplary shape. The cutting element 302 is located proximal an inlet port 1604 of the wand inlet tube 1600 to provide the scissor like cutting of the plant parts. The cutting element 302 has a longitudinal axis 1606 at a rotational center that is offset a distance 1601 from the longitudinal axis 1602. Thus, the void 1608 of the wand inlet tube 1600 provides for a part 1610 internal to the blades of the cutting element 302 and a part 1612 external to the cutting element 302.

The wand inlet tube 1600 comprises a base 1620 proximal the wand handle 202 (FIG. 2). As shown, the base 1620 may include an outlet port 1622. The outlet port 1622 is offset from the longitudinal axis 1602 in a direction different than the offset for the rotational center. As can be appreciated, the outlet port 1622 is parallel with the longitudinal axis of the wand inlet tube 1600 rather than perpendicular, as shown and described above. While the helical blade described above may be used for the configuration of the device shown in FIG. 16, the cutting element 302 may be solid in certain aspects rather than hollow. In this exemplary embodiment, the cutting surface may be formed by milling a groove in an outer surface of the cutting element 302 to form the cutting surface 308.

Although the technology has been described in language that is specific to certain structures, materials, and methodological steps, it is to be understood that the invention defined in the appended claims is not necessarily limited to the specific structures, materials, and/or steps described. Rather, the specific aspects and steps are described as forms of implementing the claimed invention. Since many embodiments of the invention can be practiced without departing from the spirit and scope of the invention, the invention resides in the claims hereinafter appended. Unless otherwise indicated, all numbers or expressions, such as those expressing dimensions, physical characteristics, etc. used in the specification (other than the claims) are understood as modified in all instances by the term “approximately.” At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the claims, each numerical

parameter recited in the specification or claims which is modified by the term “approximately” should at least be construed in light of the number of recited significant digits and by applying ordinary rounding techniques. Moreover, all ranges disclosed herein are to be understood to encompass and provide support for claims that recite any and all subranges or any and all individual values subsumed therein. For example, a stated range of 1 to 10 should be considered to include and provide support for claims that recite any and all subranges or individual values that are between and/or inclusive of the minimum value of 1 and the maximum value of 10; that is, all subranges beginning with a minimum value of 1 or more and ending with a maximum value of 10 or less (e.g., 5.5 to 10, 2.34 to 3.56, and so forth) or any values from 1 to 10 (e.g., 3, 5.8, 9.9994, and so forth).

What is claimed is:

1. A plant trimming apparatus comprising:

a wand, the wand having a wand longitudinal axis comprising:

a wand inlet tube defining a void and having a proximal end and a distal end opposite the proximal end, the wand inlet tube comprising an elongate slot placing the void in fluid communication with an exterior of the wand inlet tube, the elongate slot being in a side of the tube and substantially aligned in the longitudinal direction and having a cutting edge,

an outlet port having a first bore parallel to the wand longitudinal axis and a second bore, the proximal end of the wand inlet tube receivable in the first bore, the second bore in fluid communication with the void, and

a cutting element rotatably contained in the void defined by the wand inlet tube, wherein the cutting element comprises at least one cutting surface that rotates in close relation to the cutting edge to slice at least a plant part,

a handle, the handle coupled to at least one of the proximal end of the wand inlet tube or the outlet port;

a motor operationally coupled to the cutting element such that the motor rotates the cutting element;

a drum in fluid communication with the second bore; and a vacuum coupled to the outlet port, wherein the vacuum causes flow between the wand inlet tube and the drum.

2. The apparatus of claim 1 wherein the vacuum is coupled to the outlet port by a flexible conduit.

3. The apparatus of claim 1 wherein the second bore of the outlet port is an outlet bore and the outlet bore has an axis perpendicular to the wand longitudinal axis.

4. The apparatus of claim 1 wherein the second bore of the outlet port is an outlet bore and the outlet bore has an axis parallel to the wand longitudinal axis.

5. The apparatus of claim 1 wherein the cutting element is hollow and comprises a plurality of curved cutting blades.

6. The apparatus of claim 5 wherein each of the curved cutting blades has a cutting surface.

7. The apparatus of claim 1 wherein the wand inlet tube has a first inner diameter and the cutting element has a first outer diameter wherein the first inner diameter and the first outer diameter are approximately equal.

8. The apparatus of claim 1 wherein the wand inlet tube has a first inner diameter and the cutting element has a first outer diameter wherein the first inner diameter is greater than the first outer diameter.

9. The apparatus of claim 8 wherein the wand inlet tube has an axis at a geometric center of the wand inlet tube that is parallel to the longitudinal axis of the wand and wherein the cutting element has a rotational axis parallel to the



9

longitudinal axis of the wand and offset a distance from the geometric center of the wand inlet tube.

10. The apparatus of claim 5 wherein the void defined by the wand inlet tube comprises a first part internal to the hollow cutting element and a second part external to the hollow cutting element.

11. The apparatus of claim 1 wherein the handle is part of the wand and opposite the wand inlet tube.

12. The apparatus of claim 2 wherein the handle is at least one of the second bore and the flexible conduit.

13. The apparatus of claim 1 wherein the outlet port comprises:

a receiving portion shaped to cooperatively receive the wand inlet tube, the receiving portion comprising an inlet in fluid communication with the void;

a discharge portion shaped to cooperatively receive a conduit placing the void in fluid communication with the drum; and

a funnel portion extending between the receiving portion and the discharge portion.

14. The apparatus of claim 13 wherein the inlet of the receiving portion comprises a second elongate slot.

15. The apparatus of claim 13 wherein the funnel portion tapers from the receiving portion to the discharge portion.

16. The apparatus of claim 13 wherein the discharge portion has a circular cross-sectional shape.

17. The apparatus of claim 1 wherein the motor is operationally coupled to the cutting element in part by a cable drive.

18. The apparatus of claim 1 further comprising a filtration bag collection system.

19. The apparatus of claim 18 wherein the filtration bag collection system comprises at least a first bag having a first

10

mesh size and a second bag having a second mesh size wherein the first mesh size and the second mesh size are different.

20. A method of trimming a plant product comprising: providing a wand comprising a wand inlet tube defining a void and a cutting element having a curved cutting surface rotatably mounted in the wand inlet tube, wherein the wand inlet tube has an opening in a side of the tube and substantially aligned in the longitudinal direction and having a cutting edge arranged such that the curved cutting surface rotates in close relation to the cutting edge;

placing the wand and a container in fluid communication; rotating the cutting element in the wand inlet tube;

touching the side of the tube of the wand having the opening to the plant products such that plant product enters the void through the slot and the curve cutting surface cuts the plant product from a plant as the cutting element rotates in close relation to the cutting edge; and moving the plant product from the void to the container.

21. The method of claim 20 wherein the step of moving comprises moving the wand in a radial direction against the plant product.

22. The method of claim 20 wherein rotating the cutting element comprises selecting a speed of rotation.

23. The method of claim 20 wherein moving the plant product from the void to the container comprises using a vacuum to pull the plant product from the void through a conduit to the container.

24. The method of claim 23 further comprising filtering the plant product as it enters the container.

\* \* \* \* \*