



US010253281B2

(12) **United States Patent**
Berman et al.

(10) **Patent No.:** **US 10,253,281 B2**
(45) **Date of Patent:** **Apr. 9, 2019**

(54) **METHOD OF WASHING TEXTILE ARTICLES**

(75) Inventors: **Russell Shawn Berman**, Lithia, FL (US); **Max Donald Harper**, Knoxville, TN (US); **Joel Monroe Madenwald**, Columbus, OH (US); **Carl Henry Mattson**, Florence, NJ (US)

(73) Assignee: **Ecolab USA Inc.**, St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 215 days.

(21) Appl. No.: **13/589,633**

(22) Filed: **Aug. 20, 2012**

(65) **Prior Publication Data**

US 2014/0047647 A1 Feb. 20, 2014

(51) **Int. Cl.**

C11D 3/395 (2006.01)
C11D 3/39 (2006.01)
C11D 11/00 (2006.01)

(52) **U.S. Cl.**

CPC **C11D 3/3951** (2013.01); **C11D 3/3945** (2013.01); **C11D 3/3953** (2013.01); **C11D 3/3955** (2013.01); **C11D 11/0064** (2013.01)

(58) **Field of Classification Search**

CPC ... C11D 3/3951; C11D 3/3945; C11D 3/3953; C11D 3/3955; C11D 11/0064
USPC 8/137; 510/276, 302, 309, 310, 367, 375, 510/379; 68/9, 11

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,618,914 A	10/1986	Sato et al.	
4,830,773 A	5/1989	Olson	
5,221,496 A	6/1993	Holland	
5,306,444 A	4/1994	Kitamura et al.	
5,369,126 A	11/1994	Doran et al.	
5,454,237 A	10/1995	Pellerin	
5,739,094 A	4/1998	Bowman et al.	
5,763,412 A *	6/1998	Khan et al.	514/23
5,858,941 A	1/1999	Oakes et al.	
5,919,745 A	7/1999	Cala et al.	
5,968,893 A	10/1999	Manohar et al.	
5,986,118 A	11/1999	Fehr et al.	
5,998,358 A	12/1999	Herdt et al.	
6,004,922 A	12/1999	Watson et al.	
6,015,784 A	1/2000	Kazuta et al.	
6,225,485 B1	5/2001	Bertz et al.	
6,274,541 B1	8/2001	Man	
6,290,732 B1	9/2001	Hei et al.	
6,350,725 B1	2/2002	Levitt et al.	
6,425,959 B1	7/2002	Man	
6,479,453 B2	11/2002	Man	
6,897,188 B2	5/2005	Gohl et al.	
6,903,060 B1	6/2005	Dykstra et al.	
7,037,884 B2	5/2006	Man	
7,416,326 B2	8/2008	Sakata et al.	
7,863,237 B2	1/2011	Rigley et al.	
7,971,302 B2	7/2011	Poy et al.	

7,998,278 B2	8/2011	Hackenberger et al.	
8,287,658 B2	10/2012	Miralles et al.	
8,361,950 B2	1/2013	Man et al.	
8,569,220 B2	10/2013	Gaudreault	
8,758,520 B2	6/2014	Monsrud et al.	
2002/0151452 A1	10/2002	Bullock et al.	
2002/0187910 A1 *	12/2002	Speed et al.	510/295
2003/0216273 A1	11/2003	Mitra et al.	
2004/0028794 A1	2/2004	Van Buuren et al.	
2004/0254090 A1	12/2004	Lentsch et al.	
2005/0153859 A1 *	7/2005	Gohl et al.	510/302
2006/0111261 A1	5/2006	Sadlowski et al.	
2006/0205628 A1	9/2006	Deinhammer et al.	
2006/0211593 A1	9/2006	Smith et al.	
2007/0033702 A1 *	2/2007	Hsu	2/129
2008/0015133 A1	1/2008	Rigley et al.	
2008/0276973 A1	11/2008	Miralles et al.	
2009/0011971 A1	1/2009	Evers	

(Continued)

FOREIGN PATENT DOCUMENTS

CA	1 226 782	9/1987
EP	0 825 250 A1	2/1998

(Continued)

OTHER PUBLICATIONS

Beggs "Tunnel Washer or Extractors: What's the Proper Choice? (Part 1)" Jul. 22, 2006.*

International Search Report and Written Opinion for PCT/US2013/055279 dated Nov. 11, 2013.

Gurtler Industries, Inc., "Technical Service Report" Hibiclens® Antiseptic Skin Preparation (2008), http://www.regentmedical.com/americas/hibiciens_laundry.html.

SÜD-CHEMIE AG, "Tonsil® Highly Active Bleaching Earths", 10 pages.

International Search Report and Written Opinion, dated May 26, 2016, (PCT/US2016/012928).

"Lesson Learned—Accidental Mixing of Bleach and Acid," <https://ehs.berkeley.edu/lessons-learned/lesson-learned-accidental-mixing-bleach-and-acid>, Berkeley EH&S Office of Environment, Health & Safety (2018).

(Continued)

Primary Examiner — Amina S Khan

(74) Attorney, Agent, or Firm — Merchant & Gould P.C.

(57) **ABSTRACT**

A method of washing textile articles can be carried out, for example, in a continuous batch tunnel washer. Embodiments of the present method can include treating the textile with an aqueous composition including cleaning agent and halogen-containing bleaching agent for a time sufficient to remove soil from the textile and contacting the halogen-treated textile with an aqueous composition including a peroxy-carboxylic acid. The concentration of halogen after the sufficient time can be at a level that does not result in adverse interaction between the halogen-containing bleaching agent and the peroxy-carboxylic acid. Embodiments of the present method can clean textiles with the results of more effective stain removal and less waste through destruction of the textile article. Further, the present invention can clean a textile contacted soiled by a composition including chlorhexidine gluconate without resulting staining of the textile, which staining could have been permanent.

12 Claims, No Drawings

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0119847	A1	5/2009	Arai et al.	
2009/0264329	A1	10/2009	Underwood et al.	
2010/0170303	A1	7/2010	Gohl et al.	
2010/0229897	A1	9/2010	Miralles et al.	
2011/0107527	A1	5/2011	De Buzzaccarini et al.	
2011/0251116	A1	10/2011	Aehle et al.	
2011/0296626	A1*	12/2011	Poy	8/137
2012/0023680	A1	2/2012	Poy et al.	
2012/0129751	A1	5/2012	Miracle et al.	
2013/0111675	A1	5/2013	Soontravanich et al.	
2013/0192006	A1*	8/2013	Tinker et al.	8/137
2014/0165294	A1	6/2014	Wilker et al.	
2014/0186922	A1	7/2014	Estell et al.	
2014/0349372	A1	11/2014	Erlandsen et al.	

FOREIGN PATENT DOCUMENTS

EP	1026226	9/2000
JP	04-185763	7/1992

JP	11-229271	8/1999
WO	95/04128	2/1995
WO	WO 99/50380	10/1999
WO	WO 2007/004622	A1 1/2007
WO	WO 2012/036700	9/2010
WO	WO 2011/056935	5/2011
WO	WO 2013/032493	3/2013

OTHER PUBLICATIONS

Hlemenstine, "Mixing Bleach and Vinegar, Why You Shouldn't Mix Bleach and Vinegar and Why People Do It Anyway," ThoughtCo., (2018).
 Ecolab Safety Data Sheet Advacare Disinfectant, (Jan. 29, 2018).
 "Hazmat situation forces evacuation of Phoenix business," <http://www.azfamily.com/story/28364613/hazmat-situation-forces-evacuation-of-phoenix-business>, (2000).

* cited by examiner

1

METHOD OF WASHING TEXTILE ARTICLES

FIELD OF THE INVENTION

The present invention relates to a method of washing textile articles that can be carried out, for example, in a continuous batch tunnel washer. Embodiments of the present method can include treating the textile with an aqueous composition including cleaning agent and halogen-containing bleaching agent for a time sufficient to remove soil from the textile and contacting the halogen-treated textile with an aqueous composition including a peroxy-carboxylic acid. The concentration of halogen after the sufficient time can be at a level that does not result in adverse interaction between the halogen-containing bleaching agent and the peroxy-carboxylic acid.

Embodiments of the present method can clean textiles with the results of more effective stain removal and less waste through destruction of the textile article. Further, the present invention can clean a textile contacted soiled by a composition including chlorhexidine gluconate without resulting staining of the textile, which staining could have been permanent.

BACKGROUND OF THE INVENTION

Commercial textile washing faces numerous challenges. For example, any batch of textile articles may include a variety of soils and stains, each of which will be washed with a single, unchanging set of detergents, bleaches, finishes and so on. In addition, the textile articles should be washed in a way that does not significantly decrease the useful life of the article. Harsh bleaching or washing conditions can shorten the useful life of a textile. And, it is cumbersome to inspect each article for cleanliness and residual stains. There remains a need to additional methods and compositions for commercial washing of textiles.

SUMMARY OF THE INVENTION

The present invention includes a method of cleaning textiles. This method can include treating the textile with an aqueous composition including cleaning agent and halogen-containing bleaching agent for a time sufficient to remove soil from the textile. After the sufficient time, the concentration of halogen can be below a level that would result in an unacceptable adverse interaction between the halogen-containing bleaching agent and the peroxy-carboxylic acid. In an embodiment, the concentration of halogen after the sufficient time is less than about 30 ppm. The method can also include contacting the halogen-treated textile with an aqueous composition including a peroxy-carboxylic acid.

The present invention includes a method of cleaning textile articles. This method can include providing a continuous tunnel washer having an interior, an intake, a discharge, and a plurality of sectors that divide the interior into a plurality of zones. This method includes moving the textile articles from the intake to a sector configured for treating the textile articles with an aqueous composition including cleaning agent and halogen-containing bleaching agent. This method includes treating the textile with an aqueous composition including cleaning agent and halogen-containing bleaching agent for a time sufficient to remove soil from the textile. After the sufficient time, the concentration of halogen can be below a level that would result in an unacceptable adverse interaction between the halogen-containing bleach-

2

ing agent and the peroxy-carboxylic acid. In an embodiment, the concentration of halogen after the sufficient time is less than about 30 ppm. This method includes transferring the textile articles to a sector configured for contacting the halogen-treated textile article with an aqueous composition including a peroxy-carboxylic acid. The method can also include contacting the halogen-treated textile with an aqueous composition including a peroxy-carboxylic acid.

In an embodiment, the present method washes textile articles and effectively removes stains from as many as or more than 99% of the washed articles. In an embodiment of the present method, only 1% of the articles washed are disposed of as rag (destroyed textile articles). In an embodiment, the present method can wash chlorhexidine gluconate from a textile article without resulting in a permanent or practically permanent stain on the article.

DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to a method for cleaning textiles that results in more effective stain removal and in less waste through destruction of the textile article. The present invention also allows washing with both a halogen containing bleaching agent and a peroxy-carboxylic acid oxidizer without unwanted adverse effects. Further, the present invention can clean a textile contacted soiled by a composition including chlorhexidine gluconate without resulting staining of the textile, which staining could have been permanent.

The present invention includes a method of cleaning a textile article. The method can include treating a textile with an aqueous composition including a cleaning agent and a halogen-containing (e.g., chlorine-containing) bleaching agent. The textile can be treated for a time effective for removing soil from the textile. According to the method, the concentration of halogen (e.g., chlorine) at the end of treating can be at a level that does not result in an unacceptable reaction with another oxidizer, such as a peroxy-carboxylic acid. For example, at the end of treating the concentration of halogen can be less than about 30 ppm. The method can also include contacting the halogen-treated textile with an aqueous composition including a peroxy-carboxylic acid.

The method of the present invention can be carried out in a continuous process. For example, the present method can be carried out in a continuous batch (tunnel) washer. The present treating can occur in one module or zone and the present contacting can occur in the next module or zone. In an embodiment of such a system, the textile article is not rinsed between treating and contacting. In an embodiment of such a system, the halogen-containing wash liquor is not (otherwise) removed from the textile article between treating and contacting. That is, the textile article can proceed directly from treating to contacting. Such a continuous process can include any of a variety of additional conventional modules or zones, for example, prewashing, rinsing, and/or finishing. In an embodiment, the present method is carried out without counterflow of the aqueous composition employed for contacting.

In an embodiment, the present invention includes a method of cleaning textiles. This embodiment includes: treating the textile with an aqueous composition including cleaning agent and halogen-containing bleaching agent for a time sufficient to remove soil from the textile; and contacting the halogen-treated textile with an aqueous composition including a peroxy-carboxylic acid. By the start of contact-

ing, or after the sufficient time, the concentration of halogen is less than about 30 ppm. During treating, e.g., at beginning of the sufficient time, the concentration of halogen can be about 50 to about 100 ppm. The halogen can be provided by any of a variety of bleaching agents, such as those described hereinbelow.

Treating can be conducted under any of a variety of conditions effective for removing soil from a textile article. For example, the temperature can be suitable for removing soil from a textile article in, for example, a continuous batch tunnel washer. In an embodiment, treating is conducted at a temperature effective to reduce the concentration of halogen to less than about 30 ppm during the sufficient time. Suitable temperatures for this embodiment include, about 140° F., about 145° F., about 140 to about 150° F., about 135 to about 155° F., or about 130 to about 160° F. In an embodiment, treating is conducted with an aqueous composition at a temperature of about 140° C. or about 150° F.

Treating can be carried out at any of a variety of pH levels suitable for soil removal. Before, treating the textile article can, optionally, have been washed with an alkaline cleaning composition. However, treating need not be conducted at an alkaline pH. For example, treating can be conducted at a neutral or slightly acid pH. In an embodiment, treating is conducted at a pH of about 9.5 to about 11.5, about 10 to about 11, about 10 (e.g., 10.2), about 11 (e.g., 10.8), or about 10.5 (e.g., 10.2, 10.8, 10.2-10.8).

According to the method, the concentration of halogen at the end of treating can be at a level that does not result in an unacceptable reaction with another oxidizer, such as a peroxycarboxylic acid. For example, at the end of treating the concentration of halogen can be less than about 50 ppm, less than about 40 ppm, less than about 30 ppm, less than about 20 ppm, or less than about 10 ppm. In an embodiment, the concentration of halogen is less than about 30 ppm, about 30 ppm, or less than 30 ppm.

Contacting can employ any of a variety of peroxycarboxylic acid compositions, including known peroxycarboxylic acid compositions. Peroxycarboxylic acids are described in greater detail hereinbelow. In an embodiment, the peroxycarboxylic acid includes peroxyacetic acid. However, any of a variety of short or medium chain peroxycarboxylic acids may be employed, for example, peroxypropionic acid, peroxybutanoic acid, peroxybutanoic acid, peroxyoctanoic acid, and the like. In an embodiment, the peroxycarboxylic acid composition includes peroxyacetic acid, hydrogen peroxide, and acetic acid. Such a composition can have an acidic pH. In an embodiment, the use composition includes about 75 to about 85 ppm; about 70 to about 90 ppm; or about 60 to about 100 ppm peroxyacetic acid. In an embodiment, the use composition includes about 75 ppm; about 80 ppm; or about 85 ppm peroxyacetic acid.

In certain embodiments, the present method can be more effective than conventional methods for removing stains from textile articles, e.g., textile articles from a health care facility. In an embodiment, the present method removes stains from about 99% of textile articles treated and contacted. One method for handling articles that remain stained after an initial cleaning is to rewash the article. In an embodiment of the present method, the rate of rewash is significantly reduced. In an embodiment, only about 1% of textile articles treated and contacted require rewashing. In an embodiment, textile articles treated and contacted according to the present invention require rewashing at less than about 50% the rate of textile articles cleaned in a conventional process.

Whether or not a textile article is stained can be determined by any of a variety of accepted methods. For example, staining can be detected by visual inspection. For example, in an embodiment, a textile article is considered to be free of stains when it is suitable to be used again in a health care or hospitality environment. In an embodiment, the textile article can be described as like new in appearance. In an embodiment, free of stains means that the article has no visible stains. In an embodiment, for use in a surgical environment, a textile can be free of visible stains when examined on a light table.

In certain embodiments, the present method can be more effective than conventional methods for removing soil from textile articles without reducing articles to rag-stock. In an embodiment of the present method, only about 1% of textile articles treated and contacted are disposed of as rag. In an embodiment, textile articles treated and contacted according to the present invention are disposed of as rag at less than about 50% the rate of textile articles cleaned in a conventional process. Whether or not a textile article should be disposed of as rag can be determined by any of a variety of accepted methods. For example, rags can be detected by visual inspection. For example, in an embodiment, a textile article is judged to have been reduced to a rag when there is a visual discoloration on the textile article that is from a source other than manufacturing.

Any of a variety of textile articles can benefit from being washed according to the present method. Suitable textile articles include those from hospitality, health care, industrial, and food service facilities. In an embodiment, the textile cleaned by the present is a white textile article or a colored synthetic (e.g., polyester) textile article. In an embodiment, the textile is a white cotton textile article. In an embodiment the textile articles are from a health care facility. That is, the textiles are textile articles employed in health care. Such health care textile articles include, for example, a sheet, a towel, a patient gown, a bed spread, an incontinence pad, an operating room linen, a scrub, a wash cloth, a pillow case, or a mixture thereof.

Textile articles from a health care facility can have been contacted with hand sanitizers or other products that include chlorhexidine gluconate. Some conventional methods for cleaning textile articles that have been contacted with a composition that includes chlorhexidine gluconate can result in permanent (or for all practical purposes permanent) staining of this article. Articles that are permanently stained due to prior contact with chlorhexidine gluconate are generally not used again and may be disposed of. Advantageously, embodiments of the present method are effective for cleaning textiles that have previously been contacted with chlorhexidine gluconate without causing permanent or practically permanent staining.

The present method can include any of a variety of additional procedures employed in washing a textile article. For example, in an embodiment, the present method can include washing with an alkaline detergent (e.g., an alkaline aqueous use composition including surfactants and the like) before treating. In an embodiment, such washing employs a composition including alkaline detergent, optional water conditioner, and/or optional booster.

In an embodiment, the present method can include finishing with a finishing composition after contacting. Such an embodiment can employ a finishing composition including sour, softener, and one or more additional finishing compositions, such as starch, fluid repellent, mildicide, residual care agent, or mixture thereof. In an embodiment, the present method can employ a finishing composition lacking

sour. Although not limiting to the present invention, it is believed that the acidity supplied by the peroxy-carboxylic acid can eliminate the need for additional sour in the finishing composition.

In an embodiment, the present method includes washing with alkaline detergent before treating; and finishing with a finishing composition after contacting.

The present invention can be carried out in any of a variety of washing machines, for example, those employed in commercial laundry facilities. In an embodiment, the present method is carried out in a conventional washer/extractor machine in which a batch of laundry is subjected to all steps in a single tub. In an embodiment, the present method is carried out employing a continuous batch tunnel washer. In an embodiment, when employing a continuous batch tunnel washer, the method can be conducted without counterflow of the composition including a peroxy-carboxylic acid.

Continuous Batch Tunnel Washer

In an embodiment, the present method is carried out employing a continuous batch tunnel washer. Continuous batch tunnel washers of a variety of configurations by a variety of manufacturers are known and can be employed in the present method. Suitable continuous batch tunnel washers include those described in U.S. Pat. Nos. 5,454,237 and 7,971,302 and in U.S. Patent Publications 20110296626 and 20120023680, the disclosures of which are incorporated herein by reference. Those washers that can employ counterflow need not employ that feature for embodiments of the present invention.

A suitable continuous batch washer can include multiple sectors, zones, stages, or modules including, for example, those for pre-wash, wash, rinse, and finishing. A method employing a continuous batch tunnel washer for washing textile articles can include, for example, moving the textile articles sequentially from one module or zone to the next module or zone including, for example, one or more pre-wash zones, one or more main wash zones, a pre-rinse zone, and then transferred to an extractor that performs the final rinse and that removes water. In an embodiment, such a method can include moving the textile articles from an intake of the washer to the discharge of the washer through one or more zones or sectors, which in certain embodiments can include first and second sectors that are a pre-wash zone.

Such a method can also employ a centrifugal extractor or mechanical press for removing most of the liquor from the goods before the goods are dried. In certain systems, if centrifugal extraction is used, it can be useful to rotate the extractor at a first low speed that is designed to remove soil laden water before a final extract.

In an embodiment, the present invention includes a method of cleaning textile articles including providing a continuous tunnel washer having an interior, an intake, a discharge, and a plurality of sectors that divide the interior into a plurality of zones. This method can include moving the textile articles from the intake to a sector configured for treating the textile articles with an aqueous composition including cleaning agent and halogen-containing bleaching agent. This method can also include treating the textile articles with an aqueous composition including cleaning agent and halogen-containing bleaching agent for a time sufficient to remove soil from the textile; the concentration of halogen being less than about 30 ppm after the sufficient time. The method can include transferring the textile articles to a sector configured for contacting the halogen-treated textile article with an aqueous composition including a peroxy-carboxylic acid. This method can also include con-

tacting the halogen-treated textile article with an aqueous composition including a peroxy-carboxylic acid.

This embodiment of the present method can be conducted without counterflow of the composition including a peroxy-carboxylic acid. This method can include employing a concentration of halogen after the sufficient time of less than 30 ppm. This method can also include washing with alkaline detergent before treating. And, the method can also include finishing with a finishing composition after contacting.

An embodiment employing a tunnel washer can achieve advantageous level of stain-free textile articles. For example, in an embodiment, employing a tunnel washer stains are removed from about 99% of textile articles treated and contacted. In an embodiment, only about 1% of textile articles treated and contacted are disposed of as rag. In an embodiment, employing a tunnel washer, the method is effective to remove chlorhexidine gluconate from a textile article without leaving a stain produced from the chlorhexidine gluconate.

Washer/Extractor

The present method can be carried out in any of a variety of commercial textile washing machines. The continuous batch tunnel washer process has been described above. A washer/extractor machine operates batchwise rather than continuously. Textiles are placed in the washer/extractor, water containing a first cleaning agent is added in an amount sufficient to wet the textiles, this water is drained, water containing a second cleaning agent is added in an amount sufficient to wet the textiles, and so on through the process to rinsing and extracting (e.g., spinning). In an embodiment, the present method employs a washer/extractor configured to pre-wash, wash, rinse, and finish textiles.

In an embodiment, the present invention includes a method of cleaning textile articles including providing a washer/extractor including a chamber for containing textiles. This method can also include treating the textile articles in the chamber with an aqueous composition including cleaning agent and halogen-containing bleaching agent for a time sufficient to remove soil from the textile; the concentration of halogen being less than about 30 ppm after the sufficient time. This method can include removing this composition from the chamber. The method can include contacting the halogen-treated textile article with an aqueous composition including a peroxy-carboxylic acid and removing this composition from the chamber. This method can also include washing with alkaline detergent before treating. And, the method can also include finishing with a finishing composition after contacting.

Bleaching Agent

Bleaching agents suitable for use in the present method for lightening or whitening a textile include bleaching compounds capable of liberating an active halogen species, such as Cl_2 , Br_2 , $-\text{OCl}^-$, and/or $-\text{OBr}^-$, under conditions typically employed in textile washing. Suitable bleaching agents for use in the present method include, for example, chlorine-containing compounds such as chlorines, hypochlorites, or chloramines. Suitable halogen-releasing compounds include, for example, an alkali metal dichloroisocyanurate, chlorinated trisodium phosphate, an alkali metal hypochlorite, monochloramine, and dichloramine. Encapsulated chlorine sources may also be used to enhance the stability of the chlorine source (see, for example, U.S. Pat. Nos. 4,618,914 and 4,830,773, the disclosures of which are incorporated by reference herein).

Suitable bleaching agents also include hydrogen peroxide, or other active oxygen species other than peracids.


Detergent

A detergent composition can include, for example, an effective amount of cleaning agent and an alkaline source to provide soil removal. The cleaning agent can include any component that provides soil removal properties when dispersed or dissolved in an aqueous solution and applied to a substrate for removal of soil from the substrate. The cleaning agent typically includes at least one surfactant, and a source of alkalinity. In certain embodiments, the cleaning agent preferably includes a surfactant or surfactant system, a source of alkalinity, a water conditioning agent, and an enzyme.

Peroxy-carboxylic Acid

Peroxy-carboxylic (or percarboxylic) acids generally have the formula $R(CO_3H)_n$, where, for example, R is an alkyl, arylalkyl, cycloalkyl, aromatic, or heterocyclic group, and n is one, two, or three, and named by prefixing the parent acid with peroxy. The R group can be saturated or unsaturated as well as substituted or unsubstituted. The methods of the invention can employ a peroxy-carboxylic acid, such as, for example, peroxyacetic acid.

Peroxy-carboxylic acids can be made by the direct action of an oxidizing agent on a carboxylic acid, by autoxidation of aldehydes, or from acid chlorides, and hydrides, or carboxylic anhydrides with hydrogen or sodium peroxide. In an embodiment, the percarboxylic acid can be made by the direct, acid catalyzed equilibrium action of hydrogen peroxide on the carboxylic acid. Scheme 1 illustrates an equilibrium between carboxylic acid and oxidizing agent (Ox) on one side and peroxy-carboxylic acid and reduced oxidizing agent (Ox_{red}) on the other:



Scheme 2 illustrates an embodiment of the equilibrium of scheme 1 in which the oxidizing agent is hydrogen peroxide on one side and peroxy-carboxylic acid and water on the other:



In conventional peroxy-carboxylic acid compositions it is believed that the equilibrium constant for the reaction illustrated in scheme 2 is about 2.5, which may reflect the equilibrium for acetic acid.

The alkyl backbones of peroxy-carboxylic acids can be straight chain, branched, or a mixture thereof. Peroxy forms of carboxylic acids with more than one carboxylate moiety can have one or more of the carboxyl moieties present as peroxy-carboxyl moieties.

Peroxyacetic (or peracetic) acid is a peroxy-carboxylic acid having the formula of CH_3COOOH .

The composition of the present invention can include a carboxylic acid. Generally, carboxylic acids have the formula $R-COOH$ wherein the R can represent any number of different groups including aliphatic groups, alicyclic groups, aromatic groups, heterocyclic groups, all of which can be saturated or unsaturated as well as substituted or unsubstituted. Carboxylic acids can have one, two, three, or more carboxyl groups.

In an embodiment, the compositions and methods include a peroxy-carboxylic acid and the corresponding carboxylic acid.

Definitions

As used herein, weight percent (wt-%), percent by weight, % by weight, and the like are synonyms that refer to the concentration of a substance as the weight of that substance

divided by the weight of the composition and multiplied by 100. Unless otherwise specified, the quantity of an ingredient refers to the quantity of active ingredient.

As used herein, the term “about” modifying the quantity of an ingredient in the compositions of the invention or employed in the methods of the invention refers to variation in the numerical quantity that can occur, for example, through typical measuring and liquid handling procedures used for making concentrates or use solutions in the real world; through inadvertent error in these procedures; through differences in the manufacture, source, or purity of the ingredients employed to make the compositions or carry out the methods; and the like. The term about also encompasses amounts that differ due to different equilibrium conditions for a composition resulting from a particular initial mixture. Whether or not modified by the term “about”, the claims include equivalents to the quantities.

The present invention may be better understood with reference to the following examples. These examples are intended to be representative of specific embodiments of the invention, and are not intended as limiting the scope of the invention.

EXAMPLES

Embodiments of the present method were subjected to extensive testing—16 weeks in four commercial tunnel washers. Textiles were washed in a wash liquor including 50 to 100 ppm chlorine followed by sanitizing with a composition including 70 to 90 ppm peroxyacetic acid in water. In certain tests, up to 120 ppm chlorine was used on articles with certain stains or soil exposure. The following results were obtained:

Textile Disposed of as Rag		
Site	CBW Wash Process With Conventional Chemistry (16 week rolling average)	Method of the Present Invention (Range)
1	0.010	0.004 to 0.010
2	0.014	0.005 to 0.016
3	0.015	0.005 to 0.035
4	0.07	0.07 to 0.14

Percentage of Items that Required Rewashing		
Site	CBW Wash Process With Conventional Chemistry (16 week rolling average)	Method of the Present Invention (Range)
1	2.8	0.7 to 1.5
2	2.4	1.0 to 2.3
3	2.4	0.9 to 2.0
4	8.1	3.0 to 7.0

The conventional chemistry employed in the CBW wash process was used conventional bleaching and washing chemistries, not the inventive halogen followed by peroxy-carboxylic acid.

The standard for determining whether a textile should be disposed of as rag was a presence of a visual discoloration on the textile article that is from a source other than manufacturing.

The standard for determining whether a textile should be rewashed was whether the stain could be removed by treating with more concentrated chemistry.

It should be noted that, as used in this specification and the appended claims, the singular forms “a,” “an,” and “the” include plural referents unless the content clearly dictates otherwise. Thus, for example, reference to a composition containing “a compound” includes a mixture of two or more compounds. It should also be noted that the term “or” is generally employed in its sense including “and/or” unless the content clearly dictates otherwise.

It should also be noted that, as used in this specification and the appended claims, the term “configured” describes a system, apparatus, or other structure that is constructed or configured to perform a particular task or adopt a particular configuration. The term “configured” can be used interchangeably with other similar phrases such as arranged and configured, constructed and arranged, adapted and configured, adapted, constructed, manufactured and arranged, and the like.

All publications and patent applications in this specification are indicative of the level of ordinary skill in the art to which this invention pertains.

The invention has been described with reference to various specific and preferred embodiments and techniques. However, it should be understood that many variations and modifications may be made while remaining within the spirit and scope of the invention.

We claim:

1. A method of cleaning textile articles, comprising:
 placing a plurality of textile articles into an intake of a continuous tunnel washer having a discharge, and an interior comprising a plurality of sectors that divide the interior into a plurality of zones, the plurality of sectors including: at least a first sector, and a second sector;
 moving the plurality of textile articles from the intake into the first sector;
 treating the plurality of textile articles in the first sector at a pH from about 9.5 to about 11.5 and a temperature of about 130° F. to about 160° F. with a first aqueous composition comprising cleaning agent and a halogen-containing bleaching agent having a concentration of not more than 100 ppm for a treatment time that is at least sufficient to remove soil from the plurality of textile articles and to reduce the concentration of halogen-containing bleaching agent to less than about 30 ppm, wherein the first aqueous composition is free from peroxycarboxylic acids;
 transferring the resulting halogen-treated plurality of textile articles from the first sector to the second sector

without rinsing the halogen-containing bleach agent from the plurality of textile articles; and
 treating the resulting halogen-treated plurality of textile articles in the second sector with a second aqueous composition comprising a peroxycarboxylic acid agent having a concentration from about 60 ppm to about 100 ppm at an acidic pH; and
 wherein the method removes the chlorhexidine gluconate without leaving a permanent stain in at least selected ones of the textiles where chlorhexidine gluconate is present.

2. The method of claim **1**, further comprising treating with alkaline detergent in the first sector before treating with first aqueous composition.

3. The method of claim **1**, further comprising treating with a finishing composition in the second sector after treating with the second aqueous composition.

4. The method of claim **1**, wherein chlorhexidine gluconate is removed from about 99% of the plurality of textile articles treated with the first aqueous composition and the second aqueous composition.

5. The method of claim **1**, wherein only about 1% of textile articles treated with the first aqueous composition and the second aqueous composition have permanent stains produced from chlorhexidine gluconate.

6. The method of claim **1**, wherein the plurality of sectors includes additional sectors in addition to the first sector and the second sector, and wherein the method comprises counter flow in the additional sectors.

7. The method of claim **3**, wherein the finishing composition does not include a sour.

8. The method of claim **1**, wherein the halogen-containing bleaching agent is selected from the group consisting of: chlorine, hypochlorite, chloramine, or a combination thereof.

9. The method of claim **1**, wherein the halogen-containing bleaching agent comprises alkali metal hypochlorite.

10. The method of claim **1**, wherein the peroxycarboxylic acid agent is selected from the group consisting of: peroxyacetic acid, hydrogen peroxide, acetic acid or a combination thereof.

11. The method of claim **1**, wherein the peroxycarboxylic acid agent is peroxyacetic acid.

12. The method of claim **1**, wherein the cleaning agent comprises at least one surfactant and a source of alkalinity.

* * * * *