

US010253905B2

(12) **United States Patent**
Martin

(10) **Patent No.:** **US 10,253,905 B2**
(45) **Date of Patent:** **Apr. 9, 2019**

(54) **WIRE MANAGEMENT CLIPS**

(71) Applicant: **Hubbell Incorporated**, Shelton, CT
(US)

(72) Inventor: **Evan Ronald Martin**, Merrimack, NH
(US)

(73) Assignee: **HUBBELL INCORPORATED**,
Shelton, CT (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/672,936**

(22) Filed: **Aug. 9, 2017**

(65) **Prior Publication Data**

US 2018/0045335 A1 Feb. 15, 2018

Related U.S. Application Data

(60) Provisional application No. 62/372,342, filed on Aug.
9, 2016.

(51) **Int. Cl.**

F16L 3/04 (2006.01)
F16L 3/12 (2006.01)
H01R 4/64 (2006.01)
H02G 3/32 (2006.01)
H02G 7/05 (2006.01)
F24S 80/00 (2018.01)
F16L 3/10 (2006.01)
H02G 3/00 (2006.01)

(52) **U.S. Cl.**

CPC **F16L 3/1218** (2013.01); **F16L 3/04**
(2013.01); **F24S 80/00** (2018.05); **H01R 4/646**
(2013.01); **H02G 3/32** (2013.01); **H02G 7/05**
(2013.01); **F16L 3/1058** (2013.01); **H02G**
3/263 (2013.01)

(58) **Field of Classification Search**

CPC ... F16L 31/1218; F16L 31/04; F16L 31/1058;
H01R 4/646

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

942,693 A 12/1909 Wintermute
1,332,004 A * 2/1920 Rawleigh B43K 23/001
24/336
1,398,519 A * 11/1921 Hosch A47G 25/12
24/457
2,061,463 A * 11/1936 Hall F16B 5/0685
24/625
2,618,033 A 11/1952 Tinnerman et al.
2,712,917 A * 7/1955 Flora F16B 5/0685
248/300

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2824260 2/2014

OTHER PUBLICATIONS

International Search Report and Written Opinion mailed in PCT/
US2017/046089 dated Oct. 27, 2017 (7 pages).



Primary Examiner — Anita M King

(74) *Attorney, Agent, or Firm* — Wissing Miller LLP

(57) **ABSTRACT**

A wire management clip includes a wire compartment, a first
clip compartment and a second clip compartment arranged
perpendicular to the first clip compartment. The wire man-
agement clip may also include a retaining member extending
into the first clip compartment for contacting a surface of a
structure. The wire management clip may also include a
retaining member extending into the second clip compart-
ment for contacting a surface of the structure.

23 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,003,736	A *	10/1961	Hofgesang	A47G 29/08 248/229.26	5,451,167	A	9/1995	Zielinski	
3,020,602	A	2/1962	Siering		5,463,189	A	10/1995	Deneke et al.	
3,049,042	A	8/1962	De Lynn		5,593,327	A *	1/1997	Hlinsky	H01R 4/363 439/793
3,131,447	A *	5/1964	Tinnerman	F16L 3/24 248/228.7	5,823,483	A *	10/1998	Gaskill	A47J 43/287 248/37.6
3,208,119	A	9/1965	Alexander		6,106,310	A	8/2000	Davis et al.	
3,216,685	A *	11/1965	Alain	F16B 2/245 248/316.7	6,186,799	B1	2/2001	Mello	
3,262,662	A *	7/1966	Gastaldi	H02G 3/26 248/68.1	6,234,835	B1	5/2001	Bakker et al.	
3,528,050	A	9/1970	Hindenburg		7,152,831	B2 *	12/2006	Riedy	F16L 3/221 248/68.1
3,626,553	A *	12/1971	Darney et al.	A63C 11/006 24/288	7,607,618	B2 *	10/2009	Mori	H02G 3/32 248/51
3,983,602	A *	10/1976	Barry	A42B 3/04 224/181	8,025,508	B2 *	9/2011	Parker	H01R 4/36 439/92
4,043,527	A	8/1977	Franzmeier		8,974,245	B2 *	3/2015	Kovalov	H01R 27/02 439/100
4,087,149	A	5/1978	Fischer		9,021,667	B2 *	5/2015	Wasco	F16B 2/20 24/336
4,406,505	A	9/1983	Avramovich		9,086,175	B2 *	7/2015	Feige	F16L 3/13
4,875,876	A	10/1989	O'Loughlin		D806,529	S *	1/2018	Olenick	D8/399
5,188,318	A *	2/1993	Newcomer	F16L 3/223 174/503	2012/0192925	A1 *	8/2012	Grushkowitz	F16L 3/24 136/251
5,347,691	A	9/1994	Terazoe		2014/0061396	A1 *	3/2014	Magno, Jr.	H02G 3/32 248/72

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12

1**WIRE MANAGEMENT CLIPS****CROSS REFERENCE TO RELATED APPLICATIONS**

The present application is based on and claims benefit from U.S. Provisional Application Ser. No. 62/372,342 filed Aug. 9, 2016 entitled "Wire Management Clips" the entire contents of which are incorporated herein by reference.

BACKGROUND**Field**

The present disclosure relates generally to clips, and more particularly to wire management clips.

Description of the Related Art

In recent years, the use of photovoltaic arrays to provide electrical power in commercial, residential, and other environments has become popular. Photovoltaic arrays are generally composed of a number of photovoltaic modules set within a metallic frame and a rail system that supports the photovoltaic modules. The rail system is attached to a support structure such as a roof or the ground. When installing a photovoltaic array, a number of photovoltaic modules are assembled onto the rail system. The metallic frames of the individual photovoltaic modules, and the structural pieces, e.g., the rails, on which the modules mounted are generally made out of aluminum. Depending upon the size of the photovoltaic array, the rail system may include multiple metallic rails coupled or connected together in a grid-like pattern. As with other sources of electrical power, to ensure the integrity of wires running along the metal frames of the photovoltaic modules, a clip is needed in which the wire can be mounted.

SUMMARY

The present disclosure provides embodiments of wire management clips. In one exemplary embodiment, a wire management clip comprises a base member, a first clip compartment and a second clip compartment. The base member includes a wire compartment configured to receive one or more wires. The first clip compartment extends from the base member and is capable of being clipped to a structure. The second clip compartment extends from the first clip compartment and capable of being clipped to the structure.

In another exemplary embodiment, a wire management clip comprises a base member, a wire compartment, a first clip compartment and a second clip compartment. The wire compartment extends from the base member and is configured to receive one or more wires. The first clip compartment extends from the base member. The second clip compartment extends from the first clip compartment.

In another exemplary embodiment, a wire management clip comprises a wire compartment, a first clip compartment and a second clip compartment. The first clip compartment extends from the wire compartment and the second clip compartment extends from the first clip compartment and is arranged perpendicular to the first clip compartment.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete appreciation of the present disclosure and many of the attendant advantages thereof will be readily

2

obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, wherein:

FIG. 1 is a perspective view of a wire management clip according to an illustrative embodiment of the present disclosure;

FIG. 2 is a perspective view of a wire management clip according to an illustrative embodiment of the present disclosure;

FIG. 3 is a side view of a wire management clip according to an illustrative embodiment of the present disclosure;

FIG. 4 is a partial cutaway perspective view of a wire management clip according to an illustrative embodiment of the present disclosure;

FIG. 5 is a partial cutaway perspective view of a wire management clip according to an illustrative embodiment of the present disclosure;

FIG. 6 is a view showing a wire management clip according to an illustrative embodiment of the present disclosure attached to a structure and holding a wire in place;

FIG. 7 is a view showing a management clip according to an illustrative embodiment of the present disclosure attached to a structure and holding a wire in place;

FIG. 8 is a perspective view of a wire management clip according to another illustrative embodiment of the present disclosure;

FIG. 9 is a perspective view of a wire management clip according to another illustrative embodiment of the present disclosure;

FIG. 10 is a side view of a wire management clip according to another illustrative embodiment of the present disclosure;

FIG. 11 is a partial cutaway perspective view of a wire management clip according to another illustrative embodiment of the present disclosure; and

FIG. 12 is a partial cutaway perspective view of a wire management clip according to another illustrative embodiment of the present disclosure.

DETAILED DESCRIPTION

Illustrative embodiments of the present disclosure may be provided as improvements to wire management clips. For example, a wire management clip may be provided with dual clip compartments allowing the clip to be arranged on a structure in various configurations.

Illustrative embodiments of the present disclosure allow a wire management clip to be arranged on a structure such that an open portion of a wire compartment can always be arranged on an "uphill" side of the structure.

Illustrative embodiments of the present disclosure include teeth that extend into at least one of the dual clip compartments for securing the clip to the structure.

In certain illustrative embodiments described herein, the wire management clip may be constructed from a suitably flexible material such as plastic, nylon, rubber, etc. Alternatively, the wire management clip may be made from a suitable metal or alloy having sufficient flexibility such as but not limited to spring steel, stainless steel, etc.

A wire management clip according to an embodiment of the present disclosure is shown in FIGS. 1-3 and is referred to generally as clip **100**. Clip **100** includes a wire compartment **102**. The wire compartment **102** is formed by a resilient arm **104** which is integral with and extends from base member **108**. The shape and dimensions of resilient arm **104** are such as to provide a space or wire compartment **102** to receive and hold one or more wires (not shown). A

distal end portion **110** of resilient arm **104** includes a lead-in **106**, which in this exemplary embodiment is a substantially V-shaped and outwardly flaring member permitting outward flexing of resilient arm **104**. However, the lead-in may be in a number of different shapes, such as a rounded edge, that facilitates easy insertion of one or more wires into the wire compartment **102**. The distance B, seen in FIG. 3, between the lowest point of resilient arm **104** and base member **108** is generally slightly smaller than a diameter of a wire to be held in wire compartment **102**, thereby preventing the wire from falling from the wire compartment **102**. When resilient arm **104** is urged outwardly in the direction shown by arrow A in FIG. 3, a sufficient space is formed at opening **112** for allowing one or more wires to be slid into or out of the wire compartment **102**. The edges **103** of resilient arm **104** and base member **108** are bent outwardly from wire compartment **102** to prevent any possibly sharp edges from coming into contact with wires mounted in wire compartment **102**.

According to an embodiment of the present disclosure, clip **100** includes first and second clip compartments which are provided at right angles to each other allowing clip **100** to be mounted to structures in various configurations. The first clip compartment **114** is integral with and extends from base member **108**. Clip compartment **114** is formed integral with base member **108** by members **140** and **142** which are bent in a substantially U-shaped configuration, seen in FIGS. 4 and 5. The clip compartment **114** includes a retaining member, such as tooth **144** having one or more pointed ends, that extends from base member **108** into clip compartment **114**. In the embodiment shown in FIG. 5, the tooth **144** is a “snake fang” like tooth with two pointed ends. When clip **100** is slid onto a structure using first clip compartment **114**, tooth **144** engages the surface of the structure and holds clip **100** in position. The second clip compartment **116** is integral with and extends from first clip compartment **114**. Clip compartment **116** is formed integral with member **142** by members **146** and **148** which are bent in a substantially U-shaped configuration. The clip compartment **116** includes a retaining member, such as tooth **150** having one or more pointed ends, that extends from member **142** into clip compartment **116**. In the embodiment shown in FIG. 4, the tooth **150** is a “snake fang” like tooth with two pointed ends. When clip **100** is slid onto a structure using second clip compartment **116**, tooth **150** engages the surface of the structure and holds clip **100** in position. According to an illustrative embodiment of the present disclosure, the teeth **144**, **150** are formed in situ from portions of members **108** and **142**, respectively.

As shown in FIG. 6, clip **100** can be slid onto a structure **200** using first clip compartment **114**. In this configuration, wire **202** can be held at a right angle to the edge **204** of structure **200**. When clip **100** is slid onto a structure **300** using second clip compartment **116** as shown in FIG. 7, wire **302** can be held parallel to the edge **304** of structure **300**. Utilizing the dual clip compartment feature of the present disclosure, the open side of the clip compartment can be arranged to always be on an “uphill” side of the structure further preventing any chance of the wire falling out of the clip **100**.

Another embodiment of a wire management clip is shown in FIGS. 8-12 and is referred to generally as clip **400**. Clip **400** is substantially similar to clip **100** described above but with the clip compartments arranged differently. Clip **400** includes a wire compartment **402**. The wire compartment **402** is formed by a resilient arm **404** which is integral with and extends from base member **408**. The shape and dimensions of resilient arm **404** are such as to provide a space or

wire compartment **402** to accommodate one or more wires (not shown). A distal end portion **410** of resilient arm **404** includes a lead-in **406**, which in this exemplary embodiment is a substantially V-shaped and outwardly flaring member permitting outward flexing of resilient arm **404**. However, the lead-in **406** may be in a number of different shapes, such as a rounded edge, that facilitates easy insertion of one or more wires into the wire compartment **402**. The distance B, seen in FIG. 10, between the lowest point of resilient arm **404** and base member **408** is generally slightly smaller than a diameter of a wire to be held in wire compartment **402**, thereby preventing the wire from falling from the wire compartment **402**. When resilient arm **404** is urged outwardly in the direction shown by arrow A in FIG. 10, a sufficient space is formed at opening **412** for allowing one or more wires to be slid into or out of the wire compartment **402**. The edges **403** of resilient arm **404** and base member **408** are bent outwardly from wire compartment **402** to prevent any possibly sharp edges from coming into contact with wires mounted in the wire compartment **402**.

According to this embodiment of the present disclosure, clip **400** includes first and second clip compartments which are provided at right angles to each other allowing clip **400** to be mounted to structures in various configurations. The first clip compartment **414** is integral with and extends from the distal end of base member **408**. As shown most clearly in FIGS. 11 and 12, clip compartment **414** is formed integral with base member **408** by members **440** and **442** which are bent in a substantially U-shaped configuration. The clip compartment **414** includes a retaining member, such as tooth **444** having one or more pointed ends, that extends from base member **408** into clip compartment **414**. In the embodiment shown in FIG. 12, the tooth **444** is a “snake fang” like tooth with two pointed ends. When clip **400** is slid onto a structure using first clip compartment **414**, tooth **444** engages the surface of the structure and holds clip **400** in position. The second clip compartment **416** is integral with and extends from first clip compartment **414**. Clip compartment **416** is formed integral with member **442** by members **446** and **448** which are bent in a substantially U-shaped configuration, seen in FIG. 11. The clip compartment **416** includes a retaining member, such as tooth **450** having one or more pointed ends, that extends from member **442** into clip compartment **416**. In the embodiment shown in FIG. 11, the tooth **450** is a “snake fang” like tooth with two pointed ends. When clip **400** is slid onto a structure using second clip compartment **416**, tooth **450** engages the surface of the structure and holds clip **400** in position. According to an illustrative embodiment of the present disclosure, the teeth **444**, **450** are formed in situ from portions of members **408** and **442**, respectively.

The wire management clips as described herein may be made of any material suitable for a desired application. For example, the wire management clips may be formed from any suitable type of flexible plastic, nylon, rubber, etc. Alternatively, the wire management clips may be made from a suitable metal or alloy having sufficient flexibility such as but not limited to spring steel, stainless steel, etc. When made from a suitable metal or alloy, the “snake fang” teeth may penetrate the surface of the structure to which the wire management clip is attached providing electrical continuity to the structure.

It will be appreciated that the description herein may refer to first, second, right, left, etc. for ease of description purposes only and does not in any way relate to the wire management clip in actual use. The term “wire” is used herein in the general manner and refers to any type and size

of conductor. The wire may be solid single stranded or may consist of two or more strands. The wire may be insulated or non-insulated.

While illustrative embodiments of the present disclosure have been described and illustrated above, it should be understood that these are exemplary of the disclosure and are not to be considered as limiting. Additions, deletions, substitutions, and other modifications can be made without departing from the spirit or scope of the present disclosure. Accordingly, the present disclosure is not to be considered as limited by the foregoing description.

What is claimed is:

1. A wire management clip comprising:
a base member including a wire compartment;
a first clip compartment integrally formed into the base member and including a first opening for clipping the first clip compartment to a structure; and
a second clip compartment integrally formed into the first clip compartment and including a second opening for clipping the second clip compartment to the structure, wherein the second opening is at an angle relative to the first opening.
2. The wire management clip as recited in claim 1, further comprising a retaining member extending into the first clip compartment for contacting a surface of the structure.
3. The wire management clip as recited in claim 2, wherein the retaining member extending into the first clip compartment comprises a tooth.
4. The wire management clip as recited in claim 1, further comprising a retaining member extending into the second clip compartment for contacting a surface of the structure.
5. The wire management clip as recited in claim 4, wherein the retaining member extending into the second clip compartment comprises a tooth.
6. The wire management clip as recited in claim 1, further comprising at least one retaining member extending into at least one of the first clip compartment and the second clip compartment for contacting a surface of the structure.
7. The wire management clip as recited in claim 1, wherein the wire compartment comprises a resilient arm which is integral with and extends from the base member.
8. The wire management clip as recited in claim 7, wherein a shape and dimension of the resilient arm are such as to accommodate at least one wire.
9. The wire management clip as recited in claim 8, wherein a distal end portion of the resilient arm includes a lead-in permitting outward flexing of the resilient arm.
10. A wire management clip comprising:
a wire compartment including a base member;
a first clip compartment including:
at least a portion of the base member;
a first member extending from the base member; and
a second member extending from the first member such that the second member is substantially parallel to the base member and a first opening is formed between the base member and the second member for clipping the first clip compartment to a structure; and
a second clip compartment including:
the second member;
a third member extending from the second member; and
a fourth member extending from the third member such that the fourth member is substantially parallel to the second member and a second opening is formed between the second member and the fourth member for clipping the second clip compartment to the

structure, wherein the second opening is at an angle relative to the first opening.

11. The wire management clip as recited in claim 10, wherein the first member extends from a side edge of the base member and the second member extends from an end of the first member, and wherein the third member extends from a side of the second member and the fourth member extends from an end of the third member.

12. The wire management clip as recited in claim 10, wherein the first member extends from an end of the base member and the second member extends an end of the first member, and wherein the third member extends from a side of the second member and the fourth member extends from an end of the third member.

13. A wire management clip comprising:
a wire compartment including a base member;
a first clip compartment including:
at least a portion of the base member;
a first member extending from a side of the base member; and
a second member extending from an end of the first member such that the second member is substantially parallel to the base member and a first opening is formed between the base member and the second member for clipping the first clip compartment to a structure; and
a second clip compartment including:
the second member;
a third member extending from a side of the second member; and
a fourth member extending from an end of the third member such that the fourth member is substantially parallel to the second member and a second opening is formed between the second member and the fourth member for clipping the second clip compartment to the structure, wherein the second opening is substantially orthogonal to the first opening.

14. The wire management clip as recited in claim 13, further comprising a retaining member extending into the first clip compartment for contacting a surface of a structure.

15. The wire management clip as recited in claim 14, wherein the retaining member extending into the first clip compartment comprises a tooth.

16. The wire management clip as recited in claim 13, further comprising a retaining member extending into the second clip compartment for contacting a surface of the structure.

17. The wire management clip as recited in claim 16, wherein the retaining member extending into the second clip compartment comprises a tooth.

18. The wire management clip as recited in claim 13, further comprising at least one retaining member extending into at least one of the first clip compartment and the second clip compartment for contacting a surface of a structure.

19. The wire management clip as recited in claim 13, wherein the wire compartment comprises a resilient arm which is integral with and extends from a base member.

20. The wire management clip as recited in claim 19, wherein a shape and dimension of the resilient arm are such as to accommodate at least one wire.

21. The wire management clip as recited in claim 19, wherein a distal end portion of the resilient arm includes a lead-in permitting outward flexing of the resilient arm.

22. The wire management clip as recited in claim 1, wherein the angle is substantially 90 degrees.

23. The wire management clip as recited in claim 10,
wherein the angle is substantially 90 degrees.

* * * * *