



US010257345B2

(12) **United States Patent**
Pandurangarao

(10) **Patent No.:** **US 10,257,345 B2**
(45) **Date of Patent:** **Apr. 9, 2019**

(54) **MOBILE DEVICE COMMUNICATION ACCESS AND HANDS-FREE DEVICE ACTIVATION**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Allstate Solutions Private Limited,**
Bangalore (IN)

5,467,388 A 11/1995 Redd, Jr. et al.
5,499,182 A 3/1996 Ousborne
(Continued)

(72) Inventor: **Anil Kumar Pandurangarao,**
Karnataka (IN)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Allstate Solutions Private Limited,**
Bangalore (IN)

EP 0700009 A2 3/1996
JP 2015169472 A 9/2015
WO 2011004372 A1 1/2011

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

(21) Appl. No.: **15/959,527**

Shabeer, et. al, "Mobile Communication Safety on Road Transport," WSEAS Transactions on Communications, E-ISSN: 2224-2864, Issue 3, vol. 12, Mar. 2013, 12 pages.
(Continued)

(22) Filed: **Apr. 23, 2018**

Primary Examiner — Kwasi Karikari

(65) **Prior Publication Data**

(74) *Attorney, Agent, or Firm* — Banner & Witcoff, Ltd.

US 2018/0241873 A1 Aug. 23, 2018

(57) **ABSTRACT**

Related U.S. Application Data

(62) Division of application No. 15/284,801, filed on Oct. 4, 2016, now Pat. No. 9,979,813.


Apparatuses, systems, and methods are provided for analyzing an incoming telephonic event (e.g., call, message, and/or notification) to a mobile device during operation of a vehicle in relation to a combination of factors to determine if the incoming telephonic event is to be allowed to be received during vehicle operation. The mobile device associated with a driver of the vehicle may receive the incoming telephonic event during operation of the vehicle. An incoming telephonic event analysis application operating on the mobile device may apply a soft block preventing the incoming telephonic event from being displayed on the mobile device. Based on the incoming telephonic event data, vehicle operational data, user preferences, hands-free device activation, and driver and road ratings, the incoming telephonic event analysis application may determine whether or not to maintain the soft block or allow the incoming telephonic event to be displayed on the mobile device during operation of the vehicle.

(51) **Int. Cl.**
H04W 76/14 (2018.01)
H04M 1/725 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC *H04M 1/72577* (2013.01); *B60R 16/023* (2013.01); *B60W 40/08* (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04W 4/046; H04W 4/027; H04W 88/02; H04W 4/80; H04W 84/18; H04W 4/16;
(Continued)

20 Claims, 10 Drawing Sheets



(51)	Int. Cl.		2006/0247852 A1	11/2006	Kortge et al.
	B60R 16/023	(2006.01)	2007/0027726 A1	2/2007	Warren et al.
	B60W 40/08	(2012.01)	2007/0136107 A1	6/2007	Maguire et al.
	H04M 1/60	(2006.01)	2007/0226014 A1	9/2007	Alemayehu et al.
	H04W 4/02	(2018.01)	2007/0268158 A1	11/2007	Gunderson et al.
	H04W 68/00	(2009.01)	2008/0016145 A1	1/2008	Takase et al.
			2008/0065427 A1	3/2008	Helitzer et al.
(52)	U.S. Cl.		2008/0120175 A1	5/2008	Doering
	CPC	H04M 1/6075 (2013.01); H04M 1/6091	2008/0243321 A1	10/2008	Walser et al.
		(2013.01); H04M 1/7253 (2013.01); H04M	2008/0243558 A1	10/2008	Gupte
		1/72569 (2013.01); H04M 1/72597 (2013.01);	2008/0255722 A1	10/2008	McClellan et al.
		H04W 4/027 (2013.01); H04W 68/005	2008/0255888 A1	10/2008	Berkobin et al.
		(2013.01); H04W 76/14 (2018.02)	2008/0262670 A1	10/2008	McClellan et al.
			2008/0270519 A1	10/2008	Ekdahl et al.
(58)	Field of Classification Search		2008/0319602 A1	12/2008	McClellan et al.
	CPC	Y02D 70/144; Y02D 70/26; Y02D 70/22;	2009/0024273 A1	1/2009	Follmer et al.
		H04M 2250/02; H04M 1/05; H04M	2009/0024419 A1	1/2009	McClellan et al.
		1/7253; H04M 2207/18; H04M 1/6075;	2009/0079555 A1	3/2009	Aguirre De Carcer et al.
		H04M 1/0258	2009/0132294 A1	5/2009	Haines
	See application file for complete search history.		2010/0030582 A1	2/2010	Rippel et al.
			2010/0030592 A1	2/2010	Evans et al.
			2010/0042314 A1	2/2010	Vogt et al.
			2010/0063850 A1	3/2010	Daniel
(56)	References Cited		2010/0131303 A1	5/2010	Collopy et al.
	U.S. PATENT DOCUMENTS		2010/0131304 A1	5/2010	Collopy et al.
	5,619,568 A	4/1997 Miller	2010/0157061 A1	6/2010	Katsman et al.
	6,175,803 B1	1/2001 Chowanic et al.	2010/0174566 A1	7/2010	Helitzer et al.
	6,233,445 B1	5/2001 Boltz et al.	2010/0205012 A1	8/2010	McClellan
	6,351,698 B1	2/2002 Kubota et al.	2010/0211259 A1	8/2010	McClellan
	6,629,029 B1	9/2003 Giles	2010/0238009 A1	9/2010	Cook et al.
	7,167,787 B2	1/2007 Bastian et al.	2010/0250021 A1	9/2010	Cook et al.
	7,292,152 B2	11/2007 Torrkola et al.	2010/0323673 A1	12/2010	Etram et al.
	7,535,344 B2	5/2009 Obradovich	2011/0009107 A1	1/2011	Guba et al.
	7,565,230 B2	7/2009 Gardner et al.	2011/0039581 A1	2/2011	Cai et al.
	7,659,827 B2	2/2010 Gunderson et al.	2011/0054716 A1	3/2011	Stahlin et al.
	7,742,792 B2	6/2010 Matsui	2011/0090221 A1	4/2011	Ren
	8,090,598 B2	1/2012 Bauer et al.	2011/0092159 A1	4/2011	Park et al.
	8,270,933 B2	9/2012 Riemer et al.	2011/0106370 A1	5/2011	Duddle et al.
	8,275,348 B2	9/2012 Yen et al.	2011/0144909 A1	6/2011	Ren et al.
	8,311,858 B2	11/2012 Everett et al.	2011/0161116 A1	6/2011	Peak et al.
	8,314,708 B2	11/2012 Gunderson et al.	2011/0196571 A1	8/2011	Foladare et al.
	8,332,242 B1	12/2012 Medina, III	2011/0205043 A1	8/2011	Fujiki et al.
	8,355,818 B2	1/2013 Nielsen et al.	2011/0213628 A1	9/2011	Peak et al.
	8,489,433 B2	7/2013 Altieri et al.	2011/0219080 A1	9/2011	McWithey et al.
	8,508,353 B2	8/2013 Cook et al.	2011/0269441 A1	11/2011	Silver
	8,538,687 B2	9/2013 Plocher et al.	2011/0320492 A1	12/2011	Inghelbrecht
	8,606,512 B1	12/2013 Bogovich et al.	2012/0004933 A1	1/2012	Foladare et al.
	8,612,139 B2	12/2013 Wang et al.	2012/0010906 A1	1/2012	Foladare et al.
	8,620,575 B2	12/2013 Vogt et al.	2012/0021386 A1	1/2012	Anderson et al.
	8,626,444 B2	1/2014 Li et al.	2012/0072243 A1	3/2012	Collins et al.
	8,655,965 B2	2/2014 McWithey et al.	2012/0072244 A1	3/2012	Collins et al.
	8,682,699 B2	3/2014 Collins et al.	2012/0083287 A1	4/2012	Casto et al.
	8,686,872 B2	4/2014 Szczerba et al.	2012/0101855 A1	4/2012	Collins et al.
	8,712,429 B2	4/2014 Nagorniak	2012/0109692 A1	5/2012	Collins et al.
	8,731,768 B2	5/2014 Fernandes et al.	2012/0123806 A1	5/2012	Schumann, Jr. et al.
	8,744,492 B2	6/2014 Kuo	2012/0197669 A1	8/2012	Kote et al.
	8,805,707 B2	8/2014 Schumann, Jr. et al.	2012/0209632 A1	8/2012	Kaminski et al.
	8,810,425 B2	8/2014 Hyde et al.	2012/0226421 A1	9/2012	Kote et al.
	8,824,997 B2	9/2014 Gehlen et al.	2012/0253586 A1	10/2012	Sakakibara
	8,860,564 B2	10/2014 Rubin et al.	2012/0289214 A1	11/2012	Hynes et al.
	8,930,229 B2	1/2015 Bowne et al.	2012/0311416 A1	12/2012	Richter et al.
	8,971,927 B2	3/2015 Zhou et al.	2013/0006674 A1	1/2013	Bowne et al.
	9,020,749 B2	4/2015 Aso et al.	2013/0006675 A1	1/2013	Bowne et al.
	9,020,751 B1	4/2015 Bogovich et al.	2013/0006715 A1	1/2013	Warkentin et al.
	9,066,210 B2	6/2015 Kalita et al.	2013/0024060 A1	1/2013	Sukkarie et al.
	9,082,072 B1	7/2015 Wedding, Jr. et al.	2013/0046559 A1	2/2013	Coleman et al.
	9,142,142 B2	9/2015 Nath et al.	2013/0078963 A1	3/2013	Prasad et al.
	9,150,154 B2	10/2015 Miller et al.	2013/0090803 A1	4/2013	Stahlin et al.
	9,207,675 B1	12/2015 Walser et al.	2013/0110310 A1	5/2013	Young
	9,519,670 B2	12/2016 Stanek et al.	2013/0124082 A1	5/2013	Cho
	9,574,888 B1	2/2017 Hu et al.	2013/0137404 A1*	5/2013	Kuo H04W 4/046 455/413
	2002/0059084 A1	5/2002 Wahlbin et al.	2013/0151288 A1	6/2013	Bowne et al.
	2004/0210353 A1	10/2004 Rice	2013/0157640 A1	6/2013	Aycock
	2004/0214615 A1	10/2004 Entenmann et al.	2013/0238233 A1	9/2013	Kim et al.
	2005/0086227 A1	4/2005 Sullivan et al.	2013/0317736 A1	11/2013	Fernandes et al.
	2006/0053038 A1	3/2006 Warren et al.	2014/0019170 A1	1/2014	Coleman et al.
	2006/0200008 A1	9/2006 Moore-Ede	2014/0067434 A1	3/2014	Bourne et al.
			2014/0074402 A1	3/2014	Hassib et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0080100	A1	3/2014	Phelan et al.	
2014/0180723	A1	6/2014	Cote et al.	
2014/0207497	A1	7/2014	Collins et al.	
2014/0222280	A1	8/2014	Salomonsson et al.	
2014/0257869	A1	9/2014	Binion et al.	
2014/0267263	A1	9/2014	Beckwith et al.	
2014/0267627	A1	9/2014	Freeman et al.	
2014/0268353	A1	9/2014	Fujimura et al.	
2014/0277939	A1	9/2014	Ren et al.	
2014/0336866	A1	11/2014	Kloedon et al.	
2014/0350970	A1	11/2014	Schumann, Jr. et al.	
2014/0358840	A1	12/2014	Tadic et al.	
2015/0056973	A1*	2/2015	Efrati	H04W 76/064 455/418
2015/0112545	A1	4/2015	Binion et al.	
2015/0112730	A1	4/2015	Binion et al.	
2015/0112800	A1	4/2015	Binion et al.	
2015/0172450	A1	6/2015	Singhal	
2015/0187016	A1	7/2015	Adams et al.	
2016/0047666	A1	2/2016	Fuchs	
2016/0050315	A1	2/2016	Malhotra et al.	
2016/0073240	A1	3/2016	Helm	
2016/0134744	A1	5/2016	de la Fuente Sanchez	
2016/0231278	A1	8/2016	Goroshevskiy et al.	
2017/0122989	A1	5/2017	Ho	
2018/0158334	A1	6/2018	Perez Barrera et al.	
2018/0162410	A1	6/2018	Skillsater et al.	

OTHER PUBLICATIONS

“Drive Control—For When you Need a Little More Self Control,” retrieved Apr. 8, 2016 from <https://drivecontrolapp.com>, 2 pages. Mar. 3, 2017—U.S. Non-Final Office Action—U.S. Appl. No. 15/284,801.

“Telematics: Reinventing Auto Insurance,” retrieved Sep. 6, 2011 from http://www.insurancetech.com/blog/archives/2010/03/telematics_the.html, 10 pages.

Martin Demers, “Waste Fleet Safety: Influencing Driver Behavior” 2010 Waste Management Magazine, pp. 1-3.

Insurance Companies Utilizing Technology Fairbault Daily News, May 10, 2011, <http://www.fairbault.com/print/11435> pp. 1-3.

Jul. 13, 2015 U.S. Non-Final Office Action—U.S. Appl. No. 14/066,988.

Sep. 30, 2015 U.S. Non-Final Office Action—U.S. Appl. No. 14/227,740.

Jul. 20, 2015—U.S. Non-Final Office Action—U.S. Appl. No. 13/564,524.

Sep. 1, 2016—U.S. Final Office Action—U.S. Appl. No. 13/564,524.

Jun. 10, 2016 U.S. Non-Final Office Action—U.S. Appl. No. 14/066,988.

Nov. 22, 2016—U.S. Final Office Action—U.S. Appl. No. 14/066,988.

Mar. 28, 2016—U.S. Non-Final Office Action—U.S. Appl. No. 13/564,524.

Nov. 23, 2015—U.S. Final Office Action—U.S. Appl. No. 13/564,524.

Feb. 4, 2014—U.S. Final Office Action—U.S. Appl. No. 13/564,524.

Oct. 8, 2013—U.S. Non-Final Office Action—U.S. Appl. No. 13/564,524.

Mar. 23, 2016—U.S. Final Office Action—U.S. Appl. No. 14/227,740.

Jan. 31, 2017—U.S. Non-Final Office Action—U.S. Appl. No. 14/227,740.

Nov. 23, 2015—U.S. Final Office Action—U.S. Appl. No. 14/066,988.

“Continental Head-up Display Augmented Reality HUD” <http://continental-head-up-display.com/> website last visited on Apr. 30, 2015.

“In the Future, Your Car’s Windscreen Will Be an Augmented Reality Display” <https://transportevolved.com/2014/09/29/future-cars-windscreen-will-augmented-reality-display/> website last visited on Apr. 30, 2015.

“Autonomous Cars from Berlin” website: <http://autonomos-labs.com/research/> website last visited on Apr. 30, 2015.

Williams, Geoff—Should You Try Pay-As-You-Drive Insurance?, Jan. 13, 2014, <http://money.usnews.com/money/personal-finance/articles/2014/01/13/should-you-try-pay-as-you-drive-insurance>, U.S. News & World Report.

Rafter, Michelle—Use-Based Insurance Shifts Into High Gear, <http://www.edmunds.com/auto-insurance/pay-as-you-drive-insurance-goes-into-high-gear.html>, Feb. 27, 2014, Edmunds.

Chalon Smith, Mark—Pay-As-You-Drive Discounts: A Guide, <http://www.insurance.com/auto-insurance/saving-money/low-mileage-discounts-guide.html>, Apr. 22, 2015, Insurance.com.

How’s My Driving?—<http://www.economist.com/news/finance-and-economics/21572237-gizmos-track-driving-habits-are-changing-face-car-insurance-hows-my>—Feb. 23, 2013—Print Edition of The Economist.

Usage-Based Insurance and Telematics, http://www.naic.org/cipr_topics/topic_usage_based_insurance.htm, Last Updated Dec. 14, 2015—National Association of Insurance Commissioners & The Center for Insurance Policy and Research.

Dewri, Rinku et al—Inferring Trip Destinations From Driving Habits Data, <http://www.cs.du.edu/~rdewri/data/MyPapers/Conferences/2013WPES-Extended.pdf>, Last Visited Feb. 25, 2016.

Rosolino, V. et al: “Road Safety Performance Assessment: A New Road Network Risk Index for Info Mobility”, ScienceDirect: Procedia—Social and Behavioral Sciences 111 (2014) pp. 624-633.

Li, Z et. al.: “Road Risk Modeling and Cloud-Aided Safety-Based Route Planning”, Published in Cybernetics, IEEE Translations dated Oct. 2, 2015, pp. 1-2.

“Road Asset Management”, <https://www.arrb.com.au/Infrastructure/Road-asset-management.aspx>, Last visited Oct. 8, 2015, pp. 1-5.

Dec. 5, 2016 (WO)—International Search Report and Written Opinion—App. PCT/US2016/052877.

Feb. 2, 2017—(WO) International Search Report—App PCT/US2016/063527.

Jun. 6, 2017—U.S. Non-Final Office Action—U.S. Appl. No. 13/564,524.

Jun. 7, 2017—U.S. Final Office Action—U.S. Appl. No. 14/227,740.

May 19, 2017 (WO) International Search Report and Written Opinion—App. PCT/IN2016/050370.

May 24, 2017—(WO) International Search Report and Written Opinion—PCT/IN16/50369.

Jun. 23, 2017—U.S. Non-Final Office Action—U.S. Appl. No. 15/284,728.

“Axeda and Walsh Vision Announce Alliance for Cloud Telematics Solutions” retrieved Sep. 6, 2011 from <http://www.cbs19.tv/story/15234817/axeda-and-walsh-vision-announce-alliance-for-cloud-telematics-solutions> pp. 1-4.

Aug. 9, 2017—U.S. Final Office Action—U.S. Appl. No. 15/284,801.

Sep. 12, 2017—U.S. Final Office Action—U.S. Appl. No. 13/564,524.

Sep. 13, 2017—U.S. Non-Final Office Action—U.S. Appl. No. 14/066,988.

Nov. 16, 2017—U.S. Non-Final Office Action—U.S. Appl. No. 14/863,476.

Nov. 22, 2017—U.S. Notice of Allowance—U.S. Appl. No. 15/284,728.

Jan. 24, 2018—U.S. Notice of Allowance—U.S. Appl. No. 15/284,801.

Feb. 26, 2018—U.S. Non-Final Office Action—U.S. Appl. No. 14/227,740.

Mar. 1, 2018—U.S. Non-Final Office Action—U.S. Appl. No. 15/284,728.

Mar. 20, 2018—U.S. Non-Final Office Action—U.S. Appl. No. 15/052,291.

Aug. 3, 2018—U.S. Final Office Action—U.S. Appl. No. 14/863,476.

Sep. 4, 2018—U.S. Notice of Allowance—U.S. Appl. No. 15/284,728.

Oct. 17, 2018—U.S. Final Office Action—U.S. Appl. No. 15/052,291.

Nov. 2, 2018—U.S. Non-Final Office Action—U.S. Appl. No. 15/160,208.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8

1

**MOBILE DEVICE COMMUNICATION
ACCESS AND HANDS-FREE DEVICE
ACTIVATION**

CROSS REFERENCE TO RELATED
APPLICATIONS

This application is a divisional of and claims priority to co-pending U.S. patent application Ser. No. 15/284,801, filed Oct. 4, 2016, and entitled "Mobile Device Communication Access And Hands-Free Device Activation," which is related to U.S. patent application Ser. No. 13/564,524 entitled, "Calculation and Utilization of a Driving Score," and U.S. patent application Ser. No. 15/052,291 entitled, "Risk Maps," each of which is incorporated herein by reference in their entirety.

TECHNICAL FIELD

Aspects described herein generally relate to one or more computer systems, servers, and/or other devices including hardware and/or software. More specifically, aspects relate to analyzing an incoming telephonic event (e.g., call, message, and/or notification) to a mobile device in relation to a combination of vehicle operational data, user preferences, and hands-free device activation to determine if the incoming telephonic event is to be permitted to be received (e.g., by a user) during vehicle operation.

BACKGROUND

Distracted driving can lead to motor vehicle accidents, which may result in injury and, in some cases death. One contributing factor to distracted driving is mobile device interaction, particularly through telephone calls, text messages, and social media applications. While mobile applications and hands-free devices currently exist which purport preventing and/or minimizing direct mobile device interaction during driving, such mobile applications and hands-free devices are limited by technological shortcomings which hinder their effectiveness in reducing distracted driving in a safe manner.

For example, in regard to mobile applications, such applications are, in some instances, comprehensively restrictive and prevent all incoming calls, messages, and notifications from being provided to a mobile device of a driver until after driving has stopped. Accordingly, emergency calls, messages, and notifications may be prohibited from reaching the driver in a timely fashion in fitting with an emergency situation. Moreover, in other instances in which the mobile applications restrict the presentation of incoming calls, messages, and notifications based on a velocity of the vehicle as determined through a GPS and/or accelerometer of the mobile device, the determined velocity readings can be subverted through restricting GPS privileges of the mobile application and/or travelling at a constant speed through vehicle cruise control utilization.

With respect to hands-free devices, in some instances, such devices are configured to audibly and/or visually generate all incoming calls, messages, and notifications for the user. However, it has been shown that the audibilization and/or visualization of content do not significantly reduce distracted driving as compared to conventional mobile device usage. Additionally, in other instances in which only certain incoming calls, messages, and notifications are audibly and/or visually generated for the user, the determination is made based on pre-stored user selections that do not take

2

into consideration criteria such as traffic levels, environmental conditions, time of day, type of road, and emergency calls, messages, and notifications.

As such, in order to address the technological shortcomings mentioned above, there may exist a need for applications, apparatuses, and systems which analyze an incoming telephonic event to a mobile device in relation to a combination of vehicle telematics data, user preferences, and hands-free device activation to determine if the incoming telephonic event is to be presented at the mobile device during vehicle operation.

BRIEF SUMMARY

The following presents a simplified summary of various aspects described herein. This summary is not an extensive overview, and is not intended to identify key or critical elements or to delineate the scope of the claims. The following summary merely presents some concepts in a simplified form as an introductory prelude to the more detailed description provided below.

To overcome limitations in the prior art described above, and to overcome other limitations that will be apparent upon reading and understanding the present specification, aspects described herein are directed to methods, apparatuses, and systems configured to analyze an incoming telephonic event in relation to a combination of vehicle operational data, user preferences, and hands-free device activation to determine if the incoming telephonic event is to be presented during vehicle operation.

Some aspects described herein provide for an auto-reply system for a mobile device associated with a driver of a vehicle. The mobile device may be configured to receive an incoming telephonic event during operation of the vehicle. An incoming telephonic event analysis application operating on the mobile device may be configured to apply a soft block to the incoming telephonic event and at least temporarily prevent the event from being displayed on the mobile device. In one embodiment, after applying the soft block, the incoming telephonic event analysis application may be configured to analyze vehicle operational data and user preferences to determine whether or not to remove the soft block and allow the incoming telephonic event to be displayed on the mobile device. In another embodiment, the incoming telephonic event analysis application may be configured to analyze a calculated driver score and a calculated road risk score to determine whether or not to remove the soft block and allow the incoming telephonic event to be displayed on the mobile device.

In the event that the incoming telephonic event analysis application determines not to allow the incoming telephonic event to be displayed on the mobile device (e.g., to prevent the incoming telephonic event from being displayed on the mobile device), the incoming telephonic event analysis application may be configured to maintain the soft block until operation of the vehicle is terminated and to provide an auto-reply to the provider of the incoming telephonic event that the driver associated with the mobile device is unable to respond to the telephonic event. In the event that the incoming telephonic event analysis application determines to permit the incoming telephonic event to be displayed on the mobile device, the incoming telephonic event analysis application may remove the soft block.

Other aspects described herein provide for a hands-free device activation system including a mobile device associated with a driver of a vehicle. The mobile device may be configured to launch the incoming telephonic event analysis

application responsive to a user input or an ignition event associated with the vehicle of the driver. After launching, the incoming telephonic event analysis application may be configured to instruct the mobile device to sync and/or pair with a proximate hands-free device. During operation of the vehicle, the mobile device may receive an incoming telephonic event. The incoming telephonic event analysis application operating on the mobile device may be configured to apply a soft block to the incoming telephonic event and at least temporarily prevent the event from being displayed on the mobile device.

In one embodiment, after applying the soft block, the incoming telephonic event analysis application may be configured to analyze vehicle operational data and user preferences to determine whether or not to remove the soft block and allow the incoming telephonic event to be displayed on the mobile device. In another embodiment, the incoming telephonic event analysis application may be configured to analyze a calculated driver score and a calculated road risk score to determine whether or not to remove the soft block and allow the incoming telephonic event to be displayed on the mobile device.

In the event that the incoming telephonic event analysis application determines not to allow the incoming telephonic event to be displayed on the mobile device, the incoming telephonic event analysis application may be configured to maintain the soft block until operation of the vehicle is terminated and/or to provide an auto-reply to the provider of the incoming telephonic event that the driver associated with the mobile device is unable to respond to the telephonic event. In the event that the incoming telephonic event analysis application determines to allow the incoming telephonic event to be displayed on the mobile device, the incoming telephonic event analysis application may remove the soft block, activate the hands-free device, and transmit the incoming telephonic event to the activated hands-free device.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of aspects described herein and the advantages thereof may be acquired by referring to the following description in consideration of the accompanying drawings, in which like reference numbers indicate like features, and wherein:

FIG. 1 depicts an example auto-reply and hands-free system according to one or more aspects of the present disclosure.

FIG. 2 is a flow diagram illustrating an example of an incoming telephonic event analysis method according to one or more aspects of the disclosure.

FIG. 3A is a flow diagram illustrating an example of an incoming telephonic event data analysis method according to one or more aspects of the disclosure.

FIG. 3B is a flow diagram illustrating another example of an incoming telephonic event data analysis method according to one or more aspects of the disclosure.

FIG. 4 is a flow diagram illustrating another example of an incoming telephonic event analysis method according to one or more aspects of the disclosure.

FIG. 5 is a flow diagram illustrating an example of an incoming telephonic event analysis method based on the presence of a hands-free device according to one or more aspects of the disclosure.

FIG. 6A is a flow diagram illustrating an example of an incoming telephonic event data analysis method according to one or more aspects of the disclosure.

FIG. 6B is a flow diagram illustrating another example of an incoming telephonic event data analysis method according to one or more aspects of the disclosure.

FIG. 7 is a flow diagram illustrating another example of an incoming telephonic event analysis method based on the presence of a hands-free device according to one or more aspects of the disclosure.

FIG. 8 illustrates an example network environment and computing systems that may be used to implement aspects of the disclosure.

DETAILED DESCRIPTION

In the following description of the various embodiments, reference is made to the accompanying drawings, which form a part hereof, and in which is shown by way of illustration various embodiments in which aspects described herein may be practiced. It is to be understood that other embodiments may be utilized and structural and functional modifications may be made without departing from the scope of the described aspects and embodiments. Aspects described herein are capable of other embodiments and of being practiced or being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein are for the purpose of description and should not be regarded as limiting. Rather, the phrases and terms used herein are to be given their broadest interpretation and meaning. The use of “including” and “comprising” and variations thereof is meant to encompass the items listed thereafter and equivalents thereof as well as additional items and equivalents thereof. The use of the terms “mounted,” “connected,” “coupled,” “positioned,” “engaged” and similar terms, is meant to include both direct and indirect mounting, connecting, coupling, positioning and engaging.

FIG. 1 is a diagram illustrating various example components of an auto-reply and hands-free system **100** according to one or more aspects of the disclosure. Auto-reply and hands-free system **100** may include a vehicle **110**, a mobile computing device **120**, a network **130**, and an incoming telephonic event analysis system **140**. Each component shown in FIG. 1 may be implemented in hardware, software, or a combination of the two. Additionally, each component of the auto-reply and hands-free system **100** may include a computing device (or system) having some or all of the structural components described below in regard to computing device **801** of FIG. 8.

Vehicle **110** of the auto-reply and hands-free system **100** may be an automobile, motorcycle, scooter, bus, van, truck, semi-truck, train, boat, recreational vehicle, or other vehicle. The vehicle **110** may further be an autonomous vehicle, semi-autonomous vehicle, or non-autonomous vehicle. In some examples, vehicle **110** may include vehicle operation/performance sensors **111** capable of detecting, recording, and transmitting various vehicle performance and/or operational data and environmental conditions data. For example, sensors **111** may detect, store, and transmit data corresponding to the vehicle's speed, rates of acceleration and/or deceleration, braking, swerving, and the like. Sensors **111** also may detect, store and/or transmit data received from the vehicle's internal systems, such as impact to the body of the vehicle, air bag deployment, headlight usage, brake light operation, door opening and closing, door locking and unlocking, cruise control usage, hazard light usage, windshield wiper usage, horn usage, turn signal usage, seat belt usage, phone and radio usage within the vehicle, internal decibel levels, and other data collected by the vehicle's computer systems.

Sensors **111** also may detect, store, and/or transmit data relating to moving violations and the observance of traffic signals and signs by the vehicle **110**. Additional sensors **111** may detect, store, and transmit data relating to the maintenance of the vehicle **110**, such as the engine status, oil level, engine coolant temperature, odometer reading, the level of fuel in the fuel tank, engine revolutions per minute (RPMs), and/or tire pressure.

The sensors **111** of vehicle **110** may further include one or more cameras and proximity sensors capable of recording additional conditions inside or outside of the vehicle **110**. Internal cameras may detect conditions such as the number of the passengers in the vehicle **110**, and potential sources of driver distraction within the vehicle (e.g., pets, phone usage, and unsecured objects in the vehicle). External cameras and proximity sensors may be configured to detect environmental conditions data such as nearby vehicles, vehicle spacing, traffic levels, road conditions, traffic obstructions, animals, cyclists, pedestrians, precipitation levels, light levels, sun position, and other conditions that may factor into driving operations of vehicle **110**.

Additionally, vehicle sensors **111** may be configured to independently transmit the above-mentioned data to one or more internal computing systems including on-board computer **115**, as well as one or more external computing systems such as telematics device **113**, mobile device **120**, and/or incoming telephonic event analysis system **140**. In some instances, the data transmission to the one or more external computing systems may be performed via on-board computer **115**. In such cases, the on-board computer **115** may be configured to transmit the data received from vehicle sensors **111** to telematics device **113**, mobile device **120**, and/or incoming even analysis system **140** by way of vehicle communication system **114**.

Vehicle **110** may include a Global Positioning System (GPS) **112** which may be used to generate data corresponding to the position and/or location of vehicle **110**. GPS **112** may be configured to independently transmit the above-mentioned data to one or more internal computing systems including on-board computer **115**, as well as one or more external computing systems such as telematics device **113**, mobile device **120**, and/or incoming telephonic event analysis system **140**. In some instances, the data transmission to the one or more external computing systems may be performed via on-board computer **115**. In such cases, the on-board computer **115** may be configured to transmit the data received from GPS **112** to telematics device **113**, mobile device **120**, and/or incoming even analysis system **140** by way of vehicle communication system **114**.

Telematics device **113** may be configured to receive vehicle performance and/or operational data and environmental conditions data in the form of a data stream from on-board computer **115** via a data port, Bluetooth interface, or any comparable communication interface of the vehicle **110**. For example, telematics device **113** may include an on-board diagnostic (OBD) device adapter and may be connected to an OBD port of the vehicle **110** through which on-board computer **115** may be configured to transmit data to telematics device **113**. In certain embodiments, telematics device **113** may be configured to receive vehicle performance and/or operational data and environmental conditions data directly from vehicle sensors **111**, GPS **112**, on-board computer **115**, and/or mobile device **120** via a wired or wireless connection. Telematics device **113** may include a memory to store data received from vehicle sensors **111**, GPS **112**, on-board computer **115**, and/or mobile device **120**.

The vehicle performance and/or operational data may be collected with appropriate permissions (e.g., from the driver, vehicle owner, etc.) and may include operational data from an industry standard port such as a SAE-1962 connector, or an on board diagnostic (“OBD”) port or other vehicle data acquiring component. For example, operation data accessible via the OBDII port includes speed and engine throttle position or other variable power controls of the vehicle power source. It may also include so called “extended OBDII” or OBDIII datasets that are specific to each manufacturer and also available with manufacturer permission such as odometer reading, seat belt status, activation of brakes, degree and duration of steering direction, etc., and implementation of accident avoidance devices such as turning signals, headlights, seatbelts, activation of automated braking systems (ABS), etc. Other information regarding the operation of the vehicle may be collected such as, but not limited to, interior and exterior vehicle temperature, window displacement, exterior vehicle barometric pressure, exhaust pressure, vehicle emissions, turbo blower pressure, turbo charger RPM, vehicle GPS location, etc. The system may recognize or be configured to recognize a particular language emitted by the vehicle system and may configure the recording component to receive or convert data in SAE J1850, ISO IS09141 or KWP 2000 formats. Accordingly, U.S. and/or international OBD standards may be accommodated. For instance, data may be collected from a variety of U.S. and/or international port types to permit use in a variety of locations. Alternatively, this step may be performed by a processor after the data is recorded.

Telematics device **113** may also include sensors such as, but not limited, an accelerometer, compass, gyroscope, and GPS. Additionally, telematics device **113** may include antennas to communicate with other devices wirelessly. For example, telematics device **113** may communicate with on-board computer **115**, mobile device **120**, and/or incoming telephonic event analysis system **140** over a wide area network (WAN), cellular network, Wi-Fi network, and the like. Telematics device **113** may also communicate with on-board computer **115** and mobile device **120** via a Bluetooth connection. In certain embodiments, telematics device **113** may be configured to establish a secure communication link and/or channel with on-board computer **115**, mobile device **120**, and/or incoming telephonic event analysis system **140**.

In some arrangements, telematics device **113** may be a telematics application operating on mobile computing device **120** and may utilize hardware components comprised within mobile computing device **120** (e.g., memory, processors, communication hardware, etc.) to receive, store, and/or transmit vehicle performance and/or operational data and environmental conditions data.

Vehicle communication systems **114** may be implemented using wireless protocols such as WLAN communication protocols (e.g., IEEE 802.11), Bluetooth (e.g., IEEE 802.15.1), one or more of the Communication Access for Land Mobiles (CALM) wireless communication protocols and air interfaces, and the like. In certain systems, communication systems **114** may include specialized hardware installed in vehicle **110** (e.g., transceivers, antennas, etc.) to facilitate near field communication (NFC) and/or radio-frequency identification (RFID), while in other examples the communication systems **114** may be implemented using existing vehicle hardware components (e.g., radio and satellite equipment, navigation computers). In some instances, the vehicle communication systems **114** may be configured to transmit and receive data from vehicle sensors **111**, GPS

112, telematics device 113, on-board computer 115, mobile device 120, and/or telephonic event analysis system 140 over a wide area network (WAN), cellular network, Wi-Fi network, Bluetooth, RFID, and/or NFC.

Vehicle control computer 115 may contain some or all of the hardware/software components as the computing device 801 of FIG. 8, and may be configured to operate aspects of the driving, or other operation of vehicle 110, including but not limited to, acceleration, braking, steering, and/or route navigation. Furthermore, vehicle control computer 115 may be configured to operate one or more internal vehicle systems and/or components including at least a vehicle sound system, dashboard display and/or heads-up display system, hands-free system including input microphone and output speakers, interior lighting system, climate control system, ignition system, door locking system, and the like. Similarly, vehicle control computer 115 may be configured to operate one or more external vehicle systems and/or components including windshield wipers, exterior lighting systems (e.g., headlights, tail lights, running lights, turn signals, emergency lights, etc.), emission and exhaust systems, fuel systems, suspension systems, transmission systems, and the like. In some instances, vehicle control computer 115 may be configured to perform the incoming telephonic event analysis methods as described in further detail below in conjunction with mobile computing device 120 and/or incoming telephonic event analysis system 140.

Mobile computing device 120 may be, for example, a mobile phone, personal digital assistant (PDA), or tablet computer associated with the driver or passenger(s) of vehicle 110. As such, mobile computing device 120 may be included within the vehicle 110 and, in some instances, may be used to independently collect vehicle driving data and/or to receive vehicle driving or operational/performance data and/or environmental conditions data from one or more internal and/or external computing systems (e.g., vehicle operation sensors 111, GPS 112, telematics device 113, on-board computer 115, telematics device 120, and/or incoming telephonic event analysis system 140). In one example, software applications executing on mobile computing device 120 (e.g., telematics application and/or incoming telephonic event analysis application) may be configured to independently detect driving data and/or to receive vehicle driving data and/or environmental conditions data from one or more internal and/or external computing systems. With respect to independent vehicle data detection and collection, mobile device 120 may be equipped with one or more accelerometers and/or GPS systems which may be accessed by software applications executing on mobile computing device 120 to determine vehicle location, velocity, acceleration, direction, and other driving data. As stated above, mobile computing device 120 may be configured to transmit the independently collected vehicle driving data and/or the received vehicle driving data to one or more internal and/or external computing devices (e.g., on-board computer 115, telematics device 120, and/or incoming telephonic event analysis system 140).

Additionally, mobile computing device 120 may be configured to perform the incoming telephonic event analysis methods as described in further detail below in conjunction with on-board computer 115 and/or incoming telephonic event analysis system 140. In some instances, the incoming telephonic event analysis methods may be performed by a telematics application and/or an incoming telephonic event analysis application operating on mobile device 120. In performing such methods, mobile device 120 may be configured to detect and store data corresponding to an incom-

ing telephonic event, and may be further configured to transmit the incoming telephonic event data to on-board computer 115 and/or incoming telephonic event analysis system 140. Furthermore, mobile device 120 may be configured to receive vehicle operational data, environmental conditions data, and/or data produced during the performance of the incoming telephonic event analysis methods from sensors 111, GPS 112, telematics device 113, on-board computer 115, and/or incoming telephonic event analysis system 140.

In certain embodiments, auto-reply and hands-free system 100 may further include hands-free device 116. Hands-free device 116 may be included within vehicle 110 as a component of on-board computer 115 and/or as a standalone device. In instances in which hands-free device 116 is a standalone device, it may any one of a hands-free headphone, headset, in-ear device, glasses, necklace, watch, and/or bracelet and may also be a hands-free kit comprising at least a computing device, speaker, and microphone. In instances in which hands-free device 116 is included within vehicle 110 as a component of on-board computer 115, hands-free device 116 may be a device, component, and/or system controlled by on-board computer 115. Regardless of the type (e.g., component of on-board computer 115 and/or standalone device), hands-free device 116 may contain some or all of the hardware/software components as the computing device 801 of FIG. 8.

Hands-free device 116 may be configured to sync and/or pair with mobile device 120 in order to facilitate communication between hands-free device 116 and mobile computing device 120. The syncing and/or pairing of hands-free device 116 with mobile computing device 120 may be performed through any one, or combination of, Bluetooth, NFC, RFID, and the like and/or through any one, or combination of, a WAN, cellular network, Wi-Fi network, and the like. Responsive to syncing and/or pairing, communication between hands-free device 116 and mobile device 120 may be conducted through any one, or combination of, a WAN, cellular network, Wi-Fi network, and the like and/or through any one, or combination of, Bluetooth, NFC, and the like.

The auto-reply and hands-free system 100 may include an incoming telephonic event analysis system 140 including an authorization server 150, a third party data source server 160, and a driver risk score/risk map server 170. The incoming telephonic event analysis system 140 and each of the authorization server 150, third party data source server 160, and driver risk score/risk map server 170 may contain some or all of the hardware/software components as the computing device 801 of FIG. 8.

The incoming telephonic event analysis system 140 may be a single server containing some or all of the hardware/software components as the computing device 801 of FIG. 8. In such instances, each of the authorization server 150, third party data source server 160, and the driver risk score/risk map server 170 may be virtual machines operating on the incoming telephonic event analysis system 140. Alternatively, the incoming telephonic event analysis system 140 may be a plurality of servers containing some or all of the hardware/software components as the computing device 801 of FIG. 8. In such instances, each of the authorization server 150, third party data source server 160, and the driver risk score/risk map server 170 may be individualized server entities.

In some instances, the analysis of the incoming telephonic event described in further detail below may be performed by is performed by incoming telephonic event analysis system

140. In such instances, the mobile device 120 may transmit incoming telephonic event to incoming telephonic event analysis system 140. Such data may include the individual or entity associated with incoming telephonic event, time of receipt of the incoming telephonic event, and the type of the incoming telephonic event. Upon receipt of the incoming telephonic event data, incoming telephonic event analysis system 140, alone or in combination, with on-board computer 115 may be able to perform the processes outlined in FIGS. 2-7.

Authorization server 150 may comprise an authorization computer 152 configured to receive, process, and transmit vehicle operational data, environmental conditions data, incoming telephonic event data, user authorization preference data, driver score data, and risk map data to determine whether or not an incoming telephonic event is to be allowed to be received at the mobile device 120 during the operation of vehicle 110. The authorization server 150 may also comprise an authorization database 154 configured to store the above-mentioned data received, processed, and transmitted by authorization computer 152. Authorization server 150 may be configured to receive data from vehicle operation sensors 111, GPS 112, telematics device 113, on-board computer 115, mobile device 120, third party data source server 160, and driver score/risk map server 170. Additionally, authorization server 150 may be configured to transmit data to telematics device 113, on-board computer 115, mobile device 120, third party data source server 160, and driver score/risk map server 170. In some instances, authorization server 150 may be optional and the processes performed by authorization server 150 may be distributed to any one, or combination of, mobile device 120 and on-board computer 115.

The third party data source server 160 may comprise a third party data source computer 162 configured to receive, process, and transmit environmental conditions data associated with a geographic location of vehicle 110 including current weather condition data, forecasted weather condition data, traffic flow data, road closure data, road type data, and/or other data environmental conditions data such as flash flood, earthquake, tsunami, tornado, tropical depression, tropical storm, and hurricane warnings. The third party data source server 160 may also comprise a third party data source database 164 used to store the environmental conditions data collected by the third party data source computer 162. Third party data source server 160 may be configured to receive data from vehicle operation sensors 111, GPS 112, telematics device 113, on-board computer 115, mobile device 120, authorization server 150, and driver score/risk map server 170. Additionally, third party data source server 160 may be configured to transmit data to telematics device 113, on-board computer 115, mobile device 120, authorization server 150, and driver score/risk map server 170. In some instances, authorization server 150 may be optional and the processes performed by authorization server 150 may be distributed to any one, or combination of, mobile device 120 and on-board computer 115.

Driver score/risk map server 170 may comprise a driver score/risk map computer 172 configured to receive and analyze vehicle operational data and environmental conditions data to calculate a driver risk score for a driver of vehicle 110 and a road risk score for a road segment on which vehicle 110 is driving. The calculation of the driver risk score and the road risk score are respectively described in U.S. application Ser. No. 13/564524 entitled, "Calculation and Utilization of a Driving Score," and U.S. application Ser. No. 15/052,291 entitled, "Risk Maps," both of which

are incorporated herein by reference in their entirety. Driver score/risk map server 170 may further include driver score/risk map database 174 to store the calculated driver risk score and the road risk score. In some instances, the driver score/risk map database 174 may also include historical data including insurance claims, accident reports, and historical vehicle operations data and environmental conditions data associated with insurance claims and accident reports. Such data may be utilized by driver score/risk map computer 172 in calculating the driver risk score and the road risk score. Driver score/risk map server 170 may be configured to receive data from vehicle operation sensors 111, GPS 112, telematics device 113, on-board computer 115, mobile device 120, authorization server 150, and third party data source server 160. Additionally, driver score/risk map server 170 may be configured to transmit data to telematics device 113, on-board computer 115, mobile device 120, authorization server 150, and third party data source server 160.

The following steps that are described in regard to FIGS. 2-7 may be implemented by one or more of the components of FIGS. 1 and 8 (described in detail below) and/or other components, including other computing devices configured to perform the functions described herein.

FIG. 2 depicts a flow diagram illustrating an example of an incoming telephonic event analysis method according to one or more aspects of the disclosure. As will be described below, the processes of the incoming telephonic event analysis method may be performed by any one, or combination of, mobile device 120, on-board computer 115, and incoming telephonic event analysis system 140.

At step 202, the mobile device 120 associated with a driver of vehicle 110 may receive an incoming telephonic event during the operation of vehicle 110. The incoming telephonic event may be of any of a plurality of telephonic event types (e.g., telephone call, text message, email, application notification, etc.) and may be associated with a first individual (e.g., mother, father, spouse, child, friend, coworker, etc.) associated with the driver of vehicle 110 or a first entity (e.g., bank, doctor's office, work place, telemarketer, etc.). In some instances, the incoming telephonic event may be a first, second, or third incoming telephonic event associated with the first individual or first entity. In instances in which the incoming telephonic event is a second or third incoming telephonic event, the incoming telephonic event may be of the same type, or a different type, as the previously received telephonic event(s). For example, if the incoming telephonic event is a second incoming telephonic event and is a telephone call, a previously received first incoming telephonic event may also be a telephone call, or may be any of a text message, email, application notification, and the like.

At step 204, upon receipt of the incoming telephonic event during an active operation state of the vehicle 110, an incoming telephonic event analysis application operating on mobile device 120 may apply a soft block to the incoming telephonic event preventing the event from being displayed on (and/or preventing audio notification from) the mobile device 120 based on the active operating state of the vehicle 110. The soft block applied by the incoming event analysis application may be a fluid block, which may be either removed or maintained depending on an analysis of the incoming telephonic event. After applying the soft block, the incoming telephonic event analysis application may analyze the incoming telephonic event in relation to a velocity of the vehicle 110, a pre-stored allowable individual or entity list, and/or an emergency incoming telephonic event threshold. In some instances, the analysis of the incoming telephonic

11

event in relation to the above-mentioned factors may be performed by the incoming telephonic event analysis application of mobile device **120**, on-board computer **115**, and/or incoming telephonic event analysis system **140**.

At step **206**, the incoming telephonic event analysis application may first determine a velocity of the vehicle **110**. In determining the velocity of the vehicle **110**, the incoming telephonic event analysis application may determine the velocity of vehicle **110** by requesting velocity data of the vehicle **110** from any one, or combination of, vehicle sensors **111**, GPS **112**, telematics device **113**, on-board computer **115**, and/or incoming event analysis system **140**. The velocity of the vehicle **110** may be a static value determined at the time of receipt of the telephonic event or may be a dynamic value determined throughout the duration of the telephonic event. In instances in which the velocity of the vehicle **110** is a static value, the incoming telephonic event analysis application may request the velocity data corresponding to the time of receipt of the telephonic event. Alternatively, in instances in which the velocity of the vehicle **110** is a dynamic value, the incoming telephonic event analysis application may request a continuous velocity data stream commencing at the time of receipt of the incoming telephonic event.

Through requesting the vehicle velocity data from a third party source (e.g., vehicle sensors **111**, GPS **112**, telematics device **113**, on-board computer **115**, and/or incoming event analysis system **140**), incoming telephonic event analysis application may provide a technological solution to existing deficiencies associated with mobile applications that determine vehicle velocity based on GPS data provided by a GPS system associated with a mobile device and/or vehicle velocity determined based on accelerometer data provided by an accelerometer of the mobile device. As stated above, the velocity determinations provided by such applications are easily subverted through restricting GPS access for the mobile applications and/or through the utilization of vehicle cruise control systems (or travelling at a constant velocity) and thereby preventing mobile device accelerometer engagement. Therefore, by requesting vehicle velocity data from a third party source, occurrences of such issues may be reduced or eliminated.

In instances in which the velocity of the vehicle **110** is a static value, after receiving the requested static vehicle velocity data corresponding to the time of receipt of the incoming telephonic event, the incoming telephonic event analysis application may compare the received vehicle velocity data to a pre-stored and/or predetermined velocity threshold (e.g., **0 mph**, **5 mph**, **10 mph**, etc.). If the received vehicle velocity data is less than the pre-stored velocity threshold, the incoming telephonic event analysis application may proceed to step **214** and remove the soft block and display the incoming telephonic event on the mobile device **120**.

In one example, after removing the soft block and allowing the incoming telephonic event to be displayed on mobile device **120**, the incoming telephonic event application may allow the user to take and/or respond to the telephonic event. In other examples, the incoming telephonic event application may allow the user to take and/or respond to the telephonic event for a predetermined period of time (e.g., **30 seconds**, **1 minute**, **2 minutes**, etc.), allow the user to take and/or respond to the incoming telephonic event if it is of a specific telephonic event type (e.g., telephone call) for a predetermined period of time, or may allow the notification of the incoming telephonic event to be displayed on mobile device **120** but prevent the user from being able to take

12

and/or respond to the event until after vehicle operation has concluded. When the incoming telephonic event is allowed to be taken and/or responded to by the user for a predetermined period of time, the incoming telephonic event analysis application may provide the user with incremental countdown updates alerting the user to the termination of the predetermined allowable period. Such updates may occur any number of times within the predetermined allowable period (e.g., two times within the allowable period, three times within the allowable period, etc.). Alternatively, if the received vehicle velocity data is greater than or equal to the pre-stored velocity threshold, the incoming telephonic event analysis application may maintain the soft block and proceed to step **208**.

In instances in which the velocity of the vehicle **110** is a dynamic value, the incoming telephonic event analysis application may compare the first vehicle velocity data point from the velocity data stream corresponding to the time of receipt of the incoming telephonic event to a pre-stored and/or predetermined velocity threshold (e.g., **0 mph**, **5 mph**, **10 mph**, etc.). If the first vehicle velocity data point is less than the pre-stored velocity threshold, the incoming telephonic event analysis application may proceed to step **214** and remove the soft block and display the incoming telephonic event on the mobile device **120**.

After removing the soft block and allowing the incoming telephonic event to be displayed on mobile device **120**, the incoming telephonic event application may allow the user to take and/or respond to the telephonic event, allow the user to take and/or respond to the telephonic event for a predetermined period of time (e.g., **30 seconds**, **1 minute**, **2 minutes**, etc.), allow the user to take and/or respond to the incoming telephonic event if it is of a specific telephonic event type (e.g., telephone call) for a predetermined period of time, or allow the notification of the incoming telephonic event to be displayed on mobile device **120** but prevent the user from being able to take and/or respond to the event until after vehicle operation has concluded. However, the incoming telephonic event analysis application may continuously compare the vehicle velocity data points from the vehicle velocity data stream to the pre-stored and/or predetermined velocity threshold. In the event that a vehicle velocity data point from the vehicle velocity data stream exceeds the velocity threshold, the incoming telephonic event analysis application may alert the user that the incoming telephonic event will be terminated unless the user decreases the velocity of the vehicle to a point below the velocity threshold. Such an alert may be provided by the incoming telephonic event analysis application under any of the examples in which incoming telephonic event analysis application allows the user to take and/or respond to the incoming telephonic event. Alternatively, if the first vehicle velocity data point from the velocity data stream is greater than or equal to the pre-stored velocity threshold, the incoming telephonic event analysis application may maintain the soft block and proceed to step **208**.

At step **208**, if the received vehicle velocity data is greater than or equal to the pre-stored velocity threshold and the soft block is maintained, the incoming telephonic event analysis application may determine whether the incoming telephonic event is associated with an individual or entity pre-stored by the user through the incoming telephonic event analysis application as being an allowable individual or entity. The allowable individual or entity list may include one or more individuals or entities previously entered by the driver associated with mobile device **120** into the incoming telephonic event analysis application. The driver associated

with mobile device **120** may be allowed to enter an unlimited or finite amount (e.g., five individuals or entities) of allowable individuals or entities into the allowable individual or entity list.

If the incoming telephonic event is determined to be associated with an allowable individual or entity, the incoming telephonic event analysis application may remove the soft block and allow the incoming telephonic event to be displayed on mobile device **120** regardless of the velocity of the vehicle. After removing the soft block and allowing the incoming telephonic event to be displayed on mobile device **120**, the incoming telephonic event application may allow the user to take and/or respond to the telephonic event in the ways described above. Alternatively, if the incoming telephonic event is determined not to be associated with an allowable individual or entity, the incoming telephonic event analysis application may maintain the soft block and proceed to step **210**.

At step **210**, the incoming telephonic event analysis application may analyze telephonic event data corresponding to the incoming telephonic in comparison with previously received telephonic event data to determine whether the incoming telephonic event is a third telephonic event associated with a particular individual or entity. Such analyses are described in further detail in regard to FIGS. **3A** and **3B**.

FIG. **3A** is a flow diagram illustrating an example of an incoming telephonic event data analysis method according to one or more aspects of the disclosure. At step **302A**, the incoming telephonic event analysis application may extract telephonic event data from the incoming telephonic event. Such data may include a name, telephone number, user name (e.g., handle), event type (e.g., telephone call, text message, email, application notification, etc.), and time of receipt.

At step **304A**, the incoming telephonic event analysis application may determine whether a first immediately preceding telephonic event was received. Data corresponding to previously received telephonic events may be previously stored in memory on mobile device **120** by the incoming telephonic event analysis application. In one instance, the stored previously received telephonic event data may correspond to an active operative period of vehicle **110**, wherein the active operative is initiated by a positive ignition event (e.g., vehicle **110** is turned on). In such instances, mobile device **120** may be configured to receive indication of a positive ignition event from sensors **111**, telematics device **113**, and/or on-board computer **115** and the incoming telephonic event analysis application may be configured to create a data ledger within memory of mobile device **120** corresponding to the active operative period of vehicle **110**. As will be discussed in further detail below, the data ledger may be cleared and/or reset responsive to the conclusion of the active operative period through receipt of an indication of a negative ignition event (e.g., vehicle **110** is turned off). In doing so, memory of mobile device **120** may be actively conserved as related to the incoming telephonic event application. Alternatively, the data ledger may be achieved responsive to the conclusion of the active operative period through receipt of an indication of a negative ignition event and may be accessible at a later time.

In any event, if no data corresponding to a first immediately preceding telephonic event exists in memory (e.g., no previous telephonic event data exists in memory), the incoming telephonic event analysis application may determine that the incoming telephonic event is a first incoming telephonic event. If the incoming telephonic event is determined to be a first incoming telephonic event, incoming

telephonic event analysis application may maintain the soft block and prevent the first incoming telephonic event from being displayed on the mobile device **120** at step **212**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the first incoming telephonic event that the user is driving and currently unavailable to respond to the telephonic event. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the first telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if one or more previously stored telephonic event data entries exists in memory in the data ledger, the determination of the first immediately preceding telephonic event may be made. In instances in which a plurality of previously stored telephonic event data entries exists in the data ledger, the determination of the first immediately preceding telephonic event may be made based on a time difference between the time of receipt of the incoming telephonic event and previously stored receipt times corresponding to previously received telephonic events. The difference with the smallest magnitude may be determined to be the first immediately preceding telephonic event. Alternatively, in instances in which data corresponding to only one previously received telephonic event is stored in memory in the data ledger, a comparison of receipt times may be foregone and the one previously received telephonic event may be determined to be the first immediately preceding telephonic event.

At step **306A**, after determining that a first immediately preceding telephonic event was received, the incoming telephonic event analysis application may compare the extracted name, telephone number, and user name (e.g., handle) from the incoming telephonic event to that of the first immediately preceding telephonic event to determine whether or not the incoming telephonic event and the first immediately preceding telephonic event share a common sending individual or entity. If it is determined that the incoming telephonic event and the first immediately preceding telephonic event do not share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is a first incoming telephonic event associated with a particular sending individual or entity. After such a determination, the incoming telephonic event analysis application may maintain the soft block and prevent the first incoming telephonic event from being displayed on the mobile device **120** at step **212**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the first incoming telephonic event that the user is driving and currently unavailable to respond to the telephonic event. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the first telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if it is determined that the incoming telephonic event and the first immediately preceding telephonic event share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is at least a second incoming telephonic event associated with the particular sending individual or entity and may proceed to step **308A**.

At step **308A**, the incoming telephonic event analysis application may determine whether a second immediately

preceding telephonic event was received. In doing so, the incoming telephonic event analysis application may review the data ledger in memory to determine if a second immediately preceding telephonic event was received. If no data corresponding to a second immediately preceding telephonic event exists in memory (e.g., only data corresponding to the first immediately preceding telephonic event exists in memory), the incoming telephonic event analysis application may determine that the incoming telephonic event is a second incoming telephonic event associated with the particular individual or entity and prevent the second incoming telephonic event from being displayed on the mobile device **120** at step **212**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the second incoming telephonic event alerting the individual or entity that the user is still driving and unavailable to respond to the telephonic event, but if that it is an emergency situation, the individual or entity should provide a third telephonic event to be connected to the mobile device of the user. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the second telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if two or more previously stored telephonic event data entries exists in memory in the data ledger, the determination of the second immediately preceding telephonic event may be made. In instances in which a plurality of previously stored telephonic event data entries exists in the data ledger, the determination of the second immediately preceding telephonic event may be made based on a time difference between the time of receipt of the incoming telephonic event and previously stored receipt times corresponding to previously received telephonic events. The difference with the second smallest magnitude may be determined to be the second immediately preceding telephonic event.

At step **310A**, after determining that a second immediately preceding telephonic event was received, the incoming telephonic event analysis application may compare the extracted name, telephone number, and user name (e.g., handle) from the incoming telephonic event to that of the second immediately preceding telephonic event to determine whether or not the incoming telephonic event and the second immediately preceding telephonic event share a common sending individual or entity. If it is determined that the incoming telephonic event and the second immediately preceding telephonic event do not share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is a second incoming telephonic event associated with the particular individual or entity and prevent the second incoming telephonic event from being displayed on the mobile device **120** at step **212**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the second incoming telephonic event alerting the individual or entity that the user is still driving and unavailable to respond to the telephonic event, but if that it is an emergency situation, the individual or entity should provide a third telephonic event to be connected to the mobile device of the user. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the second telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if it is determined that the incoming telephonic event and the second immediately preceding tel-

ephonic event share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is at least a third incoming telephonic event associated with the particular sending individual or entity and, at step **214**, the incoming telephonic event analysis application may remove the soft block and allow the third incoming telephonic event to be displayed on the mobile device **120**. After removing the soft block and allowing the incoming telephonic event to be displayed on mobile device **120**, the incoming telephonic event application may allow the user to take and/or respond to the telephonic event in the ways described above.

FIG. **3B** is a flow diagram illustrating another example of an incoming telephonic event data analysis method according to one or more aspects of the disclosure. At step **302B**, the incoming telephonic event analysis application may extract telephonic event data from the incoming telephonic event. Such data may include a name, telephone number, user name (e.g., handle), event type (e.g., telephone call, text message, email, application notification, etc.), and time of receipt.

At step **304B**, the incoming telephonic event analysis application may determine whether previously stored telephonic event data is stored in memory in the data ledger associated with the active operative period of vehicle **110**. Data corresponding to previously received telephonic events may be previously stored in memory on mobile device **120** by the incoming telephonic event analysis application. In one instance, the stored previously received telephonic event data may correspond to an active operative period of vehicle **110**, wherein the active operative is initiated by a positive ignition event (e.g., vehicle **110** is turned on). In such instances, mobile device **120** may be configured to receive indication of a positive ignition event from sensors **111**, telematics device **113**, and/or on-board computer **115** and the incoming telephonic event analysis application may be configured to create a data ledger within memory of mobile device **120** corresponding to the active operative period of vehicle **110**. In one instance, the data ledger may be cleared and/or reset responsive to the conclusion of the active operative period through receipt of an indication of a negative ignition event (e.g., vehicle **110** is turned off). In doing so, memory of mobile device **120** may be actively conserved as related to the incoming telephonic event application. Alternatively, the data ledger may be achieved responsive to the conclusion of the active operative period through receipt of an indication of a negative ignition event and may be accessible at a later time.

However, in some cases, the active operating state of the vehicle **110** may be determined by a velocity, acceleration, and/or displacement magnitude and mobile device **120** may be configured to receive indication of such a magnitude from sensors **111**, telematics device **113**, and/or on-board computer **115** and the incoming telephonic event analysis application may be configured to create a data ledger within memory of mobile device **120** corresponding to the active operative period of vehicle **110**. Similarly, the termination of an active operating state of the vehicle **110** may be determined by a prolonged period (e.g., 1 min, 5 min, 10 min, etc.) without a velocity, acceleration, and/or displacement magnitude.

In some instances, the start of an active operating state of the vehicle **110** may be determined by a negative parking brake indication (e.g., parking brake disengaged), a shift into reverse or drive after a prolonged period (e.g., 5 min, 10 min, 30 min, etc.) of being in park, a positive headlight activation, brake pedal activation, gas pedal activation, and/or a state

change in one or more vehicle systems requiring user input. Conversely, the end of an active operating state of vehicle **110** may be determined by a positive parking brake indication (e.g., parking brake engagement), a shift into park, headlight deactivation, absence of brake pedal usage, gas pedal usage, and/or state change in one or more vehicle systems requiring user input. Additionally, such state changes may be time constrained. Similar to the state changes noted above, mobile device **120** may be configured to receive indication of such state changes from sensors **111**, telematics device **113**, and/or on-board computer **115**.

If no data corresponding to a previously received telephonic event exists in memory, the incoming telephonic event analysis application may determine that the incoming telephonic event is a first incoming telephonic event. If the incoming telephonic event is determined to be a first incoming telephonic event, incoming telephonic event analysis application may maintain the soft block and prevent the first incoming telephonic event from being displayed on the mobile device **120** at step **212**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the first incoming telephonic event that the user is driving and currently unavailable to respond to the telephonic event. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the first telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if data corresponding to one or more previously received telephonic events is stored in memory in the data ledger associated with the active operative period of vehicle **110**, the incoming telephonic event analysis application may consolidate the previously stored telephonic event data based on a retroactive time window, wherein the previously stored telephonic event data comprised within the consolidated window may be marked for further comparison with the telephonic event data of the incoming telephonic event. The retroactive time window may be a predetermined period of time (e.g., 1 minute, 5 minutes, 30 minutes, etc.) extending into the past from the time at which the incoming telephonic event was received at mobile device **120**. For example, if previously stored telephonic event data exists in memory in the data ledger and an incoming telephonic event is received at 3:00 PM EST, the retroactive time window may extend into the past until 2:55 PM EST. Each telephonic event received between 2:55 PM EST and 3:00 PM EST may be isolated by the incoming telephonic event analysis application from the remainder of the previously stored telephonic event data received outside of the retroactive time window and marked for further comparison.

At step **306B**, after isolating previously stored telephonic event data within the retroactive time window, the incoming telephonic event analysis application may compare the extracted name, telephone number, and user name (e.g., handle) from the incoming telephonic event to that of each of the previously stored telephonic event data entries in the consolidated time window to determine whether or not the incoming telephonic event and any of the previously stored telephonic event data entries share a common sending individual or entity. If it is determined that the incoming telephonic event and any of the previously stored telephonic event data entries do not share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is a first incoming telephonic event associated with a particular sending individual or entity. After such a determination, the incoming telephonic event analysis application may main-

tain the soft block and prevent the first incoming telephonic event from being displayed on the mobile device **120** at step **212**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the first incoming telephonic event that the user is driving and currently unavailable to respond to the telephonic event. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the first telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if it is determined that the incoming telephonic event and at least a first entry of the previously stored telephonic event data entries in the retroactive window share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is at least a second incoming telephonic event associated with the particular individual or entity and may proceed to step **308B**.

At step **308B**, the incoming telephonic event analysis application may compare the extracted name, telephone number, and user name (e.g., handle) from the incoming telephonic event to that of each of the previously stored telephonic event data entries in the consolidated time window (besides the first entry sharing the common individual or entity determined in step **306B**) to determine whether or not the incoming telephonic event and a second entry of the previously stored telephonic event data entries share a common sending individual or entity. If it is determined that the incoming telephonic event and none of the remainder of the previously stored telephonic event data entries share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is a second incoming telephonic event associated with a particular sending individual or entity. After such a determination, the incoming telephonic event analysis application may maintain the soft block and prevent the second incoming telephonic event from being displayed on the mobile device **120** at step **212**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the second incoming telephonic event that the user is driving and currently unavailable to respond to the telephonic event. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the second telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if it is determined that the incoming telephonic event and at least a second entry of the previously stored telephonic event data entries in the retroactive window share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is at least a third incoming telephonic event associated with the particular sending individual or entity and, at step **214**, the incoming telephonic event analysis application may remove the soft block and allow the third incoming telephonic event to be displayed on the mobile device **120**. After removing the soft block and allowing the incoming telephonic event to be displayed on mobile device **120**, the incoming telephonic event application may allow the user to take and/or respond to the telephonic event in the ways described above.

In some instances, when the soft block is removed by the incoming telephonic event analysis application and the incoming telephonic event is displayed on mobile device **120**, the driver associated with mobile device **120** may be

awarded points for not interacting with the mobile device 120 in response to the displayed telephonic event. Such points may be used by the driver associated with mobile device 120 to incrementally increase the predetermined vehicle velocity threshold and/or add additional individuals or entities to the allowable individual or entity list. For example, for every incoming telephonic event displayed on mobile device 120 that is not interacted with by the driver of vehicle 110, one point may be awarded to the driver. After 100 points have been awarded, the driver may be able to increase the velocity threshold by 0.1 mph. Alternatively, after 1000 points have been awarded, the driver may be able to add an additional individual or entity to the allowable individual or entity list. In some instances, the driver may receive electronic badges after surpassing certain point thresholds (e.g., 100 points, 500 points, etc.). Additionally or alternatively, the driver may receive a financial reward for reaching certain points thresholds.

At step 216, after the active operative period of vehicle 110 has been terminated and an indication of such has been received at mobile device 120, the incoming telephonic event analysis application may display a rollup on the mobile device 120 of the driver comprising each of the incoming telephonic events blocked from being displayed on mobile device 120 during driving. The rollup may include each of the data entries stored in the data ledger in memory. As such, each of the telephonic events received during operation of vehicle 110, the type of each of the telephonic events, the individual or entity associated with each of the telephonic events, an indication of availability of each of the individuals or entities associated with each of the telephonic events, and the time of receipt of each of the telephonic events. In some instances, the driver may be able to select each of the telephonic events comprised in the rollup to respond to the telephonic event in the manner corresponding to the event type (e.g., telephone call, email, text message, application specific interface, etc.). Alternatively, the driver may be able to select from the totality of telephonic event types in responding to the received telephonic event.

In some instances, the incoming telephonic event analysis application may be configured to cleared and/or reset the data ledger responsive to the conclusion of the active operative period through receipt of a state change event from sensors 111, telematics device 113, and/or on-board computer 115. In doing so, memory of mobile device 120 may be actively conserved as related to the incoming telephonic event application. Alternatively, the data ledger may be achieved responsive to the conclusion of the active operative period through receipt of an indication of a negative ignition event and may be accessible at a later time.

In examples in which the analysis of the incoming telephonic event is performed by on-board computer 115 and/or incoming telephonic event analysis system 140, mobile device 120 may transmit incoming telephonic event data to on-board computer 115 and/or incoming telephonic event analysis system 140. Such data may include the individual or entity associated with incoming telephonic event, time of receipt of the incoming telephonic event, and the type of the incoming telephonic event. Upon receipt of the incoming telephonic event data, on-board computer 115 and incoming telephonic event analysis system 140, alone or in combination, may be able to perform the determination features outlined above in steps 206, 208, and 210 (e.g., FIGS. 3A and 3B). Responsive to performing the respective determination steps, on-board computer 115 and incoming telephonic event analysis system 140, either alone or in

combination, may be configured to transmit the results of such steps to mobile device 120.

FIG. 4 is a flow diagram illustrating another example of an incoming telephonic event analysis method according to one or more aspects of the disclosure. As will be described below, the processes of the incoming telephonic event analysis method may be performed by any one, or combination of, mobile device 120, on-board computer 115, and incoming telephonic event analysis system 140.

At step 402, the mobile device 120 may receive an incoming telephonic event analysis application activation command from on-board computer 115, which may send the activation command in response to receiving a positive vehicle ignition event (e.g., turning vehicle on and commencing active vehicle operation state) and/or any one, or combination of, state change events described above. Responsive to receiving the incoming telephonic event analysis application activation command, mobile device 120 may activate the incoming telephonic event analysis application. As such, the processing of mobile device 120 may be controlled at least in part by the on-board computer 115 in cases in which an ignition event is detected. In doing so, the battery of mobile device 120 may be conserved by preventing the processes of the incoming telephonic event analysis application from running in a state outside of the operation of vehicle 110. Additionally, by automating the application activation based on an ignition event, instances in which the driver of vehicle 110 associated with mobile device 120 forgets to launch the incoming telephonic event analysis application may be reduced or eliminated.

At step 404, after the incoming telephonic event analysis application has been activated on mobile device 120 responsive to the command sent from vehicle on-board computer 115, the mobile device 120 associated with the driver of vehicle 110 may receive an incoming telephonic event during operation of vehicle 110. The incoming telephonic event may be of any of a plurality of telephonic event types. Upon receipt of the incoming telephonic event, the incoming telephonic event analysis application operating on mobile device 120 may apply a soft block to the incoming telephonic event preventing the event from being displayed on the mobile device 120 based on the active operation state of the vehicle 110.

At step 406, the mobile device 120 may transmit a data transmittal control command to telematics device 113. The data transmittal control command may be configured to activate telematics device 113 and may further include instructions for the telematics device 113 to transmit specific data elements of the vehicle operational data and environmental conditions data to incoming telephonic event analysis system 140 corresponding to the time of receipt of the incoming telephonic event. The specific data elements within the broader categories of vehicle operational data and environmental conditions data may coincide with data elements required by driver score/risk map server 170 to perform the calculations of the driver risk score and road risk score. Alternatively, the data transmittal control command may include instructions for telematics device 113 to transmit the specific data elements to mobile device 120. In such instances, the incoming telephonic event analysis application on mobile device 120 may be configured to perform the driver risk score and road risk score calculations described below in regards to driver score/risk map server 170. In either event, by transmitting only the necessary data to perform the driver risk score and road risk score calculations

corresponding to the time of receipt of the incoming telephonic event, bandwidth and processing power may be conserved.

In response to receiving the specific data elements of the vehicle operational data and environmental conditions data from telematics device 113, incoming telephonic event analysis system 140 may route the data to driver score/risk map server 170. The driver score/risk map server 170 may use the data in conjunction with historical data stored in driver score/risk map database 174 and auxiliary environmental conditions data provided by third party data source server 160 to perform the driver risk score and road risk score calculations. After performing the calculations, driver score/risk map server 170 may transmit the calculated driver risk score and road risk score to mobile device 120, which may be configured to receive the calculated driver risk score and road risk score at step 308.

At step 410, upon receiving the calculated driver risk score and road risk score from driver score/risk map server 170, the incoming telephonic event analysis application on mobile device 120 may determine whether or not to remove or to maintain the soft block applied to the incoming telephonic event. In doing so, the incoming telephonic event analysis application may compare both the driver risk score and the road risk score to allowance thresholds respective to the driver risk score and the road risk score. If both of the driver score and the road risk score are below the respective allowance thresholds, the incoming telephonic event analysis application may proceed to step 314, remove the soft block, and allow the incoming telephonic event to be displayed on the mobile device 120. After removing the soft block and allowing the incoming telephonic event to be displayed on mobile device 120, the incoming telephonic event application may allow the user to take and/or respond to the telephonic event in the ways described above. Alternatively, if either or both of the driver risk score or the road risk score is above the respective allowance threshold, the incoming telephonic event analysis application may proceed to step 312, maintain the soft block, and prevent the incoming telephonic event from being displayed on the mobile device 120.

In some instances, when the soft block is removed by the incoming telephonic event analysis application and the incoming telephonic event is displayed on mobile device 120, the driver associated with mobile device 120 may be awarded points for not interacting with the mobile device 120 in response to the displayed telephonic event. Such points may be used by the driver associated with mobile device 120 to incrementally increase the predetermined vehicle velocity threshold and/or add additional individuals or entities to the allowable individual or entity list. For example, for every incoming telephonic event displayed on mobile device 120 that is not interacted with by the driver of vehicle 110, one point may be awarded to the driver. After 100 points have been awarded, the driver may be able to increase the velocity threshold by 0.1 mph. Alternatively, after 1000 points have been awarded, the driver may be able to add an additional individual or entity to the allowable individual or entity list. In some instances, the driver may receive electronic badges after surpassing certain point thresholds (e.g., 100 points, 500 points, etc.).

At step 416, after driving has been completed and vehicle 110 is turned off, the mobile device 120 may receive an incoming telephonic event analysis application deactivation command from on-board computer 115, which may be send the deactivation command in response to receiving a negative vehicle ignition event (e.g., turning vehicle off). By

activating and deactivating the incoming telephonic event analysis application in response to a vehicle ignition event (e.g., turning vehicle on or off), the battery and processing power of mobile device 120 may be conserved by ensuring that the utilization of the incoming telephonic event analysis application coincides with periods of operation of vehicle 110. Additionally, the usage of the vehicle ignition event to trigger the incoming telephonic event analysis application may restrict the operation of the application to periods of driving and prevent operation carry over between periods of driving and periods of non-driving.

After operation of vehicle 110 has been terminated but prior to deactivation, the incoming telephonic event analysis application may provide the driver associated with mobile device 110 with a rollup comprising each of the incoming telephonic events blocked from being displayed on mobile device 120 during driving. The rollup may include each of the telephonic events received during operation of vehicle 110, the type of each of the telephonic events, the individual or entity associated with the each of the telephonic events, an indication of availability of each of the individuals or entities associated with each of the telephonic events, and the time of receipt of each of the telephonic events. In some instances, the driver may be able to select each of the telephonic events comprised in the rollup to respond to the telephonic event in the manner corresponding to the event type (e.g., telephone call, email, text message, application specific interface, etc.). Alternatively, the driver may be able to select from the totality of telephonic event types in responding to the received telephonic event.

FIG. 5 is a flow diagram illustrating an example of an incoming telephonic event analysis method based on the presence of a hands-free device according to one or more aspects of the disclosure. As will be described below, the processes of the incoming telephonic event analysis method may be performed by any one, or combination of, mobile device 120, on-board computer 115, and incoming telephonic event analysis system 140.

At step 502, mobile device 120 may launch the incoming telephonic event analysis application in response to a user input. At step 504, after the incoming telephonic event analysis application has been launched, the incoming telephonic event analysis application may cause the mobile device 120 to scan for the presence of a hands-free device 116 in the proximity of mobile device 120. In the event that a hands-free device 116 is registered during the scan conducted by mobile device 120, the incoming telephonic event analysis application may instruct the mobile device 120 to sync and/or pair with the hands-free device 116. Alternatively, if a hands-free device 116 is not registered during the scan, no instruction to sync and/or pair may be given to mobile device 120.

In either event, at step 506, mobile device 120 associated with a driver of vehicle 110 may receive an incoming telephonic event during operation of vehicle 110. The incoming telephonic event may be of any of a plurality of telephonic event types and may be associated with a first individual associated with the driver of vehicle 110 or a first entity. In some instances, the incoming telephonic event may be a first, second, or third incoming telephonic event associated with the first individual or first entity. Upon receipt of the incoming telephonic event, the incoming telephonic event analysis application operating on mobile device 120 may apply a soft block to the incoming telephonic event preventing the event from being displayed on the mobile device 120 based on the active operative state of the vehicle 110. After applying the soft block, the incoming event

analysis application may analyze the incoming telephonic event in relation to a state of syncing and/or pairing with the hands-free device **116**, a velocity of the vehicle **110** corresponding to the time of receipt of the telephonic event, a pre-stored allowable individual or entity list, and/or an emergency incoming telephonic event threshold.

At step **508**, the incoming telephonic event analysis application may determine a velocity of the vehicle **110** at the time of receiving the incoming telephonic event. In determining the velocity of the vehicle **110**, the incoming telephonic event analysis application may request velocity data of the vehicle **110** from any one, or combination of, vehicle sensors **111**, GPS **112**, telematics device **113**, on-board computer **115**, and/or incoming event analysis system **140**. The velocity of the vehicle **110** may be a static value determined at the time of receipt of the telephonic event or may be a dynamic value determined throughout the duration of the telephonic event. In instances in which the velocity of the vehicle **110** is a static value, the incoming telephonic event analysis application may request the velocity data corresponding to the time of receipt of the telephonic event. Alternatively, in instances in which the velocity of the vehicle **110** is a dynamic value, the incoming telephonic event analysis application may request a continuous velocity data stream commencing at the time of receipt of the incoming telephonic event.

In instances in which the velocity of the vehicle **110** is a static value, after receiving the requested static vehicle velocity data corresponding to the time of receipt of the incoming telephonic event, the incoming telephonic event analysis application may compare the received vehicle velocity data to a pre-stored and/or predetermined velocity threshold (e.g., 0 mph, 5 mph, 10 mph, etc.). At step **516**, if the received vehicle velocity data is less than the pre-stored velocity threshold, the incoming telephonic event analysis application may determine whether or not the mobile device **120** was synced and/or paired with the hands-free device **116**. At step **518**, if the mobile device **120** was previously synced and/or paired with the hands-free device **116** after the launching of the incoming telephonic event analysis application, the incoming telephonic event analysis application may activate the hands-free device **116**, remove the soft block, and direct the incoming telephonic event on the mobile device **120** to hands-free device **116**. Alternatively, at step **520**, if the mobile device **120** was not previously synced and/or paired with the hands-free device **116** because no hands-free device **116** was detected after launch of the incoming telephonic event analysis application, the incoming telephonic event analysis application may remove the soft block and display the incoming telephonic event on the mobile device **120**.

In one example, after step **518** or step **520**, the incoming telephonic event application may allow the user to take and/or respond to the telephonic event, allow the user to take and/or respond to the telephonic event for a predetermined period of time (e.g., 30 seconds, 1 minute, 2 minutes, etc.), allow the user to take and/or respond to the incoming telephonic event if it is of a specific telephonic event type (e.g., telephone call) for a predetermined period of time, or may allow the notification of the incoming telephonic event to be displayed on mobile device **120** but prevent the user from being able to take and/or respond to the event until after vehicle operation has concluded. When the incoming telephonic event is allowed to be taken and/or responded to by the user for a predetermined period of time, the incoming telephonic event analysis application may provide the user with incremental countdown updates alerting the user to the

termination of the predetermined allowable period. Such updates may occur any number of times within the predetermined allowable period (e.g., two times within the allowable period, three times within the allowable period, etc.). Alternatively, if the received vehicle velocity data is greater than or equal to the pre-stored velocity threshold, the incoming telephonic event analysis application may maintain the soft block and proceed to step **510**.

In instances in which the velocity of the vehicle **110** is a dynamic value, the incoming telephonic event analysis application may compare the first vehicle velocity data point from the velocity data stream corresponding to the time of receipt of the incoming telephonic event to a pre-stored and/or predetermined velocity threshold (e.g., 0 mph, 5 mph, 10 mph, etc.). At step **516**, if the first vehicle velocity data point is less than the pre-stored velocity threshold, the incoming telephonic event analysis application may determine whether or not the mobile device **120** was synced and/or paired with the hands-free device **116**. At step **518**, if the mobile device **120** was previously synced and/or paired with the hands-free device **116** after the launching of the incoming telephonic event analysis application, the incoming telephonic event analysis application may activate the hands-free device **116**, remove the soft block, and direct the incoming telephonic event on the mobile device **120** to hands-free device **116**. Alternatively, at step **520**, if the mobile device **120** was not previously synced and/or paired with the hands-free device **116** because no hands-free device **116** was detected after launch of the incoming telephonic event analysis application, the incoming telephonic event analysis application may remove the soft block and display the incoming telephonic event on the mobile device **120**.

After step **518** or step **520**, the incoming telephonic event application may allow the user to take and/or respond to the telephonic event, allow the user to take and/or respond to the telephonic event for a predetermined period of time (e.g., 30 seconds, 1 minute, 2 minutes, etc.), allow the user to take and/or respond to the incoming telephonic event if it is of a specific telephonic event type (e.g., telephone call) for a predetermined period of time, or allow the notification of the incoming telephonic event to be displayed on mobile device **120** but prevent the user from being able to take and/or respond to the event until after vehicle operation has concluded. However, the incoming telephonic event analysis application may continuously compare the vehicle velocity data points from the vehicle velocity data stream to the pre-stored and/or predetermined velocity threshold. In the event that a vehicle velocity data point from the vehicle velocity data stream exceeds the velocity threshold, the incoming telephonic event analysis application may alert the user that the incoming telephonic event will be terminated unless the user decreases the velocity of the vehicle to a point below the velocity threshold. Such an alert may be provided by the incoming telephonic event analysis application under any of the examples in which incoming telephonic event analysis application allows the user to take and/or respond to the incoming telephonic event. Alternatively, if the first vehicle velocity data point from the velocity data stream is greater than or equal to the pre-stored velocity threshold, the incoming telephonic event analysis application may maintain the soft block and proceed to Step **410**.

At step **510**, if the received vehicle velocity data is greater than or equal to the pre-stored velocity threshold and the soft block is maintained, the incoming event analysis application may determine whether the incoming telephonic event is associated with an individual or entity pre-stored by the user

through the incoming event analysis application as being an allowable individual or entity. The allowable individual or entity list may include one or more individuals or entities previously entered by the driver associated with mobile device **120** into the incoming telephonic event analysis application. The driver associated with mobile device **120** may be allowed to enter an unlimited or finite amount (e.g., five individuals or entities) of allowable individuals or entities into the allowable individual or entity list.

At step **516**, if the incoming telephonic event is determined to be associated with an allowable individual or entity, the incoming telephonic event analysis application may determine whether or not the mobile device **120** was synced and/or paired with the hands-free device **116**. At step **518**, if the mobile device **120** was previously synced and/or paired with the hands-free device **116**, the incoming telephonic event analysis application may activate the hands-free device **116**, remove the soft block, and direct the incoming telephonic event on the mobile device **120** to hands-free device **116**. Alternatively, at step **520**, if the mobile device **120** was not previously synced and/or paired with the hands-free device **116**, the incoming telephonic event analysis application may remove the soft block and display the incoming telephonic event on the mobile device **120**. Conversely, if the incoming telephonic event is determined not to be associated with an allowable individual or entity, the incoming telephonic event analysis application may maintain the soft block and prevent the incoming telephonic event from being displayed on mobile device **120** regardless of whether or not the mobile device **120** was synced and/or paired with hands-free device **116** and proceed to step **512**.

At step **512**, the incoming telephonic event analysis application may analyze telephonic event data corresponding to the incoming telephonic in comparison with previously received telephonic event data to determine whether the incoming telephonic event is a third telephonic event associated with a particular individual or entity. Such analyses are described in further detail in regard to FIGS. **6A** and **6B**.

FIG. **6A** is a flow diagram illustrating an example of an incoming telephonic event data analysis method according to one or more aspects of the disclosure. At step **602A**, the incoming telephonic event analysis application may extract telephonic event data from the incoming telephonic event. Such data may include a name, telephone number, user name (e.g., handle), event type (e.g., telephone call, text message, email, application notification, etc.), and time of receipt.

At step **604A**, the incoming telephonic event analysis application may determine whether a first immediately preceding telephonic event was received. Data corresponding to previously received telephonic events may be previously stored in memory on mobile device **120** by the incoming telephonic event analysis application. In one instance, the stored previously received telephonic event data may correspond to an active operative period of vehicle **110**, wherein the active operative is initiated by a positive ignition event (e.g., vehicle **110** is turned on). In such instances, mobile device **120** may be configured to receive indication of a positive ignition event from sensors **111**, telematics device **113**, and/or on-board computer **115** and the incoming telephonic event analysis application may be configured to create a data ledger within memory of mobile device **120** corresponding to the active operative period of vehicle **110**. As will be discussed in further detail below, the data ledger may be cleared and/or reset responsive to the conclusion of the active operative period through receipt of an indication

of a negative ignition event (e.g., vehicle **110** is turned off). In doing so, memory of mobile device **120** may be actively conserved as related to the incoming telephonic event application. Alternatively, the data ledger may be achieved responsive to the conclusion of the active operative period through receipt of an indication of a negative ignition event and may be accessible at a later time.

In any event, if no data corresponding to a first immediately preceding telephonic event exists in memory (e.g., no previous telephonic event data exists in memory), the incoming telephonic event analysis application may determine that the incoming telephonic event is a first incoming telephonic event. If the incoming telephonic event is determined to be a first incoming telephonic event, incoming telephonic event analysis application may maintain the soft block and prevent the first incoming telephonic event from being displayed on the mobile device **120** at step **514**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the first incoming telephonic event that the user is driving and currently unavailable to respond to the telephonic event. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the first telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if one or more previously stored telephonic event data entries exists in memory in the data ledger, the determination of the first immediately preceding telephonic event may be made. In instances in which a plurality of previously stored telephonic event data entries exists in the data ledger, the determination of the first immediately preceding telephonic event may be made based on a time difference between the time of receipt of the incoming telephonic event and previously stored receipt times corresponding to previously received telephonic events. The difference with the smallest magnitude may be determined to be the first immediately preceding telephonic event. Alternatively, in instances in which data corresponding to only one previously received telephonic event is stored in memory in the data ledger, a comparison of receipt times may be foregone and the one previously received telephonic event may be determined to be the first immediately preceding telephonic event.

At step **606A**, after determining that a first immediately preceding telephonic event was received, the incoming telephonic event analysis application may compare the extracted name, telephone number, and user name (e.g., handle) from the incoming telephonic event to that of the first immediately preceding telephonic event to determine whether or not the incoming telephonic event and the first immediately preceding telephonic event share a common sending individual or entity. If it is determined that the incoming telephonic event and the first immediately preceding telephonic event do not share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is a first incoming telephonic event associated with a particular sending individual or entity. After such a determination, the incoming telephonic event analysis application may maintain the soft block and prevent the first incoming telephonic event from being displayed on the mobile device **120** at step **514**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the first incoming telephonic event that the user is driving and currently unavailable to respond to the telephonic event. Furthermore, the incoming

telephonic event analysis application may store the telephonic event data associated with the first telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if it is determined that the incoming telephonic event and the first immediately preceding telephonic event share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is at least a second incoming telephonic event associated with the particular sending individual or entity and may proceed to step **608A**.

At step **608A**, the incoming telephonic event analysis application may determine whether a second immediately preceding telephonic event was received. In doing so, the incoming telephonic event analysis application may review the data ledger in memory to determine if a second immediately preceding telephonic event was received. If no data corresponding to a second immediately preceding telephonic event exists in memory (e.g., only data corresponding to the first immediately preceding telephonic event exists in memory), the incoming telephonic event analysis application may determine that the incoming telephonic event is a second incoming telephonic event associated with the particular individual or entity and prevent the second incoming telephonic event from being displayed on the mobile device **120** at step **514**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the second incoming telephonic event alerting the individual or entity that the user is still driving and unavailable to respond to the telephonic event, but if that it is an emergency situation, the individual or entity should provide a third telephonic event to be connected to the mobile device of the user. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the second telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if two or more previously stored telephonic event data entries exists in memory in the data ledger, the determination of the second immediately preceding telephonic event may be made. In instances in which a plurality of previously stored telephonic event data entries exists in the data ledger, the determination of the second immediately preceding telephonic event may be made based on a time difference between the time of receipt of the incoming telephonic event and previously stored receipt times corresponding to previously received telephonic events. The difference with the second smallest magnitude may be determined to be the second immediately preceding telephonic event.

At step **610A**, after determining that a second immediately preceding telephonic event was received, the incoming telephonic event analysis application may compare the extracted name, telephone number, and user name (e.g., handle) from the incoming telephonic event to that of the second immediately preceding telephonic event to determine whether or not the incoming telephonic event and the second immediately preceding telephonic event share a common sending individual or entity. If it is determined that the incoming telephonic event and the second immediately preceding telephonic event do not share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is a second incoming telephonic event associated with the particular individual or entity and prevent the second incoming telephonic event from being displayed on the

mobile device **120** at step **514**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the second incoming telephonic event alerting the individual or entity that the user is still driving and unavailable to respond to the telephonic event, but if that it is an emergency situation, the individual or entity should provide a third telephonic event to be connected to the mobile device of the user. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the second telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if it is determined that the incoming telephonic event and the second immediately preceding telephonic event share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is at least a third incoming telephonic event associated with the particular sending individual or entity and, at step **516**, the incoming telephonic event analysis application may determine whether or not the mobile device **120** was synced and/or paired with the hands-free device **116**. At step **518**, if the mobile device **120** was previously synced and/or paired with the hands-free device **116**, the incoming telephonic event analysis application may activate the hands-free device **116**, remove the soft block, and direct the incoming telephonic event on the mobile device **120** to hands-free device **116**. Alternatively, at step **520**, if the mobile device **120** was not previously synced and/or paired with the hands-free device **116**, the incoming telephonic event analysis application may remove the soft block and display the incoming telephonic event on the mobile device **120**.

FIG. **6B** is a flow diagram illustrating another example of an incoming telephonic event data analysis method according to one or more aspects of the disclosure. At step **602B**, the incoming telephonic event analysis application may extract telephonic event data from the incoming telephonic event. Such data may include a name, telephone number, user name (e.g., handle), event type (e.g., telephone call, text message, email, application notification, etc.), and time of receipt.

At step **604B**, the incoming telephonic event analysis application may determine whether previously stored telephonic event data is stored in memory in the data ledger associated with the active operative period of vehicle **110**. Data corresponding to previously received telephonic events may be previously stored in memory on mobile device **120** by the incoming telephonic event analysis application. In one instance, the stored previously received telephonic event data may correspond to an active operative period of vehicle **110**, wherein the active operative is initiated by a positive ignition event (e.g., vehicle **110** is turned on). In such instances, mobile device **120** may be configured to receive indication of a positive ignition event from sensors **111**, telematics device **113**, and/or on-board computer **115** and the incoming telephonic event analysis application may be configured to create a data ledger within memory of mobile device **120** corresponding to the active operative period of vehicle **110**. In one instance, the data ledger may be cleared and/or reset responsive to the conclusion of the active operative period through receipt of an indication of a negative ignition event (e.g., vehicle **110** is turned off). In doing so, memory of mobile device **120** may be actively conserved as related to the incoming telephonic event application. Alternatively, the data ledger may be achieved responsive to

the conclusion of the active operative period through receipt of an indication of a negative ignition event and may be accessible at a later time.

However, in some cases, the active operating state of the vehicle **110** may be determined by a velocity, acceleration, and/or displacement magnitude and mobile device **120** may be configured to receive indication of such a magnitude from sensors **111**, telematics device **113**, and/or on-board computer **115** and the incoming telephonic event analysis application may be configured to create a data ledger within memory of mobile device **120** corresponding to the active operative period of vehicle **110**. Similarly, the termination of an active operating state of the vehicle **110** may be determined by a prolonged period (e.g., 1 min, 5 min, 10 min, etc.) without a velocity, acceleration, and/or displacement magnitude.

In some instances, the start of an active operating state of the vehicle **110** may be determined by a negative parking brake indication (e.g., parking brake disengaged), a shift into reverse or drive after a prolonged period (e.g., 5 min, 10 min, 30 min, etc.) of being in park, a positive headlight activation, brake pedal activation, gas pedal activation, and/or a state change in one or more vehicle systems requiring user input. Conversely, the end of an active operating state of vehicle **110** may be determined by a positive parking brake indication (e.g., parking brake engagement), a shift into park, headlight deactivation, absence of brake pedal usage, gas pedal usage, and/or state change in one or more vehicle systems requiring user input. Additionally, such state changes may be time constrained. Similar to the state changes noted above, mobile device **120** may be configured to receive indication of such state changes from sensors **111**, telematics device **113**, and/or on-board computer **115**.

If no data corresponding to a previously received telephonic event exists in memory, the incoming telephonic event analysis application may determine that the incoming telephonic event is a first incoming telephonic event. If the incoming telephonic event is determined to be a first incoming telephonic event, incoming telephonic event analysis application may maintain the soft block and prevent the first incoming telephonic event from being displayed on the mobile device **120** at step **514**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the first incoming telephonic event that the user is driving and currently unavailable to respond to the telephonic event. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the first telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if data corresponding to one or more previously received telephonic events is stored in memory in the data ledger associated with the active operative period of vehicle **110**, the incoming telephonic event analysis application may consolidate the previously stored telephonic event data based on a retroactive time window, wherein the previously stored telephonic event data comprised within the consolidated window may be marked for further comparison with the telephonic event data of the incoming telephonic event. The retroactive time window may be a predetermined period of time (e.g., 1 minute, 5 minutes, 30 minutes, etc.) extending into the past from the time at which the incoming telephonic event was received at mobile device **120**. For example, if previously stored telephonic event data exists in memory in the data ledger and an incoming telephonic event is received at 3:00 PM EST, the retroactive time window may extend into the past until 2:55 PM EST. Each telephonic

event received between 2:55 PM EST and 3:00 PM EST may be isolated by the incoming telephonic event analysis application from the remainder of the previously stored telephonic event data received outside of the retroactive time window and marked for further comparison.

At step **606B**, after isolating previously stored telephonic event data within the retroactive time window, the incoming telephonic event analysis application may compare the extracted name, telephone number, and user name (e.g., handle) from the incoming telephonic event to that of each of the previously stored telephonic event data entries in the consolidated time window to determine whether or not the incoming telephonic event and any of the previously stored telephonic event data entries share a common sending individual or entity. If it is determined that the incoming telephonic event and any of the previously stored telephonic event data entries do not share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is a first incoming telephonic event associated with a particular sending individual or entity. After such a determination, the incoming telephonic event analysis application may maintain the soft block and prevent the first incoming telephonic event from being displayed on the mobile device **120** at step **514**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the first incoming telephonic event that the user is driving and currently unavailable to respond to the telephonic event. Furthermore, the incoming telephonic event analysis application may store the telephonic event data associated with the first telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if it is determined that the incoming telephonic event and at least a first entry of the previously stored telephonic event data entries in the retroactive window share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is at least a second incoming telephonic event associated with the particular individual or entity and may proceed to step **608B**.

At step **608B**, the incoming telephonic event analysis application may compare the extracted name, telephone number, and user name (e.g., handle) from the incoming telephonic event to that of each of the previously stored telephonic event data entries in the consolidated time window (besides the first entry sharing the common individual or entity determined in step **606B**) to determine whether or not the incoming telephonic event and a second entry of the previously stored telephonic event data entries share a common sending individual or entity. If it is determined that the incoming telephonic event and none of the remainder of the previously stored telephonic event data entries share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is a second incoming telephonic event associated with a particular sending individual or entity. After such a determination, the incoming telephonic event analysis application may maintain the soft block and prevent the second incoming telephonic event from being displayed on the mobile device **120** at step **514**. Additionally, the incoming telephonic event analysis application may provide a notification to the individual or entity associated with the second incoming telephonic event that the user is driving and currently unavailable to respond to the telephonic event. Furthermore, the incoming telephonic event analysis application may store the telephonic event data

associated with the second telephonic event in memory in the data ledger associated with the active operative period of vehicle **110**.

Conversely, if it is determined that the incoming telephonic event and at least a second entry of the previously stored telephonic event data entries in the retroactive window share a common sending individual or entity, the incoming telephonic event analysis application may determine that the incoming telephonic event is at least a third incoming telephonic event associated with the particular sending individual or entity and, at step **516**, the incoming telephonic event analysis application may determine whether or not the mobile device **120** was synced and/or paired with the hands-free device **116**. At step **518**, if the mobile device **120** was previously synced and/or paired with the hands-free device **116**, the incoming telephonic event analysis application may activate the hands-free device **116**, remove the soft block, and direct the incoming telephonic event on the mobile device **120** to hands-free device **116**. Alternatively, at step **520**, if the mobile device **120** was not previously synced and/or paired with the hands-free device **116**, the incoming telephonic event analysis application may remove the soft block and display the incoming telephonic event on the mobile device **120**.

After the active operative period of vehicle **110** has been terminated and an indication of such has been received at mobile device **120**, the incoming telephonic event analysis application may display a rollup on the mobile device **120** of the driver comprising each of the incoming telephonic events blocked from being displayed on mobile device **120** during driving. The rollup may include each of the data entries stored in the data ledger in memory. As such, each of the telephonic events received during operation of vehicle **110**, the type of each of the telephonic events, the individual or entity associated with the each of the telephonic events, an indication of availability of each of the individuals or entities associated with each of the telephonic events, and the time of receipt of each of the telephonic events. In some instances, the driver may be able to select each of the telephonic events comprised in the rollup to respond to the telephonic event in the manner corresponding to the event type (e.g., telephone call, email, text message, application specific interface, etc.). Alternatively, the driver may be able to select from the totality of telephonic event types in responding to the received telephonic event.

In some instances, the incoming telephonic event analysis application may be configured to cleared and/or reset the data ledger responsive to the conclusion of the active operative period through receipt of a state change event from sensors **111**, telematics device **113**, and/or on-board computer **115**. In doing so, memory of mobile device **120** may be actively conserved as related to the incoming telephonic event application. Alternatively, the data ledger may be achieved responsive to the conclusion of the active operative period through receipt of an indication of a negative ignition event and may be accessible at a later time.

In examples in which the analysis of the incoming telephonic event is performed by on-board computer **115** and/or incoming telephonic event analysis system **140**, mobile device **120** may transmit incoming telephonic event data to on-board computer **115** and/or incoming telephonic event analysis system **140**. Such data may include the individual or entity associated with incoming telephonic event, time of receipt of the incoming telephonic event, and the type of the incoming telephonic event. Upon receipt of the incoming telephonic event data, on-board computer **115** and incoming telephonic event analysis system **140**, alone or

in combination, may be able to perform the determination features outlined above in steps **508**, **510**, and **512** (e.g., FIGS. **6A** and **6B**). Responsive to performing the respective determination steps, on-board computer **115** and incoming telephonic event analysis system **140**, either alone or in combination, may be configured to transmit the results of such steps to mobile device **120**.

FIG. **7** is a flow diagram illustrating another example of an incoming telephonic event analysis method based on the presence of a hands-free device according to one or more aspects of the disclosure. As will be described below, the processes of the incoming telephonic event analysis method may be performed by any one, or combination of, mobile device **120**, on-board computer **115**, and incoming telephonic event analysis system **140**.

At step **702**, the mobile device **120** may receive an incoming telephonic event analysis application activation command from on-board computer **115**, which may send the activation command in response to receiving a positive vehicle ignition event (e.g., turning vehicle on) and/or any one, or combination of, state change events described above. Responsive to receiving the incoming telephonic event analysis application activation command, mobile device **120** may activate the incoming telephonic event analysis application.

At step **704**, after the incoming telephonic event analysis application has been activated on mobile device **120** responsive to the command sent from vehicle on-board computer **115**, the incoming telephonic event analysis application may cause the mobile device **120** to scan for the presence of a hands-free device **116** in the proximity of mobile device **120**. In the event that a hands-free device **116** is registered during the scan conducted by mobile device **120**, the incoming telephonic event analysis application may instruct the mobile device **120** to sync and/or pair with the hands-free device **116**. Alternatively, if a hands-free device **116** is not registered during the scan, no instruction to sync and/or pair may be given to mobile device

At step **706**, the mobile device **120** associated with the driver of vehicle **110** may receive an incoming telephonic event during the operation of vehicle **110**. The incoming telephonic event may be of any of a plurality of telephonic event types. Upon receipt of the incoming telephonic event, an incoming telephonic event analysis application operating on mobile device **120** may apply a soft block to the incoming telephonic event preventing the event from being displayed on the mobile device **120**.

At step **708**, the mobile device **120** may transmit a data transmittal control command to telematics device **113**. The data transmittal control command may be configured to activate telematics device **113** and may further include instructions for the telematics device **120** to transmit specific data elements of the vehicle operational data and environmental conditions data to incoming telephonic event analysis system **140** corresponding to the time of receipt of the incoming telephonic event. The specific data elements within the broader categories of vehicle operational data and environmental conditions data may coincide with data elements required by driver score/risk map server **170** to perform the calculations of the driver risk score and road risk score. Alternatively, the data transmittal control command may include instructions for telematics device **113** to transmit the specific data elements to mobile device **120**. In such instances, the incoming telephonic event analysis application on mobile device **120** may be configured to perform the driver risk score and road risk score calculations described below in regards to driver score/risk map server **170**.

In response to receiving the specific data elements of the vehicle operational data and environmental conditions data from telematics device **113**, incoming telephonic event analysis system **140** may route the data to driver score/risk map server **170**. The driver score/risk map server **170** may use the data in conjunction with historical data stored in driver score/risk map database **174** and auxiliary environmental conditions data provided by third party data source server **160** to perform the driver risk score and road risk score calculations. After performing the calculations, driver score/risk map server **170** may transmit the calculated driver risk score and road risk score to mobile device **120**, which may be configured to receive the calculated driver risk score and road risk score at step **710**.

At step **712**, upon receiving the calculated driver risk score and road risk score from driver score/risk map server **170**, the incoming telephonic event analysis application on mobile device **120** may determine whether or not to remove or to maintain the soft block applied to the incoming telephonic event. In doing so, the incoming telephonic event analysis application may compare both the driver risk score and the road risk score to allowance thresholds respective to the driver risk score and the road risk score. At step **716**, if both of the driver score and the road risk score are below the respective allowance thresholds, the incoming telephonic event analysis application may then determine whether or not the mobile device **120** was synced and/or paired with the hands-free device **116**. At step **518**, if the mobile device **120** was previously synced and/or paired with the hands-free device **116**, the incoming telephonic event analysis application may activate the hands-free device **116**, remove the soft block, and direct the incoming telephonic event on the mobile device **120** to hands-free device **116**. Alternatively, at step **720**, if the mobile device **120** was not previously synced and/or paired with the hands-free device **116** because no hands-free device **116** was initially detected, the incoming telephonic event analysis application may remove the soft block and display the incoming telephonic event on the mobile device **120**. Conversely, at step **714**, if either of the driver risk score or the road risk score is above the respective allowance threshold, the incoming telephonic event analysis application may maintain the soft block and prevent the incoming telephonic event from being displayed on the mobile device **120** regardless of whether or not the mobile device **120** was synced and/or paired with hands-free device **116**.

In some instances, after driving has been completed and vehicle **110** is turned off, vehicle control computer **115** may deactivate the incoming telephonic event analysis application on mobile device **120**. By activating and deactivating the incoming telephonic event analysis application in response to a vehicle ignition event (e.g., turning vehicle on or off), the battery and processing power of mobile device **120** may be conserved by ensuring that the utilization of the incoming telephonic event analysis application coincides with periods of operation of vehicle **110**. Additionally, the usage of the vehicle ignition event to trigger the incoming telephonic event analysis application may restrict the operation of the application to periods of driving and prevent operation carry over between periods of driving and periods of non-driving.

In some instances, when the soft block is removed by the incoming telephonic event analysis application and the incoming telephonic event is displayed on mobile device **120**, the driver associated with mobile device **120** may be awarded points for not interacting with the mobile device **120** in response to the displayed telephonic event. Such

points may be used by the driver associated with mobile device **120** to incrementally increase the predetermined vehicle velocity threshold and/or add additional individuals or entities to the allowable individual or entity list. For example, for every incoming telephonic event displayed on mobile device **120** that is not interacted with by the driver of vehicle **110**, one point may be awarded to the driver. After 100 points have been awarded, the driver may be able to increase the velocity threshold by 0.1 mph. Alternatively, after 1000 points have been awarded, the driver may be able to add an additional individual or entity to the allowable individual or entity list. In some instances, the driver may receive electronic badges after surpassing certain point thresholds (e.g., 100 points, 500 points, etc.).

After operation of vehicle **110** has been terminated, the incoming telephonic event analysis application may provide the driver associated with mobile device **110** with a rollup comprising each of the incoming telephonic events blocked from being displayed on mobile device **120** during driving. The rollup may include each of the telephonic events received during operation of vehicle **110**, the type of each of the telephonic events, the individual or entity associated with the each of the telephonic events, an indication of availability of each of the individuals or entities associated with each of the telephonic events, and the time of receipt of each of the telephonic events. In some instances, the driver may be able to select each of the telephonic events comprised in the rollup to respond to the telephonic event in the manner corresponding to the event type (e.g., telephone call, email, text message, application specific interface, etc.). Alternatively, the driver may be able to select from the totality of telephonic event types in responding to the received telephonic event.

FIG. **8** illustrates a block diagram of a computing device **801** in an auto-reply and hands-free system **600** that may be used according to one or more illustrative embodiments of the disclosure. The computing device **801** may have a processor **803** for controlling overall operation of the computing device **801** and its associated components, including RAM **805**, ROM **807**, input/output module **809**, and memory unit **815**. The computing device **801**, along with one or more additional devices (e.g., terminals **841**, **851**) may correspond to any of multiple systems or devices, such as auto-reply and hands-free systems, configured as described herein for analyzing an incoming telephonic event in relation to a combination of vehicle operational data, user preferences, and hands-free device activation to determine if the incoming telephonic event is to be allowed to be received during vehicle operation.

Input/Output (I/O) module **809** may include a microphone, keypad, touch screen, and/or stylus through which a user of the computing device **801** may provide input, and may also include one or more of a speaker for providing audio input/output and a video display device for providing textual, audiovisual and/or graphical output. Software may be stored within memory unit **815** and/or other storage to provide instructions to processor **803** for enabling device **801** to perform various functions. For example, memory unit **815** may store software used by the device **801**, such as an operating system **817**, application programs **819**, and an associated internal database **821**. The memory unit **815** includes one or more of volatile and/or non-volatile computer memory to store computer-executable instructions, data, and/or other information. Processor **803** and its associated components may allow the computing device **801** to execute a series of computer-readable instructions to perform the methods described in FIGS. **2-7**.

The computing device **801** may operate in a networked environment **800** supporting connections to one or more remote computers, such as terminals/devices **841** and **851**. Computing device **801**, and related terminals/devices **841** and **851**, may include devices installed in vehicles, mobile devices that may travel within vehicles, or devices outside of vehicles that are configured to receive and process vehicle and other sensor data. Thus, the computing device **801** and terminals/devices **841** and **851** may each include personal computers (e.g., laptop, desktop, or tablet computers), servers (e.g., web servers, database servers), vehicle-based devices (e.g., on-board vehicle computers, short-range vehicle communication systems, sensors and telematics devices), or mobile communication devices (e.g., mobile phones, portable computing devices, and the like), and may include some or all of the elements described above with respect to the computing device **801**. The network connections depicted in FIG. **8** include a local area network (LAN) **825** and a wide area network (WAN) **829**, and a wireless telecommunications network **833**, but may also include other networks. When used in a LAN networking environment, the computing device **801** may be connected to the LAN **825** through a network interface or adapter **823**. When used in a WAN networking environment, the device **801** may include a modem **827** or other means for establishing communications over the WAN **829**, such as network **831** (e.g., the Internet). When used in a wireless telecommunications network **833**, the device **801** may include one or more transceivers, digital signal processors, and additional circuitry and software for communicating with wireless computing devices **841** (e.g., mobile phones, short-range vehicle communication systems, vehicle sensing and telematics devices) via one or more network devices **835** (e.g., base transceiver stations) in the wireless network **833**.

It will be appreciated that the network connections shown are illustrative and other means of establishing a communications link between the computers may be used. The existence of any of various network protocols such as TCP/IP, Ethernet, FTP, HTTP and the like, and of various wireless communication technologies such as GSM, CDMA, Wi-Fi, and WiMAX, is presumed, and the various computing devices and auto-reply and hands-free components described herein may be configured to communicate using any of these network protocols or technologies.

Additionally, one or more application programs **819** used by the computing device **801** may include computer executable instructions for receiving data and performing other related functions as described herein.

As will be appreciated by one of skill in the art, the various aspects described herein may be embodied as a method, a computer system, or a computer program product. Accordingly, those aspects may take the form of an entirely hardware embodiment, an entirely software embodiment or an embodiment combining software and hardware aspects. Furthermore, such aspects may take the form of a computer program product stored by one or more computer-readable storage media having computer-readable program code, or instructions, embodied in or on the storage media. Any suitable computer readable storage media may be utilized, including hard disks, CD-ROMs, optical storage devices, magnetic storage devices, and/or any combination thereof. In addition, various signals representing data or events as described herein may be transferred between a source and a destination in the form of electromagnetic waves traveling through signal-conducting media such as metal wires, optical fibers, and/or wireless transmission media (e.g., air and/or space).

Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

What is claimed is:

1. A method comprising:

receiving, at a mobile device associated with a driver of a vehicle and from an on-board computer of the vehicle, an incoming telephonic event analysis application activation command;
 activating an incoming telephonic event analysis application responsive to the incoming telephonic event analysis application activation command;
 pairing with a hands-free device;
 receiving an incoming telephonic event at the mobile device;
 based on the received incoming telephonic event, transmitting a data transmittal control command to a telematics device associated with the vehicle;
 receiving a calculated driver risk score and a calculated road risk score from an incoming telephonic event analysis system;
 based on the calculated driver risk score and the calculated road risk score, activating the hands-free device paired with the mobile device; and
 transmitting the incoming telephonic event to the activated hands-free device.

2. The method of claim **1**, further comprising:

receiving an incoming telephonic event analysis application deactivation command from the on-board computer of the vehicle; and
 deactivating the incoming telephonic event analysis application responsive to the incoming telephonic event analysis application deactivation command.

3. The method of claim **2**, wherein the incoming telephonic event analysis application activation command is associated with a positive vehicle ignition event of the vehicle.

4. The method of claim **2**, wherein the incoming telephonic event analysis application deactivation command is associated with a negative vehicle ignition event of the vehicle.

5. The method of claim **1**, further comprising:

allowing the driver to respond to the incoming telephonic event for a predetermined period of time; and
 providing the driver with countdown updates corresponding to a termination of the predetermined period of time.

6. The method of claim **1**, further comprising:

receiving an additional incoming telephonic event at the mobile device;
 preventing the additional incoming telephonic event from being displayed on the mobile device based on the calculated driver risk score and the calculated road risk score; and
 generating a rollup comprising data associated with the additional incoming telephonic event.

7. The method of claim **6**, wherein the rollup is generated prior to deactivating the incoming telephonic event analysis application.

8. An apparatus comprising:

a processor; and
 memory storing computer-readable instructions that, when executed by the processor, cause the apparatus to:

37

receive an incoming telephonic event analysis application activation command from an on-board computer of a vehicle associated with a driver;
 activate an incoming telephonic event analysis application responsive to the incoming telephonic event analysis application activation command;
 pair with a hands-free device;
 receive an incoming telephonic event;
 based on the received incoming telephonic event, transmit a data transmittal control command to a telematics device associated with the vehicle;
 receive a calculated driver risk score and a calculated road risk score from an incoming telephonic event analysis system;
 based on the calculated driver risk score and the calculated road risk score, activate the hands-free device; and
 transmit the incoming telephonic event to the activated hands-free device.

9. The apparatus of claim 8, wherein the memory stores further computer-readable instructions that, when executed by the processor, cause the apparatus to:

receive an incoming telephonic event analysis application deactivation command from the on-board computer of the vehicle; and
 deactivate the incoming telephonic event analysis application responsive to the incoming telephonic event analysis application deactivation command.

10. The apparatus of claim 9, wherein the incoming telephonic event analysis application activation command is associated with a positive vehicle ignition event of the vehicle.

11. The apparatus of claim 9, wherein the incoming telephonic event analysis application deactivation command is associated with a negative vehicle ignition event of the vehicle.

12. The apparatus of claim 8, wherein the memory stores further computer-readable instructions that, when executed by the processor, cause the apparatus to:

allow the driver to respond to the incoming telephonic event for a predetermined period of time; and
 provide the driver with countdown updates corresponding to a termination of the predetermined period of time.

13. The apparatus of claim 8, wherein the memory stores further computer-readable instructions that, when executed by the processor, cause the apparatus to:

receive an additional incoming telephonic event;
 prevent the additional incoming telephonic event from being displayed based on the calculated driver risk score and the calculated road risk score; and
 generate a rollup comprising data associated with the additional incoming telephonic event.

14. The apparatus of claim 13, wherein the rollup is generated prior to deactivating the incoming telephonic event analysis application.

15. One or more non-transitory computer-readable media storing instructions that, when executed by a computing device, cause the computing device to:

38

receive an incoming telephonic event analysis application activation command from an on-board computer of a vehicle, wherein the vehicle is associated with a driver;
 activate an incoming telephonic event analysis application responsive to the incoming telephonic event analysis application activation command;
 pair with a hands-free device;
 receive an incoming telephonic event;
 based on the received incoming telephonic event, transmit a data transmittal control command to a telematics device associated with the vehicle;
 receive a calculated driver risk score and a calculated road risk score from an incoming telephonic event analysis system;
 based on the calculated driver risk score and the calculated road risk score, activate the hands-free device;
 and
 transmit the incoming telephonic event to the activated hands-free device.

16. The one or more non-transitory computer-readable media of claim 15, storing further instructions that, when executed by the computing device, cause the computing device to:

receive an incoming telephonic event analysis application deactivation command from the on-board computer of the vehicle; and
 deactivate the incoming telephonic event analysis application responsive to the incoming telephonic event analysis application deactivation command from the on-board computer of the vehicle.

17. The one or more non-transitory computer-readable media of claim 16, wherein the incoming telephonic event analysis application activation command is associated with a positive vehicle ignition event of the vehicle, and wherein the incoming telephonic event analysis application deactivation command is associated with a negative vehicle ignition event of the vehicle.

18. The one or more non-transitory computer-readable media of claim 15, storing further instructions that, when executed by the computing device, cause the computing device to:

allow the driver to respond to the incoming telephonic event for a predetermined period of time; and
 provide the driver with countdown updates corresponding to a termination of the predetermined period of time.

19. The one or more non-transitory computer-readable media of claim 15, storing further instructions that, when executed by the computing device, cause the computing device to:

receive an additional incoming telephonic event;
 prevent the additional incoming telephonic event from being displayed based on the calculated driver risk score and the calculated road risk score; and
 generate a rollup comprising data associated with the additional incoming telephonic event.

20. The one or more non-transitory computer-readable media of claim 19, wherein the rollup is generated prior to deactivating the incoming telephonic event analysis application.

* * * * *