



US010288390B2

(12) **United States Patent**  
**Meeker et al.**

(10) **Patent No.:** **US 10,288,390 B2**  
(45) **Date of Patent:** **May 14, 2019**

(54) **CONCEALED AMALGAMATED EXPLOSIVE NEUTRALIZER AND METHOD OF MANUFACTURE**

(71) Applicant: **I P Creations Limited**, Surrey (GB)

(72) Inventors: **Daniel Hill Meeker**, Fort Worth, TX (US); **Benjamin John Green**, Surrey (GB)

(73) Assignee: **I P Creations Limited**, Surrey (GB)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/172,000**

(22) Filed: **Jun. 2, 2016**

(65) **Prior Publication Data**

US 2017/0081255 A1 Mar. 23, 2017

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 14/857,061, filed on Sep. 17, 2015, now Pat. No. 9,714,199.

(51) **Int. Cl.**  
*F41J 5/26* (2006.01)  
*F41J 9/16* (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... *F41J 9/165* (2013.01); *C06B 21/0091* (2013.01); *C06B 45/12* (2013.01); *F41J 1/01* (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC .. F42D 5/04; F42B 39/14; F42B 39/20; F42B 33/00; F42B 33/06; F42B 4/00;  
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,368,310 A \* 1/1945 Lecky ..... F42C 15/28  
102/205

3,327,628 A 6/1967 Loprest  
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101450881 6/2009  
CN 101838172 9/2010

(Continued)

OTHER PUBLICATIONS

Patel, et al., "In-Situ Landmine Neutralization by Chemical versus Thermal Initiation Deminer Preferences," U. S. Army Communications—Electronics Research, Development, and Engineering Center, 2006, 7 pages, Fort Belvoir, VA. <http://www.dtic.mil/dtic/tr/fulltext/u2/a458418.pdf>.

(Continued)


*Primary Examiner* — James S Bergin

(74) *Attorney, Agent, or Firm* — Schultz & Associates, P.C.

(57) **ABSTRACT**

A concealed amalgamated neutralizer covertly combines neutralizer material comprised of various combinations of inert materials such as calcium carbonate or silicates with common explosive material for the prevention of malicious use of the explosive material in improvised explosive devices. The concealed amalgamated neutralizer device may vary in shape, size, and color and is therefore adaptable to varying methods of containment typified by common pyrotechnic products. The neutralizer material mimics the explosive material of the pyrotechnic products without detection. Upon disassembly of a concealed amalgamated neutralizer device, the neutralizer material is mixed with and neutralizes the explosive material rendering the explosive material useless as a component for an improvised explosive device.

**11 Claims, 31 Drawing Sheets**



- (51) **Int. Cl.**  
*F41J 1/01* (2006.01)  
*F42B 33/00* (2006.01)  
*C06B 45/12* (2006.01)  
*F42B 4/30* (2006.01)  
*C06B 21/00* (2006.01)
- (52) **U.S. Cl.**  
 CPC *F41J 5/26* (2013.01); *F42B 4/30* (2013.01);  
*F42B 33/001* (2013.01)
- (58) **Field of Classification Search**  
 CPC ..... *F42B 4/02*; *F42B 4/30*; *F42B 5/16*; *F42B 33/001*; *C06B 21/0091*; *C06B 45/12*; *C06B 29/04*; *F41J 5/24*; *F41J 5/26*; *F41J 1/01*; *F41J 9/16*; *F41J 9/165*; *A62D 3/30*; *A62D 3/35*; *A62D 3/37*; *A62D 3/38*; *A62D 2101/06*  
 USPC ..... 102/335, 402, 426, 481, 293; 86/50; 149/14, 108.8, 124; 89/1.13  
 See application file for complete search history.
- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- |               |         |               |       |              |         |
|---------------|---------|---------------|-------|--------------|---------|
| 3,421,441 A * | 1/1969  | Mardarello    | ..... | F42C 1/10    | 102/204 |
| 3,667,387 A * | 6/1972  | Picard        | ..... | F42B 23/00   | 102/426 |
| 3,738,276 A   | 6/1973  | Picard et al. |       |              |         |
| 3,750,527 A * | 8/1973  | Heinemann     | ..... | F42C 9/08    | 102/401 |
| 3,774,541 A * | 11/1973 | Bratton       | ..... | C06C 5/06    | 102/221 |
| 4,270,435 A * | 6/1981  | Hurst         | ..... | C06B 21/0091 | 149/33  |
| 4,372,210 A * | 2/1983  | Shaffer       | ..... | C06C 7/00    | 102/204 |
| 4,404,911 A * | 9/1983  | Bell          | ..... | F42C 15/38   | 102/200 |
| 4,426,932 A * | 1/1984  | Bell          | ..... | F42C 15/38   | 102/200 |
| 5,574,203 A   | 11/1996 | Noel et al.   |       |              |         |
- 5,665,276 A 11/1997 Kirby et al.  
 6,405,626 B1 6/2002 Bureaux et al.  
 7,299,735 B2 11/2007 Alford  
 7,690,287 B2 4/2010 Maegerlein et al.  
 7,927,437 B2 4/2011 Gangopadhyay et al.  
 8,273,197 B2 9/2012 Rostlund  
 8,308,879 B2 11/2012 Runemard et al.  
 8,505,427 B2 8/2013 Wilson et al.  
 8,585,841 B2 \* 11/2013 Lubbe ..... C06B 21/005  
 149/108.2  
 8,671,841 B2 3/2014 Raquin et al.  
 8,850,984 B2 \* 10/2014 Smylie ..... A62D 3/02  
 102/301  
 9,714,199 B2 \* 7/2017 Meeker ..... C06B 45/12  
 2002/0117071 A1 \* 8/2002 Kaliszewski ..... C06B 33/04  
 102/335  
 2005/0109230 A1 5/2005 Falquette  
 2006/0124019 A1 6/2006 Coughlin et al.  
 2010/0275802 A1 \* 11/2010 Green ..... C06B 23/004  
 102/335  
 2011/0124945 A1 5/2011 Smylie et al.  
 2014/0083402 A1 3/2014 Fridman et al.  
 2014/0170300 A1 \* 6/2014 Green ..... F41J 5/14  
 427/8  
 2017/0081254 A1 3/2017 Meeker et al.  
 2017/0081255 A1 3/2017 Meeker et al.  
 2017/0292817 A1 \* 10/2017 Hartigan ..... F41J 5/24
- FOREIGN PATENT DOCUMENTS
- |    |                    |         |                 |
|----|--------------------|---------|-----------------|
| CN | 102838434          | 12/2012 |                 |
| FR | 2777648            | 11/2001 |                 |
| GB | 2227816            | 8/1990  |                 |
| JP | 2005273971         | 10/2005 |                 |
| WO | WO-2017105571 A2 * | 6/2017  | ..... F41J 5/26 |
| WO | WO-2017105571 A3 * | 10/2017 | ..... F41J 5/26 |
- OTHER PUBLICATIONS
- U.S. Chemical Safety and Hazard Investigation Board, "Investigation Report: Donaldson Enterprises, Inc. Fireworks Disposal Explosion and Fire," Report No. 2011-06-I-HI, Jan. 2013, pp. 1-91. [http://www.csb.gov/assets/1/19/DEI\\_Final\\_01172013.pdf](http://www.csb.gov/assets/1/19/DEI_Final_01172013.pdf).
- \* cited by examiner

PORTION 100 OF PYROTECHNIC DEVICE




FIG. 1A




FIG. 1B






FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B






FIG. 4C



**FIG. 5**  
METHOD USING  
SEPARATION  
BARRIER



FIG. 6  
METHOD  
USING  
IMPLANTED  
SPHERE






FIG. 7

METHOD USING  
COVERED SPHERE




FIG. 8A




FIG. 8B






FIG. 9

METHOD USING  
SUBSTRATE




FIG. 10




FIG. 11

METHOD FOR  
AMMUNITION





FIG. 12



FIG. 13  
METHOD  
FOR  
ROMAN  
CANDLE







FIG. 14

FIG. 15  
METHOD  
FOR  
ROLLING  
SOLIDIFIED  
MATERIAL







FIG. 16



FIG. 17  
METHOD  
FOR  
ROLLING  
SLURRIES  
APPLIED TO  
PAPER







FIG. 18



**FIG. 19**  
METHOD USING  
SHELL CASE





FIG. 20



FIG. 21A  
METHOD FOR  
PYROTECHNIC  
PIGEON






FIG. 21B




FIG. 21C




FIG. 21D




FIG. 21E






FIG. 21F




FIG. 21G




FIG. 21H




FIG. 21I

**CONCEALED AMALGAMATED EXPLOSIVE  
NEUTRALIZER AND METHOD OF  
MANUFACTURE**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a continuation-in-part of U.S. patent application Ser. No. 14/857,061 filed Sep. 17, 2015, which is hereby incorporated by reference herein.

FIELD OF THE DISCLOSURE

The present disclosure relates to neutralization of explosive materials contained in explosives and pyrotechnics. In particular, the disclosure relates to devices and methods for rendering pyrotechnics and ammunition inert or less effective.

BACKGROUND

The current worldwide political climate has produced many terrorist and anti-establishment factions that are motivated to create explosive devices from commonly available consumer products. For example, roadside or improvised explosive devices known as IEDs have been encountered in Afghanistan and in Iraq by the U.S. military and in Boston by local police.

A common practice used in constructing an IED involves the acquisition and disassembly of easily acquired consumer grade explosive products such as fireworks or small arms ammunition. The products are disassembled, yielding explosive material, e.g., black powder or other incendiary material. The explosive material is then combined with projectiles such as nails or broken glass and encased in a rigid container such as an aluminum cooking pot. The results are easily concealed and a deadly combination that is both inexpensive and effective.

Consumer grade explosive products contain various explosive materials. For example, gunpowder is a very common chemical explosive and comes in two basic forms, modern, smokeless gunpowder and traditional, black powder gunpowder. Black powder is a mixture of sulfur, charcoal, and potassium nitrate (saltpeter). The sulfur and charcoal act as fuels, and the saltpeter is an oxidizer. The standard composition for gunpowder is about 75% potassium nitrate, about 15% charcoal, and about 10% sulfur (proportions by weight). The ratios can be altered somewhat depending on the purpose of the powder. For instance, power grades of gunpowder, unsuitable for use in firearms but adequate for blasting rock in quarrying operations, have proportions of about 70% nitrate, about 14% charcoal, and about 16% sulfur. Some blasting powder may be made with cheaper sodium nitrate substituted for potassium nitrate and proportions may be as low as about 40% nitrate, about 30% charcoal, and about 30% sulfur.

Most pyrotechnic compositions and explosive materials can be neutralized when mixed with an appropriate combination of inert materials, slowing the burn rate of the explosive material to a non-explosive level that effectively neutralizes the explosive material and renders the explosive material useless for an improvised explosive device.

The prior art addresses the neutralization of explosive devices. However, none of the prior art devices or methods is completely satisfactory in neutralizing explosive materials in consumer products.

For example, U.S. Pat. No. 7,690,287 to Maegerlein, et al. provides a neutralizing assembly for inhibiting operation of an explosive device. The neutralizing assembly will interrupt the function of the explosive device only when the explosive device is misused. The neutralizing assembly includes an interior chamber with a rupturable barrier containing disabling material. The rupturable barrier separates the disabling material from the explosive material. Upon misuse of the device, the rupturable barrier breaks and the disabling material is released from the interior chamber to disable the explosive material.

U.S. Pat. No. 3,738,276 to Picard, et al. discloses a halocarbon gel for stabilizing an explosive material during transport. In use, flexible bags are prepared which contain the explosive material mixed with a desensitizing substance. The bags are placed in a protective gel. The gel prevents the desensitizing substance from evaporating through the flexible bags. When the transport is complete, the bags are removed from the gel. Once the bags are removed from the gel, the desensitizing substance evaporates, thus "arming" the explosive material.

U.S. Patent Publication No. 2011/0124945 to Smylie, et al. discloses a cartridge that is adapted to achieve deactivation of an explosive composition. In Smylie, the explosive composition and the chemical deactivating agent are held in separate chambers of the cartridge separated by a wall. Upon activation, the wall is breached and the deactivating agent and the explosive composition are allowed to mix, thereby rendering the explosive composition inert.

It is, therefore, an object of this disclosure to provide a design for and method of manufacture of products which include an undetectable neutralizing agent that automatically and effectively neutralizes an explosive material upon disassembly.

SUMMARY OF THE DISCLOSURE

A concealed amalgamated neutralizer (CAN) is disclosed for the prevention of malicious conversion of consumer fireworks, ammunition, and other pyrotechnic products into dangerous explosive devices, such as an IED.

In a preferred embodiment, a method of manufacture is provided whereby neutralizer material is undetectably situated adjacent to explosive material. The neutralizer material is chosen from various combinations of inert materials such as calcium carbonate, silica, or other inert materials combined with complimentary inert bonding and pigmentation chemicals. The neutralizer material is chosen and modified to mimic the physical characteristics (grain size, density, color) of the explosive material so that when placed side by side with the explosive material, the two components are practically indistinguishable and inseparable.

In one embodiment, the neutralizer material may be a combination of pigmented inert granular constituents. In another embodiment, the neutralizer material may be a liquid or viscous slurry in combination with a source binder and capable of drying into a compact solid.

In another embodiment, a cylindrical design is provided, which positions the explosive material adjacent the neutralizer material along a common central axis. The physical position and/or ratio of the neutralizer material relative to the explosive material can vary to change the extent of the neutralization.

In one embodiment, a temporary build container is provided in the form of a "tube within a tube." A dry granular explosive material is introduced into the interstitial space between the tubes but excluded from the inner tube. A dry



granular neutralizer material of similar color, density, size and texture as the explosive material is then introduced in the inner tube. The inner tube is then removed, allowing the explosive material to contact, but not mix with, the neutralizer material at a boundary interface. The resulting solid cylindrical shape is then packed and sealed, preserving the respective positions of the two components and the boundary interface.

In another embodiment, a spherically shaped device is provided. The neutralizer materials and explosive materials may each be hemispherical and placed "side-by-side." Temporary physical barriers may be used to separate the components, which are removed during manufacture to create a final product.

In another embodiment of the invention using wet materials, a "layered" product is provided fixed to a substrate.

In each case, the neutralizer material is placed in direct physical contact with the explosive material. The neutralizer material is physically indiscernible from the explosive material, and so the boundary interface between the two is very difficult or impossible to distinguish. Upon disassembly of the product, the neutralizer material is physically mixed with the explosive material, resulting in a combined material that is inert and useless as an explosive.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The disclosed embodiments will be described with reference to the accompanying drawings.

FIG. 1A is a schematic diagram of a portion of a pyrotechnic device in accordance with a preferred embodiment of this disclosure.

FIG. 1B is a schematic diagram of a portion of a pyrotechnic device in accordance with a preferred embodiment of this disclosure.

FIG. 2A is an isometric view of a tube within a tube build container.

FIG. 2B is an isometric view of a preferred embodiment in cylindrical form.

FIG. 3A is an isometric view of a cylindrical layered build container.

FIG. 3B is an isometric view of a preferred embodiment in layered form.

FIG. 4A is a section plan view of spherical side by side build container.

FIG. 4B is a section plan view of a preferred embodiment in spherical form.

FIG. 4C is a section plan view of a spherical build container with a preferred embodiment in spherical form.

FIG. 5 is a flow chart of steps required with assembly of a preferred embodiment of this disclosure.

FIG. 6 is a flow chart of steps to build a spherical pyrotechnic device in accordance with a preferred embodiment of this disclosure.

FIG. 7 is a flow chart of steps to build a spherical pyrotechnic device in accordance with a preferred embodiment of this disclosure.

FIG. 8A is a section plan view of an alternate embodiment resulting from liquid materials.

FIG. 8B is a section plan view of an alternate embodiment resulting from liquid materials as it is being made.

FIG. 9 is a flow chart of steps required with assembly of a preferred embodiment of this disclosure.

FIG. 10 is a section plan view of an article of manufacture including a preferred embodiment of this disclosure.

FIG. 11 is a flow chart of steps for assembly of an article of manufacture including a preferred embodiment of this disclosure.

FIG. 12 is a section plan view of a Roman candle in accordance with a preferred embodiment of this disclosure.

FIG. 13 is a flow chart of steps to build a Roman candle in accordance with a preferred embodiment of this disclosure.

FIG. 14 is an isometric view of a pyrotechnic assembly in accordance with a preferred embodiment of this disclosure.

FIG. 15 is a flow chart of steps to build a pyrotechnic assembly in accordance with a preferred embodiment of this disclosure.

FIG. 16 is an isometric view of a pyrotechnic assembly in accordance with a preferred embodiment of this disclosure.

FIG. 17 is a flow chart of steps to roll a pyrotechnic device in accordance with a preferred embodiment of this disclosure.

FIG. 18 is a detail view of a pyrotechnic device in accordance with a preferred embodiment of this disclosure.

FIG. 19 is a flow chart of steps to build a device using a shell case in accordance with a preferred embodiment of this disclosure.

FIG. 20 is a cross section view of a pyrotechnic pigeon in accordance with a preferred embodiment of this disclosure.

FIG. 21A is a flow chart of steps to build a pyrotechnic pigeon in accordance with a preferred embodiment of this disclosure.

FIGS. 21B to 21I are cross section views of a pyrotechnic pigeon as it is being built in accordance with a preferred embodiment of this disclosure.

#### DETAILED DESCRIPTION

Referring to FIG. 1A, portion 100 of a pyrotechnic or explosive device is shown that includes concealed amalgamated neutralizer 104 to prevent the use of explosive composition 114 in other devices. Portion 100 comprises housing 102, which acts to enclose and/or support concealed amalgamated neutralizer 104 and explosive composition 114. Concealed amalgamated neutralizer 104 and explosive composition 114 are positioned with or adjacent to each other. Interface 132 is an indiscernible boundary interface between concealed amalgamated neutralizer 104 and explosive composition 114 and is where concealed amalgamated neutralizer 104 touches explosive composition 114. Example pyrotechnic devices that comprise portion 100 include ammunition (such as shotgun shell 1000 of FIG. 10), fireworks (such as Roman candle 1200 of FIG. 12), and other explosive devices (such as a training target comprising the devices of FIGS. 8A, 8B and 18 and percussion caps).

Concealed amalgamated neutralizer 104 is a composition having a color and grain size that is indiscernible from the color and grain size of explosive composition 114. When mixed sufficiently with explosive composition 114, explosive power of the resulting mixture is reduced as compared to the explosive power of explosive composition 114 so as to prevent the use of explosive composition 114 outside of housing 102. Concealed amalgamated neutralizer 104 comprises non-inert material 106, inert material 108, and binding agent 112. Concealed amalgamated neutralizer 104 may be formed from a slurry, such as neutralizer slurry 124 of FIG. 1B.

In alternative embodiments, concealed amalgamated neutralizer 104 is formed without being processed from a neutralizer slurry. As an example, concealed amalgamated neutralizer 104 may be formed from a dry powder.



Materials used as non-inert material **106** include aluminum and may optionally comprise or form a pigment. Non-inert material **106** may include materials similar to fuel **116** of explosive composition **114**. Non-inert material **106** alters the fuel to oxidizer ratio of explosive composition **114** and/or provides different burn characteristics so as to reduce the explosiveness of explosive composition **114** when explosive composition **114** is combined with concealed amalgamated neutralizer **104** outside of housing **102**.

Materials used in inert material **108** include magnesium silicate and chalk and may optionally comprise or form a pigment. Inert material **108** does not burn or explode and acts to reduce the explosiveness of explosive composition **114** when explosive composition **114** is combined with concealed amalgamated neutralizer **104** outside of housing **102**.

Materials used as binding agent **112** of concealed amalgamated neutralizer **104** include cellulose and shellac and also include materials similar to materials used as binding agent **122** of explosive composition **114**. Binding agent **112** acts to bind the components of concealed amalgamated neutralizer **104** together and prevent the components of concealed amalgamated neutralizer **104** from mixing with explosive composition **114** while concealed amalgamated neutralizer **104** and explosive composition **114** are contained within the pyrotechnic device comprising portion **100**.

Referring to FIG. **1B**, a substrate **103** may also be used to support various embodiments where a liquid binder is necessary. Neutralizer slurry **124** and explosive slurry **128** are formed on top of substrate **103**. Interface **133** is an indiscernible boundary interface between neutralizer slurry **124** and explosive slurry **128**. Neutralizer slurry **124** and explosive slurry **128** are positioned with or adjacent to each other and touch each other at interface **133**.

Neutralizer slurry **124** is used to form concealed amalgamated neutralizer **104**. Neutralizer slurry **124** includes non-inert material **106**, inert material **108**, and binding agent **112**. Neutralizer slurry **124** also includes solvent **126**. Once positioned with respect to substrate **103**, neutralizer slurry **124** is allowed to solidify by withdrawal of solvent **126**, e.g., via vaporization, to form concealed amalgamated neutralizer **104** as a solid or to give concealed amalgamated neutralizer **104** a more solid-like form.

Materials used as solvent **126** include methyl ethyl ketone (MEK), cellulose thinners, isopropanol, alcohol, water, hydrogen peroxide, liquefied petroleum gas (LPG), and liquid nitrogen. Solvent **126** dissolves the other components of neutralizer slurry **124** and allows neutralizer slurry **124** to be processed in a more liquid-like fashion as compared to concealed amalgamated neutralizer **104**.

Explosive composition **114** is an explosive material, also known as a pyrotechnic composition, comprising one or more fuels **116**, oxidizers **118**, and additives **120**, and binding agents **122**. Fuels **116** and oxidizers **118** interact chemically to release energy, additives **120** add additional properties, and binding agents **122** bind explosive composition **114** together. Explosive composition **114** is formed from explosive slurry **128**.

In alternative embodiments, explosive composition **114** is formed without being processed from explosive slurry **128**. As an example, explosive composition **114** may be formed from a dry powder.

Materials used as fuel **116** include: metals, metal hydrides, metal carbides, metalloids, non-metallic inorganics, carbon based compounds, organic chemicals, and organic polymers and resins. Metal fuels include: aluminum, magnesium, magnalium, iron, steel, zirconium, titanium,

ferrotitanium, ferrosilicon, manganese, zinc, copper, brass, tungsten, zirconium-nickel alloy. Metal hydride fuels include: titanium(II) hydride, zirconium(II) hydride, aluminum hydride, and decaborane. Metal carbides used as fuels include zirconium carbide. Metalloids used as fuels include: silicon, boron, and antimony. Non-metallic inorganic fuels include: sulfur, red phosphorus, white phosphorus, calcium silicide, antimony trisulfide, arsenic sulfide (realgar), phosphorus trisulfide, calcium phosphide, and potassium thiocyanate. Carbon based fuels include: carbon, charcoal, graphite, carbon black, asphaltum, and wood flour. Organic chemical fuels include: sodium benzoate, sodium salicylate, gallic acid, potassium picrate, terephthalic acid, hexamine, anthracene, naphthalene, lactose, dextrose, sucrose, sorbitol, dextrin, stearin, stearic acid, and hexachloroethane. Organic polymer and resin fuels include: fluoropolymers (such as Teflon and Viton), hydroxyl-terminated polybutadiene (HTPB), carboxyl-terminated polybutadiene (CTPB), polybutadiene acrylonitrile (PBAN), polysulfide, polyurethane, polyisobutylene, nitrocellulose, polyethylene, polyvinyl chloride, polyvinylidene chloride, shellac, and accroides resin (red gum).

Materials used as oxidizers **118** include: perchlorates, chlorates, nitrates, permanganates, chromates, oxides and peroxides, sulfates, organic chemicals, and others. Perchlorate oxidizers include: potassium perchlorate, ammonium perchlorate, and nitronium perchlorate. Chlorate oxidizers include: potassium chlorate, barium chlorate, and sodium chlorate. Nitrates include: potassium nitrate, sodium nitrate, calcium nitrate, ammonium nitrate, barium nitrate, strontium nitrate, and cesium nitrate. Permanganate oxidizers include: potassium permanganate and ammonium permanganate. Chromate oxidizers include: barium chromate, lead chromate, and potassium dichromate. Oxide and peroxide oxidizers include: barium peroxide, strontium peroxide, lead tetroxide, lead dioxide, bismuth trioxide, iron(II) oxide, iron(III) oxide, manganese(IV) oxide, chromium(III) oxide, and tin(IV) oxide. Sulfate oxidizers include: barium sulfate, calcium sulfate, potassium sulfate, sodium sulfate, and strontium sulfate. Organic oxidizers include: guanidine nitrate, hexanitroethane, cyclotrimethylene trinitramine, and cyclotetramethylene tetranitramine. Other oxidizers include: sulfur, Teflon, and boron.

Materials used as additives **120** include materials that act as: coolants, flame suppressants, opacifiers, colorants, chlorine donors, catalysts, stabilizers, anticaking agents, plasticizers, curing and crosslinking agents, and bonding agents. Coolants include: diatomaceous earth, alumina, silica, magnesium oxide, carbonates including strontium carbonate, and oximide. Flame suppressants include: potassium nitrate and potassium sulfate. Opacifiers include carbon black and graphite. Colorants include: salts of metals (including barium, strontium, calcium, sodium, and copper), copper metal, and copper acetoarsenite with potassium perchlorate. Chlorine donors include: polyvinyl chloride, polyvinylidene chloride, vinylidene chloride, chlorinated paraffins, chlorinated rubber, hexachloroethane, hexachlorobenzene, and other organochlorides and inorganic chlorides (e.g., ammonium chloride, mercurous chloride), as well as perchlorates and chlorates. Catalysts include: ammonium dichromate, iron(III) oxide, hydrated ferric oxide, manganese dioxide, potassium dichromate, copper chromite, lead salicylate, lead stearate, lead 2-ethylhexoate, copper salicylate, copper stearate, lithium fluoride, n-butyl ferrocene, di-n-butyl ferrocene. Stabilizers include: carbonates (e.g., sodium, calcium, or barium carbonate), alkaline materials, boric acid, organic nitrated amines (such as 2-nitrodiphenylamine),



petroleum jelly, castor oil, linseed oil, ethyl centralite, and 2-nitrodiphenylamine. Anticaking agents include: fumed silica, graphite, and magnesium carbonate. Plasticizers: include dioctyl adipate, isodecyl pelargonate, and dioctyl phthalate as well as other energetic materials such as: nitroglycerine, butanetriol trinitrate, dinitrotoluene, trimethylolthane trinitrate, diethylene glycol dinitrate, triethylene glycol dinitrate, bis(2,2-dinitropropyl)formal, bis(2,2-dinitropropyl)acetal, 2,2,2-trinitroethyl 2-nitroxyethyl ether, and others. Curing and crosslinking agents include: paraquinone dioxime, toluene-2, 4-diisocyanate, tris(1-(2-methyl)aziridinyl) phosphine oxide, N,N,O-tri(1,2-epoxy propyl)-4-aminophenol, and isophorone diisocyanate. Bonding agents include tris(1-(2-methyl)aziridinyl) phosphine oxide and triethanolamine.

Materials used as binding agents **122** include: gums, resins and polymers, such as: acacia gum, red gum, guar gum, copal, cellulose, carboxymethyl cellulose, nitrocellulose, rice starch, cornstarch, shellac, dextrin, hydroxyl-terminated polybutadiene (HTPB), polybutadiene acrylonitrile (PBAN), polyethylene, and polyvinyl chloride (PVC).

Explosive slurry **128** is used to form explosive composition **114**. Explosive slurry **128** includes fuel **116**, oxidizer **118**, additives **120**, and binding agent **122**. Explosive slurry **128** also includes solvent **130**. Once positioned with respect to housing **102**, explosive slurry **128** is allowed to solidify by withdrawal of solvent **130**, e.g., via vaporization, to form explosive slurry **128** as a solid or to give explosive slurry **128** more solid-like form.

Materials used as solvent **130** include methyl ethyl ketone (MEK), cellulose thinners, isopropanol, alcohol, water, and hydrogen peroxide. Solvent **130** dissolves the other components of explosive slurry **128** and allows explosive slurry **128** to be processed in a more liquid-like fashion as compared to explosive composition **114**.

Table 1 below shows typical components of dry granular explosive materials, dry neutralizer materials, coloring agents, and ratios required to neutralize the explosive materials in several preferred embodiments. The ratios indicated are by weight, but similar ratios may also be made by volume. The percentage composition of the explosive materials can vary by as much as plus or minus 15%. The percentage composition of the neutralizer materials can vary by as much as plus or minus 15%. The composition ratios can vary by as much as plus or minus 25%.

TABLE 1

Dry Explosive Materials	Dry Neutralizer Materials	Coloring Agents	DEM:DIM (by weight)
70% potassium chlorate 30% aluminum	65% magnesium silicate 30% aluminum 5% ackroyd resin	Aluminum	3:2
75% potassium nitrate 15% charcoal 10% sulfur	Silica	Carbon slurry	3:1
70% potassium nitrate 14% charcoal 16% sulfur	Silica	Carbon slurry	3:1
40% sodium nitrate 30% charcoal 30% sulfur	Chalk	Carbon black	3:2
75% potassium nitrate 19% carbon 6% sulfur	Barium	Lamp black	6:5

Table 2 below shows typical components of explosive materials, neutralizer materials, pigmentation, solvents, and

ratios. The percentage composition of the explosive materials can vary by as much as plus or minus 15%. The percentage composition of the neutralizer materials can vary by as much as plus or minus 15%. The composition ratios can vary by as much as plus or minus 25%.

TABLE 2

Explosive Materials	Neutralizer Materials	Pigmentation	Solvents	EM:IM:Sol (by weight)
75% potassium nitrate 15% charcoal 10% sulfur	Silica	Carbon black	Alcohol	3:1:1
70% potassium nitrate 14% charcoal 16% sulfur	Chalk	Lamp black	Water	3:2:2
40% sodium nitrate 30% charcoal 30% sulfur	Barium	Aluminum pigment (ultramarine)	Isopropanol	6:5:4
75% potassium nitrate 19% carbon 6% sulfur	Saw dust	Vine black	Liquid nitrogen	11:9:9

Tables 3-5 below show typical components of neutralizers, solvents, pigments, and explosive compounds, any of which may be used in pyrotechnic devices in accordance with this disclosure. Table 3 below includes a list of neutralizers and solvents, any of which may be used in pyrotechnic devices.

TABLE 3

Neutralizers	Solvents
Talcum	Methyl ethyl ketone (MEK)
Chaulk	Cellulose thinners
Barrium	Isopropanol
Manganese	Water
Aluminum	Alcohol
Silica	Hydrogen peroxide
Saw dust	Liquefied petroleum gas
Calcium carbonate	Liquid nitrogen
Barite	
Potters clay	

Table 4 below shows a list of pigments, any of which may be used in pyrotechnic devices. A pigment that is used in portion **100** of pyrotechnic device may form part of non-inert material **106** or part of inert material **108**, depending on the chemical composition of the pigment. When a pigment is used to tint concealed amalgamated neutralizer **104**, a sufficient amount is used to coat and color the granules formed from non-inert material **106** and inert material **108** within concealed amalgamated neutralizer **104**. The amount or proportion of pigment may vary depending on the grain size of the granules formed from non-inert material **106** and inert material **108** within concealed amalgamated neutralizer **104**. The pigment may be introduced to concealed amalgamated neutralizer **104** in the form of a dye. Similarly, the granules of the inert materials may be washed with a pigment or dye for a time sufficient to change their color to approximate the color of the granules of the non-inert material. The grainsize of the pigmented inert material can be controlled by sifting with an appropriate wire mesh or other method as known in the art. The mesh size is chosen to approximate the size of the non-inert material.



TABLE 4

Pigments
Aluminum pigments: ultramarine violet, ultramarine
Antimony pigments: antimony white
Arsenic pigments: orpiment natural monoclinic arsenic sulfide (As <sub>2</sub> S <sub>3</sub> )
Barium pigments: barium sulfate
Biological pigments: alizarin, alizarin crimson, gamboge, cochineal red, rose madder, indigo, Indian yellow, Tyrian purple
Cadmium pigments: cadmium yellow, cadmium red, cadmium green, cadmium orange, cadmium sulfoselenide (CdSe)
Carbon pigments: carbon black, ivory black (bone char), vine black, lamp black, India ink
Chromium pigments: chrome green, viridian, chrome yellow, chrome orange
Clay earth pigments (iron oxides): yellow ochre, raw sienna, burnt sienna, raw umber, burnt umber
Cobalt pigments: cobalt violet, cobalt blue, cerulean blue, aureolin (cobalt yellow)
Copper pigments: Azurite, Han purple, Han blue, Egyptian blue, Malachite, Paris green, Scheele's Green, Phthalocyanine Blue BN, Phthalocyanine Green G, verdigris, viridian
Iron pigments: Prussian blue, yellow ochre, iron black
Iron oxide pigments: sanguine, caput mortuum, oxide red, red ochre, Venetian red, burnt sienna
Lead pigments: lead white, cremnitz white, Naples yellow, red lead
Manganese pigments: manganese violet
Mercury pigments: vermilion
Organic pigments: quinacridone, magenta, phthalo green, phthalo blue, pigment red 170, diarylide yellow
Tin pigments: mosaic gold
Titanium pigments: titanium yellow, titanium beige, titanium white, titanium black
Ultramarine pigments: ultramarine, ultramarine green shade
Zinc pigments: zinc white, zinc ferrite
India ink

Table 5 below shows typical explosive compounds, any of which may be used in pyrotechnic devices in accordance with this disclosure. Table 5 includes the following acronyms (among others): trinitrotoluene (TNT), ammonium nitrate (AN), ammonium nitrate fuel oil (ANFO), triethylenetetramine (TETA), nitromethane (NM), pentaerythritol tetranitrate (PETN), research department explosive (RDX), erythritol tetranitrate (ETN), high-velocity military explosive (HMX), polyurethane (PU), polycaprolactone (PCP), trimethylololthane trinitrate (TMETN), hydroxyl-terminated polybutadiene (HTPB), alkyl acrylate copolymer (ACM), dioctyl adipate (DOA), ammonium perchlorate (AP), nitrocellulose (NC), and isopropyl nitrate (IPN).

TABLE 5

Explosive compounds
Aluminum powder (30%) + Potassium chlorate (70%)
Amatol (50% TNT + 50% AN)
Amatol (80% TNT + 20% AN)
Ammonium nitrate (AN + <0.5% H <sub>2</sub> O)
ANFO (94% AN + 6% fuel oil)
ANNMAL (66% AN + 25% NM + 5% Al + 3% C + 1% TETA)
Black powder (75% KNO <sub>3</sub> + 19% C + 6% S)
Blasting powder
Chopin's Composition (10% PETN + 15% RDX + 72% ETN)
Composition A-5 (98% RDX + 2% stearic acid)
Composition B (63% RDX + 36% TNT + 1% wax)
Composition C-3 (78% RDX)
Composition C-4 (91% RDX)
DADNE (1,1-diamino-2,2-dinitroethene, FOX-7)
DDF (4,4'-Dinitro-3,3'-diazonofuroxan)
Diethylene glycol dinitrate (DEGDN)
Dinitrobenzene (DNB)
Erythritol tetranitrate (ETN)
Ethylene glycol dinitrate (EGDN)
Flash powder
Gelatine (92% NG + 7% nitrocellulose)
Heptanitrocubane (HNC)
Hexamine dinitrate (HDN)
Hexanitrobenzene (HNB)
Hexanitrostilbene (HNS)

TABLE 5-continued

Explosive compounds
Hexogen (RDX)
HMTD (hexamine peroxide)
HNIW (CL-20)
Hydrazine mononitrate
Hydromite ® 600 (AN water emulsion)
MEDINA (Methylene dinitroamine)
Mixture: 24% nitrobenzene + 76% TNM
Mixture: 30% nitrobenzene + 70% nitrogen tetroxide
Nitrocellulose (13.5% N, NC)
Nitroglycerin (NG)
Nitroguanidine
Nitromethane (NM)
Nitrourea
Nobel's Dynamite (75% NG + 23% diatomite)
Nitrotriazolon (NTO)
Octanitrocubane (ONC)
Octogen (HMX grade B)
Octol (80% HMX + 19% TNT + 1% DNT)
PBXIH-135 EB (42% HMX, 33% Al, 25% PCP-TMETN's system)
PBXN-109 (64% RDX, 20% Al, 16% HTPB's system)
PBW-11 (96% HMX, 1% ACM, 3% DOA)
PBW-126 (22% NTO, 20% RDX, 20% AP, 26% Al, 12% PU's system)
Penthrate (PETN)
Pentolite (56% PETN + 44% TNT)
Picric acid (TNP)
Plastics Gel ® (45% PETN + 45% NG + 5% DEGDN + 4% NC)
RISAL P (50% IPN + 28% RDX + 15% Al + 4% Mg + 1% Zr + 2% NC)
Semtex 1A (76% PETN + 6% RDX)
Tanerit Simply ® (93% granulated AN + 6% red P + 1% C)
acetone peroxide (TATP)
Tetryl
Tetrytol (70% tetryl + 30% TNT)
trinitroazetidine (TNAZ)
Torpex (aka HBX, 41% RDX + 40% TNT + 18% Al + 1% wax)
Triaminotrinitrobenzene (TATB)
Trinitrobenzene (TNB)
Trinitrotoluene (TNT)
Tritonal (80% TNT + 20% aluminium)

65 Referring to FIG. 2A, build container 202 is shown. Build container 202 is a generally hollow cylinder having sidewall 204, open end 206, and closed end 208 defining interior



space **205**. In one embodiment, number 20 cardboard is used to form the ends and walls. Other structural materials such as mylar or vinyl will suffice. Build container **202** is used in a preferred method of assembling generally cylindrical shaped devices containing various combinations of dry compositions of explosive and neutralizer materials, as will be further described. Inner tube **210** is removably affixed within the interior of build container **202** by means common in the art, such as a suitably releasable adhesive. In the preferred embodiment, inner tube **210** is located co-axially with build container **202**, however inner tube **210** may be positioned anywhere within interior **205**. Although a single inner tube is depicted within build container **202**, it will be understood that a plurality of inner tubes may be installed inside build container **202**. Inner tube **210** has an exterior cylindrical shaped surface **212** and an open end **214** defining interior space **215**. Neutralizer material is loaded into interior space **215**, which is inside of interior space **205**, and the explosive material is loaded into interior space **205** outside of interior space **215**. Those skilled in the art will understand that shapes other than cylindrical may be used for inner tube **210** and/or build container **202** such as elliptical, rectangular, and triangular. It is further understood that the size of inner tube **210** relative to build container **202** can be changed depending on the ratio of neutralizer material to explosive material required to properly render the explosive material useless. Additionally, the overall volume of the assembled device may vary depending on intended use of the device.

It should be understood that the positions of the explosive and neutralizer materials could be reversed so that explosive material is loaded into interior space **215**, which is inside of interior space **205**, and the neutralizer material is loaded into interior space **205** outside of interior space **215**. Furthermore, the relative dimensions of the build container and the inner tube organize functions of the ratio of explosive and neutralizer materials.

FIG. 2B shows an assembled device **222** containing neutralizer material **220** and explosive material **230** separated by a boundary interface **225**. Neutralizer material **220** is comprised of components that match explosive material **230** such that neutralizer material **220** is indiscernible from explosive material **230**. Neutralizer material **220** is chosen to approximate the grain size and color of explosive material **230**. Boundary interface **225** is where explosive material **230** contacts neutralizer material **220** within assembled device **222**. Since neutralizer material **220** is indiscernible from explosive material **230**, boundary interface **225** is not visible.

Referring to FIG. 3A, alternate build container **302** is shown. Build container **302** is a generally hollow cylinder having sidewall **304**, open end **306**, and closed end **308** defining interior space **305**. Build container **302** is used for assembling generally disc shaped, layered devices.

FIG. 3B shows an assembled device **322** made from build container **302** in which dry manufacture neutralizer material **320** is layered on top of explosive material **330**. In an alternate embodiment, explosive material **330** is layered on top of neutralizer material **320**. Explosive material **330** is separated from neutralizer material **320** by boundary interface **325**.

FIG. 4A shows an alternate build container **402**. Build container **402** is comprised of two hollow, semi-spherical halves **404** and **406**. Half **404** defines interior space **408** and half **406** defines interior space **410**. A disk shaped separation barrier **409** may be affixed to either half **404** or **406** to contain the explosive material and neutralizer material during assembly.

FIG. 4B shows an assembled device **422** made from build container **402**. Explosive material **430** is separated from neutralizer material **420** by boundary interface **425**. Boundary interface **425** is imperceptible upon visual inspection.

In an alternate spherical arrangement shown in FIG. 4C, build container **402** is used to create a spherical shaped device comprised of a spherical core surrounded by a larger sphere. Explosive material **430** is a hollow sphere shape including a spherical shaped core of neutralizer material **420**. It should be understood by those skilled in the art that an arrangement of neutralizer material surrounding explosive material would be equally effective. Imperceptible boundary interface **426** is provided between explosive material **430** and neutralizer material **420**.

For simplicity in FIGS. 1-4, detonators, primers, fuses, igniters, casings, plugs, etc. are not shown as each device may require different combinations of these elements typically found in various consumer fireworks, ammunition, and other pyrotechnic products. Some devices use other sources of ignition such as heat or impact.

Referring to FIG. 5, the steps involved with constructing a device using generally dry materials are shown. At step **502**, an explosive material is chosen. The proper explosive material will be chosen based on its intended use. At step **504** the grain size of the explosive material is identified. If the explosive material contains multiple components each having different grain sizes, each grain size will be identified. At step **506**, the color of the explosive material is identified. At step **508**, a matching neutralizer material with the identified grain size is chosen. The neutralizer material and the level of neutralization desired are chosen according to Table 1 for dry materials or Table 2 for slurries. At step **510**, if the color of the neutralizer material does not match the explosive material, then the neutralizer material is colored using a pigment or dye to match the explosive material. In a different embodiment, a charcoal dye is employed to tint the neutralizer material. At step **512**, the explosive material is introduced into a build container. At step **514**, the neutralizer material is introduced into the build container, and if necessary, the build container is assembled. If necessary, at step **516**, the materials introduced in the build container are compacted. At step **518**, the separation barrier is removed from the build container. At step **520**, any ancillary components required for the device, such as plugs, primers, fuses, detonators, etc., are installed and the assembled device is wrapped in appropriate casing.

Referring to FIG. 6, one or more steps involved with constructing a spherical pyrotechnic device using generally inert materials are shown. At step **602**, an explosive material is chosen. The proper explosive material will be chosen based on its intended use. At step **604**, the dry density of the explosive material is identified. At step **606**, the color of the dried explosive material is identified. At step **608**, a slurry is prepared from the explosive material and the appropriate solvent or liquid. At step **610**, the neutralizer material with the identified dry density is chosen. At step **612**, a neutralizer slurry is prepared using the neutralizer material and proper pigmentation and solvent.

At step **614**, the neutralizer slurry is rolled into a sphere. In a preferred embodiment, the neutralizer slurry is rolled into a sphere through the use of a scoop. In one preferred embodiment, a scoop is used which is part number ZEROLL 1020 available from Centinal Restaurant Products of Indianapolis, Ind.

At step **616**, the neutralizer slurry is optionally allowed to at least partially solidify so that the sphere of the neutralizer slurry will maintain its geometry during subsequent pro-



cessing. At step **618**, the explosive slurry is rolled into a sphere such that the volume of the sphere of the neutralizer slurry and the volume of the sphere of the explosive slurry forms a selected ratio, e.g., 2:3 or about 40% to about 60%.

At step **620**, the sphere of neutralizer slurry is implanted into the sphere of the explosive slurry. The sphere of neutralizer slurry is implanted into substantially the center of the sphere of the explosive slurry to create a substantially uniform spherical explosive profile. In other embodiments, the shape and position of the neutralizer slurry within the sphere of explosive slurry is selected to create a non-uniform explosive profile that is not spherical.

At step **622**, the volume of explosive slurry into which the sphere of neutralizer slurry was implanted is rolled again to reform a spherical shape. At step **624**, the explosive slurry is allowed to solidify and, if it is not already solidified, the neutralizer slurry within the sphere of explosive slurry is also optionally allowed to solidify and dry. The sphere comprising the solidified explosive slurry and the neutralizer slurry may then be used to form a pyrotechnic device.

Referring to FIG. 7, one or more steps involved with constructing a preferred device is shown. At step **702**, an explosive material is chosen. The proper explosive material will be chosen based on its intended use. At step **704**, the dry density of the explosive material is identified. At step **706**, the color of the dried explosive material is identified. At step **708**, a slurry is prepared from the explosive material and the appropriate solvent or liquid. At step **710**, the neutralizer material with the identified dry density is chosen. At step **712**, a neutralizer slurry is prepared using the neutralizer material and proper pigmentation and solvent. At step **714**, the neutralizer slurry is rolled into a sphere. At step **716**, the neutralizer slurry is optionally allowed to at least partially solidify so that the sphere of the neutralizer slurry will maintain its geometry during subsequent processing. At step **718**, explosive slurry is applied and rolled onto the sphere of partially solidified neutralizer slurry. At step **720**, the explosive slurry is allowed to solidify and, if it is not already solidified, the neutralizer slurry within the sphere of explosive slurry is also optionally allowed to solidify and dry. The sphere comprising the solidified explosive slurry and the neutralizer slurry may then be used to form a pyrotechnical device.

FIG. 8A shows an alternate embodiment of device **824** constructed on substrate **840**. Substrate **840** is preferably paper, but may also take the form of other planar surfaces or objects. Explosive material **830** is adhered to substrate **840**. Neutralizer material **820** is adhered to both explosive material **830** and substrate **840** thereby encapsulating the explosive material and forming boundary interface **826**. Device **824** is manufactured from slurry compositions of explosive materials and neutralizer materials as will be further described.

The thickness of explosive material **830** on substrate **840** is substantially uniform along the surface of substrate **840**, except at the outer edges. The thickness of neutralizer material **820** on explosive material **830** and on substrate **840** is also substantially uniform, except at the outer edges. In alternative embodiments, the thicknesses may vary. For example, when device **824** embodies a target training dummy, a thickness of explosive material **830** at substantially the center of the target training dummy may be increased and a thickness of neutralizer material **820** may be reduced to retain a similar overall thickness. In this manner, a different pyrotechnic and visual effect is achieved so that a hit substantially in the center of the target training dummy

is distinguishable from a hit that is not substantially in the center of the target training dummy.

FIG. 8B shows an alternate embodiment of device **824** as a layer of neutralizer material **820** is being applied to explosive material **830**. Neutralizer material **820** is prepared in tank or hopper **852** and then applied to explosive material **830** on substrate **840**. Tank or hopper **852** includes an outlet **854** and a valve **856** at the underside of tank or hopper **852**, and outlet **854** is controlled by a valve **856**. The valve **856** can be adjusted to control the volume of the neutralizer slurry dispensed. One of the tank or hopper **852** or the substrate **840** is moved in a direction so that a controlled amount of neutralizer material **820** is applied to explosive material **830**. In a preferred embodiment, the thickness of neutralizer material **820** is substantially the same as the thickness of explosive material **830**. In alternative embodiments, the thicknesses of neutralizer material **820** and explosive material **830** may vary.

Referring to FIG. 9, the steps involved with constructing a preferred device is shown. At step **932**, an explosive material is chosen. The proper explosive material will be chosen based on its intended use. At step **934**, the dry density of the explosive material is identified. At step **936**, the color of the dried explosive material is identified. At step **937**, a slurry is prepared from the explosive material and the appropriate solvent or liquid. At step **938**, the neutralizer material with the identified dry density is chosen. The neutralizer material is selected from Table 3.

At step **940**, a neutralizer slurry is prepared using the neutralizer material, proper pigmentation and solvent. In a preferred embodiment, the neutralizer slurry is an embodiment of neutralizer slurry **124** of FIG. 1B and is prepared by placing all of the ingredients or components of neutralizer slurry into a tank or hopper in which the ingredients or components are mixed.

At step **942**, the explosive slurry is applied to the substrate. At step **944**, the explosive slurry is allowed to solidify and dry.

At step **946**, the neutralizer slurry is applied to the dried explosive slurry and the substrate. In a preferred embodiment, the underside of a tank or hopper, such as tank or hopper **852** of FIG. 8B, in which the neutralizer slurry was prepared includes an outlet, such as outlet **854**, controlled by a valve, such as valve **856**. The valve can be adjusted to control the volume of the neutralizer slurry dispensed. The valve is placed over the article on which neutralizer slurry **820** is to be applied. For example, the article may comprise substrate **840** and explosive material **830** of FIGS. 8A and 8B. After placement of the valve, the valve is actuated to dispense a selected amount of the neutralizer slurry onto the article to achieve a desired ratio between the amount of neutralizer slurry and the amount of explosive slurry on the article.

At step **948**, the neutralizer slurry is allowed to solidify and dry.

In one preferred embodiment, an article of manufacture, in this case a shotgun shell, is produced according to this disclosure. Referring to FIG. 10, an article of manufacture, shotgun shell **1000**, is shown. Shotgun shell **1000** includes casing **1002** enclosed on one end by base **1004**. Primer **1006** extends through base **1004** and is positioned adjacent generally cylindrically shaped concealed amalgamated device **1008**. Concealed amalgamated device **1008** is comprised of neutralizer material **1010** separated from explosive material **1012** by boundary interface **1014**. Adjacent the explosive



## 15

material and neutralizer material is wad **1016**. Shot **1018** is shown adjacent wad **1016**. Crimped closure **1017** is shown opposite base **1004**.

Referring to FIG. **11**, a flowchart showing the steps involved in loading a shotgun shell casing incorporating a preferred embodiment of the device. At step **1104**, the primer is pressed into the base. A separation barrier in the form of a cylindrical Mylar tube is placed in the casing adjacent the base at step **1106**. In a preferred embodiment, the tube is located coaxially with the primer. At step **1108**, gunpowder is loaded into the casing within the interior of the separation barrier. At step **1109**, the neutralizer material is chosen to match the color and grain size of the gunpowder. Choice of the neutralizer material includes the optional selection of a pigment or dye used to match the color of the neutralizer material to the color of the gunpowder. At step **1110**, the neutralizer material is loaded into the casing surrounding the separation barrier. At step **1112**, the separation barrier is removed. At step **1114**, a wad is loaded and pressed within the casing. At step **1116**, shot is loaded and pressed into the casing. At step **1118**, the casing is crimped closed.

In use, should the shotgun shell be disassembled, the neutralizer material is automatically and undetectably mixed with the explosive material. Since the neutralizer material cannot be easily separated from the explosive material, the mixture effectively cannot be used to form an improvised explosive device.

In one preferred embodiment, an article of manufacture, in this case a pyrotechnic device commonly referred to as a Roman candle, is produced according to this disclosure. Referring to FIG. **12**, an article of manufacture, Roman candle **1200**, is shown. Roman candle **1200** includes one or more: fuse **1202**, delay charges **1204** and **1212**, stars **1206** and **1214**, lift charges **1208** and **1216**, neutralizer rings **1210** and **1218**, clay plug **1220**, and paper wrapping **1222**.

Fuse **1202** is connected to a first delay charge **1204**. Fuse **1202** is a burning fuse that, when lit, burns for a selected amount of time based on the length of fuse **1202** and where fuse **1202** is lit along the length of fuse **1202**. Fuse **1202** passes fire to and ignites delay charge **1204**.

Delay charge **1204** is connected to fuse **1202** and packed on top of a first star **1206**, lifting charge **1208**, and shaped neutralizer ring **1210**. Delay charge **1204** comprises a pyrotechnic composition that burns at a slow constant rate that is not significantly affected by temperature or pressure and is used to control timing of the pyrotechnic device, i.e., Roman candle **1200**. After being ignited by fuse **1202**, first delay charge **1204** burns for a selected amount of time based on the composition, height, volume, and density of delay charge **1204**, and then ignites one or more of star **1206** and lift charge **1208**. Delay charge **1204** delays the time between the burning of fuse **1202** and ignition of star **1206** and lift charge **1208**.

Star **1206** is positioned between delay charge **1204** and lift charge **1208**. Star **1206** comprises a pyrotechnic composition selected to provide a visual effect, including burning a certain color or creating a spark effect once first star **1206** is ignited. Star **1206** is coated with black powder to aid the ignition of star **1206** and aid the ignition of lift charge **1208**.

First lift charge **1208** is positioned between first delay charge **1204** and second delay charge **1212** and is in contact with first star **1206** and first shaped neutralizer ring **1210**. First lift charge **1208** comprises an explosive material, such as granulated black powder or any compound selected from Table 5, and is used to shoot first star **1206** out of Roman candle **1200** and to ignite second delay charge **1212**. Ignition

## 16

of first lift charge **1208** causes first star **1206** to shoot out of Roman candle **1200** with a velocity based on one or more of the composition, size, shape, and position of first lift charge **1208** within Roman candle **1200**. As depicted in FIG. **12**, first lift charge **1208** is shaped substantially as an inverted frustum of a right angle cone with a diameter of the base contacting first delay charge **1204** being larger than a diameter of the base contacting second delay charge **1212**. The shape of lift charge **1208** in conjunction with the shape of neutralizer ring **1210** operate to control the blast profile of the explosion created when lift charge **1208** is ignited. The shape of an inverted frustum provides for the explosion created by the ignition of first lift charge **1208** to be directed out through the top of Roman candle **1200** while still allowing for sufficient contact area with second delay charge **1212** to pass fire onto and ignite second delay charge **1212** after first lift charge **1208** is ignited.

Neutralizer ring **1210** surrounds the conically slanted side of lift charge **1208** and is positioned between delay charge **1204** and delay charge **1212**. Neutralizer ring **1210** is a ring of material comprising an inert material that, as described above, is indiscernible from the explosive material of lift charge **1208** and that, if mixed with the explosive material of lift charge **1208**, results in a composition having a substantially reduced explosiveness. Material of shaped neutralizer ring **1210** has a grain size and color matching that of the grain size and color of material of lift charge **1208** so that the interface between shaped neutralizer ring **1210** and lift charge **1208** is indiscernible.

Delay charge **1212**, star **1214**, lift charge **1216**, and neutralizer ring **1218** operate in a similar fashion as delay charge **1204**, star **1206**, lift charge **1208**, and neutralizer ring **1210**, but may have the same or different compositions, sizes, shapes, positions, and geometries and provide for the same or different specific effects.

Clay plug **1220** is a bottom layer of Roman candle **1200** beneath the combination of second lift charge **1216** and neutralizer ring **1218**. Clay plug **1220** prevents fire from second lift charge **1216** from escaping through the bottom of Roman candle **1200** and prevents lift charge **1216** from being ignited from below.

Paper wrapping **1222** surrounds the sides of Roman candle **1200** forming a cylindrical shape. Paper wrapping **1222** protects Roman candle **1200** when not in use and acts as a muzzle to direct stars **1206** and **1214** when they are shot out of the top of Roman candle by lift charges **1208** and **1216**, respectively.

Referring to FIG. **13**, one or more steps involved with constructing a pyrotechnic device commonly referred to as a Roman candle is shown. At step **1302**, an explosive material is chosen. The proper explosive material will be chosen based on its intended use and may be selected from the explosive compounds from Table 5. At step **1304**, the dry density of the explosive material is identified. At step **1306**, the color of the dried explosive material is identified. At step **1308**, the lift charge, star and delay charge are prepared using explosive material. At step **1310**, the neutralizer material with the identified dry density is selected from the neutralizers listed in Table 3. At step **1312**, a neutralizer powder is prepared using the neutralizer material and proper pigmentation and solvent selected from Tables 3-4.

At step **1314**, a paper tube is prepared to receive the clay plug, one or more lift charges, one or more stars, one or more delay charges and neutralizer powder. The paper tube may be placed vertically so that the materials may be introduced from the top of the tube. At step **1316**, a clay plug is inserted into the bottom of tube that directs the explosions from the



lift charge out through the top of the tube. At step 1318, a separation barrier is inserted into the tube. The separation barrier may include a slant to be slightly conical in shape so that the lift charge is formed as a frustum. At step 1320, the lift charge is inserted into the tube inside the separation barrier, after which one or more stars are placed on top of the lift charge. At step 1322, neutralizer powder is inserted into the tube outside of the separation barrier. The neutralizer powder has the same grain size and color as the lift charge. At step 1324, the separation barrier is removed and the interface between the lift charge and the neutralizer is indiscernible due to the selected properties of the neutralizer powder. At step 1326, a delay charge is inserted into the tube and packed down so that the lift charge, stars, neutralizer powder, and delay charge will not mix during subsequent handling and processing. At step 1328, steps 1318-1326 are repeated for a desired number of stages for the pyrotechnic device. At step 1330, a fuse is introduced into the tube that contacts the top-most delay charge.

In one preferred embodiment, an article of manufacture, in this case a pyrotechnic assembly, is produced according to this disclosure. Referring then to FIG. 14, an article of manufacture, pyrotechnic assembly 1400, is shown. Pyrotechnic assembly 1400 includes: paper 1402, slurry 1404, fuse 1406, and solidified material 1408.

Paper 1402 forms an outer shell for a pyrotechnic device created from assembling pyrotechnic assembly 1400. Prior to rolling paper 1402 to form a cylinder, slurry 1404 is placed on paper 1402, solidified material 1408 is placed onto slurry 1404, and fuse 1406 is positioned. After positioning slurry 1404, solidified material 1408, and fuse 1406 onto paper 1402, paper 1402 is rolled to form a cylindrical pyrotechnic device.

Slurry 1404 is positioned on paper 1402 between paper 1402 and solidified material 1408 prior to rolling paper 1402. After rolling, slurry 1404 forms a substantially continuous layer around solidified material 1408. One of slurry 1404 and solidified material 1408 comprises neutralizer material (e.g., concealed amalgamated neutralizer 104 of FIG. 1A) and the other of slurry 1404 and solidified material 1408 comprises explosive material (e.g., explosive composition 114 of FIG. 1A). After solidifying, the boundary between the material of slurry 1404 and the material of solidified material 1408 will be indiscernible upon visual inspection. The volume of slurry 1404 is sufficient so that when the material of slurry 1404 is randomly mixed with the material of solidified material 1408, the explosiveness of the combined mixed material is substantially reduced.

Fuse 1406 is positioned to pass flame to explosive material comprised by one of slurry 1404 and solidified material 1408. Fuse 1406 contacts both slurry 1404 and solidified material 1408 so that fuse 1406 contacts both the inert material of one of slurry 1404 and solidified material 1408 and the explosive material of the other of slurry 1404 and solidified material 1408. By contacting both slurry 1404 and solidified material 1408, the position of fuse 1406 does not provide an indication of whether solidified material 1408 or slurry 1404 comprises explosive material in the final assembled device.

In an alternative embodiment where solidified material 1408 comprises the explosive material, fuse 1406 may be positioned within and incorporated into solidified material 1408 prior to the solidification of solidified material 1408. With fuse 1406 incorporated into solidified material 1408, placement of solidified material 1408 also positions fuse 1406 with respect to paper 1402 of assembly 1400.

Solidified material 1408 is positioned on slurry 1404 prior to rolling paper 1402 and contacts fuse 1406. After rolling pyrotechnic assembly 1400 into a pyrotechnic device, solidified material 1408 is located in substantially the center of the pyrotechnic device. In alternative embodiments, solidified material 1408 may be positioned away from the center of the pyrotechnic device and create a different explosion profile as compared to when the solidified material 1408 is placed in the center of the pyrotechnic device.

Referring to FIG. 15, one or more steps involved with constructing a pyrotechnic device by rolling single portions of explosive material and neutralizer material into a cylinder is shown. At step 1502, an explosive material is chosen from Table 5. The proper explosive material will be chosen based on its intended use. At step 1504, the dry density of the explosive material is identified. At step 1506, the color of the dried explosive material is identified. At step 1508, an explosive slurry is using the explosive material and the appropriate solvent or liquid. At step 1510, the neutralizer material with the identified dry density is chosen. At step 1512, a neutralizer slurry is prepared using the neutralizer material and proper pigmentation and solvent or liquid.

At step 1514, paper is prepared for creating the pyrotechnic device. The paper is formed as a square or rectangular sheet with appropriate dimensions of thickness, length, and width to form the exterior of the pyrotechnic device. At step 1516, a first slurry is applied to the paper. The first slurry is one or the other of the explosive slurry and the neutralizer slurry. At step 1518 and prior to introducing the second slurry to the first slurry, the second slurry is allowed to at least partially solidify to form a solidified material or paste that is thicker than the first slurry to aid further processing steps. The second slurry is different from the first slurry and is the other of the explosive slurry or the neutralizer slurry. At step 1520, the solidified material made from the second slurry is positioned onto the first slurry.

At step 1522, a fuse is introduced between the solidified material and the first slurry so as to contact the explosive material in one or the other of the first slurry and the second slurry. In alternative embodiments, the fuse is introduced into the second slurry prior to solidification of the second slurry. At step 1524, the paper is rolled into a cylindrical shape. The process of rolling the paper surrounds the entirety of the solidified material with the first slurry and positions the solidified material substantially in the center of the cylinder created by rolling the paper. Positioning the solidified material in the center of the cylinder gives the pyrotechnic device a substantially uniform blast profile along the circumference of the cylinder. In alternative embodiments, the solidified material is positioned off center so that the pyrotechnic device will not contain a substantially uniform blast profile along the circumference of the cylinder.

In one preferred embodiment, an article of manufacture, in this case a pyrotechnic assembly, is produced according to this disclosure. Referring to FIG. 16, an article of manufacture, assembly 1600, is shown that forms an embodiment of portion 100 of a pyrotechnic device of FIG. 1A. Assembly 1600 includes: paper 1602, explosive compound 1604, and neutralizer compound 1606.

Paper 1602 is a substrate onto which explosive compound 1604 and neutralizer compound 1606 are applied. After application of explosive compound 1604 and neutralizer compound 1606 onto paper 1602, paper 1602 is rolled from one end in direction 1608 to form a cylinder. A fuse for igniting explosive compound 1604 may be introduced to assembly 1600 before or after rolling paper 1602 into a



cylinder. After assembly into pyrotechnic device, paper **1602** protects the pyrotechnic device from unwanted ignition.

Explosive compound **1604** is any explosive material and is applied to paper **1602** as a paste or slurry to stick between multiple layers of paper **1602** after paper **1602** is rolled. The width of each portion of explosive compound **1604** applied to paper **1602** is substantially uniform. In alternative embodiments, the width of each portion of explosive compound **1604** applied to paper **1602** may vary along the length of paper **1602**. The overall ratio of the volume of explosive compound **1604** to the volume of neutralizer compound **1606** is such that, if explosive compound **1604** and neutralizer compound **1606** are removed from a pyrotechnic device created from assembly **1600** and mixed, then the resulting mixture would have a substantially reduced explosive effectiveness.

Neutralizer compound **1606** is any neutralizer material and is also applied to paper **1602** as a paste or slurry to stick between multiple layers of paper **1602** after paper **1602** is rolled. The width of each portion of neutralizer compound **1606** applied to paper **1602** is substantially uniform and is less than the width of the portions of explosive compound **1604**. When dried, neutralizer compound **1606** has a grain size that substantially matches the grain size of explosive compound **1604**. Neutralizer compound **1606** includes pigmentation so that the color of neutralizer compound **1606** substantially matches the color of explosive compound **1604**. The boundary interface between the portions of explosive compound **1604** and neutralizer compound **1606** are indiscernible upon final assembly due to the matching grain size and color between explosive compound **1604** and neutralizer compound **1606**.

In alternative embodiments, the width of each portion of explosive compound **1604** applied to paper **1602** may vary along the length of paper **1602**.

Referring to FIG. 17, one or more steps involved with constructing a pyrotechnic device by rolling multiple portions of explosive material and neutralizer material is shown. At step **1702**, an explosive material is chosen from Table 5. The proper explosive material will be chosen based on its intended use. At step **1704**, the dry density of the explosive material is identified. At step **1706**, the color of the dried explosive material is identified. At step **1708**, a slurry is prepared from the explosive material and the appropriate solvent or liquid. At step **1710**, the neutralizer material with the identified dry density is chosen. At step **1712**, a neutralizer slurry is prepared using the neutralizer material and proper pigmentation and solvent.

At step **1714**, paper is prepared as a substrate to receive the explosive slurry and neutralizer slurry. The paper is sliced into a selected length and width suitable for rolling. At step **1716**, explosive slurry and neutralizer slurry are applied to the paper in alternating portions, as shown in FIG. 16. The width of the portions may be uniform or vary based on the location of the portion with respect to the leading edge of the paper that gets rolled first and the trailing edge of the paper that gets rolled last. For example, portions closer to the trailing edge may have a longer width as compared to portions closer to the leading edge.

At step **1718**, the paper with the applied explosive slurry and neutralizer slurry is rolled into a cylindrical shape so that each portion of explosive compound contacts two portions of neutralizer compound and two layers of paper. Similarly, each portion of neutralizer compound contacts two portions of explosive compound and two layers of paper.

At step **1720**, a fuse is inserted into the cylinder created by rolling the paper. The fuse is inserted so as to contact at

least one portion of explosive slurry. At step **1722**, at least the explosive slurry is allowed to solidify and optionally the neutralizer is also allowed to solidify.

At step **1720**, the explosive slurry is allowed to solidify as well as the neutralizer slurry. The cylindrically shaped roll comprising the solidified explosive slurry and the neutralizer slurry may then be used to form a pyrotechnical device. With the color, grain size, and dry density being substantially similar, the interfaces between portions of explosive material and neutralizer material in the rolled cylinder are indiscernible upon visual inspection and the explosive material is indistinguishable from the neutralizer material. Removal of the explosive material would also remove the neutralizer material so that attempted use of the explosive material in an improvised explosive device would mix the explosive material with the neutralizer material and reduce the effectiveness of the explosive material in the improvised explosive device.

In one preferred embodiment, an article of manufacture, in this case pyrotechnic device **1800** forms, for example, an instant hit recognition flare or pyrotechnic target, and is produced according to this disclosure. Referring to FIG. 18, an article of manufacture, pyrotechnic device **1800**, is shown that forms an embodiment of portion **100** of a pyrotechnic device of FIG. 1A. Pyrotechnic device **1800** includes: cardboard lid **1801**, concealed amalgamated neutralizer **1802**, pyrotechnic composition **1803**, imperceptible boundary layer **1804**, and shell case **1805**.

Cardboard lid **1801** and shell case **1805** form an embodiment of housing **102** of FIG. 1A. Cardboard lid **1801** is fitted to the top of shell case **1805** and presses against concealed amalgamated neutralizer **1802** to compact and maintain the shape and position of concealed amalgamated neutralizer **1802** and pyrotechnic composition **1803** within pyrotechnic device **1800**.

Concealed amalgamated neutralizer **1802** is layered on top of pyrotechnic composition **1803** and is held in place by cardboard lid **1801** and shell casing **1805**. Pyrotechnic composition **1803** is an embodiment of explosive composition **114**, is layered on top of shell case floor **1806**, and is held in place by shell casing **1805**. When concealed amalgamated neutralizer **1802** is mixed with pyrotechnic composition **1803** outside of pyrotechnic device **1800**, such as in an improvised explosive device, the explosive power of the resulting mixture is reduced as compared to the explosive power of pyrotechnic composition **1803**.

Imperceptible boundary layer **1804** is present at the interface or junction between concealed amalgamated neutralizer **1802** and pyrotechnic composition **1803**. Concealed amalgamated neutralizer **1802** is selected, processed, and manufactured to comprise a grain shape, grain size, color, and density that substantially matches the grain shape, grain size, color, and density of pyrotechnic composition **1803** so that imperceptible boundary layer **1804** cannot be perceived upon visual inspection.

Shell case **1805** comprises shell case floor **1806** and contains concealed amalgamated neutralizer **1802** and pyrotechnic composition **1803**. Shell case **1805** presses against concealed amalgamated neutralizer **1802** and pyrotechnic composition **1803** to compact and maintain the shape and position of concealed amalgamated neutralizer **1802** and pyrotechnic composition **1803** within pyrotechnic device **1800**.

Referring to FIG. 19, the steps involved with constructing a pyrotechnic device with concealed amalgamated neutralizer as used in an instant hit recognition flare or pyrotechnic target using a shell case is shown. At step **1902**, an explosive material, also known as a pyrotechnic composition, is cho-



sen. The proper explosive material will be chosen based on its intended use. At step **1904** the grain size of the explosive material is identified. If the explosive material contains multiple components each having different grains sizes, each grain size will be identified. At step **1906**, the color of the explosive material is identified. At step **1908**, a matching neutralizer material, also known as a concealed amalgamated neutralizer or a concealed amalgamated neutralizer component, with the identified grain size is chosen. The neutralizer material and the level of neutralization desired is chosen according to Table 1 for dry materials or Table 2 for slurries. At step **1910**, if the color of the neutralizer material does not match the explosive material, then the neutralizer material is colored to match the explosive material using one or more pigments or dyes. In a different embodiment, a charcoal dye is employed to tint the neutralizer material. At step **1912**, the explosive material is introduced into a shell case. At step **1914**, the neutralizer material is introduced into the shell case, and if necessary, the shell case is assembled. If necessary, at step **1916**, the materials introduced in the build container are compacted. At step **1918**, a cardboard lid is installed onto and fitted to the shell case. In alternative embodiments, the materials are compacted after installation of the cardboard lid instead of or in addition to being compacted prior to installation of the cardboard lid. At step **1920**, any ancillary components required for the device, such as plugs, primers, fuses, detonators, etc., are installed.

In one preferred embodiment, an article of manufacture, in this case a pyrotechnic pigeon, is produced according to this disclosure. Referring to FIG. **20**, an article of manufacture, pyrotechnic pigeon **2000**, is shown that includes an embodiment of portion **100** of a pyrotechnic device of FIG. **1A**. Pyrotechnic pigeon **2000** is a target configured for target shooting. Pyrotechnic pigeon **2000** includes substrate layer **2002**, first plastic layer **2004**, first material layer **2006**, second material layer **2008**, and second plastic layer **2010**. The sizes and thicknesses of the layers are not shown to scale. In certain embodiments, pyrotechnic pigeon **2000** comprises a standard clay pigeon to which first plastic layer **2004**, first material layer **2006**, second material layer **2008**, and second plastic layer **2010** are applied.

Substrate layer **2002** includes a step-shaped edge **2012** at the circumference of pyrotechnic pigeon **2000**. Step-shaped edge **2012** allows for pyrotechnic pigeon **2000** to be guided and rotated as it is launched from a clay pigeon launcher. Substrate layer **2002** acts as a substrate upon which is formed first plastic layer **2004**, first material layer **2006**, second material layer **2008**, and second plastic layer **2010**. Substrate layer **2002** contacts one or more layers of plastic material. Substrate layer **2002** comprises any clay, plastic, metal, concrete, limestone, pitch, or other material that is suitable for making a targets for clay pigeon shooting, also known as clay target shooting.

First plastic layer **2004** is positioned between substrate layer **2002** and first material layer **2006**. First plastic layer **2004** protects first material layer **2006** from substrate layer **2002**. First plastic layer **2004** adheres the combination of first plastic layer **2004**, first material layer **2006**, second material layer **2008**, and second plastic layer **2010** to substrate layer **2002**.

First material layer **2006** is positioned between first plastic layer **2004** and second material layer **2008**. Second material layer **2008** is positioned between first material layer **2006** and second plastic layer **2010**.

When first material layer **2006** is the explosive material, second material layer **2008** is the neutralizer material. When first material layer **2006** is the neutralizer material, second

material layer **2008** is the explosive material. The neutralizer material is selected and processed to have the same color, density, dry weight, and grain size as the explosive material so that the junction between first material layer **2006** and second material layer **2008** is formed as an indiscernible boundary layer. The ratio of explosive material to neutralizer material is such that, if explosive material and neutralizer material were removed from pyrotechnic pigeon **2000** and mixed, then the resulting mixture would have substantially reduced usefulness as a propellant or explosive, such as in an improvised explosive device.

Second plastic layer **2010** is placed onto second material layer **2008** and substrate layer **2002**. Second plastic layer **2010** surrounds the outer edges of each of first plastic layer **2004**, first material layer **2006**, and second material layer **2008**. Second plastic layer **2010** protects and supports first material layer **2006** and second material layer **2008**. Combined, first plastic layer **2004** and second plastic layer **2010** operate to seal, protect, and encapsulate first material layer **2006** and second material layer **2008** from external moisture and humidity.

First plastic layer **2004** and second plastic layer **2010** may be homogeneous or heterogeneous and comprise any form of plastic, including: acrylic, acrylonitrile butadiene styrene (ABS), diallyl-phthalate (DAP), epoxy resin, high impact polystyrene (HIPS), high-density polyethylene (HDPE), low-density polyethylene (LDPE), medium-density polyethylene (MDPE), melamine resin, phenol formaldehyde resin (PF), polyactic acid (PLA), polyamide (PA) (nylon), polybenzimidazole (PBI), polycarbonate (PC), polycyanurate, polyester (PE), polyether sulfone (PES), polyetherether ketone (PEEK), polyetherimide (PEI), polyethylene (PE), polyethylene terephthalate (PET), polyimide (PI), polymethyl methacrylate (PMMA), polyphenylene oxide (PPO), polyphenylene sulfide (PPS), polypropylene (PP), polystyrene (PS), polytetrafluoroethylene (PTFE), polyurethane (PU), polyvinyl chloride (PVC), polyvinylidene chloride (PVDC), urea-formaldehyde, and vulcanized rubber. In one preferred embodiment, first plastic layer **2004** comprises an acrylic resin and is enhanced for adhesive properties to ensure the combination of first plastic layer **2004**, first material layer **2006**, second material layer **2008**, and second plastic layer **2010** adheres to substrate layer **2002**. Second plastic layer **2010** is enhanced for brittleness to protect the placement and positioning of the combination of first plastic layer **2004**, first material layer **2006**, second material layer **2008**, and second plastic layer **2010** on top of substrate layer **2002** during transport and handling.

Referring to FIGS. **21A** to **21I**, FIG. **21A** is a flow chart depicting steps used to create a pyrotechnic pigeon, such as pyrotechnic pigeon **2000** of FIG. **20**, and FIGS. **21B** to **21I** are cross section views of a pyrotechnic pigeon as it is being built with the steps of FIG. **21A**.

At step **2102**, an explosive material is chosen to be used for the pyrotechnic pigeon. The proper explosive material will be chosen based on its intended use and may be selected from the explosive compounds from Table 5. In one preferred embodiment, explosive material includes black powder and one or more pyrotechnic stars that become visible when the pyrotechnic pigeon is hit. In another preferred embodiment, explosive material includes flash powder to create a visible flash and audible noise when the pyrotechnic pigeon is hit.

At step **2104**, the properties of the explosive material are identified, which include the color, weight, density, and grain size of the explosive material in its final dry form in the pyrotechnic pigeon.



At step 2106, the explosive material is prepared for processing. In one preferred embodiment, the explosive material is formed as an explosive slurry that can be particlized or sprayed onto a surface.

At step 2108, a neutralizer material is chosen to be used for the pyrotechnic pigeon. The neutralizer material chosen has similar properties as the explosive material or can be processed to have properties that are substantially similar to the properties of the explosive material.

At step 2110, the neutralizer material is prepared for processing. If the neutralizer material chosen does not have an appropriate color, then a pigment is added to the neutralizer material that give the neutralizer material a color that is substantially the same as or is indiscernible from the color of the explosive material. In one preferred embodiment, the neutralizer material is formed as a neutralizer slurry that can be particlized or sprayed onto a surface.

At step 2112, substrate layer 2002 (shown in FIG. 21B) is formed. In one preferred embodiment, substrate layer 2002 is formed by compacting a mixture of pitch and pulverized limestone in a mold to form the shape of the substrate layer 2002. In another preferred embodiment, substrate layer 2002 is a pre-manufactured clay pigeon.

At step 2114, outer guide 2130 (shown in FIG. 21C) is placed onto substrate layer 2002. In one preferred embodiment, outer guide 2130 is cylindrically shaped and includes step-shaped edge 2132 that matches a portion of step-shaped edge 2012 of substrate layer 2002. Matching step-shaped edge 2132 of outer guide 2130 to the portion of step-shaped edge 2012 of substrate layer 2002 centers and seals outer guide 2130 to substrate layer 2002 so that material applied within outer guide 2130 is appropriately placed onto substrate layer 2002 without leaking onto or reaching step-shaped edge 2012 of substrate layer 2002. In certain embodiments, shapes other than or in addition to a step are used to match or key outer guide 2130 to substrate layer 2002.

At step 2116, inner guide 2134 (shown in FIG. 21D) is placed onto substrate layer 2002 within outer guide 2130. Inner guide 2134 is cylindrically shaped with an outer circumference that is similar to the inner circumference of outer guide 2130 so that inner guide 2134 fits within outer guide 2130 and is centered with respect to outer guide 2130 and to substrate layer 2002. A bottom edge of inner guide 2134 contacts a top surface of substrate layer 2002 to prevent material applied within inner guide 2134 from reaching outer guide 2130 on the top surface of substrate layer 2002.

At step 2118, first plastic layer 2004 (shown in FIG. 21E) is formed. In one preferred embodiment, first plastic layer 2004 is sprayed onto substrate layer 2002 within inner guide 2134. Inner guide 2134 prevents the application of first plastic layer 2004 from reaching the inner edge of outer guide 2130.

At step 2120, first material layer 2006 (shown in FIG. 21F) is formed. In one preferred embodiment, first material layer 2006 is an explosive material that is sprayed onto first plastic layer 2004 within inner guide 2134. Inner guide 2134 prevents the application of first material layer 2006 from reaching the inner edge of outer guide 2130.

At step 2122, second material layer 2008 (shown in FIG. 21G) is formed. In one preferred embodiment, second material layer 2008 is a neutralizer material that is sprayed onto first material layer 2006 within inner guide 2134. Inner guide 2134 prevents the application of second material layer 2008 from reaching the inner edge of outer guide 2130.

At step 2124, inner guide 2134 is removed (shown in FIG. 21H). Removing inner guide 2134 exposes outer edges of

first plastic layer 2004, first material layer 2006, and second material layer 2008. Removing inner guide 2134 also exposes the portion of the top surface of substrate layer 2002 that was covered by the bottom surface of inner guide 2134.

At step 2126, second plastic layer 2010 (shown in FIG. 21I) is formed. In one preferred embodiment, second plastic layer 2010 is sprayed so that the application of second plastic layer covers second material layer 2008, reaches the edges of first material layer 2006 and first plastic layer 2004 within outer guide 2130, and reaches the top surface of substrate layer 2002 that was covered by the bottom surface of inner guide 2134. Outer guide 2130 prevents the application of second plastic layer 2010 from reaching step-shaped edge 2012 of substrate layer 2002.

At step 2128, outer guide 2130 is removed from the fully formed pyrotechnic pigeon, such as pyrotechnic pigeon 2000 (shown in FIG. 20). Removing outer guide 2130 exposes the outer edge of second plastic layer 2010 and the portion of the top surface of substrate layer 2002 that was covered by the bottom surface of outer guide 2130.

It will be appreciated by those skilled in the art that modifications can be made to the embodiments disclosed and remain within the inventive concept. Therefore, this invention is not limited to the specific embodiments disclosed, but is intended to cover changes within the scope and spirit of the claims.

The invention claimed is:

1. A method of forming a pyrotechnic device, comprising the steps of:

- choosing an explosive material having a first set of properties; wherein the first set of properties comprises one or more of color and grain size of the explosive material in a dry form;
- choosing a neutralizer material having a second set of properties which approximate the one or more of color and grain size of the first set of properties;
- forming an indiscernible boundary interface within the pyrotechnic device and between the explosive material and the neutralizer material; wherein the indiscernible boundary interface is visually indiscernible with unassisted vision;
- forming a substrate layer; and,
- forming a plastic layer between the substrate layer and one of the explosive material and the neutralizer material.

2. The method of claim 1 wherein the step of choosing a neutralizer material further comprises choosing a ratio of a first weight of the explosive material to a second weight of the neutralizer material sufficient to reduce an explosiveness of the explosive material when the neutralizer material is mixed with the explosive material outside of the pyrotechnic device.

3. The method of claim 1 further comprising:

- placing an outer guide onto the substrate layer and matching the outer guide to a step-shaped edge of the substrate layer;
- placing an inner guide onto the substrate layer within the outer guide; and,
- forming the plastic layer on the substrate layer within the inner guide.

4. The method of claim 3 further comprising:

- preparing the explosive material by forming the explosive material as an explosive slurry;
- preparing the neutralizer material by the steps of: adding a pigment to the neutralizer material; and, forming the neutralizer material as a neutralizer slurry.



## 25

5. The method of claim 3 further comprising:  
forming a first material layer on the plastic layer within  
the inner guide;  
forming a second material layer on the first material layer  
within the inner guide; and,  
wherein when the first material layer comprises the explo-  
sive material, the second material layer comprises the  
neutralizer material; or,  
wherein when the first material layer comprises the neu-  
tralizer material, the second material layer comprises  
the explosive material.

6. The method of claim 5 further comprising:  
removing the inner guide from the substrate layer and the  
outer guide; and,  
forming a second plastic layer on the substrate layer and  
the second material layer within the outer guide.

7. The method of claim 6 further comprising:  
removing the outer guide.

8. The method of claim 1:  
wherein the step of choosing a neutralizer material further  
comprises choosing the second set of properties from  
the group of grain size, weight, density, and color.

9. The method of claim 1:  
wherein the step of choosing an explosive material further  
comprises the step of combining about 70% potassium  
chlorate and about 30% aluminum by weight; and,  
wherein the step of choosing the neutralizer material  
further comprises the step of combining about 65%

## 26

magnesium silicate, about 30% aluminum, and about  
5% ackroyd resin by weight.

10. The method of claim 1 wherein the step of forming the  
indiscernible boundary interface further comprises the step  
of applying a ratio of the explosive material to the neutral-  
izer material of about 3:2 by weight.

11. A method of forming a pyrotechnic device, comprising  
the steps of:

choosing an explosive material having a first set of  
properties;

wherein the first set of properties comprises one or more  
of color, grain size, and density of the explosive mate-  
rial in a dry form;

choosing a neutralizer material having a second set of  
properties which approximate the one or more of color,  
grain size, and density of the first set of properties;

forming an indiscernible boundary interface within the  
pyrotechnic device and between the explosive material  
and the neutralizer material;

wherein the first set of properties is visually indiscernible  
from the second set of properties by unassisted vision;

forming a substrate layer; and,  
forming a plastic layer between the substrate layer and  
one of the explosive material and the neutralizer mate-  
rial.

\* \* \* \* \*