

US010296089B2

(12) **United States Patent**  
**Peretz et al.**

(10) **Patent No.:** **US 10,296,089 B2**  
(45) **Date of Patent:** **May 21, 2019**

- (54) **HAPTIC STYLUS** 7,456,826 B2 \* 11/2008 Jurisch ..... G06F 3/03542  
345/179
- (71) Applicant: **Microsoft Technology Licensing, LLC,** 7,511,706 B2 \* 3/2009 Schena ..... G01D 7/007  
Redmond, WA (US) 178/19.01
- (72) Inventors: **Ahia Peretz,** Ramat-Gan (IL); **Vadim** 7,522,152 B2 \* 4/2009 Olien ..... G06F 3/016  
**Mishalov,** Tel-Aviv (IL) 345/156
- (73) Assignee: **Microsoft Technology Licensing, LLC,** 7,679,611 B2 \* 3/2010 Schena ..... G01D 7/007  
Redmond, WA (US) 345/179
- 8,416,066 B2 \* 4/2013 Westerinen ..... G06F 3/016  
340/407.1
- 8,525,530 B2 \* 9/2013 Fukushima ..... H01G 5/16  
324/658

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

**FOREIGN PATENT DOCUMENTS**

- (21) Appl. No.: **15/232,955** CN 203415124 1/2014
- WO 2014/117125 7/2014

(22) Filed: **Aug. 10, 2016**

**OTHER PUBLICATIONS**

(65) **Prior Publication Data**  
US 2018/0046249 A1 Feb. 15, 2018

Hinckley et al. "Motion and Context Sensing Techniques for Pen Computing", Proceedings of Graphics Interface, p. 71-78, May 29, 2013.

(51) **Int. Cl.**  
**G06F 3/01** (2006.01)  
**G06F 3/0354** (2013.01)

(Continued)

(52) **U.S. Cl.**  
CPC ..... **G06F 3/016** (2013.01); **G06F 3/03545**  
(2013.01)

*Primary Examiner* — Michael J Jansen, II

(58) **Field of Classification Search**  
CPC ..... G06F 3/03545; G06F 3/016; G06F 3/041;  
G06F 2203/015; G06F 3/0412  
See application file for complete search history.


(57) **ABSTRACT**

A device includes a housing, a tip configured to be movable with respect to the housing, a resilient element fixed to the tip, a substrate fixed to the housing, a coil mounted or patterned on the substrate, and a controller configured to induce haptic feedback via the tip based on applying a signal to the coil. A surface of the substrate faces the resilient element. The resilient element presses against the surface in response to the tip receding toward the housing. The resilient element includes magnetic material. The signal applied on the coil induces a magnetic driving force on the resilient element.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**

**20 Claims, 8 Drawing Sheets**

- 3,376,551 A \* 4/1968 Armbruster ..... B41J 3/00  
178/18.07
- 5,565,632 A \* 10/1996 Ogawa ..... G06F 3/03545  
73/862.041
- 7,202,862 B1 \* 4/2007 Palay ..... G06F 3/03545  
178/18.01



(56)

References Cited

U.S. PATENT DOCUMENTS

8,525,816 B2 \* 9/2013 Fukushima ..... G06F 3/03545  
178/18.01  
8,803,671 B2 \* 8/2014 Westerinen ..... G06F 3/016  
340/407.1  
8,884,932 B2 \* 11/2014 Fukushima ..... G06F 3/03545  
178/19.04  
8,913,041 B2 \* 12/2014 Fukushima ..... G06F 3/03545  
345/179  
8,952,939 B2 \* 2/2015 Lee ..... B44F 11/02  
345/179  
9,098,131 B2 \* 8/2015 Jeong, II ..... G06F 3/044  
9,201,520 B2 12/2015 Benko et al.  
9,239,622 B2 \* 1/2016 Park ..... G06F 3/016  
9,261,990 B2 \* 2/2016 Choi ..... G06F 3/041  
9,298,285 B2 \* 3/2016 Mohindra ..... G06F 3/03545  
9,310,898 B2 \* 4/2016 Son ..... G06F 3/03545  
9,395,862 B2 \* 7/2016 Kim ..... G06F 3/041  
9,483,120 B2 \* 11/2016 Park ..... G06F 3/016  
9,495,011 B1 \* 11/2016 Lee ..... G06F 3/016  
9,513,719 B2 \* 12/2016 Ito ..... G06F 3/044  
9,513,721 B2 \* 12/2016 Stern ..... G06F 3/03545  
9,529,458 B2 \* 12/2016 Obata ..... G06F 3/03545  
9,569,041 B2 \* 2/2017 Son ..... G06F 3/046  
9,575,572 B2 \* 2/2017 Park ..... G06F 3/041  
9,690,377 B2 \* 6/2017 Lee ..... G06F 3/016  
9,690,398 B2 \* 6/2017 Li ..... G06F 3/03545  
9,727,150 B2 \* 8/2017 Stern ..... G06F 3/03545  
9,829,987 B2 \* 11/2017 Bandt-Horn ..... G06F 3/0202  
9,841,828 B2 \* 12/2017 Peretz ..... G06F 3/03545  
9,864,440 B2 \* 1/2018 Geller ..... G06F 3/03545  
9,874,951 B2 \* 1/2018 Stern ..... G06F 3/044  
9,898,101 B2 \* 2/2018 Ishikawa ..... G06F 3/03545  
2001/0038384 A1 \* 11/2001 Fukushima ..... G06F 3/03545  
345/179  
2005/0104870 A1 \* 5/2005 Jurisch ..... G06F 3/03542  
345/179  
2005/0248549 A1 \* 11/2005 Dietz ..... G06F 3/016  
345/179  
2005/0275967 A1 \* 12/2005 Olien ..... G06F 3/016  
345/156  
2008/0143693 A1 \* 6/2008 Schena ..... G01D 7/007  
345/179  
2009/0184923 A1 \* 7/2009 Schena ..... G01D 7/007  
345/156  
2009/0251623 A1 \* 10/2009 Koyama ..... G06F 3/03545  
348/789  
2010/0160041 A1 6/2010 Grant et al.  
2011/0241703 A1 \* 10/2011 Fukushima ..... H01G 5/16  
324/662  
2011/0267182 A1 \* 11/2011 Westerinen ..... G06F 3/016  
340/407.2  
2011/0304577 A1 \* 12/2011 Brown ..... G06F 3/03545  
345/174  
2012/0098798 A1 \* 4/2012 Lee ..... G06F 3/03545  
345/179  
2012/0280947 A1 11/2012 Weaver et al.  
2013/0088465 A1 \* 4/2013 Geller ..... G06F 3/03545  
345/179  
2013/0147748 A1 \* 6/2013 Westerinen ..... G06F 3/016  
345/173  
2013/0222294 A1 \* 8/2013 Choi ..... G06F 3/041  
345/173  
2013/0307829 A1 \* 11/2013 Libin ..... G06F 3/016  
345/179  
2014/0028592 A1 \* 1/2014 Wang ..... G06F 3/03545  
345/173  
2014/0043242 A1 2/2014 Dietz et al.  
2014/0078105 A1 \* 3/2014 Son ..... G06F 3/046  
345/174

2014/0132529 A1 \* 5/2014 Jeong, II ..... G06F 3/044  
345/173  
2014/0146021 A1 5/2014 Trethewey et al.  
2014/0168124 A1 \* 6/2014 Park ..... G06F 3/016  
345/173  
2014/0168175 A1 6/2014 Mercea et al.  
2014/0210756 A1 \* 7/2014 Lee ..... G06F 3/016  
345/173  
2014/0210781 A1 7/2014 Stern  
2014/0218338 A1 \* 8/2014 Kim ..... G06F 3/041  
345/174  
2014/0245139 A1 \* 8/2014 Lee ..... G06F 3/0488  
715/702  
2014/0285453 A1 \* 9/2014 Park ..... G06F 3/016  
345/173  
2014/0292696 A1 \* 10/2014 Son ..... G06F 3/03545  
345/173  
2014/0333553 A1 \* 11/2014 Yun ..... G06F 3/016  
345/173  
2015/0015499 A1 \* 1/2015 Park ..... G06F 3/041  
345/173  
2015/0029161 A1 \* 1/2015 Koo ..... B43K 29/00  
345/179  
2015/0035807 A1 \* 2/2015 Ito ..... G06F 3/044  
345/179  
2015/0070330 A1 \* 3/2015 Stern ..... G06F 3/03545  
345/179  
2015/0084934 A1 \* 3/2015 Ho ..... G06F 3/03545  
345/179  
2015/0084935 A1 \* 3/2015 Lien ..... G06F 3/03545  
345/179  
2015/0097815 A1 \* 4/2015 Lee ..... G06F 3/03545  
345/179  
2015/0116289 A1 \* 4/2015 Stern ..... G06F 3/03545  
345/179  
2015/0160744 A1 \* 6/2015 Mohindra ..... G06F 3/03545  
345/179  
2015/0169056 A1 6/2015 Weddle et al.  
2015/0205367 A1 \* 7/2015 Bandt-Horn ..... G06F 3/0202  
345/156  
2015/0212578 A1 \* 7/2015 Lor ..... G06F 3/016  
345/173  
2015/0309598 A1 10/2015 Zelif et al.  
2015/0317001 A1 \* 11/2015 Ben-Bassat ..... G06F 3/03545  
345/179  
2015/0346849 A1 \* 12/2015 Obata ..... G06F 3/03545  
345/179  
2016/0054820 A1 2/2016 Sezgin et al.  
2016/0124530 A1 \* 5/2016 Stern ..... G06F 3/03545  
345/179  
2016/0132118 A1 \* 5/2016 Park ..... G06F 3/016  
345/173  
2016/0274684 A1 \* 9/2016 Li ..... G06F 3/03545  
2016/0282970 A1 \* 9/2016 Evreinov ..... G06F 3/03545  
2016/0364024 A1 \* 12/2016 Lien ..... G06F 1/26  
2017/0045961 A1 \* 2/2017 Stern ..... G06F 3/03545  
2017/0068345 A1 \* 3/2017 Barel ..... G06F 3/03545  
2017/0108956 A1 \* 4/2017 Tang ..... B43K 24/00  
2017/0242501 A1 \* 8/2017 Tang ..... G06F 3/03545  
2017/0285774 A1 \* 10/2017 Parikh ..... G06F 3/03545  
2018/0046249 A1 \* 2/2018 Peretz ..... G06F 3/03545

OTHER PUBLICATIONS

Perez "Active Pen Haptic: Polymer Actuator", Microsoft Surface, p. 1-10, 2015.  
Wacker Chemie AG "Silicones With Magnetic Properties", Wacker Chemie AG, Innovations Magazine, 2 P., Mar. 30, 2016.  
International Search Report and the Written Opinion Dated Oct. 25, 2017 From the International Searching Authority Re. Application No. PCT/US2017/045004. (13 Pages).

\* cited by examiner





FIG. 1



**FIG. 2**




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4A




FIG. 4B




FIG. 5A






FIG. 5B







**FIG. 6A**



**FIG. 6B**



**FIG. 6C**



**FIG. 7**

## 1

## HAPTIC STYLUS

## FIELD AND BACKGROUND OF THE INVENTION

Signal emitting styluses such as active styluses, are known in the art for use with a digitizer system. Positions of the stylus provide inputs to a computing device associated with the digitizer system and are interpreted as user commands. Often, the digitizer system is integrated with a display screen to form a touch-screen.

Digitizer systems may include a matrix of electrode junctions arranged in rows and columns. Tracking is typically based on detecting a signal emitted at a tip of the stylus and picked up by the digitizer sensor due to electrostatic coupling established between the tip and a portion of the matrix.

## SUMMARY OF THE INVENTION

The disclosure in some embodiments relates to a haptic actuator that is integrated into a handheld device and to a handheld device including the haptic actuator. The handheld device may be for example a stylus configured to interact with a computing device that includes a digitizer system, e.g., a touch enabled computing device. In some exemplary embodiments, the haptic actuator provides haptic feedback by actuating movement of a tip of the handheld device.

Alternatively, the haptic actuator may actuate movement of another element of the handheld device that is movable with respect to a housing of the handheld device. Movement may be actuated along a single axis or may be selectively actuated in three dimensions (3D). Haptic feedback may be defined based on pressure applied on the tip, velocity of the handheld device, tilt angle of the handheld device, button selection on the handheld device and input from a touch enabled computing device that is interacting with the handheld device.

According to some exemplary embodiments, the haptic actuator includes an electromagnet and a permanent magnet that are magnetically coupled to each other.

According to some embodiments of the present disclosure, the permanent magnet is a resilient element attached to the tip that is used to both provide a resilient response to contact pressure applied on the tip and to actuate the haptic feedback. Activation of the haptic actuator may be controlled by controlling input to the electromagnet to generate a magnetic field that actuates movement of the permanent magnet. In some exemplary embodiments, the permanent magnet has conductive properties and is also operated as an electrode for detecting pressure applied on the tip based on a sensed capacitive coupling between the permanent magnet and another conductive element that is stationary with respect to a housing of the stylus.

Unless otherwise defined, all technical and/or scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art. Although methods and materials similar or equivalent to those described herein can be used in the practice or testing of embodiments of the disclosure, exemplary methods and/or materials are described below. In case of conflict, the patent specification, including definitions, will control. In addition, the materials, methods, and examples are illustrative only and are not intended to be necessarily limiting.

## BRIEF DESCRIPTION OF THE SEVERAL VIEWS DRAWINGS

Some embodiments of the disclosure are herein described, by way of example only, with reference to the accompanying

## 2

drawings. With specific reference now to the drawings in detail, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of embodiments of the disclosure. In this regard, the description taken with the drawings makes apparent to those skilled in the art how embodiments of the disclosure may be practiced.

In the drawings:

FIG. 1 is a simplified block diagram of an exemplary stylus in accordance with some embodiments of the present disclosure;

FIG. 2 showing a simplified flow chart of an exemplary method for operating a stylus in accordance with some exemplary embodiments of the present disclosure;

FIGS. 3A and 3B are simplified schematic drawings of elements of a uni-axial haptic actuator including a resilient element shown in a neutral and compressed state respectively in accordance with some embodiments of the present disclosure;

FIG. 3C is a simplified schematic drawing of an electromagnet of the haptic actuator in accordance with some embodiments of the present disclosure;

FIGS. 4A and 4B are simplified schematic drawing of a uni-axial haptic actuator including a cylindrical coil and a simplified schematic drawing of an exemplary cylindrical coil in accordance with some embodiments of the present disclosure;

FIGS. 5A and 5B are simplified schematic drawing of a 3D haptic actuator in accordance with some embodiments of the present disclosure;

FIGS. 6A, 6B and 6C are simplified schematic drawings of an exemplary permanent magnet, an exemplary wall of the pyramid structure integrated with a coil and an alternate exemplary wall integrated with a exemplary coil and electrode all in accordance with some embodiments of the present disclosure; and

FIG. 7 is a simplified flow chart of an exemplary method for providing 3D haptic feedback in accordance with some exemplary embodiments of the present disclosure.

## DESCRIPTION OF SPECIFIC EMBODIMENTS OF THE INVENTION

According to some exemplary embodiments, haptic feedback in a handheld device is generated by actuating movement of a resilient element that is also configured to provide a resilient response to contact pressure applied on an interacting element of the device. Optionally, the device is a stylus and the interacting element is a writing tip of the stylus. In some exemplary embodiments, the resilient element presses against a substrate that is fixed to a housing of the device when pressure is applied. Typically, the resilient element is magnetized. The resilient element may be magnetized, for example, by embedding the resilient material with magnetic particles. A coil positioned in the device may be operated as an electromagnet to generate a magnetic field that actuates movement of the resilient element. The coil may be a planar coil or flat coil patterned on the substrate that the resilient element presses against, or may be a 3D coil that encompasses the resilient element. In this manner, haptic feedback feature may be added to a handheld device without significantly increasing space, number of parts, and cost for manufacturing the handheld device. Typically, the resilient response of resilient element **150** (shown in FIG. 1) facilitate the movement required for haptic feedback.

In some exemplary embodiments, uni-axial haptic feedback is provided with a generally flat resilient element

coupled to a coil that is patterned or mounted on the substrate on which the resilient element presses against. The coil may be interchangeably operated as an electromagnet and as an electrode. Optionally, when the coil is operated as an electromagnet, the electromagnet may actuate movement of the resilient element in one direction and the resilient element may respond by pushing in the opposite direction. Optionally, 3D haptic feedback is provided with a rounded resilient element that presses against more than one substrate, each substrate angled in different directions and associated with a coil that may be selectively controlled to operate simultaneously or separately. Each coil may be operated as an electromagnet and may actuate movement in a defined direction.

According to some exemplary embodiments, the resilient element is conductive and is also used to monitor contact pressure applied on the interacting element. Typically, the interacting element is the writing tip. Optionally, the resilient element is positioned and sized to be capacitively coupled with the coil or with a dedicated electrode and to effect changes in capacitive coupling based on its deformation under pressure. Changes in the capacitive coupling may be detected and related to pressure applied on the interactive element on which the resilient element is fixed.

According to some exemplary embodiments, a handheld device initiates haptic feedback based on one or more of pressure applied on its interacting element, velocity of the handheld device, tilt angle of the handheld device, button selection on the handheld device, and input from a touch enabled computing device that is interacting with the handheld device. In some exemplary embodiments, amplitude and frequency of a signal applied to actuate the feedback and direction at which the element is moved may be selectively controlled based on a command that is received by the handheld device or based on output from one of more sensors or buttons included in the handheld device. Optionally, the handheld device is a stylus and haptic feedback is provided by actuating movement of the writing tip of the stylus.

Reference is now made to FIG. 1 showing a simplified block diagram of an exemplary stylus and a touch enabled computing device in accordance with some embodiments of the present disclosure. Stylus 200 may typically be an active stylus that communicates with a digitizer sensor 15 of computing device 10 by transmitting signals 110 via its tip 100. The signals emitted by the stylus may include information such as detected pressure applied on the writing tip and stylus identification. Signals encoded with information may be decoded by the digitizer system. Positions of the stylus over the touch-screen may be correlated with virtual information portrayed on the screen. The stylus may also directly communicate with the computing device via other wireless communication channels, e.g. Bluetooth and near field communication (NFC).

In some exemplary embodiments, a transmitter 40 in stylus 200 generates signals 110 based on input from controller 30. Operation of stylus 200 is typically controlled by controller 30 and powered by power source 20.

Typically, signals 110 that are transmitted via tip 100 may be picked up by the digitizer sensor 15 due to electrostatic coupling established between tip 110 and a portion of digitizer sensor 15 near tip 110. Signals 110 may be beacon signals for tracking a location of tip 100 on the digitizer sensor 15 or signals encoded with information. Optionally, stylus 200 may additionally include a wireless modem 50 that may communicate with a corresponding modem 18 of computing device 10 to exchange information and commu-

nicate commands. Stylus 200 may also include one or more user selection buttons 50 and one or more sensors for detecting button selection of button 50, tilt of stylus 200, or battery state. One or more circuits 12 associated with device 10 may control and process information that is communicated between stylus 200 and device 10.

According to some exemplary embodiments of the present disclosure, stylus 200 also provides haptic feedback to a user by actuating movement of a resilient element 150 attached to tip 100. The actuated movement is typically with respect to housing 250. Tip 100 is typically movable in longitudinal direction 101 of stylus 200 and may optionally have some degree of movement in directions 102 that are perpendicular to longitudinal direction 101. Resilient element 150 is typically pressed against a structural element 260 fixed to housing 250 and provides a resilient response as tip 100 recedes into housing 250 due to contact pressure applied on tip 100.

According to some exemplary embodiments of the present disclosure, resilient element 150 is magnetized and moves in response to magnetic fields generated with a coil 220.

Typically, controller 30 controls the signals generated by transmitter 40 for activating coil 220. In some exemplary embodiments, controller 30 alternates between transmitting a signal 110 via tip 100 for communication with digitizer sensor 15 and transmitting a signal to coil 220 for actuating haptic feedback.

In some exemplary embodiments, pressure applied on tip 100 is sensed by stylus 200. Optionally, resilient element 150 includes or is formed with conductive material and pressure is monitored based on a detected capacitive coupling between resilient element 150 and an electrode fixed to surface 260 or fixed with respect to housing 250. Typically controller 30 controls electrifying resilient element 150 and sampling output from the electrode to detect capacitive coupling. Optionally, coil 220 may be operated as the electrode and controller 30 may intermittently detect capacitive coupling between resilient element 150 and coil 220 to monitor pressure applied on tip 100. In some exemplary embodiments, resilient element 150 and tip 100 are electrically connected and pressure sensing is performed based on signals 110 transmitted on tip 100.

Reference is now made to FIG. 2 showing a simplified flow chart of an exemplary method for operating a stylus in accordance with some exemplary embodiments of the present disclosure. According to some exemplary embodiments, a controller 30 alternates between transmitting a signal 110 on tip 100 (block 270) for communicating with a digitizer sensor and transmitting a signal on coil 220 to actuate haptic feedback (block 280). In some exemplary embodiments, pressure applied on tip 100 is sensed during transmission of signal 110 (block 275). In some exemplary embodiments, the haptic feedback provided is based on or is a function of the sensed pressure. In some exemplary embodiments, the haptic feedback provided is based on input for a tilt sensor included in stylus 200, a button selection on stylus 200, based on information received from computing device 10 via wireless modem 50 or based on information stored in memory associated with controller 30. Typically, the haptic feedback provided is defined based on amplitude, frequency and duration of the signal transmitted on coil 220.

Reference is now made to FIGS. 3A and 3B showing simplified schematic drawings of elements of a uni-axial haptic actuator including a resilient element shown in a neutral and compressed state respectively and to FIG. 3C showing a simplified schematic drawing of a coil of the

haptic actuator in accordance with some embodiments of the present disclosure. According to some embodiments of the present disclosure, a haptic actuator **300** includes a coil **220** that may be operated as an electromagnet to actuate movement of a resilient element **150**. Typically, resilient element **150** is a resilient or deformable permanent magnet that responds to magnetic fields generated by coil **220**. In some exemplary embodiments, resilient element **150** may be an elastomer, e.g., silicone, that is embedded with magnetic particles **155**.

Optionally, resilient element **150** is a magnetite filled high consistency rubber such as ELASTOSIL® R 781/80 provided by WACKER. Typically, tip **100** moves together with resilient element **150** to provide the haptic feedback felt by the user.

In some exemplary embodiments, resilient element **150** is a flat disk shaped element and that is supported on tip **100** with a flange member **120** that extends from tip **100**. Optionally, resilient element **150** includes a wall that tapers in a direction distal to flange member **120**.

In some exemplary embodiments, a substrate **180** fixed to a structural element **210** of housing **250** is positioned to face resilient element **150** so that resilient element **150** presses against substrate **180** as contact pressure is applied on tip **100** in a direction that forces tip **100** to recede toward housing **250**. In some exemplary embodiments, a surface **151** of resilient element **150** that makes contact with substrate **180** increases its surface area as resilient element **150** presses against substrate **180**. (FIG. 3B) Typically, compression of resilient element **150** and movement of tip **100** is uni-axial along longitudinal direction **101**.

According to some embodiments of coil **220** is mounted or patterned on a surface of substrate **180**. In some exemplary embodiments, coil **220** is patterned on a surface of substrate **180** that is distal from resilient element **150** or is otherwise physically separated from resilient element **150** with a layer of non-conductive or dielectric material included in substrate **180**. According to some exemplary embodiments, a signal transmitted in coil **220** generates a magnetic field that actuates movement of resilient element **150** together with tip **100** along the longitudinal axis **101**. A magnetic field is typically generated on coil **220** by applying voltage between terminals of coil **220**, e.g., terminal **211A** and terminal **211B**, so that current flows through coil **220**. The haptic feedback provided may be defined based on a frequency and amplitude of the applied signal. Typically, the voltage and frequency applied on coil **220** for magnifying the coil is significantly lower than the voltage and frequency applied on tip **100** for transmitting a signal to digitizer sensor **15** while the current applied on coil **220** for magnifying may be significantly higher. In some exemplary embodiments, magnetic coupling between coil **220** and resilient element increases as resilient element **150** flattens up against substrate **180** and weakens as the resilient element is restored to its neutral shape. Optionally, haptic feedback is intensified with an increase in magnetic coupling. Alternatively, the magnetic coupling is not altered by deformation of resilient element **150**.

In some exemplary embodiments, coil **220** may also be operated as an electrode and pressure applied on tip **100** may be detected based on detected capacitive coupling between resilient element **150** and coil **220**. The capacitive coupling typically increases with increasing pressure due to movement and deformation of resilient element **150** toward coil **220**. While operating coil **220** to detect pressure, terminal **211A** and **211B** may typically be shorted so that a same voltage is applied on coil **220**. Capacitive coupling may then

be detected by applying a signal on coil **220** and detecting a corresponding output on resilient element **150** or by applying a signal on resilient element **150** and detecting a corresponding output on coil **220**.

Typically, resilient element **150** is conductive or includes conductive elements and is capacitively coupled with conductive material of electromagnet **220** based on proximity and area of overlap between the elements. Typically, a level of capacitive coupling is sensitive to deformation of resilient element **150**. As resilient element is pressed against substrate **150** overlap between a surface area of resilient element **150** and coil **220** increases which typically increases the capacitive coupling. Optionally, resilient element **150** is electrically connected to tip **100** and output from coil **220** may be detected during signal transmission on tip **100** for detecting a level of capacitive coupling.

Reference is now made to FIGS. 4A and 4B showing a simplified schematic drawing of a uni-axial haptic actuator including a cylindrical coil and a simplified schematic drawing of an exemplary cylindrical coil in accordance with some embodiments of the present disclosure. According to some exemplary embodiments, haptic actuator **305** includes a coil **212**, e.g., a magnetic coil, that is wrapped around resilient element **150** as opposed to being patterned on substrate **180**. Coil **212** may be a cylindrically shaped coil that is mounted on substrate **180** and encompasses resilient element **150**. Typically, haptic actuator **301** actuates movement of resilient element **150** with tip **100** along longitudinal direction **101** similar to the movement provided by haptic actuator **300** (FIGS. 3A and 3B).

According to some exemplary embodiments of the present disclosure, substrate **180** includes a dedicated electrode **190** for detecting pressure applied on tip **100** based on capacitive coupling with resilient element **150**. Optionally, electrode **190** may be an electrode that is patterned on substrate **180**. In some exemplary embodiments, controller **150** may periodically apply a signal on resilient element **150** or electrode **190** to detect the capacitive coupling between resilient element **150** and electrode **190** and thereby monitor pressure as described for example in reference to FIGS. 3A, 3B and 3C.

Reference is now made to FIGS. 5A and 5B showing simplified schematic drawing of a 3D haptic actuator, to FIGS. 6A and 6B showing simplified schematic drawings of an exemplary coil embedded in a wall of the pyramid structure, and to FIG. 6C showing an exemplary magnetized elastomer head, all in accordance with some embodiments of the present disclosure.

According to some exemplary embodiments, writing tip **100** is an elongated element that extends into housing **250** through a collar **310**. A resilient element **320** may be fixedly attached to an end of tip **100** and fitted into a hollow pyramid structure **400**. Typically, pyramid structure **400** is fixedly attached to housing **250**. Resilient element **320** may be a substantially rounded, e.g., spherical or hemispherical, and may press against each wall **330** of pyramid structure **400**. Deformation of resilient element **320** is typically based on movement or tilt of tip **100** with respect to pyramid structure **400** and housing **250**. Writing tip **100** may tilt against collar **310** of housing **250** as well as slide through collar **310** while resilient element **320** provides a resilient reaction force in 3D as it compresses against walls **330**.

According to some exemplary embodiments, a haptic actuator **500** includes a plurality of coils, each coil **510** of the plurality integrated on a wall **330** of pyramid structure **400** (FIG. 6B) and a rounded resilient element **320** that is magnetized. In some exemplary embodiments, resilient ele-

ment **320** may be an elastomer, e.g., silicon, that is embedded with magnetic particles **155**. Optionally, resilient element **320** is a magnetite filled high consistency rubber such as ELASTOSIL® R 781/80 provided by WACKER. Typically, tip **320** moves together with resilient element **150** to provide the haptic feedback felt by the user.

According to some embodiments, coil **510** may be mounted or patterned on a surface of wall or substrate **330**. In some exemplary embodiments, coil **510** is patterned on a surface of substrate **330** that is distal from resilient element **320** or is otherwise physically separated from resilient element **320** with a layer of non-conductive or dielectric material. According to some exemplary embodiments, a signal transmitted in coil **510** generates a magnetic field that actuates movement of resilient element **320** together with tip **100** in a direction that is perpendicular to wall **330** on which coil **510** is patterned. Coil **510** operates as an electromagnet when the signal is transmitted on coil **510**. Typically, each coil **510** actuate movement in a different direction when magnified due to orientation of wall **330** on which it is patterned. In some exemplary embodiments, movement in a direction along a length of tip **100** is actuated by simultaneously transmitting a same signal on each coil **510**. Coil **510** on each wall **330** may be activated simultaneously or separately to actuate a desired movement pattern of tip **100**. Typically, an intensity and direction of the haptic feedback is based on an amplitude and frequency of a signal transmitted on each coil **510**.

In some exemplary embodiments, a pressure applied by resilient element **320** on pyramid structure **400** may be sensed based on a detected capacitive coupling between resilient element **320** and a conductive element that is integrated on each of walls **330**. In some exemplary embodiments, the conductive element is the conductive material of coil **510**. In other exemplary embodiments, dedicated electrode(s) **515** for sensing pressure is patterned on each of walls **330**.

Optionally, sensed pressure provides 3D input to the haptic actuator and may be used to define or adapt current injected on to coil **510**. Optionally, the haptic feedback may be defined to reflect pressure applied on tip **100** or may be defined in along a same direction as a direction at which the pressure is detected.

Reference is now made to FIG. 7 showing a simplified flow chart of an exemplary method for providing 3D haptic feedback in accordance with some exemplary embodiments of the present disclosure. In some exemplary embodiments, 3D haptic feedback may be defined based on detected pressure on tip **100**, may be defined based on a command received from a computing device, or may be pre-defined and stored in memory associated with the stylus. Typically, controller **30** receives indication to activate the haptic actuator based on output from a sensor of the handheld device or based on a command received from computing device **10** (block **710**). Based on input received with the indication, a controller defines amplitude, frequency and delay for selectively activating each of coil **510** that will provide the desired feedback (block **720**).

According to an aspect of some embodiments of the present invention there is provided a device including: a housing; a tip configured to be movable with respect to the housing; a resilient element fixed to the tip, wherein the resilient element includes magnetic material; a substrate fixed to the housing, wherein a surface of the substrate is positioned to face the resilient element and wherein the resilient element is configured to press against the surface in response to the tip receding toward the housing; a coil

mounted or patterned on the substrate; and a controller configured to induce haptic feedback via the tip based on applying a signal to the coil, wherein the signal applied is configured to induce a magnetic driving force on the resilient element.

Optionally, the resilient element is formed from an elastomer embedded with magnetic particles.

Optionally, the resilient element includes conductive material and is capacitively coupled to conductive material of the coil.

Optionally, an electrode patterned on the substrate, wherein the electrode is positioned on the substrate to be capacitively coupled with the resilient element.

Optionally, the controller is configured to detect changes in the capacitive coupling based on deformation of the resilient element as it presses against the surface.

Optionally, the controller is configured to detect pressure applied on the tip based on the detected capacitive coupling.

Optionally, the haptic feedback is based on the pressure detected.

Optionally, the device includes a tilt sensor and wherein the haptic feedback is based on output from the tilt sensor.

Optionally, the coil is a planar coil that is patterned on the substrate.

Optionally, the device includes a plurality of substrates formed in a pyramid structure, wherein each of at least two substrates is patterned with a planar coil that is magnetically coupled to the resilient element.

Optionally, the resilient element is a rounded element fitted into the pyramid structure and configured to press against each of the substrates of the pyramid structure.

Optionally, the controller is configured to simultaneously apply signals on each of the planar coils, wherein in the signals are either the same signal or signals that differ in at least one of amplitude, frequency and phase.

Optionally, the tip is configured to both tilt and recede into the housing based on contact pressure applied on the tip and wherein the control is configured to apply haptic feedback in three dimensions based on applying signals to each of the planar coils.

Optionally, the controller is configured to detect force applied on the tip in three dimensions based on a detected capacitive coupling between the resilient element and a conductive element on each of the substrates, wherein the conductive element is the planar coil or an electrode patterned on the substrate.

Optionally, the resilient element is a generally flat element that is fixed to the tip at a normal angle with respect to the tip and the coil is mounted on the surface of the substrate and encompassing the resilient element.

According to an aspect of some embodiments of the present invention there is provided a method including: fixing a resilient element to a tip that extends out of a housing and is movable with respect to the housing, wherein the resilient element includes magnetic material; positioning a substrate to face the resilient element, wherein the substrate is fixed to the housing and wherein the resilient element is configured to press against the surface in response to the tip receding toward the housing; wherein the substrate includes a coil that is mounted or patterned on the substrate; and inducing haptic feedback via the tip based on applying a signal on the coil, wherein the signal applied is configured to induce a magnetic driving force on the resilient element.

Optionally, the method includes detecting pressure on the tip based on changes in the capacitive coupling between the resilient element and a conductive element on the substrate,

wherein the changes in capacitive coupling is based on deformation of the resilient element as it presses against the surface.

Optionally, the method includes defining the haptic feedback based on the pressure detected.

Optionally, the method includes fitting the resilient element in a pyramid structure formed with a plurality of substrates, wherein at least two of the plurality of substrates includes a coil.

Optionally, the method includes simultaneously applying signals on each planar coil, wherein in the signals are either the same signal or signals that differ in at least one of amplitude, frequency and phase.

Certain features of the examples described herein, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the examples described herein, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable sub-combination or as suitable in any other described embodiment of the disclosure. Certain features described in the context of various embodiments are not to be considered essential features of those embodiments, unless the embodiment is inoperative without those elements.

What is claimed is:

1. A device comprising:

a housing;

a tip configured to be movable with respect to the housing;

a resilient element fixed to the tip, wherein the resilient element includes magnetic material, wherein the magnetic material is formed from conductive material;

a plurality of substrates formed in a pyramid structure fixed to the housing, wherein a surface of each substrate is positioned to face the resilient element and wherein the resilient element is configured to press against at least one surface in response to the tip receding toward the housing;

a coil patterned on at least two substrates; and

a controller configured:

apply current flow in the coil to induce haptic feedback via the tip, wherein the current flow is configured to induce a magnetic driving force on the resilient element; and

detect capacitive coupling between the coil and the magnetic material of the resilient element based on applying a constant voltage across the coil, wherein the capacitive coupling is related pressure on the tip.

2. The device according to claim 1, wherein the resilient element is formed from an elastomer embedded with magnetic particles.

3. The device according to claim 1, wherein the controller is configured to detect changes in the capacitive coupling based on deformation of the resilient element as it presses against at least one surface.

4. The device according to claim 3, wherein the controller is configured to detect pressure applied on the tip based on the detected capacitive coupling.

5. The device according to claim 4, wherein the haptic feedback is based on the pressure detected.

6. The device according to claim 1, wherein the device includes a tilt sensor and wherein the haptic feedback is based on output from the tilt sensor.

7. The device according to claim 1, comprising wherein each of at least two substrates is patterned with a planar coil that is magnetically coupled to the resilient element.

8. The device according to claim 7, wherein the resilient element is a rounded element fitted into the pyramid structure and configured to press against each of the substrates of the pyramid structure.

9. The device according to claim 7, wherein the controller is configured to simultaneously apply signals on each of the planar coils, wherein the signals are either the same signal or signals that differ in at least one of amplitude, frequency and phase.

10. The device according to claim 7, wherein the tip is configured to both tilt and recede into the housing based on contact pressure applied on the tip and wherein the controller is configured to apply haptic feedback in three dimensions based on applying signals to each of the planar coils.

11. The device according to claim 7, wherein the controller is configured to detect force applied on the tip in three dimensions based on a detected capacitive coupling between the resilient element and a conductive element on each of the substrates, wherein the conductive element is the planar coil or an electrode patterned on the substrate.

12. A method comprising:

fixing a resilient element to a tip that extends out of a housing and is movable with respect to the housing, wherein the resilient element includes magnetic material and wherein the magnetic material is conductive;

positioning a plurality of substrates in a pyramid structure to face the resilient element and fixed to the housing;

wherein the resilient element is configured to press against at least one surface in response to the tip receding toward the housing;

wherein at least two substrates include a coil that is patterned on the substrate;

inducing haptic feedback via the tip based on applying a current flow in the coil, wherein the current flow is configured to induce a magnetic driving force on the resilient element; and

detecting capacitive coupling between the coil and the magnetic material of the resilient element based on applying a constant voltage across the coil, wherein the capacitive coupling is related pressure on the tip.

13. The method according to claim 12, comprising detecting pressure on the tip based on changes in the capacitive coupling between the resilient element and a conductive element on at least one substrate, wherein the changes in capacitive coupling is based on deformation of the resilient element as it presses against the surface.

14. The method claim 13, comprising defining the haptic feedback based on the pressure detected.

15. The method according to claim 12, comprising simultaneously applying signals on each planar coil, wherein in the signals are either the same signal or signals that differ in at least one of amplitude, frequency and phase.

16. The method according to claim 12, wherein each of at least two substrates is patterned with a planar coil that is magnetically coupled to the resilient element.

17. The method according to claim 16, wherein the resilient element is a rounded element fitted into the pyramid structure and configured to press against each of the substrates of the pyramid structure.

18. The method according to claim 16, further comprising simultaneously applying signals on each of the planar coils, wherein the signals are either the same signal or signals that differ in at least one of amplitude, frequency and phase.

19. The method according to claim 16, further comprising detecting force applied on the tip in three dimensions based on a detected capacitive coupling between the resilient element and a conductive element on each of the substrates,

**11**

wherein the conductive element is the planar coil or an electrode patterned on the substrate.

**20.** The method according to claim **12**, wherein inducing the haptic feedback is further based on a tilt sensor.

\* \* \* \* \*

**12**