

(12) **United States Patent**
Polney

(10) **Patent No.:** **US 10,297,298 B2**
(45) **Date of Patent:** **May 21, 2019**

(54) **APPARATUSES AND METHODS FOR PROVIDING INTERNAL CLOCK SIGNALS OF DIFFERENT CLOCK FREQUENCIES IN A MEMORY DEVICE**

(58) **Field of Classification Search**
CPC G11C 7/1051; G11C 7/1078; G11C 7/22
USPC 365/189.05, 230.08, 233.13
See application file for complete search history.

(71) Applicant: **Micron Technology, Inc.**, Boise, ID (US)

(56) **References Cited**

(72) Inventor: **Jens Polney**, Feldkirchen (DE)

U.S. PATENT DOCUMENTS

(73) Assignee: **Micron Technology, Inc.**, Boise, ID (US)

9,054,713 B2 6/2015 Kitagawa et al.
2010/0005217 A1 1/2010 Jeddelloh
2010/0250874 A1* 9/2010 Farrell G06F 13/161
711/155

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

(21) Appl. No.: **15/730,552**

(22) Filed: **Oct. 11, 2017**

(65) **Prior Publication Data**

US 2018/0204608 A1 Jul. 19, 2018

Related U.S. Application Data

(62) Division of application No. 15/410,602, filed on Jan. 19, 2017, now Pat. No. 9,818,462.

(51) **Int. Cl.**

G11C 7/10 (2006.01)
G11C 7/22 (2006.01)
G11C 11/4076 (2006.01)
G11C 11/4096 (2006.01)

(52) **U.S. Cl.**

CPC **G11C 7/222** (2013.01); **G11C 7/1006** (2013.01); **G11C 7/109** (2013.01); **G11C 7/1084** (2013.01); **G11C 7/1093** (2013.01); **G11C 11/4076** (2013.01); **G11C 11/4096** (2013.01); **G11C 7/1066** (2013.01); **G11C 7/1078** (2013.01); **G11C 7/22** (2013.01); **G11C 2207/107** (2013.01)

OTHER PUBLICATIONS

International Search Report and Written Opinion received for PCT Appl. PCT/US2018/013073 dated Apr. 30, 2018.


Primary Examiner — Jason Lappas

(74) Attorney, Agent, or Firm — Dorsey & Whitney LLP

(57) **ABSTRACT**

Apparatuses and methods for providing internal clock signals of different clock frequencies in a semiconductor device are described in the present application. An example apparatus includes a read command buffer and a read data output circuit. The read command buffer buffers a read command responsive to a first clock signal and provides the read command responsive to a second clock signal. The read data output circuit receives a plurality of bits of data in parallel when activated by the read command from the read command buffer, and provides the plurality of bits of data serially responsive to input/output (IO) clock signals. A data clock timing circuit provides the IO clock signals having a first clock frequency in a first mode and having a second clock frequency in a second mode, and further provides the second clock signal having the first clock frequency in the first and second modes.

12 Claims, 15 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0078101 A1 3/2015 Becker
2016/0329090 A1 11/2016 Gans et al.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8A








FIG. 8B






FIG. 10




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14




FIG. 15

1

**APPARATUSES AND METHODS FOR
PROVIDING INTERNAL CLOCK SIGNALS
OF DIFFERENT CLOCK FREQUENCIES IN
A MEMORY DEVICE**

CROSS-REFERENCE TO RELATED
APPLICATION

This application is a divisional of U.S. patent application Ser. No. 15/410,602, filed Jan. 19, 2017 and issued as U.S. Pat. No. 9,818,462 on Nov. 14, 2017. This application, and issued patent, is incorporated by reference herein in its entirety and for all purposes.

BACKGROUND

Current and future generation semiconductor memory applications utilize very high memory I/O speeds to read and write data. Examples of such semiconductor memory include dynamic random access memory (DRAM) and synchronous dynamic random access memory (SDRAM), as well as many others.

The demand for high memory I/O speeds is particularly true in graphics memory, such as current and future generation GDDR5/GDDR5X specifications. Graphics memories are designed for applications requiring high bandwidths and high memory I/O speeds, for example, in excess of 8 Gbps. The high memory I/O speeds, however, consume more power than compared to lower memory I/O speeds. While many applications of such memory demand high memory I/O speeds, other applications may prioritize lower power consumption and accept lower memory I/O speeds.

It may be desirable for a semiconductor memory to be operated at various clock frequencies to provide different memory I/O speeds.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a block diagram of a semiconductor device in accordance with an embodiment of the disclosure.

FIG. 2 is a block diagram of an apparatus according to an embodiment of the disclosure.

FIG. 3 is a block diagram of a phase-locked loop (PLL) circuit according to an embodiment of the disclosure.

FIG. 4 is a timing diagram of various signals during operation of the PLL circuit of FIG. 3 according to an embodiment of the disclosure.

FIG. 5 is block diagram of an apparatus according to an embodiment of the disclosure.

FIG. 6 is a block diagram of a PLL circuit according to an embodiment of the disclosure.

FIG. 7 is a timing diagram of various signals during operation of the PLL circuit of FIG. 6 according to an embodiment of the disclosure.

FIG. 8A is a schematic diagram of a clock divider circuit according to an embodiment of the disclosure.

FIG. 8B is a timing diagram showing various clock signals during operation of the clock divider circuit of FIG. 8A according to an embodiment of the disclosure.

FIG. 9A is a block diagram of a read data output circuit according to an embodiment of the disclosure.

FIG. 9B is a block diagram of a shift register according to an embodiment of the disclosure.

FIG. 9C is a block diagram of a shift register according to an embodiment of the disclosure.

2

FIG. 9D is a timing diagram illustrating the timing of the output of the bits of data by the shift register of FIG. 9A, the shift register of FIG. 9B, and the shift register of FIG. 9C relative to one another.

FIG. 10 is a block diagram of a write data input circuit according to an embodiment of the disclosure.

FIG. 11 is a diagram illustrating the relative timing of various clock signals, serially provided internal data, and sampled data according to an embodiment of the disclosure.

FIG. 12 is a block diagram of a serial-to-parallel (S2P) circuit according to an embodiment of the disclosure.

FIG. 13A is a block diagram of a serial-in-parallel-out (SIPO) circuit according to an embodiment of the disclosure.

FIG. 13B is a timing diagram illustrating the various signals during operation of the SIPO circuit of FIG. 13A according to an embodiment of the disclosure.

FIG. 14 is a block diagram of a command buffer according to an embodiment of the disclosure.

FIG. 15 is a block diagram of a pointer counter circuit according to an embodiment of the disclosure.

DETAILED DESCRIPTION

Certain details are set forth below to provide a sufficient understanding of embodiments of the disclosure. However, it will be clear to one skilled in the art that embodiments of the disclosure may be practiced without these particular details. Moreover, the particular embodiments of the present disclosure described herein are provided by way of example and should not be used to limit the scope of the disclosure to these particular embodiments. In other instances, well-known circuits, control signals, timing protocols, and software operations have not been shown in detail in order to avoid unnecessarily obscuring the disclosure.

FIG. 1 is a block diagram of a block diagram of a semiconductor device 10 in accordance with an embodiment of the disclosure. The semiconductor device 10 includes a memory die. The memory die may include an address/command input circuit 5, address decoder 12, command decoder 15, clock input circuit 20, internal clock generator 30, timing generator 35, row decoder 40, column decoder 45, memory arrays 50, read/write amplifiers 55, I/O circuit 60, ZQ calibration circuit 65, and voltage generator 70.

In some embodiments, the semiconductor device 10 may include, without limitation, a DRAM device, such as GDDR5 SGRAM integrated into a single semiconductor chip, for example. GDDR SGRAMs may be suited for use with high-performance computing applications, including, for example, graphics intensive processing applications such as graphics cards, game consoles, and the like. The die may be mounted on an external substrate, for example, a memory module substrate, a mother board or the like. The semiconductor device 10 may further include a memory array 50. The memory array 50 includes a plurality of banks, each bank including a plurality of word lines WL, a plurality of bit lines BL, and a plurality of memory cells MC arranged at intersections of the plurality of word lines WL and the plurality of bit lines BL. The selection of the word line WL is performed by a row decoder 40 and the selection of the bit line BL is performed by a column decoder 45. Sense amplifiers (SA) are located for their corresponding bit lines BL and connected to at least one respective local I/O line, which is in turn coupled to a respective one of at least two main I/O line pairs, via transfer gates (TG), which function as switches.

The semiconductor device **10** may employ a plurality of external terminals that include address and command terminals coupled to command/address bus (C/A), clock terminals CK_t and CK_c, write clock terminals WCK_t and WCK_c, data terminals DQ, DQS, and DM, power supply terminals VDD, VSS, VDDQ, and VSSQ, and the ZQ calibration terminal (ZQ).

The command/address terminals may be supplied with an address signal and a bank address signal from outside. The address signal and the bank address signal supplied to the address terminals are transferred, via the address/command input circuit **5**, to an address decoder **12**. The address decoder **12** receives the address signal and supplies a decoded row address signal to the row decoder **40**, and a decoded column address signal to the column decoder **45**. The address decoder **12** also receives the bank address signal and supplies the bank address signal to the row decoder **40**, the column decoder **45**.

The command/address terminals may further be supplied with a command signal from outside, such as, for example, a memory controller **5**. The command signal may be provided, via the C/A bus, to the command decoder **15** via the address/command input circuit **5**. The command decoder **15** decodes the command signal to generate various internal commands that include a row command signal to select a word line and a column command signal, such as a read command or a write command, to select a bit line. Various internal commands, for example read commands and write commands, are provided to a command buffer **75**. The buffered commands are buffered by the command buffer **75** responsive to command and address clock signals CACLK and CACLKF and output responsive to buffer clock signals BUFCLK and BUFCLKF. The commands are provided to various circuits of the semiconductor device to perform operations related to the commands.

For example, when a read command is issued and a row address and a column address are timely supplied with the read command, read data is read from a memory cell in the memory array **50** designated by these row address and column address. An internal read command is buffered and then provided to input/output circuit **60** so that the read data DQ is output to outside from the data terminals DQ, DQS, and DM via read/write amplifiers **55** and the input/output circuit **60**. Similarly, when the write command is issued and a row address and a column address are timely supplied with this command, and then write data is supplied to the data terminals DQ, DQS, DM, an internal write command is buffered and then provided to input/output circuit **60** so that the write data is received by data receivers in the input/output circuit **60**, and supplied via the input/output circuit **60** and the read/write amplifiers **55** to the memory array **50** and written in the memory cell designated by the row address and the column address.

Turning to the explanation of the external terminals included in the semiconductor device **10**, the clock terminals CK_t and CK_c, and WCK_t and WCK_c are supplied with external clock signals and complementary external clock signals, respectively. The external clock signals (including complementary external clock signals) may be supplied to a clock input circuit **20**. The clock input circuit **20** may receive the external clock signals to generate internal clock signals ICLK. The internal clock signals ICLK are supplied to an internal clock generator **30**. The internal clock generator **30** provides various phase and frequency controlled internal clock signal based on the received internal clock signals ICLK and a clock enable signal CKE from the address/command input circuit **5**. For example, the internal clock

generator **30** provides command and address clock signals CACLK, CACLKF and buffer clock signals BUFCLK, BUFCLKF. The internal clock generator **30** further provides input/output (IO) clock signals. The IO clock signals are supplied to the input/output circuit **60** and are used as a timing signal for determining an output timing of read data and the input timing of write data. As will be described in more detail below, the IO clock signals may be provided at multiple clock frequencies so that data may be output from and input to the semiconductor device **10** at different data rates. A higher clock frequency may be desirable when high memory speed is critical. A lower clock frequency may be desirable when lower power consumption is critical. The internal clock signals ICLK are also supplied to a timing generator **35** and thus various internal clock signals can be generated.

The power supply terminals are supplied with power supply potentials VDD and VSS. These power supply potentials VDD and VSS are supplied to an internal voltage generator circuit **70**. The internal voltage generator circuit **70** generates various internal potentials VPP, VOD, VARY, VPERI, and the like and a reference potential ZQVREF based on the power supply potentials VDD and VSS. The internal potential VPP is mainly used in the row decoder **40**, the internal potentials VOD and VARY are mainly used in the sense amplifiers included in the memory array **50**, and the internal potential VPERI is used in many other circuit blocks. The reference potential ZQVREF is used in the ZQ calibration circuit **65**.

The power supply terminals are also supplied with power supply potentials VDDQ and VSSQ. These power supply potentials VDDQ and VSSQ are supplied to the input/output circuit **60**. The power supply potentials VDDQ and VSSQ are the same potentials as the power supply potentials VDD and VSS, respectively. However, the dedicated power supply potentials VDDQ and VSSQ are used for the input/output circuit **60** so that power supply noise generated by the input/output circuit **60** does not propagate to the other circuit blocks.

The calibration terminal ZQ is connected to the ZQ calibration circuit **65**. The ZQ calibration circuit **65** performs a calibration operation with reference to an impedance of RZQ, and the reference potential ZQVREF, when activated by the ZQ calibration command signal (ZQ_{com}). An impedance code ZQCODE obtained by the calibration operation is supplied to the input/output circuit **60**, and thus an impedance of an output buffer (not shown) included in the input/output circuit **60** is specified.

FIG. **2** is a block diagram of an apparatus **100** according to an embodiment of the disclosure. The apparatus **100** may be included in the semiconductor device **10** of FIG. **1** in some embodiments. The apparatus **100** includes a command path that includes receiver circuits **102** and **104** that receive command signals and address signals, respectively. The receiver circuit **102** may include a plurality of receiver circuits that each receive a respective one of the command signals, and similarly, the receiver circuit **104** may include a plurality of receiver circuits that each receive a respective one of the address signals. The receiver circuit **102** provides the command signals and the receiver circuit **104** provides the address signals to a command decoder and latch circuit **110**. The apparatus **100** further includes receiver circuit **106** that receives a command and address clock signal CK_t and a complementary command and address clock signal CK_c. The receiver circuit **106** provides two internal clock signals CACLK and CACLKF having relative phases to each other (i.e., provides two phases). For example, in an embodiment

5

of the disclosure, the receiver circuit **106** provides the CACLK clock signal and further provides the CACLKF clock signal, which is 180 degrees out of phase from the CACLK clock signal.

The command signals and address signals provided by the receiver circuits **102** and **104**, respectively, are latched by the command decoder and latch circuit **110** responsive to the CACLK and/or CACLKF clock signals. The command decoder and latch circuit **110** provides internal commands based on the latched command signals. For example, the command decoder and latch circuit **110** provides an internal read command RDCMD responsive to the command decoder and latch circuit **110** decoding a read command from the latched command signals. The command decoder and latch circuit **110** provides an internal write command WRCMD responsive to the command decoder and latch circuit **110** decoding a write command from the latched command signals. The internal commands, namely the read command RDCMD and write command WRCMD, have been provided by way of example, and are not intended to limit the internal commands provided by the command decoder and latch circuit **110** to merely read and write commands. In an embodiment, the command decoder and latch circuit **110** provides other internal commands additionally, or alternatively, to the read command RDCMD and/or write command WRCMD.

The read command RDCMD is provided to a read command buffer **114**. The read command buffer **114** may be implemented as a first-in, first-out (FIFO) buffer. The read command buffer **114** buffers a read command RDCMD responsive to a clock signal provided to a clk_in node of the read command buffer **114** and provides a read command RDCMD responsive to a clock signal provided to a clk_out node of the read command buffer **114**. The CACLK clock signal and/or CACLKF clock signal are provided to the clk_in node of the read command buffer **114**. The write command signal WRCMD is provided to a write command buffer **112**. The write command buffer **112** may be implemented as a FIFO buffer. The write command buffer **112** buffers a write command WRCMD responsive to a clock signal provided to a clk_in node of the write command buffer **112** and provides a write command WRCMD responsive to a clock signal provided to a clk_out node of the write command buffer **112**. The CACLK clock signal and/or CACLKF clock signal are provided to the clk_in node of the write command buffer **112**.

The read command RDCMD is provided by the read command buffer **114** to a read data output circuit **118** responsive to the clock signal provided to the clk_out node. The read data output circuit **118** receives read data, for example, from a memory array, and provides the read data to an external terminal **122** when activated by the read command RDCMD and responsive to a clock signal provided to a clock input of the read data output circuit **118**. In an embodiment, the read data output circuit **118** receives read data in parallel (e.g., 16-bits in parallel) and provides the read data to the external terminal **122** serially (e.g., multiple consecutive 1-bit output). The write command WRCMD is provided by the write command buffer **112** to a write data input circuit **120** responsive to a clock signal provided to the clk_out node. The write data input circuit **120** receives write data, for example, from the external terminal **122**, and provides the write data internally, for example, to the memory array, when activated by the write command WRCMD and responsive to a clock signal provided to a clock input of the write data input circuit **120**. In an embodiment, the write data input circuit **120** receives

6

write data serially (multiple consecutive 1-bit input) and provides the internal write data in parallel (e.g., 16-bits in parallel).

It will be appreciated that while FIGS. **2** and **5** illustrate one external terminal **122**, and respective read data output circuit **118** and write data input circuit **120**, additional external terminals, and read data output circuits and write data output circuits may be included when the apparatus **100** is included in a semiconductor device, for example, the semiconductor device **10** of FIG. **1**, without departing from the scope of the disclosure. The IO clock signals may be provided to each of the read data output circuits and write data input circuits in such embodiments. Similarly, other circuits or elements previously described with reference to FIGS. **2** and **5** may be added to support additional read data output circuits and write data input circuits, and additional external terminals without departing from the scope of the present disclosure.

The apparatus **100** further includes a clock training circuit **116** that receives the CACLK and CACLKF clock signals, and further receives buffer clock signals BUFCLK and BUFCLKF. The clock training circuit **116** compares the CACLK and CACLKF clock signals with the BUFCLK and BUFCLKF clock signals and provide a clock phase signal CLKPH having a value indicative of the phase relationship between the CACLK, CACLKF and BUFCLK, BUFCLKF clock signals. For example, the CLKPH signal may have a first logic value when the CACLK, CACLKF clock signals lead the BUFCLK, BUFCLKF clock signals and may have a second logic value when the CACLK, CACLKF clock signals lag the BUFCLK, BUFCLKF clock signals. The CLKPH signal may be provided to a memory controller that adjusts the phase of a data clock (e.g., write clock signals WCK_t and WCK_c) and the command and address clock signal.

A receiver circuit **108** receives a write clock signal WCK_t and a complementary write clock signal WCK_c. The receiver circuit **108** provides two internal clock signals DCLK and DCLKF having relative phases to each other (i.e., provides two phases). For example, in an embodiment of the disclosure, the receiver circuit **108** provides the DCLK clock signal and further provides the DCLKF clock signal, which is 180 degrees out of phase from the DCLK clock signal. The DCLK and DCLKF clock signals have a clock frequency that is the same as the clock frequency of the WCK_t and WCK_c clock signals. By way of a non-limiting example, the clock frequency of the DCLK and DCLKF clock signals and the clock frequency of the WCK_t and WCK_c clock signals may be 3 GHz. The DCLK and DCLKF clock signals are provided to a clock divider circuit **124**, which provides four clock signals DCLK0, DCLK90, DCLK180, and DCLK270 having relative phases to each other (e.g., four phase clock signals). For example, in an embodiment of the disclosure, the clock divider circuit **124** provides the DCLK0 clock signal, the DCLK90 clock signal that is 90 degrees out of phase from the DCLK0 clock signal, and further provides the DCLK180 clock signal that is 180 degrees out of phase from the DCLK0 clock signal and the DCLK270 clock signal that is 270 degrees out of phase from the DCLK0 clock signal. The four clock signals provided by the clock divider circuit **124** have a lower clock frequency than the clock frequency of the DCLK and DCLKF clock signals. For example, in an embodiment of the disclosure, the clock divider circuit **124** provides four clock signals DCLK0, DCLK90, DCLK180, DCLK270 having a clock frequency that is one-half of the clock frequency of the DCLK and DCLKF clock signals (and one-half of the

WCK_t and WCK_c clock signals). By way of a non-limiting example, the clock frequency of the DCLK and DCLKF clock signals (and one-half of the WCK_t and WCK_c clock signals) may be 3 GHz and the clock frequency of the DCLK₀, DCLK₉₀, DCLK₁₈₀, DCLK₂₇₀ clock signals may be 1.5 GHz.

The four clock signals from the clock divider circuit **124** are provided to a data clock timing circuit **130**. The data clock timing circuit **130** provides buffer clock signals BUFCLK and BUFCLKF. The BUFCLK and BUFCLKF signals are provided to the clock training circuit **116**, and to the write command buffer **112** and read command buffer **114**. The BUFCLK and BUFCLKF signals and the CACLK and CACLKF signals are compared by the clock training circuit **116** when activated to provide the clock phase signal CLKPH, which as previously described, may have a value indicative of the phase of relationship between the BUFCLK, BUFCLKF signals and the CACLK, CACLKF signals. The BUFCLK and BUFCLKF signals are also used to cause the write command buffer **112** to provide write commands to the write data input circuit **120** and to cause the read command buffer **114** to provide read commands to the read data output circuit **118**.

The data clock timing circuit **130** further provides input/output (IO) clock signals IO₀, IO₉₀, IO₁₈₀, and IO₂₇₀. The IO clock signals have relative phases to each other (e.g., four phase clock signals). For example, in an embodiment of the disclosure, the data clock timing circuit **130** provides the IO₀ clock signal, and provides the IO₉₀ clock signal that is 90 degrees out of phase from the IO₀ clock signal, the IO₁₈₀ clock signal that is 180 degrees out of phase from the IO₀ clock signal, and the IO₂₇₀ clock signal that is 270 degrees out of phase from the IO₀ clock signal. The IO clock signals are provided to the clock input of the write data input circuit **120** and to the clock input of the read data output circuit **118**. As previously described, the write data input circuit **120** provides write data from the external terminal **122** responsive to the IO clock signals when activated by the write command WRCMD and the read data output circuit **118** provides read data to the external terminal **122** responsive to the IO clock signals when activated by the read command RDCMD.

As will be described in more detail below, the data clock timing circuit **130** is configured to provide the IO clock signals and the BUFCLK and BUFCLKF clock signals to cause the read data output circuit **118** and the write data input circuit **120** to operate at a first clock frequency when in a first mode, and to operate at a second clock frequency when in a second mode. For example, in an embodiment, when in the first mode the data clock timing circuit **130** is configured to provide the IO clock signals and the BUFCLK and BUFCLKF signals to operate the read data output circuit **118** and the write data input circuit **120** at a double-data rate (DDR) and when in the second mode the data clock timing circuit **130** is configured to provide the IO clock signals and the BUFCLK and BUFCLKF signals to operate the read data output circuit **118** and the write data input circuit **120** at a quad-data rate (QDR). When operating at a DDR, two bits of data are output by the read data output circuit **118** or input by the write data input circuit **120** for each clock cycle of the write clock signal and the complementary write clock signal WCK_t, WCK_c. When operating at a QDR, four bits of data are output by the read data output circuit **118** or input by the write data input circuit **120** for each clock cycle of the write clock signal and the complementary write clock signal WCK_t, WCK_c. In such an example, the first mode of the data clock timing circuit **130** may be referred to as a DDR

mode and the second mode may be referred to as a QDR mode. The modes of operation may be selected through the use of a mode register. As known, a mode register may be used to select various modes of operations, options, features, etc. To set the various modes of operations, options, features, etc., information is programmed into the mode register having the value corresponding to the desired mode of operations, options, features, etc.

The apparatus **100** may be used to receive memory commands (e.g., read commands, write commands) according to a command and address clock CK_t, CK_c domain and provide corresponding internal memory commands to activate IO circuits (e.g., read data output circuit **118**, write data input circuit **120**) that are operated according to a write clock WCK_t, WCK_c domain. The memory commands cross between the CK clock domain and the WCK clock domain by buffering the commands in the command buffers based on the CK clock signals and providing the memory commands from the command buffers to the IO circuits based on the WCK clock signals. As will be explained in more detail below, data may be input and output according to different frequencies (e.g., DDR or QDR).

In operation, command and address signals provided by the receiver circuits **102** and **104** are latched and decoded by the command decoder and latch circuit **110** according to the CACLK and CACLKF clock signals. The CACLK and CACLKF clock signals are provided by the receiver circuit **106**.

Internal read commands RDCMD provided by the command decoder and latch circuit **110** to the read command buffer **114** are buffered responsive to the CACLK and CACLKF clock signals. The read commands are provided to the read data output circuit **118** responsive to the BUFCLK and BUFCLKF clock signals to activate the read data output circuit **118**. The BUFCLK and BUFCLKF clock signals are provided by the data clock timing circuit **130**. When activated, the read data output circuit **118** receives read data and provides the read data to an external terminal **122** responsive to the IO clock signals from the data clock timing circuit **130**. As previously described, in an embodiment, read data may be received by the read data output circuit **118** in parallel and provided to the external terminal **122** serially. The data clock timing circuit **130** may provide IO clock signals to operate the read data output circuit **118** according to a first frequency (e.g., DDR mode) or a second frequency (e.g., QDR mode).

Internal write commands WRCMD provided by the command decoder and latch circuit **110** to the write command buffer **112** are buffered responsive to the CACLK and CACLKF clock signals. The write commands are provided to the write data input circuit **120** responsive to the BUFCLK and BUFCLKF clock signals to activate the write data input circuit **120**. When activated, the write data input circuit **120** receives write data from the external terminal **122** and provides internal write data responsive to the IO clock signals from the data clock timing circuit **130**. As previously described, in an embodiment, write data may be received by the write data input circuit **120** from the external terminal **122** serially and the internal write data provided in parallel. The IO clock signals provided by the data clock timing circuit **130** may be used to operate the write data input circuit **120** according to a first frequency (e.g., DDR mode) or a second frequency (e.g., QDR mode).

In the embodiment shown in FIG. 2, the data clock timing circuit **130** includes a phase-locked loop (PLL) circuit **132** that receives the four phase clock signals DCLK₀, DCLK₉₀, DCLK₁₈₀, DCLK₂₇₀ from the a clock divider circuit **124**.

The PLL circuit **132** provides four clock signals PLLCK0, PLLCK90, PLLCK180, PLLCK270 to a first input of the multiplexer **138** responsive to the DCLK0, DCLK90, DCLK180, DCLK270 clock signals. The PLLCK0, PLLCK90, PLLCK180, PLLCK270 clock signals have relative phases to each other (e.g., 0 degrees, 90 degrees, 180 degrees, and 270 degrees). The PLLCK0, PLLCK90, PLLCK180, PLLCK270 clock signals have a higher clock frequency than the clock frequency of the DCLK0, DCLK90, DCLK180, DCLK270 clock signals. For example, in an embodiment of the disclosure, the PLL circuit **132** provides the PLLCK0, PLLCK90, PLLCK180, PLLCK270 clock signals having a clock frequency that is twice that of the clock frequency of the DCLK0, DCLK90, DCLK180, DCLK270 clock signals. By way of a non-limiting example, the clock frequency of the DCLK0, DCLK90, DCLK180, DCLK270 clock signals may be 1.5 GHz and the clock frequency of the PLLCK0, PLLCK90, PLLCK180, PLLCK270 clock signals may be 3.0 GHz. The DCLK0, DCLK90, DCLK180, DCLK270 clock signals are also provided to a second input of the multiplexer **138**. The multiplexer **138** provides either the PLLCK0, PLLCK90, PLLCK180, PLLCK270 clock signals or the DCLK0, DCLK90, DCLK180, DCLK270 clock signals as the IO clock signals based on a control signal MUXCTL.

Two of the four PLLCK clock signals are also provided to a clock divider circuit **134**. For example, in an embodiment, the two PLLCK clock signals are PLLCK0 and PLLCK180, which are complementary. The clock divider circuit **134** provides four clock signals DIVCK0, DIVCK90, DIVCK180, DIVCK270 having relative phases to each other (e.g., 0 degrees, 90 degrees, 180 degrees, and 270 degrees). Two of the four DIVCK clock signals are provided back to the PLL circuit **132**. For example, in an embodiment of the disclosure the DIVCK0 and DIVCK180 clock signals are provided. The two DIVCK clock signals may be used by the PLL circuit **132** to synchronize the PLLCK clock signals (and the DIVCK clock signals) with the DCLK clock signals. Two of the four DIVCK clock signals are provided to a first input of the multiplexer **136**. For example, the DIVCK0 and DIVCK180 clock signals may be provided to the multiplexer **136** in an embodiment of the disclosure. A second input of the multiplexer **136** receives two of the four IO clock signals provided by the multiplexer **138**. The multiplexer **136** provides the two DIVCK clock signals or the two IO clock signals as the buffer clock signals BUFCLK and BUFCLKF based on the control signal MUXCTL. The clock frequency of the DIVCK clock signals is lower than the clock frequency of the PLLCK clock signals. In an embodiment of the disclosure, the DIVCK clock signals have a clock frequency that is one-half of the clock frequency of the PLLCK clock signals.

In operation, in a first mode (e.g., DDR mode), the control signal MUXCTL has a first logic value (e.g., a high logic value) causing the multiplexer **138** to provide the DCLK0, DCLK90, DCLK180, DCLK270 clock signals as the IO clock signals, and further causing the multiplexer **136** to provide two of the four IO clock signals as the buffer clock signals BUFCLK and BUFCLKF. As a result, the clock frequency of the IO clock signals is the same as the clock frequency of the DCLK clock signals. As previously described, in an embodiment, the DCLK clock signals have a clock frequency that is one-half of the clock frequency of the WCK_t and WCK_c clock signals. Consequently, the IO clock signals have a clock frequency that is one-half of the clock frequency of the WCK_t and WCK_c clock signals. In a second mode (e.g., QDR mode), the control signal MUX-

CTL has a second logic value (e.g., a low logic value) causing the multiplexer **138** to provide the PLLCK clock signals as the IO clock signals, and further causing the multiplexer **136** to provide the two of the four DIVCK clock signals as the BUFCLK and BUFCLKF clock signals. As a result, the clock frequency of the IO clock signals is twice the clock frequency of the DCLK clock signals, and is the same clock frequency of the WCK_t and WCK_c clock signals.

As illustrated by the previous example, in a DDR mode the data clock timing circuit **130** provides four phase IO clock signals having a clock frequency that is one-half of the clock frequency of the WCK_t and WCK clock signals to operate the read data output circuit **118** and the write data input circuit **120** at a double-data rate. In a QDR mode the data clock timing circuit **130** provides four phase IO clock signals having a clock frequency that is the same as the clock frequency of the WCK_t and WCK clock signals to operate the read data output circuit **118** and the write data input circuit **120** at a quad-data rate.

The data clock timing circuit **130** has been described as including a PLL circuit **132** that receives the four phase clock signals DCLK0, DCLK90, DCLK180, DCLK270 and provides the four phase clock signals PLLCK0, PLLCK90, PLLCK180, and PLLCK270. In an alternative embodiment, the data clock timing circuit **130** includes a clock circuit other than a PLL circuit. The clock circuit would receive the four phase clock signals DCLK0, DCLK90, DCLK180, DCLK270 and provide the four phase clock signals PLLCK0, PLLCK90, PLLCK180, and PLLCK270. As previously described, the four phase PLLCK clock signals have a clock frequency that is twice the clock frequency of the four phase DCLK clock signals. More generally, the data clock timing circuit **130** may include alternative clock circuits, other than the PLL circuit **132**, that provide the four phase PLLCK clock signals responsive to the four phase DCLK clock signals as previously described without departing from the scope of the disclosure.

FIG. 3 is a block diagram of a PLL circuit **300** according to an embodiment of the disclosure. The PLL circuit **300** may be used as the PLL circuit **132** of FIG. 2. The PLL circuit **300** includes a phase/frequency detector **310** that receives four phase clock signals as reference clock signals clk_ref, for example, the DCLK0, DCLK90, DCLK180, and DCLK270 clock signals provided by the clock divider circuit **124** (FIG. 2). The phase/frequency detector **310** further receives complementary clock signals as feedback clock signals clk_fb, for example, the DIVCK0 and DIVCK180 clock signals provided by the clock divider circuit **134**. The phase/frequency detector **310** compares the phases and frequencies of the reference clock signals and the feedback clock signals and provides a PH signal that is indicative of a phase and frequency difference between the reference and feedback clock signals.

A filter circuit **320** receives the PH signal and provides a control signal CTRL. The CTRL signal provided by the filter circuit **320** is based on the PH signal. For example, in an embodiment, a voltage of the CTRL signal is based on the PH signal. The filter circuit **320** may filter the PH signal in providing the CTRL signal to provide stability to the phase loop and limit ripples that may be present in the PH signal when providing the CTRL signal.

A voltage controlled oscillator (VCO) **330** receives the CTRL signal and provides four clock signals having relative phases to each other (i.e., provides four phase clock signals) that have a clock frequency that is greater than the clock frequency of the complementary reference clock signals. In

an embodiment, the clock frequency of the four phase clock signals is twice the clock frequency of the complementary reference clock signals. By way of a non-limiting example, the clock frequency of the DCLK clock signals may be 1.5 GHz and the clock frequency of the PLLCK clock signals may be 3.0 GHz. The clock signals may be used as the PLLCK0, PLLCK90, PLLCK180, PLLCK270 previously described with reference to FIG. 2. The VCO 330 provides the four clock signals having a phase and frequency that is based on the CTRL signal. For example, the four clock signals may have a phase and frequency based on a voltage of the CTRL signal. When the voltage of the CTRL signal changes, for example, in response to a change in the PH signal from the phase/frequency detector 310, the phase and frequency of the four clock signals may change accordingly.

The clock divider circuit 134 receives two of the four clock signals provided by the VCO 330. In the embodiment of FIG. 3, complementary clock signals are received from the VCO 330 (e.g., PLLCK0 and PLLCK180). The clock divider circuit 134 divides the clock frequency of the complementary clock signals to provide lower clock frequency complementary clock signals (e.g., DIVCK0 and DIVCK180). For example, in an embodiment, the clock divider circuit 134 provides the lower clock frequency complementary clock signals having a clock frequency that is one-half of the clock frequency of the PLLCK clock signals from the VCO 330. The lower clock frequency complementary clock signals are provided as the feedback clock signals to the phase/frequency detector 310.

In operation, the phase/frequency detector 310 compares the phase and frequency of the reference clock signals (e.g., DCLK0, DCLK90, DCLK180, and DCLK270) and the feedback clock signals (e.g., DIVCK0 and DIVCK180) and provides a PH signal to the filter circuit 320 to adjust the VCO 330 until the phase and frequency of the feedback clock signals matches the phase and frequency of the reference clock signals. When the phases and frequencies match, the PLL 300 is said to be "locked." The resulting four phase clock signals provided by the PLL 300 are in phase with the reference clock signals and have a clock frequency that is greater than the clock frequency of the reference clock signals (e.g., twice the clock frequency of the reference clock signals).

FIG. 4 is a timing diagram of various signals during operation of the PLL circuit 300 according to an embodiment of the disclosure. The various signals illustrated by FIG. 4 are from when the PLL circuit 300 is locked. FIG. 4 illustrates the DCLK0, DCLK90, DCLK180, and DCLK270 which may be provided as the reference clock signals to the PLL circuit 300. The DCLK0 and DCLK180 signals are complementary. FIG. 4 further illustrates the DIVCK0 and DIVCK180 signals provided as the feedback clock signals. The DIVCK0 and DIVCK180 clock signals are also complementary. The locked condition of the PLL 300 is reflected by the DCLK0 clock signal having the same phase and frequency as the DIVCK0 clock signal, and the DCLK180 clock signal having the same phase and frequency as the DIVCK180 clock signal. As previously described, when the PLL 300 is locked, the four phase clock signals provided by the VCO 330 (e.g., PLLCK0, PLLCK90, PLLCK180, PLLCK270) are in phase with the reference clock signals and have a clock frequency that is greater than the clock frequency of the reference clock signals. As illustrated in FIG. 4, clock edges of the PLLCK0, PLLCK90, PLLCK180, PLLCK270 clock signals are aligned with the clock edges of the DCLK0, DCLK180 clock signals, and have a clock frequency that is twice the clock frequency of the DCLK0,

DCLK180 clock signals. The PLLCK0, PLLCK90, PLLCK180, PLLCK270 clock signals have relative phases to each other as well (e.g., 0 degrees, 90 degrees, 180 degrees, and 270 degrees). As previously described, the PLLCK clock signals having twice the frequency of the DCLK clock signals (and the same frequency as the WCK clock signals) may be used to operate the read data output circuit 118 and the write data input circuit 120 at a higher frequency, for example, at a QDR.

FIG. 5 is block diagram of an apparatus 500 according to an embodiment of the disclosure. The apparatus 500 includes elements previously described with reference to the apparatus 100 of FIG. 2. Common elements are referenced in FIG. 5 using the same reference numbers and reference names as used in FIG. 2. Generally, the apparatus 500 is different from the apparatus 100 of FIG. 2 with regards to the data clock timing circuit. In particular, the data clock timing circuit 530 of the apparatus 500 is different than the clock divider circuit 130 of the apparatus 100. While the data clock timing circuit 530 provides BUFCLK clock signals and IO signals responsive to DCLK clock signals, as does the clock divider circuit 130, the data clock timing circuit 530 is structured differently from the clock divider circuit 130.

The data clock timing circuit 530 includes a phase-locked loop (PLL) circuit 532 that receives the four phase clock signals DCLK0, DCLK90, DCLK180, DCLK270 from the a clock divider circuit 124. The PLL circuit 132 provides eight clock signals PLLCK0, PLLCK45, PLLCK90, PLLCK135, PLLCK180, PLLCK225, PLLCK270, and PLLCK315 having relative phases to each other responsive to the DCLK0, DCLK90, DCLK180, DCLK270 clock signals. For example, PLLCK clock signals may be phase shifted relative to each other by 45 degrees, such as 0 degrees, 45 degrees, 90 degrees, 135 degrees, 180 degrees, 225 degrees, 270 degrees, and 315 degrees. The eight clock signals may have the same clock frequency as the clock frequency of the DCLK0, DCLK90, DCLK180, DCLK270 clock signals. By way of a non-limiting example, the clock frequency of the DCLK clock signals may be 1.5 GHz and the clock frequency of the PLLCK clock signals may be 1.5 GHz.

The eight PLLCK clock signals are provided to a logic circuit 535. The logic circuit 535 provides four clock signals XORCK0, XORCK90, XORCK180, XOR270 to a first input of the multiplexer 138 responsive to the PLLCK clock signals. In an embodiment, the logic circuit 535 is an exclusive OR (XOR) logic circuit. The XORCK0, XORCK90, XORCK180, XOR270 clock signals have relative phases to each other (e.g., 0 degrees, 90 degrees, 180 degrees, and 270 degrees). The XORCK0, XORCK90, XORCK180, XOR270 clock signals have a higher clock frequency than the clock frequency of the eight PLLCK clock signals. For example, in an embodiment of the disclosure, the logic circuit 535 provides the XORCK clock signals having a clock frequency that is twice that of the clock frequency of the eight PLLCK clock signals. By way of a non-limiting example, the clock frequency of the PLLCK clock signals may be 1.5 GHz and the clock frequency of the XORCK clock signals may be 3.0 GHz.

The DCLK0, DCLK90, DCLK180, DCLK270 clock signals from the clock divider circuit 124 are also provided to a second input of the multiplexer 138. The multiplexer 138 provides either the XORCK0, XORCK90, XORCK180, XOR270 clock signals or the DCLK0, DCLK90, DCLK180, DCLK270 clock signals as the IO clock signals based on a control signal MUXCTL.

Two of the eight PLLCK clock signals are provided back to the PLL circuit 532. For example, in an embodiment, the PLLCK0 and PLLCK180 clock signals may be provided to the PLL circuit 532. The PLLCK0 and PLLCK180 clock signals are complementary clock signals. The two PLLCK clock signals may be used by the PLL circuit 532 to synchronize the PLLCK clock signals with the DCLK clock signals. The two PLLCK clock signals are also provided to a first input of the multiplexer 536. A second input of the multiplexer 536 receives two of the four IO clock signals provided by the multiplexer 538. The multiplexer 536 provides the two PLLCK clock signals or the two IO clock signals as the buffer clock signals BUFCLK and BUFCLKF based on the control signal MUXCTL.

In operation, in a first mode (e.g., DDR mode), the control signal MUXCTL has a first logic value (e.g., a high logic level) causing the multiplexer 538 to provide the DCLK0, DCLK90, DCLK180, DCLK270 clock signals as the IO clock signals, and further causing the multiplexer 536 to provide the two of the four IO clock signals as the buffer clock signals BUFCLK and BUFCLKF. As a result, the clock frequency of the IO clock signals is the same as the clock frequency of the DCLK clock signals (e.g., 1.5 GHz). As previously described, in an embodiment, the DCLK clock signals have a clock frequency that is one-half of the clock frequency of the WCK_t and WCK_c clock signals. Consequently, the IO clock signals have a clock frequency that is one-half of the clock frequency of the WCK_t and WCK_c clock signals. In a second mode (e.g., QDR mode), the control signal MUXCTL has a low logic value causing the multiplexer 538 to provide the XORCK clock signals as the IO clock signals, and further causing the multiplexer 536 to provide the two PLLCK clock signals (e.g., PLLCK0 and PLLCK180) as the BUFCLK and BUFCLKF clock signals. As a result, the clock frequency of the IO clock signals is twice the clock frequency of the DCLK clock signals, and is the same clock frequency of the WCK_t and WCK_c clock signals.

As illustrated by the previous example, in a DDR mode the data clock timing circuit 530 provides four phase IO clock signals having a clock frequency that is one-half of the clock frequency of the WCK_t and WCK_c clock signals to operate the read data output circuit 118 and the write data input circuit 120 at a double-data rate. In a QDR mode the data clock timing circuit 530 provides four phase IO clock signals having a clock frequency that is the same as the clock frequency of the WCK_t and WCK_c clock signals to operate the read data output circuit 118 and the write data input circuit 120 at a quad-data rate.

The data clock timing circuit 530 has been described as including a PLL circuit 532 that receives the four phase clock signals DCLK0, DCLK90, DCLK180, DCLK270 and provides the eight phase clock signals PLLCK0, PLLCK45, PLLCK90, PLLCK135, PLLCK180, PLLCK225, PLLCK270, and PLLCK315. In an alternative embodiment, the data clock timing circuit 530 includes a delay-locked loop (DLL) circuit instead of a PLL circuit. The DLL circuit would receive the four phase clock signals DCLK0, DCLK90, DCLK180, DCLK270 and provide the eight phase clock signals PLLCK0, PLLCK45, PLLCK90, PLLCK135, PLLCK180, PLLCK225, PLLCK270, and PLLCK315. As previously described, the eight phase PLLCK clock signals have a clock frequency that is the same as the clock frequency as the four phase DCLK clock signals. More generally, the data clock timing circuit 530 may include a clock circuit that provides the eight phase

PLLCK clock signals responsive to the four phase DCLK clock signals as previously described without departing from the scope of the disclosure.

FIG. 6 is a block diagram of a PLL circuit 600 according to an embodiment of the disclosure. The PLL circuit 600 may be used as the PLL circuit 532 of FIG. 5. The PLL circuit 600 includes a phase/frequency detector 610 that receives four phase clock signals as reference clock signals clk_ref, for example, the DCLK0, DCLK90, DCLK180, and DCLK270 clock signals provided by the clock divider circuit 124 (FIG. 5). The phase/frequency detector 610 further receives complementary clock signals as feedback clock signals clk_fb, for example, the PLLCK0 and PLLCK180 clock signals provided by the PLL circuit 600. The phase/frequency detector 610 compares the phases and frequencies of the reference clock signals clk_ref and the feedback clock signals clk_fb and provides a PH signal that is indicative of a phase and frequency difference between the reference and feedback clock signals.

A filter circuit 620 receives the PH signal and provides a control signal CTRL. The CTRL signal provided by the filter circuit 620 is based on the PH signal. For example, in an embodiment, a voltage of the CTRL signal is based on the PH signal. The filter circuit 620 may filter the PH signal in providing the CTRL signal to provide stability to the phase loop and limit ripples that may be present in the PH signal when providing the CTRL signal.

A voltage controlled oscillator (VCO) 630 receives the CTRL signal and provides eight clock signals having relative phases to each other (i.e., provides eight phase clock signals) that have a clock frequency that is the same as the clock frequency of the complementary reference clock signals clk_ref. By way of a non-limiting example, the clock frequency of the DCLK clock signals may be 1.5 GHz and the clock frequency of the PLLCK clock signals may be 1.5 GHz. The clock signals may be used as the PLLCK0, PLLCK45, PLLCK90, PLLCK135, PLLCK180, PLLCK225, PLLCK270, and PLLCK315 clock signals previously described with reference to FIG. 5. The VCO 630 provides the eight clock signals having a phase and frequency that is based on the CTRL signal. For example, the eight clock signals may have a phase and frequency based on a voltage of the CTRL signal. When the voltage of the CTRL signal changes, for example, in response to a change in the PH signal from the phase/frequency detector 610, the phase and frequency of the eight clock signals may change accordingly.

The logic circuit 535 receives the eight phase clock signals provided by the VCO 630. The logic circuit 535 provides four clock signals XORCK0, XORCK90, XORCK180, XORCK270 based on logic operations on the eight PLLCK clock signals. In an embodiment, the logic circuit 535 is an XOR logic circuit, and the logic operations may be as follows: XORCK0=PLLCK0 xor PLLCK90; XORCK90=PLLCK45 xor PLLCK135; XORCK180=PLLCK90 xor PLLCK180; and XORCK270=PLLCK270 xor PLLCK225. The XORCK0, XORCK90, XORCK180, XORCK270 clock signals have relative phases to each other (e.g., 0 degrees, 90 degrees, 180 degrees, and 270 degrees). The XORCK0, XORCK90, XORCK180, XORCK270 clock signals have a higher clock frequency than the clock frequency of the eight PLLCK clock signals. For example, in an embodiment of the disclosure, the logic circuit 535 provides the XORCK clock signals having a clock frequency that is twice that of the clock frequency of the eight PLLCK clock signals. By way of a non-limiting example, the clock frequency of the

PLLCK clock signals may be 1.5 GHz and the clock frequency of the XORCK clock signals may be 3.0 GHz.

In operation, the phase/frequency detector **610** compares the phase and frequency of the reference clock signals (e.g., DCLK**0**, DCLK**90**, DCLK**180**, and DCLK**270**) and the feedback clock signals (e.g., PLLCK**0** and PLLCK**180**) and provides a PH signal to the filter circuit **E20** to adjust the VCO **630** until the phase and frequency of the feedback clock signals *clk_fb* matches the phase and frequency of the reference clock signals *clk_ref*. When the phases and frequencies match, the PLL **600** is said to be “locked.” The resulting eight phase clock signals provided by the PLL **600** are in phase with the reference clock signals *clk_ref*. The logic circuit **535** logically operates on the eight phase clock signals and provides the four XORCK clock signals that are in phase with the DCLK**0** and DCLK**180** clock signals and have a clock frequency that is greater than the clock frequency of the DCLK**0** and DCLK**180** reference clock signals (e.g., twice the clock frequency).

FIG. **7** is a timing diagram of various signals during operation of the PLL circuit **600** according to an embodiment of the disclosure. The various signals illustrated by FIG. **7** are provided by the logic circuit **B25** when the PLL circuit **600** is locked. FIG. **7** illustrates the DCLK**0**, DCLK**90**, DCLK**180**, and DCLK**270** clock signals which may be provided as the reference clock signals *clk_ref* to the PLL circuit **600**. The DCLK**0** and DCLK**180** signals are complementary. FIG. **7** further illustrates the PLLCK**0** and PLLCK**180** clock signals provided as the feedback clock signals *clk_fb*. The PLLCK**0** and PLLCK**180** clock signals are also complementary. The locked condition of the PLL **600** is reflected by the DCLK**0** clock signal having the same phase and frequency as the PLLCK**0** clock signal, and the DCLK**180** clock signal having the same phase and frequency as the PLLCK**180** clock signal. As previously described, when the PLL **600** is locked, the eight phase clock signals (e.g., PLLCK**0**, PLLCK**45**, PLLCK**90**, PLLCK**135**, PLLCK**180**, PLLCK**225**, PLLCK**270**, PLLCK**315**) provided by the VCO **630** are in phase with the reference clock signals *clk_ref* and have a clock frequency that is the same clock frequency of the reference clock signals. As illustrated in FIG. **7**, clock edges of the PLLCK**0**, PLLCK**45**, PLLCK**90**, PLLCK**135**, PLLCK**180**, PLLCK**225**, PLLCK**270**, and PLLCK**315** clock signals are aligned with the clock edges of the DCLK**0**, DCLK**180** clock signals, and have a clock frequency that is the same as the clock frequency of the DCLK**0**, DCLK**180** clock signals.

The PLLCK**0**, PLLCK**45**, PLLCK**90**, PLLCK**135**, PLLCK**180**, PLLCK**225**, PLLCK**270**, and PLLCK**315** clock signals have relative phases to each other as well (e.g., 0 degrees, 45 degrees, 90 degrees, 135 degrees, 180 degrees, 215 degrees, 270, and 315 degrees). The PLLCK clock signals are provided to the logic circuit **535** to provide the four XORCK clock signals based on logic operations on the eight PLLCK clock signals. FIG. **7** illustrates the XORCK clock signals resulting from an XOR logic operation. For example, XORCK**0**=PLLCK**0** xor PLLCK**90**; XORCK**90**=PLLCK**45** xor PLLCK**135**; XORCK**180**=PLLCK**90** xor PLLCK**180**; and XORCK**270**=PLLCK**270** xor PLLCK**225**. The XORCK**0**, XORCK**90**, XORCK**180**, XORCK**270** clock signals have twice the clock frequency of the eight PLLCK clock signals (and the same frequency as the WCK clock signals) and may be used to operate the read data output circuit **118** and the write data input circuit **120** at a higher frequency, for example, at a QDR mode.

FIG. **8A** is a schematic diagram of a clock divider circuit **800** according to an embodiment of the disclosure. The clock divider circuit **800** includes a four phase clock divider circuit **810** that receives complementary input clock signals CLKP and CLKN and provides four clock signals CLKP**0**, CLKP**90**, CLKP**180**, and CLKP**270**. The four CLKP clock signals have relative phases to each other (i.e., four phase clock signals). For example, the CLKP**0** clock signal is 0 degrees, the CLKP**90** clock signal is 90 degrees out of phase from the CLKP**0** clock signal, the CLKP**180** clock signal is 180 degrees out of phase from the CLKP**0** clock signal, and the CLKP**270** is 270 degrees out of phase from the CLKP**0** clock signal. The four phase CLKP clock signals have a clock frequency that is lower than the clock frequency of the CLKP and CLKN clock signals. For example, in an embodiment, the CLKP**0**, CLKP**90**, CLKP**180**, and CLKP**270** clock signals have a clock frequency that is one-half of the clock frequency of the CLKP and CLKN clock signals.

The clock divider circuit **800** may be used for the clock divider circuit **124** and the clock divider circuit **134** in an embodiment. The CLKP and CLKN clock signals may be the DCLK and DCLKF clock signals and the four CLKP signals may be the DCLK**0**, DCLK**90**, DCLK**180**, and DCLK**270** clock signals when the clock divider circuit **800** is used for the clock divider circuit **124**. The CLKP and CLKN clock signals may be two PLLCK clock signals and the four CLKP signals may be the DIVCK**0**, DIVCK**90**, DIVCK**180**, and DIVCK**270** clock signals when the clock divider circuit **800** is used for the clock divider circuit **134**.

The phase clock divider circuit **810** includes clock divider stages **814** and **818**. Each of the clock divider stages **814** and **818** receives the CLKP and CLKN signals, and provides two of the four phase clock signals. The clock divider stage **814** provides the CLKP**90** and CLKP**270** clock signals and the clock divider stage **818** provides the CLKP**0** and CLKP**180** clock signals. The clock divider circuit **800** further includes a bias circuit **830** that provides bias currents to the phase clock divider circuit **810**. The bias currents provided by the bias circuit **830** bias the four phase clock divider circuit **810** for operation.

In operation, the CLKP and CLKN clock signals control coupling of the bias current from the bias circuit **830** to the clock divider stages **814** and **818**. As the CLKP and CLKN clock signals control the coupling of the bias current, the clock divider stage **814** provides the CLKP**90** and CLKP**270** clock signals and the clock divider stage **818** provides the CLKP**0** and CLKP**180** clock signals. FIG. **8B** is a timing diagram showing various clock signals during operation of the clock divider circuit **800** according to an embodiment of the disclosure. The CLKP and CLKN clock signals are shown as complementary clock signals. The CLKP**0**, CLKP**90**, CLKP**180**, and CLKP**270** have a relative 90 degree phase relationship with each other, as shown by rising clock edges of the four phase CLKP clock signals being 90 degrees out of phase (and falling clock edges of the four phase CLKP clock signals being 90 degrees out of phase). The CLKP**0**, CLKP**90**, CLKP**180**, and CLKP**270** clock signals have a clock frequency that is one-half of the clock frequency of the CLKP and CLKN clock signals.

FIG. **9A** is a block diagram of a read data output circuit **900** according to an embodiment of the disclosure. The read data output circuit **900** is provided with four phase clock signals. The four clock signals *pllclk_0*, *pllclk_90*, *pllclk_180*, *pllclk_270* may have a relative 90 degree phase relationship with each other. For example, the *pllclk_0* may be 0 degrees, *pllclk_90* may be 90 degrees, *pllclk_180* may be 180 degrees, and *pllclk_270* may be 270 degrees. The

read data output circuit **900** may be used for the read data output circuit **118** in an embodiment. In such an embodiment, the `pllclk_0`, `pllclk_90`, `pllclk_180`, and `pllclk_270` clock signals provided to the read data output circuit **900** may be the four phase clock signals `IO0`, `IO90`, `IO180`, and `IO270`.

The read data output circuit **900** includes a shift register **910** and a shift register **920**. The shift register **910** receives a first clock signal `pllclk_i` or `pllclk_j` and the shift register **920** receives a second clock signal `pllclk_(i+90)` or `pllclk_(j+90)` that has a phase 90 degrees relative to the first clock signal ($i=0, j=180$). For example, the shift register **910** may receive the `pllclk_0` clock signal and the shift register **920** may receive the `pllclk_90` clock signal. Alternatively, the shift register **910** may receive the `pllclk_180` clock signal and the shift register **920** may receive the `pllclk_270` clock signal. Each shift register is configured to load bits of data in parallel and provide the bits of data serially responsive to the respective `pllclk` clock signal. In an embodiment, eight bits of data are provided to the shift register **910** and eight bits of data are provided to the shift register **920**. In such embodiments, the read data output circuit **900** receives 16 bits of data in parallel and provides the 16 bits of data serially responsive to the `pllclk` clock signals (eight bits from shift register **910** and eight bits from shift register **920**). Four bits of data are provided per clock cycle of the `pllclk` clock signals, with all 16 bits of data provided over four clock cycles of the `pllclk` clock signals. The read data output circuit **900** further includes a multiplexer **940** that provides the output of the shift register **910** or the shift register **920** based on a control signal provided by the XOR logic circuit **930**. The XOR logic circuit **930** receives the first and second clock signals (e.g., `pllclk0` and `pllclk90`; or `pllclk180` and `pllclk270`) and performs an exclusive-OR operation on the clock signals to provide the control signal to the multiplexer **940**.

In operation, the bits of data are loaded into the shift registers **910** and **920** in parallel and shifted out of the shift registers **910** and **920** serially responsive to the respective `pllclk` clock signal. The XOR logic circuit **930** provides a control signal that switches between high and low logic levels at a frequency that is twice as fast as the clock frequency of the `pllclk` clock signals. As a result, the multiplexer **940** is controlled to switch back and forth between the shift registers **910** and **920** to serially provide four bits of data every clock cycle of the `pllclk` clock signals.

With reference to FIGS. **2** and **5**, when the IO clock signals have a clock frequency that is one-half the clock frequency of the WCK clock signals (e.g., the data clock timing circuit **130** and **530** are in a DDR mode), two bits of data are provided by the read data output circuit **900** per clock period of the WCK clock signal. When the IO clock signals have a clock frequency that is the same clock frequency as the WCK clock signals (e.g., the data clock timing circuit **130** and **530** are in a QDR mode), four bits of data are provided by the read data output circuit **900** per clock period of the WCK clock signal.

FIG. **9B** is a block diagram of a shift register **950** according to an embodiment of the disclosure. The shift register **950** may be used as the shift register **910** and **920** in an embodiment. The shift register **950** includes a shift register **952** and a shift register **954**. The shift registers **952** and **954** each receive bits of data in parallel and provide the bits of data serially responsive to a respective `pllclk` clock signal. For example, in an embodiment, the shift register **952** receives four bits of data in parallel and provides the four bits of data serially responsive to the `pllclk_i` clock signal,

and the shift register **954** receives four bits of data in parallel and provides the four bits of data serially responsive to the `pllclk_(i+180)` clock signal. The shift register **952** may receive the `pllclk_i` clock signal, where i may be 0 or 90, and the shift register **954** may receive the `pllclk_(i+180)` clock signal. For example, where the shift register **952** receives the `pllclk_0` clock signal, the shift register **954** receives the `pllclk_180` clock signal; where the shift register **952** receives the `pllclk_90` clock signal, the shift register **954** receives the `pllclk_270` clock signal. A multiplexer **956** provides data bits from either the shift register **952** or the shift register **954** as controlled by the `pllclk` clock signal provided to the shift register **954** (i.e., `pllclk_(i+180)`).

In operation, the shift register **950** receives bits of data in parallel and serially provides the bits of data according to the `pllclk_i` and `pllclk_(i+180)` clock signals. The `pllclk` clock signal controls the multiplexer **956** to alternately provide bits of data from the shift registers **952** and **954** as the bits of data are shifted through the shift registers **952** and **954**. As a result, the shift register **950** provides two bits of data per clock cycle of the `pllclk` clock signal.

FIG. **9C** is a block diagram of a shift register **960** according to an embodiment of the disclosure. The shift register **960** may be used as the shift registers **952** and **954**. The shift register **960** receives bits of data in parallel and provides the bits of data serially responsive to the `pllclk_i` clock signal. The shift register **960** includes five D-flip flops (DFF) **970(0)**-**970(4)** and four multiplexers **972(0)**-**972(3)**. Each multiplexer is controlled by a load register control signal to provide either a respective bit of data or an output of a respective DFF **970**. Each of the DFFs **970(0)**-**970(4)** provides an output based on an input responsive to the `pllclk_i` clock signal (wherein i may be 0, 90, 180, or 270).

In operation, the multiplexers **972** provide a respective data bit to a corresponding DFF **970** when the load register control signal has a first logic value (e.g., high logic level). For example, when the load register control signal is a high logic level, the multiplexer **972(0)** provides bit<0> to the DFF **970(0)**, the multiplexer **972(1)** provides bit<1> to the DFF **970(1)**, the multiplexer **972(2)** provides bit<2> to the DFF **970(2)**, and the multiplexer **972(3)** provides bit<3> to the DFF **970(3)**. The value of the bit of data from a respective multiplexer **972** is output by the DFFs **970** when the `pllclk` clock signal changes to a high clock level. The load register control signal is changed to a second logic level (e.g., a low logic level) and the multiplexers **970** provide the output from a previous DFF **970**. As the `pllclk` clock signal changes between the high clock level and a low clock level, the bits of data are shifted through the DFFs **970** to provide the bits of data serially. One bit of data is provided per clock cycle of the `pllclk` clock signal.

After the last bit of data is provided, new respective bits of data may be loaded by changing the load register control signal to the first logic level. The DFFs **970** may be reset to provide an output of a known logic value by changing a hold pattern signal provided to the DFF **970(4)** to the desired logic value and clocking the `pllclk` clock signal to shift the logic value through the DFF **970(3)**, the DFF **970(2)**, the DFF **970(1)**, and then the DFF **970(0)**.

FIG. **9D** is a timing diagram illustrating the timing of the output of the bits of data by the shift register **900**, the shift register **950**, and the shift register **960** relative to one another. Generally, the shift register **900** provides four bits of data per clock cycle of the `pllclk` signal, the shift register **950** provides two bits of data per clock cycle of the `pllclk` signal, and the shift register **960** provides one bit of data per clock cycle of the `pllclk` signal.

FIG. 10 is a block diagram of a write data input circuit 1000 according to an embodiment of the disclosure. The write data input circuit 1000 includes a receiver circuit 1010 configured to receive bits of data serially (i.e., consecutive single bits) and serially provide internal data D to a sampler circuit 1020. The sampler circuit 1020 further receives four clock signals pllclk_0, pllclk_90, pllclk_180, pllclk_270. The four clock signals pllclk have a relative 90 degree phase relationship with each other. For example, the pllclk_0 may be 0 degrees, pllclk_90 may be 90 degrees, pllclk_180 may be 180 degrees, and pllclk_270 may be 270 degrees. The write data input circuit 1000 may be used for the write data input circuit 120 in an embodiment. In such an embodiment, the pllclk_0, pllclk_90, pllclk_180, and pllclk_270 clock signals provided to the write data input circuit 1000 may be the four phase clock signals IO0, IO90, IO180, and IO270. The sampler circuit 1020 samples the serially provided internal data D and provides sampled data SD responsive to the four pllclk clock signals. The sampler circuit 1020 samples one bit of the internal data D every rising edge of each of the four pllclk clock signals and provides four bits in parallel.

FIG. 11 is a diagram illustrating the relative timing of the pllclk clock signals, the serially provided internal data D from the receiver circuit 1010, and the sampled data SD provided by the sampler circuit 1020 according to an embodiment of the disclosure. In the embodiment illustrated in FIG. 11, the receiver circuit 1010 serially receives 16 bits of data and serially provides a corresponding 16 bits of internal data D. Four bits of internal data D are provided per clock cycle of the pllclk clock signals, and the sampler circuit 1020 provides four bits of sampled data SD in parallel, with each bit provided over one clock cycle of the pllclk clock signals. As the receiver circuit 1010 serially provides the internal data D, the rising edge of the pllclk_0 clock signal causes the sampler circuit 1020 to sample data bit 0 of the internal data D and provide sampled data bit 0 over one clock cycle of the pllclk_0 clock signal. The rising edge of the pllclk_90 clock signal causes the sampler circuit 1020 to sample data bit 1 of the internal data D and provide sampled data bit 1 over one clock cycle of the pllclk_90 clock signal. The rising edge of the pllclk_180 clock signal causes the sampler circuit 1020 to sample data bit 2 of the internal data D and provide sampled data bit 2 over one clock cycle of the pllclk_180 clock signal. The rising edge of the pllclk_270 clock signal causes the sampler circuit 1020 to sample data bit 3 of the internal data D and provide sampled data bit 3 over one clock cycle of the pllclk_270 clock signal. The next rising edge of the pllclk_0 clock signal causes the sampler circuit 1020 to sample data bit 4 of the internal data D and provide sampled data bit 4 over one clock cycle of the pllclk_0 clock signal. The sampling of the internal data D and providing a corresponding sampled data bit responsive to the rising edges of the pllclk_0, pllclk_90, pllclk_180, and pllclk_270 clock signals continues until the 16 bits of serially provided internal data D have been sampled (over four clock cycles of the pllclk clock signals).

As illustrated by FIG. 11, the sampler circuit 1020 serially receives 16 bits of internal data D, four bits of data per clock cycle of the pllclk clock signals, and provides four bits of sampled data SD in parallel, each bit of the sampled data provided over one clock cycle of the pllclk clock signals.

With reference to FIG. 10, the sampled data SD is provided to a serial-to-parallel (S2P) circuit 1030. The S2P circuit 1030 further receives the four pllclk clock signals and a write enable signal wren. Four delayed pllclk clock signals

are also provided to the S2P circuit 1030. The four delayed pllclk clock signals are provided by a delay circuit 1040 that delays the four pllclk clock signals. The S2P circuit 1030 receives the sampled data SD responsive to the pllclk clock signals and provides corresponding bits of data in parallel responsive to an active write enable signal wren. In an embodiment of the disclosure, 16 bits of sampled data SD are received by the S2P circuit 1030. The 16 bits of sampled data SD are received as four bits in parallel for each clock cycle of pllclk clock signals, and over four clock cycles of the pllclk signals, as previously described with reference to FIG. 11. After the 16 bits of sampled data SD have been received by the S2P circuit 1030, 16 corresponding bits of data are provided in parallel by activation of the write enable signal wren.

In summary, the write data input circuit 1000 receives bits of data serially (e.g., four bits of data per clock cycle of the pllclk clock signals) and provides corresponding bits of data in parallel. In an embodiment, 16 bits of data are received by the write data input circuit 1000 over four clock cycles of the pllclk clock signals, and 16 corresponding bits of data are provided in parallel thereafter. As previously described, the pllclk_0, pllclk_90, pllclk_180, and pllclk_270 clock signals provided to the write data input circuit 1000 may be the four phase clock signals IO0, IO90, IO180, and IO270. The IO clock signals may be provided, for example, by a clock divider circuit. The IO clock signals may have a first clock frequency in a first mode (e.g., DDR mode) and have a higher second clock frequency in a second mode (e.g., QDR mode).

FIG. 12 is a block diagram of a serial-to-parallel (S2P) circuit 1200 according to an embodiment of the disclosure. The S2P circuit 1200 may be used for the S2P circuit 1030 in an embodiment. The S2P circuit 1200 includes serial-in-parallel-out (SIPO) circuits 1210, 1220, 1230, and 1240. Each SIPO circuit receives a respective one of the four pllclk clock signals. As shown in FIG. 12, the SIPO circuit 1210 receives the pllclk_0 clock signal, the SIPO circuit 1220 receives the pllclk_90 clock signal, the SIPO circuit 1230 receives the pllclk_180 clock signal, and the SIPO circuit 1240 receives the pllclk_270 clock signal. Each of the SIPO circuits serially receives four bits of sampled data SD responsive to the respective pllclk clock signal and provides four corresponding bits in parallel. For example, in an embodiment where the S2P circuit 1200 receives 16 bits of sampled data SD as four bits in parallel for each clock cycle of pllclk clock signals, and over four clock cycles of the pllclk signals, each SIPO circuit receives four bits of sampled data serially and provides a corresponding four bits of data in parallel. The four SIPO circuits 1210, 1220, 1230, and 1240 provide a total of 16 bits of data in parallel.

FIG. 13A is a block diagram of a serial-in-parallel-out (SIPO) circuit 1300 according to an embodiment of the disclosure. The SIPO circuit 1300 may be used for the SIPO circuit 1210, 1220, 1230, and 1240. The SIPO circuit 1300 includes a pointer counter circuit 1310 that receives a pllclk clock signal and provides pointer signals iptr<0>, iptr<1>, iptr<2>, and iptr<3>. The pointer counter circuit 1310 sequentially provides one active pointer signal responsive to the pllclk clock signal. The SIPO circuit 1300 further includes a SIPO block 1320. The SIPO block includes latches 1330(0)-1330(3) and 1340(0)-1340(3), and buffers 1350(0)-1350(3). The latch 1330(0) latches and provides data responsive to an active pointer signal iptr<0>, the latch 1330(1) latches and provides data responsive to an active pointer signal iptr<1>, the latch 1330(2) latches and provides data responsive to an active pointer signal iptr<2>, and

the latch **1330(3)** latches and provides data responsive to an active pointer signal $\text{iptr}\langle 3 \rangle$. The latches **1340(0)**-**1340(3)** latch and provide respective data responsive to an active pointer signal $\text{iptr}\langle 3 \rangle$. The buffers **1350(0)**-**1350(3)** are concurrently activated by an active write enable signal wren to output data BP0 - BP3 in parallel, which correspond to the data of the latches **1340(0)**-**1340(3)**.

FIG. **13B** is a timing diagram illustrating the various signals during operation of the SIPO circuit **1300** according to an embodiment of the disclosure. The various signals illustrated by FIG. **13B** are for the SIPO circuit **1300** when used as the SIPO circuit **1210** of FIG. **12**.

As previously described with reference to FIGS. **10** and **11**, bit **0**, bit **4**, bit **8**, and bit **C** of the bits of sampled data SD are provided by the sampler circuit **1020** over four clock cycles of the pllclk_0 clock signal. With reference to FIG. **13B**, a rising edge of the pllclk_0 clock signal at time T0 causes the pointer counter circuit **1310** to provide an active pointer signal $\text{iptr}\langle 0 \rangle$ to cause the latch **1330(0)** to latch bit **0** of the sampled data SD and provide the same to the latch **1340(0)**. A rising edge of the pllclk_0 clock signal at time T1 causes the pointer counter circuit **1310** to provide an active pointer signal $\text{iptr}\langle 1 \rangle$ to cause the latch **1330(1)** to latch bit **4** of the sampled data SD and provide the same to the latch **1340(1)**. A rising edge of the pllclk_0 clock signal at time T2 causes the pointer counter circuit **1310** to provide an active pointer signal $\text{iptr}\langle 2 \rangle$ to cause the latch **1330(2)** to latch bit **8** of the sampled data SD and provide the same to the latch **1340(2)**. A rising edge of the pllclk_0 clock signal at time T3 causes the pointer counter circuit **1310** to provide an active pointer signal $\text{iptr}\langle 3 \rangle$ to cause the latch **1330(3)** to latch bit **C** of the sampled data SD and provide the same to the latch **1340(3)**. The rising edge of the pllclk_0 clock signal at time T3 also causes the latches **1340(0)**-**1340(3)** to latch and provide the respective input data and provide the same to a respective buffer **1350(0)**-**1350(3)**. A rising edge of the pllclk_0 clock signal at time T4 causes the write enable signal wren to activate the buffers **1350(0)**-**1350(3)** to provide the respective bit of data. As illustrated by the previous example, four bits of sampled data provided to the SIPO circuit **1300** serially are latched responsive to the pllclk clock signal and then provided in parallel.

FIG. **14** is a block diagram of a command buffer **1400** according to an embodiment of the disclosure. The command buffer **1400** may be implemented as a first-in, first-out (FIFO) buffer. The command buffer **1400** includes a input pointer counter circuit **1410** and an output pointer counter circuit **1420**. The input pointer counter circuit **1410** receives complementary clock signals clk_int and clk_inf , and further receives an input pointer counter reset signal reset_inp . The input pointer counter circuit **1410** provides an active input pointer signal inp_pointer responsive to the clk_int and clk_inf clock signals. For example, responsive to first clock transitions of the clk_int and clk_inf clock signals (e.g., the clk_int clock signal transitions to a high clock level and the clk_inf clock signal transitions to a low clock level) the input pointer counter circuit **1410** provides an active $\text{inp_pointer}\langle 0 \rangle$ signal with all other inp_pointer signals inactive. Responsive to second clock transitions of the clk_int and clk_inf clock signals, the input pointer counter circuit **1410** provides an active $\text{inp_pointer}\langle 1 \rangle$ signal with all other inp_pointer signals inactive. The next clock transitions result in an active $\text{inp_pointer}\langle 2 \rangle$ signal, and so on. In an embodiment of the disclosure, the input pointer signals includes five input pointer signals $\text{inp_pointer}\langle 0 \rangle$, $\text{inp_pointer}\langle 1 \rangle$, $\text{inp_pointer}\langle 2 \rangle$, $\text{inp_pointer}\langle 3 \rangle$, and $\text{inp_pointer}\langle 4 \rangle$. The input pointer counter circuit **1410** is

reset to a known state (e.g., providing an active $\text{inp_pointer}\langle 0 \rangle$ signal with all other inp_pointer signals inactive) by an active reset signal reset_inp .

The output pointer counter circuit **1420** receives complementary clock signals clk_outt and clk_outf , and further receives an output pointer counter reset signal reset_outp . The output pointer counter circuit **1420** provides an active output pointer signal outp_pointer responsive to the clk_outt and clk_outf clock signals. For example, responsive to first clock transitions of the clk_outt and clk_outf clock signals (e.g., the clk_outt clock signal transitions to a high clock level and the clk_outf clock signal transitions to a low clock level) the output pointer counter circuit **1420** provides an active $\text{outp_pointer}\langle 0 \rangle$ signal with all other outp_pointer signals inactive. Responsive to second clock transitions of the clk_outt and clk_outf clock signals, the output pointer counter circuit **1420** provides an active $\text{outp_pointer}\langle 1 \rangle$ signal with all other outp_pointer signals inactive. The next clock transitions result in an active $\text{outp_pointer}\langle 2 \rangle$ signal, and so on. In an embodiment of the disclosure, the output pointer signals includes five output pointer signals $\text{outp_pointer}\langle 0 \rangle$, $\text{outp_pointer}\langle 1 \rangle$, $\text{outp_pointer}\langle 2 \rangle$, $\text{outp_pointer}\langle 3 \rangle$, and $\text{outp_pointer}\langle 4 \rangle$. The output pointer counter circuit **1420** is reset to a known state (e.g., providing an active $\text{outp_pointer}\langle 0 \rangle$ signal with all other outp_pointer signals inactive) by an active reset signal reset_outp .

The input and output pointer signals are provided to a buffer block **1430**. The buffer block **1430** receives input commands command_in that are buffered responsive to an active input pointer signal and receives commands command_out that are provided by the buffer block **1430** responsive to an active output pointer signal. In this manner, the commands are buffered according to the timing of the clk_int and clk_inf clock domain and the commands are provided according to the timing of the clk_outt and clk_outf clock domain. The buffer block **1430** includes D flip flops (DFFs) **1440(0)**-**1440(4)** and buffers **1450(0)**-**1450(4)**. In an embodiment, the buffers **1450(0)**-**1450(4)** may be tristate buffers. A tristate buffer has a high impedance when deactivated, and provides an output based on the input when activated.

Each DFF **1440(0)**-**1440(4)** is clocked by a respective input pointer signal inp_pointer to capture an input command and provide the command to a respective buffer **1450(0)**-**1450(4)**. For example, the DFF **1440(0)** captures a command (i.e., command_in) and provides the command to the buffer **1450(0)** responsive to the input pointer signal $\text{inp_pointer}\langle 0 \rangle$, the DFF **1440(1)** captures a command (i.e., command_in) and provides the command to the buffer **1450(1)** responsive to the input pointer signal $\text{inp_pointer}\langle 1 \rangle$, the DFF **1440(2)** captures a command (i.e., command_in) and provides the command to the buffer **1450(2)** responsive to the input pointer signal $\text{inp_pointer}\langle 2 \rangle$, and so on. Each buffer **1450(0)**-**1450(4)** is activated responsive to a respective output pointer signal outp_pointer to provide the command at its input as provided by a respective DFF **1440**. For example, the buffer **1450(0)** is activated and provides a respective command responsive to the output pointer signal $\text{outp_pointer}\langle 0 \rangle$, the buffer **1450(1)** is activated and provides a respective command responsive to the output pointer signal $\text{outp_pointer}\langle 1 \rangle$, the buffer **1450(2)** is activated and provides a respective command responsive to the output pointer signal $\text{outp_pointer}\langle 2 \rangle$, and so on.

In the embodiment of FIG. 14, the command buffer 1400 has a depth of five. That is, the command buffer 1400 can buffer five commands before writing over the earliest buffered command.

In operation, the command_in commands are captured by an activated one of the DFFs 1440 responsive to the clk_int and clk_inf clock signals. The clk_int and clk_inf clock signals cause the input pointer counter circuit 1410 to provide an active input pointer to clock one of the DFFs 1440 to capture the command_in command. The input pointers are activated sequentially, so that command_in commands may be captured by the DFFs 1440 as the clk_int and clk_inf clock signals clocks between high and low clock levels. The command buffer 1400 provides commands from the latches 1440(0)-1440(4) one at a time by controlling activation of the buffers 1450(0)-1450(4) with the output pointer signals outp_pointer responsive to the clk_outt and clk_outf clock signals. As the clk_outt and clk_outf clock signals clock between high and low clock signals the output pointer counter circuit 1420 sequentially provides an active output pointer signal outp_pointer to activate a respective buffer 1450.

The command buffer 1400 may be used as the read command buffer 114. In an embodiment where the command buffer 1400 is used as the read command buffer 114, the clk_int and clk_inf clock signals may be the internal clock signals CACLK and CACLKF, and the clk_outt and clk_outf clock signals may be the BUFCLK and BUFCLKF clock signals. The command_in commands may be the RDCMD read commands. The command buffer 1400 may be used as the write command buffer 114. In an embodiment where the command buffer 1400 is used as the write command buffer 112, the clk_int and clk_inf clock signals may be the internal clock signals CACLK and CACLKF, and the clk_outt and clk_outf clock signals may be the BUFCLK and BUFCLKF clock signals. The command_in commands may be the WRCMD write commands.

FIG. 15 is a block diagram of a counter circuit 1500 according to an embodiment of the disclosure. The counter circuit 1500 is a five-bit counter that provides one active value responsive to the complementary clock signals clk_0_i and clk_180_i. The counter circuit 1500 includes D flip flops (DFFs) 1510(0)-1510(4). The DFFs 1510(0)-1510(4) receive the clk_0_i and clk_180_i clock signals. A reset signal reset_n_i is provided to the DFF 1510(4) to reset the counter circuit to a known value. In an embodiment of the disclosure, the counter circuit 1500 may be used for the input pointer counter circuit 1410, and also used as the output pointer counter circuit 1420. In such an embodiment, the clk_0_i and clk_180_i clock signals for use as an input pointer counter circuit 1410 are provided by the clk_int and clk_inf clock signals, and the reset_n_i signal is provided by the reset_inp signal. The clk_0_i and clk_180_i clock signals when the counter circuit 1500 is used use as an input pointer counter circuit 1420 are provided by the clk_outt and clk_outf clock signals, and the reset_n_i signal is provided by the reset_outp signal.

In operation, as the clk_0_i and clk_180_i clock signals clock between high and low clock levels, an active value (e.g., high logic level) propagates through the DFFs 1510(0)-1510(4) and wraps around when reaching the DFF 1510(4). For example, responsive to a first rising edge of the clk_0_i clock signal (and a falling edge of the clk_180_i clock signal), the DFF 1510(0) provides a high logic level output and the remaining DFFs 1510(1)-1510(4) provide a low logic level output (i.e., the output count cnt_0<4:0> is 00001). The high logic level of the DFF 1510(0) is also

provided to the input of the DFF 1510(1) and the low logic level of the DFF 1510(4) is provided to the input of the DFF 1510(0). Responsive to a second rising edge of the clk_0_i clock signal (and a falling edge of the clk_180_i clock signal), the DFF 1510(1) provides a high logic level output because of the high logic level from the DFF 1510(0), and the remaining DFFs 1510(0) and 1510(2)-1510(4) provide a low logic level output (i.e., the output count cnt_0<4:0> is 00010). The high logic level of the DFF 1510(1) is also provided to the input of the DFF 1510(2) and the low logic level of the DFF 1510(0) is provided to the input of the DFF 1510(1). Responsive to a third rising edge of the clk_0_i clock signal (and a falling edge of the clk_180_i clock signal), the DFF 1510(2) provides a high logic level output because of the high logic level from the DFF 1510(1), and the remaining DFFs 1510(0), 1510(1), 1510(3), and 1510(4) provide a low logic level output (i.e., the output count cnt_0<4:0> is 00100). As the clk_0_i and clk_180_i clock signals continue to clock between high and low clock levels the high logic level output propagates through the DFFs.

From the foregoing it will be appreciated that, although specific examples have been described herein for purposes of illustration, various modifications may be made without deviating from the scope of the disclosure. That is, specific examples have been described with reference to the Figures, however, these specific examples have been provided by way of example, and are not intended to limit the scope of the disclosure to the specific examples. For example, specific numbers of clock signals have been previously described for some of the Figures. However, the specific numbers of clock signals were provided merely as examples, and do not limit the scope of the disclosures to those embodiments having the specific numbers of clock signals. For example, with reference to FIGS. 2 and 5, rather than using two command and address clock signals CACLK, CACLKF, and two buffer clock signals BUFCLK, BUFCLKF for write and read command buffers 112 and 114, another embodiment may use one command address clock signal and one buffer clock signal. In another example, the read data output circuit 118 is described as receiving 16 bits of data and the write data input circuit 120 is described as providing 16 bits of data, in another embodiment the read data output circuit may receive greater or fewer bits of data, and the write data input circuit may provide greater or fewer bits of data. Generally, as previously discussed, describing details of specific examples is not intended to limit the scope of the disclosure to those specific examples. Accordingly, the scope of the disclosure should not be limited except as by the appended claims.

What is claimed is:

1. An apparatus, comprising:

- a read data output circuit configured to receive read data in parallel and serially provide the read data when activated by a read command and responsive to input/output (IO) clock signals;
- a write data input circuit configured to serially receive write data and provide the write data when activated by a write command and responsive to the IO clock signal; and
- a data clock timing circuit configured to receive four phase input clock signals having a first clock frequency, and responsive to the four phase input clock signals, configured to provide the IO clock signals having the first clock frequency in a first mode and provide the IO clock signals having a second clock frequency in a second mode wherein the second clock frequency is higher than the first clock frequency.

25

2. The apparatus of claim 1 wherein the data clock timing circuit comprises:
- a phase locked loop (PLL) circuit configured to receive the four phase input clock signals and provide four phase PLL clock signals having the second clock frequency;
 - a first multiplexer coupled to receive the four phase input clock signals and to receive the four phase PLL clock signals, the first multiplexer configured to selectively provide responsive to a multiplexer control signal the four phase input clock signals or the four phase PLL clock signals as the IO clock signals;
 - a clock divider circuit coupled to receive the four phase PLL clock signals and provide four phase divided clock signals having the first clock frequency, wherein two of the four phase divided clock signals are provided to the PLL circuit; and
 - a second multiplexer coupled to receive the two of the four phase divided clock signals and to receive two of the IO clock signals, the second multiplexer configured to selectively provide responsive to the multiplexer controls signal the two of the four phase divided clock signals or the two of the IO clock signals as a buffer clock signal, wherein the buffer clock signal has the first clock frequency.
3. The apparatus of claim 2 wherein the PLL circuit comprises:
- a phase frequency detector;
 - a filter circuit; and
 - a voltage controlled oscillator.
4. The apparatus of claim 1 wherein the data clock timing circuit comprises:
- a phase locked loop (PLL) circuit configured to receive the four phase input clock signals and provide eight phase PLL clock signals having the first clock frequency;
 - a logic circuit coupled to receive the eight phase PLL clock signals and provide four phase logic clock signals having the second frequency, two of the four phase logic clock signals provided to the PLL circuit;
 - a first multiplexer coupled to receive the four phase input clock signals and to receive the four phase logic clock signals, the first multiplexer configured to selectively provide responsive to a multiplexer control signal the four phase input clock signals or the four phase logic clock signals as the IO clock signals; and
 - a second multiplexer coupled to receive the two of the eight phase PLL clock signals and to receive two of the IO clock signals, the second multiplexer configured to selectively provide responsive to the multiplexer con-

26

- trols signal the two of the eight phase PLL clock signals or the two of the IO clock signals as a buffer clock signal, wherein the buffer clock signal has the first clock frequency.
5. The apparatus of claim 4 wherein the PLL circuit comprises:
- a phase frequency detector;
 - a filter circuit; and
 - a voltage controlled oscillator.
6. The apparatus of claim 1, further comprising:
- a write command buffer configured to buffer write commands responsive to command and address clock signals and provide the write commands to the write data input circuit responsive to a buffer clock signal, wherein the buffer clock signal has the first clock frequency; and
 - a read command buffer configured to buffer read commands responsive to the command and address clock signals and provide the read commands responsive to the buffer clock signal.
7. A method, comprising:
- providing four phase clock signals having a first clock frequency to a read data output circuit when in a first mode;
 - providing the four phase clock signals having a second clock frequency to the read data output circuit when in a second mode;
 - activating the read data output circuit;
 - receiving at the read data output circuit a plurality of bits of data in parallel; and
 - serially outputting the plurality of bits of data responsive to the four phase clock signals.
8. The method of claim 7 wherein activating the read data output circuit comprises providing a read command to the read data output circuit.
9. The method of claim 8 wherein the read command is provided by a read command buffer and the method further comprises providing a buffer clock signal having the first clock frequency in both the first and second modes.
10. The method of claim 7 wherein providing the four phase clock signals comprises providing four clock signals having a 90 degree phase relationship with each other.
11. The method of claim 7 wherein the first mode is a double data rate mode and the second mode is a quad data rate mode.
12. The method of claim 7 wherein the second clock frequency is twice the clock frequency of the first clock frequency.

* * * * *