



US010303041B2

(12) **United States Patent**
Sharma

(10) **Patent No.:** **US 10,303,041 B2**
(45) **Date of Patent:** **May 28, 2019**

(54) **CLOSED LOOP POSITION CONTROL FOR CAMERA ACTUATOR**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)
(72) Inventor: **Shashank Sharma**, San Francisco, CA (US)
(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 149 days.

(21) Appl. No.: **15/233,661**

(22) Filed: **Aug. 10, 2016**

(65) **Prior Publication Data**

US 2018/0046063 A1 Feb. 15, 2018

(51) **Int. Cl.**

G03B 13/36 (2006.01)
G03B 5/02 (2006.01)
G03B 3/10 (2006.01)
G02B 7/08 (2006.01)
G02B 27/64 (2006.01)
H04N 5/232 (2006.01)

(52) **U.S. Cl.**

CPC **G03B 13/36** (2013.01); **G02B 7/08** (2013.01); **G02B 27/646** (2013.01); **G03B 3/10** (2013.01); **G03B 5/02** (2013.01); **H04N 5/23212** (2013.01); **H04N 5/23287** (2013.01); **G03B 2205/0015** (2013.01); **G03B 2205/0069** (2013.01)

(58) **Field of Classification Search**

CPC . H04N 5/23287; H04N 5/23212; G03B 13/36
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2015/0146025 A1 5/2015 Bang et al.
2015/0296112 A1* 10/2015 Park H04N 5/2257
348/208.7
2016/0018624 A1 1/2016 Yeo
2016/0070270 A1* 3/2016 Beard G02B 27/646
318/647

(Continued)

FOREIGN PATENT DOCUMENTS

WO 2008041171 4/2008
WO 2016040353 4/2008
WO 2015045527 4/2015

OTHER PUBLICATIONS



International Search Report and Written Opinion from PCT/US2017/045747, dated Nov. 6, 2017, Apple Inc., pp. 1-11.

Primary Examiner — Christopher K Peterson
(74) *Attorney, Agent, or Firm* — Robert C. Kowert; Meyertons, Hood, Kivlin, Kowert & Goetzel, P.C.

(57) **ABSTRACT**

In some embodiments, a camera unit of a multifunction device may include an optical package and an actuator for moving the optical package. In some embodiments, the actuator may include an asymmetric magnet arrangement. The asymmetric magnet arrangement may include a lateral position control magnet situated at a first side of the optical package, and a pair of transverse position control magnets situated at respective second and third sides of the optical package opposite one another with respect to an axis between the optical package and the lateral magnet. In some embodiments, the actuator may include one or more position sensor magnets attached to the optical package, and one or more magnetic field sensors for determining a position of the position sensor magnets.

18 Claims, 12 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0178869 A1* 6/2016 Shen G02B 13/0035
348/208.11
2016/0231528 A1 8/2016 Wong et al.
2017/0139225 A1* 5/2017 Lim G02B 27/646

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F




FIG. 2G




FIG. 2H




FIG. 2I




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

1

CLOSED LOOP POSITION CONTROL FOR CAMERA ACTUATOR

BACKGROUND

Technical Field

This disclosure relates generally to position measurement and more specifically to position measurement for managing the motion of camera components.

Description of the Related Art

The advent of small, mobile multipurpose devices such as smartphones and tablet or pad devices has resulted in a need for high-resolution, small form factor cameras for integration in the devices. Some small form factor cameras may incorporate optical image stabilization (OIS) mechanisms that may sense and react to external excitation/disturbance by adjusting location of the optical lens on the X and/or Y axis in an attempt to compensate for unwanted motion of the lens. Some small form factor cameras may incorporate an autofocus (AF) mechanism whereby the object focal distance can be adjusted to focus an object plane in front of the camera at an image plane to be captured by the image sensor. In some such autofocus mechanisms, the optical lens is moved as a single rigid body along the optical axis (referred to as the Z axis) of the camera to refocus the camera.

In addition, high image quality is easier to achieve in small form factor cameras if lens motion along the optical axis is accompanied by minimal parasitic motion in the other degrees of freedom, for example on the X and Y axes orthogonal to the optical (Z) axis of the camera. Thus, some small form factor cameras that include autofocus mechanisms may also incorporate optical image stabilization (OIS) mechanisms that may sense and react to external excitation/disturbance by adjusting location of the optical lens on the X and/or Y axis in an attempt to compensate for unwanted motion of the lens. In such systems, knowledge of the position of the lens is useful.

SUMMARY OF EMBODIMENTS

Some embodiments include a camera unit of a multifunction device. The camera unit may include an optical package and an actuator for moving the optical package. In some embodiments, the actuator may include an asymmetric magnet arrangement for actuation along an optical axis and/or along a plane that is orthogonal to the optical axis. The asymmetric magnet arrangement may include a lateral position control magnet and a pair of transverse position control magnets. The lateral position control magnet may be situated at a first side of the optical package. The pair of transverse position control magnets may be situated on respective second and third sides of the optical package opposite one another with respect to an axis between the optical package and the lateral position control magnet.

Furthermore, the actuator may include one or more position sensor magnets and one or more magnetic field sensors. The position sensor magnets may be attached to the optical package. The magnetic field sensors may be used to determine a position of at least one of the position sensor magnets. For instance, the optical package may include one or more lenses that define an optical axis, and a magnetic field sensor may be used to determine a position of a position sensor magnet along the optical axis.

2

Some embodiments include a magnetic actuator for moving an optical package. The magnetic actuator may include an asymmetric magnet arrangement for actuation along an optical axis of the optical package and/or along a plane that is orthogonal to the optical axis. The asymmetric magnet arrangement may include a lateral position control magnet, a first transverse position control magnet, and a second transverse position control magnet. The lateral position control magnet may be disposed proximate a first side of a moving member that is attached to the optical package. The first transverse position control magnet may be disposed proximate a second side of the moving member. The second transverse position control magnet may be disposed proximate a third side of the moving member. The third side may be opposite the second side with respect to an axis between the moving member and the lateral position control magnet.

Furthermore, the magnetic actuator may include one or more position sensor magnets and one or more magnetic field sensors for determining a position of the moving member. The position sensor magnets may be attached to the moving member. The magnetic field sensors may be used to determine a position of the moving member.

Some embodiments include a system having an optical package and an actuator for moving the optical package. The actuator may include an asymmetric magnet arrangement for actuation along an optical axis and/or along a plane that is orthogonal to the optical axis. The asymmetric magnet arrangement may include a lateral position control magnet and a pair of transverse position control magnets. The lateral position control magnet may be situated at a first side of the optical package. The pair of transverse position control magnets may be situated on respective second and third sides of the optical package opposite one another with respect to an axis between the optical package and the lateral position control magnet.

Furthermore, the actuator may include one or more position sensor magnets and one or more magnetic field sensors. The position sensor magnets may be attached to the optical package. The magnetic field sensors may be configured to measure one or more magnetic field components. For instance, at least one of the transverse position control magnets may contribute to a first magnetic field component corresponding to a first axis, and at least one of the position sensor magnets may contribute to a second magnetic field component corresponding to a second axis that is orthogonal to the first axis. In some embodiments, at least one of the magnetic field sensors may be configured to measure the first magnetic field component and the second magnetic field component.

In some embodiments, the system may include one or more processors and memory. The memory may include program instructions that, when executed by the processors, cause the processors to perform operations. In some implementations, the operations may include determining the first magnetic field component. For instance, the determination of the first magnetic field may be based at least in part on one or more measurements from a magnetic field sensor. Furthermore, the operations may include determining the second magnetic field component. For instance, the determination of the second magnetic field component may be based at least in part on one or more measurements from the magnetic field sensor. In various examples, the operations may include calculating a position of a position sensor magnet along an optical axis defined by one or more lenses of the optical package. For instance, the calculation of the position of the position sensor magnet along the optical axis

may be based at least in part on the first magnetic field component and the second magnetic field component.

Some implementations include a method for determining a position of one or more camera components. The method may include generating a measurement of a magnetic field resulting at least in part from one or more position sensor magnets. For example, the measurement may be generated by using one or more magnetic field sensors to measure a magnetic field component created at least in part by one or more position sensor magnets that are fixedly mounted to a camera lens carrier. The camera lens carrier may be moveably coupled to a substrate. The magnetic field sensors may be fixedly mounted to the substrate. An autofocus actuator may provide motion of the camera lens carrier in a direction orthogonal to the substrate. In some implementations, the method may include calculating a position measurement for the lens carrier. For instance, position measurement for the lens carrier may be calculated based at least in part on the measurement of the magnetic field resulting from the position sensor magnets. Furthermore, the method may include adjusting a position of the camera lens carrier by altering a voltage and/or a current supplied to an autofocus coil of the autofocus actuator attached to the camera lens carrier. For example, the voltage and/or the current supplied to the autofocus coil may be altered based at least in part on position measurement calculated for the lens carrier.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A illustrates an example embodiment of a camera having an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 1B depicts an example embodiment of an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 1C illustrates an example embodiment of an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 2A depicts a side view of an example embodiment of an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 2B illustrates a top view of an example embodiment of an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 2C depicts a side view of an example embodiment of an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 2D illustrates a side view of an example embodiment of an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 2E depicts a side view of an example embodiment of an actuator module or assembly that may, for example, be

used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 2F illustrates a side view of an example embodiment of an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 2G depicts a side view of an example embodiment of an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 2H illustrates a side view of an example embodiment of an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 2I depicts a side view of an example embodiment of an actuator module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments.

FIG. 3 is a flowchart of a method for magnetic sensing for autofocus position detection and control, according to at least some embodiments.

FIG. 4 is a flowchart of a method for magnetic sensing for autofocus position detection and control, according to at least some embodiments.

FIG. 5 illustrates a block diagram of a portable multifunction device with a camera that may include an actuator module in accordance with some embodiments.

FIG. 6 depicts a portable multifunction device having a camera that may include an actuator module in accordance with some embodiments.

FIG. 7 illustrates an example computer system configured to implement aspects of magnetic sensing for autofocus and/or optical image stabilization position detection and control, according to some embodiments.

This specification includes references to “one embodiment” or “an embodiment.” The appearances of the phrases “in one embodiment” or “in an embodiment” do not necessarily refer to the same embodiment. Particular features, structures, or characteristics may be combined in any suitable manner consistent with this disclosure.

“Comprising.” This term is open-ended. As used in the appended claims, this term does not foreclose additional structure or steps. Consider a claim that recites: “An apparatus comprising one or more processor units” Such a claim does not foreclose the apparatus from including additional components (e.g., a network interface unit, graphics circuitry, etc.).

“Configured To.” Various units, circuits, or other components may be described or claimed as “configured to” perform a task or tasks. In such contexts, “configured to” is used to connote structure by indicating that the units/circuits/components include structure (e.g., circuitry) that performs those task or tasks during operation. As such, the unit/circuit/component can be said to be configured to perform the task even when the specified unit/circuit/component is not currently operational (e.g., is not on). The units/circuits/components used with the “configured to” language include hardware—for example, circuits, memory storing program instructions executable to implement the operation, etc. Reciting that a unit/circuit/component is “configured to” perform one or more tasks is expressly intended not to invoke 35 U.S.C. § 112, sixth paragraph, for

that unit/circuit/component. Additionally, “configured to” can include generic structure (e.g., generic circuitry) that is manipulated by software and/or firmware (e.g., an FPGA or a general-purpose processor executing software) to operate in manner that is capable of performing the task(s) at issue. “Configure to” may also include adapting a manufacturing process (e.g., a semiconductor fabrication facility) to fabricate devices (e.g., integrated circuits) that are adapted to implement or perform one or more tasks.

“First,” “Second,” etc. As used herein, these terms are used as labels for nouns that they precede, and do not imply any type of ordering (e.g., spatial, temporal, logical, etc.). For example, a buffer circuit may be described herein as performing write operations for “first” and “second” values. The terms “first” and “second” do not necessarily imply that the first value must be written before the second value.

“Based On.” As used herein, this term is used to describe one or more factors that affect a determination. This term does not foreclose additional factors that may affect a determination. That is, a determination may be solely based on those factors or based, at least in part, on those factors. Consider the phrase “determine A based on B.” While in this case, B is a factor that affects the determination of A, such a phrase does not foreclose the determination of A from also being based on C. In other instances, A may be determined based solely on B.

DETAILED DESCRIPTION

Some embodiments include camera equipment outfitted with controls, magnets, and sensors to improve the position accuracy of a miniature actuation mechanism for a compact camera module. More specifically, in some embodiments, compact camera modules may include one or more actuators to deliver functions such as autofocus (AF) and optical image stabilization (OIS). One approach to delivering a very compact actuator for OIS is to use a Voice Coil Motor (VCM) arrangement including one or more AF coils, one or more OIS coils, and/or one or more magnets. As current is applied to the coils, the magnetic fields generated interact with the magnetic fields of the magnets to generate forces that move at least a portion of the actuator in a desired manner. One or more position sensor magnets may be attached to the moving portion (or moving body) of the actuator, and one or more magnetic field sensors (e.g., Hall sensors, tunneling magnetoresistance (TMR) sensor, giant magnetoresistance (GMR) sensor, etc.) may be used to determine a position of the position sensor magnets. As a position sensor magnet moves with the moving portion of the actuator, the magnetic field component(s) detected by the magnetic field sensor may change, which in turn may alter the voltage across sense terminals of the magnetic field sensor.

Some embodiments may allow the magnetic field sensor output voltage to be very well correlated to the position of the moving body of the actuator, such that the sensor output can be used as a measure of position, and be used to feedback the position, and allow more accurate positioning. Using a VCM, in some embodiments the forces generated may be substantially linear with applied current. Furthermore, the position of the moving body may be substantially proportional to the current applied to the coils.

In some embodiments, a camera unit of a multifunction device may include an optical package and an actuator for moving the optical package. The actuator may include an asymmetric magnet arrangement for actuation along an optical axis and/or along a plane that is orthogonal to the

optical axis. The asymmetric magnet arrangement may include a lateral position control magnet and a pair of transverse position control magnets. The lateral position control magnet may be situated at a first side of the optical package. The pair of transverse position control magnets may be situated on respective second and third sides of the optical package opposite one another with respect to an axis between the optical package and the lateral position control magnet. In some embodiments, the asymmetric magnet arrangement may allow for the camera unit to be located adjacent, or proximate to, another camera unit such as to reduce or eliminate interference between the magnetic fields of the adjacent camera units. In some examples, the camera unit may be a first camera unit that is disposed adjacent, or proximate to, a second camera unit that has a symmetric magnet arrangement.

Furthermore, the actuator may include one or more position sensor magnets and one or more magnetic field sensors. The position sensor magnets may be attached to the optical package. The magnetic field sensors may be used to determine a position of at least one of the position sensor magnets. For instance, the optical package may include one or more lenses that define an optical axis, and a magnetic field sensor may be used to determine a position of a position sensor magnet along the optical axis. In some embodiments, the magnetic field sensors may include one or more Hall sensors, one or more TMR sensors, and/or one or more GMR sensors.

In some examples, at least one of the transverse position control magnets may contribute to a first magnetic field component corresponding to a first axis, and at least one of the position sensor magnets may contribute to a second magnetic field component corresponding to a second axis. For instance, the second axis may be orthogonal to the first axis. Furthermore, at least one of the magnetic field sensors may be configured to measure at least one of the first magnetic field component and the second magnetic field component. For example, the magnetic field sensors may be configured to measure both the first magnetic field component and the second magnetic field component for determination of an angle between the first magnetic field component and the second magnetic field component. In some examples, the angle between the first magnetic field component and the second magnetic field component may be an angle of the resultant magnetic flux density vector that is based on a first magnetic flux density vector corresponding to the first magnetic field component and a second magnetic flux density vector corresponding to the second magnetic field component.

According to some examples, a pair of position sensor magnets may be oriented with magnetic fields transverse to magnetic fields of the pair of transverse position control magnets. For instance, the pair of position sensor magnets may be situated on the respective second and third sides of the optical package opposite one another with respect to the axis between the optical package and the lateral position control magnet. Additionally or alternatively, a pair of position sensor magnets may be oriented with magnetic fields having polarity alignments that are parallel and/or antiparallel to polarity alignments of magnetic fields of the pair of transverse position control magnets. In some examples, the pair of position sensor magnets may be situated on the first side and a fourth side of the optical package. The fourth side of the optical package may be opposite the first side along the axis between the optical package and the lateral position control magnet.

In some examples, a non-magnetic dummy mass may be situated at the fourth side of the optical package. Furthermore, in some embodiments, there may be no magnets situated at the fourth side of the optical package. For instance, there may be no lateral position control magnets or transverse position control magnets situated at the fourth side of the optical package.

In some embodiments, an actuator for moving an optical package may include an asymmetric magnet arrangement for actuation along an optical axis and/or along a plane that is orthogonal to the optical axis. The asymmetric magnet arrangement may include a lateral position control magnet, a first transverse position control magnet, and a second transverse position control magnet. The lateral position control magnet may be disposed proximate a first side of a moving member that is attached to the optical package. The first transverse position control magnet may be disposed proximate a second side of the moving member. The second transverse position control magnet may be disposed proximate a third side of the moving member. The third side may be opposite the second side with respect to an axis between the moving member and the lateral position control magnet.

Furthermore, the magnetic actuator may include one or more position sensor magnets and one or more magnetic field sensors for determining a position of the moving member. The position sensor magnets may be attached to the moving member. In various embodiments, the optical package may include one or more lenses that define an optical axis, and at least one of the magnetic field sensors may be configured to measure at least one magnetic field component for determination of a position of the moving member with respect to the optical axis. The magnetic field sensors may include, for example, a Hall sensor, a TMR sensor, and/or a GMR sensor. In some embodiments, the magnetic field sensors may include at least one Hall sensor and at least one of a TMR sensor or a GMR sensor.

In some examples, the optical package may be attached to a top side of the moving member, and the magnetic field sensors may be attached to a base disposed proximate a bottom side of the moving member. The bottom side of the moving member may be opposite the top side of the moving member. The magnetic actuator may be configured to move the moving member relative to the base.

In some examples, the first transverse position control magnet may contribute to a first magnetic field component corresponding to a first axis, and at least one of the position sensor magnets may contribute to a second magnetic field component corresponding to a second axis. For instance, the second axis may be orthogonal to the first axis. Furthermore, at least one of the magnetic field sensors may be configured to measure the first magnetic field component and/or the second magnetic field component.

In some embodiments, the position sensor magnets may include a first position sensor magnet and a second position sensor magnet. The first position sensor magnet may be oriented with a first magnetic field along a first direction. The second position sensor magnet may be oriented with a second magnetic field along a second direction. In some examples, the second direction may be antiparallel to the first direction. In other embodiments, the second direction may be parallel to the first direction.

In some embodiments, the magnetic field sensors may include a first magnetic field sensor and a second magnetic field sensor. For instance, the first magnetic field sensor may be disposed proximate the second side of the moving member, and the second magnetic field member may be disposed proximate the third side of the moving member.

According to some embodiments, the magnetic actuator may include one or more autofocus coils that are attached to the moving member. In some embodiments, the magnetic actuator may include two autofocus coils attached to the moving member. A first autofocus coil may be disposed proximate the first transverse position control magnet and/or proximate the second side of the moving member. Likewise, a second autofocus coil may be disposed proximate the second transverse position control magnet and/or proximate the third side of the moving member. Other embodiments, however, may include fewer or more autofocus coils. Furthermore, the autofocus coils may be positioned differently in other embodiments.

In some examples, at least one autofocus coil may define a central space that is encircled by the autofocus coil. One or more position sensor magnets may be disposed (or nested) within the central space encircled by the autofocus coil. In some embodiments, a support structure may be disposed within the autofocus coil. In such embodiments, one or more position sensor magnets may be attached to the support structure. The support structure may be configured to support the position sensor magnet(s) within the central space encircled by the autofocus coil such that the position sensor magnet(s) move along with the autofocus coil and the moving member.

In some embodiments, the magnetic actuator may include optical image stabilization coils. The optical image stabilization coils may be disposed proximate, or attached to, the base. In some examples, the magnetic actuator may include three optical image stabilization coils. For instance, a first optical image stabilization coil may be disposed on the base and proximate the first side of the moving member. A second optical image stabilization coil may be disposed on the base and proximate the second side of the moving member. A third optical image stabilization coil may be disposed on the base and proximate the third side of the moving member. Other examples, however, may include fewer or more optical image stabilization coils. Moreover, the optical image stabilization coils may be positioned differently in other embodiments.

In some embodiments, a system may include an optical package and an actuator for moving the optical package. The actuator may include an asymmetric magnet arrangement for actuation along an optical axis and/or along a plane that is orthogonal to the optical axis. The asymmetric magnet arrangement may include a lateral position control magnet and a pair of transverse position control magnets. The lateral position control magnet may be situated at a first side of the optical package. The pair of transverse position control magnets may be situated on respective second and third sides of the optical package opposite one another with respect to an axis between the optical package and the lateral position control magnet.

Furthermore, the actuator may include one or more position sensor magnets and one or more magnetic field sensors. The position sensor magnets may be attached to the optical package. The magnetic field sensors may be configured to measure one or more magnetic field components. For instance, at least one of the transverse position control magnets may contribute to a first magnetic field component corresponding to a first axis, and at least one of the position sensor magnets may contribute to a second magnetic field component corresponding to a second axis that is orthogonal to the first axis. In some embodiments, at least one of the magnetic field sensors may be configured to measure the first magnetic field component and the second magnetic field component.

In some embodiments, the position sensor magnets may include a first position sensor magnet and a second position sensor magnet. Furthermore, the magnetic field sensors may include a first magnetic field sensor and a second magnetic field sensor. The first position sensor magnet may be oriented with a first magnetic field along a first direction. The first magnetic field sensor may be oriented to measure one or more magnetic field components of the first magnetic field of the first position sensor magnet. The second position sensor magnet may be oriented with a second magnetic field along a second direction. In some examples, the second direction may be antiparallel to the first direction. In other embodiments, the second direction may be parallel to the first direction. The second magnetic field sensor may be oriented to measure one or more magnetic field components of the second magnetic field of the second position sensor magnet.

In some embodiments, the system may include one or more processors and memory. The memory may include program instructions that, when executed by the processors, cause the processors to perform operations. In some implementations, the operations may include determining the first magnetic field component. For instance, the determination of the first magnetic field may be based at least in part on one or more measurements from a magnetic field sensor. Furthermore, the operations may include determining the second magnetic field component. For instance, the determination of the second magnetic field component may be based at least in part on one or more measurements from the magnetic field sensor. In various examples, the operations may include calculating a first position of a position sensor magnet along an optical axis defined by one or more lenses of the optical package. For instance, the calculation of the first position of the position sensor magnet along the optical axis may be based at least in part on the first magnetic field component and the second magnetic field component.

In some embodiments, the actuator may include one or more autofocus coils. The memory may include program instructions that, when executed by the processors, cause the processors to determine, based at least in part on the first position, an adjustment to at least one of a voltage or a current supplied to an autofocus coil. Such an adjustment may cause a position sensor magnet that is attached to the autofocus coil to move to a second position, along the optical axis, that is different than the first position.

Some embodiments include a method for determining a position of one or more camera components. The method may include generating a measurement of a magnetic field resulting at least in part from one or more position sensor magnets. For example, the measurement may be generated by using one or more magnetic field sensors to measure a magnetic field component created at least in part by one or more position sensor magnets that are fixedly mounted to a camera lens carrier. The camera lens carrier may be moveably coupled to a substrate. The magnetic field sensors may be fixedly mounted to the substrate. An autofocus actuator may provide motion of the camera lens carrier in a direction orthogonal to the substrate. In some implementations, the method may include calculating a position measurement for the lens carrier. For instance, position measurement for the lens carrier may be calculated based at least in part on the measurement of the magnetic field resulting from the position sensor magnets. Furthermore, the method may include adjusting a position of the camera lens carrier by altering a voltage and/or a current supplied to an autofocus coil of the autofocus actuator attached to the camera lens carrier. For example, the voltage and/or the current supplied to the

autofocus coil may be altered based at least in part on position measurement calculated for the lens carrier.

Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present disclosure. However, it will be apparent to one of ordinary skill in the art that some embodiments may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

It will also be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first contact could be termed a second contact, and, similarly, a second contact could be termed a first contact, without departing from the intended scope. The first contact and the second contact are both contacts, but they are not the same contact.

The terminology used in the description herein is for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the description and the appended claims, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

As used herein, the term “if” may be construed to mean “when” or “upon” or “in response to determining” or “in response to detecting,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” may be construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event],” depending on the context.

FIGS. 1A-2I illustrate embodiments of an example actuator module or assembly in which embodiments as described herein may be applied. As one of skill in the art will readily ascertain in light of having read the included disclosure, a wide variety of configurations of position sensors and magnets fulfill differing design goals in different embodiments without departing from the scope and intent of the present disclosure. As one of skill in the art will readily ascertain in light of having read the included disclosure, a wide variety of actuator configurations fulfill differing design goals in different embodiments without departing from the scope and intent of the present disclosure. For example, while the embodiments shown herein reflect voice coil motor actuators, one of skill in the art will readily understand that different actuators, including non-magnetic motorized actuators such as rotary motors or piezo-electric actuators, can be used with embodiments without departing from the scope and intent of the present disclosure.

FIG. 1A illustrates an example embodiment of a camera module **100a** having an actuator module or assembly that may, for example, be used to provide magnetic sensing for

11

autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments. The camera module **100a** may include an optical package (e.g., including a tele-lens) **102a** and an actuator **104a** for moving the optical package **102a**. In some 5 embodiments, a plurality of position sensor magnets **106a** may be attached to the optical package **102a**. In various embodiments, the actuator **104a** may include an asymmetric magnet arrangement for actuation along an optical axis and/or along a plane that is orthogonal to the optical axis. The asymmetric magnet arrangement may include a lateral position control magnet **108a** and a pair of transverse position control magnets **110a** and **112a**. The lateral position control magnet **108a** may be situated at a first side of the optical package **102a**. The pair of transverse position control magnets **110a** and **112a** may be situated on respective second and third sides of the optical package **102a**. The pair of transverse position control magnets **110a** and **112a** may be opposite one another with respect to an axis between the optical package **102a** and the lateral position control magnet **108a**. The first side may be a side of the optical package **102a** at which no transverse position control magnets are present. In some embodiments, the camera module **100a** may include one or more magnetic field sensors (obscured by coils in FIG. 1A but visible in FIGS. 2A-2I) configured to measure one or more magnetic field components to enable determination of a position of the position sensor magnets **106a**.

A lens carrier **114a** may allow mounting of autofocus coils **116a** and other components of an autofocus system to the optical package **102a**. The actuator **104a** may include optical image stabilization components such as, but not limited to, optical image stabilization coils **118a**, **120a**, and **122a** mounted to an actuator base **124a**. In some embodiments, the transverse position control magnets **110a** and **112a** (e.g., dual-pole magnets) may include a pair of magnets with differing dominant magnetic field orientations (e.g., antiparallel), whereas the lateral position control magnet **108a** (e.g., a single-pole magnet) may have only a single dominant magnetic field orientation.

In some embodiments, no actuator lateral magnet is situated on a remaining side of the optical package (occupied in FIG. 1A by dummy mass **126a**) at which neither the lateral position control magnet **108a** nor the transverse position control magnets **110a** and **112a** are situated.

In some embodiments, a non-magnetic dummy mass **126a** is situated on a remaining side of the optical package at which neither the lateral position control magnet **108a** nor the transverse position control magnets **110a** and **112a** are situated.

FIG. 1B depicts an example embodiment of an actuator **300b** module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments. In some embodiments, the actuator **100b** may include a plurality of position sensor magnets **102b** and **104b**. A lateral position control magnet **106b** may be situated at a first side (e.g., of the optical package, which is not shown in FIG. 1B), and a pair of transverse position control magnets **108b** and **110b** may be situated on respective second and third sides of the optical package opposite one another with respect to an axis between the optical package and the lateral position control magnet **106b**. The first side may be a side of the optical package at which no transverse position control magnets are present. In some embodiments, one or more magnetic field sensors (not shown in FIG. 1B but visible in FIGS. 2A-2I)

12

may be included for determining a position of the position sensor magnets **102b** and **104b**.

In some embodiments, no actuator magnets are situated on a remaining side of the optical package (e.g., the side occupied by dummy mass **112b** in FIG. 1B) at which neither the lateral position control magnet **106b** nor the transverse position control magnets **108b** and **110b** (with the direction of their upper magnets indicated) are situated.

In some embodiments, the plurality of position sensor magnets **102b** and **104b** may include a pair of magnets **102b** and **104b** oriented with magnetic fields transverse to the magnetic fields of the pair of transverse position control magnets **108b** and **110b**. The plurality of position sensor magnets **102b** and **104b** may include a pair of magnets **102b** and **104b** situated on the respective second and third sides of the optical package opposite one another with respect to the axis between the optical package and the lateral position control magnet **106b**.

FIG. 1C illustrates an example embodiment of an actuator **100c** module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments. In some embodiments, the actuator **100c** may include a plurality of position sensor magnets **102c** and **104c**. A lateral position control magnet **106c** may be situated at a first side (e.g., of the optical package, which is not shown in FIG. 1C). Furthermore, a pair of transverse position control magnets **108c** and **110c** may be situated on respective second and third sides of the optical package opposite one another with respect to an axis between the optical package and the lateral position control magnet **106c**. The first side may be a side of the optical package at which no transverse position control magnets are present. In some embodiments, one or more magnetic field sensors (not shown in FIG. 1C but visible in FIGS. 2A-2I) are included for determining a position of the position sensor magnets **102c** and **104c**.

In some embodiments, no actuator magnets are situated on a remaining side of the optical package (e.g., the side occupied by dummy mass **112c** in FIG. 1C) at which neither the lateral position control magnet **106c** nor the transverse position control magnets **108c** and **110c** are situated.

In some embodiments, the plurality of position sensor magnets **102c** and **104c** may include a pair of magnets **102c** and **104c** oriented with magnetic fields parallel and antiparallel to the magnetic fields of the pair of transverse position control magnets **108c** and **110c**. The plurality of position sensor magnets **102c** and **104c** may include a pair of magnets **102c** and **104c** situated on the respective first and fourth sides (e.g., the sides occupied by the lateral position control magnet **106c** and the dummy mass **112c**) of the optical package opposite one another with respect to an axis between the optical package and the actuator transverse position control magnets **108c** and **110c**.

FIG. 2A depicts a side view of an example embodiment of a camera module having an actuator **200a** module or assembly that may, for example, be used to move an optical package **202a** and provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments. As shown in FIG. 2A, the actuator **200a** may include a base or substrate **204a** and a cover **206a**. The base **204a** may include and/or support one or more position sensors (e.g., Hall sensors, TMR sensors, GMR sensors, etc.) **208a**, one or more optical image stabilization coils **210a**, and one or more suspension wires **212a**, which may at least partly enable magnetic sensing for autofocus and/or optical image

stabilization position detection, e.g., by detecting movements of position sensor magnets **214a**.

In some embodiments, the actuator **200a** may include one or more autofocus coils **216a** and one or more position control magnets **218a**, which may at least partly enable autofocus functionality such as moving the optical package **202a** along the Z axis and/or along an optical axis defined by one or more lenses of the optical package **202a**. In some examples, at least one position sensor magnet **214a** may be disposed proximate to at least one autofocus coil **216a**. In some embodiments, at least one position sensor magnet **214a** may be coupled to at least one autofocus coil **216a**. For instance, the autofocus coils **216a** may each define a central space that is encircled by the respective autofocus coil **216a**. The position sensor magnets **214a** may be disposed within the central spaces encircled by the autofocus coils **216a**. Additionally or alternatively, the position sensor magnets **214a** may be attached to support structures (not shown) that are fixed to the autofocus coils **216a**. For example, a support structure, to which a position sensor magnet **214a** is attached, may be disposed within a central space encircled by an autofocus coil **216a** and the support structure may be fixed to the autofocus coil **216**. In various embodiments, the actuator **200a** may include two position control magnets **218**, two autofocus coils **216a**, and two position sensor magnets **214a**, e.g., as illustrated in FIG. 4A. However, in other embodiments, the actuator **200a** may include fewer or more position control magnets **218a**, autofocus coils **216a**, and/or position sensor magnets **214a**.

In some embodiments, the actuator **200a** may include four suspension wires **212a**. The optical package **202a** may be suspended with respect to the base **204a** by suspending one or more upper springs **220a** on the suspension wires **212a**. In some embodiments, the actuator may include one or more lower springs **222a**. The upper spring(s) **220a** and lower spring(s) **222a** may be collectively referred to herein as optics springs. In the optical package **202a**, an optics component (e.g., one or more lens elements, a lens assembly, etc.) may be screwed, mounted or otherwise held in or by an optics holder. Note that upper spring(s) **220a** and lower spring(s) **222a** may be flexible to allow the optical package **202a** a range of motion along the Z (optical) axis for optical focusing, and suspension wires **212a** may be flexible to allow a range of motion on the X-Y plane orthogonal to the optical axis for optical image stabilization. Also note that, while embodiments show the optical package **202a** suspended on wires **212a**, other mechanisms may be used to suspend the optical package **202a** in other embodiments.

In various embodiments, the camera module may include an image sensor **224a**. The image sensor may be disposed below the optical package **202a** such that light rays may pass through one or more lens elements of the optical package **202a** (e.g., via an aperture at the top of the optical package **202a**) and to the image sensor **224a**.

FIG. 2B illustrates a top view of an example embodiment of an actuator **200b** module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments. In some embodiments, the actuator **200b** may include a plurality of position sensor magnets **202b** and **204b**. Furthermore, the actuator **200b** may have an asymmetric magnet arrangement that includes a lateral position control magnet **206b** and a pair of transverse position control magnets **208b** and **210b**. The lateral position control magnet **206b** may be situated at a first side (e.g., of the optical package, which is not shown in FIG. 2B). The pair of

transverse position control magnets **208b** and **210b** may be situated on respective second and third sides of the optical package opposite one another with respect to an axis between the optical package and the lateral position control magnet **206b**. The first side may be a side of the optical package at which no transverse position control magnets are present. In some embodiments, one or more magnetic field sensors (not shown in FIG. 2B but visible in FIG. 2C) are included for determining a position of the position sensor magnets **202b** and **204b**. In some embodiments, the actuator **200b** may include one or more coils that provide autofocus and/or optical image stabilization functionality. For example, the actuator **200b** may include autofocus coils **212b** and **214b**, as well as optical image stabilization coils **216b** and **218b**. Although not shown in FIG. 2B, the actuator **200b** may include another optical image stabilization coil situated at the first side, e.g., beneath the lateral position control magnet **206b**.

In some embodiments, no actuator magnets are situated on a remaining side of the optical package (e.g., the side occupied by dummy mass **220c** in FIG. 2B) at which neither the lateral position control magnet **206b** nor the transverse position control magnets **208b** and **210b** are situated.

In some embodiments, the plurality of position sensor magnets **202b** and **204b** may include a pair of magnets **202b** and **204b** oriented with magnetic fields transverse to the magnetic fields of the pair of transverse position control magnets **208b** and **210b**. Furthermore, the plurality of position sensor magnets **202b** and **204b** may include a pair of magnets **202b** and **204b** situated on the respective second and third sides of the optical package opposite one another with respect to the axis between the optical package and the lateral position control magnet **206b**.

FIG. 2C depicts a side view of an example embodiment of an actuator **200c** module or assembly that may, for example, be used to provide magnetic sensing for autofocus and/or optical image stabilization position detection in small form factor cameras, according to at least some embodiments. In some examples, FIG. 2C may depict a cross sectional view of the actuator **200b** as indicated by the cross section line 2C-2C in FIG. 2B. In some embodiments, the actuator **200c** may include an actuator base **202c**, one or multiple position sensor magnets (e.g., position sensor magnet **204c**), and one or multiple position control magnets (e.g., transverse position control magnet **206c**). In some embodiments, the actuator **200c** may include one or more magnetic field sensors such as a Hall sensor **208c** and/or a tunneling magnetoresistance (TMR)/giant magnetoresistance (GMR) sensor **210c**. Furthermore, in some embodiments, the actuator **200c** may include one or more coils. For example, the actuator **200c** may include one or more autofocus coils **212c** and/or one or more optical image stabilization coils **214c**. In some embodiments, a lateral offset **216c** may be provided between the position sensor magnet **204c** and the TMR/GMR sensor **210c**.

The magnetic field sensors may be used for determining a position of the position sensor magnets. For instance, the actuator **200c** may include a Hall sensor **208c** and a TMR/GMR sensor **210c**. In some examples, the Hall sensor **208c** may be used for determining a position of the position sensor magnet **204c** along the X-Y plane for optical image stabilization purposes. Furthermore, in some examples, the TMR/GMR sensor **210c** may be used for determining a position of the position sensor magnet **204c** along the Z axis for autofocus purposes. The position of the position sensor magnet **204c** along the X-Y plane and/or along the Z axis may be used for determining a position of the optical

package and/or one or more components of the optical package. In various examples, such position information may be used for providing closed loop position control along the X, Y, and/or Z axes.

In some embodiments, a magnetic field sensor (e.g., TMR/GMR sensor **210c**) may be disposed and/or oriented such that it is capable of measuring one or more magnetic field components. For instance, the magnetic field sensor may be configured to measure one or more magnetic field components that individually correspond to an axis (e.g., X, Y, and Z axes). In some examples, the transverse position control magnet **206c** may contribute to a first magnetic field component corresponding to a first axis. The position sensor magnet **204c** may contribute to a second magnetic field component corresponding to a second axis that is different than the first axis. For instance, the second axis may be orthogonal to the first axis. The magnetic field sensor may be configured to measure the first magnetic field component and the second magnetic field component. As the position sensor magnet **204c** moves (e.g., along the Z axis for autofocus purposes), the magnitude of its contribution to the second magnetic field component may change. The magnetic field sensors measurements of the first magnetic field component and the second magnetic field component may be used to calculate an angle between the first magnetic field component and the second magnetic field component. The angle between the first magnetic field component and the second magnetic field component may correlate with a position of the position sensor magnet **204c**. For instance, by simulating performance of the actuator **200c**, or by testing the actual actuator **200c**, multiple measurements may be obtained that may be used to characterize the behavior of the actuator **200c** with respect to an angle (e.g., between the first magnetic field component and the second magnetic field component) and position (e.g., of the position sensor magnet **204c** along the Z axis). In some instances, the simulation and/or testing measurements may be used to characterize the behavior of the actuator **200c** to correlate changes in the angle (e.g., between the first magnetic field component and the second magnetic field component) with changes in the position. For instance, the change in the angle between the first magnetic field component and the second magnetic field component may be correlated with a particular autofocus stroke. In some embodiments, changes in the position of position sensor magnet **204c** along the X-Y plane may also be taken into consideration in characterizing the behavior of the actuator **200c**. Once the behavior of the actuator **200c** is characterized, the resulting correlations may be used as a map for determining the position of the position sensor magnet **204c** along the X, Y, and/or Z axes.

FIG. 2D illustrates a side view of an example embodiment of an actuator **200d** module or assembly that may, for example, be used to provide magnetic sensing for autofocus position detection in small form factor cameras, according to at least some embodiments. In some embodiments, the actuator **200d** may include a plurality of position sensor magnets, for example position sensor magnet **202d** nested between autofocus coil **204d**. A transverse position control magnet **206d** (e.g., a dual pole magnet) may be situated in the actuator **200d**. In some embodiments, the actuator **200d** may include one or more magnetic field sensors **208d** (e.g., a Hall sensor, a TMR sensor, and/or a GMR sensor) for determining a position of the position sensor magnet **202d**. In some embodiments, no lateral offset is provided between position sensor magnet **202d** and the magnetic field sensor **208d**.

FIG. 2E depicts a side view of an example embodiment of an actuator **200e** module or assembly that may, for example, be used to provide magnetic sensing for autofocus position detection in small form factor cameras, according to at least some embodiments. In some embodiments, the actuator **200e** may include a plurality of position sensor magnets, for example position sensor magnet **202e** mounted between an autofocus coil **204e** and an optical package (not shown). A transverse position control magnet **206e** may be situated in the actuator **200e**. In FIG. 2E, the transverse position control magnet **206e** is illustrated as a single pole magnet. In other examples, the transverse position control magnet **206e** may be a dual pole magnet. In some embodiments, the actuator **200e** may include one or more magnetic field sensors **208e** (e.g., a Hall sensor, a TMR sensor, and/or a GMR sensor) for determining a position of the position sensor magnet **202e**. In some embodiments, a lateral offset toward the transverse position control magnet **206e** may be provided between the position sensor magnet **202e** and the magnetic field sensor **208e**.

FIG. 2F illustrates a side view of an example embodiment of an actuator **200f** module or assembly that may, for example, be used to provide magnetic sensing for autofocus position detection in small form factor cameras, according to at least some embodiments. In some embodiments, the actuator **200f** may include a plurality of position sensor magnets, for example position sensor magnet **202f** mounted within an autofocus coil **204f**. A transverse position control magnet **206f** may be situated in the actuator **200f**. In some embodiments, the actuator **200f** may include one or more magnetic field sensors **208f** (e.g., a Hall sensor, a TMR sensor, and/or a GMR sensor) for determining a position of the position sensor magnet **202f**. In some embodiments, a lateral offset toward the optical package (not shown) may be provided between position sensor magnet **202f** and the magnetic field sensor **208f**.

FIG. 2G depicts a side view of an example embodiment of an actuator **200g** module or assembly that may, for example, be used to provide magnetic sensing for autofocus position detection in small form factor cameras, according to at least some embodiments. In some embodiments, the actuator **200g** may include a plurality of position sensor magnets, for example position sensor magnet **202g** mounted within an autofocus coil **204g**. A transverse position control magnet **206g** may be situated in the actuator **200g**. In some embodiments, the actuator **200g** may include one or more magnetic field sensors **208g** (e.g., a Hall sensor, a TMR sensor, and/or a GMR sensor) for determining a position of the position sensor magnet **202g**. In some embodiments, a lateral offset toward the transverse position control magnet **206g** may be provided between position sensor magnet **202g** and the magnetic field sensor **208g**.

FIG. 2H illustrates a side view of an example embodiment of an actuator **200h** module or assembly that may, for example, be used to provide magnetic sensing for autofocus position detection in small form factor cameras, according to at least some embodiments. In some embodiments, the actuator **200h** may include a plurality of position sensor magnets, for example position sensor magnet **202h** mounted within an autofocus coil **204h** and an optics package (not shown). A transverse position control magnet **206h** may be situated in the actuator **200h**. In some embodiments, the actuator **200h** may include one or more magnetic field sensors **208h** (e.g., a Hall sensor, a TMR sensor, and/or a GMR sensor) for determining a position of the position

sensor magnets. In some embodiments, no lateral offset is provided between position sensor magnet **202h** and the magnetic field sensor **208h**.

FIG. **2I** depicts a side view of an example embodiment of an actuator **200i** module or assembly that may, for example, be used to provide magnetic sensing for autofocus position detection in small form factor cameras, according to at least some embodiments. In some embodiments, an actuator **200i** may include a plurality of position sensor magnets, for example position sensor magnet **202i** mounted within an autofocus coil **204i** and an optics package (not shown). A transverse position control magnet **206i** may be situated in the actuator **200i**. In some embodiments, the actuator **200i** may include one or more magnetic field sensors **208i** (e.g., a Hall sensor, a TMR sensor, and/or a GMR sensor) for determining a position of the position sensor magnets. In some embodiments, a lateral offset toward the transverse position control magnet **206i** may be provided between position sensor magnet **202i** and the magnetic field sensor **208i**.

FIG. **3** is a flowchart of a method **300** for magnetic sensing for autofocus position detection and control, according to at least some embodiments. At **302**, the method **300** may include generating a measurement of a magnetic field resulting at least in part from one or more position sensor magnets. The position sensor magnets may be part of a magnetic actuator. In some examples, the magnetic actuator may be configured to move an optical package of a camera unit. Generating the measurement of the magnetic field may include measuring one or more magnetic field components created at least in part by one or more position sensor magnets that are fixedly mounted to a camera lens carrier. The optical package may be disposed on the camera lens carrier. The camera lens carrier may be configured to move with respect to a base.

In some embodiments, one or more autofocus coils may be attached to the camera lens carrier. The autofocus coils may be configured to interact with one or more magnets of the magnetic actuator to provide autofocus functionality. For instance, a voltage and/or a current may be applied to the autofocus coils, thereby causing the autofocus coils to produce a first magnetic field that interacts with a second magnetic field produced by one or more magnets. The interaction between at least the first magnetic field and the second magnetic field may impose one or more forces on the autofocus coils that cause the autofocus coils to move along the *Z* axis and/or the optical axis. In some examples, the position sensor magnets may be nested within the autofocus coils.

The magnetic actuator may include one or more magnetic field sensors configured to measure one or more magnetic field components. For instance, the magnetic field sensors may include a Hall sensor, a TMR sensor, and/or a GMR sensor. In some embodiments, the magnetic field sensors may

In some embodiments, one or more optical image stabilization coils of the magnetic actuator may be disposed on, or proximate to, the base. The optical image stabilization coils may be configured to interact with one or more magnets to provide optical image stabilization functionality. For instance, a voltage and/or a current may be applied to the optical image stabilization coils, thereby causing the optical image stabilization coils to produce a first magnetic field that interacts with a second magnetic field produced by one or more magnets. The interaction between at least the first magnetic field and the second magnetic field may impose one or more forces on the optical image stabilization coils

that cause the optical image stabilization coils to move along the *x* and/or *y* axes (e.g., along the *x-y* plane that is orthogonal to the *Z* axis).

At **304**, the method **300** may include calculating a position measurement for the lens carrier based at least in part upon the measurement of the magnetic field. At **306**, the method **300** may include adjusting a position of a camera lens carrier. For instance, the position of the camera lens carrier may be adjusted by altering a voltage and/or a current supplied to an autofocus coil of an autofocus actuator that is attached to the camera lens carrier. In some examples, the position of the camera lens carrier may be adjusted based at least in part on the position measurement.

FIG. **4** is a flowchart of a method **400** for magnetic sensing for autofocus position detection and control, according to at least some embodiments. In some examples, a system may include an optical package and an actuator for moving the optical package. The actuator may include a lateral position control magnet and a pair of transverse position control magnets. The lateral position control magnet may be situated at a first side of the optical package. The pair of transverse position control magnets may be situated on respective second and third sides of the optical package opposite one another with respect to an axis between the optical package and the lateral position control magnet.

Furthermore, the actuator may include one or more position sensor magnets and one or more magnetic field sensors. The position sensor magnets may be attached to the optical package. The magnetic field sensors may be configured to measure one or more magnetic field components. For instance, at least one of the transverse position control magnets may contribute to a first magnetic field component corresponding to a first axis, and at least one of the position sensor magnets may contribute to a second magnetic field component corresponding to a second axis that is orthogonal to the first axis. In some embodiments, at least one of the magnetic field sensors may be configured to measure the first magnetic field component and the second magnetic field component.

At **402**, the method **400** may include determining a first magnetic field component. For instance, the magnetic field sensors may be used to measure the first magnetic field component produced at least in part by a transverse position control magnet. At **404**, the method **400** may include determining a second magnetic field component. For instance, the magnetic field sensors may be used to measure the second magnetic field component produced at least in part by a position sensor magnet.

At **406**, the method **400** may include calculating a first position of the position sensor magnet. For instance, the first position of the position sensor magnet may be a position along an optical axis defined by one or more lenses of the optical package. In various embodiments, the calculation of the first position may be based at least in part on the first magnetic field component and the second magnetic field component. For instance, the first position may be calculated based at least in part on an angle between the first magnetic field component and the second magnetic field component. The angle between the first magnetic field component and the second magnetic field component may correlate with a position of the position sensor magnet. For instance, by simulating performance of the actuator, or by testing the actual actuator, multiple measurements may be obtained that may be used to characterize the behavior of the actuator with respect to the angle, between the first magnetic field component and the second magnetic field component, and position of the position sensor magnet along the optical axis. In

some instances, the simulation and/or testing measurements may be used to characterize the behavior of the actuator to correlate changes in the angle with changes in the position. For instance, a particular change in the angle between the first magnetic field component and the second magnetic field component may be correlated with a particular autofocus stroke. In some embodiments, changes in the position of position sensor magnet along the X-Y plane may also be taken into consideration in characterizing the behavior of the actuator. Once the behavior of the actuator is characterized, the resulting correlations may be used as a map for determining the position of the position sensor magnet along the X, Y, and/or Z axes.

At **408**, the method **400** may include determining an adjustment to a voltage and/or a current supplied to an autofocus coil to cause the position sensor magnet to move to a second position. For instance, the second position may be a position along the optical axis that is different than the first position. In various embodiments, determination of the adjustment to the voltage and/or the current supplied to the autofocus coil may be based at least in part on the first position of the position sensor magnet.

Multifunction Device Examples

Embodiments of electronic devices, user interfaces for such devices, and associated processes for using such devices are described. In some embodiments, the device is a portable communications device, such as a mobile telephone, that also contains other functions, such as PDA and/or music player functions. Example embodiments of portable multifunction devices include, without limitation, the iPhone®, iPod Touch®, and iPad® devices from Apple Inc. of Cupertino, Calif. Other portable electronic devices, such as laptops, cameras, cell phones, or tablet computers, may also be used. It should also be understood that, in some embodiments, the device is not a portable communications device, but is a desktop computer with a camera. In some embodiments, the device is a gaming computer with orientation sensors (e.g., orientation sensors in a gaming controller). In other embodiments, the device is not a portable communications device, but is a camera.

In the discussion that follows, an electronic device that includes a display and a touch-sensitive surface is described. It should be understood, however, that the electronic device may include one or more other physical user-interface devices, such as a physical keyboard, a mouse and/or a joystick.

The device typically supports a variety of applications, such as one or more of the following: a drawing application, a presentation application, a word processing application, a website creation application, a disk authoring application, a spreadsheet application, a gaming application, a telephone application, a video conferencing application, an e-mail application, an instant messaging application, a workout support application, a photo management application, a digital camera application, a digital video camera application, a web browsing application, a digital music player application, and/or a digital video player application.

The various applications that may be executed on the device may use at least one common physical user-interface device, such as the touch-sensitive surface. One or more functions of the touch-sensitive surface as well as corresponding information displayed on the device may be adjusted and/or varied from one application to the next and/or within a respective application. In this way, a common physical architecture (such as the touch-sensitive sur-

face) of the device may support the variety of applications with user interfaces that are intuitive and transparent to the user.

Attention is now directed toward embodiments of portable devices with cameras. FIG. 5 is a block diagram illustrating portable multifunction device **500** with camera **564** in accordance with some embodiments. Camera **564** is sometimes called an “optical sensor” for convenience, and may also be known as or called an optical sensor system. Device **500** may include memory **502** (which may include one or more computer readable storage mediums), memory controller **522**, one or more processing units (CPUs) **520**, peripherals interface **518**, RF circuitry **508**, audio circuitry **510**, speaker **511**, touch-sensitive display system **512**, microphone **513**, input/output (I/O) subsystem **506**, other input or control devices **516**, and external port **524**. Device **500** may include one or more optical sensors **564**. These components may communicate over one or more communication buses or signal lines **503**.

It should be appreciated that device **500** is only one example of a portable multifunction device, and that device **500** may have more or fewer components than shown, may combine two or more components, or may have a different configuration or arrangement of the components. The various components shown in FIG. 5 may be implemented in hardware, software, or a combination of hardware and software, including one or more signal processing and/or application specific integrated circuits.

Memory **502** may include high-speed random access memory and may also include non-volatile memory, such as one or more magnetic disk storage devices, flash memory devices, or other non-volatile solid-state memory devices. Access to memory **502** by other components of device **500**, such as CPU **520** and the peripherals interface **518**, may be controlled by memory controller **522**.

Peripherals interface **518** can be used to couple input and output peripherals of the device to CPU **520** and memory **502**. The one or more processors **520** run or execute various software programs and/or sets of instructions stored in memory **502** to perform various functions for device **500** and to process data.

In some embodiments, peripherals interface **518**, CPU **520**, and memory controller **522** may be implemented on a single chip, such as chip **504**. In some other embodiments, they may be implemented on separate chips.

RF (radio frequency) circuitry **508** receives and sends RF signals, also called electromagnetic signals. RF circuitry **508** converts electrical signals to/from electromagnetic signals and communicates with communications networks and other communications devices via the electromagnetic signals. RF circuitry **508** may include well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth. RF circuitry **508** may communicate with networks, such as the Internet, also referred to as the World Wide Web (WWW), an intranet and/or a wireless network, such as a cellular telephone network, a wireless local area network (LAN) and/or a metropolitan area network (MAN), and other devices by wireless communication. The wireless communication may use any of a variety of communications standards, protocols and technologies, including but not limited to Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSDPA), wideband code division multiple

access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g and/or IEEE 802.11n), voice over Internet Protocol (VoIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

Audio circuitry **510**, speaker **511**, and microphone **513** provide an audio interface between a user and device **500**. Audio circuitry **510** receives audio data from peripherals interface **518**, converts the audio data to an electrical signal, and transmits the electrical signal to speaker **511**. Speaker **511** converts the electrical signal to human-audible sound waves. Audio circuitry **510** also receives electrical signals converted by microphone **513** from sound waves. Audio circuitry **510** converts the electrical signal to audio data and transmits the audio data to peripherals interface **518** for processing. Audio data may be retrieved from and/or transmitted to memory **502** and/or RF circuitry **508** by peripherals interface **518**. In some embodiments, audio circuitry **510** also includes a headset jack (e.g., **612**, FIG. 6). The headset jack provides an interface between audio circuitry **510** and removable audio input/output peripherals, such as output-only headphones or a headset with both output (e.g., a headphone for one or both ears) and input (e.g., a microphone).

I/O subsystem **506** couples input/output peripherals on device **500**, such as touch screen **512** and other input control devices **516**, to peripherals interface **518**. I/O subsystem **506** may include display controller **556** and one or more input controllers **560** for other input or control devices. The one or more input controllers **560** receive/send electrical signals from/to other input or control devices **516**. The other input control devices **516** may include physical buttons (e.g., push buttons, rocker buttons, etc.), dials, slider switches, joysticks, click wheels, and so forth. In some alternate embodiments, input controller(s) **560** may be coupled to any (or none) of the following: a keyboard, infrared port, USB port, and a pointer device such as a mouse. The one or more buttons (e.g., **608**, FIG. 6) may include an up/down button for volume control of speaker **511** and/or microphone **513**. The one or more buttons may include a push button (e.g., **606**, FIG. 6).

Touch-sensitive display **512** provides an input interface and an output interface between the device and a user. Display controller **556** receives and/or sends electrical signals from/to touch screen **512**. Touch screen **512** displays visual output to the user. The visual output may include graphics, text, icons, video, and any combination thereof (collectively termed "graphics"). In some embodiments, some or all of the visual output may correspond to user-interface objects.

Touch screen **512** has a touch-sensitive surface, sensor or set of sensors that accepts input from the user based on haptic and/or tactile contact. Touch screen **512** and display controller **556** (along with any associated modules and/or sets of instructions in memory **502**) detect contact (and any movement or breaking of the contact) on touch screen **512** and converts the detected contact into interaction with user-interface objects (e.g., one or more soft keys, icons,

web pages or images) that are displayed on touch screen **512**. In an example embodiment, a point of contact between touch screen **512** and the user corresponds to a finger of the user.

Touch screen **512** may use LCD (liquid crystal display) technology, LPD (light emitting polymer display) technology, or LED (light emitting diode) technology, although other display technologies may be used in other embodiments. Touch screen **512** and display controller **556** may detect contact and any movement or breaking thereof using any of a variety of touch sensing technologies now known or later developed, including but not limited to capacitive, resistive, infrared, and surface acoustic wave technologies, as well as other proximity sensor arrays or other elements for determining one or more points of contact with touch screen **512**. In an example embodiment, projected mutual capacitance sensing technology is used, such as that found in the iPhone®, iPod Touch®, and iPad® from Apple Inc. of Cupertino, Calif.

Touch screen **512** may have a video resolution in excess of 500 dpi. In some embodiments, the touch screen has a video resolution of approximately 560 dpi. The user may make contact with touch screen **512** using any suitable object or appendage, such as a stylus, a finger, and so forth. In some embodiments, the user interface is designed to work primarily with finger-based contacts and gestures, which can be less precise than stylus-based input due to the larger area of contact of a finger on the touch screen. In some embodiments, the device translates the rough finger-based input into a precise pointer/cursor position or command for performing the actions desired by the user.

In some embodiments, in addition to the touch screen, device **500** may include a touchpad (not shown) for activating or deactivating particular functions. In some embodiments, the touchpad is a touch-sensitive area of the device that, unlike the touch screen, does not display visual output. The touchpad may be a touch-sensitive surface that is separate from touch screen **512** or an extension of the touch-sensitive surface formed by the touch screen.

Device **500** also includes power system **562** for powering the various components. Power system **562** may include a power management system, one or more power sources (e.g., battery, alternating current (AC)), a recharging system, a power failure detection circuit, a power converter or inverter, a power status indicator (e.g., a light-emitting diode (LED)) and any other components associated with the generation, management and distribution of power in portable devices.

Device **500** may also include one or more optical sensors or cameras **564**. FIG. 5 shows an optical sensor **564** coupled to optical sensor controller **558** in I/O subsystem **506**. Optical sensor **564** may include charge-coupled device (CCD) or complementary metal-oxide semiconductor (CMOS) phototransistors. Optical sensor **564** receives light from the environment, projected through one or more lens, and converts the light to data representing an image. In conjunction with imaging module **543** (also called a camera module), optical sensor **564** may capture still images or video. In some embodiments, an optical sensor **564** is located on the back of device **500**, opposite touch screen display **512** on the front of the device, so that the touch screen display **512** may be used as a viewfinder for still and/or video image acquisition. In some embodiments, another optical sensor is located on the front of the device so that the user's image may be obtained for videoconferencing while the user views the other video conference participants on the touch screen display.

Device **500** may also include one or more proximity sensors **566**. FIG. **5** shows proximity sensor **566** coupled to peripherals interface **518**. Alternately, proximity sensor **566** may be coupled to input controller **560** in I/O subsystem **506**. In some embodiments, the proximity sensor **566** turns off and disables touch screen **512** when the multifunction device **500** is placed near the user's ear (e.g., when the user is making a phone call).

Device **500** includes one or more orientation sensors **568**. In some embodiments, the one or more orientation sensors **568** include one or more accelerometers (e.g., one or more linear accelerometers and/or one or more rotational accelerometers). In some embodiments, the one or more orientation sensors **568** include one or more gyroscopes. In some embodiments, the one or more orientation sensors **568** include one or more magnetometers. In some embodiments, the one or more orientation sensors **568** include one or more of global positioning system (GPS), Global Navigation Satellite System (GLONASS), and/or other global navigation system receivers. The GPS, GLONASS, and/or other global navigation system receivers may be used for obtaining information concerning the location and orientation (e.g., portrait or landscape) of device **500**. In some embodiments, the one or more orientation sensors **568** include any combination of orientation/rotation sensors. FIG. **5** shows the one or more orientation sensors **568** coupled to peripherals interface **518**. Alternately, the one or more orientation sensors **568** may be coupled to an input controller **560** in I/O subsystem **506**. In some embodiments, information is displayed on the touch screen display **512** in a portrait view or a landscape view based on an analysis of data received from the one or more orientation sensors **568**.

In some embodiments, the software components stored in memory **502** include operating system **526**, communication module (or set of instructions) **528**, contact/motion module (or set of instructions) **530**, graphics module (or set of instructions) **532**, text input module (or set of instructions) **534**, Global Positioning System (GPS) module (or set of instructions) **535**, arbiter module **558** and applications (or sets of instructions) **536**. Furthermore, in some embodiments memory **502** stores device/global internal state **557**. Device/global internal state **557** includes one or more of: active application state, indicating which applications, if any, are currently active; display state, indicating what applications, views or other information occupy various regions of touch screen display **512**; sensor state, including information obtained from the device's various sensors and input control devices **516**; and location information concerning the device's location and/or attitude.

Operating system **526** (e.g., Darwin, RTXC, LINUX, UNIX, OS X, WINDOWS, or an embedded operating system such as VxWorks) includes various software components and/or drivers for controlling and managing general system tasks (e.g., memory management, storage device control, power management, etc.) and facilitates communication between various hardware and software components.

Communication module **528** facilitates communication with other devices over one or more external ports **524** and also includes various software components for handling data received by RF circuitry **508** and/or external port **524**. External port **524** (e.g., Universal Serial Bus (USB), FIREWIRE, etc.) is adapted for coupling directly to other devices or indirectly over a network (e.g., the Internet, wireless LAN, etc.). In some embodiments, the external port is a multi-pin (e.g., 30-pin) connector.

Contact/motion module **530** may detect contact with touch screen **512** (in conjunction with display controller

556) and other touch sensitive devices (e.g., a touchpad or physical click wheel). Contact/motion module **530** includes various software components for performing various operations related to detection of contact, such as determining if contact has occurred (e.g., detecting a finger-down event), determining if there is movement of the contact and tracking the movement across the touch-sensitive surface (e.g., detecting one or more finger-dragging events), and determining if the contact has ceased (e.g., detecting a finger-up event or a break in contact). Contact/motion module **530** receives contact data from the touch-sensitive surface. Determining movement of the point of contact, which is represented by a series of contact data, may include determining speed (magnitude), velocity (magnitude and direction), and/or an acceleration (a change in magnitude and/or direction) of the point of contact. These operations may be applied to single contacts (e.g., one finger contacts) or to multiple simultaneous contacts (e.g., "multitouch"/multiple finger contacts). In some embodiments, contact/motion module **530** and display controller **556** detect contact on a touchpad.

Contact/motion module **530** may detect a gesture input by a user. Different gestures on the touch-sensitive surface have different contact patterns. Thus, a gesture may be detected by detecting a particular contact pattern. For example, detecting a finger tap gesture includes detecting a finger-down event followed by detecting a finger-up (lift off) event at the same position (or substantially the same position) as the finger-down event (e.g., at the position of an icon). As another example, detecting a finger swipe gesture on the touch-sensitive surface includes detecting a finger-down event followed by detecting one or more finger-dragging events, and subsequently followed by detecting a finger-up (lift off) event.

Graphics module **532** includes various known software components for rendering and displaying graphics on touch screen **512** or other display, including components for changing the intensity of graphics that are displayed. As used herein, the term "graphics" includes any object that can be displayed to a user, including without limitation text, web pages, icons (such as user-interface objects including soft keys), digital images, videos, animations and the like.

In some embodiments, graphics module **532** stores data representing graphics to be used. Each graphic may be assigned a corresponding code. Graphics module **532** receives, from applications etc., one or more codes specifying graphics to be displayed along with, if necessary, coordinate data and other graphic property data, and then generates screen image data to output to display controller **556**.

Text input module **534**, which may be a component of graphics module **532**, provides soft keyboards for entering text in various applications (e.g., contacts **537**, e-mail **540**, IM **541**, browser **547**, and any other application that needs text input).

GPS module **535** determines the location of the device and provides this information for use in various applications (e.g., to telephone **538** for use in location-based dialing, to camera **543** as picture/video metadata, and to applications that provide location-based services such as weather widgets, local yellow page widgets, and map/navigation widgets).

Applications **536** may include the following modules (or sets of instructions), or a subset or superset thereof: contacts module **537** (sometimes called an address book or contact list);

telephone module 538;
 video conferencing module 539;
 e-mail client module 540;
 instant messaging (IM) module 541;
 workout support module 542;
 camera module 543 for still and/or video images;
 image management module 544;
 browser module 547;
 calendar module 548;
 widget modules 549, which may include one or more of:
 weather widget 549-1, stocks widget 549-2, calculator
 widget 549-3, alarm clock widget 549-4, dictionary
 widget 549-5, and other widgets obtained by the user,
 as well as user-created widgets 549-6;
 widget creator module 550 for making user-created wid-
 gets 549-6;
 search module 551;
 video and music player module 552, which may be made
 up of a video player module and a music player
 module;
 notes module 553;
 map module 554; and/or
 online video module 555.

Examples of other applications 536 that may be stored in
 memory 502 include other word processing applications,
 other image editing applications, drawing applications, pre-
 sentation applications, JAVA-enabled applications, encryp-
 tion, digital rights management, voice recognition, and voice
 replication.

In conjunction with touch screen 512, display controller
 556, contact module 530, graphics module 532, and text
 input module 534, contacts module 537 may be used to
 manage an address book or contact list (e.g., stored in
 application internal state 557), including: adding name(s) to
 the address book; deleting name(s) from the address book;
 associating telephone number(s), e-mail address(es), physi-
 cal address(es) or other information with a name; associating
 an image with a name; categorizing and sorting names;
 providing telephone numbers or e-mail addresses to initiate
 and/or facilitate communications by telephone 538, video
 conference 539, e-mail 540, or IM 541; and so forth.

In conjunction with RF circuitry 508, audio circuitry 510,
 speaker 511, microphone 513, touch screen 512, display
 controller 556, contact module 530, graphics module 532,
 and text input module 534, telephone module 538 may be
 used to enter a sequence of characters corresponding to a
 telephone number, access one or more telephone numbers in
 address book 537, modify a telephone number that has been
 entered, dial a respective telephone number, conduct a
 conversation and disconnect or hang up when the conver-
 sation is completed. As noted above, the wireless commu-
 nication may use any of a variety of communications
 standards, protocols and technologies.

In conjunction with RF circuitry 508, audio circuitry 510,
 speaker 511, microphone 513, touch screen 512, display
 controller 556, optical sensor 564, optical sensor controller
 558, contact module 530, graphics module 532, text input
 module 534, contact list 537, and telephone module 538,
 videoconferencing module 539 includes executable instruc-
 tions to initiate, conduct, and terminate a video conference
 between a user and one or more other participants in
 accordance with user instructions.

In conjunction with RF circuitry 508, touch screen 512,
 display controller 556, contact module 530, graphics module
 532, and text input module 534, e-mail client module 540
 includes executable instructions to create, send, receive, and
 manage e-mail in response to user instructions. In conjunc-

tion with image management module 544, e-mail client
 module 540 makes it very easy to create and send e-mails
 with still or video images taken with camera module 543.

In conjunction with RF circuitry 508, touch screen 512,
 display controller 556, contact module 530, graphics module
 532, and text input module 534, the instant messaging
 module 541 includes executable instructions to enter a
 sequence of characters corresponding to an instant message,
 to modify previously entered characters, to transmit a
 respective instant message (for example, using a Short
 Message Service (SMS) or Multimedia Message Service
 (MMS) protocol for telephony-based instant messages or
 using XMPP, SIMPLE, or IMPS for Internet-based instant
 messages), to receive instant messages and to view received
 instant messages. In some embodiments, transmitted and/or
 received instant messages may include graphics, photos,
 audio files, video files and/or other attachments as are
 supported in a MMS and/or an Enhanced Messaging Service
 (EMS). As used herein, "instant messaging" refers to both
 telephony-based messages (e.g., messages sent using SMS
 or MMS) and Internet-based messages (e.g., messages sent
 using XMPP, SIMPLE, or IMPS).

In conjunction with RF circuitry 508, touch screen 512,
 display controller 556, contact module 530, graphics module
 532, text input module 534, GPS module 535, map module
 554, and music player module 546, workout support module
 542 includes executable instructions to create workouts
 (e.g., with time, distance, and/or calorie burning goals);
 communicate with workout sensors (sports devices); receive
 workout sensor data; calibrate sensors used to monitor a
 workout; select and play music for a workout; and display,
 store and transmit workout data.

In conjunction with touch screen 512, display controller
 556, optical sensor(s) 564, optical sensor controller 558,
 contact module 530, graphics module 532, and image man-
 agement module 544, camera module 543 includes execut-
 able instructions to capture still images or video (including
 a video stream) and store them into memory 502, modify
 characteristics of a still image or video, or delete a still
 image or video from memory 502.

In conjunction with touch screen 512, display controller
 556, contact module 530, graphics module 532, text input
 module 534, and camera module 543, image management
 module 544 includes executable instructions to arrange,
 modify (e.g., edit), or otherwise manipulate, label, delete,
 present (e.g., in a digital slide show or album), and store still
 and/or video images.

In conjunction with RF circuitry 508, touch screen 512,
 display system controller 556, contact module 530, graphics
 module 532, and text input module 534, browser module
 547 includes executable instructions to browse the Internet
 in accordance with user instructions, including searching,
 linking to, receiving, and displaying web pages or portions
 thereof, as well as attachments and other files linked to web
 pages.

In conjunction with RF circuitry 508, touch screen 512,
 display system controller 556, contact module 530, graphics
 module 532, text input module 534, e-mail client module
 540, and browser module 547, calendar module 548 includes
 executable instructions to create, display, modify, and store
 calendars and data associated with calendars (e.g., calendar
 entries, to do lists, etc.) in accordance with user instructions.

In conjunction with RF circuitry 508, touch screen 512,
 display system controller 556, contact module 530, graphics
 module 532, text input module 534, and browser module
 547, widget modules 549 are mini-applications that may be
 downloaded and used by a user (e.g., weather widget 549-1,

stocks widget **549-2**, calculator widget **549-3**, alarm clock widget **549-4**, and dictionary widget **549-5**) or created by the user (e.g., user-created widget **549-6**). In some embodiments, a widget includes an HTML (Hypertext Markup Language) file, a CSS (Cascading Style Sheets) file, and a JavaScript file. In some embodiments, a widget includes an XML (Extensible Markup Language) file and a JavaScript file (e.g., Yahoo! Widgets).

In conjunction with RF circuitry **508**, touch screen **512**, display system controller **556**, contact module **530**, graphics module **532**, text input module **534**, and browser module **547**, the widget creator module **550** may be used by a user to create widgets (e.g., turning a user-specified portion of a web page into a widget).

In conjunction with touch screen **512**, display system controller **556**, contact module **530**, graphics module **532**, and text input module **534**, search module **551** includes executable instructions to search for text, music, sound, image, video, and/or other files in memory **502** that match one or more search criteria (e.g., one or more user-specified search terms) in accordance with user instructions.

In conjunction with touch screen **512**, display system controller **556**, contact module **530**, graphics module **532**, audio circuitry **510**, speaker **511**, RF circuitry **508**, and browser module **547**, video and music player module **552** includes executable instructions that allow the user to download and play back recorded music and other sound files stored in one or more file formats, such as MP3 or AAC files, and executable instructions to display, present or otherwise play back videos (e.g., on touch screen **512** or on an external, connected display via external port **524**). In some embodiments, device **500** may include the functionality of an MP3 player.

In conjunction with touch screen **512**, display controller **556**, contact module **530**, graphics module **532**, and text input module **534**, notes module **553** includes executable instructions to create and manage notes, to do lists, and the like in accordance with user instructions.

In conjunction with RF circuitry **508**, touch screen **512**, display system controller **556**, contact module **530**, graphics module **532**, text input module **534**, GPS module **535**, and browser module **547**, map module **554** may be used to receive, display, modify, and store maps and data associated with maps (e.g., driving directions; data on stores and other points of interest at or near a particular location; and other location-based data) in accordance with user instructions.

In conjunction with touch screen **512**, display system controller **556**, contact module **530**, graphics module **532**, audio circuitry **510**, speaker **511**, RF circuitry **508**, text input module **534**, e-mail client module **540**, and browser module **547**, online video module **555** includes instructions that allow the user to access, browse, receive (e.g., by streaming and/or download), play back (e.g., on the touch screen or on an external, connected display via external port **524**), send an e-mail with a link to a particular online video, and otherwise manage online videos in one or more file formats, such as H.264. In some embodiments, instant messaging module **541**, rather than e-mail client module **540**, is used to send a link to a particular online video.

Each of the above identified modules and applications correspond to a set of executable instructions for performing one or more functions described above and the methods described in this application (e.g., the computer-implemented methods and other information processing methods described herein). These modules (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these

modules may be combined or otherwise re-arranged in various embodiments. In some embodiments, memory **502** may store a subset of the modules and data structures identified above. Furthermore, memory **502** may store additional modules and data structures not described above.

In some embodiments, device **500** is a device where operation of a predefined set of functions on the device is performed exclusively through a touch screen and/or a touchpad. By using a touch screen and/or a touchpad as the primary input control device for operation of device **500**, the number of physical input control devices (such as push buttons, dials, and the like) on device **500** may be reduced.

The predefined set of functions that may be performed exclusively through a touch screen and/or a touchpad include navigation between user interfaces. In some embodiments, the touchpad, when touched by the user, navigates device **500** to a main, home, or root menu from any user interface that may be displayed on device **500**. In such embodiments, the touchpad may be referred to as a “menu button.” In some other embodiments, the menu button may be a physical push button or other physical input control device instead of a touchpad.

FIG. **6** illustrates a portable multifunction device **500** having a touch screen **512** in accordance with some embodiments. The touch screen **512** may display one or more graphics within user interface (UI) **600**. In this embodiment, as well as others described below, a user may select one or more of the graphics by making a gesture on the graphics, for example, with one or more fingers **602** (not drawn to scale in the figure) or one or more styluses **603** (not drawn to scale in the figure).

Device **500** may also include one or more physical buttons, such as “home” or menu button **604**. As described previously, menu button **604** may be used to navigate to any application **536** in a set of applications that may be executed on device **500**. Alternatively, in some embodiments, the menu button **604** is implemented as a soft key in a GUI displayed on touch screen **512**.

In one embodiment, device **500** includes touch screen **512**, menu button **604**, push button **606** for powering the device on/off and locking the device, volume adjustment button(s) **608**, Subscriber Identity Module (SIM) card slot **610**, head set jack **612**, and docking/charging external port **524**. Push button **606** may be used to turn the power on/off on the device by depressing the button and holding the button in the depressed state for a predefined time interval; to lock the device by depressing the button and releasing the button before the predefined time interval has elapsed; and/or to unlock the device or initiate an unlock process. In an alternative embodiment, device **500** also may accept verbal input for activation or deactivation of some functions through microphone **513**.

It should be noted that, although many of the examples herein are given with reference to optical sensor/camera **564** (on the front of a device), a rear-facing camera or optical sensor that is pointed opposite from the display may be used instead of or in addition to an optical sensor/camera **564** on the front of a device.

Example Computer System

FIG. **7** illustrates an example computer system **700** that may be configured to execute any or all of the embodiments described above. In different embodiments, computer system **700** may be any of various types of devices, including, but not limited to, a personal computer system, desktop computer, laptop, notebook, tablet, slate, pad, or netbook

computer, mainframe computer system, handheld computer, workstation, network computer, a camera, a set top box, a mobile device, a consumer device, video game console, handheld video game device, application server, storage device, a television, a video recording device, a peripheral device such as a switch, modem, router, or in general any type of computing or electronic device.

Various embodiments of a camera motion control system as described herein, including embodiments of magnetic position sensing, as described herein may be executed in one or more computer systems **700**, which may interact with various other devices. Note that any component, action, or functionality described above with respect to FIGS. 1-6 may be implemented on one or more computers configured as computer system **700** of FIG. 7, according to various embodiments. In the illustrated embodiment, computer system **700** includes one or more processors **710** coupled to a system memory **720** via an input/output (I/O) interface **730**. Computer system **700** further includes a network interface **740** coupled to I/O interface **730**, and one or more input/output devices **750**, such as cursor control device **760**, keyboard **770**, and display(s) **780**. In some cases, it is contemplated that embodiments may be implemented using a single instance of computer system **700**, while in other embodiments multiple such systems, or multiple nodes making up computer system **700**, may be configured to host different portions or instances of embodiments. For example, in one embodiment some elements may be implemented via one or more nodes of computer system **700** that are distinct from those nodes implementing other elements.

In various embodiments, computer system **700** may be a uniprocessor system including one processor **710**, or a multiprocessor system including several processors **710** (e.g., two, four, eight, or another suitable number). Processors **710** may be any suitable processor capable of executing instructions. For example, in various embodiments processors **710** may be general-purpose or embedded processors implementing any of a variety of instruction set architectures (ISAs), such as the x86, PowerPC, SPARC, or MIPS ISAs, or any other suitable ISA. In multiprocessor systems, each of processors **710** may commonly, but not necessarily, implement the same ISA.

System memory **720** may be configured to store camera control program instructions **722** and/or camera control data accessible by processor **710**. In various embodiments, system memory **720** may be implemented using any suitable memory technology, such as static random access memory (SRAM), synchronous dynamic RAM (SDRAM), nonvolatile/Flash-type memory, or any other type of memory. In the illustrated embodiment, program instructions **722** may be configured to implement a lens control application **724** incorporating any of the functionality described above. Additionally, existing camera control data **732** of memory **720** may include any of the information or data structures described above. In some embodiments, program instructions and/or data may be received, sent or stored upon different types of computer-accessible media or on similar media separate from system memory **720** or computer system **700**. While computer system **700** is described as implementing the functionality of functional blocks of previous Figures, any of the functionality described herein may be implemented via such a computer system.

In one embodiment, I/O interface **730** may be configured to coordinate I/O traffic between processor **710**, system memory **720**, and any peripheral devices in the device, including network interface **740** or other peripheral interfaces, such as input/output devices **750**. In some embodi-

ments, I/O interface **730** may perform any necessary protocol, timing or other data transformations to convert data signals from one component (e.g., system memory **720**) into a format suitable for use by another component (e.g., processor **710**). In some embodiments, I/O interface **730** may include support for devices attached through various types of peripheral buses, such as a variant of the Peripheral Component Interconnect (PCI) bus standard or the Universal Serial Bus (USB) standard, for example. In some embodiments, the function of I/O interface **730** may be split into two or more separate components, such as a north bridge and a south bridge, for example. Also, in some embodiments some or all of the functionality of I/O interface **730**, such as an interface to system memory **720**, may be incorporated directly into processor **710**.

Network interface **740** may be configured to allow data to be exchanged between computer system **700** and other devices attached to a network **785** (e.g., carrier or agent devices) or between nodes of computer system **700**. Network **785** may in various embodiments include one or more networks including but not limited to Local Area Networks (LANs) (e.g., an Ethernet or corporate network), Wide Area Networks (WANs) (e.g., the Internet), wireless data networks, some other electronic data network, or some combination thereof. In various embodiments, network interface **740** may support communication via wired or wireless general data networks, such as any suitable type of Ethernet network, for example; via telecommunications/telephony networks such as analog voice networks or digital fiber communications networks; via storage area networks such as Fibre Channel SANs, or via any other suitable type of network and/or protocol.

Input/output devices **750** may, in some embodiments, include one or more display terminals, keyboards, keypads, touchpads, scanning devices, voice or optical recognition devices, or any other devices suitable for entering or accessing data by one or more computer systems **700**. Multiple input/output devices **750** may be present in computer system **700** or may be distributed on various nodes of computer system **700**. In some embodiments, similar input/output devices may be separate from computer system **700** and may interact with one or more nodes of computer system **700** through a wired or wireless connection, such as over network interface **740**.

As shown in FIG. 7, memory **720** may include program instructions **722**, which may be processor-executable to implement any element or action described above. In one embodiment, the program instructions may implement the methods described above. In other embodiments, different elements and data may be included. Note that data may include any data or information described above.

Those skilled in the art will appreciate that computer system **700** is merely illustrative and is not intended to limit the scope of embodiments. In particular, the computer system and devices may include any combination of hardware or software that can perform the indicated functions, including computers, network devices, Internet appliances, PDAs, wireless phones, pagers, etc. Computer system **700** may also be connected to other devices that are not illustrated, or instead may operate as a stand-alone system. In addition, the functionality provided by the illustrated components may in some embodiments be combined in fewer components or distributed in additional components. Similarly, in some embodiments, the functionality of some of the illustrated components may not be provided and/or other additional functionality may be available.

Those skilled in the art will also appreciate that, while various items are illustrated as being stored in memory or on storage while being used, these items or portions of them may be transferred between memory and other storage devices for purposes of memory management and data integrity. Alternatively, in other embodiments some or all of the software components may execute in memory on another device and communicate with the illustrated computer system via inter-computer communication. Some or all of the system components or data structures may also be stored (e.g., as instructions or structured data) on a computer-accessible medium or a portable article to be read by an appropriate drive, various examples of which are described above. In some embodiments, instructions stored on a computer-accessible medium separate from computer system **700** may be transmitted to computer system **700** via transmission media or signals such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as a network and/or a wireless link. Various embodiments may further include receiving, sending or storing instructions and/or data implemented in accordance with the foregoing description upon a computer-accessible medium. Generally speaking, a computer-accessible medium may include a non-transitory, computer-readable storage medium or memory medium such as magnetic or optical media, e.g., disk or DVD/CD-ROM, volatile or non-volatile media such as RAM (e.g. SDRAM, DDR, RDRAM, SRAM, etc.), ROM, etc. In some embodiments, a computer-accessible medium may include transmission media or signals such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as network and/or a wireless link.

The methods described herein may be implemented in software, hardware, or a combination thereof, in different embodiments. In addition, the order of the blocks of the methods may be changed, and various elements may be added, reordered, combined, omitted, modified, etc. Various modifications and changes may be made as would be obvious to a person skilled in the art having the benefit of this disclosure. The various embodiments described herein are meant to be illustrative and not limiting. Many variations, modifications, additions, and improvements are possible. Accordingly, plural instances may be provided for components described herein as a single instance. Boundaries between various components, operations and data stores are somewhat arbitrary, and particular operations are illustrated in the context of specific illustrative configurations. Other allocations of functionality are envisioned and may fall within the scope of claims that follow. Finally, structures and functionality presented as discrete components in the example configurations may be implemented as a combined structure or component. These and other variations, modifications, additions, and improvements may fall within the scope of embodiments as defined in the claims that follow.

What is claimed is:

1. A camera unit, comprising:

an optical package including one or more lenses that define an optical axis; and

an asymmetric magnet arrangement for actuation along the optical axis and along a plane that is orthogonal to the optical axis, wherein the asymmetric magnet arrangement includes:

a lateral position control magnet situated at a first side of the optical package; and

a pair of transverse position control magnets situated on respective second and third sides of the optical

package opposite one another with respect to an axis between the optical package and the lateral position control magnet, wherein at least one of the transverse position control magnets contributes to a first magnetic field component corresponding to a first axis; one or more position sensor magnets attached to the optical package, wherein at least one of the position sensor magnets contributes to a second magnetic field component corresponding to a second axis that is orthogonal to the first axis; and one or more magnetic field sensors configured to measure the first magnetic field component and the second magnetic field component for determination of an angle between the first magnetic field component and the second magnetic field component to enable determination of a position, along the optical axis, of at least one of the one or more position sensor magnets.

2. The camera unit of claim **1**, wherein:

the one or more position sensor magnets include a pair of position sensor magnets oriented with magnetic fields transverse to magnetic fields of the pair of transverse position control magnets; and

the pair of position sensor magnets are situated on the respective second and third sides of the optical package opposite one another with respect to the axis between the optical package and the lateral position control magnet.

3. The camera unit of claim **1**, wherein:

the one or more position sensor magnets include a pair of position sensor magnets oriented with magnetic fields parallel or antiparallel to magnetic fields of the pair of transverse position control magnets; and

the pair of position sensor magnets are situated on the first side and a fourth side of the optical package, the fourth side being opposite the first side along the axis between the optical package and the lateral position control magnet.

4. The camera unit of claim **1**, wherein:

a non-magnetic dummy mass is situated at a fourth side of the optical package that is opposite the first side of the optical package along the axis between the optical package and the lateral position control magnet; and

no lateral position control magnets or transverse position control magnets are situated at the fourth side of the optical package.

5. The camera unit of claim **1**, wherein:

the one or more magnetic field sensors include at least one of a Hall sensor, a tunneling magnetoresistance (TMR) sensor, or a giant magnetoresistance (GMR) sensor.

6. An actuator module for moving an optical package, comprising:

an asymmetric magnetic arrangement for actuation along an optical axis of the optical package and along a plane that is orthogonal to the optical axis, wherein the asymmetric magnetic arrangement includes:

a lateral position control magnet disposed proximate a first side of a moving member, the moving member attached to the optical package;

a first transverse position control magnet disposed proximate a second side of the moving member; and

a second transverse position control magnet disposed proximate a third side of the moving member, the third side opposite the second side with respect to an axis between the moving member and the lateral position control magnet, wherein at least one of the

33

- transverse position control magnets contributes to a first magnetic field component corresponding to a first axis;
- one or more position sensor magnets attached to the moving member, wherein at least one of the position sensor magnets contributes to a second magnetic field component corresponding to a second axis that is orthogonal to the first axis; and
- one or more magnetic field sensors configured to measure one or more magnetic field components to enable determination of a position of the moving member, wherein at least one of the magnetic field sensors is configured to measure the first magnetic field component and the second magnetic field component for determination of an angle between the first magnetic field component and the second magnetic field component.
7. The actuator module of claim 6, wherein: at least one of the one or more magnetic field sensors is configured to measure at least one magnetic field component for determination of a position of the moving member with respect to the optical axis.
8. The actuator module of claim 6, wherein: at least one of the one or more coils is an autofocus coil; and at least one of the position sensor magnets is nested within a central space encircled by the autofocus coil.
9. The actuator module of claim 6, wherein: the optical package is attached to a top side of the moving member; the one or more magnetic field sensors are attached to the base disposed proximate a bottom side of the moving member that is opposite the top side of the moving member; and the actuator is configured to move the moving member relative to the base.
10. The actuator module of claim 9, further comprising: a plurality of optical image stabilization coils attached to the base, wherein each of the plurality of optical image stabilization coils are configured to receive a flow of current that interacts with one of more magnetic fields produced by at least a portion of the asymmetric magnet arrangement such that the optical package moves for optical image stabilization.
11. The actuator module of claim 6, wherein the one or more position sensor magnets include: a first position sensor magnet oriented with a first magnetic field along a first direction; and a second position sensor magnet oriented with a second magnetic field along a second direction that is antiparallel to the first direction.
12. The actuator module of claim 6, wherein: the one or more position sensor magnets include: a first position sensor magnet oriented with a first magnetic field along a first direction; and a second position sensor magnet oriented with a second magnetic field along a second direction that is parallel to the first direction.
13. The actuator module of claim 6, wherein the one or more magnetic field sensors include: a first magnetic field sensor disposed proximate the second side of the moving member; and a second magnetic field sensor disposed proximate the third side of the moving member.

34

14. The actuator module of claim 6, wherein: the one or more magnetic field sensors include at least one Hall sensor and at least one of a tunneling magnetoresistance (TMR) sensor or a giant magnetoresistance (GMR) sensor.
15. A system, comprising: one or more processors; an optical package including one or more lenses that define an optical axis; an actuator for moving the optical package, wherein the actuator includes: an asymmetric magnet arrangement for actuation along the optical axis and along a plane that is orthogonal to the optical axis, wherein the asymmetric magnet arrangement includes: a lateral position control magnet situated at a first side of the optical package; and a pair of transverse position control magnets situated on respective second and third sides of the optical package opposite one another with respect to an axis between the optical package and the lateral position control magnet, at least one transverse position control magnets of the pair of transverse position control magnets contributing to a first magnetic field component corresponding to a first axis; one or more position sensor magnets attached to the optical package, at least one position sensor magnet of the one or more position magnets contributing to a second magnetic field component corresponding to a second axis that is orthogonal to the first axis; and one or more magnetic field sensors configured to measure magnetic field components including the first magnetic field component and the second magnetic field component; one or more coils attached to the optical package and configured to move along the optical axis; and memory comprising program instructions that, when executed by the one or more processors, cause the one or more processors to: determine, based at least in part on one or more measurements from a first magnetic field sensor of the one or more magnetic field sensors, the first magnetic field component; determine, based at least in part on the one or more measurements from the first magnetic field sensor, the second magnetic field component; and calculate a first position, along the optical axis, of the first position sensor magnet based at least in part on the first magnetic field component and the second magnetic field component.
16. The system of claim 15, wherein: a first position sensor magnet of the one or more position sensor magnets is oriented with a first magnetic field along a first direction; the first magnetic field sensor of the one or more magnetic field sensors is oriented to measure one or more magnetic field components of the first magnetic field of the first position sensor magnet; a second position sensor magnet of the one or more position sensor magnets is oriented with a second magnetic field along a second direction that is antiparallel to the first direction; and a second magnetic field sensor of the one or more magnetic field sensors is oriented to measure one or more magnetic field components of the second magnetic field of the second position sensor magnet.

17. The system of claim 15, wherein:
 a first position sensor magnet of the one or more position
 sensor magnets is oriented with a first magnetic field
 along a first direction;
 the first magnetic field sensor of the one or more magnetic 5
 field sensors is oriented to measure one or more mag-
 netic field components of the first magnetic field of the
 first position sensor magnet;
 a second position sensor magnet of the one or more
 position sensor magnets is oriented with a second 10
 magnetic field along a second direction that is parallel
 to the first direction; and
 a second magnetic field sensor of the one or more mag-
 netic field sensors is oriented to measure one or more
 magnetic field components of the second magnetic field 15
 of the second position sensor magnet.

18. The system of claim 15, wherein:
 at least one of the one or more coils is an autofocus coil;
 and
 the program instructions, when executed by the one or 20
 more processors, further cause the one or more proces-
 sors to:
 determine, based at least in part on the first position, an
 adjustment to at least one of a voltage or a current
 supplied to the autofocus coil to cause the first 25
 position sensor magnet to move to a second position,
 along the optical axis, that is different than the first
 position.

* * * * *