

US010308243B2

(12) **United States Patent**
Lavoie

(10) **Patent No.:** **US 10,308,243 B2**
(45) **Date of Patent:** **Jun. 4, 2019**

(54) **VEHICLE REMOTE PARK ASSIST WITH OCCUPANT DETECTION**

(58) **Field of Classification Search**
None
See application file for complete search history.

(71) Applicant: **Ford Global Technologies, LLC**,
Dearborn, MI (US)

(56) **References Cited**

(72) Inventor: **Erick Michael Lavoie**, Dearborn, MI
(US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Ford Global Technologies, LLC**,
Dearborn, MI (US)

6,724,322 B2 4/2004 Tang
6,768,420 B2 7/2004 McCarthy et al.
6,997,048 B2 2/2006 Komatsu et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 179 days.

FOREIGN PATENT DOCUMENTS

CN 101929921 A 12/2010
CN 103049159 B 7/2015
(Continued)

(21) Appl. No.: **15/220,083**

(22) Filed: **Jul. 26, 2016**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

Daimler AG, *Remote Parking Pilot*, Mar. 2016 (3 Pages).
(Continued)

US 2018/0029591 A1 Feb. 1, 2018


Primary Examiner — Anne M Antonucci
Assistant Examiner — Kenny A. Taveras
(74) *Attorney, Agent, or Firm* — Frank Lollo; Neal,
Gerber & Eisenberg LLP; James P. Muraff

(51) **Int. Cl.**
G05D 1/00 (2006.01)
G05D 3/00 (2006.01)
G06F 7/00 (2006.01)
G06F 17/00 (2019.01)
B60W 30/06 (2006.01)
B60W 50/14 (2012.01)
G06N 7/00 (2006.01)
B62D 15/02 (2006.01)

(57) **ABSTRACT**
Systems and methods are disclosed for vehicle remote park assist with occupant detection. An example disclosed vehicle includes range detection sensors and a remote parking unit. The example range detection sensors determine whether a target parking space is narrow. The example remote parking unit, in response to a request from a mobile device external to the vehicle, when the target parking space is narrow, scans, with occupant detection sensors, the interior of the vehicle. Additionally, the example remote parking unit, in response to detecting an occupant in the vehicle, sends a first notification to the mobile device.

(52) **U.S. Cl.**
CPC **B60W 30/06** (2013.01); **B60W 50/14**
(2013.01); **B62D 15/027** (2013.01); **B62D**
15/0285 (2013.01); **G06N 7/005** (2013.01);
B60W 2050/143 (2013.01); **B60W 2420/42**
(2013.01); **B60W 2420/52** (2013.01); **B60W**
2420/54 (2013.01); **B60W 2750/308** (2013.01)

21 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,813,844 B2 10/2010 Gensler
 8,098,146 B2 1/2012 Petrucelli et al.
 8,692,773 B2 4/2014 You
 9,014,920 B1 * 4/2015 Torres G08B 21/0202
 701/45
 9,302,675 B2 4/2016 Schilling
 9,318,022 B2 4/2016 Barth
 9,842,444 B2 12/2017 Van Wiemeersch
 9,845,070 B2 12/2017 Petel
 9,846,431 B2 12/2017 Petel
 9,921,743 B2 3/2018 Bryant
 9,946,255 B2 4/2018 Matters
 9,975,504 B2 5/2018 Dalke
 10,131,347 B2 11/2018 Kim
 2003/0098792 A1 5/2003 Edwards et al.
 2006/0010961 A1 1/2006 Gibson et al.
 2006/0227010 A1 10/2006 Berstis
 2009/0125181 A1 5/2009 Luke
 2009/0128315 A1 5/2009 Griesser
 2009/0146813 A1 6/2009 Nuno
 2009/0174574 A1 7/2009 Endo et al.
 2012/0007741 A1 1/2012 Laffey, Sr. et al.
 2013/0043989 A1 2/2013 Niemz
 2013/0124061 A1 5/2013 Khanafer
 2014/0222252 A1 * 8/2014 Matters B62D 15/027
 701/2
 2015/0163649 A1 6/2015 Chen
 2015/0220791 A1 8/2015 Wu
 2015/0329110 A1 11/2015 Stefan
 2016/0114726 A1 4/2016 Nagata
 2017/0076603 A1 3/2017 Bostick
 2017/0192428 A1 7/2017 Vogt
 2017/0301241 A1 10/2017 Urhahne
 2017/0308075 A1 10/2017 Whitaker

2018/0029591 A1 2/2018 Lavoie
 2018/0039264 A1 2/2018 Messner
 2018/0043884 A1 2/2018 Johnson
 2018/0056939 A1 3/2018 van Roermund
 2018/0194344 A1 7/2018 Wang
 2018/0236957 A1 8/2018 Min


FOREIGN PATENT DOCUMENTS

CN 105513412 A 4/2016
 CN 106598630 A 4/2017
 CN 104290751 B 1/2018
 DE 19817142 A1 10/1999
 DE 19821163 A1 11/1999
 DE 102012200725 A1 * 7/2013 B62D 15/027
 DE 102012200725 A1 7/2013
 DE 102014009077 A1 2/2015
 DE 102016125282 A1 7/2017
 GB 2517835 A 3/2015
 JP 2000293797 A 10/2000
 JP 5586450 B2 9/2014
 WO WO 2013/123813 A1 8/2013
 WO WO 2016/128200 A1 8/2016
 WO WO 2016/134822 A1 9/2016
 WO WO 2017/096307 A1 6/2017
 WO WO 2017/096728 A1 6/2017
 WO WO 2017/097942 A1 6/2017

OTHER PUBLICATIONS

Search Report dated Jan. 19, 2018 for GB Patent Application No. 1711988.4 (3 pages).
 Tesla Model S Owner's Manual v2018.44. Oct. 29, 2018.
 Search Report dated Oct. 10, 2018 for GB Patent Application No. 1806499.8 (4 pages).

* cited by examiner






FIG. 2




FIG. 3




FIG. 4

1

VEHICLE REMOTE PARK ASSIST WITH OCCUPANT DETECTION

TECHNICAL FIELD

The present disclosure generally relates to semi-autonomous vehicles and, more specifically, vehicle remote park assist with occupant detection.

BACKGROUND

A semi-autonomous vehicle is a vehicle that is normally operated by a driver, but certain specialized functions are autonomous. For example, some vehicles have adaptive cruise control or autopilot that facilitates, in certain circumstances, the vehicle controlling its speed and following distance independent of driver controlling input. Increasingly, vehicles are equipped with parking assist functions that will park the vehicle. When activated remotely, parking assist systems facilitate parking vehicles in narrow spaces.

SUMMARY

The appended claims define this application. The present disclosure summarizes aspects of the embodiments and should not be used to limit the claims. Other implementations are contemplated in accordance with the techniques described herein, as will be apparent to one having ordinary skill in the art upon examination of the following drawings and detailed description, and these implementations are intended to be within the scope of this application.

Example embodiments are disclosed for vehicle remote park assist with occupant detection. An example disclosed vehicle includes range detection sensors and a remote parking unit. The example range detection sensors determine whether a target parking space is narrow. The example remote parking unit, in response to a request from a mobile device external to the vehicle, when the target parking space is narrow, scans, with occupant detection sensors, the interior of the vehicle. Additionally, the example remote parking unit, in response to detecting an occupant in the vehicle, sends a first notification to the mobile device.

An example disclosed method to remotely park a vehicle includes determining, with range detection sensors, whether a target parking space is narrow. The example method also includes, in response to a request from a mobile device external to the vehicle when the target parking space is narrow, scanning, with occupant detection sensors, the interior of the vehicle, and in response to detecting an occupant in the vehicle, sending, via a processor, a first notification to the mobile device.

An example disclosed tangible computer readable medium comprises instruction that, when executed, cause a vehicle to determine, with range detection sensors, whether a target parking space is narrow. Additionally, the example instructions, when executed, cause the vehicle to, in response to a request from a mobile device external to the vehicle, when the target parking space is narrow, scan, with occupant detection sensors, the interior of the vehicle, and in response to detecting an occupant in the vehicle, send a first notification to the mobile device.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the invention, reference may be made to embodiments shown in the following drawings. The components in the drawings are not necessarily to scale

2

and related elements may be omitted, or in some instances proportions may have been exaggerated, so as to emphasize and clearly illustrate the novel features described herein. In addition, system components can be variously arranged, as known in the art. Further, in the drawings, like reference numerals designate corresponding parts throughout the several views.

FIG. 1 illustrates a vehicle operating in accordance with the teachings of this disclosure.

FIG. 2 is a block diagram of electronic components of the vehicle of FIG. 1.

FIG. 3 is a flow diagram of a method to perform remote assisted parking that may be implemented by the electronic components of FIG. 2.

FIG. 4 is a flow diagram of another method to perform remote assisted parking that may be implemented by the electronic components of FIG. 2.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

While the invention may be embodied in various forms, there are shown in the drawings, and will hereinafter be described, some exemplary and non-limiting embodiments, with the understanding that the present disclosure is to be considered an exemplification of the invention and is not intended to limit the invention to the specific embodiments illustrated.

Remote park assist systems facilitate a customer exiting the vehicle before the remote park assist system autonomously parks the vehicle. The driver activates the remote park assist system using a button on a key and/or an interface on an authorized mobile device (e.g., a smart phone, a smart watch, a tablet, etc.). In such a manner, a vehicle may be parked in a narrow space in which the doors of the vehicle cannot be opened. This facilitates parking vehicles more densely in a space saving manner. However, if the vehicle is parked while an occupant or an object of interest (e.g., a purse, a wallet, a mobile device, etc.) is in the vehicle, traditionally, the remote park assist system needs reverse to a point where the door can be opened.

As disclosed herein below, a vehicle includes a remote parking unit to autonomously park the vehicle. The remote parking unit is communicatively coupled, via one or more vehicle data buses, to other electronic control units (ECUs) that control the motive functions of the vehicle. For example, the ECUs may include a transmission control unit, a throttle control unit, and a brake control, etc. The remote parking unit is also communicatively coupled to range detection sensors to detect objects in the proximity of the vehicle and the location, size and shape of the parking spot. Additionally, the remote parking unit includes an occupant detector. As used herein, an occupant is defined to include (i) humans and animals, and (ii) objects configured to be detected (e.g., a purse, a wallet, a mobile device, a stroller, a child seat, etc.). The occupant detector monitors the interior of the vehicle for occupants. When the remote parking unit is activated, the occupant detector determines whether an occupant is inside the vehicle. If an occupant is not detected, the occupant detector sends a message to the key fob or the mobile device to remind the driver the vehicle is about to be parked into a narrow space. If an occupant is detected, the remote parking unit (a) instructs the transmission control unit to shift the transmission into park, and (b) sends a message to the key fob or the mobile device to notify the driver that the occupant is in the vehicle. In some examples, the occupant detector, based on data from the

range detection and navigation data, determines whether the parking space is currently narrow or projected become a narrow parking space in the future. As used herein a narrow parking space is a parking space in which the vehicle, with its doors closed, is able to fit, but the doors cannot be open to facilitate the entrance or exit of the driver or an occupant. For example, if the parking lot in which the vehicle is being parked is designed to have narrow parking spots, the occupant detector may act as if the parking spot is a narrow parking spot even if one or more of the adjacent parking spaces are currently empty.

FIG. 1 illustrates an assisted vehicle **100** operating in accordance with the teachings of this disclosure. As used herein, an assisted vehicle **100** is a vehicle that includes a remote parking unit **102** that controls the motive functions of the vehicle to park the vehicle without a driver occupying the vehicle. The assisted vehicle **100** may be a standard gasoline powered vehicle, a hybrid vehicle, an electric vehicle, a fuel cell vehicle, and/or any other mobility implement type of vehicle. The assisted vehicle **100** includes parts related to mobility, such as a powertrain with an engine, a transmission, a suspension, a driveshaft, and/or wheels, etc. Additionally, the assisted vehicle **100** may be semi-autonomous or autonomous. A semi-autonomous vehicle is a vehicle that autonomously controls some routine motive functions (e.g., assisted parking, remote assisted parking, adaptive cruise control, etc.) while the driver controls the vehicle. An autonomous vehicle is a vehicle that autonomously controls the motive functions of the vehicle without direct user steering input. In the illustrated example, the assisted vehicle **100** includes range detection sensors **104**, a wireless network node **106**, occupant detection sensors **108**, electronic control units (ECUs) **110**, and the remote parking unit **102**. In some examples, the assisted vehicle **100** includes an on-board communications platform **112**.

The range detection sensors **104** sense objects, such as parked vehicle **114**, and characterize spaces, such a parking space **116**, in the vicinity of the assisted vehicle **100**. The range detection sensors **104** include ultrasonic sensors, cameras, infrared sensors, RADAR, and/or LiDAR, etc. In the illustrated example, the range detection sensors **104** are embedded in the bumper of the assisted vehicle **100** to detect the parked vehicles **114** and characterized the parking space **116** for the remote parking unit **102**. Alternatively, the range detection sensors **104** may be positioned in other locations (e.g., on the roof of the assisted vehicle **100**, etc.) to facilitate detecting the parked vehicles **114** and characterized the parking space **116**. In the illustrated example, the range detection sensors **104** determine a mirror width (W_M) (e.g., the width between the side view mirrors of the parked vehicles **114**) and a total width (W_T) (e.g. the width between the parked vehicles **114** at the point that a vehicle parked between them would open its doors).

The wireless network node **106** connects to a mobile device **117** (e.g., a smart phone, a smart watch, a tablet computer, etc.) of the driver of the assisted vehicle **100**. In some examples, the wireless network node **106** is configured in accordance with Bluetooth Low Energy (BLE) as specified in the Bluetooth Specification 4.0 (as revised) maintained by the Bluetooth Special Interest Group. Alternatively, in some examples, the wireless network node **106** may operate in accordance with other local area or personal area network standards, such as Bluetooth, IEEE 802.11 or IEEE 802.15.4. When connected to the mobile device **117**, the wireless network node **106** facilitates input by a user to the remote parking unit **102** (e.g., activating the remote

parking system, etc.). Additionally, the remote parking unit **102** may send notifications to the mobile device **117** via the wireless network node **106**.

The occupant detection sensors **108** detect occupants inside the assisted vehicle **100**. In some examples, the occupant detection sensors **108** detect indicators of the presences of the occupants (e.g., biometric sensors, weight sensors, interior ultrasonic sensors, cameras, heartbeat sensors, etc.). Additionally, in some examples, the occupant detection sensors **108** detect tags associated with the occupants (e.g., radio-frequency identification (RFID) readers, BLE nodes, etc.). The tags are active or passive devices configured to attach to objects (e.g., purses, wallets, car seats, baby carriers, etc.) that respond when interrogated by the corresponding occupant detection sensor **108**. For example, the tag may be a passive RFID circuit that responds when interrogated by an RFID reader. The occupant detection sensors **108**, from time to time (e.g., periodically, aperiodically, etc.) activate their various functions (sometimes referred to as “scanning”) to detect occupants inside the cabin of the assisted vehicle **100**.

The ECUs **110** monitor and control subsystems of the assisted vehicle **100**. The ECUs **110** communicate and exchange information via the a vehicle data bus (e.g., the vehicle data bus **202** of FIG. 2 below). Additionally, the ECU(s) **110** may communicate properties (such as, status of the ECU **110**, sensor readings, control state, error and diagnostic codes, etc.) to and receive instructions from other devices (e.g., the remote parking unit **102**, etc.) Some assisted vehicles **100** may have seventy or more ECUs **110** located in various locations around the assisted vehicle **100** communicatively coupled by the vehicle data bus. The ECUs **110** are discrete sets of electronics that include their own circuit(s) (such as integrated circuits, microprocessors, memory, storage, etc.) and firmware, sensors, actuators, and/or mounting hardware. In the illustrated example, the ECUs **110** include a steering control unit **118**, a brake control unit **120**, a throttle control unit **122**, and a transmission control unit **124**. The steering control unit **118** includes actuators to control the steering (e.g., the angle of the wheels) of the assisted vehicle **100** without driver input. The brake control unit **120** includes actuators to operate the brakes of the assisted vehicle **100** without driver input. Additionally, the throttle control unit **122** controls is capable of adjust the throttle position of the assisted vehicle **100** without driver input. The transmission control unit **124** facilitates changed the transmission setting of the assisted vehicle **100** without driver input.

The on-board communications platform **112** includes wired or wireless network interfaces to enable communication with external networks. The on-board communications platform **112** also includes hardware (e.g., processors, memory, storage, antenna, etc.) and software to control the wired or wireless network interfaces. The on-board communications platform **112** may include controllers for Bluetooth® and/or other standards-based networks (e.g., Global System for Mobile Communications (GSM), Universal Mobile Telecommunications System (UMTS), Long Term Evolution (LTE), Code Division Multiple Access (CDMA), WiMAX (IEEE 802.16m); Near Field Communication (NFC); local area wireless network (including IEEE 802.11 a/b/g/n/ac or others), and Wireless Gigabit (IEEE 802.11ad), etc.). The on-board communications platform **112** may also include a global positioning system (GPS) receiver. Further, the external network(s) may be a public network, such as the Internet; a private network, such as an intranet; or combinations thereof, and may utilize a variety of networking

protocols now available or later developed including, but not limited to, TCP/IP-based networking protocols.

The remote parking unit **102** parts the assisted vehicle **100** into the parking space **116** in response to a request from a user (e.g., via the mobile device **117** communicatively coupled to the wireless network node **106**). The remote parking unit **102** facilitates parking the assisted vehicle **100** into a narrow parking space (e.g., the parking space **116**) without the driver in the assisted vehicle **100**. For example, the driver may park the assisted vehicle **100** near the target parking space **116**, exit the assisted vehicle **100**, and engage the remote parking assist system. In such an example, the remote parking unit **102** may maneuver the assisted vehicle **100** into the parking space **116** by controlling the ECUs **110**. Additionally, the remote parking unit **102** facilitates the assisted vehicle **100** exiting the parking space **116** without the driver in the assisted vehicle **100**.

The remote parking unit **102**, via the range detection sensors **104**, locates the parked vehicle(s) **112** and characterizes the spatial dimensions of the parking space **116**. Based on the mirror width (W_M), the total width (W_T) and a vehicle width (W_V) of the assisted vehicle **100**, the remote parking unit **102** determines whether the assisted vehicle **100** will fit into the parking space **116**. If the assisted vehicle **100** will fit into the parking space **116**, the remote parking unit **102** calculates a path **126** to maneuver the assisted vehicle **100** into the parking space **116**. If the assisted vehicle **100** will fit into the parking space **116**, the remote parking unit **102** notifies the driver (e.g., via the mobile device **117**).

Additionally, the remote parking unit **102**, via the occupant detection sensors **108**, monitors the cabin of the assisted vehicle **100** to determine whether occupants are inside the assisted vehicle **100**. In some examples, the occupant detection sensors **108** detect indicia of the occupant(s), such as a heartbeat, weight on one of the seats, camera object recognition, movement, etc. In some examples, the occupant detection sensors **108** detect the tags affixed to objects in the cabin. If an occupant is detected when the driver activates the remote parking system, the remote parking unit **102**, via the transmission control unit **124**, shifts the transmission of the assisted vehicle **100** into park and sends a notification, via the wireless network node **106**, to the driver that an occupant was detected in the assisted vehicle **100**.

In some examples, the remote parking unit **102** determines whether the parking space **116** will become a narrow parking space. For example, if only one parked vehicle **114** is currently adjacent to the parking space **116**, the parking space **116** may become a narrow parking space when another parked vehicle **114** parks adjacent to the parking space **116**. In some such examples, the remote parking unit **102** connects, via the on-board communications platform **112**, to a server on an external network (e.g., the Internet) to determine whether the parking space **116** is a known narrow parking space. For example, a navigation data provider (e.g., Google®, MapQuest®, Waze®, etc.) may supply data on whether the current location of the assisted vehicle **100** (e.g., supplied by the GPS receiver of the on-board communications platform **112**) is a location with narrow parking spaces. Additionally or alternatively, in some examples, the remote parking unit **102** analyzes other vehicle park in the vicinity and/or analyzes (e.g., when the range detection sensors **104** include external cameras) width of the marking delineating the parking space **116**. In some such examples, if the parking space **116** may become a narrow parking space, the remote parking unit **102** acts as if it is currently a narrow parking space.

FIG. 2 is a block diagram of electronic components **200** of the assisted vehicle **100** of FIG. 1. In the illustrated example, the electronic components **200** include the remote parking unit **102**, the on-board communications platform **112**, the sensors **104** and **108**, the wireless network node **106**, the ECUs **110**, and a vehicle data bus **202**.

The remote parking unit **102** includes a processor or controller **204**, and memory **206**. The processor or controller **204** may be any suitable processing device or set of processing devices such as, but not limited to: a microprocessor, a microcontroller-based platform, a suitable integrated circuit, one or more field programmable gate arrays (FPGAs), and/or one or more application-specific integrated circuits (ASICs). The memory **206** may be volatile memory (e.g., RAM, which can include non-volatile RAM, magnetic RAM, ferroelectric RAM, and any other suitable forms); non-volatile memory (e.g., disk memory, FLASH memory, EPROMs, EEPROMs, memristor-based non-volatile solid-state memory, etc.), unalterable memory (e.g., EPROMs), read-only memory, and/or high-capacity storage devices (e.g., hard drives, solid state drives, etc.). In some examples, the memory **206** includes multiple kinds of memory, particularly volatile memory and non-volatile memory.

The memory **206** is computer readable media on which one or more sets of instructions, such as the software for operating the methods of the present disclosure can be embedded. The instructions may embody one or more of the methods or logic as described herein. In a particular embodiment, the instructions may reside completely, or at least partially, within any one or more of the memory **206**, the computer readable medium, and/or within the processor **204** during execution of the instructions.

The terms “non-transitory computer-readable medium” and “computer-readable medium” should be understood to include a single medium or multiple media, such as a centralized or distributed database, and/or associated caches and servers that store one or more sets of instructions. The terms “non-transitory computer-readable medium” and “computer-readable medium” also include any tangible medium that is capable of storing, encoding or carrying a set of instructions for execution by a processor or that cause a system to perform any one or more of the methods or operations disclosed herein. As used herein, the term “computer readable medium” is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals.

The vehicle data bus **202** communicatively couples the remote parking unit **102**, the on-board communications platform **112**, the sensors **104** and **108**, the wireless network node **106**, and the ECUs **110**. In some examples, the vehicle data bus **202** includes one or more data buses. The vehicle data bus **202** may be implemented in accordance with a controller area network (CAN) bus protocol as defined by International Standards Organization (ISO) 11898-1, a Media Oriented Systems Transport (MOST) bus protocol, a CAN flexible data (CAN-FD) bus protocol (ISO 11898-7), a K-line bus protocol (ISO 9141 and ISO 14230-1), and/or an Ethernet™ bus protocol IEEE 802.3 (2002 onwards), etc. In some examples, the ECUs **110** and sensors **104** and **108** are organized on separate data buses to manage, for example, safety, data congestion, data management, etc. For example, the sensitive ECUs **110** (e.g., the brake control unit **120**, the throttle control unit **122**, etc.) may be on a separate bus from the other ECUs **110** and sensors **104** and **108**.

FIG. 3 is a flow diagram of a method to perform remote assisted parking that may be implemented by the electronic components **200** of FIG. 2. Initially, at block **302**, the remote

parking unit 102 monitors the interior of the assisted vehicle 100 for occupants. At block 304, the remote parking unit 102 waits until the driver activates the remote parking system. In response to the driver activating the remote parking system, at block 306, the remote parking unit 102 determines whether the occupant detection sensors 108 detect an occupant in the interior of the assisted vehicle 100. For example, the occupant detection sensors 108 may detect a tag affixed to a purse in the cabin of the assisted vehicle 100. If the occupant detection sensors 108 detect an occupant in the interior of the assisted vehicle 100, the method continues at block 308. Otherwise, if the occupant detection sensors 108 do not detect an occupant in the interior of the assisted vehicle 100, the method continues at block 314.

At block 308, the remote parking unit 102 instructs the transmission control unit 124 to shift the transmission of the assisted vehicle 100 into park. At block 310, the remote parking unit 102 instructs the assisted vehicle 100 (e.g., via a body control unit) to alert the driver (e.g., activate hazard lights, activate a horn with a short burst pattern, flash lights of the vehicle, etc.). At block 312, the remote parking unit 102, via the wireless network node 106, sends a notification to the mobile device 117 of the driver to inform them of the detected occupant. In some examples, the notification causes the mobile device 117 to display a text or picture warning, vibrate, and/or produce an audio warning, etc. In some examples, if an identifier is associated with the occupant (e.g., an identifier of an RFID tag associated with the occupant), the notification includes the identifier.

At block 314, the remote parking unit 102, via the wireless network node 106, sends a notification to the mobile device 117 of the driver to (i) remind the driver that the of the narrow parking spot and (ii) prompt a confirmation process on the mobile device 117. For example, the notification may cause the mobile device 117 to display, "Warning: there is not enough room to open vehicle doors when parked in this space." At block 316, the remote parking unit 102 waits until a confirmation is received from the mobile device 117 of the driver. At block 318, the remote parking unit 102 parks the assisted vehicle 100 in the parking space 116.

FIG. 4 is a flow diagram of another method to perform remote assisted parking that may be implemented by the electronic components 200 of FIG. 2. Initially, at block 402, the remote parking unit 102 waits until the driver activates the remote parking system. At block 404, the remote parking unit 102 determines, via the range detection sensors 104, the dimensions of the parking space 116. For example, the remote parking unit 102 determines the mirror width (W_M) and the total width (W_T) of the parking space 116. At block 406, the remote parking unit 102 determines whether the parking space 116 is a narrow parking space. If the parking space 116 is not a narrow parking space, the method continues at block 408. Otherwise, if the parking space 116 is a narrow parking space, the method continues at block 418.

At block 408, the remote parking unit 102 analyzes whether the parking space 116 will become a narrow parking space. In some examples, the remote parking unit 102 connects, via the on-board communications platform 112, to a server on an external network (e.g., via an application programming interface (API)) to request navigation data indicating whether the parking area in the vicinity of the assisted vehicle 100 is designated as having narrow parking spaces. Alternatively or additionally, in some examples, the remote parking unit 102 analyzes markings in the parking space 116 delineating the boundaries of the parking space

116. At block 410, the remote parking unit 102 determines whether the parking space 116 may become a narrow parking space. If the parking space 116 may become a narrow parking space, the method continues to block 412. Otherwise, if the parking space 116 will not become a narrow parking space, the method continues to block 416.

At block 412, the remote parking unit 102, via the wireless network node 106, sends a notification to the mobile device 117 of the driver to (i) remind the driver that the of the narrow parking spot and (ii) prompt a confirmation process on the mobile device 117. At block 414, the remote parking unit 102 waits until a confirmation is received from the mobile device 117 of the driver. At block 316, the remote parking unit 102 parks the assisted vehicle 100 in the parking space 116.

At block 418, the remote parking unit 102 scans the interior of the assisted vehicle 100 for occupants. At block 420, the remote parking unit 102 determines whether the occupant detection sensors 108 detect an occupant in the interior of the assisted vehicle 100. For example, the occupant detection sensors 108 may detect a heartbeat with a heartbeat sensor and weight from a weight sensor monitoring the back seat. If the occupant detection sensors 108 detect an occupant in the interior of the assisted vehicle 100, the method continues at block 422. Otherwise, if the occupant detection sensors 108 do not detect an occupant in the interior of the assisted vehicle 100, the method continues at block 412.

At block 422, the remote parking unit 102 instructs the transmission control unit 124 to shift the transmission of the assisted vehicle 100 into park. At block 424, the remote parking unit 102, via the wireless network node 106, sends a notification to the mobile device 117 of the driver to inform them of the detected occupant. In some examples, if an identifier is associated with the occupant (e.g., an identifier of an RFID tag associated with the occupant), the notification includes the identifier.

The flowchart of FIGS. 3 and 4 are a methods that may be implemented by machine readable instructions that comprise one or more programs that, when executed by a processor (such as the processor 204 of FIG. 2), cause the assisted vehicle 100 to implement the remote parking unit 102 of FIG. 1. Further, although the example program(s) is/are described with reference to the flowcharts illustrated in FIGS. 3 and 4, many other methods of implementing the example the remote parking unit 102 may alternatively be used. For example, the order of execution of the blocks may be changed, and/or some of the blocks described may be changed, eliminated, or combined.

In this application, the use of the disjunctive is intended to include the conjunctive. The use of definite or indefinite articles is not intended to indicate cardinality. In particular, a reference to "the" object or "a" and "an" object is intended to denote also one of a possible plurality of such objects. Further, the conjunction "or" may be used to convey features that are simultaneously present instead of mutually exclusive alternatives. In other words, the conjunction "or" should be understood to include "and/or". The terms "includes," "including," and "include" are inclusive and have the same scope as "comprises," "comprising," and "comprise" respectively.

The above-described embodiments, and particularly any "preferred" embodiments, are possible examples of implementations and merely set forth for a clear understanding of the principles of the invention. Many variations and modifications may be made to the above-described embodiment(s) without substantially departing from the

9

spirit and principles of the techniques described herein. All modifications are intended to be included herein within the scope of this disclosure and protected by the following claims.

What is claimed is:

1. A vehicle comprising:
range detection sensors to determine whether a target parking space is narrow; and
a remote parking unit to:
responsive to a request from a mobile device external to the vehicle:

when the target parking space is narrow:
scan, with occupant detection sensors, an interior of the vehicle; and

responsive to detecting no occupants in the vehicle,
send, to the mobile device, a first notification indicating that the target parking space is narrow.

2. The vehicle of claim **1**, wherein the range detection sensors include at least one of a plurality of ultrasonic sensors, a RADAR, a LiDAR, an infrared sensors, or a camera.

3. The vehicle of claim **1**, wherein the occupant detection sensors include at least one of an ultrasonic sensor, a weight sensor, a camera, a heartbeat sensor, or an RFID reader.

4. The vehicle of claim **1**, wherein the target parking space is narrow when a width of the target parking space is less than a width of the vehicle with doors of the vehicle open to facilitate entering and exiting the vehicle.

5. The vehicle of claim **1**, wherein when the target parking space is not narrow, the remote parking unit is to determine a likelihood that the target parking space will become narrow.

6. The vehicle of claim **5**, wherein the remote parking unit is to, when the target parking space is likely to become narrow, scan, the with occupant detection sensors, the interior of the vehicle.

7. The vehicle of claim **5**, wherein the remote parking unit is to determine the likelihood at least in part by receiving navigation data from an external server, the navigation data indicating one or more locations with a narrow parking space.

8. The vehicle of claim **5**, wherein the remote parking unit is to determine the likelihood at least in part by scanning, via the range detection sensors:

one or more parking spaces that are similar to the target parking space; and
one or more objects surrounding the one or more parking spaces.

9. The vehicle of claim **1**, wherein the remote parking unit is to, in response to detecting an occupant in the vehicle, activate a warning produced by the vehicle.

10. The vehicle of claim **9**, wherein the warning includes at least one of activating a horn in a short burst pattern, flashing lights of the vehicle, or activating hazard light of the vehicle.

10

11. The vehicle of claim **1**, wherein the remote parking unit is to, when the target parking space is narrow, send a second notification to the mobile device.

12. A method to remotely park a vehicle comprising:
determining, with range detection sensors, whether a target parking space is narrow;
in response to a request from a mobile device external to the vehicle:
when the target parking space is narrow:
scanning, with occupant detection sensors, an interior of the vehicle; and
in response to detecting no occupants in the vehicle,
sending, via a processor, to the mobile device, a first notification indicating that the target parking space is narrow.

13. The method of claim **12**, wherein the range detection sensors include at least one of a plurality of ultrasonic sensors, a RADAR, a LiDAR, an infrared sensors, or a camera.

14. The method of claim **12**, wherein the occupant detection sensors include at least one of an ultrasonic sensor, a weight sensor, a camera, a heartbeat sensor, or an RFID reader.

15. The method of claim **12**, wherein the target parking space is narrow when a width of the target parking space is less than a width of the vehicle with doors of the vehicle open to facilitate entering and exiting the vehicle.

16. The method of claim **12**, including, when the target parking space is not narrow, determining a likelihood that the target parking space will become narrow.

17. The method of claim **16**, including, when the target parking space is likely to become narrow, scanning, the with occupant detection sensors, the interior of the vehicle.

18. The method of claim **12**, including, in response to detecting an occupant in the vehicle, activating a warning produced by the vehicle.

19. The method of claim **18**, wherein activating the warning includes at least one of activating a horn in a short burst pattern, flashing lights of the vehicle, or activating hazard light of the vehicle.

20. The method of claim **12**, including, when the target parking space is narrow, sending a second notification to the mobile device.

21. A tangible, non-transitory, computer-readable medium comprising instruction that, when executed, cause a vehicle to:

determine, with range detection sensors, whether a target parking space is narrow;
in response to a request from a mobile device external to the vehicle:
when the target parking space is narrow;
scan, with occupant detection sensors, an interior of the vehicle; and
in response to detecting no occupants in the vehicle,
send, to the mobile device, a first notification indicating that the target parking space is narrow.

* * * * *