

US010324271B2

(12) **United States Patent**  
**Tang et al.**

(10) **Patent No.:** **US 10,324,271 B2**  
(45) **Date of Patent:** **\*Jun. 18, 2019**

- (54) **OPTICAL IMAGE CAPTURING SYSTEM**
- (71) Applicant: **ABILITY OPTO-ELECTRONICS TECHNOLOGY CO. LTD.**, Taichung (TW)
- (72) Inventors: **Nai-Yuan Tang**, Taichung (TW); **Yeong-Ming Chang**, Taichung (TW)
- (73) Assignee: **ABILITY OPTO-ELECTRONICS TECHNOLOGY CO. LTD.**, Taichung (TW)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 756 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/971,307**

(22) Filed: **Dec. 16, 2015**

(65) **Prior Publication Data**  
US 2017/0052345 A1 Feb. 23, 2017

(30) **Foreign Application Priority Data**  
Aug. 17, 2015 (TW) ..... 104126746 A

(51) **Int. Cl.**  
**G02B 9/62** (2006.01)  
**G02B 13/00** (2006.01)  
**G02B 13/06** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G02B 13/0045** (2013.01); **G02B 9/62** (2013.01); **G02B 13/06** (2013.01)

(58) **Field of Classification Search**  
CPC ..... G02B 9/62; G02B 13/0045  
USPC ..... 359/708-713, 754, 756-762  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,581,791 B1 *	2/2017	Liu	.....	G02B 13/0045
9,599,798 B1 *	3/2017	Tang	.....	G02B 13/06
9,784,990 B2 *	10/2017	Liu	.....	G02B 27/646
9,880,396 B2 *	1/2018	Tang	.....	G02B 13/06
9,904,035 B2 *	2/2018	Lai	.....	G02B 5/005
9,977,223 B2 *	5/2018	Lai	.....	G02B 13/04

(Continued)

FOREIGN PATENT DOCUMENTS

CN	106405789 A	2/2017
CN	106405792 A	2/2017

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 14/974,443, filed Dec. 18, 2015.

(Continued)


*Primary Examiner* — Darryl J Collins

(74) *Attorney, Agent, or Firm* — Muncy, Geissler, Olds & Lowe, P.C.

(57) **ABSTRACT**

A six-piece optical lens for capturing image and a six-piece optical module for capturing image are provided. In order from an object side to an image side, the optical lens along the optical axis includes a first lens with refractive power, a second lens with refractive power, a third lens with refractive power, a fourth lens with refractive power, a fifth lens with refractive power and a sixth lens with refractive power. At least one of the image-side surface and object-side surface of each of the six lens elements is aspheric. The optical lens can increase aperture value and improve the imaging quality for use in compact cameras.

**25 Claims, 32 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

9,989,736 B2 \* 6/2018 Tang ..... G02B 13/0045  
10,001,628 B2 \* 6/2018 Lai ..... G02B 13/0045  
10,007,085 B2 \* 6/2018 Tang ..... G02B 13/0045  
10,012,819 B2 \* 7/2018 Lai ..... G02B 7/04  
10,031,319 B2 \* 7/2018 Lai ..... G02B 5/005  
2018/0059369 A1 \* 3/2018 Chang ..... G02B 5/005  
2018/0074291 A1 \* 3/2018 Chang ..... G02B 5/005  
2018/0188490 A1 \* 7/2018 Chang ..... G02B 13/0045  
2018/0188495 A1 \* 7/2018 Chang ..... G02B 13/0045

FOREIGN PATENT DOCUMENTS

EP 1 881 356 B1 5/2013  
TW M503575 U 6/2015  
WO WO 2015/060166 A1 4/2015

OTHER PUBLICATIONS

U.S. Appl. No. 14/980,098, filed Dec. 28, 2015.  
U.S. Appl. No. 14/980,213, filed Dec. 28, 2015.

U.S. Appl. No. 14/980,046, filed Dec. 28, 2015.  
U.S. Appl. No. 14/985,801, filed Dec. 31, 2015.  
U.S. Appl. No. 14/985,849, filed Dec. 31, 2015.  
U.S. Appl. No. 14/971,767, filed Dec. 16, 2015.  
U.S. Appl. No. 14/972,579, filed Dec. 17, 2015.  
U.S. Appl. No. 14/972,669, filed Dec. 17, 2015.  
U.S. Appl. No. 14/974,902, filed Dec. 18, 2015.  
U.S. Appl. No. 14/972,507, filed Dec. 17, 2015.  
U.S. Appl. No. 14/971,649, filed Dec. 16, 2015.  
U.S. Appl. No. 14/985,922, filed Dec. 31, 2015.  
U.S. Appl. No. 14/971,457, filed Dec. 16, 2015.  
U.S. Appl. No. 14/971,563, filed Dec. 16, 2015.  
U.S. Appl. No. 14/974,596, filed Dec. 18, 2015.  
U.S. Appl. No. 14/975,022, filed Dec. 18, 2015.  
U.S. Appl. No. 14/973,111, filed Dec. 17, 2015.  
U.S. Appl. No. 14/972,835, filed Dec. 17, 2015.  
U.S. Appl. No. 14/973,212, filed Dec. 17, 2015.  
U.S. Appl. No. 14/974,716, filed Dec. 18, 2015.  
U.S. Appl. No. 14/971,726, filed Dec. 16, 2015.  
U.S. Appl. No. 14/973,168, filed Dec. 17, 2015.  
U.S. Appl. No. 14/987,289, filed Jan. 4, 2016.

\* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2A




FIG. 2B






FIG. 2C




FIG. 2D




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4A




FIG. 4B






FIG. 4C




FIG. 4D




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6A




FIG. 6B






FIG. 6C




FIG. 6D




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A




FIG. 8B






FIG. 8C




FIG. 8D

## 1

**OPTICAL IMAGE CAPTURING SYSTEM****CROSS-REFERENCE TO RELATED APPLICATION**

This application claims the benefit of Taiwan Patent Application No. 104126746, filed on Aug. 17, 2015, in the Taiwan Intellectual Property Office, the disclosure of which is incorporated herein in its entirety by reference.

**BACKGROUND OF THE INVENTION**

## 1. Field of the Invention

The present disclosure relates to an optical image capturing system, and more particularly to a compact optical image capturing system which can be applied to electronic products.

## 2. Description of the Related Art

In recent years, with the rise of portable electronic devices having camera functionalities, the demand for an optical image capturing system is raised gradually. The image sensing device of ordinary photographing camera is commonly selected from charge coupled device (CCD) or complementary metal-oxide semiconductor sensor (CMOS Sensor). In addition, as advanced semiconductor manufacturing technology enables the minimization of pixel size of the image sensing device, the development of the optical image capturing system directs towards the field of high pixels. Therefore, the requirement for high imaging quality is rapidly raised.

The traditional optical image capturing system of a portable electronic device comes with different designs, including a four-lens or a five-lens design. However, the requirement for the higher pixels and the requirement for a large aperture of an end user, like functionalities of micro filming and night view, or the requirement of wide view angle of the portable electronic device have been raised. But the optical image capturing system with the large aperture design often produces more aberration resulting in the deterioration of quality in peripheral image formation and difficulties of manufacturing, and the optical image capturing system with wide view angle design increases distortion rate in image formation, thus the optical image capturing system in prior arts cannot meet the requirement of the higher order camera lens module.

Therefore, how to effectively increase quantity of incoming light and view angle of the optical lenses, not only further improves total pixels and imaging quality for the image formation, but also considers the equity design of the miniaturized optical lenses, becomes a quite important issue.

**SUMMARY OF THE INVENTION**

The aspect of embodiment of the present disclosure directs to an optical image capturing system and an optical image capturing lens which use combination of refractive powers, convex and concave surfaces of six-piece optical lenses (the convex or concave surface in the disclosure denotes the geometrical shape of an image-side surface or an object-side surface of each lens on an optical axis) to increase the quantity of incoming light of the optical image capturing system and the view angle of the optical lenses,

## 2

and to improve total pixels and imaging quality for image formation, so as to be applied to minimized electronic products.

The term and its definition to the lens element parameter in the embodiment of the present invention are shown as below for further reference.

The lens element parameter related to a length or a height in the lens element

A maximum height for image formation of the optical image capturing system is denoted by HOI. A height of the optical image capturing system is denoted by HOS. A distance from the object-side surface of the first lens element to the image-side surface of the sixth lens element is denoted by InTL. A distance from an aperture stop (aperture) to an image plane is denoted by InS. A distance from the first lens element to the second lens element is denoted by In12 (instance). A central thickness of the first lens element of the optical image capturing system on the optical axis is denoted by TP1 (instance).

The lens element parameter related to a material in the lens element

An Abbe number of the first lens element in the optical image capturing system is denoted by NA1 (instance). A refractive index of the first lens element is denoted by Nd1 (instance).

The lens element parameter related to a view angle in the lens element

A view angle is denoted by AF. Half of the view angle is denoted by HAF. A major light angle is denoted by MRA.

The lens element parameter related to exit/entrance pupil in the lens element

An entrance pupil diameter of the optical image capturing system is denoted by HEP. A maximum effective half diameter (EHD) of any surface of a single lens element refers to a perpendicular height between an intersection point on the surface of the lens element where the incident light with the maximum view angle in the optical system passes through the outmost edge of the entrance pupil and the optical axis. For example, the maximum effective half diameter of the object-side surface of the first lens element is denoted by EHD 11. The maximum effective half diameter of the image-side surface of the first lens element is denoted by EHD 12. The maximum effective half diameter of the object-side surface of the second lens element is denoted by EHD 21. The maximum effective half diameter of the image-side surface of the second lens element is denoted by EHD 22. The maximum effective half diameters of any surfaces of other lens elements in the optical image capturing system are denoted in the similar way.

The lens element parameter related to a depth of the lens element shape

A distance in parallel with an optical axis from a maximum effective diameter position to an axial point on the object-side surface of the sixth lens element is denoted by InRS61 (instance). A distance in parallel with an optical axis from a maximum effective diameter position to an axial point on the image-side surface of the sixth lens element is denoted by InRS62 (instance).

The lens element parameter related to the lens element shape

A critical point C is a tangent point on a surface of a specific lens element, and the tangent point is tangent to a plane perpendicular to the optical axis and the tangent point cannot be a crossover point on the optical axis. To follow the past, a distance perpendicular to the optical axis between a critical point C51 on the object-side surface of the fifth lens element and the optical axis is HVT51 (instance). A distance per-

pendicular to the optical axis between a critical point C52 on the image-side surface of the fifth lens element and the optical axis is HVT52 (instance). A distance perpendicular to the optical axis between a critical point C61 on the object-side surface of the sixth lens element and the optical axis is HVT61 (instance). A distance perpendicular to the optical axis between a critical point C62 on the image-side surface of the sixth lens element and the optical axis is HVT62 (instance). Distances perpendicular to the optical axis between critical points on the object-side surfaces or the image-side surfaces of other lens elements and the optical axis are denoted in the similar way described above.

The object-side surface of the sixth lens element has one inflection point IF611 which is nearest to the optical axis, and the sinkage value of the inflection point IF611 is denoted by SGI611 (instance). SGI611 is a horizontal shift distance in parallel with the optical axis from an axial point on the object-side surface of the sixth lens element to the inflection point which is nearest to the optical axis on the object-side surface of the sixth lens element. A distance perpendicular to the optical axis between the inflection point IF611 and the optical axis is HIF611 (instance). The image-side surface of the sixth lens element has one inflection point IF621 which is nearest to the optical axis and the sinkage value of the inflection point IF621 is denoted by SGI621 (instance). SGI621 is a horizontal shift distance in parallel with the optical axis from an axial point on the image-side surface of the sixth lens element to the inflection point which is nearest to the optical axis on the image-side surface of the sixth lens element. A distance perpendicular to the optical axis between the inflection point IF621 and the optical axis is HIF621 (instance).

The object-side surface of the sixth lens element has one inflection point IF612 which is the second nearest to the optical axis and the sinkage value of the inflection point IF612 is denoted by SGI612 (instance). SGI612 is a horizontal shift distance in parallel with the optical axis from an axial point on the object-side surface of the sixth lens element to the inflection point which is the second nearest to the optical axis on the object-side surface of the sixth lens element. A distance perpendicular to the optical axis between the inflection point IF612 and the optical axis is HIF612 (instance). The image-side surface of the sixth lens element has one inflection point IF622 which is the second nearest to the optical axis and the sinkage value of the inflection point IF622 is denoted by SGI622 (instance). SGI622 is a horizontal shift distance in parallel with the optical axis from an axial point on the image-side surface of the sixth lens element to the inflection point which is the second nearest to the optical axis on the image-side surface of the sixth lens element. A distance perpendicular to the optical axis between the inflection point IF622 and the optical axis is HIF622 (instance).

The object-side surface of the sixth lens element has one inflection point IF613 which is the third nearest to the optical axis and the sinkage value of the inflection point IF613 is denoted by SGI613 (instance). SGI613 is a horizontal shift distance in parallel with the optical axis from an axial point on the object-side surface of the sixth lens element to the inflection point which is the third nearest to the optical axis on the object-side surface of the sixth lens element. A distance perpendicular to the optical axis between the inflection point IF613 and the optical axis is HIF613 (instance). The image-side surface of the sixth lens element has one inflection point IF623 which is the third nearest to the optical axis and the sinkage value of the inflection point IF623 is denoted by SGI623 (instance). SGI623 is a horizontal shift

distance in parallel with the optical axis from an axial point on the image-side surface of the sixth lens element to the inflection point which is the third nearest to the optical axis on the image-side surface of the sixth lens element. A distance perpendicular to the optical axis between the inflection point IF623 and the optical axis is HIF623 (instance).

The object-side surface of the sixth lens element has one inflection point IF614 which is the fourth nearest to the optical axis and the sinkage value of the inflection point IF614 is denoted by SGI614 (instance). SGI614 is a horizontal shift distance in parallel with the optical axis from an axial point on the object-side surface of the sixth lens element to the inflection point which is the fourth nearest to the optical axis on the object-side surface of the sixth lens element. A distance perpendicular to the optical axis between the inflection point IF614 and the optical axis is HIF614 (instance). The image-side surface of the sixth lens element has one inflection point IF624 which is the fourth nearest to the optical axis and the sinkage value of the inflection point IF624 is denoted by SGI624 (instance). SGI624 is a horizontal shift distance in parallel with the optical axis from an axial point on the image-side surface of the sixth lens element to the inflection point which is the fourth nearest to the optical axis on the image-side surface of the sixth lens element. A distance perpendicular to the optical axis between the inflection point IF624 and the optical axis is HIF624 (instance).

The inflection points on the object-side surfaces or the image-side surfaces of the other lens elements and the distances perpendicular to the optical axis thereof or the sinkage values thereof are denoted in the similar way described above.

The lens element parameter related to an aberration Optical distortion for image formation in the optical image capturing system is denoted by ODT. TV distortion for image formation in the optical image capturing system is denoted by TDT. Further, the range of the aberration offset for the view of image formation may be limited to 50%-100%. An offset of the spherical aberration is denoted by DFS. An offset of the coma aberration is denoted by DFC.

The vertical coordinate axis of the characteristic diagram of modulation transfer function represents a contrast transfer rate (values are from 0 to 1). The horizontal coordinate axis represents a spatial frequency (cycles/mm; lp/mm; line pairs per mm). Theoretically, an ideal image capturing system can 100% show the line contrast of a photographed object. However, the values of the contrast transfer rate at the vertical coordinate axis are smaller than 1 in the actual image capturing system. The transfer rate of its comparison value is less than a vertical axis. In addition, comparing to the central region, it is generally more difficult to achieve a fine degree of recovery in the edge region of image capturing. The contrast transfer rates (MTF values) with spatial frequencies of 55 cycles/m at the optical axis, 0.3 field of view and 0.7 field of view of a visible spectrum on the image plane are respectively denoted by MTFE0, MTFE3 and MTFE7. The contrast transfer rates (MTF values) with spatial frequencies of 110 cycles/m at the optical axis, 0.3 field of view and 0.7 field of view on the image plane are respectively denoted by MTFQ0, MTFQ3 and MTFQ7. The contrast transfer rates (MTF values) with spatial frequencies of 220 cycles/m at the optical axis, 0.3 field of view and 0.7 field of view on the image plane are respectively denoted by MTFH0, MTFH3 and MTFH7. The contrast transfer rates (MTF values) with spatial frequencies of 440 cycles/m at the optical axis, 0.3 field of view and 0.7 field of view on the image plane are respectively denoted by MTF0, MTF3 and

## 5

MTF7. The three fields of view described above are representative to the centre, the internal field of view and the external field of view of the lens elements. Thus, they may be used to evaluate whether the performance of a specific optical image capturing system is excellent. The design of the optical image capturing system of the present invention mainly corresponds to a pixel size in which a sensing device below 1.12 micrometers is included. Therefore, the quarter spatial frequencies, the half spatial frequencies (half frequencies) and the full spatial frequencies (full frequencies) of the characteristic diagram of modulation transfer function respectively are at least 110 cycles/mm, 220 cycles/mm and 440 cycles/mm.

If an optical image capturing system needs to satisfy with the images aimed to infrared spectrum, such as the requirement for night vision with lower light source, the used wavelength may be 850 nm or 800 nm. As the main function is to recognize shape of an object formed in monochrome and shade, the high resolution is unnecessary, and thus, a spatial frequency, which is less than 100 cycles/mm, is used to evaluate the functionality of the optical image capturing system, when the optical image capturing system is applied to the infrared spectrum. When the foregoing wavelength 850 nm is applied to focus on the image plane, the contrast transfer rates (MTF values) with a spatial frequency of 55 cycles/mm at the optical axis, 0.3 field of view and 0.7 field of view on the image plane are respectively denoted by MTF10, MTF13 and MTF17. However, the infrared wavelength of 850 nm or 800 nm may be hugely different to wavelength of the regular visible light wavelength, and thus, it is hard to design an optical image capturing system which has to focus on the visible light and the infrared light (dual-mode) simultaneously while achieve a certain function respectively.

The disclosure provides an optical image capturing system, which is able to focus on the visible light and the infrared light (dual-mode) simultaneously while achieve a certain function respectively, and an object-side surface or an image-side surface of the fourth lens element has inflection points, such that the angle of incidence from each field of view to the fourth lens element can be adjusted effectively and the optical distortion and the TV distortion can be corrected as well. Besides, the surfaces of the fourth lens element may have a better optical path adjusting ability to acquire better imaging quality.

The disclosure provides an optical image capturing system, in order from an object side to an image side, including a first, second, third, fourth, fifth, sixth lens elements and an image plane. The first lens element has refractive power. An object-side surface and an image-side surface of the sixth lens element are aspheric. Focal lengths of the first through sixth lens elements are  $f_1$ ,  $f_2$ ,  $f_3$ ,  $f_4$ ,  $f_5$  and  $f_6$  respectively. A focal length of the optical image capturing system is  $f$ . An entrance pupil diameter of the optical image capturing system is HEP. A distance on an optical axis from an object-side surface of the first lens element to the image plane is HOS. Thicknesses in parallel with an optical axis of the first through sixth lens elements at height  $\frac{1}{2}$  HEP respectively are ETP1, ETP2, ETP3, ETP4, ETP5 and ETP6. A sum of ETP1 to ETP6 described above is SETP. Thicknesses of the first through sixth lens elements on the optical axis respectively are TP1, TP2, TP3, TP4, TP5 and TP6. A sum of TP1 to TP6 described above is STP. The following relations are satisfied:  $1.2 \leq f/HEP \leq 10.0$  and  $0.5 \leq SETP/STP < 1$ .

The disclosure provides another optical image capturing system, in order from an object side to an image side,

## 6

including a first, second, third, fourth, fifth, sixth lens elements and an image plane. The first lens element has positive refractive power, and the position near the optical axis on an object-side surface of the first lens element may be a convex surface. The second lens element has refractive power. The third lens element has refractive power. The fourth lens element has refractive power. The fifth lens element has refractive power. The sixth lens element has refractive power, and an object-side surface and an image-side surface of the sixth lens element are aspheric. At least two lens elements among the first through sixth lens elements respectively have at least one inflection point on at least one surface thereof. At least one of the first through fourth lens elements has positive refractive power. Focal lengths of the first through sixth lens elements are  $f_1$ ,  $f_2$ ,  $f_3$ ,  $f_4$ ,  $f_5$  and  $f_6$  respectively. A focal length of the optical image capturing system is  $f$ . An entrance pupil diameter of the optical image capturing system is HEP. A distance on an optical axis from an object-side surface of the first lens element to the image plane is HOS. A horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to the image plane is ETL. A horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to a coordinate point on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP is EIN. The following relations are satisfied:  $1.2 \leq f/HEP \leq 10.0$ ,  $HOI > 3.0$  mm and  $0.2 \leq EIN/ETL < 1$ .

The disclosure provides another optical image capturing system, in order from an object side to an image side, including a first, second, third, fourth, fifth, sixth lens elements and an image plane. The sixth lens element has at least one inflection point on at least one surface among an object-side surface and an image-side surface, wherein the optical image capturing system consists of six lens elements with refractive power and at least three lens elements among the first through sixth lens elements respectively have at least one inflection point on at least one surface thereof. The first lens element has positive refractive power. The second lens element has negative refractive power. The third lens element has refractive power. The fourth lens element has refractive power. The fifth lens element has refractive power. The sixth lens element has refractive power. Focal lengths of the first through sixth lens elements are  $f_1$ ,  $f_2$ ,  $f_3$ ,  $f_4$ ,  $f_5$  and  $f_6$  respectively. A focal length of the optical image capturing system is  $f$ . An entrance pupil diameter of the optical image capturing system is HEP. A half of maximum view angle of the optical image capturing system is HAF. A distance on an optical axis from an object-side surface of the first lens element to the image plane is HOS. A horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to the image plane is ETL. A horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to a coordinate point on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP is EIN. The following relations are satisfied:  $1.2 \leq f/HEP \leq 3.5$ ,  $0.4 \leq |\tan(HAF)| \leq 6.0$ ,  $HOI > 3.0$  mm and  $0.2 \leq EIN/ETL < 1$ .

A thickness of a single lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) particularly affects the corrected aberration of common area of each field of view of light and the capability of correcting optical path difference between each field of view of light in the scope of  $\frac{1}{2}$  entrance pupil diameter (HEP). The capability of aberration correction is enhanced if the thickness becomes greater, but

the difficulty for manufacturing is also increased at the same time. Therefore, it is necessary to control the thickness of a single lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP), in particular to control the ratio relation (ETP/TP) of the thickness (ETP) of the lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) to the thickness (TP) of the lens element to which the surface belongs on the optical axis. For example, the thickness of the first lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ETP1. The thickness of the second lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ETP2. The thicknesses of other lens elements are denoted in the similar way. A sum of ETP1 to ETP6 described above is SETP. The embodiments of the present invention may satisfy the following relation:  $0.3 \leq \text{SETP}/\text{EIN} < 1$ .

In order to enhance the capability of aberration correction and reduce the difficulty for manufacturing at the same time, it is particularly necessary to control the ratio relation (ETP/TP) of the thickness (ETP) of the lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) to the thickness (TP) of the lens element on the optical axis lens. For example, the thickness of the first lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ETP1. The thickness of the first lens element on the optical axis is TP1. The ratio between both of them is ETP1/TP1. The thickness of the second lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ETP2. The thickness of the second lens element on the optical axis is TP2. The ratio between both of them is ETP2/TP2. The ratio relations of the thicknesses of other lens element in the optical image capturing system at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) to the thicknesses (TP) of the lens elements on the optical axis lens are denoted in the similar way. The embodiments of the present invention may satisfy the following relation:  $0.2 \leq \text{ETP}/\text{TP} \leq 3$ .

A horizontal distance between two adjacent lens elements at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ED. The horizontal distance (ED) described above is in parallel with the optical axis of the optical image capturing system and particularly affects the corrected aberration of common area of each field of view of light and the capability of correcting optical path difference between each field of view of light at the position of  $\frac{1}{2}$  entrance pupil diameter (HEP). The capability of aberration correction may be enhanced if the horizontal distance becomes greater, but the difficulty for manufacturing is also increased and the degree of 'miniaturization' to the length of the optical image capturing system is restricted. Thus, it is essential to control the horizontal distance (ED) between two specific adjacent lens elements at height of  $\frac{1}{2}$  entrance pupil diameter (HEP).

In order to enhance the capability of aberration correction and reduce the difficulty for 'miniaturization' to the length of the optical image capturing system at the same time, it is particularly necessary to control the ratio relation (ED/IN) of the horizontal distance (ED) between the two adjacent lens elements at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) to the horizontal distance (IN) between the two adjacent lens elements on the optical axis. For example, the horizontal distance between the first lens element and the second lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ED12. The horizontal distance between the first lens element and the second lens element on the optical axis is IN12. The ratio between both of them is ED12/IN12. The horizontal distance between the second lens element and the third lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ED23. The horizontal distance between the second lens element and the third lens element on the

optical axis is IN23. The ratio between both of them is ED23/IN23. The ratio relations of the horizontal distances between other two adjacent lens elements in the optical image capturing system at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) to the horizontal distances between the two adjacent lens elements on the optical axis are denoted in the similar way.

A horizontal distance in parallel with the optical axis from a coordinate point on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP to the image plane is EBL. A horizontal distance in parallel with the optical axis from an axial point on the image-side surface of the sixth lens element to the image plane is BL. The embodiments of the present invention enhance the capability of aberration correction and reserve space for accommodating other optical elements. The following relation may be satisfied:  $0.2 \leq \text{EBL}/\text{BL} < 1.1$ . The optical image capturing system may further include a light filtration element. The light filtration element is located between the sixth lens element and the image plane. A distance in parallel with the optical axis from a coordinate point on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP to the light filtration element is EIR. A distance in parallel with the optical axis from an axial point on the image-side surface of the sixth lens element to the light filtration element is PIR. The embodiments of the present invention may satisfy the following relation:  $0.1 \leq \text{EIR}/\text{PIR} \leq 1.1$ .

The height of optical system (HOS) may be reduced to achieve the minimization of the optical image capturing system when the absolute value of  $f_1$  is larger than  $f_6$  ( $|f_1| > f_6$ ).

When  $|f_2| + |f_3| + |f_4| + |f_5|$  and  $|f_1| + |f_6|$  are satisfied with above relations, at least one of the second through fifth lens elements may have weak positive refractive power or weak negative refractive power. The weak refractive power indicates that an absolute value of the focal length of a specific lens element is greater than 10. When at least one of the second through fifth lens elements has the weak positive refractive power, the positive refractive power of the first lens element can be shared, such that the unnecessary aberration will not appear too early. On the contrary, when at least one of the second through fifth lens elements has the weak negative refractive power, the aberration of the optical image capturing system can be corrected and fine tuned.

The sixth lens element may have negative refractive power and a concave image-side surface. Hereby, the back focal length is reduced for keeping the miniaturization, to miniaturize the lens element effectively. In addition, at least one of the object-side surface and the image-side surface of the sixth lens element may have at least one inflection point, such that the angle of incident with incoming light from an off-axis field of view can be suppressed effectively and the aberration in the off-axis field of view can be corrected further.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The detailed structure, operating principle and effects of the present disclosure will now be described in more details hereinafter with reference to the accompanying drawings that show various embodiments of the present disclosure as follows.

FIG. 1A is a schematic view of the optical image capturing system according to the first embodiment of the present application.

FIG. 1B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion grid of the

optical image capturing system in the order from left to right according to the first embodiment of the present application.

FIG. 1C is a characteristic diagram of modulation transfer of a visible light according to the first embodiment of the present application.

FIG. 1D is a characteristic diagram of modulation transfer of infrared rays according to the first embodiment of the present application.

FIG. 2A is a schematic view of the optical image capturing system according to the second embodiment of the present application.

FIG. 2B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion grid of the optical image capturing system in the order from left to right according to the second embodiment of the present application.

FIG. 2C is a characteristic diagram of modulation transfer of a visible light according to the second embodiment of the present application.

FIG. 2D is a characteristic diagram of modulation transfer of infrared rays according to the second embodiment of the present application.

FIG. 3A is a schematic view of the optical image capturing system according to the third embodiment of the present application.

FIG. 3B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion grid of the optical image capturing system in the order from left to right according to the third embodiment of the present application.

FIG. 3C is a characteristic diagram of modulation transfer of a visible light according to the third embodiment of the present application.

FIG. 3D is a characteristic diagram of modulation transfer of infrared rays according to the third embodiment of the present application.

FIG. 4A is a schematic view of the optical image capturing system according to the fourth embodiment of the present application.

FIG. 4B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion grid of the optical image capturing system in the order from left to right according to the fourth embodiment of the present application.

FIG. 4C is a characteristic diagram of modulation transfer of a visible light according to the fourth embodiment of the present application.

FIG. 4D is a characteristic diagram of modulation transfer of infrared rays according to the fourth embodiment of the present application.

FIG. 5A is a schematic view of the optical image capturing system according to the fifth embodiment of the present application.

FIG. 5B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion grid of the optical image capturing system in the order from left to right according to the fifth embodiment of the present application.

FIG. 5C is a characteristic diagram of modulation transfer of a visible light according to the fifth embodiment of the present application.

FIG. 5D is a characteristic diagram of modulation transfer of infrared rays according to the fifth embodiment of the present application.

FIG. 6A is a schematic view of the optical image capturing system according to the sixth embodiment of the present application.

FIG. 6B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion grid of the optical image capturing system in the order from left to right according to the sixth embodiment of the present application.

FIG. 6C is a characteristic diagram of modulation transfer of a visible light according to the sixth embodiment of the present application.

FIG. 6D is a characteristic diagram of modulation transfer of infrared rays according to the sixth embodiment of the present application.

FIG. 7A is a schematic view of the optical image capturing system according to the seventh embodiment of the present application.

FIG. 7B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion grid of the optical image capturing system in the order from left to right according to the seventh embodiment of the present application.

FIG. 7C is a characteristic diagram of modulation transfer of a visible light according to the seventh embodiment of the present application.

FIG. 7D is a characteristic diagram of modulation transfer of infrared rays according to the seventh embodiment of the present application.

FIG. 8A is a schematic view of the optical image capturing system according to the eighth embodiment of the present application.

FIG. 8B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion grid of the optical image capturing system in the order from left to right according to the eighth embodiment of the present application.

FIG. 8C is a characteristic diagram of modulation transfer of a visible light according to the eighth embodiment of the present application.

FIG. 8D is a characteristic diagram of modulation transfer of infrared rays according to the eighth embodiment of the present application.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the exemplary embodiments of the present disclosure, examples of which are illustrated in the accompanying drawings. Therefore, it is to be understood that the foregoing is illustrative of exemplary embodiments and is not to be construed as limited to the specific embodiments disclosed, and that modifications to the disclosed exemplary embodiments, as well as other exemplary embodiments, are intended to be included within the scope of the appended claims. These embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the inventive concept to those skilled in the art. The relative proportions and ratios of elements in the drawings may be exaggerated or diminished in size for the sake of clarity and convenience in the drawings, and such arbitrary proportions are only illustrative and not limiting in any way. The same reference numbers are used in the drawings and the description to refer to the same or like parts.

It will be understood that, although the terms 'first', 'second', 'third', etc., may be used herein to describe various elements, these elements should not be limited by these terms. The terms are used only for the purpose of distinguishing one component from another component. Thus, a first element discussed below could be termed a

second element without departing from the teachings of embodiments. As used herein, the term “or” includes any and all combinations of one or more of the associated listed items.

An optical image capturing system, in order from an object side to an image side, includes a first, second, third, fourth, fifth and sixth lens elements with refractive power and an image plane. The optical image capturing system may further include an image sensing device which is disposed on an image plane.

The optical image capturing system may use three sets of wavelengths which are 486.1 nm, 587.5 nm and 656.2 nm, respectively, wherein 587.5 nm is served as the primary reference wavelength and a reference wavelength for retrieving technical features. The optical image capturing system may also use five sets of wavelengths which are 470 nm, 510 nm, 555 nm, 610 nm and 650 nm, respectively, wherein 555 nm is served as the primary reference wavelength and a reference wavelength for retrieving technical features.

A ratio of the focal length  $f$  of the optical image capturing system to a focal length  $f_p$  of each of lens elements with positive refractive power is PPR. A ratio of the focal length  $f$  of the optical image capturing system to a focal length  $f_n$  of each of lens elements with negative refractive power is NPR. A sum of the PPR of all lens elements with positive refractive power is  $\Sigma PPR$ . A sum of the NPR of all lens elements with negative refractive powers is  $\Sigma NPR$ . It is beneficial to control the total refractive power and the total length of the optical image capturing system when following conditions are satisfied:  $0.5 \leq \Sigma PPR / |\Sigma NPR| \leq 15$ . Preferably, the following relation may be satisfied:  $1 \leq \Sigma PPR / |\Sigma NPR| \leq 3.0$ .

The optical image capturing system may further include an image sensing device which is disposed on an image plane. Half of a diagonal of an effective detection field of the image sensing device (imaging height or the maximum image height of the optical image capturing system) is HOI. A distance on the optical axis from the object-side surface of the first lens element to the image plane is HOS. The following relations are satisfied:  $HOS/HOI \leq 10$  and  $0.5 \leq HOS/f \leq 10$ . Preferably, the following relations may be satisfied:  $1 \leq HOS-HOI \leq S$  and  $1 \leq HOS/f \leq 7$ . Hereby, the miniaturization of the optical image capturing system can be maintained effectively, so as to be carried by lightweight portable electronic devices.

In addition, in the optical image capturing system of the disclosure, according to different requirements, at least one aperture stop may be arranged for reducing stray light and improving the imaging quality.

In the optical image capturing system of the disclosure, the aperture stop may be a front or middle aperture. The front aperture is the aperture stop between a photographed object and the first lens element. The middle aperture is the aperture stop between the first lens element and the image plane. If the aperture stop is the front aperture, a longer distance between the exit pupil and the image plane of the optical image capturing system can be formed, such that more optical elements can be disposed in the optical image capturing system and the efficiency of receiving images of the image sensing device can be raised. If the aperture stop is the middle aperture, the view angle of the optical image capturing system can be expended, such that the optical image capturing system has the same advantage that is owned by wide angle cameras. A distance from the aperture stop to the image plane is  $InS$ . The following relation is satisfied:  $0.2 \leq InS/HOS \leq 1.1$ . Hereby, features of maintaining

the minimization for the optical image capturing system and having wide-angle are available simultaneously.

In the optical image capturing system of the disclosure, a distance from the object-side surface of the first lens element to the image-side surface of the sixth lens element is  $InTL$ . A sum of central thicknesses of all lens elements with refractive power on the optical axis is  $\Sigma TP$ . The following relation is satisfied:  $0.1 \leq \Sigma TP / InTL \leq 0.9$ . Hereby, contrast ratio for the image formation in the optical image capturing system and defect-free rate for manufacturing the lens element can be given consideration simultaneously, and a proper back focal length is provided to dispose other optical components in the optical image capturing system.

A curvature radius of the object-side surface of the first lens element is  $R1$ . A curvature radius of the image-side surface of the first lens element is  $R2$ . The following relation is satisfied:  $0.001 \leq |R1/R2| \leq 20$ . Hereby, the first lens element may have proper strength of the positive refractive power, so as to avoid the longitudinal spherical aberration to increase too fast. Preferably, the following relation may be satisfied:  $0.01 \leq |R1/R2| < 10$ .

A curvature radius of the object-side surface of the sixth lens element is  $R11$ . A curvature radius of the image-side surface of the sixth lens element is  $R12$ . The following relation is satisfied:  $-7 < (R11-R12)/(R11+R12) < 50$ . Hereby, the astigmatism generated by the optical image capturing system can be corrected beneficially.

A distance between the first lens element and the second lens element on the optical axis is  $IN12$ . The following relation is satisfied:  $IN12/f \leq 3.0$ . Hereby, the chromatic aberration of the lens elements can be improved, such that the performance can be increased.

A distance between the fifth lens element and the sixth lens element on the optical axis is  $IN56$ . The following relation is satisfied:  $IN56/f \leq 0.8$ . Hereby, the chromatic aberration of the lens elements can be improved, such that the performance can be increased.

Central thicknesses of the first lens element and the second lens element on the optical axis are  $TP1$  and  $TP2$ , respectively. The following relation is satisfied:  $0.1 \leq (TP1+IN12)/TP2 \leq 10$ . Hereby, the sensitivity produced by the optical image capturing system can be controlled, and the performance can be increased.

Central thicknesses of the fifth lens element and the sixth lens element on the optical axis are  $TP5$  and  $TP6$ , respectively, and a distance between the aforementioned two lens elements on the optical axis is  $IN56$ . The following relation is satisfied:  $0.1 \leq (TP6+IN56)/TP5 \leq 10$ . Hereby, the sensitivity produced by the optical image capturing system can be controlled and the total height of the optical image capturing system can be reduced.

Central thicknesses of the second lens element, the third lens element and the fourth lens element on the optical axis are  $TP2$ ,  $TP3$  and  $TP4$ , respectively. A distance between the second lens element and the third lens element on the optical axis is  $IN23$ . A distance between the third lens element and the fourth lens element on the optical axis is  $IN34$ . A distance between the fourth lens element and the fifth lens element on the optical axis is  $IN45$ . A distance on the optical axis from the object-side surface of the first lens element to the image-side surface of the sixth lens element is  $InTL$ . The following relation is satisfied:  $0.1 \leq TP4/(IN34+TP4+IN45) < 1$ . Hereby, the aberration generated by the process of moving the incident light can be adjusted slightly layer upon layer, and the total height of the optical image capturing system can be reduced.



In the optical image capturing system of the disclosure, a distance perpendicular to the optical axis between a critical point C61 on the object-side surface of the sixth lens element and the optical axis is HVT61. A distance perpendicular to the optical axis between a critical point C62 on the image-side surface of the sixth lens element and the optical axis is HVT62. A horizontal displacement distance on the optical axis from an axial point on the object-side surface of the sixth lens element to the critical point C61 is SGC61. A horizontal displacement distance on the optical axis from an axial point on the image-side surface of the sixth lens element to the critical point C62 is SGC62. The following relations may be satisfied:  $0 \text{ mm} \leq \text{HVT61} \leq 3 \text{ mm}$ ,  $0 \text{ mm} < \text{HVT62} \leq 6 \text{ mm}$ ,  $0 \leq \text{HVT61}/\text{HVT62}$ ,  $0 \text{ mm} \leq |\text{SGC61}| \leq 0.5 \text{ mm}$ ,  $0 \text{ mm} < |\text{SGC62}| \leq 2 \text{ mm}$  and  $0 < |\text{SGC62}|/(|\text{SGC62}|+\text{TP6}) \leq 0.9$ . Hereby, the aberration in the off-axis view field can be corrected.

The optical image capturing system of the disclosure satisfies the following relation:  $0.2 \leq \text{HVT62}/\text{HOI} \leq 0.9$ . Preferably, the following relation may be satisfied:  $0.3 \leq \text{HVT62}/\text{HOI} \leq 0.8$ . Hereby, the aberration of surrounding view field can be corrected.

The optical image capturing system of the disclosure satisfies the following relation:  $0 \leq \text{HVT62}/\text{HOS} \leq 0.5$ . Preferably, the following relation may be satisfied:  $0.2 \leq \text{HVT62}/\text{HOS} \leq 0.45$ . Hereby, the aberration of surrounding view field can be corrected.

In the optical image capturing system of the disclosure, a distance in parallel with an optical axis from an inflection point on the object-side surface of the sixth lens element which is nearest to the optical axis to an axial point on the object-side surface of the sixth lens element is denoted by SGI611. A distance in parallel with an optical axis from an inflection point on the image-side surface of the sixth lens element which is nearest to the optical axis to an axial point on the image-side surface of the sixth lens element is denoted by SGI621. The following relations are satisfied:  $0 < \text{SGI611}/(\text{SGI611}+\text{TP6}) \leq 0.9$  and  $0 < \text{SGI621}/(\text{SGI621}+\text{TP6}) \leq 0.9$ . Preferably, the following relations may be satisfied:  $0.1 \leq \text{SGI611}/(\text{SGI611}+\text{TP6}) \leq 0.6$  and  $0.1 \leq \text{SGI621}/(\text{SGI621}+\text{TP6}) \leq 0.6$ .

A distance in parallel with the optical axis from the inflection point on the object-side surface of the sixth lens element which is the second nearest to the optical axis to an axial point on the object-side surface of the sixth lens element is denoted by SGI612. A distance in parallel with an optical axis from an inflection point on the image-side surface of the sixth lens element which is the second nearest to the optical axis to an axial point on the image-side surface of the sixth lens element is denoted by SGI622. The following relations are satisfied:  $0 < \text{SGI612}/(\text{SGI612}+\text{TP6}) \leq 0.9$  and  $0 < \text{SGI622}/(\text{SGI622}+\text{TP6}) \leq 0.9$ . Preferably, the following relations may be satisfied:  $0.1 \leq \text{SGI612}/(\text{SGI612}+\text{TP6}) \leq 0.6$  and  $0.1 \leq \text{SGI622}/(\text{SGI622}+\text{TP6}) \leq 0.6$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens element which is nearest to the optical axis and the optical axis is denoted by HIF611. A distance perpendicular to the optical axis between an inflection point on the image-side surface of the sixth lens element which is nearest to the optical axis and an axial point on the image-side surface of the sixth lens element is denoted by HIF621. The following relations are satisfied:  $0.001 \text{ mm} \leq |\text{HIF611}| \leq 5 \text{ mm}$  and  $0.001 \text{ mm} \leq |\text{HIF621}| \leq 5 \text{ mm}$ . Preferably, the following relations may be satisfied:  $0.1 \text{ mm} \leq |\text{HIF611}| \leq 3.5 \text{ mm}$  and  $1.5 \text{ mm} \leq |\text{HIF621}| \leq 3.5 \text{ mm}$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens element which is the second nearest to the optical axis and the optical axis is denoted by HIF612. A distance perpendicular to the optical axis between an axial point on the image-side surface of the sixth lens element and an inflection point on the image-side surface of the sixth lens element which is the second nearest to the optical axis is denoted by HIF622. The following relations are satisfied:  $0.001 \text{ mm} \leq |\text{HIF612}| \leq 5 \text{ mm}$  and  $0.001 \text{ mm} \leq |\text{HIF622}| \leq 5 \text{ mm}$ . Preferably, the following relations may be satisfied:  $0.1 \text{ mm} \leq |\text{HIF622}| \leq 3.5 \text{ mm}$  and  $0.1 \text{ mm} \leq |\text{HIF612}| \leq 3.5 \text{ mm}$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens element which is the third nearest to the optical axis and the optical axis is denoted by HIF613. A distance perpendicular to the optical axis between an axial point on the image-side surface of the sixth lens element and an inflection point on the image-side surface of the sixth lens element which is the third nearest to the optical axis is denoted by HIF623. The following relations are satisfied:  $0.001 \text{ mm} \leq |\text{HIF613}| \leq 5 \text{ mm}$  and  $0.001 \text{ mm} \leq |\text{HIF623}| \leq 0.5 \text{ mm}$ . Preferably, the following relations may be satisfied:  $0.1 \text{ mm} \leq |\text{HIF623}| \leq 0.3.5 \text{ mm}$  and  $0.1 \text{ mm} \leq |\text{HIF613}| \leq 3.5 \text{ mm}$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens element which is the fourth nearest to the optical axis and the optical axis is denoted by HIF614. A distance perpendicular to the optical axis between an axial point on the image-side surface of the sixth lens element and an inflection point on the image-side surface of the sixth lens element which is the fourth nearest to the optical axis is denoted by HIF624. The following relations are satisfied:  $0.001 \text{ mm} \leq |\text{HIF614}| \leq 5 \text{ mm}$  and  $0.001 \text{ mm} \leq |\text{HIF624}| \leq 5 \text{ mm}$ . Preferably, the following relations may be satisfied:  $0.1 \text{ mm} \leq |\text{HIF624}| \leq 3.5 \text{ mm}$  and  $0.1 \text{ mm} \leq |\text{HIF614}| \leq 3.5 \text{ mm}$ .

In one embodiment of the optical image capturing system of the present disclosure, the chromatic aberration of the optical image capturing system can be corrected by alternatively arranging the lens elements with large Abbe number and small Abbe number.

The above Aspheric formula is:

$$z = ch^2/[1+[1-(k+1)c^2h^2]^{0.5}] + A4h^4 + A6h^6 + A8h^8 + A10h^{10} + A12h^{12} + A14h^{14} + A16h^{16} + A18h^{18} + A20h^{20} + \quad (1),$$

where  $z$  is a position value of the position along the optical axis and at the height  $h$  which reference to the surface apex;  $k$  is the conic coefficient,  $c$  is the reciprocal of curvature radius, and  $A4$ ,  $A6$ ,  $A8$ ,  $A10$ ,  $A12$ ,  $A14$ ,  $A16$ ,  $A18$ , and  $A20$  are high order aspheric coefficients.

The optical image capturing system provided by the disclosure, the lens elements may be made of glass or plastic material. If plastic material is adopted to produce the lens elements, the cost of manufacturing will be lowered effectively. If lens elements are made of glass, the heat effect can be controlled and the designed space arranged for the refractive power of the optical image capturing system can be increased. Besides, the object-side surface and the image-side surface of the first through sixth lens elements may be aspheric, so as to obtain more control variables. Comparing with the usage of traditional lens element made by glass, the number of lens elements used can be reduced and the aberration can be eliminated. Thus, the total height of the optical image capturing system can be reduced effectively.

In addition, in the optical image capturing system provided by the disclosure, if the lens element has a convex

surface, the surface of the lens element adjacent to the optical axis is convex in principle. If the lens element has a concave surface, the surface of the lens element adjacent to the optical axis is concave in principle.

The optical image capturing system of the disclosure can be adapted to the optical image capturing system with automatic focus if required. With the features of a good aberration correction and a high quality of image formation, the optical image capturing system can be used in various application fields.

The optical image capturing system of the disclosure can include a driving module according to the actual requirements. The driving module may be coupled with the lens elements to enable the lens elements producing displacement. The driving module may be the voice coil motor (VCM) which is applied to move the lens to focus, or may be the optical image stabilization (OIS) which is applied to reduce the distortion frequency owing to the vibration of the lens while shooting.

At least one of the first, second, third, fourth, fifth and sixth lens elements of the optical image capturing system of the disclosure may further be designed as a light filtration element with a wavelength of less than 500 nm according to the actual requirement. The light filtration element may be made by coating at least one surface of the specific lens element characterized of the filter function, and alternatively, may be made by the lens element per se made of the material which is capable of filtering short wavelength.

According to the above embodiments, the specific embodiments with figures are presented in detail as below.

#### The First Embodiment (Embodiment 1)

Please refer to FIG. 1A and FIG. 1B. FIG. 1A is a schematic view of the optical image capturing system according to the first embodiment of the present application. FIG. 1B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion curve of the optical image capturing system in the order from left to right according to the first embodiment of the present application, FIG. 1C is a characteristic diagram of modulation transfer of a visible light according to the first embodiment of the present application, and FIG. 1D is a characteristic diagram of modulation transfer of infrared rays according to the first embodiment of the present application. As shown in FIG. 1A, in order from an object side to an image side, the optical image capturing system includes a first lens element **110**, an aperture stop **100**, a second lens element **120**, a third lens element **130**, a fourth lens element **140**, a fifth lens element **150**, a sixth lens element **160**, an IR-bandstop filter **180**, an image plane **190**, and an image sensing device **192**.

The first lens element **110** has negative refractive power and it is made of plastic material. The first lens element **110** has a concave object-side surface **112** and a concave image-side surface **114**, and both of the object-side surface **112** and the image-side surface **114** are aspheric. The object-side surface **112** has two inflection points. The thickness of the first lens element on the optical axis is TP1. The thickness of the first lens element at height of 1:2 entrance pupil diameter (HEP) is denoted by ETP1.

A distance in parallel with an optical axis from an inflection point on the object-side surface of the first lens element which is nearest to the optical axis to an axial point on the object-side surface of the first lens element is denoted by SGI111. A distance in parallel with an optical axis from an inflection point on the image-side surface of the first lens element which is nearest to the optical axis to an axial point

on the image-side surface of the first lens element is denoted by SGI121. The following relations are satisfied:  $SGI111 = -0.0031$  mm and  $|SGI111|/(|SGI111|+TP1) = 0.0016$ .

A distance in parallel with an optical axis from an inflection point on the object-side surface of the first lens element which is the second nearest to the optical axis to an axial point on the object-side surface of the first lens element is denoted by SGI112. A distance in parallel with an optical axis from an inflection point on the image-side surface of the first lens element which is the second nearest to the optical axis to an axial point on the image-side surface of the first lens element is denoted by SGI122. The following relations are satisfied:  $SGI112 = 1.3178$  mm and  $|SGI112|/(|SGI112|+TP1) = 0.4052$ .

A distance perpendicular to the optical axis from the inflection point on the object-side surface of the first lens element which is nearest to the optical axis to an axial point on the object-side surface of the first lens element is denoted by HIF111. A distance perpendicular to the optical axis from the inflection point on the image-side surface of the first lens element which is nearest to the optical axis to an axial point on the image-side surface of the first lens element is denoted by HIF121. The following relations are satisfied:  $HIF111 = 0.5557$  mm and  $HIF111/HOI = 0.111$ .

A distance perpendicular to the optical axis from the inflection point on the object-side surface of the first lens element which is the second nearest to the optical axis to an axial point on the object-side surface of the first lens element is denoted by HIF112. A distance perpendicular to the optical axis from the inflection point on the image-side surface of the first lens element which is the second nearest to the optical axis to an axial point on the image-side surface of the first lens element is denoted by HIF122. The following relations are satisfied:  $HIF112 = 5.3732$  mm and  $HIF112/HOI = 1.0746$ .

The second lens element **120** has positive refractive power and it is made of plastic material. The second lens element **120** has a convex object-side surface **122** and a convex image-side surface **124**, and both of the object-side surface **122** and the image-side surface **124** are aspheric. The object-side surface **122** has an inflection point. The thickness of the second lens element on the optical axis is TP2. The thickness of the second lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ETP2.

A distance in parallel with an optical axis from an inflection point on the object-side surface of the second lens element which is nearest to the optical axis to an axial point on the object-side surface of the second lens element is denoted by SGI211. A distance in parallel with an optical axis from an inflection point on the image-side surface of the second lens element which is nearest to the optical axis to an axial point on the image-side surface of the second lens element is denoted by SGI221. The following relations are satisfied:  $SGI211 = 0.1069$  mm,  $|SGI211|/(|SGI211|+TP2) = 0.0412$ ,  $SGI221 = 0$  mm and  $|SGI221|/(|SGI221|+TP2) = 0$ .

A distance perpendicular to the optical axis from the inflection point on the object-side surface of the second lens element which is nearest to the optical axis to an axial point on the object-side surface of the second lens element is denoted by HIF211. A distance perpendicular to the optical axis from the inflection point on the image-side surface of the second lens element which is nearest to the optical axis to an axial point on the image-side surface of the second lens element is denoted by HIF221. The following relations are satisfied:  $HIF211 = 1.1264$  mm,  $HIF211/HOI = 0.2253$ ,  $HIF221 = 0$  mm and  $HIF221/HOI = 0$ .

The third lens element **130** has negative refractive power and it is made of plastic material. The third lens element **130** has a concave object-side surface **132** and a convex image-side surface **134**, and both of the object-side surface **132** and the image-side surface **134** are aspheric. The object-side surface **132** and the image-side surface **134** both have an inflection point. The thickness of the third lens element on the optical axis is TP3. The thickness of the third lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ETP3.

A distance in parallel with an optical axis from an inflection point on the object-side surface of the third lens element which is nearest to the optical axis to an axial point on the object-side surface of the third lens element is denoted by SGI311. A distance in parallel with an optical axis from an inflection point on the image-side surface of the third lens element which is nearest to the optical axis to an axial point on the image-side surface of the third lens element is denoted by SGI321. The following relations are satisfied:  $SGI311 = -0.3041$  mm,  $|SGI311|/(|SGI311|+TP3) = 0.4445$ ,  $SGI321 = -0.1172$  mm and  $|SGI321|/(|SGI321|+TP3) = 0.2357$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the third lens element which is nearest to the optical axis and the optical axis is denoted by HIF311. A distance perpendicular to the optical axis from the inflection point on the image-side surface of the third lens element which is nearest to the optical axis to an axial point on the image-side surface of the third lens element is denoted by HIF321. The following relations are satisfied:  $HIF311 = 1.5907$  mm,  $HIF311/HOI = 0.3181$ ,  $HIF321 = 1.3380$  mm and  $HIF321/HOI = 0.2676$ .

The fourth lens element **140** has positive refractive power and it is made of plastic material. The fourth lens element **140** has a convex object-side surface **142** and a concave image-side surface **144**, and both of the object-side surface **142** and the image-side surface **144** are aspheric. The object-side surface **142** has two inflection points and the image-side surface **144** has an inflection point. The thickness of the fourth lens element on the optical axis is TP4. The thickness of the fourth lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ETP4.

A distance in parallel with an optical axis from an inflection point on the object-side surface of the fourth lens element which is nearest to the optical axis to an axial point on the object-side surface of the fourth lens element is denoted by SGI411. A distance in parallel with an optical axis from an inflection point on the image-side surface of the fourth lens element which is nearest to the optical axis to an axial point on the image-side surface of the fourth lens element is denoted by SGI421. The following relations are satisfied:  $SGI411 = 0.0070$  mm,  $|SGI411|/(|SGI411|+TP4) = 0.0056$ ,  $SGI421 = 0.0006$  mm and  $|SGI421|/(|SGI421|+TP4) = 0.0005$ .

A distance in parallel with an optical axis from an inflection point on the object-side surface of the fourth lens element which is the second nearest to the optical axis to an axial point on the object-side surface of the fourth lens element is denoted by SGI412. A distance in parallel with an optical axis from an inflection point on the image-side surface of the fourth lens element which is the second nearest to the optical axis to an axial point on the image-side surface of the fourth lens element is denoted by SGI422. The following relations are satisfied:  $SGI412 = -0.2078$  mm and  $|SGI412|/(|SGI412|+TP4) = 0.1439$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the fourth lens

element which is nearest to the optical axis and the optical axis is denoted by HIF411. A distance perpendicular to the optical axis between the inflection point on the image-side surface of the fourth lens element which is nearest to the optical axis and the optical axis is denoted by HIF421. The following relations are satisfied:  $HIF411 = 0.4706$  mm,  $HIF411/HOI = 0.0941$ ,  $HIF421 = 0.1721$  mm and  $HIF421/HOI = 0.0344$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the fourth lens element which is the second nearest to the optical axis and the optical axis is denoted by HIF412. A distance perpendicular to the optical axis between the inflection point on the image-side surface of the fourth lens element which is the second nearest to the optical axis and the optical axis is denoted by HIF422. The following relations are satisfied:  $HIF412 = 2.0421$  mm and  $HIF412/HOI = 0.4084$ .

The fifth lens element **150** has positive refractive power and it is made of plastic material. The fifth lens element **150** has a convex object-side surface **152** and a convex image-side surface **154**, and both of the object-side surface **152** and the image-side surface **154** are aspheric. The object-side surface **152** has two inflection points and the image-side surface **154** has an inflection point. The thickness of the fifth lens element on the optical axis is TP5. The thickness of the fifth lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ETP5.

A distance in parallel with an optical axis from an inflection point on the object-side surface of the fifth lens element which is nearest to the optical axis to an axial point on the object-side surface of the fifth lens element is denoted by SGI511. A distance in parallel with an optical axis from an inflection point on the image-side surface of the fifth lens element which is nearest to the optical axis to an axial point on the image-side surface of the fifth lens element is denoted by SGI521. The following relations are satisfied:  $SGI511 = 0.00364$  mm,  $|SGI511|/(|SGI511|+TP5) = 0.00338$ ,  $SGI521 = -0.63365$  mm and  $|SGI521|/(|SGI521|+TP5) = 0.37154$ .

A distance in parallel with an optical axis from an inflection point on the object-side surface of the fifth lens element which is the second nearest to the optical axis to an axial point on the object-side surface of the fifth lens element is denoted by SGI512. A distance in parallel with an optical axis from an inflection point on the image-side surface of the fifth lens element which is the second nearest to the optical axis to an axial point on the image-side surface of the fifth lens element is denoted by SGI522. The following relations are satisfied:  $SGI512 = -0.32032$  mm and  $|SGI512|/(|SGI512|+TP5) = 0.23009$ .

A distance in parallel with an optical axis from an inflection point on the object-side surface of the fifth lens element which is the third nearest to the optical axis to an axial point on the object-side surface of the fifth lens element is denoted by SGI513. A distance in parallel with an optical axis from an inflection point on the image-side surface of the fifth lens element which is the third nearest to the optical axis to an axial point on the image-side surface of the fifth lens element is denoted by SGI523. The following relations are satisfied:  $SGI513 = 0$  mm,  $|SGI513|/(|SGI513|+TP5) = 0$ ,  $SGI523 = 0$  mm and  $|SGI523|/(|SGI523|+TP5) = 0$ .

A distance in parallel with an optical axis from an inflection point on the object-side surface of the fifth lens element which is the fourth nearest to the optical axis to an axial point on the object-side surface of the fifth lens element is denoted by SGI514. A distance in parallel with an optical axis from an inflection point on the image-side surface of the

fifth lens element which is the fourth nearest to the optical axis to an axial point on the image-side surface of the fifth lens element is denoted by SGI524. The following relations are satisfied:  $SGI514=0$  mm,  $|SGI514|/(|SGI514|+TP5)=0$ ,  $SGI524=0$  mm and  $|SGI524|/(|SGI524|+TP5)=0$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the fifth lens element which is nearest to the optical axis and the optical axis is denoted by HIF511. A distance perpendicular to the optical axis between the inflection point on the image-side surface of the fifth lens element which is nearest to the optical axis and the optical axis is denoted by HIF521. The following relations are satisfied:  $HIF511=0.28212$  mm,  $HIF511/HOI=0.05642$ ,  $HIF521=2.13850$  mm and  $HIF521/HOI=0.42770$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the fifth lens element which is the second nearest to the optical axis and the optical axis is denoted by HIF512. A distance perpendicular to the optical axis between the inflection point on the image-side surface of the fifth lens element which is the second nearest to the optical axis and the optical axis is denoted by HIF522. The following relations are satisfied:  $HIF512=2.51384$  mm and  $HIF512/HOI=0.50277$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the fifth lens element which is the third nearest to the optical axis and the optical axis is denoted by HIF513. A distance perpendicular to the optical axis between the inflection point on the image-side surface of the fifth lens element which is the third nearest to the optical axis and the optical axis is denoted by HIF523. The following relations are satisfied:  $HIF513=0$  mm,  $HIF513/HOI=0$ ,  $HIF523=0$  mm and  $HIF523/HOI=0$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the fifth lens element which is the fourth nearest to the optical axis and the optical axis is denoted by HIF514. A distance perpendicular to the optical axis between the inflection point on the image-side surface of the fifth lens element which is the fourth nearest to the optical axis and the optical axis is denoted by HIF524. The following relations are satisfied:  $HIF514=0$  mm,  $HIF514/HOI=0$ ,  $HIF524=0$  mm and  $HIF524/HOI=0$ .

The sixth lens element **160** has negative refractive power and it is made of plastic material. The sixth lens element **160** has a concave object-side surface **162** and a concave image-side surface **164**, and the object-side surface **162** has two inflection points and the image-side surface **164** has an inflection point. Hereby, the angle of incident of each view field on the sixth lens element can be effectively adjusted and the spherical aberration can thus be improved. The thickness of the sixth lens element on the optical axis is TP6. The thickness of the sixth lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) is denoted by ETP6.

A distance in parallel with an optical axis from an inflection point on the object-side surface of the sixth lens element which is nearest to the optical axis to an axial point on the object-side surface of the sixth lens element is denoted by SGI611. A distance in parallel with an optical axis from an inflection point on the image-side surface of the sixth lens element which is nearest to the optical axis to an axial point on the image-side surface of the sixth lens element is denoted by SGI621. The following relations are satisfied:  $SGI611=-0.38558$  mm,  $|SGI611|/(|SGI611|+TP6)=0.27212$ ,  $SGI621=0.12386$  mm and  $|SGI621|/(|SGI621|+TP6)=0.10722$ .

A distance in parallel with an optical axis from an inflection point on the object-side surface of the sixth lens element which is the second nearest to the optical axis to an axial point on the object-side surface of the sixth lens element is denoted by SGI612. A distance in parallel with an optical axis from an inflection point on the image-side surface of the sixth lens element which is the second nearest to the optical axis to an axial point on the image-side surface of the sixth lens element is denoted by SGI621. The following relations are satisfied:  $SGI612=-0.47400$  mm,  $|SGI612|/(|SGI612|+TP6)=0.31488$ ,  $SGI622=0$  mm and  $|SGI622|/(|SGI622|+TP6)=0$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens element which is nearest to the optical axis and the optical axis is denoted by HIF611. A distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens element which is nearest to the optical axis and the optical axis is denoted by HIF621. The following relations are satisfied:  $HIF611=2.24283$  mm,  $HIF611/HOI=0.44857$ ,  $HIF621=1.07376$  mm and  $HIF621/HOI=0.21475$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens element which is the second nearest to the optical axis and the optical axis is denoted by HIF612. A distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens element which is the second nearest to the optical axis and the optical axis is denoted by HIF622. The following relations are satisfied:  $HIF612=2.48895$  mm and  $HIF612/HOI=0.49779$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens element which is the third nearest to the optical axis and the optical axis is denoted by HIF613. A distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens element which is the third nearest to the optical axis and the optical axis is denoted by HIF623. The following relations are satisfied:  $HIF613=0$  mm,  $HIF613/HOI=0$ ,  $HIF623=0$  mm and  $HIF623/HOI=0$ .

A distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens element which is the fourth nearest to the optical axis and the optical axis is denoted by HIF614. A distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens element which is the fourth nearest to the optical axis and the optical axis is denoted by HIF624. The following relations are satisfied:  $HIF614=0$  mm,  $HIF614/HOI=0$ ,  $HIF624=0$  mm and  $HIF624/HOI=0$ .

In the first embodiment, a horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to the image plane is ETL. A horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to a coordinate point on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP is EIN. The following relations are satisfied:  $ETL=19.304$  mm,  $EIN=15.733$  mm and  $EIN/ETL=0.815$ .

The first embodiment satisfies the following relations:  $ETP1=2.371$  mm,  $ETP2=2.134$  mm,  $ETP3=0.497$  mm,  $ETP4=1.111$  mm,  $ETP5=1.783$  mm and  $ETP6=1.404$  mm. A sum of ETP1 to ETP6 described above SETP=9.300 mm.  $TP1=2.064$  mm,  $TP2=2.500$  mm,  $TP3=0.380$  mm,  $TP4=1.186$  mm,  $TP5=2.184$  mm and  $TP6=1.105$  mm. A sum

of TP1 to TP6 described above  $STP=9.419$  mm.  $SETP/STP=0.987$ .  $SETP/EIN=0.5911$ .

The present embodiment particularly controls the ratio relation (ETP/TP) of the thickness (ETP) of each lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) to the thickness (TP) of the lens element to which the surface belongs on the optical axis in order to achieve a balance between manufacturability and capability of aberration correction. The following relations are satisfied:  $ETP1/TP1=1.149$ ,  $ETP2/TP2=0.854$ ,  $ETP3/TP3=1.308$ ,  $ETP4/TP4=0.936$ ,  $ETP5/TP5=0.817$  and  $ETP6/TP6=1.271$ .

The present embodiment controls a horizontal distance between each two adjacent lens elements at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) to achieve a balance between the degree of miniaturization for the length of the optical image capturing system HOS, the manufacturability and the capability of aberration correction. The ratio relation (ED/IN) of the horizontal distance (ED) between the two adjacent lens elements at height of  $\frac{1}{2}$  entrance pupil diameter (HEP) to the horizontal distance (IN) between the two adjacent lens elements on the optical axis is particularly controlled. The following relations are satisfied: a horizontal distance in parallel with the optical axis between the first lens element and the second lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP)  $ED12=5.285$  mm; a horizontal distance in parallel with the optical axis between the second lens element and the third lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP)  $ED23=0.283$  mm; a horizontal distance in parallel with the optical axis between the third lens element and the fourth lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP)  $ED34=0.330$  mm; a horizontal distance in parallel with the optical axis between the fourth lens element and the fifth lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP)  $ED45=0.348$  mm; a horizontal distance in parallel with the optical axis between the fifth lens element and the sixth lens element at height of  $\frac{1}{2}$  entrance pupil diameter (HEP)  $ED56=0.187$  mm. A sum of ED12 to ED56 described above is denoted as SED and  $SED=6.433$  mm.

The horizontal distance between the first lens element and the second lens element on the optical axis  $IN12=5.470$  mm and  $ED12/IN12=0.966$ . The horizontal distance between the second lens element and the third lens element on the optical axis  $IN23=0.178$  mm and  $ED23/IN23=1.590$ . The horizontal distance between the third lens element and the fourth lens element on the optical axis  $IN34=0.259$  mm and  $ED34/IN34=1.273$ . The horizontal distance between the fourth lens element and the fifth lens element on the optical axis  $IN45=0.209$  mm and  $ED45/IN45=1.664$ . The horizontal distance between the fifth lens element and the sixth lens element on the optical axis  $IN56=0.034$  mm and  $ED56/IN56=5.557$ . A sum of IN12 to IN56 described above is denoted as SIN.  $SIN=6.150$  mm.  $SED/SIN=1.046$ .

The first embodiment also satisfies the following relations:  $ED12/ED23=18.685$ ,  $ED23/ED34=0.857$ ,  $ED34/ED45=0.947$ ,  $ED45/ED56=1.859$ ,  $IN12/IN23=30.746$ ,  $IN23/IN34=0.686$ ,  $IN34/IN45=1.239$  and  $IN45/IN56=6.207$ .

A horizontal distance in parallel with the optical axis from a coordinate point on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP to the image plane  $EBL=3.570$  mm. A horizontal distance in parallel with the optical axis from an axial point on the image-side surface of the sixth lens element to the image plane  $BL=4.032$  mm. The embodiment of the present invention may satisfy the following relation:  $EBL/BL=0.8854$ . In the present invention, a distance in parallel with the optical axis from a coordinate point

on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP to the IR-bandstop filter  $EIR=1.950$  mm. A distance in parallel with the optical axis from an axial point on the image-side surface of the sixth lens element to the IR-bandstop filter  $PIR=2.121$  mm. The following relation is satisfied:  $EIR/PIR=0.920$ .

The IR-bandstop filter **180** is made of glass material without affecting the focal length of the optical image capturing system and it is disposed between the sixth lens element **160** and the image plane **190**.

In the optical image capturing system of the first embodiment, a focal length of the optical image capturing system is  $f$ , an entrance pupil diameter of the optical image capturing system is HEP, and half of a maximal view angle of the optical image capturing system is HAF. The detailed parameters are shown as below:  $f=4.075$  mm,  $f/HEP=1.4$ ,  $HAF=50.01$  and  $\tan(HAF)=1.1918$ .

In the optical image capturing system of the first embodiment, a focal length of the first lens element **110** is  $f1$  and a focal length of the sixth lens element **160** is  $f6$ . The following relations are satisfied:  $f1=-7.828$  mm,  $|f/f1|=0.52060$ ,  $f6=-4.886$  and  $|f1|>|f6|$ .

In the optical image capturing system of the first embodiment, focal lengths of the second lens element **120** to the fifth lens element **150** are  $f2$ ,  $f3$ ,  $f4$  and  $f5$ , respectively. The following relations are satisfied:  $|f2|+|f3|+|f4|+|f5|=95.50815$  mm,  $|f1|+f6|=12.71352$  mm and  $|f2|+|f3|+|f4|+|f5|>|f1|+|f6|$ .

A ratio of the focal length  $f$  of the optical image capturing system to a focal length  $f_p$  of each of lens elements with positive refractive power is PPR. A ratio of the focal length  $f$  of the optical image capturing system to a focal length  $f_n$  of each of lens elements with negative refractive power is NPR. In the optical image capturing system of the first embodiment, a sum of the PPR of all lens elements with positive refractive power is  $\Sigma PPR=f/f1+f/f3+f/f5=1.63290$ . A sum of the NPR of all lens elements with negative refractive powers is  $\Sigma NPR=1/f/f1+|f/f3|+|f/f6|=1.51305$ ,  $\Sigma PPR/|\Sigma NPR|=1.07921$ . The following relations are also satisfied:  $f/f2=0.69101$ ,  $|f/f3|=0.15834$ ,  $|f/f4|=0.06883$ ,  $|f/f5|=0.87305$  and  $|f/f6|=0.83412$ .

In the optical image capturing system of the first embodiment, a distance from the object-side surface **112** of the first lens element to the image-side surface **164** of the sixth lens element is  $InTL$ . A distance on an optical axis from the object-side surface **112** of the first lens element to the image plane **190** is HOS. A distance from an aperture **100** to an image plane **190** is  $InS$ . Half of a diagonal length of an effective detection field of the image sensing device **192** is HOI. A distance from the image-side surface **164** of the sixth lens element to the image plane **190** is BFL. The following relations are satisfied:  $InTL+BFL=HOS$ ,  $HOS=19.54120$  mm,  $HOI=5.0$  mm,  $HOS/HOI=3.90824$ ,  $HOS/f=4.7952$ ,  $InS=11.685$  mm and  $InS/HOS=0.59794$ .

In the optical image capturing system of the first embodiment, a total central thickness of all lens elements with refractive power on the optical axis is ETP. The following relations are satisfied:  $\Sigma TP=8.13899$  mm and  $\Sigma TP/InTL=0.52477$ . Hereby, contrast ratio for the image formation in the optical image capturing system and defect-free rate for manufacturing the lens element can be given consideration simultaneously, and a proper back focal length is provided to dispose other optical components in the optical image capturing system.

In the optical image capturing system of the first embodiment, a curvature radius of the object-side surface **112** of the first lens element is  $R11$ . A curvature radius of the image-

side surface **114** of the first lens element is R2. The following relation is satisfied:  $|R1/R2|=8.99987$ . Hereby, the first lens element may have proper strength of the positive refractive power, so as to avoid the longitudinal spherical aberration to increase too fast.

In the optical image capturing system of the first embodiment, a curvature radius of the object-side surface **162** of the sixth lens element is R11. A curvature radius of the image-side surface **164** of the sixth lens element is R12. The following relation is satisfied:  $(R11-R12)/(R11+R12)=1.27780$ . Hereby, the astigmatism generated by the optical image capturing system can be corrected beneficially.

In the optical image capturing system of the first embodiment, a sum of focal lengths of all lens elements with positive refractive power is  $\Sigma PP$ . The following relations are satisfied:  $\Sigma PP=f1+f3+f5=69.770$  mm and  $f5/(12+f4+f5)=0.067$ . Hereby, it is favorable for allocating the positive refractive power of a single lens element to other positive lens elements and the significant aberrations generated in the process of moving the incident light can be suppressed.

In the optical image capturing system of the first embodiment, a sum of focal lengths of all lens elements with negative refractive power is  $\Sigma NP$ . The following relations are satisfied:  $\Sigma NP=f1+f3+f6=-38.451$  mm and  $f6/(f1+f3+f6)=0.127$ . Hereby, it is favorable for allocating the positive refractive power of the sixth lens element **160** to other negative lens elements and the significant aberrations generated in the process of moving the incident light can be suppressed.

In the optical image capturing system of the first embodiment, a distance between the first lens element **110** and the second lens element **120** on the optical axis is IN12. The following relations are satisfied: IN12=6.418 mm and  $IN12/f=1.57491$ . Hereby, the chromatic aberration of the lens elements can be improved, such that the performance can be increased.

In the optical image capturing system of the first embodiment, a distance between the fifth lens element **150** and the sixth lens element **160** on the optical axis is IN56. The following relations are satisfied: IN56=0.025 mm and  $IN56/f=0.00613$ . Hereby, the chromatic aberration of the lens elements can be improved, such that the performance can be increased.

In the optical image capturing system of the first embodiment, central thicknesses of the first lens element **110** and the second lens element **120** on the optical axis are TP1 and TP2, respectively. The following relations are satisfied: TP1=1.934 mm, TP2=2.486 mm and  $(TP1+IN12)/TP2=3.36005$ . Hereby, the sensitivity produced by the optical image capturing system can be controlled, and the performance can be increased.

In the optical image capturing system of the first embodiment, central thicknesses of the fifth lens element **150** and the sixth lens element **160** on the optical axis are TP5 and TP6, respectively, and a distance between the aforementioned two lens elements on the optical axis is IN56. The following relations are satisfied: TP5=1.072 mm, TP6=1.031 mm and  $(TP6+IN56)/TP5=0.98555$ . Hereby, the sensitivity produced by the optical image capturing system can be controlled and the total height of the optical image capturing system can be reduced.

In the optical image capturing system of the first embodiment, a distance between the third lens element **130** and the fourth lens element **140** on the optical axis is IN34. A distance between the fourth lens element **140** and the fifth lens element **150** on the optical axis is IN45. The following relations are satisfied: IN34=0.401 mm, IN45=0.025 mm and  $TP4/(IN34+TP4+IN45)=0.74376$ . Hereby, the aberration generated by the process of moving the incident light

can be adjusted slightly layer upon layer, and the total height of the optical image capturing system can be reduced.

In the optical image capturing system of the first embodiment, a distance in parallel with an optical axis from a maximum effective half diameter position to an axial point on the object-side surface **152** of the fifth lens element is InRS51. A distance in parallel with an optical axis from a maximum effective half diameter position to an axial point on the image-side surface **154** of the fifth lens element is InRS52. A central thickness of the fifth lens element **150** is TP5. The following relations are satisfied: InRS51=-0.34789 mm, InRS52=-0.88185 mm,  $InRS51 \square / TP5=0.32458$  and  $InRS52 \square / TP5=0.82276$ . Hereby, it is favorable for manufacturing and forming the lens element and for maintaining the minimization for the optical image capturing system.

In the optical image capturing system of the first embodiment, a distance perpendicular to the optical axis between a critical point C51 on the object-side surface **152** of the fifth lens element and the optical axis is HVT51. A distance perpendicular to the optical axis between a critical point C52 on the image-side surface **154** of the fifth lens element and the optical axis is HVT52. The following relations are satisfied: HVT51=0.515349 mm and HVT52=0 mm.

In the optical image capturing system of the first embodiment, a distance in parallel with an optical axis from a maximum effective half diameter position to an axial point on the object-side surface **162** of the sixth lens element is InRS61. A distance in parallel with an optical axis from a maximum effective half diameter position to an axial point on the image-side surface **164** of the sixth lens element is InRS62. A central thickness of the sixth lens element **160** is TP6. The following relations are satisfied: InRS61=-0.58390 mm, InRS62=0.41976 mm,  $InRS61 \square / TP6=0.56616$  and  $InRS62 \square / TP6=0.40700$ . Hereby, it is favorable for manufacturing and forming the lens element and for maintaining the minimization for the optical image capturing system.

In the optical image capturing system of the first embodiment, a distance perpendicular to the optical axis between a critical point C61 on the object-side surface **162** of the sixth lens element and the optical axis is HVT61. A distance perpendicular to the optical axis between a critical point C62 on the image-side surface **164** of the sixth lens element and the optical axis is HVT62. The following relations are satisfied: HVT61=0.515349 mm and HVT62=0 mm.

In the optical image capturing system of the first embodiment, the following relation is satisfied:  $HVT51/HOI=0.1031$ . Hereby, the aberration of surrounding view field can be corrected.

In the optical image capturing system of the first embodiment, the following relation is satisfied:  $HVT51/HOS=0.02634$ . Hereby, the aberration of surrounding view field can be corrected.

In the optical image capturing system of the first embodiment, the second lens element **120**, the third lens element **130** and the sixth lens element **160** have negative refractive power. An Abbe number of the second lens element is NA2. An Abbe number of the third lens element is NA3. An Abbe number of the sixth lens element is NA6. The following relation is satisfied:  $NA6/NA2 \leq 1$ . Hereby, the chromatic aberration of the optical image capturing system can be corrected.

In the optical image capturing system of the first embodiment, TV distortion and optical distortion for image formation in the optical image capturing system are TOT and ODT, respectively. The following relations are satisfied:  $|TDT|=2.124\%$  and  $|ODT|=5.076\%$ .

In the optical image capturing system of the present embodiment, contrast transfer rates of modulation transfer

with spatial frequencies of 55 cycles/mm of a visible light at the optical axis on the image plane, 0.3 HOI and 0.7 HOI are respectively denoted by MTFE0, MTFE3 and MTFE7. The following relations are satisfied: MTFE0 is about 0.84, MTFE3 is about 0.84 and MTFE7 is about 0.75. The contrast transfer rates of modulation transfer with spatial frequencies of 110 cycles/mm of a visible light at the optical axis on the image plane, 0.3 HOI and 0.7 HOI are respectively denoted by MTFQ0, MTFQ3 and MTFQ7. The following relations are satisfied: MTFQ0 is about 0.66, MTFQ3 is about 0.65 and MTFQ7 is about 0.51. The contrast transfer rates of modulation transfer with spatial frequencies of 220 cycles/mm (MTF values) at the optical axis on the image plane, 0.3 HOI and 0.7 HOI are respectively denoted by MTFH0, MTFH3 and MTFH7. The following relations are satisfied;

MTFH0 is about 0.17, MTFH3 is about 0.07 and MTFH7 is about 0.14.

In the optical image capturing system of the present embodiment, when the infrared wavelength 850 nm is applied to focus on the image plane, contrast transfer rates of modulation transfer with a spatial frequency (55 cycles/mm) (MTF values) of the image at the optical axis on the image plane, 0.3 HOI and 0.7 HOI are respectively denoted by MTFI0, MTFI3 and MTFI7. The following relations are satisfied: MTFI0 is about 0.81, MTFI3 is about 0.8 and MTFI7 is about 0.15.

Please refer to the following Table 1 and Table 2.

The detailed data of the optical image capturing system of the first embodiment is as shown in Table 1.

TABLE 1

Data of the optical image capturing system f = 4.075 mm, f/HEP = 1.4, HAF = 50.000 deg							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length
0	Object	Plano	Plano				
1	Lens 1	-40.99625704	1.934	Plastic	1.515	56.55	-7.828
2		4.555209289	5.923				
3	Ape. stop	Plano	0.495				
4	Lens 2	5.333427366	2.486	Plastic	1.544	55.96	5.897
5		-6.781659971	0.502				
6	Lens 3	-5.697794287	0.380	Plastic	1.642	22.46	-25.738
7		-8.883957518	0.401				
8	Lens 4	13.19225664	1.236	Plastic	1.544	55.96	59.205
9		21.55681832	0.025				
10	Lens 5	8.987806345	1.072	Plastic	1.515	56.55	4.668
11		-3.158875374	0.025				
12	Lens 6	-29.46491425	1.031	Plastic	1.642	22.46	-4.886
13		3.593484273	2.412				
14	IR-bandstop filter	Plano	0.200		1.517	64.13	
15		Plano	1.420				
16	Image plane	Plano					

Reference wavelength (d-line) = 555 nm, shield position: clear aperture (CA) of the first plano = 5.800 mm; clear aperture (CA) of the third plano = 1.570 mm; clear aperture (CA) of the fifth plano = 1.950 mm

40

As for the parameters of the aspheric surfaces of the first embodiment, reference is made to Table 2.

TABLE 2

Aspheric Coefficients						
	Surface #					
	1	2	4	5	6	7
k	4.310876E+01	-4.707622E+00	2.616025E+00	2.445397E+00	5.645686E+00	-2.117147E+01
A4	7.054243E-03	1.714312E-02	-8.377541E-03	-1.789549E-02	-3.379055E-03	-1.370959E-02
A6	-5.233264E-04	-1.502232E-04	-1.838068E-03	-3.657520E-03	-1.225453E-03	6.250200E-03
A8	3.077890E-05	-1.359611E-04	1.233332E-03	-1.131622E-03	-5.979572E-03	-5.854426E-03
A10	-1.260650E-06	2.680747E-05	-2.390895E-03	1.390351E-03	4.556449E-03	4.049451E-03
A12	3.319093E-08	-2.017491E-06	1.998555E-03	-4.152857E-04	-1.177175E-03	-1.314592E-03
A14	-5.051600E-10	6.604615E-08	-9.734019E-04	5.487286E-05	1.370522E-04	2.143097E-04
A16	3.380000E-12	-1.301630E-09	2.478373E-04	-2.919339E-06	-5.974015E-06	-1.399894E-05
	Surface #					
	8	9	10	11	12	13
k	-5.287220E+00	6.200000E+01	-2.114008E+01	-7.699904E+00	-6.155476E+01	-3.120467E-01
A4	-2.937377E-02	-1.359965E-01	-1.263831E-01	-1.927804E-02	-2.492467E-02	-3.521844E-02
A6	2.743532E-03	6.628518E-02	6.965399E-02	2.478376E-03	-1.835360E-03	5.629654E-03
A8	-2.457574E-03	-2.129167E-02	-2.116027E-02	1.438785E-03	3.201343E-03	-5.466925E-04
A10	1.874319E-03	4.396344E-03	3.819371E-03	-7.013749E-04	-8.990757E-04	2.231154E-05
A12	-6.013661E-04	-5.542899E-04	-4.040283E-04	1.253214E-04	1.245343E-04	5.548990E-07

TABLE 2-continued

Aspheric Coefficients						
A14	8.792480E-05	3.768879E-05	2.280473E-05	-9.943196E-06	-8.788363E-06	-9.396920E-08
A16	-4.770527E-06	-1.052467E-06	-5.165452E-07	2.898397E-07	2.494302E-07	2.728360E-09

Table 1 is the detailed structure data to the first embodiment in FIG. 1A, wherein the unit of the curvature radius, the thickness, the distance, and the focal length is millimeters (mm). Surfaces 0-16 illustrate the surfaces from the object side to the image plane in the optical image capturing system. Table 2 is the aspheric coefficients of the first embodiment, wherein  $k$  is the conic coefficient in the aspheric surface formula, and A1-A20 are the first to the twentieth order aspheric surface coefficient. Besides, the tables in the following embodiments are referenced to the schematic view and the aberration graphs, respectively, and definitions of parameters in the tables are equal to those in the Table 1 and the Table 2, so the repetitious details will not be given here.

#### The Second Embodiment (Embodiment 2)

Please refer to FIG. 2A, FIG. 2B, FIGS. 2C, and 2D. FIG. 2A is a schematic view of the optical image capturing system according to the second embodiment of the present application, FIG. 2B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion curve of the optical image capturing system in the order from left to right according to the second embodiment of the present application. FIG. 2C is a characteristic diagram of modulation transfer of a visible light according to the second embodiment of the present application, and FIG. 2D is a characteristic diagram of modulation transfer of infrared rays according to the second embodiment of the present application. As shown in FIG. 2A, in order from an object side to an image side, the optical image capturing system includes an aperture stop 200, a first lens element 210, a second lens element 220, a third lens element 230, a fourth lens element 240, a fifth lens element 250, a sixth lens element 260, an IR-bandstop filter 280, an image plane 290, and an image sensing device 292.

The first lens element 210 has positive refractive power and it is made of plastic material. The first lens element 210 has a convex object-side surface 212 and a concave image-side surface 214, and both of the object-side surface 212 and the image-side surface 214 are aspheric and have an inflection point.

The second lens element 220 has negative refractive power and it is made of plastic material. The second lens element 220 has a convex object-side surface 222 and a convex image-side surface 224, and both of the object-side surface 222 and the image-side surface 224 are aspheric and have an inflection point.

The third lens element 230 has positive refractive power and it is made of plastic material. The third lens element 230

has a convex object-side surface 232 and a convex image-side surface 234, and both of the object-side surface 232 and the image-side surface 234 are aspheric. The object-side surface 232 has two inflection points and the image-side surface 234 has an inflection point.

The fourth lens element 240 has positive refractive power and it is made of plastic material. The fourth lens element 240 has a concave object-side surface 242 and a convex image-side surface 244, and both of the object-side surface 242 and the image-side surface 244 are aspheric and have an inflection point.

The fifth lens element 250 has positive refractive power and it is made of plastic material. The fifth lens element 250 has a concave object-side surface 252 and a convex image-side surface 254, and both of the object-side surface 252 and the image-side surface 254 are aspheric and have two inflection points.

The sixth lens element 260 has positive refractive power and it is made of plastic material. The sixth lens element 260 has a convex object-side surface 262 and a concave image-side surface 264. Hereby, the back focal length is reduced to miniaturize the lens element effectively. In addition, the object-side surface 262 has three inflection points and the image-side surface 264 has an inflection point, such that the angle of incident with incoming light from an off-axis view field can be suppressed effectively and the aberration in the off-axis view field can be corrected further.

The IR-bandstop filter 280 is made of glass material without affecting the focal length of the optical image capturing system and it is disposed between the sixth lens element 260 and the image plane 290.

In the optical image capturing system of the second embodiment, a sum of focal lengths of all lens elements with positive refractive power is  $\Sigma PP$ . The following relations are satisfied:  $\Sigma PP = 433.422$  mm and  $f1/\Sigma PP = 0.018$ . Hereby, it is favorable for allocating the positive refractive power of a single lens element to other positive lens elements and the significant aberrations generated in the process of moving the incident light can be suppressed.

In the optical image capturing system of the second embodiment, a sum of focal lengths of all lens elements with negative refractive power is  $\Sigma NP$ . The following relation is satisfied:  $\Sigma NP = -14.820$  mm and  $f2/\Sigma NP = 1.0$ . Hereby, it is favorable for allocating the negative refractive power of a single lens element to other negative lens elements.

Please refer to the following Table 3 and Table 4. The detailed data of the optical image capturing system of the second embodiment is as shown in Table 3.

TABLE 3

Data of the optical image capturing system $f = 4.953$ mm; $f/HEP = 1.4$ ; $HAF = 45$ deg							
Surface #	Curvature Radius	Thickness	Material	Index	Abbe #	Focal length	
0	Object	Plano	At infinity				
1	Ape. stop	Plano	0.050				
2	Lens 1	3.995478936	1.039	Plastic	1.544	55.96	7.807
3		59.5076314	0.000				



TABLE 3-continued

Data of the optical image capturing system f = 4.953 mm; f/HEP = 1.4; HAF = 45 deg							
Surface #	Curvature	Radius	Thickness	Material	Index	Abbe #	Focal length
4	Shading Sheet	Plano	0.345				
5	Lens 2	4.998721852	0.250	Plastic	1.642	22.46	-14.820
6		3.191592237	0.222				
7	Lens 3	9.444021769	0.602	Plastic	1.544	55.96	12.604
8		-24.53241903	0.374				
9	Lens 4	-2.1378009	0.566	Plastic	1.544	55.96	239.856
10		-2.325825141	0.090				
11	Lens 5	-2.808128216	0.296	Plastic	1.642	22.46	156.951
12		-2.785001481	0.090				
13	Lens 6	1.844710742	1.177	Plastic	1.544	55.96	16.204
14		1.800157486	0.799				
15	IR-bandstop filter	Plano	0.463	BK_7	1.517	64.13	
16		Plano	1.157				
17	Image plane	Plano	0.000				

Reference wavelength (d-line) = 555 nm, shield position: clear aperture (CA) of the fourth plano = 1.580 mm.

As for the parameters of the aspheric surfaces of the second embodiment, reference is made to Table 4.

TABLE 4

Aspheric Coefficients						
	Surface #					
	2	3	5	6	7	8
k	-1.961641E+00	2.439335E-01	6.855239E+00	1.737615E-01	-2.545734E-01	4.183236E+01
A4	-1.006733E-02	-3.150902E-02	-7.815730E-02	-6.234155E-02	-3.384114E-03	2.817718E-02
A6	2.618328E-02	1.097767E-02	-6.165708E-03	4.449867E-03	-1.215951E-02	-3.225285E-02
A8	-4.122737E-02	-7.587808E-03	2.775275E-02	1.102960E-02	-1.281730E-03	2.312459E-02
A10	3.329170E-02	9.216555E-04	-2.670014E-02	-9.363305E-03	1.642740E-03	-1.263646E-02
A12	-1.522910E-02	7.172076E-04	1.087225E-02	2.756237E-03	-9.005442E-05	3.312170E-03
A14	3.650647E-03	-2.972302E-04	-2.111975E-03	-3.444127E-04	-3.635405E-05	-3.738929E-04
A16	-3.635111E-04	3.186748E-05	1.482106E-04	1.448798E-05	3.607974E-06	1.446833E-05

	Surface #					
	9	10	11	12	13	14
k	-2.340358E-01	-1.096038E-01	-2.457226E-01	-1.414328E-01	-4.890481E+00	-1.285742E+00
A4	9.996625E-02	-2.147220E-01	-2.371507E-01	-7.486442E-02	-3.129158E-02	-5.458921E-02
A6	-8.277938E-02	2.126566E-01	2.425273E-01	5.518559E-02	7.201426E-03	1.088385E-02
A8	7.455823E-02	-1.066437E-01	-1.425446E-01	-2.595232E-02	-1.253499E-03	-1.535375E-03
A10	-3.777211E-02	3.059359E-02	5.529110E-02	9.763182E-03	1.391165E-04	1.404926E-04
A12	1.003382E-02	-4.225953E-03	-1.273438E-02	-2.050258E-03	-9.047444E-06	-7.914381E-06
A14	-1.329068E-03	1.626831E-04	1.565544E-03	2.106285E-04	3.204900E-07	2.470624E-07
A16	7.051993E-05	1.033356E-05	-7.966336E-05	-8.377410E-06	-4.889580E-09	-3.260760E-09

In the second embodiment, the presentation of the aspheric surface formula is similar to that in the first embodiment. Besides, the definitions of parameters in following tables are equal to those in the first embodiment, so the repetitious details will not be given here.

The following contents may be deduced from Table 3 and Table 4.

Second embodiment (Primary reference wavelength = 587.5 nm)					
ETP1	ETP2	ETP3	ETP4	ETP5	ETP6
0.627	0.530	0.517	0.206	0.372	1.281

-continued

Second embodiment (Primary reference wavelength = 587.5 nm)					
ETP1/TP1	ETP2/TP2	ETP3/TP3	ETP4/TP4	ETP5/TP5	ETP6/TP6
0.603	2.120	0.859	0.364	1.257	1.088

Second embodiment (Primary reference wavelength = 587.5 nm)					
ETL	EBL	EIN	EIR	PIR	EIN/ETL
7.226	1.978	5.248	0.359	0.799	0.726

Second embodiment (Primary reference wavelength = 587.5 nm)					
SETP/EIN	EIR/PIR	SETP	STP	SETP/STP	BL
0.673	0.449	3.533	3.930	0.899	2.413

## 31

-continued

Second embodiment (Primary reference wavelength = 587.5 nm)					
ED12	ED23	ED34	ED45	ED56	EBL/BL
0.339	0.091	0.121	0.200	0.962	0.8197
SED	SIN	SED/SIN	ED12/ED23	ED23/ED34	ED34/ED45
1.714	1.122	1.529	3.712	0.753	0.607
ED12/ IN12	ED23/ IN23	ED34/ IN34	ED45/IN45	ED56/IN56	ED45/ED56
0.983	0.412	0.324	2.224	10.687	0.208
f1/f1	f2/f2	f3/f3	f4/f4	f5/f5	f6/f6
0.63437	0.33419	0.39292	0.02065	0.03155	0.30564
$\Sigma$ PPR	$\Sigma$ NPR	$\Sigma$ PPR/ $\Sigma$ NPR	IN12/f	IN56/f	TP4/(IN34 + TP4 + IN45)
0.63437	0.33419	0.39292	0.02065	0.03155	0.30564
f1/f2	f2/f3	(TP1 + IN12)/TP2	(TP6 + IN56)/TP5		
0.52680	1.17575	5.37787	5.08880		
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
7.45289	5.03991	1.49058	1.00404	1.01435	0.21978
HVT51	HVT52	HVT61	HVT62	HVT62/HOI	HVT62/HOS
0	1.96492	2.25246	2.90315	0.58063	0.38953
TP2/TP3	TP3/TP4	InRS61	InRS62	InRS61 /TP6	InRS62 /TP6
0.38677	1.09878	0.27595	0.25307	0.23342	0.21407
MTFE0	MTFE3	MTFE7	MTFQ0	MTFQ3	MTFQ7
0.74	0.65	0.4	0.44	0.33	0.07
MTFI0	MTFI3	MTFI7			
0.58	0.64	0.23			

The following contents may be deduced from Table 3 and Table 4.

Related inflection point values of second embodiment (Primary reference wavelength: 555 nm)							
HIF111	1.1925	HIF111/HOI	0.2385	SGI111	0.1636	$ SGI111 /( SGI111  + TP1)$	0.1423
HIF121	0.2118	HIF121/HOI	0.0424	SGI121	0.0003	$ SGI121 /( SGI121  + TP1)$	0.0003
HIF211	0.4952	HIF211/HOI	0.0990	SGI211	0.0201	$ SGI211 /( SGI211  + TP2)$	0.0744
HIF221	0.7637	HIF221/HOI	0.1527	SGI221	0.0719	$ SGI221 /( SGI221  + TP2)$	0.2233
HIF311	0.6513	HIF311/HOI	0.1303	SGI311	0.0181	$ SGI311 /( SGI311  + TP3)$	0.0272
HIF312	1.5585	HIF312/HOI	0.3117	SGI312	-0.0246	$ SGI312 /( SGI312  + TP3)$	0.0367
HIF321	1.8081	HIF321/HOI	0.3616	SGI321	-0.2470	$ SGI321 /( SGI321  + TP3)$	0.2764
HIF411	1.7855	HIF411/HOI	0.3571	SGI411	-0.4637	$ SGI411 /( SGI411  + TP4)$	0.4408
HIF421	1.3364	HIF421/HOI	0.2673	SGI421	-0.5534	$ SGI421 /( SGI421  + TP4)$	0.4847
HIF511	1.1991	HIF511/HOI	0.2398	SGI511	-0.4045	$ SGI511 /( SGI511  + TP5)$	0.6181
HIF512	1.9791	HIF512/HOI	0.3958	SGI512	-0.6948	$ SGI512 /( SGI512  + TP5)$	0.7354
HIF521	1.3122	HIF521/HOI	0.2624	SGI521	-0.3940	$ SGI521 /( SGI521  + TP5)$	0.6118
HIF522	2.1278	HIF522/HOI	0.4256	SGI522	-0.6217	$ SGI522 /( SGI522  + TP5)$	0.7132
HIF611	0.9083	HIF611/HOI	0.1817	SGI611	0.1670	$ SGI611 /( SGI611  + TP6)$	0.1238
HIF612	3.0353	HIF612/HOI	0.6071	SGI612	0.3263	$ SGI612 /( SGI612  + TP6)$	0.2163
HIF613	3.2055	HIF613/HOI	0.6411	SGI613	0.3034	$ SGI613 /( SGI613  + TP6)$	0.2042
HIF621	1.1736	HIF621/HOI	0.2347	SGI621	0.2888	$ SGI621 /( SGI621  + TP6)$	0.1963

## The Third Embodiment (Embodiment 3)

Please refer to FIG. 3A, FIG. 3B, FIGS. 3C, and 3D. FIG. 3A is a schematic view of the optical image capturing system

## 32

according to the third embodiment of the present application, FIG. 3B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion curve of the optical image capturing system in the order from left to right according to the third embodiment of the present application, FIG. 3C is a characteristic diagram of modulation transfer of a visible light according to the third embodiment of the present application, and FIG. 3D is a characteristic diagram of modulation transfer of infrared rays according to the third embodiment of the present application. As shown in FIG. 3A, in order from an object side to an image side, the optical image capturing system includes an aperture stop 300, a first lens element 310, a second lens element 320, a third lens element 330, a fourth lens element 340, a fifth lens element 350, a sixth lens element 360, an IR-bandstop filter 380, an image plane 390, and an image sensing device 392.

The first lens element 310 has positive refractive power and it is made of plastic material. The first lens element 310 has a convex object-side surface 312 and a concave image-side surface 314, and both of the object-side surface 312 and the image-side surface 314 are aspheric and have an inflection point.

The second lens element 320 has negative refractive power and it is made of plastic material. The second lens element 320 has a convex object-side surface 322 and a concave image-side surface 324, and both of the object-side surface 322 and the image-side surface 324 are aspheric and have an inflection point.

The third lens element 330 has positive refractive power and it is made of plastic material. The third lens element 330 has a convex object-side surface 332 and a concave image-side surface 334, and both of the object-side surface 332 and the image-side surface 334 are aspheric and have two inflection points.

The fourth lens element 340 has positive refractive power and it is made of plastic material. The fourth lens element 340 has a concave object-side surface 342 and a convex image-side surface 344, and both of the object-side surface 342 and the image-side surface 344 are aspheric. The object-side surface 342 has three inflection points and the image-side surface 344 has an inflection point.

The fifth lens element 350 has positive refractive power and it is made of plastic material. The fifth lens element 350 has a concave object-side surface 352 and a convex image-side surface 354, and both of the object-side surface 352 and the image-side surface 354 are aspheric. The object-side



TABLE 6-continued

Aspheric Coefficients					
	Surface #				
	10	11	12	13	14
k	-1.479008E-01	-2.815444E-01	-1.650796E-01	-3.992221E+00	-1.257079E+00
A4	-2.612404E-01	-1.258625E-01	3.232059E-02	-4.394994E-02	-7.478522E-02
A6	2.391956E-01	8.887666E-02	-4.479161E-02	3.545002E-03	1.698028E-02
A8	-1.377034E-01	-1.040803E-02	4.437671E-02	2.728426E-03	-2.632893E-03
A10	5.040766E-02	-4.768864E-03	-1.845551E-02	-1.123773E-03	2.595745E-04
A12	-1.032729E-02	1.274375E-03	3.831477E-03	1.832750E-04	-1.575611E-05
A14	1.026347E-03	-5.094577E-05	-3.953097E-04	-1.408575E-05	5.402099E-07
A16	-3.415701E-05	-6.242368E-06	1.622541E-05	4.204356E-07	-8.144580E-09

The presentation of the aspheric surface formula in the third embodiment is similar to that in the first embodiment. Besides, the definitions of parameters in following tables are equal to those in the first embodiment so the repetitious details will not be given here.

The following contents may be deduced from Table 5 and Table 6.

Third embodiment (Primary reference wavelength: 555 nm)					
ETP1	ETP2	ETP3	ETP4	ETP5	ETP6
0.396	0.516	0.445	0.516	0.434	1.191
ETP1/TP1	ETP2/TP2	ETP3/TP3	ETP4/TP4	ETP5/TP5	ETP6/TP6
0.527	1.719	0.756	0.593	1.328	1.150
ETL	EBL	EIN	EIR	PIR	EIN/ETL
6.987	1.906	5.081	0.286	0.729	0.727
SETP/EIN	EIR/PIR	SETP	STP	SETP/STP	BL
0.688	0.393	3.498	3.874	0.903	2.349
ED12	ED23	ED34	ED45	ED56	EBL/BL
0.353	0.091	0.115	0.300	0.723	0.8114
SED	SIN	SED/SIN	ED12/ED23	ED23/ED34	ED34/ED45
1.583	1.047	1.512	3.863	0.794	0.385
ED12/IN12	ED23/IN23	ED34/IN34	ED45/IN45	ED56/IN56	ED45/ED56
1.004	0.549	0.337	3.094	8.035	0.414

15

-continued

Third embodiment (Primary reference wavelength: 555 nm)					
f/f1	f/f2	f/f3	f/f4	f/f5	f/f6
0.57187	0.29366	0.43577	0.13337	0.12866	0.05384
Σ PPR	Σ NPR	Σ PPR/ Σ NPR	IN12/f	IN56/f	TP4/(IN34 + TP4 + IN45)
1.32352	0.29366	4.50690	0.07076	0.01809	0.66530
f1/f2	f2/f3	(TP1 + IN12)/TP2	(TP6 + IN56)/TP5		
0.51351	1.48391	3.67707	3.44293		
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
7.26965	4.92053	1.45393	0.98313	1.02117	0.68523
HVT51	HVT52	HVT61	HVT62	HVT62/HOI	HVT62/HOS
0	0	1.85754	2.58775	0.51755	0.35597
TP2/TP3	TP3/TP4	InRS61	InRS62	InRS61 /TP6	InRS62 /TP6
0.50971	0.67560	-0.07003	-0.06993	0.06761	0.06751
MTFE0	MTFE3	MTFE7	MTFQ0	MTFQ3	MTFQ7
0.6	0.55	0.53	0.2	0.22	0.28
MTFI0	MTFI3	MTFI7			
0.35	0.45	0.27			

20

25

30

35

40

45

The following contents may be deduced from Table 5 and Table 6.

Related inflection point values of third embodiment (Primary reference wavelength: 555 nm)							
HIF111	1.2209	HIF111/HOI	0.2442	SGI111	0.2042	SGI111 /( SGI111  + TP1)	0.2138
HIF121	0.5959	HIF121/HOI	0.1192	SGI121	0.0132	SGI121 /( SGI121  + TP1)	0.0173
HIF211	0.6247	HIF211/HOI	0.1249	SGI211	0.0342	SGI211 /( SGI211  + TP2)	0.1024
HIF221	0.8802	HIF221/HOI	0.1760	SGI221	0.0948	SGI221 /( SGI221  + TP2)	0.2401
HIF311	0.7629	HIF311/HOI	0.1526	SGI311	0.0483	SGI311 /( SGI311  + TP3)	0.0758
HIF312	1.6243	HIF312/HOI	0.3249	SGI312	0.0583	SGI312 /( SGI312  + TP3)	0.0901
HIF321	0.6678	HIF321/HOI	0.1336	SGI321	0.0088	SGI321 /( SGI321  + TP3)	0.0147
HIF322	1.7707	HIF322/HOI	0.3541	SGI322	-0.1673	SGI322 /( SGI322  + TP3)	0.2213
HIF411	1.3064	HIF411/HOI	0.2613	SGI411	-0.2209	SGI411 /( SGI411  + TP4)	0.2023
HIF412	1.6746	HIF412/HOI	0.3349	SGI412	-0.3321	SGI412 /( SGI412  + TP4)	0.2760
HIF413	1.8692	HIF413/HOI	0.3738	SGI413	-0.3853	SGI413 /( SGI413  + TP4)	0.3066
HIF421	1.3422	HIF421/HOI	0.2684	SGI421	-0.5050	SGI421 /( SGI421  + TP4)	0.3669
HIF511	1.0465	HIF511/HOI	0.2093	SGI511	-0.2509	SGI511 /( SGI511  + TP5)	0.4342
HIF512	1.5111	HIF512/HOI	0.3022	SGI512	-0.4390	SGI512 /( SGI512  + TP5)	0.5731
HIF521	1.1184	HIF521/HOI	0.2237	SGI521	-0.2144	SGI521 /( SGI521  + TP5)	0.3960
HIF522	1.6488	HIF522/HOI	0.3298	SGI522	-0.3710	SGI522 /( SGI522  + TP5)	0.5315

Related inflection point values of third embodiment (Primary reference wavelength: 555 nm)							
HIF523	2.0430	HIF523/HOI	0.4086	SGI523	-0.4813	$ SGI523 /( SGI523  + TP5)$	0.5954
HIF524	2.2614	HIF524/HOI	0.4523	SGI524	-0.5462	$ SGI524 /( SGI524  + TP5)$	0.6255
HIF611	0.8117	HIF611/HOI	0.1623	SGI611	0.1363	$ SGI611 /( SGI611  + TP6)$	0.1163
HIF621	1.0439	HIF621/HOI	0.2088	SGI621	0.2607	$ SGI621 /( SGI621  + TP6)$	0.2011

#### The Fourth Embodiment (Embodiment 4)

Please refer to FIG. 4A, FIG. 4B, FIGS. 4C, and 4D. FIG. 4A is a schematic view of the optical image capturing system according to the fourth embodiment of the present application, FIG. 4B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion curve of the optical image capturing system in the order from left to right according to the fourth embodiment of the present application, FIG. 4C is a characteristic diagram of modulation transfer of a visible light according to the fourth embodiment of the present application, and FIG. 4D is a characteristic diagram of modulation transfer of infrared rays according to the fourth embodiment of the present application. As shown in FIG. 4A, in order from an object side to an image side, the optical image capturing system includes a first lens element 410, an aperture stop 400, a second lens element 420, a third lens element 430, a fourth lens element 440, a fifth lens element 450, a sixth lens element 460, an IR-bandstop filter 480, an image plane 490, and an image sensing device 492.

The first lens element 410 has positive refractive power and it is made of plastic material. The first lens element 410 has a convex object-side surface 412 and a concave image-side surface 414, and both of the object-side surface 412 and the image-side surface 414 are aspheric.

The second lens element 420 has negative refractive power and it is made of plastic material. The second lens element 420 has a convex object-side surface 422 and a concave image-side surface 424, and both of the object-side surface 422 and the image-side surface 424 are aspheric and have an inflection point.

The third lens element 430 has positive refractive power and it is made of plastic material. The third lens element 430 has a convex object-side surface 432 and a convex image-side surface 434, and both of the object-side surface 432 and the image-side surface 434 are aspheric. The image-side surface 434 has an inflection point.

The fourth lens element 440 has negative refractive power and it is made of plastic material. The fourth lens element

440 has a concave object-side surface 442 and a convex image-side surface 444, and both of the object-side surface 442 and the image-side surface 444 are aspheric and have two inflection points.

The fifth lens element 450 has positive refractive power and it is made of plastic material. The fifth lens element 450 has a convex object-side surface 452 and a convex image-side surface 454, and both of the object-side surface 452 and the image-side surface 454 are aspheric. The image-side surface 454 has an inflection point.

The sixth lens element 460 has negative refractive power and it is made of plastic material. The sixth lens element 460 has a convex object-side surface 462 and a concave image-side surface 464. Hereby, the back focal length is reduced to miniaturize the lens element effectively. In addition, the object-side surface 462 has two inflection points and the image-side surface 464 has an inflection point, such that the angle of incident with incoming light from an off-axis view field can be suppressed effectively and the aberration in the off-axis view field can be corrected further.

The IR-bandstop filter 480 is made of glass material without affecting the focal length of the optical image capturing system and it is disposed between the sixth lens element 460 and the image plane 490.

In the optical image capturing system of the fourth embodiment, a sum of focal lengths of all lens elements with positive refractive power is  $\Sigma PP$ . The following relation is satisfied:  $\Sigma PP=47.676$  mm and  $f1/\Sigma PP=0.753$ . Hereby, it is favorable for allocating the positive refractive power of a single lens element to other positive lens elements and the significant aberrations generated in the process of moving the incident light can be suppressed.

In the optical image capturing system of the fourth embodiment, a sum of focal lengths of all lens elements with negative refractive power is  $\Sigma NP$ . The following relation is satisfied:  $\Sigma NP=-80.546$  mm and  $f2/\Sigma NP=0.423$ . Hereby, it is favorable for allocating the negative refractive power of a single lens element to other negative lens elements.

Please refer to the following Table 7 and Table 8.

The detailed data of the optical image capturing system of the fourth embodiment is as shown in Table 7.

TABLE 7

Data of the optical image capturing system $f = 4.111$ mm; $f/HEP = 1.6$ ; $HAF = 50$ deg							
Surface #	Curvature Radius	Thickness	Material	Index	Abbe #	Focal length	
0	Object	Plano	At infinity				
1	Lens 1	17.34656208	0.761	Plastic	1.642	22.46	35.902
2		67.13151839	0.552				
3	Ape. Stop	Plano	0.035				
4	Lens 2	5.047189235	0.395	Plastic	1.642	22.46	-34.078
5		3.981478296	0.132				
6	Lens 3	16.68310252	1.200	Plastic	1.544	55.96	5.332
7		-3.435271485	0.400				
8	Lens 4	-1.847104712	0.829	Plastic	1.544	55.96	-14.926
9		-2.767193112	0.035				
10	Lens 5	59548.81632	0.787	Plastic	1.544	55.96	6.443

TABLE 7-continued

Data of the optical image capturing system							
f = 4.111 mm; f/HEP = 1.6; HAF = 50 deg							
Surface #	Curvature Radius	Thickness	Material	Index	Abbe #	Focal length	
11	-3.51665046	0.035					
12	Lens 6	2.429934365	0.862	Plastic	1.642	22.46	-31.543
13		1.868748779	1.192				
14	IR-band stop filter	Plano	0.200	BK_7	1.517	64.13	
15		Plano	1.097				
16	Image plane	Plano					

Reference wavelength (d-line) = 555 nm

As for the parameters of the aspheric surfaces of the fourth embodiment, reference is made to Table 8.

TABLE 8

Aspheric Coefficients							
	Surface #						
	1	2	4	5	6	7	
k	5.554860E-02	1.395180E-09	-2.588400E-10	1.650050E-09	-6.200000E+01	-5.516332E-01	
A4	9.903745E-03	1.835753E-02	-1.814708E-02	4.519014E-04	1.534036E-02	3.827013E-03	
A6	5.268991E-05	-1.628823E-03	-6.386123E-03	-1.637551E-02	-7.588269E-04	6.392777E-03	
A8	1.339594E-05	1.133817E-05	-1.679457E-03	4.872018E-03	4.351936E-06	-7.161817E-04	
A10	0.000000E+00	0.000000E+00	0.000000E+00	-8.428907E-04	0.000000E+00	0.000000E+00	
A12	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	
A14	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	
A16	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	
	Surface #						
	8	9	10	11	12	13	
k	-5.127197E-01	-2.150950E-01	1.075242E-06	-5.600000E-13	-7.074972E-01	-9.147335E-01	
A4	4.677542E-02	-1.186631E-02	-2.111275E-02	1.405716E-02	-1.780381E-02	-2.779886E-02	
A6	4.704409E-03	6.444206E-03	3.278762E-03	-4.191465E-03	-9.001808E-04	1.226077E-03	
A8	-7.474037E-04	-4.255366E-04	-2.485104E-04	4.942612E-04	5.914431E-05	-3.324507E-05	
A10	0.000000E+00	0.000000E+00	5.217018E-06	0.000000E+00	1.641048E-07	1.730271E-07	
A12	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	
A14	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	
A16	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	

The presentation of the aspheric surface formula in the fourth embodiment is similar to that in the first embodiment. Besides the definitions of parameters in following tables are equal to those in the first embodiment so the repetitious details will not be given here.

The following contents may be deduced from Table 7 and Table 8.

Fourth embodiment (Primary reference wavelength: 587.5 nm)					
ETP1	ETP2	ETP3	ETP4	ETP5	ETP6
0.742	0.473	0.929	0.852	0.623	0.937
ETP1/TP1	ETP2/TP2	ETP3/TP3	ETP4/TP4	ETP5/TP5	ETP6/TP6
0.975	1.198	0.775	1.028	0.792	1.087
ETL	EBL	EIN	EIR	PIR	EIN/ETL
8.445	2.140	6.305	0.843	1.192	0.747

-continued

Fourth embodiment (Primary reference wavelength: 587.5 nm)					
SETP/EIN	EIR/PIR	SETP	STP	SETP/STP	BL
0.723	0.708	4.557	4.833	0.943	2.489
ED12	ED23	ED34	ED45	ED56	EBL/BL
0.619	0.049	0.282	0.288	0.510	0.8598
SED	SIN	SED/SIN	ED12/ED23	ED23/ED34	ED34/ED45
1.748	1.89	1.470	12.624	0.174	0.977
ED12/IN12	ED23/IN23	ED34/IN34	ED45/IN45	ED56/IN56	ED45/ED56
1.055	0.370	0.704	8.239	14.571	0.565
f/f1	f/f2	f/f3	f/f4	f/f5	f/f6
0.11452	0.12065	0.77112	0.27546	0.63812	0.13034

-continued

Fourth embodiment (Primary reference wavelength: 587.5 nm)					
$\Sigma$ PPR	$\Sigma$ NPR	$\Sigma$ PPR/ $\Sigma$ NPR	IN12/f	IN56/f	TP4/(IN34 + TP4 + IN45)
1.52376	0.52646	2.89437	0.14267	0.00851	0.65563
f1/f2	f2/f3	(TP1 + IN12)/TP2	(TP6 + IN56)/TP5		
1.05352	6.39138	3.41260	1.14018		
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
8.51142	6.02256	1.70228	0.84582	1.75704	1.43721
HVT51	HVT52	HVT61	HVT62	HVT62/HOI	HVT62/HOS
0.014042	2.57282	2.36839	3.10690	0.62138	0.36503
TP2/TP3	TP3/TP4	InRS61	InRS62	InRS61 /TP6	InRS62 /TP6
0.32899	1.44788	0.20720	0.55678	0.24032	0.64577
MTFE0	MTFE3	MTFE7	MTFQ0	MTFQ3	MTFQ7
0.5	0.14	0.05	0.22	0.05	0.02
MTFI0		MTFI3		MTFI7	
0.42		0.55		0.11	

The following contents may be deduced from Table 7 and Table 8.

Related inflection point values of fourth embodiment (Primary reference wavelength: 555 nm)							
HIF211	0.7565	HIF211/HOI	0.1513	SGI211	0.0497	SGI211 /( SGI211  + TP2)	0.1118
HIF221	0.9861	HIF221/HOI	0.1972	SGI221	0.1130	SGI221 /( SGI221  + TP2)	0.2226
HIF321	1.1648	HIF321/HOI	0.2330	SGI321	-0.1795	SGI321 /( SGI321  + TP3)	0.1301
HIF411	1.0196	HIF411/HOI	0.2039	SGI411	-0.2377	SGI411 /( SGI411  + TP4)	0.2229
HIF412	1.9786	HIF412/HOI	0.3957	SGI412	-0.4501	SGI412 /( SGI412  + TP4)	0.3520
HIF421	1.6809	HIF421/HOI	0.3362	SGI421	-0.5306	SGI421 /( SGI421  + TP4)	0.3903
HIF422	2.2824	HIF422/HOI	0.4565	SGI422	-0.8432	SGI422 /( SGI422  + TP4)	0.5043
HIF521	2.0437	HIF521/HOI	0.4087	SGI521	-0.5646	SGI521 /( SGI521  + TP5)	0.4178
HIF611	1.3736	HIF611/HOI	0.2747	SGI611	0.3291	SGI611 /( SGI611  + TP6)	0.2762
HIF612	3.2319	HIF612/HOI	0.6464	SGI612	0.2927	SGI612 /( SGI612  + TP6)	0.2534
HIF621	1.4948	HIF621/HOI	0.2990	SGI621	0.4803	SGI621 /( SGI621  + TP6)	0.3578

#### The Fifth Embodiment (Embodiment 5)

Please refer to FIG. 5A, FIG. 5B, FIGS. 5C, and 5D. FIG. 5A is a schematic view of the optical image capturing system according to the fifth embodiment of the present application, FIG. 5B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion curve of the optical image capturing system in the order from left to right according to the fifth embodiment of the present application, FIG. 5C is a characteristic diagram of modulation transfer of a visible light according to the fifth embodiment of the present application and FIG. 5D is a characteristic diagram of modulation transfer of infrared rays according to the fifth embodiment of the present application. As shown in FIG. 5A, in order from an object side to an image side, the optical image capturing system includes a first lens element 510, an aperture stop 500, a second lens element 520, a third lens element 530, a fourth lens element 540, a fifth lens element 550, a sixth lens element 560, an IR-bandstop filter 580, an image plane 590, and an Image sensing device 592.

The first lens element 510 has positive refractive power and it is made of plastic material. The first lens element 510 has a convex object-side surface 512 and a concave image-side surface 514, and both of the object-side surface 512 and the image-side surface 514 are aspheric.

The second lens element 520 has negative refractive power and it is made of plastic material. The second lens element 520 has a convex object-side surface 522 and a concave image-side surface 524, and both of the object-side surface 522 and the image-side surface 524 are aspheric and have an inflection point.

The third lens element 530 has positive refractive power and it is made of plastic material. The third lens element 530 has a convex object-side surface 532 and a convex image-side surface 534, and both of the object-side surface 532 and the image-side surface 534 are aspheric. The object-side surface 532 has two inflection points and the image-side surface 534 has an inflection point.

The fourth lens element 540 has negative refractive power and it is made of plastic material. The fourth lens element 540 has a concave object-side surface 542 and a convex image-side surface 544, and both of the object-side surface 542 and the image-side surface 544 are aspheric and have an inflection point.

The fifth lens element 550 has positive refractive power and it is made of plastic material. The fifth lens element 550 has a concave object-side surface 552 and a convex image-

side surface 554, and both of the object-side surface 552 and the image-side surface 554 are aspheric. The object-side surface 552 has three inflection points and the image-side surface 554 has an inflection point.

The sixth lens element 560 has positive refractive power and it is made of plastic material. The sixth lens element 560 has a convex object-side surface 562 and a concave image-side surface 564. Hereby, the back focal length is reduced to miniaturize the lens element effectively. In addition, the object-side surface 562 has two inflection points and the image-side surface 564 has an inflection point, such that the angle of incident with incoming light from an off-axis view field can be suppressed effectively and the aberration in the off-axis view field can be corrected further.

The IR-bandstop filter 580 is made of glass material without affecting the focal length of the optical image capturing system and it is disposed between the sixth lens element 560 and the image plane 590.

In the optical image capturing system of the fifth embodiment, a sum of focal lengths of all lens elements with

43

positive refractive power is  $\Sigma PP$ . The following relation is satisfied:  $\Sigma PP=162.005$  mm and  $f1/\Sigma PP=0.852$ . Hereby, it is favorable for allocating the positive refractive power of a single lens element to other positive lens elements and the significant aberrations generated in the process of moving the incident light can be suppressed.

In the optical image capturing system of the fifth embodiment, sum of focal lengths of all lens elements with negative

44

refractive power is  $\Sigma NP$ . The following relation is satisfied:  $\Sigma NP=-171.598$  mm and  $f2/NP=0.932$ . Hereby, it is favorable for allocating the negative refractive power of a single lens element to other negative lens elements.

Please refer to the following Table 9 and Table 10.

The detailed data of the optical image capturing system of the fifth embodiment is as shown in Table 9.

TABLE 9

Data of the optical image capturing system							
f = 3.326 mm; f/HEP = 1.7; HAF = 54.997 deg							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal length
0	Object	Plano	At infinity				
1	Lens 1	6.681753882	0.702	Plastic	1.642	22.46	138.040
2		6.914548873	0.628				
3	Ape. Stop	Plano	0.129				
4	Lens 2	82.35806969	0.351	Plastic	1.544	55.96	-159.994
5		42.3203389	0.100				
6	Lens 3	9.473683495	0.735	Plastic	1.544	55.96	7.365
7		-6.834435187	0.243				
8	Lens 4	-2.128070835	0.490	Plastic	1.544	55.96	-11.604
9		-3.545749782	0.100				
10	Lens 5	-10.19254308	0.627	Plastic	1.544	55.96	6.059
11		-2.541819156	0.100				
12	Lens 6	2.816746668	1.166	Plastic	1.642	22.46	10.542
13		4.058679118	0.461				
14	IR-bandstop filter	Plano	0.200	BK_7	1.517	64.13	
15		Plano	1.620				
16	Image plane	Plano					

Reference wavelength (d-line) = 555 nm; shield position: clear aperture (CA) of the first plano = 1.970 mm, clear aperture (CA) of the fifth plano = 1.210 mm.

As for the parameters of the aspheric surfaces of the fifth embodiment, reference is made to Table 10.

TABLE 10

Aspheric Coefficients						
	Surface #					
	1	2	4	5	6	7
k	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00
A4	2.835656E-02	6.370060E-02	-6.180874E-02	-8.882535E-02	-1.237852E-01	2.695004E-02
A6	-6.233198E-03	-6.080604E-02	1.930073E-01	8.883206E-03	1.375984E-01	-2.104317E-01
A8	2.677624E-03	8.130283E-02	-6.381346E-01	1.845246E-02	-3.811348E-01	2.721081E-01
A10	-1.186971E-04	-7.039792E-02	1.192921E+00	-7.200306E-02	5.357589E-01	-2.257568E-01
A12	-2.920694E-04	3.606312E-02	-1.325914E+00	3.806542E-02	-4.678795E-01	1.155652E-01
A14	1.065180E-04	-9.868588E-03	7.983282E-01	9.247433E-03	2.123531E-01	-3.308663E-02
A16	-1.154680E-05	1.092361E-03	-2.058566E-01	-8.137112E-03	-3.627640E-02	3.984448E-03
	Surface #					
	8	9	10	11	12	13
k	0.000000E+00	0.000000E+00	0.000000E+00	-1.492782E-02	-1.295286E-01	-2.647596E-02
A4	1.205456E-01	2.947361E-02	-6.852074E-03	4.032468E-02	1.120730E-02	3.931182E-02
A6	-2.742641E-01	-8.481391E-02	4.197502E-02	-4.333732E-02	-2.941921E-02	-2.974786E-02
A8	2.883468E-01	8.561316E-02	-3.277696E-02	3.133523E-02	8.325070E-03	7.422920E-03
A10	-1.468376E-01	-4.401118E-02	1.295738E-02	-1.202019E-02	-1.414167E-03	-1.067041E-03
A12	3.964669E-02	1.237212E-02	-3.034365E-03	2.530156E-03	1.073489E-04	8.877732E-05
A14	-5.422279E-03	-1.899300E-03	3.776192E-04	-2.701599E-04	5.160513E-07	-3.941874E-06
A16	2.970141E-04	1.275659E-04	-1.868229E-05	1.156612E-05	-3.128510E-07	7.201570E-08



45

The presentation of the aspheric surface formula in the fifth embodiment is similar to that in the first embodiment. Besides the definitions of parameters in following tables are equal to those in the first embodiment so the repetitious details will not be given here.

The following contents may be deduced from Table 9 and Table 10.

Fifth embodiment (Primary reference wavelength: 587.5 nm)					
ETP1	ETP2	ETP3	ETP4	ETP5	ETP6
0.712	0.321	0.678	0.559	0.503	1.138
ETP1/TP1	ETP2/TP2	ETP3/TP3	ETP4/TP4	ETP5/TP5	ETP6/TP6
1.015	0.913	0.923	1.141	0.801	0.975
ETL	EBL	EIN	EIR	PIR	EIN/ETL
7.572	2.162	5.410	0.342	0.461	0.714
SETP/EIN	EIR/PIR	SETP	STP	SETP/STP	BL
0.723	0.742	3.911	4.072	0.960	2.281
ED12	ED23	ED34	ED45	ED56	EBL/BL
0.641	0.116	0.147	0.190	0.406	0.9478
SED	SIN	SED/SIN	ED12/ED23	ED23/ED34	ED34/ED45
1.499	1.300	1.153	5.500	0.794	0.774
ED12/ IN12	ED23/ IN23	ED34/ IN34	ED45/IN45	ED56/IN56	ED45/ED56
0.846	1.165	0.604	1.896	4.056	0.468

46

-continued

Fifth embodiment (Primary reference wavelength: 587.5 nm)					
f/f1	f/f2	f/f3	f/f4	f/f5	f/f6
0.02410	0.02079	0.45166	0.28666	0.54902	0.31554
Σ PPR	Σ NPR	Σ PPR/ Σ NPR	IN12/f	IN56/f	TP4/(IN34 + TP4 + IN45)
1.34031	0.30745	4.35944	0.22573	0.03006	0.59129
f1/f2	f2/f3	(TP1 + IN12)/TP2		(TP6 + IN56)/TP5	
0.86278	21.72459	4.12447		1.98651	
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
7.64213	5.36107	1.52843	0.82688	3.90083	2.13558
HVT51	HVT52	HVT61	HVT62	HVT62/HOI	HVT62/HOS
0	2.29182	1.64543	2.01953	0.40391	0.26426
TP2/TP3	TP3/TP4	InRS61	InRS62	InRS61 / TP6	InRS62 / TP6
0.47878	1.47903	-0.45322	-0.68042	0.39357	0.59087
MTFE0	MTFE3	MTFE7	MTFQ0	MTFQ3	MTFQ7
0.26	0.13	0.21	0.12	0.02	0.06
MTFI0		MTFI3		MTFI7	
0.52		0.42		0.52	

The following contents may be deduced from Table 9 and Table 10.

Related inflection point values of fifth embodiment (Primary reference wavelength: 555 nm)							
HIF211	0.1465	HIF211/HOI	0.0293	SGI211	0.0001	SGI211 /( SGI211  + TP2)	0.0003
HIF221	0.1546	HIF221/HOI	0.0309	SGI221	0.0002	SGI221 /( SGI221  + TP2)	0.0007
HIF311	0.2916	HIF311/HOI	0.0583	SGI311	0.0037	SGI311 /( SGI311  + TP3)	0.0051
HIF312	1.1870	HIF312/HOI	0.2374	SGI312	-0.1950	SGI312 /( SGI312  + TP3)	0.2097
HIF321	1.5175	HIF321/HOI	0.3035	SGI321	-0.5421	SGI321 /( SGI321  + TP3)	0.4245
HIF411	1.1053	HIF411/HOI	0.2211	SGI411	-0.2762	SGI411 /( SGI411  + TP4)	0.3572
HIF421	1.8710	HIF421/HOI	0.3742	SGI421	-0.6834	SGI421 /( SGI421  + TP4)	0.5790
HIF511	0.7033	HIF511/HOI	0.1407	SGI511	-0.0233	SGI511 /( SGI511  + TP5)	0.0357
HIF512	1.2097	HIF512/HOI	0.2419	SGI512	-0.0457	SGI512 /( SGI512  + TP5)	0.0677
HIF513	2.1162	HIF513/HOI	0.4232	SGI513	-0.2948	SGI513 /( SGI513  + TP5)	0.3188
HIF521	1.7929	HIF521/HOI	0.3586	SGI521	-0.5763	SGI521 /( SGI521  + TP5)	0.4777
HIF611	1.0277	HIF611/HOI	0.2055	SGI611	0.1796	SGI611 /( SGI611  + TP6)	0.1349
HIF612	2.4386	HIF612/HOI	0.4877	SGI612	-0.1839	SGI612 /( SGI612  + TP6)	0.1377
HIF621	1.2087	HIF621/HOI	0.2417	SGI621	0.2022	SGI621 /( SGI621  + TP6)	0.1494

## The Sixth Embodiment (Embodiment 6)

Please refer to FIG. 6A, FIG. 6B, FIGS. 6C, and 6D. FIG. 6A is a schematic view of the optical image capturing system according to the sixth Embodiment of the present application. FIG. 6B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion curve of the optical image capturing system in the order from left to right according to the sixth Embodiment of the present application, FIG. 6C is a characteristic diagram of modulation transfer of a visible light according to the sixth embodiment of the present application and FIG. 6D is a characteristic diagram of modulation transfer of infrared rays according to the sixth embodiment of the present application. As shown in FIG. 6A, in order from an object side to an image side, the optical image capturing system includes an aperture stop 600, a first lens element 610, a second lens element 620, a third lens element 630, a fourth lens element 640, a fifth lens element 650, a sixth lens element 660, an IR-bandstop filter 680, an image plane 690, and an image sensing device 692.

The first lens element 610 has positive refractive power and it is made of plastic material. The first lens element 610 has a convex object-side surface 612 and a concave image-side surface 614, and both of the object-side surface 612 and the image-side surface 614 are aspheric.

The second lens element 620 has negative refractive power and it is made of plastic material. The second lens element 620 has a convex object-side surface 622 and a concave image-side surface 624, and both of the object-side surface 622 and the image-side surface 624 are aspheric. The object-side surface 622 has an inflection point and the image-side surface 624 has an inflection point.

The third lens element 630 has positive refractive power and it is made of plastic material. The third lens element 630 has a convex object-side surface 632 and a convex image-side surface 634, and both of the object-side surface 632 and the image-side surface 634 are aspheric. The object-side surface 632 has an inflection point.

The fourth lens element 640 has positive refractive power and it is made of plastic material. The fourth lens element 640 has a concave object-side surface 642 and a convex

image-side surface 644, and both of the object-side surface 642 and the image-side surface 644 are aspheric and have an inflection point.

The fifth lens element 650 has negative refractive power and it is made of plastic material. The fifth lens element 650 has a convex object-side surface 652 and a concave image-side surface 654, and both of the object-side surface 652 and the image-side surface 654 are aspheric and have an inflection point.

The sixth lens element 660 has negative refractive power and it is made of plastic material. The sixth lens element 660 has a convex object-side surface 662 and a concave image-side surface 664. The object-side surface 662 has three inflection points and the image-side surface 664 has an inflection point. Hereby, the back focal length is reduced to miniaturize the lens element effectively. In addition, the angle of incident with incoming light from an off-axis view field can be suppressed effectively and the aberration in the off-axis view field can be corrected further.

The IR-bandstop filter 680 is made of glass material without affecting the focal length of the optical image capturing system and it is disposed between the sixth lens element 660 and the image plane 690.

In the optical image capturing system of the sixth Embodiment, a sum of focal lengths of all lens elements with positive refractive power is  $\Sigma PP$ . The following relations are satisfied:  $\Sigma PP = 22.243$  mm and  $f1/\Sigma PP = 0.294$ . Hereby, it is favorable for allocating the positive refractive power of a single lens element to other positive lens elements and the significant aberrations generated in the process of moving the incident light can be suppressed.

In the optical image capturing system of the sixth Embodiment, a sum of focal lengths of all lens elements with negative refractive power is  $\Sigma NP$ . The following relations are satisfied:  $\Sigma NP = -34.287$  mm and  $f2/\Sigma NP = 0.278$ . Hereby, it is favorable for allocating the negative refractive power of a single lens element to other negative lens elements.

Please refer to the following Table 11 and Table 12.

The detailed data of the optical image capturing system of the sixth Embodiment is as shown in Table 11.

TABLE 11

Data of the optical image capturing system							
f = 4.563 mm; f/HEP = 1.8; HAF = 40.000 deg							
Surface #	Curvature	Radius	Thickness	Material	Index	Abbe #	Focal length
0	Object	Plano	At infinity				
1	Shading Sheet	Plano	1.000				
2	Ape. Stop	Plano	-0.085				
3	Lens 1	2.579290664	0.606	Plastic	1.565	58.00	6.549
4		7.734889904	0.556				
5	Lens 2	5.556318651	0.253	Plastic	1.650	21.40	-9.536
6		2.888331595	0.269				
7	Lens 3	7.728664802	0.537	Plastic	1.565	58.00	10.256
8		-22.86501904	0.680				
9	Lens 4	-4.66250381	0.743	Plastic	1.565	58.00	5.438
10		-1.962479007	0.050				
11	Lens 5	2.41460167	0.464	Plastic	1.583	30.20	-15.936
12		1.782475086	0.799				
13	Lens 6	2.078176161	0.397	Plastic	1.565	54.50	-8.815
14		1.366326724	0.400				
15	IR-bandstop filter	Plano	0.200	BK_7	1.517	64.13	

TABLE 11-continued

Data of the optical image capturing system						
f = 4.563 mm; f/HEP = 1.8; HAF = 40.000 deg						
Surface #	Curvature	Radius	Thickness	Material	Index	Abbe #
16		Plano	0.445			
17	Image plane	Plano				

Reference wavelength = 555 nm; shield position: clear aperture (CA) of the first plano = 1.900 mm; clear aperture (CA) of the fifth plano = 1.350 mm.

As for the parameters of the aspheric surfaces of the sixth Embodiment, reference is made to Table 12.

TABLE 12

Aspheric Coefficients						
	Surface #					
	3	4	5	6	7	8
k	-1.965330E-01	-5.000000E+01	-1.977522E+01	1.561681E+00	-6.455515E-01	-1.008752E+01
A4	4.026434E-03	1.013456E-02	-7.128416E-02	-9.428671E-02	-2.599203E-02	-2.490729E-02
A6	2.336774E-03	-2.971436E-03	1.975980E-02	2.900219E-02	1.157674E-03	-2.651769E-05
A8	-4.089523E-04	9.681266E-04	-6.821332E-03	-8.979447E-03	-3.039551E-04	3.595911E-04
A10	2.399946E-04	-3.267278E-04	7.492140E-04	1.029104E-03	-6.128456E-04	-4.705564E-04
A12	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00
A14	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00
A16	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00

	Surface #					
	9	10	11	12	13	14
k	-1.265114E+01	-1.071704E+00	-1.802359E+00	-2.574175E+00	-1.160409E+01	-5.450052E+00
A4	-2.979570E-02	-5.029708E-03	-3.219111E-02	-2.248485E-02	-4.553388E-02	-2.712084E-02
A6	1.626347E-03	-1.656088E-04	1.885319E-03	6.073019E-04	3.495820E-03	1.106529E-03
A8	5.929791E-04	-3.525839E-04	1.425334E-04	-3.453233E-05	-3.180846E-05	4.771164E-05
A10	-1.404506E-05	1.886284E-04	-1.613797E-04	-6.029119E-06	-2.611113E-05	-1.019275E-06
A12	0.000000E+00	0.000000E+00	3.597321E-05	5.934568E-07	4.841602E-06	-1.085111E-07
A14	0.000000E+00	0.000000E+00	-3.203031E-06	-1.151533E-07	-2.688688E-07	-9.429300E-09
A16	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00

In the sixth Embodiment, the presentation of the aspheric surface formula is similar to that in the first embodiment. Besides, the definitions of parameters in following tables are equal to those in the first embodiment, so the repetitious details will not be given here.

The following contents may be deduced from Table 11 and Table 12.

Sixth embodiment (Primary reference wavelength: 555 nm)					
ETP1	ETP2	ETP3	ETP4	ETP5	ETP6
0.355	0.427	0.401	0.534	0.553	0.564

ETP1/TP1	ETP2/TP2	ETP3/TP3	ETP4/TP4	ETP5/TP5	ETP6/TP6
0.587	1.683	0.747	0.719	1.192	1.420

ETL	EBL	EIN	EIR	PIR	EIN/ETL
6.050	0.742	5.308	0.097	0.400	0.877

SETP/EIN	EIR/PIR	SETP	STP	SETP/STP	BL
0.534	0.242	2.835	3.000	0.945	1.041

40

-continued

Sixth embodiment (Primary reference wavelength: 555 nm)					
ED12	ED23	ED34	ED45	ED56	EBL/BL
0.437	0.148	0.570	0.713	0.605	0.7128

SED	SIN	SED/SIN	ED12/ED23	ED23/ED34	ED34/ED45
2.473	2.354	1.051	2.944	0.261	0.799

ED12/IN12	ED23/IN23	ED34/IN34	ED45/IN45	ED56/IN56	ED45/ED56
0.786	0.553	0.838	14.258	0.757	1.178

f/f1	f/f2	f/f3	f/f4	f/f5	f/f6
0.69678	0.47855	0.44493	0.83919	0.28635	0.51768

Σ PPR	Σ NPR	Σ PPR/Σ NPR	IN12/f	IN56/f	TP4/(IN34 + TP4 + IN45)
1.98090	1.28258	1.54447	0.12194	0.17511	0.50444

f1/f2	f2/f3	(TP1 + IN12)/TP2	(TP6 + IN56)/TP5
0.68680	0.92975	4.58532	2.57619

65

-continued

Sixth embodiment (Primary reference wavelength: 555 nm)					
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
6.39538	5.35447	1.63439	0.98672	2.20237	0.32047
HVT51	HVT52	HVT61	HVT62	HVT62/HOI	HVT62/HOS
1.8222	1.98075	1.21254	1.73115	0.44241	0.27069
TP2/TP3	TP3/TP4	InRS61	InRS62	InRS61 / TP6	InRS62 / TP6
0.47179	0.72292	-0.87802	-0.58316	2.21158	1.46888
MTFE0	MTFE3	MTFE7	MTFQ0	MTFQ3	MTFQ7
0.88	0.87	0.85	0.71	0.7	0.62
MTFI0		MTFI3		MTFI7	
0.38		0.42		0.31	

The following contents may be deduced from Table 11 and Table 12.

Related inflection point values of sixth Embodiment (Primary reference wavelength: 555 nm)							
HIF211	0.4489	HIF211/HOI	0.1147	SGI211	0.0149	SGI211 /( SGI211  + TP2)	0.0554
HIF221	0.7922	HIF221/HOI	0.2025	SGI221	0.0832	SGI221 /( SGI221  + TP2)	0.2472
HIF222	1.3566	HIF222/HOI	0.3467	SGI222	0.1641	SGI222 /( SGI222  + TP2)	0.3931
HIF311	0.6531	HIF311/HOI	0.1669	SGI311	0.0230	SGI311 /( SGI311  + TP3)	0.0410
HIF411	1.6839	HIF411/HOI	0.4303	SGI411	-0.4018	SGI411 /( SGI411  + TP4)	0.3510
HIF421	1.6943	HIF421/HOI	0.4330	SGI421	-0.7544	SGI421 /( SGI421  + TP4)	0.5038
HIF511	1.0132	HIF511/HOI	0.2589	SGI511	0.1737	SGI511 /( SGI511  + TP5)	0.2722
HIF521	1.0665	HIF521/HOI	0.2726	SGI521	0.2553	SGI521 /( SGI521  + TP5)	0.3548
HIF611	0.6028	HIF611/HOI	0.1541	SGI611	0.0678	SGI611 /( SGI611  + TP6)	0.1458
HIF612	2.6002	HIF612/HOI	0.6645	SGI612	-0.5213	SGI612 /( SGI612  + TP6)	0.5677
HIF613	2.7986	HIF613/HOI	0.7152	SGI613	-0.6859	SGI613 /( SGI613  + TP6)	0.6334
HIF621	0.7866	HIF621/HOI	0.2010	SGI621	0.1659	SGI621 /( SGI621  + TP6)	0.2947

### The Seventh Embodiment (Embodiment 7)

Please refer to FIG. 7A and FIG. 7B, FIGS. 7C, and 7D. FIG. 7A is a schematic view of the optical image capturing system according to the seventh Embodiment of the present application, FIG. 7B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion curve of the optical image capturing system in the order from left to right according to the seventh Embodiment of the present application, FIG. 7C is a characteristic diagram of modulation transfer of a visible light according to the seventh embodiment of the present application and FIG. 7D is a characteristic diagram of modulation transfer of infrared rays according to the seventh embodiment of the present application. As shown in FIG. 7A, in order from an object side to an image side, the optical image capturing system includes an aperture stop 700, a first lens element 710, a second lens element 720, a third lens element 730, a fourth lens element 740, a fifth lens element 750, a sixth lens element 760, an IR-bandstop filter 780, an image plane 790, and an image sensing device 792.

The first lens element 710 has positive refractive power and it is made of plastic material. The first lens element 710 has a convex object-side surface 712 and a concave image-side surface 714, and both of the object-side surface 712 and the image-side surface 714 are aspheric. The image-side surface 714 has an inflection point.

The second lens element 720 has negative refractive power and it is made of plastic material. The second lens element 720 has a convex object-side surface 722 and a

concave image-side surface 724, and both of the object-side surface 722 and the image-side surface 724 are aspheric and have an inflection point.

The third lens element 730 has positive refractive power and it is made of plastic material. The third lens element 730 has a convex object-side surface 732 and a convex image-side surface 734, and both of the object-side surface 732 and the image-side surface 734 are aspheric. The object-side surface 732 has an inflection point.

The fourth lens element 740 has positive refractive power and it is made of plastic material. The fourth lens element 740 has a concave object-side surface 742 and a convex image-side surface 744, and both of the object-side surface 742 and the image-side surface 744 are aspheric. The image-side surface 744 has an inflection point.

The fifth lens element 750 has negative refractive power and it is made of plastic material. The fifth lens element 750 has a concave object-side surface 752 and a convex image-side surface 754, and both of the object-side surface 752 and the image-side surface 754 are aspheric. The image-side surface 754 has an inflection point.

The sixth lens element 760 has negative refractive power and it is made of plastic material. The sixth lens element 760 has a convex object-side surface 762 and a concave image-

side surface 764. The object-side surface 762 and the image-side surface 764 both have an inflection point. Hereby, the back focal length is reduced to miniaturize the lens element effectively. In addition, the angle of incident with incoming light from an off-axis view field can be suppressed effectively and the aberration in the off-axis view field can be corrected further.

The IR-bandstop filter 780 is made of glass material without affecting the focal length of the optical image capturing system and it is disposed between the sixth lens element 760 and the image plane 790.

In the optical image capturing system of the seventh Embodiment, a sum of focal lengths of all lens elements with positive refractive power is  $\Sigma PP$ . The following relations are satisfied:  $\Sigma PP=19.725$  mm and  $f1/\Sigma PP=0.314$ . Hereby, it is favorable for allocating the positive refractive power of a single lens element to other positive lens elements and the significant aberrations generated in the process of moving the incident light can be suppressed.

In the optical image capturing system of the seventh Embodiment, a sum of focal lengths of all lens elements with negative refractive power is  $\Sigma NP$ . The following relations are satisfied:  $\Sigma NP=-30.530$  mm and  $f2/\Sigma NP=0.376$ . Hereby, it is favorable for allocating the negative refractive power of a single lens element to other negative lens elements.

Please refer to the following Table 13 and Table 14. The detailed data of the optical image capturing system of the seventh Embodiment is as shown in Table 13.

TABLE 13

Data of the optical image capturing system f = 3.826 mm; f/HEP = 2.0; HAF = 45.011 deg							
Surface #	Curvature	Radius	Thickness	Material	Index	Abbe #	Focal length
0	Object	Plano	At infinity				
1	Ape. Stop	Plano	-0.177				
2	Lens 1	2.451628472	0.456	Plastic	1.565	58	6.2089
3		7.593955211	0.605				
4	Lens 2	9.20476938	0.230	Plastic	1.65	21.4	-11.5891
5		4.101911628	0.081				
6	Lens 3	8.266818278	0.720	Plastic	1.565	58	11.1367
7		-25.5153165	0.284				
8	Lens 4	-4.110161954	0.741	Plastic	1.565	58	2.4422
9		-1.10031385	0.057				
10	Lens 5	-0.852339838	0.399	Plastic	1.65	21.4	-14.5421
11		-1.109749857	0.050				
12	Lens 6	2.197528479	0.892	Plastic	1.583	30.2	-4.5196
13		1.019069274	0.700				
14	IR-bandstop filter	Plano	0.200	BK_7	1.517	64.13	
15		Plano	0.581				
16	Image plane	Plano					

Reference wavelength = 555 nm

As for the parameters of the aspheric surfaces of the seventh Embodiment, reference is made to Table 14.

TABLE 14

Aspheric Coefficients							
	Surface #						
	2	3	4	5	6	7	
k	-6.708971E+00	2.366389E-01	-5.000000E+01	-2.108209E+01	-5.000000E+01	5.000000E+01	
A4	5.687816E-02	-8.721802E-03	-5.793894E-02	-4.239361E-02	-4.739335E-02	-3.104705E-02	
A6	-2.726341E-02	-1.657761E-02	-1.055616E-02	1.344941E-02	9.539779E-03	-4.275211E-03	
A8	1.566366E-02	9.455618E-03	-4.356157E-03	-1.287968E-02	4.180823E-03	-1.116079E-03	
A10	-1.079401E-02	-1.226395E-02	-9.042318E-03	2.260505E-03	-1.936540E-03	-1.320171E-03	
A12	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	
A14	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	
A16	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	

	Surface #					
	8	9	10	11	12	13
k	-8.505141E+00	-3.098627E+00	-3.307933E+00	-2.965300E+00	-1.896969E+01	-4.723456E+00
A4	-3.653360E-02	-5.896215E-02	-3.670965E-02	-1.310974E-02	-2.075990E-02	-1.628749E-02
A6	-7.299408E-04	8.525515E-04	5.668904E-03	8.713727E-04	1.455101E-03	2.125293E-03
A8	-2.048637E-03	2.330987E-03	-2.711504E-04	-4.868056E-04	-5.434359E-04	-2.267018E-04
A10	-1.322170E-03	-5.259619E-04	-2.036266E-04	-9.688778E-05	2.943673E-05	2.292451E-06
A12	0.000000E+00	0.000000E+00	-4.185495E-05	-1.134496E-05	1.910955E-05	1.263752E-06
A14	0.000000E+00	0.000000E+00	-6.120895E-05	1.120284E-05	-2.291830E-06	-7.065258E-08
A16	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00

In the seventh Embodiment, the presentation of the aspheric surface formula is similar to that in the first embodiment. Besides, the definitions of parameters in following tables are equal to those in the first embodiment, so the repetitious details will not be given here.

The following contents may be deduced from Table 13 and Table 14.

Seventh embodiment (Primary reference wavelength: 555 nm)					
ETP1	ETP2	ETP3	ETP4	ETP5	ETP6
0.307	0.309	0.653	0.510	0.455	1.055

-continued

Seventh embodiment (Primary reference wavelength: 555 nm)					
ETP1/TP1	ETP2/TP2	ETP3/TP3	ETP4/TP4	ETP5/TP5	ETP6/TP6
0.673	1.345	0.907	0.688	1.139	1.182
ETL	EBL	EIN	EIR	PIR	EIN/ETL
5.810	1.202	4.609	0.420	0.700	0.793
SETP/EIN	EIR/PIR	SETP	STP	SETP/STP	BL
0.714	0.599	3.290	3.439	0.957	1.482

-continued

Seventh embodiment (Primary reference wavelength: 555 nm)					
ED12	ED23	ED34	ED45	ED56	EBL/BL
0.545	0.040	0.198	0.036	0.499	0.8111
SED	SIN	SED/SIN	ED12/ED23	ED23/ED34	ED34/ED45
25.077	25.022	1.002	13.508	0.204	5.452
ED12/ IN12	ED23/ IN23	ED34/ IN34	ED45/IN45	ED56/IN56	ED45/ED56
0.900	0.498	0.697	0.632	9.989	0.073
f/f1	f/f2	f/f3	f/f4	f/f5	f/f6
0.61819	0.33287	0.34463	1.57178	0.26319	0.85036
$\Sigma$ PPR	$\Sigma$ NPR	$\Sigma$ PPR/ $\Sigma$ NPR	IN12/f	IN56/f	TP4/(IN34 + TP4 + IN45)
2.53460	1.44642	1.75233	0.15820	0.01307	0.68454
f1/f2	f2/f3	(TP1 + IN12)/TP2	(TP6 + IN56)/TP5		
0.53846	1.03532	4.61583	2.35880		
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
5.99858	4.51664	1.53260	0.97041	2.13021	0.335779
HVT51	HVT52	HVT61	HVT62	HVT62/HOI	HVT62/HOS
0	0	1.41631	2.38961	0.61053	0.39836
TP2/TP3	TP3/TP4	InRS61	InRS62	InRS61 /TP6	InRS62 /TP6
0.31962	0.97083	-0.27838	0.02112	0.31204	0.02368
MTFE0	MTFE3	MTFE7	MTFQ0	MTFQ3	MTFQ7
0.9	0.88	0.85	0.81	0.7	0.6
MTFI0	MTFI3	MTFI7			
0.45	0.02	0.22			

The following contents may be deduced from Table 13 and Table 14.

Related inflection point values of seventh Embodiment (Primary reference wavelength: 555 nm)							
HIF121	0.6570	HIF121/HOI	0.1678	SGI121	0.0257	$ SGI121 /( SGI121  + TP1)$	0.0533
HIF211	0.3620	HIF211/HOI	0.0925	SGI211	0.0060	$ SGI211 /( SGI211  + TP2)$	0.0253
HIF221	0.5754	HIF221/HOI	0.1470	SGI221	0.0327	$ SGI221 /( SGI221  + TP2)$	0.1245
HIF311	0.4435	HIF311/HOI	0.1133	SGI311	0.0097	$ SGI311 /( SGI311  + TP3)$	0.0134
HIF521	1.8502	HIF521/HOI	0.4727	SGI521	-1.0585	$ SGI521 /( SGI521  + TP5)$	0.7260
HIF611	0.6678	HIF611/HOI	0.1706	SGI611	0.0731	$ SGI611 /( SGI611  + TP6)$	0.0757
HIF621	0.9079	HIF621/HOI	0.2320	SGI621	0.2606	$ SGI621 /( SGI621  + TP6)$	0.2261

#### The Eight Embodiment (Embodiment 8)

Please refer to FIG. 8A, FIG. 8B, FIGS. 8C, and 8D. FIG. 8A is a schematic view of the optical image capturing system according to the eighth Embodiment of the present application, FIG. 8B is longitudinal spherical aberration curves, astigmatic field curves, and an optical distortion curve of the optical image capturing system in the order from left to right according to the eighth Embodiment of the present application, FIG. 8C is a characteristic diagram of modulation transfer of a visible light according to the eighth embodiment of the present application and FIG. 8D is a character-

istic diagram of modulation transfer of infrared rays according to the eighth embodiment of the present application. As shown in FIG. 8A, in order from an object side to an image side, the optical image capturing system includes an aperture stop 800, a first lens element 810, a second lens element 820, a third lens element 830, a fourth lens element 840, a fifth lens element 850, a sixth lens element 860, an IR-bandstop filter 880, an image plane 890, and an image sensing device 892.

The first lens element 810 has positive refractive power and it is made of plastic material. The first lens element 810 has a convex object-side surface 812 and a concave image-side surface 814, both of the object-side surface 812 and the image-side surface 814 are aspheric, and the image-side surface 814 has an inflection point.

The second lens element 820 has negative refractive power and it is made of plastic material. The second lens element 820 has a concave object-side surface 822 and a concave image-side surface 824, and both of the object-side surface 822 and the image-side surface 824 are aspheric. The image-side surface 824 has two inflection points.

The third lens element 830 has negative refractive power and it is made of plastic material. The third lens element 830 has a convex object-side surface 832 and a concave image-side surface 834, and both of the object-side surface 832 and the image-side surface 834 are aspheric. The object-side surface 832 and the image-side surface 834 both have an inflection point.

The fourth lens element 840 has positive refractive power and it is made of plastic material. The fourth lens element 840 has a concave object-side surface 842 and a convex image-side surface 844, and both of the object-side surface 842 and the image-side surface 844 are aspheric. The object-side surface 842 has three inflection points.

The fifth lens element 850 has positive refractive power and it is made of plastic material. The fifth lens element 850 has a convex object-side surface 852 and a convex image-side surface 854, and both of the object-side surface 852 and the image-side surface 854 are aspheric. The object-side surface 852 has three inflection points and the image-side surface 854 has an inflection point.

55

The sixth lens element 860 has negative refractive power and it is made of plastic material. The sixth lens element 860 has a concave object-side surface 862 and a concave image-side surface 864. The object-side surface 862 has two inflection points and the image-side surface 864 has an inflection point. Hereby, the back focal length is reduced to miniaturize the lens element effectively. In addition, the angle of incident with incoming light from an off-axis view field can be suppressed effectively and the aberration in the off-axis view field can be corrected further.

The IR-bandstop filter 880 is made of glass material without affecting the focal length of the optical image

capturing system and it is disposed between the sixth lens element **860** and the image plane **890**.

In the optical image capturing system of the eighth Embodiment, a sum of focal lengths of all lens elements with positive refractive power is  $\Sigma PP$ . The following relations are satisfied:  $\Sigma PP=12.785$  mm and  $f5/\Sigma PP=0.10$ . Hereby, it is favorable for allocating the positive refractive power of a single lens element to other positive lens elements and the significant aberrations generated in the process of moving the incident light can be suppressed.

In the optical image capturing system of the eighth Embodiment, a sum of focal lengths of all lens elements with negative refractive power is  $\Sigma NP$ . The following relations are satisfied:  $\Sigma NP=-112.117$  mm and  $f6/\Sigma NP=0.00$ . Hereby, it is favorable for allocating the negative refractive power of a single lens element to other negative lens elements.

Please refer to the following Table 15 and Table 16. The detailed data of the optical image capturing system of the eighth Embodiment is as shown in Table 15.

TABLE 15

Data of the optical image capturing system $f = 3.213$ mm; $f/HEP = 2.4$ ; $HAF = 50.015$ deg							
Surface #	Curvature	Radius	Thickness	Material	Index	Abbe #	Focal length
0	Object	Plano	At infinity				
1	Shading sheet	Plano	0.000				
2	Ape. Stop	Plano	-0.108				
3	Lens 1	2.117380565	0.267	Plastic	1.565	58.00	6.003
4		5.351202213	0.632				
5	Lens 2	-70.37596785	0.230	Plastic	1.517	21.40	-11.326
6		8.30936549	0.050				
7	Lens 3	7.333171865	0.705	Plastic	1.565	58.00	-99.749
8		6.265499794	0.180				
9	Lens 4	-71.32533363	0.832	Plastic	1.565	58.00	5.508
10		-3.003657909	0.050				
11	Lens 5	3.397431079	0.688	Plastic	1.583	30.20	1.274
12		-0.886432266	0.050				
13	Lens 6	-3.715425702	0.342	Plastic	1.650	21.40	-1.042
14		0.867623637	0.700				
15	IR-bandstop filter	Plano	0.200		1.517	64.13	
16		Plano	0.407				
17	Image plane	Plano					

Reference wavelength = 555 nm; shield position: clear aperture (CA) of the first plano = 0.640 mm

As for the parameters of the aspheric surfaces of the eighth Embodiment, reference is made to Table 16.

TABLE 16

Aspheric Coefficients						
	Surface #					
	3	4	5	6	7	8
k	-1.486403E+00	2.003790E+01	-4.783682E+01	-2.902431E+01	-5.000000E+01	-5.000000E+01
A4	2.043654E-02	-2.642626E-02	-6.237485E-02	-4.896336E-02	-7.363667E-02	-5.443257E-02
A6	-2.231403E-04	-4.147746E-02	-8.137705E-02	-1.981368E-02	1.494245E-02	1.263891E-04
A8	-1.387235E-02	2.901026E-02	4.589961E-02	3.312952E-03	6.252296E-03	-9.655324E-03
A10	-3.431740E-02	-9.512960E-02	-5.485574E-02	5.634445E-03	-2.226544E-03	1.318692E-03
A12	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00
A14	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00
	Surface #					
	9	10	11	12	13	14
k	-5.000000E+01	8.520005E-01	-5.000000E+01	-4.524978E+00	-5.000000E+01	-4.286435E+00
A4	3.105497E-02	-6.786287E-03	-9.520247E-02	-4.666187E-02	5.856863E-03	-2.635938E-02
A6	-1.532514E-02	6.693976E-03	-5.507560E-05	3.849227E-03	2.442214E-03	3.694093E-03
A8	-6.443603E-04	8.220809E-04	1.932773E-03	1.041053E-03	-2.201034E-03	-1.355873E-04
A10	4.321089E-04	-2.798394E-04	3.346274E-04	4.713339E-06	-1.065215E-04	-5.321575E-05
A12	0.000000E+00	0.000000E+00	1.125736E-05	-2.834871E-06	1.227641E-04	6.838440E-06
A14	0.000000E+00	0.000000E+00	-1.671951E-05	-2.293810E-06	-1.181115E-05	-2.530792E-07

In the eighth Embodiment, the presentation of the aspheric surface formula is similar to that in the first embodiment. Besides, the definitions of parameters in following tables are equal to those in the first embodiment, so the repetitious details will not be given here.

The following contents may be deduced from Table 15 and Table 16.

Eighth embodiment (Primary reference wavelength: 555 nm)					
ETP1	ETP2	ETP3	ETP4	ETP5	ETP6
0.203	0.263	0.710	0.760	0.479	0.556
ETP1/TP1	ETP2/TP2	ETP3/TP3	ETP4/TP4	ETP5/TP5	ETP6/TP6
0.759	1.142	1.008	0.914	0.696	1.628
ETL	EBL	EIN	EIR	PIR	EIN/ETL
5.234	1.134	4.100	0.527	0.700	0.783
SETP/EIN	EIR/PIR	SETP	STP	SETP/STP	BL
0.725	0.753	2.971	3.064	0.970	1.304
ED12	ED23	ED34	ED45	ED56	EBL/BL
0.580	0.050	0.161	0.150	0.188	0.8696
SED		SIN		SED/SIN	
1.129		0.962		1.173	
ED12/IN12	ED23/IN23	ED34/IN34	ED45/IN45	ED56/IN56	
0.917	1.005	0.896	2.997	3.756	

-continued

Eighth embodiment (Primary reference wavelength: 555 nm)					
f/f1	f/f2	f/f3	f/f4	f/f5	f/f6
0.53529	0.28371	0.03221	0.58335	2.52139	3.08263
Σ PPR	Σ NPR	Σ PPR/ Σ NPR	IN12/f	IN56/f	TP4/(IN34 + TP4 + IN45)
6.72266	0.84594	7.94700	0.19680	0.01556	0.78362
f1/f2	f2/f3	(TP1 + IN12)/TP2		(TP6 + IN56)/TP5	
0.53001	0.11354	3.90947		0.56888	
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
5.33002	4.02576	1.36178	0.97981	1.92371	1.09084
HVT51	HVT52	HVT61	HVT62	HVT62/HOI	HVT62/HOS
0.67483	0	0.00000	2.23965	0.57222	0.42020
TP2/TP3	TP3/TP4	InRS61	InRS62	InRS61/TP6	InRS62/TP6
0.32631	0.84713	-0.74088	-0.06065	2.16896	0.17755
MTFE0	MTFE3	MTFE7	MTFQ0	MTFQ3	MTFQ7
0.9	0.85	0.8	0.77	0.63	0.51
MTFI0		MTFI3		MTFI7	
0.45		0.03		0.22	

The following contents may be deduced from Table 15 and Table 16.

Related inflection point values of eighth Embodiment (Primary reference wavelength: 555 nm)							
HIF121	0.57452	HIF121/HOI	0.14679	SGI121	0.02858	SGI121 /( SGI121  + TP1)	0.09675
HIF221	0.40206	HIF221/HOI	0.10272	SGI221	0.00821	SGI221 /( SGI221  + TP2)	0.03448
HIF222	1.11769	HIF222/HOI	0.28556	SGI222	-0.02234	SGI222 /( SGI222  + TP2)	0.08853
HIF311	0.37391	HIF311/HOI	0.09553	SGI311	0.00785	SGI311 /( SGI311  + TP3)	0.01102
HIF321	0.42061	HIF321/HOI	0.10746	SGI321	0.01170	SGI321 /( SGI321  + TP3)	0.01633
HIF411	0.19878	HIF411/HOI	0.05079	SGI411	-0.00023	SGI411 /( SGI411  + TP4)	0.00028
HIF412	0.87349	HIF412/HOI	0.22317	SGI412	0.00583	SGI412 /( SGI412  + TP4)	0.00695
HIF413	1.87638	HIF413/HOI	0.47940	SGI413	-0.17360	SGI413 /( SGI413  + TP4)	0.17263
HIF511	0.36373	HIF511/HOI	0.09293	SGI511	0.015644	SGI511 /( SGI511  + TP5)	0.02222
HIF512	1.7159	HIF512/HOI	0.43840	SGI512	-0.446747	SGI512 /( SGI512  + TP5)	0.39358
HIF513	1.93653	HIF513/HOI	0.49477	SGI513	-0.638544	SGI513 /( SGI513  + TP5)	0.48124
HIF521	1.54767	HIF521/HOI	0.39542	SGI521	-0.792114	SGI521 /( SGI521  + TP5)	0.53505
HIF611	0.82168	HIF611/HOI	0.20993	SGI611	-0.060958	SGI611 /( SGI611  + TP6)	0.15143
HIF612	0.98146	HIF612/HOI	0.25076	SGI612	-0.07785	SGI612 /( SGI612  + TP6)	0.18561
HIF621	0.76476	HIF621/HOI	0.20306	SGI621	0.238143	SGI621 /( SGI621  + TP6)	0.41079



## 61

The above-mentioned descriptions represent merely the exemplary embodiment of the present disclosure, without any intention to limit the scope of the present disclosure thereto. Various equivalent changes, alternations or modifications based on the claims of present disclosure are all consequently viewed as being embraced by the scope of the present disclosure.

What is claimed is:

1. An optical image capturing system, from an object side to an image side, comprising:

- a first lens element with positive refractive power;
- a second lens element with refractive power;
- a third lens element with refractive power;
- a fourth lens element with refractive power;
- a fifth lens element with refractive power;
- a sixth lens element with refractive power; and
- an image plane;

wherein the optical image capturing system consists of six lens elements with refractive power, a maximum height for image formation on the image plane perpendicular to an optical axis in the optical image capturing system is denoted by HOI, at least one of the second through sixth lens elements has positive refractive power, an object-side surface and an image-side surface of the sixth lens element are aspheric, focal lengths of the first through sixth lens elements are  $f_1$ ,  $f_2$ ,  $f_3$ ,  $f_4$ ,  $f_5$  and  $f_6$  respectively, a focal length of the optical image capturing system is  $f$ , an entrance pupil diameter of the optical image capturing system is HEP, a distance on the optical axis from an axial point on an object-side surface of the first lens element to an axial point on the image plane is HOS, thicknesses in parallel with the optical axis of the first through sixth lens elements at height  $\frac{1}{2}$  HEP respectively are ETP1, ETP2, ETP3, ETP4, ETP5 and ETP6, a sum of ETP1 to ETP6 described above is SETP, thicknesses of the first through sixth lens elements on the optical axis respectively are TP1, TP2, TP3, TP4, TP5 and TP6, a sum of TP1 to TP6 described above is STP, and the following relations are satisfied:  $1.2 \leq f/HEP \leq 10.0$  and  $0.5 \leq SETP/STP < 1$ .

2. The optical image capturing system of claim 1, wherein a horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to the image plane is ETL, a horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to a coordinate point on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP is EIN, and the following relation is satisfied:  $0.2 \leq EIN/ETL < 1$ .

3. The optical image capturing system of claim 2, wherein the thicknesses in parallel with the optical axis of the first through sixth lens elements at height  $\frac{1}{2}$  HEP respectively are ETP1, ETP2, ETP3, ETP4, ETP5 and ETP6, the sum of ETP1 to ETP6 described above is SETP, and the following relation is satisfied:  $0.3 \leq SETP/EIN < 1$ .

4. The optical image capturing system of claim 1, wherein the optical image capturing system comprises a light filtration element, the light filtration element is located between the sixth lens element and the image plane, a distance in parallel with the optical axis from a coordinate point on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP to the light filtration element is EIR, a distance in parallel with the optical axis from an axial point on the

## 62

image-side surface of the sixth lens element to the light filtration element is PIR, and the following relation is satisfied:  $0.1 \leq EIR/PIR \leq 1.1$ .

5. The optical image capturing system of claim 1, wherein an object-side surface or an image-side surface of at least one of the six lens elements has at least one inflection point.

6. The optical image capturing system of claim 1, wherein contrast transfer rates of modulation transfer with spatial frequencies of 55 cycles/mm (MTF values) of a visible light at the optical axis on the image plane, 0.3 HOI and 0.7 HOI are respectively denoted by MTFE0, MTFE3 and MTFE7, and the following relations are satisfied:  $MTFE0 \geq 0.2$ ,  $MTFE3 \geq 0.01$  and  $MTFE7 \geq 0.01$ .

7. The optical image capturing system of claim 1, wherein a half of maximum view angle of the optical image capturing system is HAF, and the following relation is satisfied:  $0.4 \leq |\tan(HAF)| \leq 6.0$ .

8. The optical image capturing system of claim 1, wherein a horizontal distance in parallel with the optical axis from a coordinate point on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP to the image plane is EBL, a horizontal distance in parallel with the optical axis from an axial point on the image-side surface of the sixth lens element to the image plane is BL, and the following relation is satisfied:  $0.1 \leq EBL/BL < 1.1$ .

9. The optical image capturing system of claim 5, further comprising an aperture stop, and an image sensing device is disposed on the image plane, wherein a distance from the aperture stop to the image plane on the optical axis is InS, a distance perpendicular to the optical axis between the inflection point and the optical axis is HIF, and the following relations are satisfied:  $0.1 \leq InS/HOS \leq 1.1$  and  $0 \leq HIF/HOI \leq 0.9$ .

10. An optical image capturing system, from an object side to an image side, comprising:

- a first lens element with positive refractive power;
- a second lens element with refractive power;
- a third lens element with refractive power;
- a fourth lens element with refractive power;
- a fifth lens element with refractive power;
- a sixth lens element with refractive power; and
- an image plane;

wherein the optical image capturing system consists of six lens elements with refractive power and at least one of the six lens elements is made of plastic, a maximum height for image formation on the image plane perpendicular to an optical axis in the optical image capturing system is denoted by HOI, at least one of the second through sixth lens elements has positive refractive power, focal lengths of the first through sixth lens elements are  $f_1$ ,  $f_2$ ,  $f_3$ ,  $f_4$ ,  $f_5$  and  $f_6$  respectively, a focal length of the optical image capturing system is  $f$ , an entrance pupil diameter of the optical image capturing system is HEP, a distance on the optical axis from an axial point on an object-side surface of the first lens element to an axial point on the image plane is HOS, a horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to the image plane is ETL, a horizontal distance in parallel with the optical axis from the coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to a coordinate point on an image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP is EIN, and the following relations are satisfied:  $1.2 \leq f/HEP \leq 10.0$  and  $0.2 \leq EIN/ETL < 1$ .

11. The optical image capturing system of claim 10, wherein a horizontal distance in parallel with the optical axis from a coordinate point on an image-side surface of the fifth lens element at height  $\frac{1}{2}$  HEP to a coordinate point on an object-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP is ED56, a distance from the fifth lens element to the sixth lens element on the optical axis is IN56, and the following relation is satisfied:  $0 < ED56/IN56 \leq 50$ .

12. The optical image capturing system of claim 10, wherein a horizontal distance in parallel with the optical axis from a coordinate point on an image-side surface of the first lens element at height  $\frac{1}{2}$  HEP to a coordinate point on an object-side surface of the second lens element at height  $\frac{1}{2}$  HEP is ED12, a distance from the first lens element to the second lens element on the optical axis is IN12, and the following relation is satisfied:  $0 < ED12/IN12 < 10$ .

13. The optical image capturing system of claim 10, wherein a thickness in parallel with the optical axis of the second lens element at height  $\frac{1}{2}$  HEP is ETP2, a thickness of the second lens element on the optical axis is TP2, and the following relation is satisfied:  $0 < ETP2/TP2 \leq 3$ .

14. The optical image capturing system of claim 10, wherein a thickness in parallel with the optical axis of the fifth lens element at height  $\frac{1}{2}$  HEP is ETP5, a thickness of the fifth lens element on the optical axis is TP5, and the following relation is satisfied:  $0 < ETP5/TP5 \leq 3$ .

15. The optical image capturing system of claim 10, wherein a thickness in parallel with the optical axis of the sixth lens element at height  $\frac{1}{2}$  HEP is ETP6, a thickness of the sixth lens element on the optical axis is TP6, and the following relation is satisfied:  $0 < ETP6/TP6 \leq 5$ .

16. The optical image capturing system of claim 10, wherein a distance from the first lens element to the second lens element on the optical axis is IN12, and the following relation is satisfied:  $0 < IN12/f \leq 60$ .

17. The optical image capturing system of claim 10, wherein contrast transfer rates of modulation transfer with spatial frequencies of 55 cycles/mm of an infrared operation wavelength 850 nm at the optical axis on the image plane, 0.3 HOI and 0.7 HOI are respectively denoted by MTFI0, MTFI3 and MTFI7, and the following relations are satisfied:  $MTFI0 \geq 0.01$ ,  $MTFI3 \geq 0.01$  and  $MTFI7 \geq 0.01$ .

18. The optical image capturing system of claim 10, wherein contrast transfer rates of modulation transfer with spatial frequencies of 110 cycles/mm of a visible light at the optical axis on the image plane, 0.3 HOT and 0.7 HOI are respectively denoted by MTFQ0, MTFQ3 and MTFQ7, and the following relations are satisfied:  $MTFQ0 \geq 0.2$ ,  $MTFQ3 \geq 0.01$  and  $MTFQ7 \geq 0.01$ .

19. The optical image capturing system of claim 10, wherein at least one of the first, the second, the third, the fourth, the fifth and the sixth lens elements is a light filtration element with a wavelength of less than 500 nm.

20. An optical image capturing system, from an object side to an image side, comprising:

- a first lens element with positive refractive power;
- a second lens element with negative refractive power;
- a third lens element with refractive power;
- a fourth lens element with refractive power;
- a fifth lens element with refractive power;
- a sixth lens element with refractive power, and

an image plane;

wherein the optical image capturing system consists of six lens elements with refractive power and at least one of the six lens elements is made of plastic, a maximum height for image formation on the image plane perpendicular to an optical axis in the optical image capturing system is denoted by HOT, at least one of the first through sixth lens elements has at least one inflection point on at least one surface thereof, an object-side surface and an image-side surface of at least one of the six lens elements are aspheric, focal lengths of the first through sixth lens elements are  $f_1$ ,  $f_2$ ,  $f_3$ ,  $f_4$ ,  $f_5$  and  $f_6$  respectively, a focal length of the optical image capturing system is  $f$ , an entrance pupil diameter of the optical image capturing system is HEP, a half of maximum view angle of the optical image capturing system is HAF, a distance on the optical axis from an axial point on an object-side surface of the first lens element to an axial point on the image plane is HOS, a horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to the image plane is ETL, a horizontal distance in parallel with the optical axis from a coordinate point on the object-side surface of the first lens element at height  $\frac{1}{2}$  HEP to a coordinate point on an image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP is EIN, and the following relations are satisfied:  $1.2 \leq f/HEP \leq 3.5$ ,  $0.4 \leq |\tan(HAF)| \leq 6.0$ ,  $HOI > 3.0$  mm and  $0.2 \leq EIN/ETL < 1$ .

21. The optical image capturing system of claim 20, wherein a horizontal distance in parallel with the optical axis from a coordinate point on the image-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP to the image plane is EBL, a horizontal distance in parallel with the optical axis from an axial point on the image-side surface of the sixth lens element to the image plane is BL, and the following relation is satisfied:  $0.1 \leq EBL/BL \leq 1.1$ .

22. The optical image capturing system of claim 21, wherein a horizontal distance in parallel with the optical axis from a coordinate point on an image-side surface of the fifth lens element at height  $\frac{1}{2}$  HEP to a coordinate point on an object-side surface of the sixth lens element at height  $\frac{1}{2}$  HEP is ED56, a distance from the fifth lens element to the sixth lens element on the optical axis is IN56, and the following relation is satisfied:  $0 < ED56/IN56 \leq 50$ .

23. The optical image capturing system of claim 20, wherein a distance from the fifth lens element to the sixth lens element on the optical axis is IN56, and the following relation is satisfied:  $0 < IN56/f \leq 5.0$ .

24. The optical image capturing system of claim 23, wherein the optical image capturing system satisfies the following relation:  $0 \text{ mm} < HOS \leq 50 \text{ mm}$ .

25. The optical image capturing system of claim 23, further comprising an aperture stop, an image sensing device and a driving module, the image sensing device is disposed on the image plane, a distance from the aperture stop to the image plane on the optical axis is InS, the driving module and the six lens elements couple to each other and shifts are produced for the six lens elements, and the following relation is satisfied:  $0.1 \leq InS/HOS \leq 1.1$ .