



US010330323B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 10,330,323 B2**
(45) **Date of Patent:** **Jun. 25, 2019**

(54) **COOKING DEVICE**

(71) Applicant: **LG ELECTRONICS INC.**, Seoul (KR)
(72) Inventors: **Seungyoun Kim**, Seoul (KR); **Jongho Lee**, Seoul (KR); **Youngsoo Kim**, Seoul (KR)
(73) Assignee: **LG ELECTRONICS INC.**, Seoul (KR)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 317 days.

(21) Appl. No.: **15/195,651**
(22) Filed: **Jun. 28, 2016**

(65) **Prior Publication Data**
US 2017/0082294 A1 Mar. 23, 2017

(30) **Foreign Application Priority Data**
Sep. 21, 2015 (KR) 10-2015-0133018

(51) **Int. Cl.**
F24C 3/00 (2006.01)
F24C 3/08 (2006.01)
F24C 3/12 (2006.01)
F24C 15/32 (2006.01)
F24C 15/34 (2006.01)

(52) **U.S. Cl.**
CPC *F24C 3/082* (2013.01); *F24C 3/004* (2013.01); *F24C 3/087* (2013.01); *F24C 3/122* (2013.01); *F24C 15/322* (2013.01); *F24C 15/34* (2013.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,698,377 A *	10/1972	Smith	F24C 15/322
				126/21 A
3,719,180 A *	3/1973	Pere	A21B 1/26
				126/21 A
4,211,909 A	7/1980	Yoshida et al.		
4,498,453 A *	2/1985	Ueda	F24C 15/322
				126/21 A
4,627,409 A *	12/1986	Kagomoto	F24C 15/322
				126/19 R
4,648,377 A *	3/1987	Van Camp	F24C 15/322
				126/21 A
4,813,398 A *	3/1989	Savage	F24C 15/322
				126/21 A
4,823,766 A *	4/1989	Violi	F24C 15/327
				126/20

(Continued)

FOREIGN PATENT DOCUMENTS

CA	1114262 A	12/1981
EP	0 105 931 A1	4/1984


(Continued)

Primary Examiner — Avinash A Savani
Assistant Examiner — Martha M Becton
(74) *Attorney, Agent, or Firm* — Dentons US LLP

(57) **ABSTRACT**

A cooking device including a frame that defines a cooking chamber, a burner cover provided in the frame to form a combustion chamber and includes an opening for flowing air, a burner provided inside the combustion chamber, and a barrier member provided between the burner cover and the frame in order to prevent heat of air discharged from the combustion chamber from being delivered to the frame.

20 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,867,132 A * 9/1989 Yenchu F24C 15/322
 126/21 A
 4,909,236 A * 3/1990 Del Fabbro F24C 15/322
 126/21 A
 5,121,737 A * 6/1992 Yenchu, III F24C 15/322
 126/21 A
 5,471,972 A * 12/1995 Corliss, II F24C 14/025
 126/21 A
 5,568,803 A * 10/1996 Brown F24C 15/322
 126/21 A
 6,371,104 B1 * 4/2002 Voohris F24C 15/322
 126/21 A
 7,071,448 B1 * 7/2006 Kim F24C 15/16
 126/333
 9,534,791 B2 * 1/2017 Wie F24C 3/025
 9,874,357 B2 * 1/2018 Wie H05K 999/99
 9,939,159 B2 * 4/2018 Wie F24C 3/004
 2003/0164167 A1 * 9/2003 Van Vleet F24C 3/006
 126/512
 2005/0056267 A1 * 3/2005 Levi F24C 15/322
 126/21 R
 2006/0278214 A1 * 12/2006 Park F24C 15/006
 126/273 R
 2009/0032521 A1 * 2/2009 Kim F24C 15/18
 219/400

2009/0045184 A1 * 2/2009 Nam F24C 15/322
 219/400
 2009/0104037 A1 * 4/2009 Kellermann F04D 29/263
 416/204 R
 2010/0006085 A1 * 1/2010 Thomas F24C 15/325
 126/21 A
 2010/0263656 A1 * 10/2010 Ryu F23D 14/065
 126/39 E
 2013/0333685 A1 * 12/2013 Jeong F24C 15/322
 126/21 A
 2014/0144422 A1 * 5/2014 Wie F24C 3/087
 126/39 E
 2014/0144423 A1 * 5/2014 Wie F24C 15/322
 126/39 E
 2015/0285509 A1 * 10/2015 Wie F24C 3/004
 126/273 R
 2015/0285510 A1 * 10/2015 Wie F24C 3/025
 126/273 R
 2015/0285514 A1 * 10/2015 Wie H05K 999/99
 126/21 A

FOREIGN PATENT DOCUMENTS

JP 8-285285 A 11/1996
 JP 2013-217630 A 10/2013
 KR 10-2004-0088708 A 10/2004
 KR 10-2014-0067749 A 6/2014

* cited by examiner

Fig. 1




Fig. 2




Fig.3




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9





Fig.10



1**COOKING DEVICE****CROSS-REFERENCE TO RELATED APPLICATION**

The present application claims priority under 35 U.S.C. 119 and 35 U.S.C. 365 to Korean Patent Application No. 10-2015-0133018 (filed on Sep. 21, 2015), which is hereby incorporated by reference in its entirety.

BACKGROUND

A cooking device is a device for cooking food using a heating source.

One type of conventional cooking device is a gas oven range, such as described in Korean Patent Publication No. 10-2014-0067749 (published on Jun. 5, 2014). The gas oven range described therein includes a burner being supported by a support plate. The support plate is provided at the rear wall of a cavity of the oven.

Air heated by the burner passes through an opening in the support plate and flows into a space between the support plate and the rear wall of the cavity. An inner circumferential surface of the cavity includes an enamel coating layer to protect the inner circumferential surface of the cavity from heat or impact. However, with this configuration, the heated air passing through the opening in the support plate comes in direct contact the rear wall of the cavity, which may cause the enamel coating layer to break or damage. The present disclosure solves this problem.

SUMMARY

The present disclosure provides a cooking device that prevents an enamel coating layer from breaking as a result of air heated by a burner. Additionally, the present disclosure provides a cooking device capable of causing air heated by a burner to smoothly flow to a cooking chamber.

According to an aspect of the present disclosure, a cooking device includes: a frame that defines a cooking chamber; a burner cover provided inside the frame to form a combustion chamber, the burner cover having an opening for air to flow; a burner provided inside the combustion chamber; and a barrier member provided between the burner cover and the frame, wherein the barrier member prevents air that is discharged from the combustion chamber from contacting the frame.

According to yet another aspect of the present disclosure, a cooking device includes: a frame that defines a cooking chamber; a barrier member attached to the frame; a burner cover fastened to the barrier member and spaced apart from the frame; a combustion chamber having a burner provided therein; a fan motor provided outside of the frame, the fan motor having a shaft connected thereto that passes through the frame and the barrier member; and a fan connected to the shaft of the fan motor, the fan being disposed between the burner cover and the frame.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiments of the invention and together with the description serve to explain the principle of the invention. In the drawings:

2

FIG. 1 is a perspective view of a cooking device according to an embodiment of the present disclosure.

FIG. 2 is a front view of a cooking device according to an embodiment of the present disclosure, in a state in which a door of the cooking device is removed.

FIG. 3 is a diagram showing a state in which a burner assembly is removed from the embodiment shown in FIG. 2.

FIG. 4 is an exploded perspective view of a burner assembly according to an embodiment of the present disclosure.

FIG. 5 is a perspective view of a burner device according to an embodiment of the present disclosure.

FIG. 6 is a perspective view of a barrier member according to an embodiment of the present disclosure.

FIG. 7 is a cross-sectional view taken along line A-A of the embodiment shown in FIG. 6.

FIG. 8 is a view showing a cover fastener of a barrier member according to an embodiment of the present disclosure.

FIG. 9 is a diagram showing a state in which a burner cover is fastened to a barrier member according to an embodiment of the present disclosure.

FIG. 10 is a cross-sectional view showing a state in which a burner assembly is fastened to a rear wall of a frame according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Reference will now be made in detail to embodiments of the present disclosure, examples of which are illustrated in the accompanying drawings.

Hereinafter, exemplary embodiments of the present disclosure will be described with reference to the accompanying drawings. Regarding the reference numerals assigned to the elements in the drawings, it should be noted that the same elements may be designated by the same reference numerals, wherever possible, even though they are shown in different drawings. Also, in the description of embodiments, detailed description of well-known related structures or functions may be omitted when it is deemed that such description may cause ambiguous interpretation of the present disclosure.

Also, in the description of embodiments, terms such as first, second, A, B, (a), (b) or the like may be used herein when describing components of the present invention. Each of these terminologies is not used to define an essence, order or sequence of a corresponding component but used merely to distinguish the corresponding component from other component(s). It should be noted that if it is described in the specification that one component is "connected," "coupled" or "joined" to another component, the former may be directly "connected," "coupled," and "joined" to the latter or "connected," "coupled," and "joined" to the latter via another component.

FIG. 1 is a perspective view of a cooking device according to an embodiment of the present disclosure, and FIG. 2 is a front view when a door is removed from the cooking device according to the embodiment of the present disclosure.

Referring to FIGS. 1 and 2, a cooking device 1 may include an oven unit 20. As shown, the cooking device 1 may further include a cook-top unit 60, a drawer unit 40, a control unit 50, and/or an outer case 11. The outer case 11 may cover both side surfaces and rear surfaces of the oven

3

unit **20** and the drawer unit **40**. It is understood, however, that the cook-top unit **60** and the drawer unit **40** may be omitted.

The cook-top unit **60**, the oven unit **20**, and the drawer unit **40** may be provided at an upper portion, a center portion, and a lower portion of the cooking device **1**, respectively. Further, the control unit **50** may be provided at a rear portion of an upper surface of the cooking device **1**.

The cook-top unit **60** may include a plurality of cook-top burners **61**, which may be used to heat items or cook food by burning a gas. An operational unit **62** to operate the plurality of cook-top burners **61** may be provided at a front end of the cook-top unit **60**. Alternatively, the operational unit **62** may be provided at an upper surface of the cook-top unit **60**.

According to another embodiment of the present disclosure, the cook-top unit **60** may include one or more electric heaters. However, the one or more electric heaters may not be exposed to the outside of the cook-top unit **60**.

The oven unit **20** may include a frame **21** that forms a cooking chamber **22** in which the heating or cooking of food is performed. For example, the frame **21** may have a rectangular parallelepiped shape of which a front surface is open, but the frame is not limited to such shape.

The oven unit **20** may further include a burner assembly **23** to heat or cook food accommodated in the cooking chamber **22**. The oven unit **20** may further include an upper burner **24**. The burner assembly **23** and the upper burner **24** may simultaneously heat the food, or any one of the burner assembly **23** and the upper burner **24** may heat the food. For example, the upper burner **24** may provide heat to the food from above the food in the frame **21**, and the burner assembly **23** may be provided at the rear of the food in the frame **21**. The upper burner **24** may be installed at an upper wall of the frame **21**, and the burner assembly **23** may be installed at a rear wall of the frame **21**.

The oven unit **20** may further include a door **25** to provide access to the cooking chamber **22**. The door **25** may be rotatably connected to the cooking device **1**. For example, the door **25** may be a pull-down door such that the door **25** opens and closes the cooking chamber **22** in a pull-down method in which an upper end is vertically rotated about a lower end. It is understood, however, that the door **25** is not limited to any particular configuration or opening/operating method.

The door **25** may further include a door handle **26**. For example, the door handle **26** may be gripped by a user hand to rotate the door **25**. The door handle **26** may be provided at an upper end of a front surface of the door **25**.

The drawer unit **40** functions to maintain the container, in which the food or item is stored, at a predetermined temperature. The drawer unit **40** may include a drawer **41** in which the container is accommodated. The drawer **41** may be inserted into or withdrawn from the cooking device **1** in a sliding method, but is not limited thereto. A handle **42** may be provided at a front surface of the drawer **41** so that a user can pull the drawer in a sliding method.

The control unit **50** may receive an operation signal for operating the cooking device **1**, e.g., an operation signal to operate at least one of the cook-top unit **60**, the oven unit **20** and the drawer unit **40**. Further, the control unit **50** may display a variety of information relating to the operation of the cooking device **1**.

FIG. **3** is a view illustrating the burner assembly removed from the cooking device shown in FIG. **2**, FIG. **4** is an exploded perspective view of the burner assembly, and FIG.

4

5 is a perspective view of a burner device according to an embodiment of the present disclosure.

Referring to FIGS. **2** through **5**, the frame **21** may include two sidewalls **31**, a bottom wall **32**, an upper wall **33**, and a rear wall **35**. Here, the term “front” refers to a direction toward a front surface of the cooking device **1**, and the term “rear” refers to a direction toward a rear surface of the cooking device **1**. Further, in the cooking chamber **22**, the term “front” refers to a direction toward the door **25** of the oven unit **20**, and the term “rear” refers to a direction toward the rear wall **35** of the frame **21**.

The burner assembly **23** may be attached to the rear wall **35** of the frame **21**. That is, in the embodiment, since the burner assembly **23** is not located under the frame **21** but is installed at the rear wall **35** of the frame **21**, a recessed portion **32a** recessed downward may be formed at the bottom wall **32** of the frame **21**, and thus a capacity of the frame **21** may be increased. Although the above-described burner assembly **23** is provided or installed at the rear wall **35** of the frame **21**, it is understood that the burner assembly **23** may instead be provided at any one of both of the sidewalls **31** of the frame **21**.

The burner assembly **23** may include a burner device **100**. The burner device **100** may include a burner **110** to generate a flame by burning a mixture gas in which the gas and air are mixed, and a burner cover **130** to cover the burner **110**.

Both ends of the burner **110** may be spaced apart from each other. The burner **110** may have a non-annular shape.

The burner **110** may comprise a plurality of gas outlet holes **114**. For example, the burner **110** may comprise an inner periphery and an outer periphery, and the plurality of gas outlet holes **114** may be defined on the inner periphery of the burner **110**, but the burner **110** structure is not limited thereto.

The burner assembly **23** may further include an assembly cover **190** to cover the burner device **100**. Additionally, the burner assembly **23** may include a fan **210** and a fan motor **212**.

A burner hole **36** through which the burner **110** passes may be formed in the rear wall **35** of the frame **21**. For example, the burner **110** may be provided in the frame **21** and a part thereof may pass through the burner hole **36** to be located between the rear wall **35** of the frame **21** and the outer case **11**.

An exhaust hole **34** through which an exhaust gas is discharged may be formed in the upper wall **33** of the frame **21**. Alternatively, the exhaust hole **34** may be formed in the rear wall **35** or one of both of the sidewalls **31** of the frame **21**.

The burner cover **130** defines a combustion chamber **C** in which gas is burned. A portion of the burner **110** may be provided in the combustion chamber **C**.

The burner cover **130** may include a first cover **140** and a second cover **160**. For example, at least a portion of the first cover **140** may cover the front of the burner **110**, and at least a portion of the second cover **160** may cover the rear of the burner **110**.

The first cover **140** may include a first opening **142** through which air within the cooking chamber **22** passes, and the second cover may include a second opening **162** through which air passing through the first opening **142** passes.

Additionally, the first cover **140** may include a first cover fastening hole **144** and the second cover **160** may include a second cover fastening hole **146**. The first cover **140** and the second cover **160** may be coupled together via a fastening member that is fastened to the cover fastening hole **144**.

5

The first cover **140** may include a first barrier fastening hole **146** and the second cover **160** may include a second barrier fastening hole **166**. The fastening member may pass through the barrier fastening holes **146** and **166** and fastened to the barrier member **240**. According to the present disclosure, as the fastening member passes through the first cover **140** and the second cover **160**, a fastening force of the first cover **140** and the second cover **160** may increase.

The burner device **100** may further include an ignition unit **230** to ignite the mixed gas supplied to the burner **110**. For example, the ignition unit **230** may be installed on the burner **110** in the frame **21**. When the ignition unit **230** is installed on the burner **110**, at least a part of the ignition unit **230** may be located in the burner cover **130**.

The fan motor **212** may be provided between the rear wall **35** of the frame **21** and the outer case **11**, and the fan **210** may be located in the frame **21**. A shaft **213** of the fan motor **212** may pass through the rear wall **35** of the frame **21** and may be coupled to the fan **210**. The fan motor **212** may be fixed to the rear wall **35** of the frame **21** or the outer case **11** by a motor mount (not shown).

The assembly cover **190** may protect the burner device **100**. The assembly cover **190** may also block or prevent food or the like from contacting the burner device **100**.

The assembly cover **190** may include a front plate **191**, an extension part **193** extending from the front plate **191** toward the rear wall **35** of the frame **21**, and a contact part **195** bent from the extension part **193**.

An air suction hole **192** through which air within the cooking chamber **22** is suctioned is provided on the front plate **191**, and an air discharge hole **194** through which air heated by the burner device **100** is discharged into the cooking chamber **22** is provided on the extension part **193**. In another example, the air discharge hole **194** may be provided on the front plate **191** or provided on each of the front plate **191** and the extension part **193**.

Air passing through the air suction hole **192** is introduced into the combustion chamber **C** via the first opening **142** of the first cover **140**.

The contact part **195** may contact the rear wall **35** of the frame **21** when the contact part **195** covers the burner device **100**. A coupling hole **196** to which a coupling member (not shown) is coupled may be provided on the contact part **195**.

A lower end of the assembly cover **190** may contact the bottom wall **32** of the frame **21** when the assembly cover **190** is coupled to the rear wall **35** of the frame **21** by the coupling member. That is, the front plate **191** and lower ends of the extension part **193** and the contact part **195** may contact the bottom wall **32** of the frame **21**. Alternatively, the front plate **191** and the extension part **193** may contact the bottom wall **32** of the frame **21**.

Here, the assembly cover **190** may contact the bottom wall **32** of the frame **21** between the recessed portion **32a** of the bottom wall **32** and the rear wall **35** of the frame **21**.

The burner assembly **23** may further include a nozzle holder **220**. The nozzle holder **220** may be provided between the rear wall **35** of the frame **21** and the outer case **11**. For example, the nozzle holder **220** may be attached to the rear wall **35** of the frame **21**. In another example, if an insulator is provided outside of the cavity **21**, the nozzle holder **220** may be provided on the insulator. The nozzle holder **220** may be aligned with the burner **110** passing through the rear wall **35** of the frame **21** to spray gas into the burner **110**.

The burner device **100** may further include a barrier member **240** to block or reduce heat generated by the burner **110** or air heated by the burner **110** from being delivered to the rear wall **35** of the frame **21**. The barrier member **240**

6

may be, for example, provided on the rear wall **35** of the frame **21** and the burner cover **230** may be provided on the barrier member **240**.

At least one first fastening hole **37** and at least one second fastening hole **38** for fastening the barrier member **240** may be formed in the rear wall **35** of the frame **21**.

The fastening structure of the barrier member **240** will be described below in more detail with reference to the figures.

FIG. **6** is a perspective view of a barrier member according to an embodiment of the present disclosure, FIG. **7** is a cross-sectional view taken along line A-A of FIG. **6**, and FIG. **8** is a view showing a cover fastener of a barrier member according to an embodiment of the present disclosure.

Referring to FIG. **3** and FIGS. **6** through **8**, the barrier member **240** may include a barrier plate **241** capable of being in contact with the rear wall **35** of the frame **21**.

A shaft through-hole **243**, through which a shaft **213** of the fan motor **212** passes, may be formed in the barrier plate **241**. The diameter of the shaft through-hole **243** may be larger than that the diameter of the fan **210**.

The barrier member **240** may be separated from the frame **21** to be drawn out of the cooking chamber **22** when the fan **210** is attached to the shaft **213** of the fan motor **212**. In addition, the barrier member **240** may be fastened to the frame **21** without interfering with the fan **210** when the fan **210** is attached to the shaft **213** of the fan motor **212**. In addition, the barrier member **240** may be fastened to the frame **21** without interfering with the fan **210** when the fan **210** is attached to the shaft **213** of the fan motor **212**. Accordingly, the assembly order of the burner assembly **23** may be diversified, which can improve operation performance and make the structure easier to service.

A burner through-hole **242**, through which the burner **110** passes, may be provided in the barrier plate **241**.

The burner **110** may pass through the second cover **160**, the burner through-hole **242** of the barrier plate **241**, and the burner hole **36** of the frame **21**, when it is received in the burner cover **130**.

A wire (not shown) may be connected to the ignition unit **230** and pass through the burner through-hole **242**. For protection, a flange **242a** may be formed in the barrier plate **241** to prevent the wire from being damaged. For example, the flange **242a** may be formed by a burring process.

The diameter of the burner through-hole **242** may be less than the diameter of the burner hole **36**. The flange **242a** may be received in the burner hole **36** or may pass through the burner hole **36**.

A frame fastening hole **248** to fasten with the frame **21** may be further provided in the barrier plate **241**.

The barrier member **240** may further include a cover fastener **250** to fasten with the burner cover **130**.

The cover fastener **250** may extend from the barrier plate **241**. For example, the cover fastener **250** may be formed by cutting and/or bending a portion of the barrier plate **241**. Alternatively, the cover fastener **250** may be manufactured as a separate structure to be fastened to the barrier plate **241**.

The cover fastener **250** may include an extension **251** that extends from an end of the barrier plate **241** and a fastening body **252** that is bent from an end of the extension **251** and fastened to the burner cover **130**.

Although not limited thereto, the extension **251** and the fastening body **252** may be approximately at a right angle with respect to each other.

To prevent a reduction in the internal volume of the cooking chamber **22** when the burner cover **130** is fastened to the cover fastener **250**, the horizontal distance from the

shaft through-hole **243** to the second opening **162** of the burner cover **130** may be shorter than the horizontal length of the cover fastener **250**.

The fastening body **252** may extend in a vertical direction. A fastening hole **253** may be formed in the fastening body **252**. The fastening member passing through the burner cover **130** may be fastened to the fastening hole **253**.

A strength reinforcement unit **254** may be provided on the extension **251** to provide strength reinforcement thereto. The strength reinforcement unit **252** may protrude or be recessed to one side by a press working process.

In addition, a strength reinforcement unit **255** may be formed on a part of the barrier plate **241**, in which the cover fastener **250** is located, and in the vicinity of the part of the barrier plate. Although not limited thereto, the strength reinforcement unit **254** of the extension **251** and the strength reinforcement unit **254** of the barrier plate **241** may be continuously formed.

The barrier member **240** may further include a frame fastener **247** to fasten with the frame **21**. The frame fastener **247** may extend in a direction that is opposite that of the extension direction of the cover fastener **250** in the barrier plate **241**. The frame fastener **247** may have a hook shape and may pass through the first fastening hole **37** of the frame **21** to engage with the frame **21**.

Meanwhile, the barrier plate **241** may be divided into a vertical part **241a** and an inclination part **241b**, and the shaft through-hole **243** may be located in the inclination part **241b**.

As illustrated, for example, the vertical part **241a** may be a part that is parallel to a vertical line and the inclination part **241b** may be inclined from the vertical line by a predetermined angle.

The frame fastening hole **248** and the frame fastener **247** may be located in the vertical part **241a**.

FIG. **9** is a diagram showing a state in which a burner cover is fastened to a barrier member according to an embodiment of the present disclosure, and FIG. **10** is a cross-sectional view showing a state in which a burner assembly according is fastened to a rear wall of a frame according to an embodiment of the disclosure.

Referring to FIGS. **9** and **10**, the burner cover **130** is fastened to the barrier member **240** by the fastening member **S1** when the barrier member **240** is fastened to the rear wall **35** of the frame **21**. The burner cover **130** is spaced apart from the barrier plate **241** when the burner cover **130** is fastened to the barrier member **240**. Accordingly, an exhaust flow path **P** along which heated air flows is defined between the burner cover **130** and the barrier plate **241**. That is, the barrier plate **241** forms the exhaust flow path **P**.

In the exhaust flow path **P**, the flow path of the inclination part **241b** is larger than the flow path of the vertical part **241a**. However, the width of the exhaust flow path **P** may be reduced from the inclination part **241b** adjacent to the fan **210** (part adjacent to the shaft through-hole) to the vertical part **241a**.

Air discharged from the burner cover **130** may flow along the exhaust flow path **P** by the fan **210** and air discharged from the fan **210** may flow along the inclination part **241b**, thereby improving flowing performance.

Hereinafter, operation of the burner assembly will be described.

Referring to FIGS. **1** to **10**, when the burner assembly **23** starts to operate, gas is sprayed from the nozzle holder **220** to the burner **110**. Then, air located in the vicinity of the gas inlet of the burner **110** (e.g., air outside the frame) is supplied

to the gas inlet of the burner **110** along with gas. The mixed gas is ignited by the ignition unit **230** when it is supplied to the burner **110**.

The fan motor **212** may be powered on to rotate the fan **210**. When the fan **210** rotates, air within the cooking chamber **22** is introduced into the combustion chamber **C** through the air suction hole **192** of the assembly cover **190**. The air introduced into the combustion chamber **C** then passes through the inner circumferential surface of the burner **110**.

The air introduced into the combustion chamber **C** is heated by the flame generated by the burner **110** and is discharged from the combustion chamber **C**. The air discharged from the combustion chamber **C** flows along the exhaust flow path **P** between the burner cover **130** and the barrier plate **241**. The air is then discharged to the cooking chamber **22** through the air discharge hole **194** of the assembly cover **190**.

According to an embodiment of the present disclosure, the burner cover **130** forms an independent combustion chamber **C**, and the combustion chamber **C** and the exhaust flow path **P** are partitioned by the burner cover **130**. Thus, air flowing along the exhaust flow path **P1** may be prevented from being reintroduced into the combustion chamber **C**.

Additionally, according to an embodiment of the present disclosure, as the barrier member **240** forms the exhaust flow path **P**, a contact area between the heated air and the rear wall **35** of the frame **21** can be reduced so as to prevent the enamel coating layer coated on the rear wall **35** of the frame **21** from being damaged.

Although embodiments have been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure. More particularly, various variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

What is claimed is:

1. A cooking device, comprising:

a frame to form a cooking chamber;

a burner cover provided in the frame to form a combustion chamber;

a burner provided inside the combustion chamber;

the burner cover comprising a first cover covering a front of the burner and a second cover such that at least a portion of the second cover covers a rear of the burner, wherein the first cover includes a first opening through which air from within the cooking chamber passes and the second cover includes a second opening through which air heated by the burner in the combustion chamber exits the burner cover; and

a barrier member provided between the burner cover and a rear wall of the frame to form an exhaust flow path for the heated air to prevent damage to the rear wall of the frame by the heat of air discharged from the combustion chamber,

wherein air heated by the burner in the combustion chamber passes through the second hole, passes through the exhaust flow path between the burner cover and the barrier member, and is discharged to the cooking chamber.

9

2. The cooking device of claim 1, further comprising:
a fan motor provided outside of the frame; and
a fan connected to a shaft of the fan motor within the
frame,
wherein the barrier member includes a shaft through-hole 5
that receives the shaft.
3. The cooking device of claim 2, wherein:
the fan is provided between the frame and the burner
cover, and
the diameter of the shaft through-hole is larger than the 10
diameter of the fan.
4. The cooking device of claim 2, wherein:
the barrier member includes a vertical part and an incli-
nation part that is inclined relative to the vertical part,
and 15
the shaft through-hole is provided in the inclination part.
5. The cooking device of claim 4, wherein:
an exhaust flow path is provided between the burner cover
and the barrier member to guide air from the combus-
tion chamber to the cooking chamber, and 20
the exhaust flow path is wider at the inclination part than
at the vertical part.
6. The cooking device of claim 5, wherein the width of the
exhaust flow path decreases from a part adjacent to the shaft
through-hole of the inclination part to the vertical part. 25
7. The cooking device of claim 1, wherein the barrier
member is attached to the frame.
8. The cooking device of claim 7, wherein the barrier
member includes:
a barrier plate that contacts the frame; and 30
a cover fastener extending from the barrier plate, whereby
the cover fastener is configured to fasten with the
burner cover.
9. The cooking device of claim 8, wherein the cover
fastener includes: 35
an extension portion that extends from the barrier plate;
and
a fastening body that is bent from an end of the extension
portion, whereby the fastening body is configured to 40
fasten with the burner cover.
10. The cooking device of claim 9, wherein the extension
portion includes a strength reinforcement unit.
11. The cooking device of claim 8, wherein a strength
reinforcement unit for strength reinforcement is formed on 45
a portion of the barrier plate where the burner fastener is
located.
12. The cooking device of claim 8, wherein:
the fastening body includes a fastening hole that is
configured to fasten with a fastening member, and 50
the burner cover includes a first cover and a second cover,
whereby the fastening member passes through the first
and second covers and is fastened with the fastening hole.
13. The cooking device of claim 12, wherein the opening
of the burner cover includes a first opening provided in the
first cover and a second opening provided in the second 55
cover.
14. The cooking device of claim 1, wherein the barrier
member further includes a burner through-hole through
which the burner passes.

10

15. The cooking device of claim 14, further comprising:
an ignition unit to ignite a mixed gas, the ignition unit
having a wire connected thereto, and
a flange formed in the barrier plate, the flange configured
to prevent damage to the wire.
16. A cooking device, comprising:
a frame to form a cooking chamber;
a burner cover provided in the frame to form a combustion
chamber;
a burner provided inside the combustion chamber;
the burner cover comprising a first cover covering a front
of the burner and a second cover such that at least a
portion of the second cover covers a rear of the burner,
wherein the first cover includes a first opening through
which air from within the cooking chamber passes
and the second cover includes a second opening
through which air heated by the burner in the com-
bustion chamber exits the burner cover;
a barrier member attached to the frame to form an exhaust
flow path for the heated air to prevent damage to the
rear wall of the frame by the heat of air discharged from
the combustion chamber;
a fan motor provided outside of the frame, the fan motor
having a shaft connected thereto that passes through the
frame and the barrier member;
a fan connected to the shaft of the fan motor, the fan being
disposed between the burner cover and the frame; and
wherein the burner cover is attached to the barrier mem-
ber within the frame and spaced apart from the frame
such that air heated by the burner in the combustion
chamber passes through the second hole, passes
through the exhaust flow path between the burner cover
and the barrier member, and is discharged to the
cooking chamber.
17. The cooking device of claim 16, wherein the barrier
member comprises:
a barrier plate that contacts the frame; and
a cover fastener extending from the barrier plate, whereby
the cover fastener is configured to fasten with the
burner cover.
18. The cooking device of claim 17, wherein:
the barrier member includes a shaft through-hole to
receive the shaft of the fan motor, and
the diameter of the shaft through-hole is larger than the
diameter of the fan.
19. The cooking device of claim 17, wherein:
the burner cover includes an opening through which air
heated by the burner passes, and
a horizontal distance between the shaft through-hole and
the opening is less than a horizontal length of the cover
fastener.
20. The cooking device of claim 17, further comprising:
an extension portion that extends from the barrier plate;
and
a fastening body that is bent from an end of the extension
portion, whereby the fastening body is configured to
fasten with the burner cover.

* * * * *