



US010338348B2

(12) **United States Patent**
Chen et al.

(10) **Patent No.:** **US 10,338,348 B2**
(45) **Date of Patent:** **Jul. 2, 2019**

(54) **OPTICAL IMAGE CAPTURING LENS SYSTEM**

(71) Applicant: **LARGAN PRECISION CO., LTD.**,
Taichung (TW)

(72) Inventors: **Kuan-Ming Chen**, Taichung (TW);
Tsung-Han Tsai, Taichung (TW);
Hsin-Hsuan Huang, Taichung (TW)

(73) Assignee: **LARGAN PRECISION CO., LTD.**,
Taichung (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/709,979**

(22) Filed: **Sep. 20, 2017**

(65) **Prior Publication Data**

US 2018/0011300 A1 Jan. 11, 2018

Related U.S. Application Data

(60) Continuation of application No. 14/987,049, filed on Jan. 4, 2016, now Pat. No. 9,798,109, which is a (Continued)

(30) **Foreign Application Priority Data**

Nov. 21, 2012 (TW) 101143390 A

(51) **Int. Cl.**
G02B 9/60 (2006.01)
G02B 13/18 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G02B 13/0045** (2013.01); **G02B 9/60** (2013.01); **G02B 27/0025** (2013.01)

(58) **Field of Classification Search**
CPC G02B 13/0045; G02B 9/60
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,035,063 A 7/1977 Ikeda
8,649,112 B2 2/2014 Tsai et al.
(Continued)

FOREIGN PATENT DOCUMENTS

JP 1983-033211 2/1983
JP 58-132712 A 8/1983
(Continued)


Primary Examiner — William Choi

(74) *Attorney, Agent, or Firm* — Locke Lord LLP; Tim Tingkang Xia, Esq.

(57) **ABSTRACT**

This disclosure provides an optical image capturing lens system comprising: a positive first lens element having a convex object-side surface, a negative second lens element, a positive third lens element having a convex image-side surface, a fourth lens element having a concave object-side surface and a convex image-side surface; and a positive fifth lens element having a convex object-side surface at a paraxial region thereof, both of the object-side and image-side surfaces being aspheric, and at least one inflection point is positioned on at least one of the object-side and image-side surfaces thereof. When particular relations are satisfied, the angle at which light projects onto the image plane can be efficiently controlled for increasing the relative illumination and preventing the occurrence of vignetting.

26 Claims, 21 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/573,997, filed on Dec. 17, 2014, now Pat. No. 9,261,677, which is a division of application No. 13/785,453, filed on Mar. 5, 2013, now Pat. No. 8,922,909.

(51) **Int. Cl.**

G02B 13/00 (2006.01)

G02B 27/00 (2006.01)

(58) **Field of Classification Search**

USPC 359/714, 753, 763, 764, 766

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2013/0335833 A1* 12/2013 Liao G02B 13/0045
359/713

2014/0015997 A1 1/2014 Baba

2014/0063621 A1* 3/2014 Hsueh G02B 13/0045
359/714

FOREIGN PATENT DOCUMENTS

JP 1984-083121 5/1984

JP 1985-198512 10/1985

JP 1985-201314 10/1985

JP 2011-085733 A 4/2011

* cited by examiner




Fig. 1A




Fig. 1B




Fig. 2A




Fig. 2B




Fig. 3A




Fig. 3B




Fig. 4A




Fig. 4B




Fig. 5A




Fig. 5B




Fig. 6A




Fig. 6B




Fig. 7A




Fig. 7B




Fig. 8A




Fig. 8B




Fig. 9A




Fig. 9B




Fig. 10A




Fig. 10B




Fig. 11

OPTICAL IMAGE CAPTURING LENS SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of U.S. application Ser. No. 14/987,049 filed on Jan. 4, 2016, now approved, which is a continuation application of U.S. application Ser. No. 14/573,997 filed on Dec. 17, 2014, which is a divisional application of U.S. application Ser. No. 13/785,453 filed on Mar. 5, 2013, which claims priority under 35 U.S.C. 119(e) to Taiwan Application Serial No. 101143390 filed on Nov. 21, 2012, the entire contents of which are incorporated by reference herein.

BACKGROUND

Field of the Disclosure

The present disclosure relates to an optical image capturing lens system, and more particularly, to a compact optical image capturing lens system used in electronic products.

Description of the Related Art

The demand for compact imaging lens assembly has grown in recent years as the popularity of portable electronic products with the photographing function has increased. The sensor of a general photographing camera is none other than CCD (Charge Coupled Device) or CMOS (Complementary Metal Oxide Semiconductor) sensor. Furthermore, as the advanced semiconductor manufacturing technology has allowed the pixel size of sensors to be reduced, and the current electronic products are leaning toward a trend of being more compact, there is an increasing demand for higher image quality.

A conventional compact imaging lens system with high image quality equipped on a portable electronic product is often composed of four lens elements such as the lens system set forth in U.S. Pat. No. 8,179,470. However, with the popularity of high level portable electronic products, such as smart phone and PDA (Personal Digital Assistant), the demand for the pixel size and image quality of compact imaging lens system increase fast, and the conventional lens system with four lens elements can no longer satisfy the imaging lens systems of even higher level. Although lens systems adopting five lens elements begin to emerge recently, such as the lens system set forth in U.S. Pat. No. 8,000,030, the lens system struggles in handling the off-axis incident-light so that it tends to have a vignetting effect in the formed image and the relative illumination of the lens system is so low that the image quality becomes undesirable.

In light of the foregoing, an optical image capturing lens system that is suitable for portable electronic devices and has excellent image quality is in need; especially for those whose fifth lens element is configured with stronger positive reflective power, which is favorable for positioning the principle point away toward the image plane. Thus, the angle of incidence from the off-axis field can be effectively controlled for improving relative illumination of peripheral Image and preventing the occurrence of vignetting, which are favorable for improving image quality.

SUMMARY

The present disclosure provides an optical image capturing lens system, in order from an object side to an image side comprising five lens elements with refractive power: a first lens element with positive refractive power having a convex

object-side surface; a second lens element with negative refractive power; a third lens element with positive refractive power having a convex image-side surface; a fourth lens element with refractive power having a concave object-side surface and a convex image-side surface; and a fifth lens element with positive refractive power having a convex object-side surface at a paraxial region, both of the object-side and image-side surfaces being aspheric, and at least one inflection point is formed on at least one of the object-side surface and the image-side surface thereof; wherein the lens elements with refractive power in the optical image capturing lens system are the first lens element, the second lens element, the third lens element, the fourth lens element, and the fifth lens element; wherein a focal length of the optical image capturing lens system is f , a focal length of the fifth lens element is f_5 , a curvature radius of the object-side surface of the fifth lens element is R_9 , a curvature radius of the object-side surface of the first lens element is R_1 , a curvature radius of the object-side surface of the third lens element is R_5 , a curvature radius of the image-side surface of the third lens element is R_6 , and they satisfy the following relations: $0.55 < f/f_5 < 2.0$; $0 < R_9/R_1 < 1.7$; and $0.2 < (R_5 + R_6)/(R_5 - R_6) < 2.5$.

On the other hand, the present disclosure provides an optical image capturing lens system, in order from an object side to an image side comprising five lens elements with refractive power: a first lens element with positive refractive power having a convex object-side surface; a second lens element with negative refractive power; a third lens element with positive refractive power having a convex image-side surface; a fourth lens element with negative refractive power having a concave object-side surface and a convex image-side surface, and both of the object-side and image-side surfaces being aspheric; and a fifth lens element with positive refractive power having a convex object-side surface at a paraxial region and a concave image-side surface at a paraxial region, both of the object-side and image-side surfaces being aspheric, and at least one inflection point is formed on at least one of the object-side surface and the image-side surface thereof; wherein the lens elements with refractive power in the optical image capturing lens system are the first lens element, the second lens element, the third lens element, the fourth lens element, and the fifth lens element; wherein a focal length of the optical image capturing lens system is f , a focal length of the fifth lens element is f_5 , a curvature radius of the object-side surface of the third lens element is R_5 , a curvature radius of the image-side surface of the third lens element is R_6 , and they satisfy the following relations: $0.55 < f/f_5 < 2.0$; and $0.2 < (R_5 + R_6)/(R_5 - R_6) < 2.5$.

Furthermore, the present disclosure provides an optical image capturing lens system, in order from an object side to an image side comprising five lens elements with refractive power: a first lens element with positive refractive power having a convex object-side surface; a second lens element with negative refractive power; a third lens element with refractive power; a fourth lens element with negative refractive power having a concave object-side surface and a convex image-side surface, and both of the object-side and image-side surfaces being aspheric; and a fifth lens element with positive refractive power having a convex object-side surface at a paraxial region, both of the object-side and image-side surfaces being aspheric, and at least one inflection point is formed on at least one of the object-side surface and the image-side surface thereof; wherein the lens elements with refractive power in the optical image capturing lens system are the first lens element, the second lens

element, the third lens element, the fourth lens element, and the fifth lens element; wherein a focal length of the optical image capturing lens system is f , a focal length of the fifth lens element is f_5 , a curvature radius of the object-side surface of the fifth lens element is R_9 , a curvature radius of the object-side surface of the first lens element is R_1 , an Abbe number of the fourth lens element is V_4 , an Abbe number of the fifth lens element is V_5 , and they satisfy the following relations: $0.55 < f/f_5 < 2.0$; $0 < R_9/R_1 < 1.7$; and $0.2 < V_4/V_5 < 0.6$.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A shows an optical image capturing lens system in accordance with the first embodiment of the present disclosure.

FIG. 1B shows the aberration curves of the first embodiment of the present disclosure.

FIG. 2A shows an optical image capturing lens system in accordance with the second embodiment of the present disclosure.

FIG. 2B shows the aberration curves of the second embodiment of the present disclosure.

FIG. 3A shows an optical image capturing lens system in accordance with the third embodiment of the present disclosure.

FIG. 3B shows the aberration curves of the third embodiment of the present disclosure.

FIG. 4A shows an optical image capturing lens system in accordance with the fourth embodiment of the present disclosure.

FIG. 4B shows the aberration curves of the fourth embodiment of the present disclosure.

FIG. 5A shows an optical image capturing lens system in accordance with the fifth embodiment of the present disclosure.

FIG. 5B shows the aberration curves of the fifth embodiment of the present disclosure.

FIG. 6A shows an optical image capturing lens system in accordance with the sixth embodiment of the present disclosure.

FIG. 6B shows the aberration curves of the sixth embodiment of the present disclosure.

FIG. 7A shows an optical image capturing lens system in accordance with the seventh embodiment of the present disclosure.

FIG. 7B shows the aberration curves of the seventh embodiment of the present disclosure.

FIG. 8A shows an optical image capturing lens system in accordance with the eighth embodiment of the present disclosure.

FIG. 8B shows the aberration curves of the eighth embodiment of the present disclosure.

FIG. 9A shows an optical image capturing lens system in accordance with the ninth embodiment of the present disclosure.

FIG. 9B shows the aberration curves of the ninth embodiment of the present disclosure.

FIG. 10A shows an optical image capturing lens system in accordance with the tenth embodiment of the present disclosure.

FIG. 10B shows the aberration curves of the tenth embodiment of the present disclosure.

FIG. 11 indicates the distance represented by the relation of Yc_{51} of the present disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present disclosure provides an optical image capturing lens system, which comprises, in order from the object-side to the image-side, a first lens element, a second lens element, a third lens element, a fourth lens element and a fifth lens element.

The first lens element has positive refractive power, which provides the main refractive power of the system, and thereby the total track length of the system is reduced. When the first lens element has a convex object-side surface, the distribution of the positive refractive power thereof can be adjusted for reducing the total optical track length of the system.

The second lens element has negative refractive power, which is favorable for correcting the aberration produced by the first lens element. When the second lens element has a convex object-side surface and a concave image-side surface, it is favorable for correcting the astigmatism of the system and improving image quality.

The third lens element has positive refractive power, which can reduce the sensitivity of the system. When the third lens element has a convex image-side surface, the spherical aberration can be corrected.

The fourth lens element has a negative refractive power, which can correct the aberration of the system. When the fourth lens element has a concave object-side surface and a convex image-side surface, the astigmatism can be corrected.

When the fifth lens element has positive refractive power, the principle point can be positioned away toward the image plane for effectively controlling the angle of incidence from the off-axis field. Thus, the relative illumination of peripheral image can be increased and the occurrence of vignetting can be prevented. When the fifth lens element has a convex object-side surface and a concave image-side surface, the astigmatism can be favorably corrected. When at least one inflection point is formed on at least one of the object-side surface and the image-side surface thereof, the angle of incidence onto the image sensor from the off-axis field can be effectively reduced so that the sensing efficiency of the image sensor can be improved and the off-axis aberration can be corrected.

A focal length of the optical image capturing lens system is f . A focal length of the fifth lens element is f_5 . When the relation of $0.55 < f/f_5 < 2.0$ is satisfied, by configuring stronger positive refractive power for the fifth lens element, the principle point can be positioned away toward the image plane for effectively controlling the angle of incidence from the off-axis field. Thus, the relative illumination of peripheral image can be increased and the occurrence of vignetting can be prevented; preferably, the following relation is satisfied: $0.75 < f/f_5 < 1.8$.

A curvature radius of the object-side surface of the fifth lens element is R_9 . A curvature radius of the object-side surface of the first lens element is R_1 . When the relation of $0 < R_9/R_1 < 1.7$ is satisfied, the distribution of the positive refractive power can be balanced for reducing the sensitivity of the system; preferably, the following relation is satisfied: $0.2 < R_9/R_1 < 1.3$.

A curvature radius of the object-side surface of the third lens element is R_5 . A curvature radius of the image-side surface of the third lens element is R_6 . When the relation of $0.2 < (R_5 + R_6)/(R_5 - R_6) < 2.5$ is satisfied, the spherical aberration can be reduced and the astigmatism can be reduced for improving image quality.

5

An Abbe number of the fourth lens element is V_4 . An Abbe number of the fifth lens element is V_5 . When the relation of $0.2 < V_4/V_5 < 0.6$ is satisfied, the chromatic aberration of the system can be effectively corrected.

An axial distance between the fourth lens element and the fifth lens element is T_{45} . An axial distance between the third lens element and the fourth lens element is T_{34} . When the relation of $0 < T_{45}/T_{34} < 0.35$ is satisfied, the interval distances between lens elements are proper for the assembly of the lens system and the manufacture yield rate thereof can be improved.

A central thickness of the second lens element is CT_2 . A central thickness of the fourth lens element is CT_4 . An axial distance between the second lens element and the third lens element is T_{23} . An axial distance between the third lens element and the fourth lens element is T_{34} . When the relation of $0.5 < (CT_2 + CT_4)/(T_{23} + T_{34}) < 0.9$ is satisfied, the manufacture yield rate can be improved.

A focal length of the fourth lens element is f_4 . A focal length of the second lens element is f_2 . When the relation of $0.1 < f_4/f_2 < 0.85$ is satisfied, the aberration can be favorably corrected.

A curvature radius of the object-side surface of the second lens element is R_3 . A curvature radius of the image-side surface of the second lens element is R_4 . When the relation of $0.05 < (R_3 - R_4)/(R_3 + R_4) < 0.5$ is satisfied, the astigmatism can be reduced and the aberration can be corrected for improving resolution.

A vertical distance with respect to an optical axis between a critical point on the object-side surface of the fifth lens element and the optical axis is Y_{c51} ; wherein the critical point is not on the axis. A focal length of the optical image capturing lens system is f . When the relation of $0.1 < Y_{c51}/f < 0.7$ is satisfied, it is favorable for reducing the angle of incidence onto the image sensor from the off-axis field and further correcting the aberration of off-axis field.

A curvature radius of the object-side surface of the fourth lens element is R_7 . A curvature radius of the image-side surface of the fourth lens element is R_8 . When the relation of $-0.5 < (R_7 - R_8)/(R_7 + R_8) < -0.1$ is satisfied, the astigmatism can be effectively corrected.

An axial distance between the first lens element and the second lens element is T_{12} . An axial distance between the second lens element and the third lens element is T_{23} . When the relation of $0.02 < T_{12}/T_{23} < 0.4$ is satisfied, it is favorable for lens elements assembly and improving manufacture yield rate.

A central thickness of the fourth lens element is CT_4 . A central thickness of the fifth lens element is CT_5 . When the relation of $0.1 < CT_4/CT_5 < 0.40$ is satisfied, it is favorable for the molding and manufacture of lens elements, which is also favorable for obtaining good image quality.

In the aforementioned optical image capturing lens system, the lens elements can be made of glass or plastic materials. If the lens elements are made of glass, the freedom for distributing the refractive power of the optical image capturing lens system can be increased. If plastic material is adopted to produce the lens elements, the production cost will be reduced effectively. Additionally, the surfaces of the lens elements can be aspheric and easily made into non-spherical profiles, allowing more design parameter freedom which can be used to reduce aberrations and the number of the lens elements used in an optical system. Consequently, the total track length of the optical image capturing lens system can be effectively reduced.

In the present optical image capturing lens system, there can be at least one stop provided, such as an aperture stop,

6

a glare stop or a field stop. Said glare stop or said field stop is for eliminating the stray light and thereby improving the image resolution thereof.

In the present optical image capturing lens system, an aperture stop can be configured as a front stop or a middle stop. A front stop can provide a longer distance between an exit pupil of the system and an image plane, and the image-sensing efficiency of an image sensor can be improved. A middle stop is favorable for enlarging the field of view of the system and thereby provides a wider field of view for the same.

According to the optical image capturing lens system of the present disclosure, each of an object-side surface and an image-side surface of every lens element has a paraxial region and a peripheral region. The paraxial region refers to the region of the surface where light rays travel close to an optical axis and the peripheral region refers to the region of the surface where light rays travel away from the optical axis. Particularly, when a lens element has a convex surface, it indicates that the surface is convex at the paraxial region and when the lens element has a concave surface, it indicates that the surface is concave at the paraxial region.

A critical point is referred as a tangential point on a surface of the lens element concerned where the corresponding tangent through the critical point is perpendicular to the optical axis. Please refer to FIG. 11. A vertical distance with respect to the optical axis **1101** between a critical point **1102** on the object-side surface **1151** of the fifth lens element **1150** and the optical axis **1101** is Y_{c51} ; wherein the critical point **1102** is not on the optical axis **1101**.

The present optical image capturing lens system can be optionally applied to MEMS (Micro-Electro-Mechanical System) focusing and zoom optical systems. In addition, as the optical image capturing lens system has the advantages of superior aberration correction ability and finer image quality, it is suitable for applications in imaging systems such as 3D (3 dimensional) image capturing, digital cameras, portable devices, digital tablets and etc.

Preferred embodiments of the present disclosure will be described in the following paragraphs by referring to the accompanying drawings.

Embodiment 1

FIG. 1A shows an optical image capturing lens system in accordance with the first embodiment of the present disclosure, and FIG. 1B shows the aberration curves of the first embodiment of the present disclosure. The optical image capturing lens system of the first embodiment of the present disclosure mainly comprises five lens elements with refractive power, in order from an object side to an image side:

a first lens element **110** made of plastic with positive refractive power having a convex object-side surface **111** and a convex image-side surface **112**, and the object-side and image-side surfaces **111** and **112** thereof being aspheric;

a second lens element **120** made of plastic with negative refractive power having a convex object-side surface **121** and a concave image-side surface **122**, and the object-side and image-side surfaces **121** and **122** thereof being aspheric;

a third lens element **130** made of plastic with positive refractive power having a convex object-side surface **131** and a convex image-side surface **132**, and the object-side and image-side surfaces **131** and **132** thereof being aspheric;

a fourth lens element **140** made of plastic with negative refractive power having a concave object-side surface **141** and a convex image-side surface **142**, the object-side and image-side surfaces **141** and **142** thereof being aspheric; and

a fifth lens element **150** made of plastic with positive refractive power having a convex object-side surface **151** at

7

a paraxial region and a concave image-side surface **152** at a paraxial region, the object-side and image-side surfaces **151** and **152** thereof being aspheric, and at least one inflection point is formed on both of the object-side surface **151** and the image-side surface **152**;

wherein a stop **100**, which is an aperture stop, is disposed between the imaged object and the first lens element **110**; the optical image capturing lens system further comprises an IR-cut filter **160** disposed between the fifth lens element **150**

8

and an image plane **180**, and the IR-cut filter **160** is made of glass and has no influence on the focal length of the optical image capturing lens system.

The detailed optical data of the first embodiment is shown in TABLE 1, and the aspheric surface data is shown in TABLE 2, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 1

(Embodiment 1)								
f = 3.74 mm, Fno = 2.20, HFOV = 37.7 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.175					
2	Lens 1	2.032 ASP	0.470	Plastic	1.544	55.9	3.71	
3		-263.946 ASP	0.030					
4	Lens 2	2.181 ASP	0.250	Plastic	1.650	21.4	-7.06	
5		1.412 ASP	0.284					
6	Lens 3	124.009 ASP	0.551	Plastic	1.544	55.9	5.05	
7		-2.808 ASP	0.498					
8	Lens 4	-0.630 ASP	0.320	Plastic	1.640	23.3	-3.51	
9		-1.049 ASP	0.030					
10	Lens 5	1.268 ASP	1.020	Plastic	1.535	55.7	4.30	
11		2.031 ASP	0.600					
12	IR-filter	Plano	0.300	Glass	1.517	64.2	—	
13		Plano	0.646					
14	Image	Plano	—					

Note:

Reference Wavelength is 587.6 nm (d-line).

TABLE 2

Aspheric Coefficients					
Surface #	2	3	4	5	6
k =	1.0714E+00	5.0000E+00	-1.5565E+01	-6.2105E+00	5.0000E+00
A4 =	-8.4108E-03	3.1583E-02	5.0526E-02	5.8404E-02	-6.3337E-02
A6 =	-1.5168E-03	2.9537E-02	-3.0609E-02	-1.5144E-02	-4.9594E-03
A8 =	1.8056E-03	-6.1921E-02	-7.9384E-02	-4.2118E-01	5.3428E-03
A10 =	-8.8081E-02	-1.8644E-01	-2.6755E-02	1.5195E+00	-8.6243E-03
A12 =	2.0966E-01	2.7117E-01	-5.7592E-02	-2.9598E+00	-3.6756E-02
A14 =	-2.2964E-01	-2.1640E-01	1.9413E-02	2.6977E+00	3.0051E-01
A16 =	7.1422E-02	7.6083E-02	1.5743E-02	-9.1379E-01	-1.9391E-01
Surface #	7	8	9	10	11
k =	3.9473E+00	-3.8979E+00	-7.6363E-01	-1.3482E+01	-1.1042E+01
A4 =	5.3711E-03	-2.5165E-01	1.0144E-01	-9.9728E-02	-4.8309E-02
A6 =	-1.5353E-01	2.6756E-01	4.4522E-03	5.1553E-02	1.2017E-02
A8 =	4.3530E-01	-4.2684E-02	3.3889E-02	-3.0815E-02	-3.9260E-03
A10 =	-6.7201E-01	-3.9255E-02	-1.9174E-03	1.0557E-02	5.7301E-04
A12 =	6.3073E-01	1.1619E-02	-4.8088E-03	-1.5922E-03	4.2376E-06
A14 =	-2.2943E-01	2.4649E-02	-1.6018E-03	7.9380E-05	-1.1853E-05
A16 =	2.8931E-02	-1.6190E-02	7.6164E-04	3.2837E-07	9.7578E-07

The equation of the aspheric surface profiles is expressed as follows:

$$X(Y) = (Y^2/R)/(1 + \sqrt{1 - (1+k)*(Y/R)^2}) + \sum_i (Ai)*(Y^i)$$

wherein:

X: the relative distance between a point on the aspheric surface at a distance Y from the optical axis and the tangential plane at the aspheric surface vertex;

Y: the vertical distance from the point on the curve of the aspheric surface to the optical axis;

R: the curvature radius;

k: the conic coefficient;

Ai: the aspheric coefficient of order i.

In the first embodiment of the present optical image capturing lens system, the focal length of the optical image capturing lens system is f, the f-number of the optical image capturing lens system is Fno, half of the maximal field of view of the optical image capturing lens system is HFOV, and they satisfy the relations: f=3.74 (mm), Fno=2.20, HFOV=37.7 deg.

In the first embodiment of the present optical image capturing lens system, an Abbe number of the fourth lens element **140** is V4, an Abbe number of the fifth lens element **150** is V5, and they satisfy the relation: V4/V5=0.42.

In the first embodiment of the present optical image capturing lens system, a central thickness of the fourth lens element **140** is CT4, a central thickness of the fifth lens element **150** is CT5, and they satisfy the relation: CT4/CT5=0.31.

In the first embodiment of the present optical image capturing lens system, a central thickness of the second lens element **120** is CT2, a central thickness of the fourth lens element **140** is CT4, an axial distance between the second lens element **120** and the third lens element **130** is T23, an axial distance between the third lens element **130** and the fourth lens element **140** is T34, and they satisfy the relation: (CT2+CT4)/(T23+T34)=0.73.

In the first embodiment of the present optical image capturing lens system, an axial distance between the first lens element **110** and the second lens element **120** is T12, an axial distance between the second lens element **120** and the third lens element **130** is T23, and they satisfy the relation: T12/T23=0.11.

In the first embodiment of the present optical image capturing lens system, an axial distance between the fourth lens element **140** and the fifth lens element **150** is T45, an axial distance between the third lens element **130** and the fourth lens element **140** is T34, and they satisfy the relation: T45/T34=0.06.

In the first embodiment of the present optical image capturing lens system, a curvature radius of the object-side surface **121** of the second lens element **120** is R3, a curvature radius of the image-side surface **122** of the second lens element **120** is R4, and they satisfy the relation: (R3-R4)/(R3+R4)=0.21.

In the first embodiment of the present optical image capturing lens system, a curvature radius of the object-side surface **131** of the third lens element **130** is R5, a curvature radius of the image-side surface **132** of the third lens element **130** is R6, and they satisfy the relation: (R5+R6)/(R5-R6)=0.96.

In the first embodiment of the present optical image capturing lens system, a curvature radius of the object-side

surface **141** of the fourth lens element **140** is R7, a curvature radius of the image-side surface **142** of the fourth lens element **140** is R8, and they satisfy the relation: (R7-R8)/(R7+R8)=-0.25.

In the first embodiment of the present optical image capturing lens system, a curvature radius of the object-side surface **151** of the fifth lens element **150** is R9, a curvature radius of the object-side surface **111** of the first lens element **110** is R1, and they satisfy the relation: R9/R1=0.62.

In the first embodiment of the present optical image capturing lens system, a focal length of the optical image capturing lens system is f, a focal length of the fifth lens element **150** is f5, and they satisfy the relation: f/f5=0.87.

In the first embodiment of the present optical image capturing lens system, a focal length of the fourth lens element **140** is f4, a focal length of the second lens element **120** is f2, and they satisfy the relation: f4/f2=0.50.

In the first embodiment of the present optical image capturing lens system, a vertical distance with respect to the optical axis between a non-axial critical point on the object-side surface **151** of the fifth lens element **150** and the optical axis is Yc51, a focal length of the optical image capturing lens system is f, and they satisfy the relation: Yc51/f=0.27.

Embodiment 2
FIG. 2A shows an optical image capturing lens system in accordance with the second embodiment of the present disclosure, and FIG. 2B shows the aberration curves of the second embodiment of the present disclosure. The optical image capturing lens system of the second embodiment of the present disclosure mainly comprises five lens elements with refractive power, in order from an object side to an image side:

a first lens element **210** made of plastic with positive refractive power having a convex object-side surface **211** and a convex image-side surface **212**, and the object-side and image-side surfaces **211** and **212** thereof being aspheric;

a second lens element **220** made of plastic with negative refractive power having a convex object-side surface **221** and a concave image-side surface **222**, and the object-side and image-side surfaces **221** and **222** thereof being aspheric;

a third lens element **230** made of plastic with positive refractive power having a concave object-side surface **231** and a convex image-side surface **232**, and the object-side and image-side surfaces **231** and **232** thereof being aspheric;

a fourth lens element **240** made of plastic with negative refractive power having a concave object-side surface **241** and a convex image-side surface **242**, the object-side and image-side surfaces **241** and **242** thereof being aspheric; and

a fifth lens element **250** made of plastic with positive refractive power having a convex object-side surface **251** at a paraxial region and a concave image-side surface **252** at a paraxial region, the object-side and image-side surfaces **251** and **252** thereof being aspheric, and at least one inflection point is formed on both of the object-side surface **251** and the image-side surface **252**;

wherein a stop **200**, which is an aperture stop, is disposed between the first lens element **210** and the second lens element **220**; the optical image capturing lens system further comprises an IR-cut filter **260** disposed between the fifth lens element **250** and an image plane **280**, and the IR-cut filter **260** is made of glass and has no influence on the focal length of the optical image capturing lens system.

The detailed optical data of the second embodiment is shown in TABLE 3, and the aspheric surface data is shown in TABLE 4, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 3

(Embodiment 2)							
f = 3.56 mm, Fno = 2.30, HFOV = 38.1 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	Infinity				
1	Lens 1	2.225 ASP	0.462	Plastic	1.544	55.9	3.01
2		-5.766 ASP	-0.037				
3	Ape. Stop	Plano	0.104				
4	Lens 2	1.946 ASP	0.240	Plastic	1.634	23.8	-4.93
5		1.142 ASP	0.340				
6	Lens 3	-36.661 ASP	0.562	Plastic	1.544	55.9	4.48
7		-2.299 ASP	0.447				
8	Lens 4	-0.617 ASP	0.320	Plastic	1.634	23.8	-3.30
9		-1.051 ASP	0.030				
10	Lens 5	1.288 ASP	1.077	Plastic	1.535	55.7	4.40
11		2.015 ASP	0.600				
12	IR-filter	Plano	0.200	Glass	1.517	64.2	—
13		Plano	0.454				
14	Image	Plano	—				

Note:

Reference Wavelength is 587.6 nm (d-line).

TABLE 4

Aspheric Coefficients					
Surface #	1	2	4	5	6
k =	8.1653E-02	3.0000E+00	-1.5293E+01	-5.0817E+00	-2.0000E+01
A4 =	-2.3778E-02	8.3530E-03	5.8783E-02	9.8192E-02	-3.9138E-02
A6 =	-2.4824E-02	2.1303E-02	1.3571E-03	2.9680E-02	7.8360E-03
A8 =	-1.3837E-02	-7.1084E-02	-6.6352E-02	-4.0958E-01	2.7004E-02
A10 =	-8.8738E-02	-1.6692E-01	3.5704E-02	1.5179E+00	1.3182E-02
A12 =	2.0966E-01	1.2529E-01	-2.4991E-02	-2.8963E+00	-9.0889E-04
A14 =	-2.2964E-01	3.8258E-01	-6.2266E-02	2.6734E+00	1.6702E-01
A16 =	7.1422E-02	-4.1985E-01	9.3994E-02	-9.4575E-01	-1.2946E-01
Surface #	7	8	9	10	11
k =	3.0920E+00	-3.7600E+00	-7.5294E-01	-1.4088E+01	-9.8363E+00
A4 =	3.7574E-02	-2.4507E-01	9.7868E-02	-1.1142E-01	-5.1064E-02
A6 =	-1.3289E-01	2.7240E-01	2.8868E-03	5.7981E-02	1.2850E-02
A8 =	4.4631E-01	-4.6102E-02	3.4716E-02	-3.0555E-02	-4.1512E-03
A10 =	-6.8889E-01	-4.4372E-02	-1.3598E-03	1.0399E-02	5.6347E-04
A12 =	6.1427E-01	9.0807E-03	-4.5951E-03	-1.6411E-03	6.0360E-06
A14 =	-2.3058E-01	2.5005E-02	-1.5202E-03	7.4194E-05	-1.2173E-05
A16 =	4.2667E-02	-1.2040E-02	6.9837E-04	3.5469E-06	1.1103E-06

45

The equation of the aspheric surface profiles of the second embodiment has the same form as that of the first embodiment. Moreover, the description of the factors in the relations is as those set forth in the first embodiment, but the values of the relations of the second embodiment are listed in the following TABLE 5.

TABLE 5

(Embodiment 2)			
f [mm]	3.56	$(R3 - R4)/(R3 + R4)$	0.26
Fno	2.30	$(R5 + R6)/(R5 - R6)$	1.13
HFOV [deg.]	38.1	$(R7 - R8)/(R7 + R8)$	-0.26
V4/V5	0.43	R9/R1	0.58
CT4/CT5	0.30	f/f5	0.81
$(CT2 + CT4)/(T23 + T34)$	0.71	f4/f2	0.67
T12/T23	0.20	Yc51/f	0.28
T45/T34	0.07		

55

Embodiment 3

FIG. 3A shows an optical image capturing lens system in accordance with the third embodiment of the present disclosure, and FIG. 3B shows the aberration curves of the third

embodiment of the present disclosure. The optical image capturing lens system of the third embodiment of the present disclosure mainly comprises five lens elements with refractive power, in order from an object side to an image side:

a first lens element **310** made of plastic with positive refractive power having a convex object-side surface **311** and a concave image-side surface **312**, and the object-side and image-side surfaces **311** and **312** thereof being aspheric;

a second lens element **320** made of plastic with negative refractive power having a convex object-side surface **321** and a concave image-side surface **322**, and the object-side and image-side surfaces **321** and **322** thereof being aspheric;

a third lens element **330** made of plastic with positive refractive power having a concave object-side surface **331** and a convex image-side surface **332**, and the object-side and image-side surfaces **331** and **332** thereof being aspheric;

a fourth lens element **340** made of plastic with negative refractive power having a concave object-side surface **341**

65

13

and a convex image-side surface **342**, the object-side and image-side surfaces **341** and **342** thereof being aspheric; and

a fifth lens element **350** made of plastic with positive refractive power having a convex object-side surface **351** at a paraxial region and a concave image-side surface **352** at a paraxial region, the object-side and image-side surfaces **351** and **352** thereof being aspheric, and at least one inflection point is formed on both of the object-side surface **351** and the image-side surface **352**;

wherein a stop **300**, which is an aperture stop, is disposed between the first lens element **310** and the second lens

14

element **320**; the optical image capturing lens system further comprises an IR-cut filter **360** disposed between the fifth lens element **350** and an image plane **380**, and the IR-cut filter **360** is made of glass and has no influence on the focal length of the optical image capturing lens system.

The detailed optical data of the third embodiment is shown in TABLE 6, and the aspheric surface data is shown in TABLE 7, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 6

(Embodiment 3)								
f = 3.72 mm, Fno = 2.23, HFOV = 36.9 deg.								
Surface #		Curvature		Thickness	Material	Index	Abbe #	Focal Length
		Radius						
0	Object	Plano		Infinity				
1	Lens 1	1.773	ASP	0.561	Plastic	1.544	55.9	3.55
2		19.077	ASP	0.026				
3	Ape. Stop	Plano		0.039				
4	Lens 2	2.004	ASP	0.240	Plastic	1.640	23.3	-6.66
5		1.299	ASP	0.362				
6	Lens 3	-27.186	ASP	0.444	Plastic	1.544	55.9	5.04
7		-2.506	ASP	0.448				
8	Lens 4	-0.609	ASP	0.300	Plastic	1.640	23.3	-3.23
9		-1.031	ASP	0.030				
10	Lens 5	1.333	ASP	1.195	Plastic	1.535	55.7	3.91
11		2.523	ASP	0.600				
12	IR-filter	Plano		0.200	Glass	1.517	64.2	—
13		Plano		0.502				
14	Image	Plano		—				

Note:

Reference Wavelength is 587.6 nm (d-line).

TABLE 7

Aspheric Coefficients					
Surface #	1	2	4	5	6
k =	7.4089E-01	0.0000E+00	-1.4645E+01	-4.5241E+00	-1.0486E+01
A4 =	-9.7144E-03	-4.0634E-02	2.4701E-02	7.1973E-02	-4.0175E-02
A6 =	6.0601E-03	8.0257E-02	-6.9002E-02	2.1410E-02	-1.2917E-02
A8 =	-2.6776E-02	-2.5643E-02	-5.3423E-03	-4.0160E-01	5.7505E-02
A10 =	-5.7273E-02	-1.8898E-01	7.5517E-02	1.5419E+00	-3.1388E-02
A12 =	2.0966E-01	1.7287E-01	-1.0039E-01	-2.9198E+00	-1.5407E-01
A14 =	-2.2964E-01	-9.6660E-02	-2.2328E-01	2.7105E+00	3.9953E-01
A16 =	7.1422E-02	7.0652E-02	2.6241E-01	-9.8661E-01	-2.0640E-01
Surface #	7	8	9	10	11
k =	3.1869E+00	-3.6037E+00	-7.2059E-01	-1.5560E+01	-1.0263E+01
A4 =	1.0018E-02	-2.8387E-01	7.5879E-02	-1.0345E-01	-5.2325E-02
A6 =	-1.4325E-01	2.8247E-01	7.8950E-03	5.6197E-02	1.3950E-02
A8 =	4.4378E-01	-3.5626E-02	3.7322E-02	-3.0877E-02	-4.2635E-03
A10 =	-6.9808E-01	-4.1760E-02	-7.1500E-04	1.0422E-02	5.5549E-04
A12 =	6.0487E-01	6.1130E-03	-4.5614E-03	-1.6199E-03	9.5805E-06
A14 =	-2.3358E-01	2.2746E-02	-1.5942E-03	7.7794E-05	-1.1168E-05
A16 =	4.3455E-02	-1.2156E-02	6.0200E-04	2.3766E-06	9.1396E-07

15

The equation of the aspheric surface profiles of the third embodiment has the same form as that of the first embodiment. Moreover, the description of the factors in the relations is as those set forth in the first embodiment, but the values of the relations of the third embodiment are listed in the following TABLE 8.

TABLE 8

(Embodiment 3)			
f [mm]	3.72	$(R3 - R4)/(R3 + R4)$	0.21
Fno	2.23	$(R5 + R6)/(R5 - R6)$	1.20
HFOV [deg.]	36.9	$(R7 - R8)/(R7 + R8)$	-0.26
V4/V5	0.42	R9/R1	0.75
CT4/CT5	0.25	f/f5	0.95
$(CT2 + CT4)/(T23 + T34)$	0.67	f4/f2	0.48
T12/T23	0.18	Yc51/f	0.27
T45/T34	0.07		

Embodiment 4

FIG. 4A shows an optical image capturing lens system in accordance with the fourth embodiment of the present disclosure, and FIG. 4B shows the aberration curves of the fourth embodiment of the present disclosure. The optical image capturing lens system of the fourth embodiment of the present disclosure mainly comprises five lens elements with refractive power, in order from an object side to an image side:

a first lens element **410** made of plastic with positive refractive power having a convex object-side surface **411** and a convex image-side surface **412**, and the object-side and image-side surfaces **411** and **412** thereof being aspheric;

a second lens element **420** made of plastic with negative refractive power having a convex object-side surface **421**

16

and a concave image-side surface **422**, and the object-side and image-side surfaces **421** and **422** thereof being aspheric;

a third lens element **430** made of plastic with positive refractive power having a concave object-side surface **431** and a convex image-side surface **432**, and the object-side and image-side surfaces **431** and **432** thereof being aspheric;

a fourth lens element **440** made of plastic with negative refractive power having a concave object-side surface **441** and a convex image-side surface **442**, the object-side and image-side surfaces **441** and **442** thereof being aspheric; and

a fifth lens element **450** made of plastic with positive refractive power having a convex object-side surface **451** at a paraxial region and a concave image-side surface **452** at a paraxial region, the object-side and image-side surfaces **451** and **452** thereof being aspheric, and at least one inflection point is formed on both of the object-side surface **451** and the image-side surface **452**;

wherein a stop **400**, which is an aperture stop, is disposed between the imaged object and the first lens element **410**; the optical image capturing lens system further comprises an IR-cut filter **460** disposed between the fifth lens element **450** and an image plane **480**, and the IR-cut filter **460** is made of glass and has no influence on the focal length of the optical image capturing lens system.

The detailed optical data of the fourth embodiment is shown in TABLE 9, and the aspheric surface data is shown in TABLE 10, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 9

(Embodiment 4)									
f = 3.68 mm, Fno = 2.00, HFOV = 37.1 deg.									
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length		
0	Object	Plano	Infinity						
1	Ape. Stop	Plano	-0.248						
2	Lens 1	1.847 ASP	0.526	Plastic	1.544	55.9	3.29		
3		-50.954 ASP	0.030						
4	Lens 2	2.148 ASP	0.220	Plastic	1.640	23.3	-5.96		
5		1.319 ASP	0.340						
6	Lens 3	-48.887 ASP	0.539	Plastic	1.544	55.9	5.23		
7		-2.701 ASP	0.458						
8	Lens 4	-0.635 ASP	0.294	Plastic	1.640	23.3	-3.41		
9		-1.057 ASP	0.030						
10	Lens 5	1.335 ASP	1.123	Plastic	1.544	55.9	4.21		
11		2.250 ASP	0.600						
12	IR-filter	Plano	0.200	Glass	1.517	64.2	—		
13		Plano	0.554						
14	Image	Plano	—						

Note:

Reference Wavelength is 587.6 nm (d-line).

TABLE 10

Aspheric Coefficients					
Surface #	2	3	4	5	6
k =	1.0829E+00	0.0000E+00	-1.8753E+01	-6.2538E+00	-1.0000E+00
A4 =	-9.1391E-03	3.7581E-02	3.4444E-02	5.9180E-02	-6.3131E-02
A6 =	-3.9936E-04	5.1245E-02	-2.1882E-02	-9.5912E-03	-4.9236E-03
A8 =	3.4520E-03	-4.8719E-02	-5.0533E-02	-4.0733E-01	5.4422E-03

TABLE 10-continued

Aspheric Coefficients					
A10 =	-8.7179E-02	-1.7981E-01	-3.1008E-02	1.5320E+00	-1.3181E-02
A12 =	2.2756E-01	2.8399E-01	-7.4777E-02	-2.9676E+00	-3.8945E-02
A14 =	-2.3055E-01	-2.4277E-01	5.8911E-03	2.6898E+00	2.9359E-01
A16 =	6.7784E-02	7.7891E-02	4.2469E-02	-9.0369E-01	-1.8213E-01
Surface #	7	8	9	10	11
k =	3.9699E+00	-3.8803E+00	-7.4308E-01	-1.5877E+01	-1.0475E+01
A4 =	1.2672E-04	-2.4898E-01	9.2494E-02	-1.0634E-01	-5.1258E-02
A6 =	-1.4563E-01	2.5654E-01	9.6358E-03	5.2878E-02	1.2411E-02
A8 =	4.2826E-01	-4.3146E-02	3.4183E-02	-3.0336E-02	-3.9218E-03
A10 =	-6.7890E-01	-3.4223E-02	-2.2157E-03	1.0604E-02	5.5943E-04
A12 =	6.3172E-01	1.3252E-02	-4.7160E-03	-1.5962E-03	4.4047E-06
A14 =	-2.2629E-01	2.3847E-02	-1.5381E-03	6.9786E-05	-1.1802E-05
A16 =	2.8689E-02	-1.6582E-02	6.6311E-04	8.0575E-07	1.0210E-06

The equation of the aspheric surface profiles of the fourth embodiment has the same form as that of the first embodiment. Moreover, the description of the factors in the relations is as those set forth in the first embodiment, but the values of the relations of the fourth embodiment are listed in the following TABLE 11.

TABLE 11

(Embodiment 4)			
f [mm]	3.68	(R3 - R4)/(R3 + R4)	0.24
Fno	2.00	(R5 + R6)/(R5 - R6)	1.12
HFOV [deg.]	37.1	(R7 - R8)/(R7 + R8)	-0.25
V4/V5	0.42	R9/R1	0.72
CT4/CT5	0.26	f/f5	0.87
(CT2 + CT4)/(T23 + T34)	0.64	f4/f2	0.57
T12/T23	0.09	Yc51/f	0.26
T45/T34	0.07		

Embodiment 5

FIG. 5A shows an optical image capturing lens system in accordance with the fifth embodiment of the present disclosure, and FIG. 5B shows the aberration curves of the fifth embodiment of the present disclosure. The optical image capturing lens system of the fifth embodiment of the present disclosure mainly comprises five lens elements with refractive power, in order from an object side to an image side:

a first lens element **510** made of plastic with positive refractive power having a convex object-side surface **511** and a concave image-side surface **512**, and the object-side and image-side surfaces **511** and **512** thereof being aspheric;

a second lens element **520** made of plastic with negative refractive power having a convex object-side surface **521**

and a concave image-side surface **522**, and the object-side and image-side surfaces **521** and **522** thereof being aspheric;

a third lens element **530** made of plastic with positive refractive power having a convex object-side surface **531** and a convex image-side surface **532**, and the object-side and image-side surfaces **531** and **532** thereof being aspheric;

a fourth lens element **540** made of plastic with negative refractive power having a concave object-side surface **541** and a convex image-side surface **542**, the object-side and image-side surfaces **541** and **542** thereof being aspheric; and

a fifth lens element **550** made of plastic with positive refractive power having a convex object-side surface **551** at a paraxial region and a concave image-side surface **552** at a paraxial region, the object-side and image-side surfaces **551** and **552** thereof being aspheric, and at least one inflection point is formed on both of the object-side surface **551** and the image-side surface **552**;

wherein a stop **500**, which is an aperture stop, is disposed between the imaged object and the first lens element **510**; the optical image capturing lens system further comprises an IR-cut filter **560** and a cover glass **570** disposed sequentially between the fifth lens element **550** and an image plane **580**, and both of the IR-cut filter **560** and a cover glass **570** are made of glass and have no influence on the focal length of the optical image capturing lens system.

The detailed optical data of the fifth embodiment is shown in TABLE 12, and the aspheric surface data is shown in TABLE 13, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 12

(Embodiment 5)								
f = 3.58 mm, Fno = 2.44, HFOV = 39.3 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.135					
2	Lens 1	1.920 ASP	0.400	Plastic	1.544	55.9	4.49	
3		8.304 ASP	0.012					
4	Lens 2	1.761 ASP	0.230	Plastic	1.640	23.3	-8.47	
5		1.261 ASP	0.279					
6	Lens 3	21.828 ASP	0.423	Plastic	1.544	55.9	3.96	
7		-2.372 ASP	0.664					
8	Lens 4	-0.467 ASP	0.318	Plastic	1.640	23.3	-2.29	
9		-0.868 ASP	0.059					
10	Lens 5	1.250 ASP	1.161	Plastic	1.544	55.9	2.66	

TABLE 12-continued

(Embodiment 5)							
f = 3.58 mm, Fno = 2.44, HFOV = 39.3 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
11		6.162	ASP	0.250			
12	IR-filter	Plano	0.210	Glass	1.517	64.2	—
13		Plano	0.400				
14	Cover-glass	Plano	0.400	Glass	1.517	64.2	—
15		Plano	0.380				
16	Image	Plano	—				

Note:

Reference Wavelength is 587.6 nm (d-line).

TABLE 13

Aspheric Coefficients					
Surface #	2	3	4	5	6
k =	1.2073E+00	9.9000E+01	-9.2527E+00	-5.4246E+00	9.9000E+01
A4 =	2.4422E-03	4.2679E-02	5.8938E-02	6.9015E-02	-9.3742E-02
A6 =	-3.3738E-02	-1.0949E-01	-3.9721E-02	-9.8064E-02	-6.7721E-02
A8 =	-2.3463E-02	-1.9110E-01	-1.9504E-01	3.5137E-01	4.7605E-02
A10 =	-1.2298E-01	-2.0823E-01	-9.3475E-02	-1.2152E+00	1.1916E-01
A12 =	2.6706E-01	3.5859E-01	-1.4695E-01	1.4063E+00	-7.4447E-03
A14 =	-2.8710E-01	-2.1104E-01	2.8033E-01	-6.6888E-01	-1.2667E-02
A16 =	3.1835E-05	3.3569E-05	1.7263E-01	1.1473E-01	2.5948E-02

Surface #	7	8	9	10	11
k =	1.3017E+00	-2.1426E+00	-8.4275E-01	-1.0817E+01	-3.2239E+00
A4 =	-7.1040E-02	-2.4886E-01	1.2873E-01	-4.0235E-02	-4.7833E-02
A6 =	5.8007E-02	2.1485E-01	3.5434E-03	7.3124E-03	2.3226E-03
A8 =	-2.6669E-01	2.6326E-03	2.6700E-02	1.6760E-03	4.7641E-03
A10 =	3.7300E-01	8.8610E-03	-3.3857E-03	-3.7414E-03	-3.2450E-03
A12 =		4.9003E-03	-2.9769E-03	1.4978E-03	9.0544E-04
A14 =		4.4013E-03	-1.0091E-03	-2.3483E-04	-1.2376E-04
A16 =		-2.1303E-02	3.6516E-04	1.3195E-05	6.8178E-06

The equation of the aspheric surface profiles of the fifth embodiment has the same form as that of the first embodiment. Moreover, the description of the factors in the relations is as those set forth in the first embodiment, but the values of the relations of the fifth embodiment are listed in the following TABLE 14.

TABLE 14

(Embodiment 5)			
f [mm]	3.58	$(R3 - R4)/(R3 + R4)$	0.17
Fno	2.44	$(R5 + R6)/(R5 - R6)$	0.80
HFOV [deg.]	39.3	$(R7 - R8)/(R7 + R8)$	-0.30
V4/V5	0.42	R9/R1	0.65
CT4/CT5	0.27	f/f5	1.35
$(CT2 + CT4)/(T23 + T34)$	0.58	f4/f2	0.27
T12/T23	0.04	Yc51/f	0.38
T45/T34	0.09		

Embodiment 6

FIG. 6A shows an optical image capturing lens system in accordance with the sixth embodiment of the present disclosure, and FIG. 6B shows the aberration curves of the sixth embodiment of the present disclosure. The optical image capturing lens system of the sixth embodiment of the present disclosure mainly comprises five lens elements with refractive power, in order from an object side to an image side:

a first lens element **610** made of plastic with positive refractive power having a convex object-side surface **611**

and a convex image-side surface **612**, and the object-side and image-side surfaces **611** and **612** thereof being aspheric;

a second lens element **620** made of plastic with negative refractive power having a convex object-side surface **621** and a concave image-side surface **622**, and the object-side and image-side surfaces **621** and **622** thereof being aspheric;

a third lens element **630** made of plastic with positive refractive power having a convex object-side surface **631** and a convex image-side surface **632**, and the object-side and image-side surfaces **631** and **632** thereof being aspheric;

a fourth lens element **640** made of plastic with negative refractive power having a concave object-side surface **641** and a convex image-side surface **642**, the object-side and image-side surfaces **641** and **642** thereof being aspheric; and

a fifth lens element **650** made of plastic with positive refractive power having a convex object-side surface **651** at a paraxial region and a concave image-side surface **652** at a paraxial region, the object-side and image-side surfaces **651** and **652** thereof being aspheric, and at least one inflection point is formed on both of the object-side surface **651** and the image-side surface **652**;

wherein a stop **600**, which is an aperture stop, is disposed between the imaged object and the first lens element **610**; the optical image capturing lens system further comprises an IR-cut filter **660** and a cover glass **670** disposed sequentially between the fifth lens element **650** and an image plane **680**, and the IR-cut filter **660** and a cover glass **670** are made of

glass and have no influence on the focal length of the optical image capturing lens system.

The detailed optical data of the sixth embodiment is shown in TABLE 15, and the aspheric surface data is shown in TABLE 16, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 15

(Embodiment 6)									
f = 3.79 mm, Fno = 2.43, HFOV = 38.4 deg.									
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length		
0	Object	Plano	Infinity						
1	Ape. Stop	Plano	-0.130						
2	Lens 1	2.296 ASP	0.369	Plastic	1.544	55.9	3.85		
3		-22.850 ASP	0.015						
4	Lens 2	1.673 ASP	0.240	Plastic	1.640	23.3	-6.75		
5		1.138 ASP	0.352						
6	Lens 3	32.760 ASP	0.523	Plastic	1.544	55.9	4.32		
7		-2.516 ASP	0.583						
8	Lens 4	-0.580 ASP	0.326	Plastic	1.640	23.3	-2.71		
9		-1.061 ASP	0.030						
10	Lens 5	1.255 ASP	1.105	Plastic	1.544	55.9	3.40		
11		2.695 ASP	0.400						
12	IR-filter	Plano	0.210	Glass	1.517	64.2	—		
13		Plano	0.400						
14	Cover-glass	Plano	0.400	Glass	1.517	64.2	—		
15		Plano	0.250						
16	Image	Plano	—						

Note:

Reference Wavelength is 587.6 nm (d-line).

TABLE 16

Aspheric Coefficients					
Surface #	2	3	4	5	6
k =	1.6350E+00	9.9000E+01	-1.0833E+01	-5.0808E+00	9.9000E+01
A4 =	5.9321E-03	8.1276E-02	9.3298E-02	7.7510E-02	-5.4548E-02
A6 =	-8.2136E-03	3.5592E-02	-2.2318E-02	1.4119E-02	-4.2690E-03
A8 =	1.2927E-02	-6.1733E-02	-9.0064E-02	-4.1802E-01	-1.9518E-02
A10 =	-8.7402E-02	-2.3238E-01	5.9638E-03	1.5187E+00	-2.5664E-03
A12 =	2.0052E-01	3.0589E-01	-2.3832E-02	-2.9333E+00	-8.9097E-03
A14 =	-1.7285E-01	-9.2200E-02	-7.6091E-02	2.7144E+00	3.0856E-01
A16 =	9.4950E-06	9.9240E-06	1.1385E-01	-9.5604E-01	-2.1561E-01
Surface #	7	8	9	10	11
k =	3.5317E+00	-3.3743E+00	-7.8765E-01	-1.3049E+01	-1.2105E+01
A4 =	1.3753E-02	-2.4349E-01	8.8400E-02	-1.0402E-01	-5.2856E-02
A6 =	-1.6163E-01	2.4358E-01	2.2706E-03	5.3720E-02	1.3679E-02
A8 =	4.3468E-01	-2.0294E-02	3.4706E-02	-3.0916E-02	-4.1391E-03
A10 =	-6.8355E-01	-3.7686E-02	-6.4866E-04	1.0491E-02	5.5842E-04
A12 =	6.1773E-01	3.0533E-03	-4.3675E-03	-1.6075E-03	1.0930E-05
A14 =	-2.3532E-01	2.0505E-02	-1.7224E-03	8.1215E-05	-1.1296E-05
A16 =	4.5270E-02	-1.1370E-02	7.4275E-04	1.1731E-06	7.7650E-07

The equation of the aspheric surface profiles of the sixth embodiment has the same form as that of the first embodiment. Moreover, the description of the factors in the relations is as those set forth in the first embodiment, but the values of the relations of the sixth embodiment are listed in the following TABLE 17.

TABLE 17

(Embodiment 6)			
f [mm]	3.79	$(R3 - R4)/(R3 + R4)$	0.19
Fno	2.43	$(R5 + R6)/(R5 - R6)$	0.86
HFOV [deg.]	38.4	$(R7 - R8)/(R7 + R8)$	-0.29
V4/V5	0.42	R9/R1	0.55
CT4/CT5	0.30	f/f5	1.11
$(CT2 + CT4)/(T23 + T34)$	0.61	f4/f2	0.40
T12/T23	0.04	Yc51/f	0.27
T45/T34	0.05		

Embodiment 7

FIG. 7A shows an optical image capturing lens system in accordance with the seventh embodiment of the present disclosure, and FIG. 7B shows the aberration curves of the seventh embodiment of the present disclosure. The optical image capturing lens system of the seventh embodiment of the present disclosure mainly comprises five lens elements with refractive power, in order from an object side to an image side:

a first lens element 710 made of plastic with positive refractive power having a convex object-side surface 711 and a convex image-side surface 712, and the object-side and image-side surfaces 711 and 712 thereof being aspheric;

a second lens element 720 made of plastic with negative refractive power having a convex object-side surface 721

and a concave image-side surface 722, and the object-side and image-side surfaces 721 and 722 thereof being aspheric;

a third lens element 730 made of plastic with positive refractive power having a concave object-side surface 731 and a convex image-side surface 732, and the object-side and image-side surfaces 731 and 732 thereof being aspheric;

a fourth lens element 740 made of plastic with negative refractive power having a concave object-side surface 741 and a convex image-side surface 742, the object-side and image-side surfaces 741 and 742 thereof being aspheric; and

a fifth lens element 750 made of plastic with positive refractive power having a convex object-side surface 751 at a paraxial region and a concave image-side surface 752 at a paraxial region, the object-side and image-side surfaces 751 and 752 thereof being aspheric, and at least one inflection point is formed on both of the object-side surface 751 and the image-side surface 752;

wherein a stop 700, which is an aperture stop, is disposed between the imaged object and the first lens element 710; the optical image capturing lens system further comprises an IR-cut filter 760 disposed between the fifth lens element 750 and an image plane 780, and the IR-cut filter 760 is made of glass and has no influence on the focal length of the optical image capturing lens system.

The detailed optical data of the seventh embodiment is shown in TABLE 18, and the aspheric surface data is shown in TABLE 19, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 18

(Embodiment 7)									
f = 3.68 mm, Fno = 2.20, HFOV = 38.6 deg.									
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length		
0	Object	Plano	Infinity						
1	Ape. Stop	Plano	-0.170						
2	Lens 1	2.012 ASP	0.436	Plastic	1.535	55.7	3.51		
3		-25.469 ASP	0.050						
4	Lens 2	2.298 ASP	0.254	Plastic	1.632	23.4	-6.18		
5		1.385 ASP	0.255						
6	Lens 3	-76.015 ASP	0.626	Plastic	1.544	55.9	4.78		
7		-2.521 ASP	0.462						
8	Lens 4	-0.639 ASP	0.274	Plastic	1.632	23.4	-3.68		
9		-1.026 ASP	0.120						
10	Lens 5	1.197 ASP	0.946	Plastic	1.530	55.8	4.76		
11		1.654 ASP	0.600						
12	IR-filter	Plano	0.300	Glass	1.517	64.2	—		
13		Plano	0.607						
14	Image	Plano	—						

Note:

Reference Wavelength is 587.6 nm (d-line).

TABLE 19

Aspheric Coefficients					
Surface #	2	3	4	5	6
k =	1.0985E+00	-2.0000E+01	-2.2040E+01	-6.8049E+00	4.9998E+00
A4 =	-1.1948E-02	2.3013E-02	3.4069E-02	5.6952E-02	-5.6174E-02
A6 =	6.4180E-03	3.1108E-02	-3.6851E-02	-1.7033E-02	1.0565E-04
A8 =	2.6365E-03	-2.4973E-02	-8.1375E-02	-4.3544E-01	1.3478E-02

TABLE 19-continued

Aspheric Coefficients					
A10 =	-1.0066E-01	-2.1280E-01	-8.0588E-03	1.5359E+00	-2.0089E-02
A12 =	2.0893E-01	2.6725E-01	-5.2836E-02	-2.9469E+00	-3.4103E-02
A14 =	-2.3061E-01	-2.2442E-01	1.7242E-02	2.6910E+00	3.0073E-01
A16 =	7.1642E-02	7.2963E-02	3.1773E-03	-9.1639E-01	-1.9693E-01
Surface #	7	8	9	10	11
k =	3.4239E+00	-3.7767E+00	-7.9012E-01	-1.1200E+01	-8.7374E+00
A4 =	1.7321E-02	-2.4247E-01	1.0547E-01	-1.0430E-01	-4.9839E-02
A6 =	-1.4315E-01	2.6422E-01	8.7983E-03	5.1734E-02	1.2179E-02
A8 =	4.2555E-01	-4.6064E-02	3.4007E-02	-3.0814E-02	-3.9452E-03
A10 =	-6.7529E-01	-3.9482E-02	-2.6062E-03	1.0585E-02	5.7216E-04
A12 =	6.3110E-01	1.4348E-02	-4.9075E-03	-1.5848E-03	5.8795E-06
A14 =	-2.2866E-01	2.4177E-02	-1.6316E-03	7.8519E-05	-1.1856E-05
A16 =	2.8000E-02	-1.6301E-02	7.6040E-04	2.7386E-07	1.0125E-06

The equation of the aspheric surface profiles of the seventh embodiment has the same form as that of the first embodiment. Moreover, the description of the factors in the relations is as those set forth in the first embodiment, but the values of the relations of the seventh embodiment are listed in the following TABLE 20.

TABLE 20

(Embodiment 7)			
f [mm]	3.68	$(R3 - R4)/(R3 + R4)$	0.25
Fno	2.20	$(R5 + R6)/(R5 - R6)$	1.07
HFOV [deg.]	38.6	$(R7 - R8)/(R7 + R8)$	-0.23
V4/V5	0.42	R9/R1	0.59
CT4/CT5	0.29	f/f5	0.77
$(CT2 + CT4)/(T23 + T34)$	0.74	f4/f2	0.60
T12/T23	0.20	Yc51/f	0.28
T45/T34	0.26		

Embodiment 8

FIG. 8A shows an optical image capturing lens system in accordance with the eighth embodiment of the present disclosure, and FIG. 8B shows the aberration curves of the eighth embodiment of the present disclosure. The optical image capturing lens system of the eighth embodiment of the present disclosure mainly comprises five lens elements with refractive power, in order from an object side to an image side:

a first lens element **810** made of plastic with positive refractive power having a convex object-side surface **811** and a concave image-side surface **812**, and the object-side and image-side surfaces **811** and **812** thereof being aspheric;

a second lens element **820** made of plastic with negative refractive power having a convex object-side surface **821** and a concave image-side surface **822**, and the object-side and image-side surfaces **821** and **822** thereof being aspheric;

a third lens element **830** made of plastic with positive refractive power having a concave object-side surface **831** and a convex image-side surface **832**, and the object-side and image-side surfaces **831** and **832** thereof being aspheric;

a fourth lens element **840** made of plastic with negative refractive power having a concave object-side surface **841** and a convex image-side surface **842**, the object-side and image-side surfaces **841** and **842** thereof being aspheric; and

a fifth lens element **850** made of plastic with positive refractive power having a convex object-side surface **851** at a paraxial region and a concave image-side surface **852** at a paraxial region, the object-side and image-side surfaces **851** and **852** thereof being aspheric, and at least one inflection point is formed on both of the object-side surface **851** and the image-side surface **852**;

wherein a stop **800**, which is an aperture stop, is disposed between the imaged object and the first lens element **810**; the optical image capturing lens system further comprises an IR-cut filter **860** disposed between the fifth lens element **850** and an image plane **880**, and the IR-cut filter **860** is made of glass and has no influence on the focal length of the optical image capturing lens system.

The detailed optical data of the eighth embodiment is shown in TABLE 21, and the aspheric surface data is shown in TABLE 22, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 21

(Embodiment 8)								
f = 3.87 mm, Fno = 2.20, HFOV = 37.0 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.259					
2	Lens 1	1.617 ASP	0.559	Plastic	1.535	55.7	3.04	
3		226.988 ASP	0.107					
4	Lens 2	3.681 ASP	0.230	Plastic	1.650	21.4	-5.30	
5		1.735 ASP	0.328					
6	Lens 3	-16.403 ASP	0.480	Plastic	1.530	55.8	5.37	
7		-2.449 ASP	0.340					
8	Lens 4	-0.636 ASP	0.230	Plastic	1.543	56.5	-3.03	
9		-1.168 ASP	0.099					
10	Lens 5	1.389 ASP	1.432	Plastic	1.530	55.8	4.21	
11		2.366 ASP	0.500					

TABLE 21-continued

(Embodiment 8)							
f = 3.87 mm, Fno = 2.20, HFOV = 37.0 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
12	IR-filter	Plano	0.300	Glass	1.517	64.2	—
13		Plano	0.393				
14	Image	Plano	—				

Note:

Reference Wavelength is 587.6 nm (d-line).

TABLE 22

Aspheric Coefficients					
Surface #	2	3	4	5	6
k =	8.8082E-01	-7.5000E+00	-4.9085E+01	-9.0858E+00	5.0000E+00
A4 =	-1.5535E-02	1.1586E-02	-1.7296E-02	6.8448E-02	-7.2397E-02
A6 =	-1.1634E-02	2.9889E-03	3.3097E-02	1.4822E-02	-1.1351E-02
A8 =	2.2660E-02	9.0217E-02	-6.5563E-02	-3.6757E-01	-3.3709E-04
A10 =	-9.9282E-02	-2.8496E-01	-4.4848E-02	1.4964E+00	-6.6748E-03
A12 =	2.0936E-01	2.7221E-01	-5.5306E-02	-2.9482E+00	-3.5522E-02
A14 =	-2.2924E-01	-2.2455E-01	2.0189E-02	2.6920E+00	3.0035E-01
A16 =	7.1675E-02	7.2529E-02	3.5168E-03	-9.1651E-01	-1.9621E-01
Surface #	7	8	9	10	11
k =	3.3809E+00	-3.9779E+00	-7.0568E-01	-1.8711E+01	-7.6750E+00
A4 =	2.3011E-02	-1.9799E-01	7.9182E-02	-1.1917E-01	-4.7231E-02
A6 =	-1.5023E-01	2.4576E-01	1.9110E-02	5.9979E-02	1.3998E-02
A8 =	4.4313E-01	-4.7164E-02	3.2960E-02	-3.0297E-02	-4.3665E-03
A10 =	-6.9205E-01	-3.2774E-02	-4.5132E-03	1.0395E-02	5.6352E-04
A12 =	6.3297E-01	8.5599E-03	-5.4231E-03	-1.6425E-03	9.8797E-06
A14 =	-2.2842E-01	2.4764E-02	-1.5136E-03	7.5671E-05	-1.1040E-05
A16 =	2.7817E-02	-1.6562E-02	7.8275E-04	2.5050E-06	8.8446E-07

The equation of the aspheric surface profiles of the eighth embodiment has the same form as that of the first embodiment. Moreover, the description of the factors in the relations is as those set forth in the first embodiment, but the values of the relations of the eighth embodiment are listed in the following TABLE 23.

TABLE 23

(Embodiment 8)			
f [mm]	3.87	$(R3 - R4)/(R3 + R4)$	0.36
Fno	2.20	$(R5 + R6)/(R5 - R6)$	1.35
HFOV [deg.]	37.0	$(R7 - R8)/(R7 + R8)$	-0.30
V4/V5	1.01	R9/R1	0.86
CT4/CT5	0.16	f/f5	0.92
$(CT2 + CT4)/(T23 + T34)$	0.69	f4/f2	0.57
T12/T23	0.33	Yc51/f	0.24
T45/T34	0.29		

Embodiment 9

FIG. 9A shows an optical image capturing lens system in accordance with the ninth embodiment of the present disclosure, and FIG. 9B shows the aberration curves of the ninth embodiment of the present disclosure. The optical image capturing lens system of the ninth embodiment of the present disclosure mainly comprises five lens elements with refractive power, in order from an object side to an image side:

a first lens element **910** made of plastic with positive refractive power having a convex object-side surface **911** and a concave image-side surface **912**, and the object-side and image-side surfaces **911** and **912** thereof being aspheric;

a second lens element **920** made of plastic with negative refractive power having a convex object-side surface **921** and a concave image-side surface **922**, and the object-side and image-side surfaces **921** and **922** thereof being aspheric;

a third lens element **930** made of plastic with positive refractive power having a concave object-side surface **931** and a convex image-side surface **932**, and the object-side and image-side surfaces **931** and **932** thereof being aspheric;

a fourth lens element **940** made of plastic with negative refractive power having a concave object-side surface **941** and a convex image-side surface **942**, the object-side and image-side surfaces **941** and **942** thereof being aspheric; and

a fifth lens element **950** made of plastic with positive refractive power having a convex object-side surface **951** at a paraxial region and a convex image-side surface **952** at a paraxial region, the object-side and image-side surfaces **951** and **952** thereof being aspheric, and at least one inflection point is formed on both of the object-side surface **951** and the image-side surface **952**;

wherein a stop **900**, which is an aperture stop, is disposed between the imaged object and the first lens element **910**; the optical image capturing lens system further comprises an IR-cut filter **960** disposed between the fifth lens element **950** and an image plane **980**, and the IR-cut filter **960** is made of glass and has no influence on the focal length of the optical image capturing lens system.

The detailed optical data of the ninth embodiment is shown in TABLE 24, and the aspheric surface data is shown in TABLE 25, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 24

(Embodiment 9)							
f = 3.69 mm, Fno = 2.50, HFOV = 37.8 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	Infinity				
1	Ape. Stop	Plano	-0.187				
2	Lens 1	1.520 ASP	0.387	Plastic	1.543	56.5	2.94
3		29.242 ASP	0.085				
4	Lens 2	3.037 ASP	0.200	Plastic	1.634	23.8	-4.52
5		1.437 ASP	0.253				
6	Lens 3	-60.133 ASP	0.344	Plastic	1.530	55.8	4.88
7		-2.482 ASP	0.297				
8	Lens 4	-0.638 ASP	0.264	Plastic	1.543	56.5	-3.07
9		-1.185 ASP	0.085				
10	Lens 5	1.904 ASP	1.154	Plastic	1.535	55.7	3.55
11		-1000.000 ASP	0.600				
12	IR-filter	Plano	0.300	Glass	1.517	64.2	—
13		Plano	1.079				
14	Image	Plano	—				

Note:

Reference Wavelength is 587.6 nm (d-line).

TABLE 25

Aspheric Coefficients					
Surface #	2	3	4	5	6
k =	8.4942E-01	5.0000E+00	-5.1195E+01	-7.6806E+00	5.0000E+00
A4 =	-1.4163E-02	9.7591E-03	-1.5521E-02	7.4081E-02	-7.4291E-02
A6 =	-1.1809E-02	1.5290E-02	4.9094E-02	2.3565E-02	3.5861E-03
A8 =	2.2841E-02	1.0224E-01	-3.6905E-02	-3.5074E-01	2.6136E-03
A10 =	-1.1506E-01	-3.0889E-01	-1.6298E-02	1.5375E+00	-4.5930E-02
A12 =	2.0941E-01	2.8111E-01	-4.0517E-02	-2.9438E+00	-4.0887E-02
A14 =	-2.2684E-01	-2.2442E-01	2.1050E-02	2.6926E+00	2.9846E-01
A16 =	7.1392E-02	7.2363E-02	3.3764E-03	-9.1648E-01	-1.9688E-01
Surface #	7	8	9	10	11
k =	3.1219E+00	-3.3345E+00	-6.7520E-01	-3.7148E+01	-1.4950E+01
A4 =	3.7833E-02	-2.1195E-01	7.8531E-02	-1.1881E-01	-5.9456E-02
A6 =	-1.3905E-01	2.5214E-01	1.4509E-02	6.0938E-02	1.5190E-02
A8 =	4.5473E-01	-4.2494E-02	3.1277E-02	-2.9963E-02	-4.2929E-03
A10 =	-6.7082E-01	-3.8403E-02	-4.7280E-03	1.0496E-02	5.3201E-04
A12 =	6.2922E-01	8.5310E-03	-4.9970E-03	-1.6264E-03	6.0534E-06
A14 =	-2.2794E-01	2.4778E-02	-7.8422E-04	7.2885E-05	-1.1820E-05
A16 =	2.7383E-02	-1.5273E-02	1.5330E-03	-2.6697E-06	7.9535E-07

The equation of the aspheric surface profiles of the ninth embodiment has the same form as that of the first embodiment. Moreover, the description of the factors in the relations is as those set forth in the first embodiment, but the values of the relations of the ninth embodiment are listed in the following TABLE 26.

TABLE 26

(Embodiment 9)			
f [mm]	3.69	$(R3 - R4)/(R3 + R4)$	0.36
Fno	2.50	$(R5 + R6)/(R5 - R6)$	1.09
HFOV [deg.]	37.8	$(R7 - R8)/(R7 + R8)$	-0.30
V4/V5	1.01	R9/R1	1.25
CT4/CT5	0.23	f/f5	1.04
$(CT2 + CT4)/(T23 + T34)$	0.84	f4/f2	0.68
T12/T23	0.34	Yc51/f	0.21
T45/T34	0.29		

Embodiment 10

FIG. 10A shows an optical image capturing lens system in accordance with the tenth embodiment of the present disclosure, and FIG. 10B shows the aberration curves of the tenth embodiment of the present disclosure. The optical image capturing lens system of the tenth embodiment of the present disclosure mainly comprises five lens elements with refractive power, in order from an object side to an image side:

a first lens element **1010** made of plastic with positive refractive power having a convex object-side surface **1011** and a concave image-side surface **1012**, and the object-side and image-side surfaces **1011** and **1012** thereof being aspheric;

a second lens element **1020** made of plastic with negative refractive power having a convex object-side surface **1021** and a concave image-side surface **1022**, and the object-side and image-side surfaces **1021** and **1022** thereof being aspheric;

a third lens element **1030** made of plastic with positive refractive power having a convex object-side surface **1031** and a convex image-side surface **1032**, and the object-side and image-side surfaces **1031** and **1032** thereof being aspheric;

a fourth lens element **1040** made of plastic with negative refractive power having a concave object-side surface **1041** and a convex image-side surface **1042**, the object-side and image-side surfaces **1041** and **1042** thereof being aspheric; and

a fifth lens element **1050** made of plastic with positive refractive power having a convex object-side surface **1051** at

a paraxial region and a convex image-side surface **1052** at a paraxial region, the object-side and image-side surfaces **1051** and **1052** thereof being aspheric, and at least one inflection point is formed on both of the object-side surface **1051** and the image-side surface **1052**;

wherein a stop **1000**, which is an aperture stop, is disposed between the first lens element **1010** and the second lens element **1020**; the optical image capturing lens system further comprises an IR-cut filter **1060** disposed between the fifth lens element **1050** and an image plane **1080**, and the IR-cut filter **1060** is made of glass and has no influence on the focal length of the optical image capturing lens system.

The detailed optical data of the ninth embodiment is shown in TABLE 27, and the aspheric surface data is shown in TABLE 28, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 27

(Embodiment 10)									
f = 3.81 mm, Fno = 2.40, HFOV = 35.0 deg.									
Surface #		Curvature		Thickness	Material	Index	Abbe #	Focal	
		Radius						Length	
0	Object	Plano		Infinity					
1	Lens 1	1.988	ASP	0.413	Plastic	1.572	58.6	4.76	
2		6.804	ASP	0.052					
3	Ape. Stop	Plano		0.030					
4	Lens 2	1.498	ASP	0.240	Plastic	1.640	23.3	-8.12	
5		1.090	ASP	0.312					
6	Lens 3	9.644	ASP	0.465	Plastic	1.572	58.6	3.67	
7		-2.632	ASP	0.631					
8	Lens 4	-0.508	ASP	0.333	Plastic	1.640	23.3	-3.73	
9		-0.811	ASP	0.030					
10	Lens 5	2.441	ASP	1.117	Plastic	1.535	55.7	4.45	
11		-79.758	ASP	0.600					
12	IR-filter	Plano		0.300	Glass	1.517	64.2	—	
13		Plano		0.774					
14	Image	Plano		—					

Note:

Reference Wavelength is 587.6 nm (d-line).

TABLE 28

Aspheric Coefficients					
Surface #	1	2	4	5	6
k =	7.9476E-01	0.0000E+00	-8.1799E+00	-3.8540E+00	3.0000E+00
A4 =	-6.5216E-03	-4.5570E-02	4.0284E-02	6.6043E-02	-2.6383E-02
A6 =	-8.7940E-03	7.8552E-02	-5.0720E-02	2.0801E-02	-5.0133E-03
A8 =	-2.9802E-02	-4.3003E-02	1.5812E-02	-3.9922E-01	6.4172E-02
A10 =	-6.3542E-02	-1.8949E-01	8.7300E-02	1.5393E+00	-2.8438E-02
A12 =	1.8680E-01	2.0324E-01	-1.0255E-01	-2.9222E+00	-1.5467E-01
A14 =	-2.1139E-01	-1.3683E-01	-2.5787E-01	2.7166E+00	3.9717E-01
A16 =	7.1408E-02	9.4834E-02	3.0685E-01	-9.8032E-01	-2.0493E-01
Surface #	7	8	9	10	11
k =	2.8026E+00	-1.8353E+00	-7.6892E-01	-2.5918E+01	-1.0000E+00
A4 =	1.2618E-02	-2.4054E-01	1.2256E-01	-1.0017E-01	-4.7422E-02
A6 =	-1.3318E-01	2.7880E-01	3.9438E-02	5.5018E-02	8.4223E-03
A8 =	4.5270E-01	-1.0997E-02	3.2783E-02	-3.0403E-02	-2.6272E-03
A10 =	-6.8780E-01	-3.2387E-02	-1.6683E-03	1.0473E-02	4.5083E-04
A12 =	6.1499E-01	1.3339E-03	-4.9853E-03	-1.6273E-03	-2.3190E-05
A14 =	-2.2653E-01	1.8217E-02	-1.6810E-03	7.4990E-05	-1.1365E-05
A16 =	4.7330E-02	-1.5173E-02	5.7218E-04	1.8567E-06	1.8555E-06

The equation of the aspheric surface profiles of the ninth embodiment has the same form as that of the first embodiment. Moreover, the description of the factors in the relations is as those set forth in the first embodiment, but the values of the relations of the ninth embodiment are listed in the following TABLE 29.

TABLE 29

(Embodiment 10)			
f [mm]	3.81	$(R3 - R4)/(R3 + R4)$	0.16
Fno	2.40	$(R5 + R6)/(R5 - R6)$	0.57
HFOV [deg.]	35.0	$(R7 - R8)/(R7 + R8)$	-0.23
V4/V5	0.42	R9/R1	1.23
CT4/CT5	0.30	f/f5	0.86
$(CT2 + CT4)/(T23 + T34)$	0.61	f4/f2	0.46
T12/T23	0.26	Yc51/f	0.23
T45/T34	0.05		

It is to be noted that TABLES 1-29 show different data of the different embodiments; however, the data of the different embodiments are obtained from experiments. Therefore, any optical image capturing lens system of the same structure is considered to be within the scope of the present disclosure even if it uses different data. The embodiments depicted above and the appended drawings are exemplary and are not intended to limit the scope of the present disclosure.

What is claimed is:

1. An optical image capturing lens system comprising five lens elements, the five lens elements being, in order from an object side to an image side: a first lens element, a second lens element, a third lens element, a fourth lens element and a fifth lens element, and there is a gap between every two adjacent lens elements;

wherein the first lens element has positive refractive power and an object-side surface being convex at a paraxial region thereof, the fourth lens element has negative refractive power and at least one of an object-side surface thereof and an image-side surface thereof being aspheric, the fifth lens element has an image-side surface being concave at paraxial region thereof and at least one inflection point formed on at least one of an object-side surface and the image-side surface of the fifth lens element, an absolute value of a focal length of the fourth lens element is smaller than an absolute value of a focal length of third lens element, and an absolute value of a curvature radius of an image-side surface of the fourth lens element is smaller than an absolute value of a curvature radius of an image-side surface of the fifth lens element; wherein the optical image capturing lens system has a total of five lens elements;

wherein an axial distance between the third lens element and the fourth lens element is T34 and an axial distance between the fourth lens element and the fifth lens element is T45, and they satisfy the following relation:

$$0 < T45/T34 < 0.35.$$

2. The optical image capturing lens system according to claim 1, wherein the second lens element has negative refractive power and the third lens element has positive refractive power.

3. The optical image capturing lens system according to claim 1, wherein the object-side surface of the fifth lens element is convex at a paraxial region thereof.

4. The optical image capturing lens system according to claim 1, wherein the first lens element has an image-side surface being concave at a paraxial region thereof.

5. The optical image capturing lens system according to claim 1, wherein a vertical distance with respect to an optical

axis between a non-axial critical point on the object-side surface of the fifth lens element and the optical axis is Yc51, a focal length of the optical image capturing lens system is f, and they satisfy the following relation:

$$0.1 < Yc51/f < 0.7.$$

6. The optical image capturing lens system according to claim 1, wherein a focal length of the second lens element is f2, a focal length of the fourth lens element is f4, and they satisfy the following relation:

$$0.1 < f4/f2 < 0.85.$$

7. The optical image capturing lens system according to claim 1, wherein a sign of a curvature radius of an object-side surface of the third lens element is the same as a sign of a curvature radius of an image-side surface of the third lens element; each of the first lens element, the second lens element, the third lens element, the fourth lens element, and the fifth lens element has the object-side surface and image-side surface thereof being aspheric and is made of plastic.

8. The optical image capturing lens system according to claim 1, wherein a sign of a curvature radius of the object-side surface of the fourth lens element is the same as a sign of a curvature radius of the image-side surface of the fourth lens element.

9. The optical image capturing lens system according to claim 1, wherein the axial distance between the third lens element and the fourth lens element is T34, which is the largest axial distance among axial distances between every two adjacent lens elements.

10. An optical image capturing lens system comprising five lens elements, the five lens elements being, in order from an object side to an image side: a first lens element, a second lens element, a third lens element, a fourth lens element and a fifth lens element, and there is a gap between every two adjacent lens elements;

wherein the first lens element has positive refractive power, the second lens element has negative refractive power, the fourth lens element has negative refractive power and at least one of an object-side surface thereof and an image-side surface thereof being aspheric; the fifth lens element has positive refractive power, an object-side surface being convex at a paraxial region thereof and an image-side surface being concave at a paraxial region thereof, and at least one inflection point formed on at least one of the object-side surface thereof and the image-side surface thereof; an absolute value of a focal length of the fourth lens element is smaller than an absolute value of a focal length of third lens element, and an absolute value of a curvature radius of the image-side surface of the fourth lens element is smaller than an absolute value of a curvature radius of the object-side surface of the fifth lens element; wherein the optical image capturing lens system has a total of five lens elements;

wherein an axial distance between the third lens element and the fourth lens element is T34, an axial distance between the fourth lens element and the fifth lens element is T45, and they satisfy the following relation:

$$0 < T45/T34 < 0.35.$$

11. The optical image capturing lens system according to claim 10, wherein the first lens element, the second lens element, the third lens element, the fourth lens element and the fifth lens element are made of plastic, and the third lens element has positive refractive power.

12. The optical image capturing lens system according to claim 10, wherein the third lens element has an object-side surface being convex at a paraxial region thereof.

35

13. The optical image capturing lens system according to claim 10, wherein the first lens element has an image-side surface being concave at a paraxial region thereof.

14. The optical image capturing lens system according to claim 10, wherein the object-side surfaces and image-side surfaces of the first lens element, the second lens element, the third lens element, the fourth lens element and the fifth lens element are aspheric, a vertical distance with respect to an optical axis between a non-axial critical point on the object-side surface of the fifth lens element and the optical axis is $Yc51$, a focal length of the optical image capturing lens system is f , and they satisfy the following relation:

$$0.1 < Yc51/f < 0.7.$$

15. The optical image capturing lens system according to claim 10, wherein a focal length of the optical image capturing lens system is f , a focal length of the fifth lens element is $f5$, and they satisfy the following relation:

$$0.55 < f/f5 < 2.0.$$

16. The optical image capturing lens system according to claim 10, wherein the axial distance between the third lens element and the fourth lens element is $T34$, which is the largest axial distance among axial distances between every two adjacent lens elements.

17. The optical image capturing lens system according to claim 10, wherein a sign of a curvature radius of an object-side surface of the third lens element is the same as a sign of a curvature radius of an image-side surface of the third lens element.

18. The optical image capturing lens system according to claim 10, wherein a sign of a curvature radius of the object-side surface of the fourth lens element is the same as a sign of a curvature radius of the image-side surface of the fourth lens element.

19. An optical image capturing lens system comprising five lens elements, the five lens elements being, in order from an object side to an image side: a first lens element, a second lens element, a third lens element, a fourth lens element and a fifth lens element, and there is a gap between every two adjacent lens elements;

wherein the first lens element has positive refractive power and an object-side surface being convex at a paraxial region thereof, the fourth lens element has negative refractive power and at least one of an object-side surface thereof and an image-side surface thereof being aspheric, the fifth lens element has an image-side surface being concave at a paraxial region thereof and at least one inflection point formed on at least one of an object-side surface thereof and the image-side surface

36

thereof, an absolute value of a focal length of the fourth lens element is smaller than an absolute value of a focal length of third lens element, and an absolute value of a curvature radius of the image-side surface of the third lens element is smaller than an absolute value of a curvature radius of an image-side surface of the fifth lens element; wherein the optical image capturing lens system has a total of five lens elements

wherein an axial distance between the third lens element and the fourth lens element is $T34$, an axial distance between the fourth lens element and the fifth lens element is $T45$, and they satisfy the following relation:

$$0 < T45/T34 < 0.35.$$

20. The optical image capturing lens system according to claim 19, wherein the third lens element has positive refractive power.

21. The optical image capturing lens system according to claim 19, wherein the fifth lens element has positive refractive power.

22. The optical image capturing lens system according to claim 19, wherein the third lens element has an object-side surface being convex at a paraxial region thereof.

23. The optical image capturing lens system according to claim 19, wherein a vertical distance with respect to an optical axis between a non-axial critical point on an object-side surface of the fifth lens element and the optical axis is $Yc51$, a focal length of the optical image capturing lens system is f , and they satisfy the following relation:

$$0.1 < Yc51/f < 0.7.$$

24. The optical image capturing lens system according to claim 19, wherein a sign of a curvature radius of an object-side surface of the third lens element is the same as a sign of a curvature radius of an image-side surface of the third lens element.

25. The optical image capturing lens system according to claim 19, wherein a sign of a curvature radius of the object-side surface of the fourth lens element is the same as a sign of a curvature radius of the image-side surface of the fourth lens element.

26. The optical image capturing lens system according to claim 19, wherein the object-side surfaces and image-side surfaces of the first lens element, the second lens element, the third lens element, the fourth lens element and the fifth lens element are aspheric; an axial distance between the third lens element and the fourth lens element is $T34$, which is the largest axial distance among axial distances between every two adjacent lens elements.

* * * * *