



US010349262B2

(12) **United States Patent**
Mufti et al.

(10) **Patent No.:** **US 10,349,262 B2**
(45) **Date of Patent:** ***Jul. 9, 2019**

(54) **REALM TRANSLATION IN AN IMS NETWORK**

(71) Applicant: **T-Mobile USA, Inc.**, Bellevue, WA (US)

(72) Inventors: **Shujaar Mufti**, Snoqualmie, WA (US);
Zeeshan Jahangir, Bellevue, WA (US)

(73) Assignee: **T-Mobile USA, Inc.**, Bellevue, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/707,795**

(22) Filed: **Sep. 18, 2017**

(65) **Prior Publication Data**

US 2018/0007533 A1 Jan. 4, 2018

Related U.S. Application Data

(63) Continuation of application No. 14/697,935, filed on Apr. 28, 2015, now Pat. No. 9,769,646.
(Continued)

(51) **Int. Cl.**
H04W 8/02 (2009.01)
H04L 29/06 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04W 8/02** (2013.01); **H04L 29/06197** (2013.01); **H04L 65/1006** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04L 29/06197; H04L 69/22; H04L 65/1006; H04L 65/1016; H04L 65/1036; H04L 65/1073; H04W 60/04; H04W 8/02
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,374,605 B2 2/2013 Kuhn et al.
8,468,267 B2 6/2013 Yang et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1849270 A1 10/2007
EP 1944945 A1 7/2008
WO 2016138222 9/2016

OTHER PUBLICATIONS

International Searching Authority, International Search Report and Written Opinion, PCT Patent Application PCT/US2016/019660, dated Jul. 1, 2016, 16 pages.

(Continued)

Primary Examiner — Chi H Pham


Assistant Examiner — Weibin Huang

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(57) **ABSTRACT**

Various embodiments of the present technology allow multi-realm support at I/S-CSCF to IMS by the same I/S-CSCF nodes. Some embodiments allow for a registration message to be received from an IMS client. The registration message can be used to establish, through an Internet Protocol Multimedia Subsystem (IMS) core network, a service between a first endpoint associated with a first realm and a second endpoint associated with a second, different realm. The registration message can be translated so that the second endpoint believes the first endpoint is associated with the second realm before being transmitted to the second endpoint. Upon receiving a successful IMS registration message from the IMS core network, a binding can be created between the first endpoint and the second endpoint.

19 Claims, 6 Drawing Sheets



Related U.S. Application Data

- (60) Provisional application No. 62/121,430, filed on Feb. 26, 2015.
- (51) **Int. Cl.**
H04W 60/04 (2009.01)
H04W 84/04 (2009.01)
- (52) **U.S. Cl.**
 CPC *H04L 65/1016* (2013.01); *H04L 65/1036* (2013.01); *H04L 65/1073* (2013.01); *H04L 69/22* (2013.01); *H04W 60/04* (2013.01); *H04W 84/042* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 8,499,340 B2 * 7/2013 Lindholm H04L 29/12584
 370/401
- 8,611,890 B2 12/2013 Ionescu
- 8,762,559 B2 6/2014 Engelhart et al.
- 8,792,480 B2 7/2014 Lu et al.
- 9,749,904 B1 * 8/2017 Zhang H04W 36/0022
- 9,769,646 B2 * 9/2017 Mufti H04L 65/1016
- 2003/0225900 A1 * 12/2003 Morishige H04L 29/12358
 709/230
- 2006/0067338 A1 3/2006 Hua et al.
- 2006/0256748 A1 * 11/2006 Jung H04L 65/104
 370/328

- 2009/0024870 A1 1/2009 Pressley et al.
- 2009/0055899 A1 * 2/2009 Deshpande H04L 65/1069
 726/4
- 2009/0093237 A1 * 4/2009 Levenshteyn H04L 65/104
 455/412.1
- 2009/0093249 A1 4/2009 Zhu et al.
- 2009/0111430 A1 4/2009 Li et al.
- 2009/0168758 A1 7/2009 Apelqvist et al.
- 2009/0193469 A1 * 7/2009 Igarashi H04N 7/17309
 725/56
- 2010/0062767 A1 3/2010 Leis et al.
- 2010/0191829 A1 * 7/2010 Cagenius H04L 12/2834
 709/219
- 2010/0220703 A1 9/2010 Farrugia et al.
- 2011/0125925 A1 * 5/2011 Bouthemy H04L 12/2834
 709/250
- 2012/0214480 A1 8/2012 Ionescu
- 2013/0171974 A1 * 7/2013 Bae H04W 8/12
 455/411
- 2014/0092853 A1 4/2014 Noldus et al.
- 2014/0325078 A1 10/2014 Shan et al.
- 2015/0172349 A1 * 6/2015 Gonzalez De Langarica
 H04L 65/1016
 709/219

OTHER PUBLICATIONS

European Patent Office, Extended European Search Report, EP Patent Application 16756400.4, dated Sep. 12, 2018, 9 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

1

REALM TRANSLATION IN AN IMS
NETWORKCROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/697,935 filed Apr. 28, 2015, now U.S. Pat. No. 9,769,646, which claims priority to U.S. Provisional Application Ser. No. 62/121,430 filed Feb. 26, 2015, both of which are incorporated herein by reference in their entireties for all purposes.

BACKGROUND

The Internet Protocol Multimedia Subsystem (“IMS”) is an architectural framework for delivering Internet Protocol (“IP”) multimedia to mobile users, such as users of smart phones or tablet computers. An IMS core network (“IMS network”) permits wireless and wireline devices to access multimedia, messaging, and voice applications and services. IMS standards and specifications have been promulgated by the 3rd Generation Partnership Project (“3GPP”™). To allow the IMS network to be integrated with Internet resources, the 3GPP specifications use Internet Engineering Task Force protocols within the IMS network, such as Session Initiation Protocol (“SIP”) and Diameter. SIP is a signaling protocol used for creating, modifying and terminating two-party or multiparty sessions consisting of one or several media streams. A mobile device registers its IP address with a SIP registrar server within an IMS network by generating and sending a SIP request message with a “REGISTER” method token. Once registered, a mobile device may subsequently establish multimedia sessions via the IMS network.

An IMS client (or IMS stack) software component on a mobile device allows one or more applications on the mobile device to register for various application services that are available on the IMS network, such as Voice over LTE (VoLTE), Rich Communication Services (RCS), Short Message Service over Internet Protocol (SMS over IP), and Presence. If the registration is successful, the mobile device application may then take advantage of the functionality offered by the application service to which it is registered. If the registration is unsuccessful, however, then the application will be unable to take advantage of the offered functionality.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the present technology will be described and explained through the use of the accompanying drawings in which:

FIG. 1 is a diagram of a representative Internet Protocol Multimedia Subsystem (IMS) environment.

FIG. 2 is a block diagram of a representative mobile device that may request IMS services.

FIG. 3 is a block diagram providing a simplified view of the registration and delivery of IMS application services to mobile devices which are assigned to different realms.

FIG. 4 is a block diagram of a CSCF node within an IMS network.

FIG. 5 is a flowchart illustrating a representative set of operations that may be used to manage communications between user equipment and services that are associated with different realms.

2

FIG. 6 is a sequence diagram illustrating an example of a set of communications between components of a communication network.

The drawings have not been drawn to scale. Similarly, some components and/or operations may be separated into different blocks or combined into a single block for the purposes of discussion of some of the embodiments of the present invention. Moreover, while the invention is amenable to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and are described in detail below. The intention, however, is not to limit the invention to the particular embodiments described. On the contrary, the invention is intended to cover all modifications, equivalents, and alternatives falling within the scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION

Various embodiments of the present technology generally relate to an Internet protocol multimedia network subsystem (IMS). An IMS is a standardized set of architecture specifications allowing service providers to deliver multimedia services independent of the type of network (e.g., packet-switched network, circuit-switched cellular, fixed-line network, etc.) on which they are being run. One important component of IMS based service delivery is the availability of clients on end-user devices (both hardware clients like handsets, and software clients like smartphone apps). These IMS clients can be tailored to suit the specific needs of service providers and may require custom development to make them interoperate with the IMS core network. Moreover, since the IMS domain relies on a trusted relationship between the network and the end-user, the IMS services are marketed and offered to the operator’s own subscribers (i.e., trusted and known) thereby limiting the number of users that can potentially utilize and be eligible for these services.

In contrast, some embodiments of the present technology relate to an IMS network that provides multiple realm support. To this end, various embodiments of the present technology allow multi-realm support at an interrogating control session control function (I-CSCF) server/serving control session control function (S-CSCF) server to the IMS network by the same I/S-CSCF nodes. For example, some embodiments can allow an IMS subscriber to use both voice calling over LTE and over Wi-Fi (VoLTE and VoWiFi), which each use different realm values, by implementing logic on the I/S-CSCF to retain the user equipment (UE) provided realm, and to update all subsequent responses with that value. This provides operators the flexibility to maintain multiple realms per service, while simultaneously maintaining one global realm towards the home subscriber service (HSS). Thus, the operator could also define different realms for various business reasons, such as different realms associated with different brands (e.g., a premium brand of service, a budget brand of service, corporate service brands, etc.).

In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of embodiments of the present invention. It will be apparent, however, to one skilled in the art that embodiments of the present invention may be practiced without some of these specific details. Moreover, the techniques introduced here can be embodied as special-purpose hardware (e.g., circuitry), as programmable circuitry appropriately programmed with software and/or firmware, or as a combination of special-purpose and

programmable circuitry. Hence, embodiments may include a machine-readable medium having stored thereon instructions that may be used to program a computer (or other electronic devices) to perform a process. The machine-readable medium may include, but is not limited to, floppy diskettes, optical disks, compact disc read-only memories (CD-ROMs), magneto-optical disks, ROMs, random access memories (RAMs), erasable programmable read-only memories (EPROMs), electrically erasable programmable read-only memories (EEPROMs), magnetic or optical cards, flash memory, or other type of media/machine-readable medium suitable for storing electronic instructions.

The phrases “in some embodiments,” “according to some embodiments,” “in the embodiments shown,” “in other embodiments,” and the like generally mean the particular feature, structure, or characteristic following the phrase is included in at least one implementation of the present invention, and may be included in more than one implementation. In addition, such phrases do not necessarily refer to the same embodiments or different embodiments.

FIG. 1 illustrates an example of a communications environment **100** in which some embodiments of the present invention may be utilized. As illustrated in FIG. 1, communications environment **100** may include one or more clients **105** (such as a mobile phone, tablet computer, mobile media device, mobile gaming device, vehicle-based computer, wearable computer, etc.), wireless access network **110**, access gateway server **115**, and IMS network **120**. IMS network **120** may include a variety of components such as call session control function servers **125**, services gateway **130**, subscriber repository **135** (e.g., a Home Subscriber Server), and application servers **140**.

It will be appreciated that communications environment **100** may include one or more networks that correspond to a number of IP-based and other networks such as the Internet, DSL networks, public switched telephone networks (PSTN) and other wire-line networks (e.g., SS7-based networks), wireless networks such as those using CDMA, GSM, 3G, 4G, IEEE 802.11x, and/or satellite phone communications or the like, and local area networks. For example, wireless access network **110** may be interfaced with other networks through access gateway server **115**. Access gateway server **115** may be a Gateway GPRS Support Node (GGSN) for General Packet Radio Service (GPRS), a Packet Data Gateway (PDG) for Wi-Fi, Systems Architecture Evolution Gateway (SAE-GW) or a Packet Data Network Gateway (PDN-GW) for 3GPP Long Term Evolution (LTE), and the like.

IMS network **120** allows service providers to implement various mobile services for mobile devices. IMS registration for different IMS services may be based, for example, on SIP Event Package for Registration Information defined in Request for Comments (RFC) 3680 and procedures defined in 3GPP Test Specification (TS) 24.229. Users may employ mobile devices **105A-105N** to communicate with other users and devices. In addition, users may employ mobile devices **105A-105N** to receive, provide, or otherwise interact with multiple IMS services. For example, location-based services are services that use the actual or approximate location of a mobile device to provide, enhance, or supplement a service to the mobile device. Location-based services include, but are not limited to, services such as emergency services (e.g., E911), asset tracking or recovery services (e.g., the tracking of a stolen car), location-based alerts or advertising services (e.g., targeted advertisements that depend on the location of a mobile device user), social networking services (e.g., services that report the relative location of friends or family), and/or the like.

In addition, users may employ mobile devices **105A-105N** to receive, provide, or otherwise interact with additional IMS services, including image sharing services, gaming services, multimedia telephony services, instant messaging and presence services, video conferencing and sharing services, Voice over LTE, Push-to-talk over Cellular (PoC) services, 3GPP combinational services (CSI), and other telecommunications and Internet converged services. Once a mobile device **105A-105N** has successfully registered with the IMS network **120**, the device may establish multimedia sessions managed by IMS network **120** in order to access applications and services that facilitate communication, location-based services and/or other services.

To ease the integration of IMS network **120** with Internet resources, various specifications (e.g., 3GPP specifications) use Internet Engineering Task Force protocols within IMS network **120**. An example of one such protocol is session initiation protocol (SIP). SIP is a signaling protocol used for creating, modifying and terminating two-party or multiparty sessions consisting of one or several media streams. Endpoints must register with IMS network **120** in order to use IMS services. Traditionally, a mobile device, or other endpoint, registers its IP address with a SIP registrar server within IMS network **120** by generating and sending a SIP request message with a “REGISTER” method token. The IMS network **120** handles the authentication. CSCF **125** manages the signaling from devices **105** to services hosted by application server **140**. CSCF can include multiple servers and proxies including proxy-CSCF (P-CSCF), interrogating-CSCF (I-CSCF) and serving-CSCF (S-CSCF).

A subscriber attempting to register with the network discovers which P-CSCF server it shall use for registration. Besides having the host name of the P-CSCF server internally configured, clients **105** may also request the P-CSCF server host name from the access network or obtain it through Dynamic Host Configuration Protocol (DHCP). The client sends a register message to the P-CSCF server. The client uses a Domain Name System (DNS) query to resolve the P-CSCF server host name into an IP address and Transport protocol (e.g., User Datagram Protocol (UDP)). The register message contains subscriber registration data, (“registration data”). This registration data includes the subscriber’s public identifier, the home realm and the subscriber’s contact address.

During registration, the P-CSCF server selects an inbound proxy, based on the home realm, and then forwards the register message to the selected inbound proxy, such as an I-CSCF server. The I-CSCF server can then determine if the home realm matches the realm of the user device. If so, the setup can proceed as normal. If not, the I-CSCF masks or translates the realm associated with the user device so that the HSS will accept the registration. The I-CSCF server then queries subscriber repository **135**, based on the subscriber’s public identifier, and asks for information regarding the S-CSCF server that shall be allocated for this subscriber. If no S-CSCF server is allocated to the subscriber at this moment, then I-CSCF server allocates one, based on information from the S-CSCF capabilities, received from subscriber repository **135**. “S-CSCF capabilities” is a subscription parameter that indicates the capabilities that the S-CSCF to be selected for this subscriber should support. The I-CSCF server then forwards the Register message to the selected S-CSCF server.

The selected S-CSCF server informs subscriber repository **135** that this subscriber has registered and that this S-CSCF (the selected S-CSCF) has been assigned to that subscriber. Subscriber repository **135** stores the S-CSCF

5

address for this subscriber, so subsequent registration or session establishment may be directed to this S-CSCF server. Subscriber repository **135** supplies the subscription profile to the S-CSCF server, which the S-CSCF server stores. The S-CSCF server also stores the contact address of the client, realm associated with the client, home realm, and the host name of the P-CSCF server. This enables the S-CSCF server to contact this terminal for session establishment, translate the realms before sending the message through the allocated P-CSCF server for the subscriber.

Subscriber repository **135**, coupled to CSCF **125** and/or services gateway **130**, may be a master user database containing the subscription-related information (subscriber profiles) that supports IMS network **120**. Subscriber repository **135** may also perform authentication and authorization of the user, and can provide information about the subscriber's location and IP information. The subscriber repository **135** may be a home subscriber server (HSS) that can create a temporary binding between the provided user identity and the registration state as just described.

As shown in FIG. 2, which is a block diagram of a representative mobile device, each mobile device **105** typically includes a processor **205** for executing processing instructions, a data storage medium component **210** (e.g., hard drive, flash memory, memory card, etc.), volatile memory and/or nonvolatile memory **215**, a power supply **220**, one or more network interfaces (e.g., Bluetooth Interface **225**; and Network Communication Interface **230**, which enables the mobile phone to communicate by transmitting and receiving wireless signals using licensed, semi-licensed or unlicensed spectrum over a telecommunications network; GPS and WiFi interfaces, among others, may also be provided (not shown)), an audio interface **235**, a microphone **240**, a display **245**, a keypad or keyboard **250**, and other input and/or output interfaces **255**. The various components of a mobile device may be interconnected via a bus.

The volatile and nonvolatile memories generally include storage media for storing information such as processor-readable instructions, data structures, program modules, or other data. Some examples of information that may be stored include basic input/output systems (BIOS), operating systems, and applications. The stored information may include one or more SIP clients capable of generating, transmitting and interpreting syntactically correct SIP messages. As described above, SIP clients permit the mobile device to register with and communicate via the IMS network **120**.

FIG. 3 is a block diagram providing a simplified view of the registration and delivery of IMS application services to mobile devices. Applications running in the mobile device **105** use an IMS client **325** to register for application services in the IMS network **120**. The IMS client (or IMS stack) maintains an IMS registration as long as an application needs to stay connected with a corresponding application service. The IMS proxies (*-CSCFs) **125** in IMS network **120** maintain the registration initiated by the mobile device and provide the appropriate routing for IMS traffic. When for any reason one of the application servers involved rejects the initial registration request, the IMS service is not available to the mobile device and the application functionality on the mobile device may be substantially or completely impacted by the registration failure.

FIG. 3 illustrates multiple applications **310**, **315**, and **320** on mobile device **105**. The applications on mobile device **105** may be associated with different home service providers (e.g., different realms) and communicate with the IMS network **120** through IMS client **325**. IMS client **325** may reside within mobile device **105** and manage communica-

6

tions between mobile device applications and other components in IMS network **120**. For example, IMS client **325** can receive registration requests from mobile device applications **310**, **315**, and **320**, forward the received registration requests to IMS network **120**, receive registration status notification subscription requests from the mobile device applications, and forward the received registration status notification subscription requests to the IMS network **120**.

In some embodiments, IMS client **325** can additionally receive registration status notifications from application services **330**, **335**, and **340**, which may belong to different home realms, and forward the received status notifications to the appropriate mobile device applications. Those skilled in the art will appreciate that the IMS client **325** may be implemented in an Android™, Windows™, iOS™, or other operating system environment that is used by mobile devices.

IMS client **325** can connect to communication manager component **345** within one or more of the CSCF **125** in IMS network **120**. Communication manager **345** can reside within the IMS network **120**; it manages registrations and communications between one or more mobile device applications **310**, **315**, and **320** and one or more application services **330**, **335**, and **340**. For example, communication manager **345** can do the following:

1. receive registration requests from the mobile device applications,
2. translate or mask the realms when the UE realm is different than the HSS realm,
3. receive registration status notification subscription requests from the IMS client,
4. translate the HSS realm back to the UE realm, and
5. forward the received registration status notification subscription requests to the appropriate application servers.

In some embodiments, communication manager **345** may receive a single request that functions as both a registration request and a registration status notification subscription request.

FIG. 4 is a block diagram of a CSCF node **125** within IMS network **120** (as illustrated in FIG. 3), which implements the functionality of the communication manager **345**. CSCF **125** may contain one or more processors **405** for executing processing instructions, a data storage medium component **410** (e.g., hard drive, flash memory, memory card, etc.), a volatile memory and/or nonvolatile memory **415**, and a translation module **420**.

Although depicted separately, it will be appreciated that translation module **420** may be incorporated into data storage **410** or memory **415**, or may be incorporated into a component that is external to CSCF **125**. Instructions for implementing functions of the translation module **420** may be stored in the data storage medium and/or memory and executed by the processor. While the functionality of translation module **420** is depicted as residing within the CSCF **125**, it will be appreciated that translation module **420** may be implemented independently from the CSCF **125**. That is, translation module **420** may be operated as a stand-alone service within IMS network **120** or may be incorporated in other network nodes within IMS network **120**.

FIG. 5 is a flowchart illustrating a representative set of operations **500** that may be used to manage communications between user equipment (UE) and services that are associated with different realms. As illustrated in FIG. 5, a message is received from a UE directed to an IMS service during receiving operation **505**. The IMS service may have a different realm (or domain) than the UE. Identification

operation **510** identifies the realm of the UE and the realm of the IMS service. Differentiation operation **515** determines whether the realms are different.

If differentiation operation **515** determines that the realms of the UE and the IMS service are different, then differentiation operation **515** branches to translation operation **520** where the original realm of the UE is translated to the service realm. This can be done, for example, by updating a realm header field parameter within a SIP message with the service realm. The message is then transmitted with the updated service realm during transmission operation **525**. A response from the IMS service is received during receiving operation **530** and the service realm in the message is translated back to the original UE realm during translation operation **535**. The message with the original UE realm is then transmitted back to the UE during transmission operation **540**.

If differentiation operation **515** determines that the realms of the UE and the IMS service are not different, then differentiation operation **515** branches to transmission operation **545** where the message is transmitted to the IMS service without translation. A response message is received from the IMS service during receiving operation **550**. Since no translation is needed, because the realms match, the message is forwarded to the UE without translation during forwarding operation **555**.

FIG. 6 is a sequence diagram illustrating an example of a set of communications between components of a communication network. As illustrated in FIG. 6, UE **605** generates a SIP REGISTER message that identifies the UE as being associated with a first realm (e.g., xxx.com). In a first communication, the UE transmits SIP register message to S-CSCF **610**, which is associated with a home realm of HSS **615** (e.g., yyy.com). CSCF **610** supports dual realm and generates a Diameter Multimedia-Auth-Request (MAR), which in a second communication, is transmitted to the destination home realm. Upon processing the request, HSS **615** generates a Diameter Multimedia-Auth-Answer (MAA). If the realms were different the Diameter MAA would be a message indicating that the realm was not served. However, since CSCF **610** translated or masked the original UE realm so that the HSS determined UE **605** was associated with the desired home realm, such a message is not generated. Instead the HSS generates an unauthorized message (e.g., SIP **401**), which in a third communication it transmits back to the S-CSCF **610**.

Upon receiving the response from the HSS, CSCF **610** updates the realms in the response (instead of rejecting the register request) and forwards the message to the UE in a fourth communication. CSCF **610** can then respond with a request for a server assignment for the service. The UE, in a fifth communication, sends a SIP REGISTER request to the S-CSCF **610**. The CSCF **610** again translates the SIP REGISTER request to generate a Diameter Server-Assignment-Request (SAR) to the destination home realm, in a sixth communication. Upon processing the request, HSS **615** generates a Diameter Server-Assignment-Answer (SAA) identifying a server. The HSS **615**, in a seventh communication, sends the Diameter SAS to the S-CSCF **610**. The S-CSCF **610** again converts the message back to the UE realm before transmitting it to UE **605** (eighth communication) and thereby creating a binding between UE **605** and an application service.

Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise,” “comprising,” and the like are to be construed in an inclusive sense, as opposed to an exclusive or exhaustive sense; that

is to say, in the sense of “including, but not limited to.” As used herein, the terms “connected,” “coupled,” or any variant thereof means any connection or coupling, either direct or indirect, between two or more elements; the coupling or connection between the elements can be physical, logical, or a combination thereof. Additionally, the words “herein,” “above,” “below,” and words of similar import, when used in this application, refer to this application as a whole and not to any particular portions of this application. Where the context permits, words in the above Detailed Description using the singular or plural number may also include the plural or singular number respectively. The word “or,” in reference to a list of two or more items, covers all of the following interpretations of the word: any of the items in the list, all of the items in the list, and any combination of the items in the list.

The above Detailed Description of examples of the invention is not intended to be exhaustive or to limit the invention to the precise form disclosed above. While specific examples for the invention are described above for illustrative purposes, various equivalent modifications are possible within the scope of the invention, as those skilled in the relevant art will recognize. For example, while processes or blocks are presented in a given order, alternative implementations may perform routines having steps, or employ systems having blocks, in a different order, and some processes or blocks may be deleted, moved, added, subdivided, combined, and/or modified to provide alternative or subcombinations. Each of these processes or blocks may be implemented in a variety of different ways. Also, while processes or blocks are at times shown as being performed in series, these processes or blocks may instead be performed or implemented in parallel, or may be performed at different times. Further any specific numbers noted herein are only examples: alternative implementations may employ differing values or ranges.

The teachings of the invention provided herein can be applied to other systems, not necessarily the system described above. The elements and acts of the various examples described above can be combined to provide further implementations of the invention. Some alternative implementations of the invention may include not only additional elements to those implementations noted above, but also may include fewer elements.

These and other changes can be made to the invention in light of the above Detailed Description. While the above description describes certain examples of the invention, and describes the best mode contemplated, no matter how detailed the above appears in text, the invention can be practiced in many ways. Details of the system may vary considerably in its specific implementation, while still being encompassed by the invention disclosed herein. As noted above, particular terminology used when describing certain features or aspects of the invention should not be taken to imply that the terminology is being redefined herein to be restricted to any specific characteristics, features, or aspects of the invention with which that terminology is associated. In general, the terms used in the following claims should not be construed to limit the invention to the specific examples disclosed in the specification, unless the above Detailed Description section explicitly defines such terms. Accordingly, the actual scope of the invention encompasses not only the disclosed examples, but also all equivalent ways of practicing or implementing the invention under the claims.

To reduce the number of claims, certain aspects of the invention are presented below in certain claim forms, but the applicant contemplates the various aspects of the invention in any number of claim forms. For example, while only one

aspect of the invention is recited as a computer-readable medium claim, other aspects may likewise be embodied as a computer-readable medium claim, or in other forms, such as being embodied in a means-plus-function claim. Any claims intended to be treated under 35 U.S.C. § 112(f) will begin with the words “means for”, but use of the term “for” in any other context is not intended to invoke treatment under 35 U.S.C. § 112(f). Accordingly, the applicant reserves the right to pursue additional claims after filing this application to pursue such additional claim forms, in either this application or in a continuing application.

We claim:

1. At least one non-transitory computer-readable medium, carrying instructions, which when executed by at least one data processor, performs a method for use in a telecommunications network for routing communications, the method comprising:

receiving a request from an initiating device to establish a service connection session between the initiating device and an endpoint through an Internet Protocol Multimedia Subsystem (IMS) session, wherein the initiating device is assigned to a first realm, and wherein the endpoint is associated with a second, different realm; and, providing a Session Initiation Protocol (SIP) REGISTER message based on the request to create the IMS session, wherein the SIP REGISTER message identifies the initiating device as being assigned to the second realm; wherein the IMS session is created between the initiating device and the endpoint, wherein, during the session, the first realm is translated into the second realm upon receiving messages from the initiating device; and wherein, during the session, the second realm is translated into the first realm upon receiving messages from the endpoint.

2. The non-transitory computer-readable medium of claim **1**, wherein the endpoint is an IMS service including white board discussions, video conferencing, Push to talk over Cellular (PoC), Voice over IP (VoIP), real-time content sharing, instant messaging, interactive gaming Voice over LTE (VoLTE), short messaging service (SMS) over IP, Rich Communication Suite (RCS), or Presence.

3. The non-transitory computer-readable medium of claim **1**, wherein the request is a SIP request and generating the registration message based on the request includes setting a realm header field parameter of the SIP request to identify the second realm.

4. The non-transitory computer-readable medium of claim **1**, wherein the method further comprises: receiving a response message from the endpoint, wherein the response message from the endpoint identifies the second realm; and generating a translated response message that identifies the first realm instead of the second realm before forwarding the message onto the initiating device.

5. The non-transitory computer-readable medium of claim **1**, wherein the method further comprises: receiving a response message from the endpoint, wherein the response message from the endpoint identifies the second realm; and generating a translated response message that identifies the first realm instead of the second realm before forwarding the message onto the initiating device.

6. The non-transitory computer-readable medium of claim **1**, wherein the endpoint is one of multiple IMS services each assigned to a different realm, and wherein the method further comprises generating a bill for the initiating device based on the second realm.

7. The non-transitory computer-readable medium of claim **1**, wherein the endpoint is one of multiple IMS services each assigned to a different realm.

8. A communications system offering Internet Protocol Multimedia Subsystem (IMS) services, the communications system comprising:

a subscriber database that stores multiple subscriber profiles, wherein each subscriber profile of the multiple subscriber profiles is associated with a home realm; a memory; and a hardware processor coupled to the memory, wherein the communications system is configured to: mask the home realm of user equipment associated with a subscriber profile in messages between a selected IMS service and the user equipment, wherein the home realm is different than a destination realm associated with the IMS service, wherein the masking comprises translating an IMS registration message so that the destination realm interprets the user equipment as being associated with the destination realm, wherein the home realm is translated into the destination realm upon receiving messages from the user equipment, and wherein the destination realm is translated into the home realm upon receiving messages from the IMS service.

9. The communications system of claim **8**, wherein the subscriber database is a home subscriber server and the communication manager is part of a serving control session control function (S-CSCF) node.

10. The communications system of claim **8**, wherein the subscriber database is a home subscriber server.

11. The communications system of claim **8**, wherein the subscriber database is a home subscriber server (HSS), the translation occurs at least partially in a serving control session control function (S-CSCF) node, and the S-CSCF node uses Diameter interfaces to download subscriber profiles from the HSS.

12. The communications system of claim **8**, wherein the subscriber database is a home subscriber server, the translation occurs at least partially in a serving control session control function (S-CSCF) node, and the S-CSCF node translates a realm field parameter in the SIP REGISTER message from the originating realm to the destination realm.

13. The communications system of claim **8**, wherein each of the IMS services is associated with a different realm that is associated with a different brand.

14. The communications system of claim **8**, wherein the IMS services include white board discussions, video conferencing, Push to talk over Cellular (PoC), Voice over IP (VoIP), real-time content sharing, instant messaging, interactive gaming Voice over LTE (VoLTE), short messaging service (SMS) over IP, Rich Communication Suite (RCS), or Presence.

15. A method for use in a telecommunications network for routing communications, the method comprising: receiving a request from an initiating device to establish a service connection session between the initiating device and an endpoint through an Internet Protocol Multimedia Subsystem (IMS) session,

11

wherein the initiating device is assigned to a first realm,
 and
 wherein the endpoint is associated with a second,
 different realm; and,
 providing a Session Initiation Protocol (SIP) REGISTER 5
 message based on the request to create the IMS session,
 wherein the SIP REGISTER message identifies the
 initiating device as being assigned to the second
 realm;
 wherein the IMS session is created between the initi- 10
 ating device and the endpoint,
 wherein, during the session, the first realm is translated
 into the second realm upon receiving messages from
 the initiating device; and
 wherein, during the session, the second realm is trans- 15
 lated into the first realm upon receiving messages
 from the endpoint.
16. The method of claim **15**, wherein the endpoint is an
 IMS service including white board discussions, video con-
 ferencing, Push to talk over Cellular (PoC), Voice over IP 20
 (VoIP), real-time content sharing, instant messaging, inter-

12

active gaming Voice over LTE (VoLTE), short messaging
 service (SMS) over IP, Rich Communication Suite (RCS), or
 Presence.

17. The method of claim **15**, wherein the request is a SIP
 request and generating the registration message based on the
 request includes setting a realm header field parameter of the
 SIP request to identify the second realm.

18. The method of claim **15**, wherein the method further
 comprises:

receiving a response message from the endpoint,
 wherein the response message from the endpoint iden-
 tifies the second realm; and
 generating a translated response message that identifies
 the first realm instead of the second realm before
 forwarding the message onto the initiating device.

19. The method of claim **15**, wherein the endpoint is one
 of multiple IMS services each assigned to a different realm,
 and wherein the method further comprises generating a bill
 for the initiating device based on the second realm.

* * * * *