



US010355482B2

(12) **United States Patent**
Raneri et al.

(10) **Patent No.:** **US 10,355,482 B2**
(45) **Date of Patent:** **Jul. 16, 2019**

(54) **CONTROLLABLE ELECTRICAL OUTLET WITH A CONTROLLED WIRED OUTPUT**

(71) Applicant: **Lutron Technology Company LLC**,
Coopersburg, PA (US)

(72) Inventors: **Daniel C. Raneri**, Orefield, PA (US);
Joseph C. Guellnitz, Albrightsville, PA (US);
Joel S. Spira, Coopersburg, PA (US)

(73) Assignee: **Lutron Technology Company LLC**,
Coopersburg, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/911,829**

(22) Filed: **Mar. 5, 2018**

(65) **Prior Publication Data**

US 2018/0198278 A1 Jul. 12, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/604,621, filed on May 24, 2017, now Pat. No. 9,912,152, which is a (Continued)

(51) **Int. Cl.**
H01R 13/66 (2006.01)
H01R 25/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H02J 3/005** (2013.01); **H01R 13/6683** (2013.01); **H01R 25/006** (2013.01);
(Continued)

(58) **Field of Classification Search**
USPC 307/24
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,363,269 A 11/1994 McDonald
5,754,445 A 5/1998 Jouper et al.
(Continued)

FOREIGN PATENT DOCUMENTS

WO WO2001/033527 A1 11/1999


Primary Examiner — Rexford N Barnie
Assistant Examiner — Xuan Ly

(74) *Attorney, Agent, or Firm* — Amy Yanek; Glen Farbanish; Philip Smith

(57) **ABSTRACT**

A controllable electrical outlet may be used to control one or more standard electrical outlets. The controllable electrical outlet may include a first connection configured to be electrically coupled to a hot connection, a second connection configured to be electrically coupled to a standard electrical outlet, and a third connection configured to be electrically coupled to a neutral connection. The controllable electrical outlet may also include a load control circuit, a communication circuit, and a control circuit. The load control circuit may be electrically coupled in series between the first and second screw terminals to control power delivered to the standard electrical outlet, and the control circuit may be coupled to the load control circuit and the communication circuit. The control circuit may be configured to control power delivered to the standard electrical outlet in response to a wireless signal received via the communication circuit.

20 Claims, 3 Drawing Sheets



Related U.S. Application Data					
	continuation of application No. 14/634,257, filed on Feb. 27, 2015, now Pat. No. 9,685,783.		7,756,556 B2	7/2010	Patel et al.
			7,938,676 B1	5/2011	Patel et al.
			8,105,094 B2	1/2012	Patel et al.
			8,175,533 B2	5/2012	Schubert
(60)	Provisional application No. 61/946,127, filed on Feb. 28, 2014.		8,417,388 B2	4/2013	Altonen et al.
			8,823,268 B2	9/2014	Saveri, III et al.
			8,918,346 B2	12/2014	Lu et al.
(51)	Int. Cl.		9,167,669 B2	10/2015	Karc et al.
	<i>H01R 31/06</i> (2006.01)		9,172,245 B1	10/2015	Lentine et al.
	<i>H01R 24/78</i> (2011.01)		9,201,481 B2	12/2015	Hirosaka et al.
	<i>H02J 3/00</i> (2006.01)		9,627,928 B2	4/2017	Keswani et al.
(52)	U.S. Cl.		2010/0070217 A1	3/2010	Shimada et al.
	CPC <i>H01R 31/065</i> (2013.01); <i>H01R 24/78</i> (2013.01); <i>Y10T 307/352</i> (2015.04)		2011/0304205 A1	12/2011	Lee
			2012/0194952 A1	8/2012	Crucs
			2012/0296486 A1	11/2012	Marriam, II et al.
(56)	References Cited		2013/0229067 A1	9/2013	DiDonato et al.
	U.S. PATENT DOCUMENTS		2013/0234534 A1	9/2013	Lin
			2014/0132084 A1	5/2014	Pham et al.
	6,252,407 B1 6/2001 Gershen				
	6,380,852 B1 * 4/2002 Hartman H04B 15/02 307/116				

* cited by examiner




Fig. 1




Fig. 2




Fig. 3A




Fig. 3B




Fig. 3C

CONTROLLABLE ELECTRICAL OUTLET WITH A CONTROLLED WIRED OUTPUT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 15/604,621, filed May 24, 2017 (now U.S. Pat. No. 9,912,512, issued Mar. 6, 2018), which is a continuation of U.S. patent application Ser. No. 14/634,257, filed Feb. 27, 2015 (now U.S. Pat. No. 9,685,783, issued Jun. 20, 2017), which claims priority to commonly-assigned U.S. Provisional Application No. 61/946,127, filed Feb. 28, 2014, entitled CONTROLLABLE ELECTRICAL OUTLET WITH A CONTROLLED WIRED OUTPUT, the entire disclosures of which are hereby incorporated by reference.

BACKGROUND

Field of the Disclosure

The present disclosure relates to a load control system for controlling the power delivered to one or more electrical loads, and more particularly, to a load control system comprising a controllable electrical outlet having a controlled wired output for controlling the power delivered to outlets of other electrical outlets and thus electrical loads connected to those outlets.

Description of the Related Art

Many consumers reduce the total cost of electrical energy by reducing the total energy usages of electrical loads, such as lighting loads. For example, lighting loads are often controlled in response to occupancy and vacancy sensors, which detect occupancy and/or vacancy conditions in a space, to save energy. Typically, the lighting loads are turned on when the space is occupied and turned off when the space is unoccupied. In addition, consumers are becoming more sensitive to the amount of energy consumed by electrical loads, such as plug-in electrical loads that are plugged into electrical receptacles. Such plug-in electrical loads may still consume energy to maintain a standby mode when “turned off” and are often referred to as “vampire” loads. Some standards (such as ASHRAE 90.1 and California Title 24) are now requiring that many electrical outlets installed in new construction or major renovations must be controlled (e.g., switched) to provide energy savings. For example, the electrical outlets may be controlled in response to a time-clock and/or an occupancy or vacancy sensor.

Some prior art systems for controlling (e.g., switching) electrical outlets include load control devices that may be remotely-located, for example, out of view above a ceiling of a room, behind a wall of a room, or in a remote electrical closet. Installation of these prior art systems may be complicated since electrical wires need to be run from the remotely-located load control devices to the electrical outlets. The load control devices may be responsive to input devices (e.g., wireless transmitters), such as timeclocks and/or an occupancy or vacancy sensors. However, to program the load control device to be responsive to the input devices, the remotely-located load control devices must be accessed (e.g., to press a button on the load control device), which increases the time (and thus the cost) required to program the system since the load control device is remotely located from the input devices. Further, the need to have an

additional load control device for controlling the electrical outlets adds cost to the load control system.

Some prior art electrical outlets are configured to directly receive wireless signals, e.g., radio-frequency (RF) signals, such that an additional remotely-located load control device is not required to control the electrical outlets. However, these RF-responsive electrical outlets cost more than a standard electrical outlet. In order to provide control of most of the electrical outlets in a building, an RF-responsive electrical outlet must be installed in each and every wallbox where control of plug-in electrical loads is desired, which greatly adds to the cost of the load control system.

SUMMARY

As described herein, a load control system having a controllable electrical outlet may provide a low cost solution for controlling a plurality of standard electrical outlets. The load control system may not require any additional electrical devices (e.g., other than the controllable electrical outlet) to control the standard electrical outlets, which for example, may make it simple to install. The controllable electrical outlet may be coupled in series between a power source and at least one standard electrical outlet for controlling the power delivered to the standard electrical outlet. The controllable electrical outlet may comprise one or more of: (1) at least one electrical receptacle adapted to receive a plug of a plug-in electrical load; (2) a first electrical connection (e.g., screw terminal) adapted to be electrically coupled to the power source for receiving a hot voltage (e.g., for powering the electrical load); (3) a second electrical connection (e.g., screw terminal) adapted to be electrically coupled to the standard electrical outlet; (4) a third electrical connection (e.g., screw terminal) adapted to be electrically coupled to a neutral connection; (5) a load control circuit coupled in series electrical connection between the first and second electrical connections for controlling the power delivered to the standard electrical outlet; (6) a communication circuit for receiving a digital message; and/or (7) a digital control circuit coupled to the load control circuit and the communication circuit for controlling the power delivered to the standard electrical outlet in response to the digital message received via the communication circuit.

The controllable electrical outlet may also comprise one or more actuators. An actuator may provide a user interface for configuring the controllable electrical outlet. For example, an actuator may be used to associate the controllable electrical outlet with an input device (e.g., a radio-frequency (RF) transmitter), such that the communication circuit is able to receive the digital message from the input device. The controllable electrical outlet may be installed in a standard electrical wallbox, e.g., replacing a previously-installed standard electrical outlet. The actuator may be located on an exterior face of the controllable electrical outlet, for example, such that it may be easily accessed to associate the controllable electrical outlet with the input device thus simplifying configuration of the load control system. The communication circuit (e.g., an RF receiver and antenna) may be located in the controllable electrical outlet (e.g., in the same room as an input device), for example, to provide optimum reception of wireless signals from an input device. The controllable electrical outlet may be controlled manually (e.g., in response to remote controls) and/or automatically (e.g., in response to sensors and/or timeclocks). The controllable electrical outlet may also be configured to measure the power consumed by electrical loads plugged

into the second electrical connection and report the power usage information via the RF signals.

In addition, a load control system for controlling one or more plug-in electrical loads adapted to receive power from a power source is described herein. The load control system may comprise a standard electrical outlet adapted to receive power from the power source, a controllable electrical outlet adapted to receive power from the power source, and an input device configured to transmit a digital message to the controllable electrical outlet. The controllable electrical outlet may comprise at least one electrical receptacle configured to receive a plug of a plug-in electrical load and an electrical connection configured to be electrically coupled to the standard electrical outlet. The controllable electrical outlet may be configured to control the power delivered to the standard electrical outlet in response to the digital message received via the communication circuit.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a simple diagram of an example load control system having a controllable electrical outlet.

FIG. 2 is a simplified block diagram of an example controllable electrical outlet.

FIGS. 3A-3C are perspective views of example controllable electrical outlets.

DETAILED DESCRIPTION

FIG. 1 is a simple diagram of an example load control system 100 having a load control device (e.g., a controllable electrical outlet 110), a plurality of standard electrical outlets 120, and a plurality of plug-in electrical loads (e.g., a computer 104 and a monitor 106). The controllable electrical outlet 110 may be adapted to be installed in a standard electrical wallbox (not shown). The controllable electrical outlet 110 may be adapted to be connected to a power source, such as an alternating-current (AC) power source 102 for receiving a hot voltage V_H (e.g., an AC mains line voltage, such as 120 V at 60 Hz or 230 V at 50 Hz) at a line voltage input 116 (e.g., a hot terminal). The controllable electrical outlet 110 may also be connected to the neutral side of the AC power source 102. Alternatively or additionally, the controllable electrical outlet 110 may be configured to receive power from a direct-current (DC) power source.

The controllable electrical outlet 110 may comprise upper and lower receptacles 112, 114 into which the plug of a plug-in electrical load may be plugged. Each receptacle 112, 114 may have a hot connection and a neutral connection for receipt of the corresponding prongs of an electrical plug. The controllable electrical outlet 110 may provide the hot voltage V_H at the upper receptacle 112, such that any electrical loads plugged into the upper receptacle are continuously powered. The controllable electrical outlet 110 may comprise an internal load control circuit (not shown), e.g., a relay for generating a switched-hot voltage V_{SH} , which may be provided at the lower receptacle 114. Accordingly, any electrical loads plugged into the lower receptacle 114 may be powered and unpowered in response to closing and opening the relay, respectively. Alternatively, the upper and lower receptacles 112, 114 could both provide the hot voltage V_H or both could provide the switched-hot voltage V_{SH} , or the controllable electrical outlet 110 may provide the hot voltage V_H at the lower receptacle 114 and the switched-hot voltage V_{SH} at the upper receptacle 112.

The controllable electrical outlet 110 may also comprise a controlled wired output 118 (e.g., a switched-hot terminal)

for providing the switched voltage V_{SH} to the standard electrical outlets 120. The standard electrical outlets 120 may each be configured to receive both the hot voltage V_H and the switched-hot voltage V_{SH} . For example, the standard electrical outlets 120 may receive the hot voltage V_H via an electrical wire 126 connected to the line voltage input 116 of the controllable electrical outlet 110. The standard electrical outlets 120 may receive the switched-hot voltage V_{SH} via an electrical wire 128 connected to the controlled wired output 118 of the controllable electrical outlet 110. One or more of the standard electrical outlets 120 may also be connected to the neutral side of the AC power source 102. The controllable electrical outlet 110 may “pass through” the hot voltage V_H to provide the hot voltage V_H from the AC power source 102 to the electrical wire 126 (e.g., directly). Alternatively, the electrical wire 126 may be wired to the hot side of the AC power source 102 around the controllable electrical outlet 110, such that the hot voltage V_H does not pass through the controllable electrical outlet 110 on its way to the standard electrical outlet 120.

Each of the standard electrical outlets 120 may comprise upper and lower receptacles 122, 124 into which an electrical load may be plugged. The upper receptacle 122 of a standard electrical outlet 120 may be electrically coupled to the electrical wire 126 for receiving the hot voltage V_H , such that any electrical loads plugged into the upper receptacles are continuously powered. The lower receptacle 124 of a standard electrical outlet 120 may be electrically coupled to the electrical wire 128 for receiving the switched-hot voltage V_{SH} , such that any electrical loads plugged into the lower receptacle may be powered and unpowered in response to the closing and opening, respectively, of the relay of the controllable electrical outlet 110. Referring to the example of FIG. 1, the computer 104 may be adapted to be plugged into the upper receptacle 122 of one of the standard electrical outlets 120 (e.g., such that the computer 104 is continuously powered), while the monitor 106 may be adapted to be plugged into the lower receptacle 124 of one of the standard electrical outlets (e.g., such that the monitor 106 may be turned on and off by the controllable electrical outlet 110). Alternatively, the upper and lower receptacles 122, 124 of a standard electrical outlet 120 could both be coupled to the hot voltage V_H or could both be coupled to the switched-hot voltage V_{SH} .

The controllable electrical outlet 110 may be configured to measure the magnitude of the total load current conducted by one or more of the plug-in electrical loads plugged into the controllable electrical outlet 110 and/or the standard electrical outlets 120. For example, the controllable electrical outlet 110 may be configured to measure the magnitude of a first load current conducted by the switched electrical loads (e.g., the electrical loads connected to the lower receptacle 124), and the magnitude of a second load current conducted by the unswitched electrical loads (e.g., the electrical loads connected to the upper receptacle 122).

The controllable electrical outlet 110 may be configured to control the relay to turn the electrical loads plugged into the lower receptacles 114, 124 and/or the standard electrical outlets 120 on and off in response to wireless signals, e.g., radio-frequency (RF) signals 108, received from one or more input devices (e.g., RF transmitters). For example, the input devices may comprise a remote control device 130, an occupancy sensor 140, and/or a system controller 150 (e.g., a central controller or gateway device). As such, the controllable electrical outlet 110 may be controlled automatically (e.g., via an occupancy sensor 140) or manually (e.g., via a remote control device 130). Because the controllable

5

electrical outlet **110** may comprise the controlled wired output **118** for controlling the standard electrical outlets **120**, the standard electrical outlets **120** do not need to be responsive to the RF signals **106** in order to switch the respective plug-in electrical loads on and off, thus greatly reducing the cost of the load control system **100**.

The remote control device **130** may comprise a battery-powered handheld remote control, or could alternatively be mounted to a wall or supported on a pedestal to be mounted on a tabletop. Examples of battery-powered remote control devices are described in greater detail in commonly-assigned U.S. Pat. No. 8,330,638, issued Dec. 11, 2012, entitled WIRELESS BATTERY-POWERED REMOTE CONTROL HAVING MULTIPLE MOUNTING MEANS, the entire disclosures of which are hereby incorporated by reference.

The remote control device **130** may transmit digital messages to the controllable electrical outlet **110** via the RF signals **108** in response to actuations of one or more buttons **132** for turning the electrical loads plugged into the lower receptacles **114**, **124** on and off. The remote control device **130** may be associated with the controllable electrical outlet **110** by actuating one or more of the buttons **132** of the remote control device and an actuator (e.g., programming button **119**) of the controllable electrical outlet **110**. Since the controllable electrical outlet **110** may be adapted to be installed in a standard electrical wallbox and the programming button **119** may be located on the controllable electrical outlet **110**, the programming button **119** may be easily accessed to associate the controllable electrical outlet **110** with the remote control device **130**. In addition, the controllable electrical outlet **110** may be installed in the same room in which the remote control device **130** is located to enhance the reliability of the RF communications. Examples of methods of associating wireless control devices are described in greater detail in commonly-assigned U.S. Patent Application Publication No. 2008/0111491, published May 15, 2008, entitled RADIO-FREQUENCY LIGHTING CONTROL SYSTEM; U.S. Patent Application Publication No. 2013/0214609, published Aug. 22, 2013, entitled TWO-PART LOAD CONTROL SYSTEM MOUNTABLE TO A SINGLE ELECTRICAL WALLBOX; and U.S. patent application Ser. No. 13/830,237, filed Mar. 14, 2013, entitled COMMISSIONING LOAD CONTROL SYSTEMS; the entire disclosures of which are hereby incorporated by reference.

The occupancy sensor **140** may be configured to detect occupancy and vacancy conditions in the space in which the load control system **100** is installed. The occupancy sensor **140** may transmit digital messages to the controllable electrical outlet **110** via the RF signals **108** in response to detecting the occupancy or vacancy conditions. The controllable electrical outlet **110** may be configured to turn the electrical loads plugged into the lower receptacles **114**, **124** on in response to an occupancy condition and off in response to a vacancy condition. The occupancy sensor **140** may be associated with the controllable electrical outlet **110** by actuating a button on the occupancy sensor and/or an actuator (e.g., the programming button **119**) of the controllable electrical outlet **110**. Since the controllable electrical outlet **110** may be located in the same room as the occupancy sensor **140**, the occupancy sensor **140** may be easily associated with the controllable electrical outlet **110** and reliable RF communications may be provided. Alternatively, the occupancy sensor **140** may operate as a vacancy sensor to only turn off the lighting loads in response to detecting a vacancy condition (e.g., to not turn on the lighting loads in

6

response to detecting an occupancy condition). Examples of RF load control systems having occupancy and vacancy sensors are described in greater detail in commonly-assigned U.S. Pat. No. 8,009,042, issued Aug. 30, 2011 Sep. 3, 2008, entitled RADIO-FREQUENCY LIGHTING CONTROL SYSTEM WITH OCCUPANCY SENSING; U.S. Pat. No. 8,199,010, issued Jun. 12, 2012, entitled METHOD AND APPARATUS FOR CONFIGURING A WIRELESS SENSOR; and U.S. Pat. No. 8,228,184, issued Jul. 24, 2012, entitled BATTERY-POWERED OCCUPANCY SENSOR, the entire disclosures of which are hereby incorporated by reference.

The system controller **150** may be configured to communicate with a network **152** (e.g., a wireless or wired local area network) via a wired digital communication link **154** (e.g., an Ethernet communication link) for access to the Internet. Alternatively or additionally, the system controller **150** may be wirelessly connected to the network **152**, e.g., using Long-Term Evolution (LTE) or Wi-Fi technology. For example, the system controller **150** may be configured to receive digital messages (e.g., Internet Protocol packets) via the network **152** from a network device (not shown), such as a smart phone (e.g., an iPhone® smart phone, an Android® smart phone, or a BlackBerry® smart phone), a personal computer, a laptop, a wireless-capable media device (e.g., MP3 player, gaming device, or television), a tablet device, (e.g., an iPad® hand-held computing device), a Wi-Fi or wireless-communication-capable television, or any other suitable Internet-Protocol-enabled device. Examples of load control systems operable to communicate with network devices on a network are described in greater detail in commonly-assigned U.S. Patent Application Publication No. 2013/0030589, published Jan. 31, 2013, entitled LOAD CONTROL DEVICE HAVING INTERNET CONNECTIVITY, the entire disclosure of which is hereby incorporated by reference.

The system controller **150** may operate as a central controller for the load control system **100**. The system controller **150** may operate as a gateway device to simply relay digital messages between the network **152** and the controllable electrical outlet **110**. The system controller **150** may be configured to transmit digital messages via the RF signals **108** to the controllable electrical outlet **110** for turning on and off the electrical loads plugged into the controllable electrical outlet **110** and/or the standard electrical outlets **120**. Accordingly, the controllable electrical outlet **110** may be responsive to data received by the system controller **150** from the Internet, such as weather information and emergency status information. The system controller **150** may be further configured to transmit digital messages including one or more of: a timeclock command, a load shed command, a demand response command, a peak demand command, or time-of-day pricing information. The system controller **150** may be configured to control the controllable electrical outlet **110** in accordance with one or more timeclock events of a timeclock schedule, for example, to turn on the switched electrical loads during the day and to turn off the switched electrical loads at night. In addition, the controllable electrical outlet **110** may be configured to transmit feedback information, such as the status and energy consumption of the controlled loads (e.g., load current), back to the system controller **150**, which may be configured to report the information to an external device via the network **152**.

The controllable electrical outlet **110** may be configured to store information regarding the type of input device from which the controllable electrical outlet **100** received the

digital message. The controllable electrical outlet **110** may be configured to store information regarding how the controllable electrical outlet **110** controlled the electrical loads in response to receiving the digital message. For example, this may be performed by the controller electrical outlet **110** after controlling the electrical loads plugged into the controllable electrical outlet **110** and/or the standard electrical outlets **120** in response to a digital messages received via the RF signals **108**. The controllable electrical outlet **110** may transmit this information to the system controller **150**. The system controller **150** may analyze this information to determine how much energy is saved in response to certain types of input devices. For example, the system controller **150** may be configured to determine how much energy is saved as a result of the controllable electrical outlet **110** turning off the electrical loads plugged into the controllable electrical outlet **110** and/or the standard electrical outlets **120** in response to the occupancy sensor **140** versus how much energy is saved as a result of the controllable electrical outlet turning off the electrical loads in response to the remote control device **130**.

The controllable electrical outlet **110** may be configured to determine a balance between the amount of power consumed by the switched and unswitched electrical loads and report this information to the system controller **150**. The system controller **150** may be configured to transmit (e.g., to a network device via the network **152**) a digital message including an alert that the amount of power consumed by the switched and unswitched electrical loads is unbalanced, for example, if the unswitched electrical loads are consuming a much greater amount of power than the switched electrical loads. For example, the alert may be included in an email or text message sent to a building manager.

Some plug-in electrical loads may still consume energy to maintain a standby mode when off. These electrical loads may be referred to as “vampire” loads. In addition, some plug-in power supplies may still consume energy even when the power supply is not charging a rechargeable load. The controllable electrical outlet **110** may be configured to detect whether one or more of the plug-in electrical loads plugged into the controllable electrical outlet **110** and/or the standard electrical outlets **120** are off, are in the standby mode, and/or are not charging a rechargeable load. The controllable electrical outlet **110** may be configured to determine that a plug-in electrical load is off, is in standby mode, and/or is not charging a rechargeable load if the magnitude of the load current conducted by the plug-in electrical load is less than a predetermined current threshold. For example, the controllable electrical outlet **110** may be configured to remove power from the plug-in electrical load if the controllable electrical outlet has received a digital message indicating a vacancy condition from the occupancy sensor **140** and has determined that the plug-in electrical load is off, is in the standby mode, and/or is not charging a rechargeable load. The controllable electrical outlet **110** will not remove power from the plug-in electrical load when the load is on or charging. For example, if a television is on, the television is considered to be in use independent of whether the room is occupied or not. Perhaps the user is listening to a particular program on the television from another room. When the television is turned off (e.g., changed to standby mode), the controllable electrical outlet **110** may disconnect the television from the AC power source when the room becomes unoccupied, for example, to save energy.

The plug-in electrical load may be configured to communicate (e.g., wirelessly communicate), to the system controller **150**, information relating to whether the plug-in

electrical load is off, in the standby mode, and/or not charging a rechargeable load. For example, the plug-in electrical load may be configured to send a digital message to the system controller **150** when the plug-in electrical load is in the standby mode. Accordingly, the system controller **150** may be configured to determine that the plug-in electrical load is in a standby mode and control the controllable electrical outlet **110** (e.g., the load control circuit of the controllable electrical outlet **110**) to disconnect power from the plug-in electrical load. For example, the system controller **150** may send a digital message to the controllable electrical outlet **110** indicating that the controllable electrical outlet **110** should disconnect power from the plug-in electrical load

The plug-in electrical load may be configured to communicate (e.g., wirelessly communicate), to the system controller **150**, information relating to an electrical signature of the plug-in electrical load. The system controller **150** may be configured to compare the electrical signature of the plug-in electrical load to one or more electrical signatures stored in a memory. The system controller **150** may be configured to send a digital message to the controllable electrical outlet **110** to cease controlling the power delivered to the plug-in electrical load in response to the digital message, for example, if the electrical signature of the plug-in electrical load matches one of the electrical signatures stored in the memory.

Some plug-in electrical loads may be critical loads that should be continuously powered (e.g., computers, medical devices, etc.). The controllable electrical outlet **110** may be configured to determine if a critical load is plugged into the controllable electrical outlet **110** and/or the standard electrical outlets **120** and to prevent the critical load from being turned off, e.g., by disabling control of the critical load by the input devices (e.g., the remote control device **130**, the occupancy sensor **140**, and/or the controller **150**). For example, the controllable electrical outlet **110** may be configured to determine that the computer **104** is plugged into one of the controllable electrical outlet **110** and/or the standard electrical outlets **120** by monitoring an electrical signature of the load current drawn by the computer. The controllable electrical outlet **110** may be configured to record and store the electrical signature of the load current conducted by the computer **104** when the computer **104** is plugged into the controllable electrical outlet **110** and/or the standard electrical outlets **120**, e.g., when the load control system **100** is first configured after installation. The controllable electrical outlet **110** may also have one or more predetermined electrical signatures of critical loads stored in memory prior to installation. During normal operation, the controllable electrical outlet **110** may be configured to compare an electrical signature drawn by an electrical load to one or more of the plurality of electrical signatures stored in memory. If the controllable electrical outlet **110** determines that an electrical load plugged into the controllable electrical outlet **110** and/or a standard electrical outlet **120** is a critical load via its electrical signature (e.g., that the electrical load is the computer **104**), the controllable electrical outlet **110** may be configured to continuously power the electrical load at all times, e.g., by not disconnecting power from the electrical load in response to the remote control device **130**, the occupancy sensor **140**, and/or the controller **150**.

The controllable electrical outlet **110** may be configured to determine that the room in which an electrical load (e.g., the computer **104** and/or the monitor **106**) is located is occupied in response to the magnitudes of the load currents

conducted by the switched and/or unswitched electrical loads. For example, if the magnitude of the load current conducted by the computer **104** has increased and/or is actively changing, the controllable electrical outlet **110** may be configured to determine that the room is occupied. If the controllable electrical outlet **110** determines that one or more of the electrical loads plugged into the controllable electrical outlet **110** and/or the standard electrical outlets **120** are off, are in the standby mode, and/or are not charging a rechargeable load, the controllable electrical outlet **110** may determine that the room is vacant. The controllable electrical outlet **110** may be configured to turn on and off the electrical loads plugged into the controllable electrical outlet **110** and/or the standard electrical outlets **120** in response to the occupancy and/or vacancy conditions determined from the magnitudes of the load currents. Alternatively or additionally, the system controller **150** may be configured to determine information regarding an occupancy or vacancy condition in a space in which the controllable electrical outlet **110** is installed in response to the magnitude of the load current measured by the controllable electrical outlet **110**. For example, the controllable electrical outlet **110** may transmit, to the system controller **150**, a digital message that includes information relating to the magnitudes of the load currents conducted by the switched and/or unswitched electrical loads.

As described above, the remote control device **130**, the occupancy sensor **140**, and/or the system controller **150** may operate as a control-source device (e.g., an RF transmitter) and the controllable electrical outlet **110** may operate as a control-target device (e.g., an RF receiver). Alternatively or additionally, the control devices of the load control system **100** may comprise an RF transceiver, such that the devices are able to transmit and receive the RF signals **108**. For example, the controllable electrical outlet **110** may be configured to transmit feedback information, such as the status and energy consumption of the controlled loads, back to the system controller **150**, which may be configured to report the information to external devices via the network **152**. Examples of RF load control systems are described in commonly-assigned U.S. Pat. No. 5,905,442, issued on May 18, 1999, entitled METHOD AND APPARATUS FOR CONTROLLING AND DETERMINING THE STATUS OF ELECTRICAL DEVICES FROM REMOTE LOCATIONS, and U.S. Patent Application Publication No. 2014/0001977, published Jan. 2, 2014, entitled LOAD CONTROL SYSTEM HAVING INDEPENDENTLY-CONTROLLED UNITS RESPONSIVE TO A BROADCAST CONTROLLER, the entire disclosures of which are both hereby incorporated by reference.

In addition, the controllable electrical outlet **110** may operate a signal repeater of the load control system **100**. For example, the controllable electrical outlet **110** may be configured to receive a digital message from one of the control devices of the load control system **100** (e.g., the remote control device **130**, the occupancy sensor **140**, the system controller **150**, or another controllable electrical outlet) and to retransmit the digital message to other control devices of the load control system (e.g., the system controller **150** or another controllable electrical outlet). Examples of RF load control systems having signal repeaters are described in greater detail in commonly-assigned U.S. Pat. No. 5,848,054, issued Dec. 8, 1998, entitled REPEATER FOR TRANSMISSION SYSTEM FOR CONTROLLING AND DETERMINING THE STATUS OF ELECTRICAL DEVICES FROM REMOTE LOCATIONS, and U.S. Pat. No. 6,803,728, issued Oct. 12, 2004, entitled SYSTEM FOR

CONTROL OF DEVICES, the entire disclosures of which are hereby incorporated by reference.

Since the controllable electrical outlet **110** may be adapted to be installed in the standard electrical wallbox and may be responsive to the RF signals **108** (e.g., that are transmitted directly to the controllable electrical outlet **110**), the load control system **100** may not require any additional control devices (e.g., load control devices installed above the ceiling of the room, behind the walls of the room, or in an electrical closet) in order to provide control of the electrical loads plugged into the controllable electrical outlet **110** and the standard electrical outlets **120** in response to the RF signals **108**. This reduces the overall cost of the load control system **100** and simplifies the installation of the load control system **100** since no additional control devices need to be installed.

The controllable electrical outlet **110** could be responsive to other types of input devices, such as, for example, daylight sensors, radiometers, cloudy-day sensors, shadow sensors, window sensors, temperature sensors, humidity sensors, pressure sensors, smoke detectors, carbon monoxide detectors, air-quality sensors, motion sensors, security sensors, proximity sensors, fixture sensors, partition sensors, keypads, kinetic or solar-powered remote controls, key fobs, cell phones, smart phones, tablets, personal digital assistants, personal computers, laptops, timeclocks, audio-visual controls, safety devices (such as fire protection, water protection, and medical emergency devices), power monitoring devices (such as power meters, energy meters, utility submeters, utility rate meters), residential, commercial, or industrial controllers, interface devices with other control systems (such as security systems and emergency alert systems), and/or any combination of these input devices. One or more of the different types of input devices may be provided in a single load control system **100**.

The load control system **100** may also comprise one or more other types of plug-in electrical load and/or switched electrical loads, such as, for example, lighting loads (e.g., incandescent lamps, halogen lamps, electronic low-voltage lighting loads, and magnetic low-voltage lighting loads); dimming ballasts for driving gas-discharge lamps; light-emitting diode (LED) drivers for driving LED light sources; table or floor lamps; screw-in luminaires including dimmer circuits and incandescent or halogen lamps; screw-in luminaires including ballasts and compact fluorescent lamps; screw-in luminaires including LED drivers and LED light sources; motor loads, such as ceiling fans and exhaust fans; motorized window treatments; projection screens; motorized interior or exterior shutters; heating and/or cooling systems; heating, ventilation, and air-conditioning (HVAC) systems; air conditioners; compressors; electric baseboard heater controllers; controllable dampers; variable air volume controllers; fresh air intake controllers; ventilation controllers; hydraulic valves for use in radiators and radiant heating system; humidity control units; humidifiers; dehumidifiers; water heaters; boiler controllers; pool pumps; refrigerators; freezers; appliances; televisions; computer monitors; printers; copiers; fax machines; video cameras; audio systems; amplifiers; speakers; overhead projectors; visual presenters; smart boards; coffee makers; toasters; elevators; power supplies; generators; electric chargers; electric vehicle chargers; medical devices (e.g., heart/lung machines), or alternative energy controllers.

FIG. 2 is a simplified block diagram of an example controllable electrical outlet **200** that may be deployed as, for example, the controllable electrical outlet **110** of the load control system **100** shown in FIG. 1. The controllable electrical outlet **200** may be adapted to be mounted in a

standard electrical wallbox. As shown, the controllable electrical outlet **200** may include a line-side hot electrical connection H_{LINE} (e.g., the line voltage input **116**) and a line-side neutral electrical connection N_{LINE} . The line-side hot electrical connection H_{LINE} and the line-side neutral electrical connection N_{LINE} may be coupled to an AC power source **202** (e.g., the AC power source **102**) for receiving a power source voltage (e.g., the hot voltage V_H) from the AC power source **202**. The controllable electrical outlet **200** may further comprise a first load-side hot electrical connection H_{LOAD1} and a first load-side neutral electrical connection N_{OUT1} , which may be provided at an electrical receptacle (e.g., the upper unswitched receptacle **112** of the controllable electrical outlet **110**) for powering a first electrical load (e.g., a first plug-in electrical load). The hot voltage V_H received at the line-side hot electrical connection H_{LINE} may be fed through the controllable electrical outlet **200** to the first load-side hot electrical connection H_{LOAD1} .

The controllable electrical outlet **200** may further comprise a second load-side hot electrical connection H_{LOAD2} and a second load-side neutral electrical connection N_{LOAD2} , which may also be provided at an electrical receptacle (e.g., the lower switched receptacle **114** of the controllable electrical outlet **110**) for powering a second electrical load (e.g., a second plug-in electrical load). The controllable electrical outlet **200** may comprise a load control circuit **210** (e.g., a controllable switching circuit, such as a relay) coupled in series electrical connection between the line-side hot electrical connection H_{LINE} and the second load-side hot electrical connection H_{LOAD2} and at least one operating coil for opening and closing the SPST switch. The load control circuit **210** may be rendered conductive and non-conductive in response to a control circuit **212** (e.g., a digital control circuit) to provide a switched-hot voltage (e.g., the switched-hot voltage V_{SH}) at the second load-side hot electrical connection H_{LOAD2} for turning the second electrical load on and off. For example, the control circuit **212** may be coupled to the at least one operating coil of the relay for opening and closing the SPST switch of the relay. The control circuit **212** may include one or more of a processor (e.g., a microprocessor), a microcontroller, a programmable logic device (PLD), a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), or any suitable processing device.

The controllable electrical outlet **200** may further comprise a third load-side hot electrical connection H_{LOAD3} and a third load-side neutral electrical connection N_{LOAD3} . For example, the third load-side hot electrical connection H_{LOAD3} may be provided at a wired electrical connection, such as a screw terminal (e.g., the controlled wired output **118** of the controllable electrical outlet **110**) for powering one or more downstream standard electrical outlets (e.g., the standard electrical outlets **120**). The third load-side neutral electrical connection N_{LOAD3} may also be provided at a screw terminal. However, the third load-side neutral electrical connection N_{LOAD3} may be an optional connection since the third load-side neutral electrical connection N_{LOAD3} is coupled to the line-side neutral electrical connection N_{LINE} (e.g., which is coupled to the neutral side of the AC power source **202**). The switched-hot voltage V_{SH} may be provided at the third load-side switched-hot electrical connection H_{LOAD3} . The downstream electrical outlets may receive the switched-hot voltage V_{SH} via an electrical wire

208 (e.g., the electrical wire **128** of FIG. 1). The control circuit **212** may be configured to control the load control circuit **210** for connecting power to or disconnecting power from one or more of the receptacles of each of the downstream electrical outlets. The downstream electrical outlets may receive the hot voltage V_H via an electrical wire (e.g., the electrical wire **126** of FIG. 1) that is wired to the line-side hot electrical connection H_{LINE} in the electrical wallbox of the controllable electrical outlet **200**.

Alternatively or additionally, the load control circuit **210** may comprise a dimmer circuit or driver circuit for controlling the amount of power delivered to the electrical loads connected to the second load-side hot electrical connection H_{LOAD2} , the third load-side hot electrical connection H_{LOAD3} , and/or the downstream electrical outlets. For example, the load control circuit **210** may comprise a bidirectional semiconductor switch (e.g., a triac), which may be controlled by the control circuit **212** using a standard phase-control dimming technique.

The controllable electrical outlet **200** may comprise one or more sense circuits for detecting and/or measuring the power being consumed by the electrical loads plugged into the controllable electrical outlet **200** and/or the downstream electrical outlets. For example, the controllable electrical outlet **200** may comprise a first sense circuit **214** coupled in series between the line-side hot electrical connection H_{LINE} and the first load-side hot electrical connection H_{LOAD1} for measuring a load current conducted by the first electrical load, and a second sense circuit **216** coupled in series with the load control circuit **210** for measuring a load current conducted by the second electrical loads and one or more electrical loads plugged into the downstream electrical outlets. The sense circuits **214**, **216** may generate respective first and second sense signals V_{S1} , V_{S2} that are received by the control circuit **212** and are representative of the magnitudes of the respective load currents.

While the downstream electrical outlets may receive the hot voltage V_H via an electrical wire that is wired to the line-side hot electrical connection H_{LINE} as described above, the downstream electrical outlets could (e.g., alternatively) receive power through the controllable electrical outlet **200**. For example, the controllable electrical outlet **200** could comprise one or more additional electrical connections to which the unswitched receptacles of the downstream electrical outlets could be connected. The first sense circuit **214** could be coupled to the additional electrical connections, for example, such that a total load current of the first electrical load and the unswitched receptacles of the downstream electrical outlets may be conducted through the first sense circuit **214**. Accordingly, the magnitude of the first sense signal V_{S1} generated by the first sense circuit **214** may be representative of the total load current of the unswitched electrical loads coupled to the controllable electrical outlet **200**, and the magnitude of the second sense signal V_{S2} generated by the sense circuit **216** may be representative of the total load current of the switched electrical loads controlled by the controllable electrical outlet **200**.

The controllable electrical outlet **200** may comprise a communication circuit **218**, for example, a wireless communication circuit (e.g., an RF transceiver coupled to an antenna) for transmitting and receiving digital messages (e.g., via wireless signals, such as the RF signals **108** of FIG. 1). The communication circuit **218** may be configured to receive the digital messages via the RF signals **108** according to a predefined RF communication protocol, such as, for example, one or more of LUTRON CLEAR CONNECT, WIFI, BLUETOOTH, ZIGBEE, Z-WAVE, KNX-RF, LTE,

or ENOCEAN RADIO protocols. Alternatively, the communication circuit **218** may comprise an RF transmitter for only transmitting RF signals and/or an RF receiver for only receiving RF signals. The controllable electrical outlet **200** may be configured to receive the digital messages via a different wireless medium, such as, for example, infrared (IR) signals or sound (e.g., voice). In addition, the communication circuit **218** may comprise a power-line communication (PLC) circuit and/or a wired communication circuit, for example, a digital communication link operating in accordance with a predefined communication protocol (e.g., of Ethernet, IP, XML, Web Services, QS, DMX, BACnet, Modbus, LonWorks, and/or KNX protocols), a serial digital communication link, an RS-485 communication link, an RS-232 communication link, a digital addressable lighting interface (DALI) communication link, a LUTRON ECOSYSTEM communication link, or an analog control link. In addition, the communication circuit **218** could be adapted to receive one of a line-voltage control signal, a phase-control signal, a 0-10V control signal, and a contact closure output control signal.

The controllable electrical outlet **200** may comprise a memory **220** communicatively coupled to the control circuit **212**. The control circuit **212** may be configured to use the memory **220** for the storage and/or retrieval of, for example, the serial numbers of the input devices (e.g., the wireless transmitters) to which the controllable electrical outlet **200** is responsive (e.g., associated with). The memory **220** may be implemented as an external integrated circuit (IC) or as an internal circuit of the control circuit **212**.

The controllable electrical outlet **200** may comprise one or more actuators **222** (e.g., buttons) for providing manual user inputs to the control circuit **212**. For example, the control circuit **212** may be configured to control the load control circuit **210** to render the relay conductive and non-conductive in response to actuations of the actuators **222**. In addition, the control circuit **212** may be configured to associate the controllable electrical outlet **200** with one or more of the input devices (e.g., the remote control device **130**, the occupancy sensor **140**, and the controller **150**) in response to actuations of one or more of the actuators **222** (e.g., the programming button **119** of the controllable electrical outlet **110**).

The controllable electrical outlet **200** may include a power supply **224** coupled between the line-side hot electrical connection H_{LINE} and the line-side neutral electrical connection N_{LINE} for generating a DC supply voltage V_{CC} for powering one or more of the control circuit **212**, the communication circuit **218**, the memory **220**, and other low-voltage circuitry of the controllable electrical outlet **200**.

The control circuit **212** may be configured to control the load control circuit **210** to render the relay conductive and non-conductive in response to digital messages received via RF signals from input devices (e.g., the remote control device **130**, the occupancy sensor **140**, and the system controller **150** shown in FIG. 1). For example, the control circuit **212** may receive digital messages including commands for providing manual control of the switched electrical loads (e.g., from the remote control device **130**) and/or for providing automated control of the switched electrical loads (e.g., from the occupancy sensor **140** and/or the system controller **150**). A system controller (e.g., the system controller **150**) may be configured to transmit digital messages to the controllable electrical outlet **200** to control the switched electrical loads in accordance with one or more timeclock events of a timeclock schedule, for example, to turn on the switched electrical loads during the day and to

turn off the switched electrical loads at night. In addition, the control circuit **212** may be configured to cause the communication circuit **218** to transmit, for example, one or more digital messages including information regarding the power consumed by the unswitched and/or switched electrical loads to the system controller.

After controlling the load control circuit **210** in response to digital messages received via the communication circuit **218**, the control circuit **212** may be configured to store in the memory **220** information regarding the type of input device from which the communication circuit **218** received the digital message, and/or how the control circuit **212** controlled the load control circuit **210** in response to that digital message. The control circuit **212** may transmit this information to the system controller for analysis regarding how much energy is saved in response to certain types of input devices. For example, the system controller **150** may be configured to determine how much energy is saved as a result of the controllable electrical outlet **200** turning off the controlled electrical loads in response to the occupancy sensor **140** versus how much energy is saved as a result of the controllable electrical outlet turning off the controlled electrical loads in response to the remote control device **130**.

The control circuit **210** may be configured to measure the amount of power consumed by the unswitched electrical loads (e.g., in response to the first sense signal V_{S1} generated by the first sense circuit **214**) and/or to determine the amount of power consumed by the switched electrical loads (e.g., in response to the second sense signal V_{S2} generated by the sense circuit **216**). The control circuit **210** may be configured to determine a balance between the amount of power consumed by the unswitched and switched electrical loads and report this information to the system controller. The controllable electrical outlet **200** and/or the system controller may be configured to transmit a digital message including an alert that the amount of power consumed by the unswitched and switched electrical loads is unbalanced (e.g., in an email or text message).

The control circuit **212** may be configured to detect whether one or more of the electrical loads plugged into the controllable electrical outlet and/or the downstream electrical outlets are off, are in the standby mode, and/or are not charging a rechargeable load. The control circuit **212** may be configured to determine that a plug-in electrical load is off, is in standby mode, and/or is not charging a rechargeable load if the magnitude of the load current conducted by the plug-in electrical load is less than a predetermined current threshold. For example, the control circuit **212** may be configured to control the load control circuit **210** to remove power from the plug-in electrical load if the control circuit has received a digital message indicating a vacancy condition from an occupancy or vacancy sensor and has determined that the plug-in electrical load is off, is in the standby mode, and/or is not charging a rechargeable load. The control circuit **212** may not remove power from the plug-in electrical load when the load is on or charging.

The control circuit **212** may be configured to determine if a critical load is plugged into the controllable electrical outlet **220** and/or the downstream electrical outlets. The control circuit **212** may be configured to disable control of the critical load by the input devices (e.g., the remote control device **130**, the occupancy sensor **140**, and/or the controller **150**). For example, the control circuit **212** may be configured to determine that a particular plug-in electrical load (e.g., a computer) is plugged into one of the controllable electrical outlet and/or the downstream electrical outlets by monitoring an electrical signature of the load current drawn by the

electrical load. The control circuit **212** may be configured to record the electrical signature of the load current conducted by a plug-in electrical load plugged into the controllable electrical outlet **200** and/or the downstream electrical outlets (e.g., using one of the first and second sense circuits **214**, **216**) and to store the recorded electrical signature in the memory **220**. The controllable electrical outlet **200** may have one or more predetermined electrical signatures of critical loads stored in the memory **220** prior to installation. The control circuit **212** may be configured to compare an electrical signature drawn by a plug-in electrical load plugged into the controllable electrical outlet **200** and/or the downstream electrical outlets to one or more of the plurality of electrical signatures stored in the memory **220**. If the electrical signature shows that the electrical load plugged into one of the controllable electrical outlet **200** and/or the downstream electrical outlets is a critical load, the control circuit **212** may be configured to continuously power the critical load at all times. For example, the controllable electrical outlet **200** may prevent power from being disconnected from the critical load in response to a signal received from an input device (e.g., the remote control device **130**, the occupancy sensor **140**, and/or the controller **150**).

The control circuit **212** may be configured to determine that the room in which the controllable electrical outlet **200** is located is occupied based on a magnitude of the load current conducted by an electrical load plugged into the controllable electrical outlet **200** and/or a downstream electrical outlet. For example, if the magnitude of the load current conducted by a particular plug-in electrical load has increased and/or is actively changing, the control circuit **212** may be configured to determine that the room is occupied. If the control circuit **212** determines that one or more of the electrical loads plugged into the controllable electrical outlet **200** and/or the downstream electrical outlets are off, are in the standby mode, and/or are not charging a rechargeable load, the control circuit **212** may determine that the room is vacant. The control circuit **212** may be configured to control the load control circuit **210** in response to the occupancy and/or vacancy conditions determined from the magnitudes of one or more load currents.

FIG. 3A is a perspective view of an example controllable electrical outlet **300**. The controllable electrical outlet **300** may be an example of the controllable electrical outlet **110** of FIG. 1 and/or the controllable electrical outlet **200** of FIG. 2. The controllable electrical outlet **300** may comprise a front enclosure portion **302** and a rear enclosure portion **304**. The controllable electrical outlet **300** may be mounted to a standard electrical wallbox. The controllable electrical outlet **300** may include similar circuitry as the controllable electrical outlet **200** (as shown FIG. 2), which may be housed in both the front and rear enclosure portions **302**, **304**. For example, a portion of the electrical circuitry may be located in the rear enclosure portion **304** (e.g., the load control circuit **210** and the power supply **224**) and a portion of the electrical circuitry may be located in the front enclosure portion **302** (e.g., the control circuit **212**, the memory **220**, and the wireless communication circuit **218**). Accordingly, the controllable electrical outlet **300** may comprise a wireless communication circuit that is located outside of the electrical wallbox. The front enclosure portion **302** may comprise a programming button **306** (e.g., the programming button **119** and/or one of the actuators **222**), which may be actuated to associate the controllable electrical outlet **300** with one or more input devices (e.g., wireless transmitters). The controllable electrical outlet **300** may be responsive to

RF signals and may be installed in the same room in which the input devices are located to enhance the reliability of the RF communications.

The rear enclosure portion **304** may comprise a hot screw terminal **308** for receiving a hot voltage from an AC power source (e.g., the line voltage input **116** of the controllable electrical outlet **110** and/or the line-side hot electrical connection H_{LINE} of the controllable electrical outlet **200**). The rear enclosure portion **304** may also comprise at least one neutral terminal (not shown) adapted to be coupled to the neutral side of the AC power source (e.g., the line-side neutral electrical connection N_{LINE} of the controllable electrical outlet **200**). The rear enclosure portion **304** may comprise a wired-output screw terminal **310** (e.g., the controlled wired output **118** of the controllable electrical outlet **110** and/or the third load-side hot electrical connection H_{LOAD3} of the controllable electrical outlet **200**). The wired-output screw terminal **310** may be adapted to be electrically connected to one or more downstream standard electrical outlets (e.g., the standard electrical outlets **120**). The controllable electrical outlet **300** may provide a switched-hot voltage V_{SH} at the wired-output screw terminal **310**, such that the controllable electrical outlet may be able to connect power to or disconnect power from one or more of the receptacles of each of the downstream electrical outlets.

The front enclosure portion **302** may comprise upper and lower receptacles **312**, **314** for receiving the plugs of plug-in electrical loads. For example, the upper receptacle **312** may be an unswitched receptacle (e.g., similar to the upper receptacle **112** of the controllable electrical outlet **110** and/or the first load-side hot and neutral electrical connections H_{LOAD1} , N_{LOAD1} of the controllable electrical outlet **200**) and the lower receptacle **314** may be a switched receptacle (e.g., similar to the lower receptacle **114** of the controllable electrical outlet **110** and/or the second load-side hot and neutral electrical connections H_{LOAD2} , N_{LOAD2} of the controllable electrical outlet **200**). The controllable electrical outlet **300** may also comprise receptacles located on the sides, top, and/or bottom of the front enclosure portion **302** (not shown).

The front enclosure portion **302** may be configured to be detached from the rear enclosure portion **304**. The controllable electrical outlet **300** may comprise a mounting yoke (not shown) that may be connected to the rear enclosure portion **304**. The mounting yoke may be mounted to the electrical wallbox while the front enclosure portion **302** is detached from the rear enclosure portion **304**. The hot screw terminal **308** may be connected to the AC power source and the wired-output screw terminal **310** may be connected to the downstream electrical outlets. After the rear enclosure portion **304** is mounted to the wallbox, the front enclosure portion **302** may be attached to the rear enclosure portion **304**, e.g., via a mounting screw **316**. The front enclosure portion **302** may be adapted to be located (e.g., mostly located) outside the electrical wallbox.

FIG. 3B is a perspective view of another example controllable electrical outlet **320**. The controllable electrical outlet **320** may be an example of the controllable electrical outlet **110** of FIG. 1 and/or the controllable electrical outlet **200** of FIG. 2. The controllable electrical outlet **320** may be mounted to an electrical wallbox. The controllable electrical outlet **320** may comprise a bezel portion **322** adapted to be received through an opening of a faceplate **325**. The controllable electrical outlet **320** may include circuitry that is similar to the circuitry of the controllable electrical outlet **200**. The circuitry may be housed (e.g., housed entirely) in a rear enclosure portion **324** of the controllable electrical

outlet **320**, for example, such that a wireless communication circuit (e.g., the wireless communication circuit **218**) may be located inside of the wallbox. An actuator, such as a programming button **326** may be provided on the bezel portion **322**. The programming button **326** may be actuated to associate the controllable electrical outlet **320** with one or more input devices (e.g., wireless transmitters).

The bezel portion **322** may comprise an upper receptacle **332** (e.g., an unswitched receptacle) and a lower receptacle **334** (e.g., a switched receptacle) for receiving the plugs of plug-in electrical loads (e.g., such as on the controllable electrical outlet **300** shown in FIG. **3A**). The controllable electrical outlet **320** may comprise a mounting yoke (not shown) that is connected to the rear enclosure portion **324** and allows the controllable electrical outlet **320** to be mounted to the electrical wallbox. The faceplate **325** may be attached to the mounting yoke via one or more screws, such as the two screws **336** shown in the example of FIG. **3B**. The controllable electrical outlet **320** may be responsive to RF signals and may be installed in the same room in which the input devices are located to enhance the reliability of the RF communications.

The rear enclosure portion **324** may comprise a hot screw terminal **328** for receiving a hot voltage from an AC power source and a neutral terminal (not shown) adapted to be coupled to the neutral side of the AC power source (e.g., similar to the controllable electrical outlet **300** shown in FIG. **3A**). The rear enclosure portion **324** may also comprise a wired-output screw terminal **330** adapted to be electrically connected to one or more downstream standard electrical outlets. The controllable electrical outlet **320** may provide a switched-hot voltage at the wired-output screw terminal **330**, such that the controllable electrical outlet **320** is able to connect power to or disconnect power from one or more of the receptacles of one or more downstream electrical outlets.

FIG. **3C** is a perspective view of another example controllable electrical outlet **350**. The controllable electrical outlet **350** may be an example of the controllable electrical outlet **110** of FIG. **1** and/or the controllable electrical outlet **200** of FIG. **2**. The controllable electrical outlet **350** may be configured to be plugged into a standard electrical outlet **340** that has upper and lower receptacles **342**, **344**. The standard electrical outlet **340** may comprise a rear enclosure **345** having a first hot screw terminal **346** for receiving a hot voltage from an AC power source, a second hot screw terminal **348** adapted to be electrically connected to one or more downstream standard electrical outlets, and at least one neutral terminal (not shown) adapted to be coupled to the neutral side of the AC power. The first hot screw terminal **346** may be electrically connected to the upper receptacle **342** and the second hot screw terminal **348** may be electrically connected to the lower receptacle **344**. The standard electrical outlet **340** may be adapted to be mounted to a standard electrical wallbox.

The controllable electrical outlet **350** may comprise an enclosure **352** having upper and lower electrical receptacles **354**, **356** (for receiving the plugs of plug-in electrical loads) provided on a front surface **358**. The controllable electrical outlet **350** may comprise upper and lower electrical plugs **360**, **362** provided on a rear surface **364**. The upper and lower electrical plugs **360**, **362** may be adapted to plug into the upper and lower receptacles **342**, **344** of the standard electrical outlet **340**, respectively. Accordingly, the upper electrical plug **360** may be adapted to be coupled to the AC power source via the upper receptacle **342** for receiving the hot voltage V_H . As such, the upper electrical plug **360** may receive the hot voltage V_H , which for example, may be

similar to as described with reference to the line-side hot and neutral electrical connections H_{LINE} , N_{LINE} of the controllable electrical outlet **200**. The lower electrical plug **362** may be adapted to be coupled to the downstream electrical outlets via the lower receptacle **344**. As such, the lower electrical plug **362** may operate similar to the third load-side hot and neutral electrical connections H_{LOAD3} , N_{LOAD3} of the controllable electrical outlet **200**. Thus, the upper electrical plug **360** may operate similar to the line voltage input **116** of FIG. **1**, while the lower electrical plug **362** may operate similar to the wired output **118** of FIG. **1**.

The controllable electrical outlet **350** may include circuitry that is similar to the circuitry of the controllable electrical outlet **200**. The circuitry may be housed (e.g., housed entirely) in the enclosure **352** of the controllable electrical outlet **350** (e.g., such that the wireless communication circuit **218** may be located outside of the wallbox). For example, the upper receptacle **354** may be an unswitched receptacle and the lower receptacle **356** may be a switched receptacle. The enclosure **352** may comprise a programming button **366** (e.g., the programming button **119** and/or one of the actuators **222**), which may be actuated to associate the controllable electrical outlet **350** with one or more input devices (e.g., wireless transmitters). The controllable electrical outlet **350** may be responsive to RF signals and may be installed in the same room in which the input devices are located to enhance the reliability of the RF communications. The controllable electrical outlet **350** may be fixedly attached to the standard electrical outlet **340** via a mounting screw **368** (e.g., a "tamper-proof" screw) received through an opening **369** of the standard electrical outlet **350**, for example, to prevent removal or theft of the controllable electrical outlet **350** after installation.

The controllable electrical outlet **350** may additionally or alternatively comprise upper and lower receptacles **370**, **372** located on a side surface **374** of the enclosure **352**. For example, the upper and lower receptacles **370**, **372** on the side surface **374** may operate the same as the upper and lower receptacle **354**, **356** on the front surface **358**, respectively. In other words, the upper receptacle **370** may be an unswitched receptacle and the lower receptacle **372** may be a switched receptacle. Since the upper and lower receptacles **370**, **372** are arranged at a right angle to the front surface of the standard electrical outlet **340**, the upper and lower receptacles **370**, **372** on the side surface **374** may accommodate electrical plugs if there is not much room between the standard electrical outlet **350** and adjacent furniture. The controllable electrical outlet **350** may additionally or alternatively comprise one or more receptacles located on the top surface and/or bottom surface of the enclosure **352**.

If one of more of the controllable electrical outlets **300**, **320**, **350** includes a load control circuit for controlling the amount of power delivered to the plug-in electrical loads (e.g., a dimmer circuit), the respective electrical outlet may comprise a protrusion at the controlled receptacle for preventing a standard electrical plug from being plugged into the controlled receptacle. Examples of such protrusions for preventing standard plugs from being plugged into a controlled receptacle are described in greater detail in commonly-assigned U.S. Pat. No. 7,198,523, issued Apr. 3, 2007, and U.S. Pat. No. 7,311,558, issued Dec. 25, 2007, both entitled RECEPTACLE AND PLUG THEREFOR, the entire disclosures of which are hereby incorporated by reference.

While the controllable electrical outlets **300**, **320**, **350** shown in FIGS. **3A-3C** have U.S. style receptacles and/or plugs, the controllable electrical outlets **300**, **320** **350** may

19

alternatively or additionally have receptacles and/or plugs of styles used in other countries. In addition, the controllable electrical outlets **300**, **320**, **350** could comprise other types of receptacles, for example, one or more Universal Serial Bus (USB) connectors, and an internal power supply for charging an electrical device, such as the battery of a smart phone.

Although the present invention has been described in relation to particular embodiments thereof, many other variations and modifications and other uses will become apparent to those skilled in the art. It is preferred, therefore, that the present invention be limited not by the specific disclosure herein, but only by the appended claims.

What is claimed is:

1. An electrical outlet comprising:
 - a first connection configured to be electrically coupled to a hot connection;
 - a second connection configured to be electrically coupled to a downstream electrical outlet;
 - an electrical receptacle in electrical connection with the first connection and configured to receive a plug of a plug-in electrical load;
 - a load control circuit electrically coupled between the first and second connections to control power delivered to the downstream electrical outlet;
 - a sense circuit electrically coupled to the load control circuit and configured to measure a magnitude of a load current conducted through the second electrical connection;
 - a communication circuit; and
 - a control circuit coupled to the load control circuit, the sense circuit, and the communication circuit, the control circuit configured to:
 - receive at least one message via the communication circuit;
 - determine that the at least one message comprises an indication to disconnect power;
 - based at least in part on determining that the at least one message comprises the indication to disconnect power, compare the magnitude of the load current conducted through the second electrical connection, as measured by the sense circuit, to a threshold; and
 - when the magnitude of the load current conducted through the second electrical connection is determined to be below the threshold, control the load control circuit to disconnect power from the downstream electrical outlet in response to the indication to disconnect power; and
 - wherein when the magnitude of the load current conducted through the second electrical connection is determined to be above the threshold, the control circuit is configured not to disconnect power from the downstream electrical outlet in response to the indication to disconnect power.
2. The electrical outlet of claim 1, further comprising at least one actuator configured to be actuated;
 - wherein the control circuit is further coupled to the at least one actuator; and
 - wherein the control circuit is further configured to:
 - based at least in part on an actuation of the at least one actuator, control the load control circuit to connect power to or disconnect power from the downstream electrical outlet.
3. The electrical outlet of claim 1, further comprising at least one actuator configured to be actuated;
 - wherein the control circuit is further coupled to the at least one actuator; and

20

wherein the control circuit is further configured to:

- based at least in part on an actuation of the at least one actuator, associate the electrical outlet with a device such that the electrical outlet is responsive to messages transmitted by the device; and

wherein the received at least one message is transmitted by the device.

4. The electrical outlet of claim 3, wherein the electrical outlet is configured to be mounted in an electrical wallbox; and

- wherein the at least one actuator is located on an outside of the electrical outlet such that the at least one actuator is accessible to a user when the electrical outlet is mounted in the electrical wallbox.

5. The electrical outlet of claim 1, wherein the electrical outlet is configured to be mounted in an electrical wallbox.

6. The electrical outlet of claim 1, wherein the load control circuit is further configured to control power delivered to the electrical receptacle.

7. The electrical outlet of claim 6, further comprising a second electrical receptacle in electrical connection with the first connection and configured to receive a plug of a plug-in electrical load, and wherein the load control circuit is not configured to control power delivered to the second electrical receptacle.

8. An electrical outlet comprising:

- a connection configured to be electrically coupled to a hot connection;

- an electrical receptacle in electrical connection with the connection and configured to receive a plug of a plug-in electrical load;

- a load control circuit electrically coupled to the connection and configured to control power delivered to the electrical receptacle;

- a sense circuit electrically coupled to the load control circuit and configured to measure a magnitude of a load current conducted at the electrical receptacle;

- a communication circuit; and

- a control circuit coupled the load control circuit, the sense circuit, and the communication circuit, the control circuit configured to:

- receive at least one message via the communication circuit;

- determine that the at least one message comprises an indication to disconnect power;

- based at least in part on determining that the at least one message comprises the indication to disconnect power, compare the magnitude of the load current conducted electrical receptacle, as measured by the sense circuit, to a threshold; and

- when the magnitude of the load current electrical receptacle is determined to be below the threshold, control the load control circuit to disconnect power from the electrical receptacle in response to the indication to disconnect power; and

- wherein when the magnitude of the load current conducted electrical receptacle is determined to be above the threshold, the control circuit is configured not to disconnect power from the electrical receptacle in response to the indication to disconnect power.

9. The electrical outlet of claim 8, further comprising at least one actuator configured to be actuated;

- wherein the control circuit is further coupled to the at least one actuator; and

21

wherein the control circuit is further configured to:
 based at least in part on an actuation of the at least one
 actuator, control the load control circuit to connect
 power to or disconnect power from the electrical
 receptacle. 5

10. The electrical outlet of claim **8**, further comprising at
 least one actuator configured to be actuated;
 wherein the control circuit is further coupled to the at least
 one actuator; and
 wherein the control circuit is further configured to: 10
 based at least in part on an actuation of the at least one
 actuator, associate the electrical outlet with a device
 such that the electrical outlet is responsive to mes-
 sages transmitted by the device; and
 wherein the received at least one message is transmitted 15
 by the device.

11. The electrical outlet of claim **10**, wherein the electrical
 outlet is configured to be mounted in an electrical wallbox;
 and
 wherein the at least one actuator is located on an outside 20
 of the electrical outlet such that the at least one actuator
 is accessible to a user when the electrical outlet is
 mounted in the electrical wallbox.

12. The electrical outlet of claim **8**, wherein the electrical
 outlet is configured to be mounted in an electrical wallbox. 25

13. The electrical outlet of claim **8**,
 wherein the connection comprises a first connection;
 wherein the electrical outlet further comprises a second
 connection configured to be electrically coupled to a
 downstream electrical outlet; and 30
 wherein the load control circuit is further configured to
 control power delivered to the downstream electrical
 outlet.

14. The electrical outlet of claim **13**, further comprising a
 second electrical receptacle in electrical connection with the 35
 first connection and configured to receive a plug of a plug-in
 electrical load, and wherein the load control circuit is not
 configured to control power delivered to the second electri-
 cal receptacle.

15. An electrical outlet comprising: 40
 a first connection configured to be electrically coupled to
 a hot connection;
 a second connection configured to be electrically coupled
 to a downstream electrical outlet;
 an electrical receptacle in electrical connection with the 45
 first connection and configured to receive a plug of a
 plug-in electrical load;
 a load control circuit electrically coupled between the first
 and second connections and configured to control
 power delivered to the downstream electrical outlet and 50
 to the electrical receptacle, wherein the load control
 circuit is not configured to control power delivered to
 the first electrical outlet;
 a sense circuit electrically coupled to the load control
 circuit and configured to measure a magnitude of a load 55
 current conducted through the load control circuit;
 a control circuit coupled to the load control circuit, the
 sense circuit, and the communication circuit, the con-
 trol circuit configured to:
 receive at least one message via the communication 60
 circuit;

22

determine that the at least one message comprises an
 indication to disconnect power;
 based at least in part on determining that the at least one
 message comprises the indication to disconnect
 power, compare the magnitude of the load current
 conducted through the load control circuit, as mea-
 sured by the sense circuit, to a threshold; and
 when the magnitude of the load current conducted
 through the load control circuit is determined to be
 below the threshold, control the load control circuit
 to disconnect power from the downstream electrical
 outlet and from the electrical receptacle in response
 to the indication to disconnect power; and
 wherein when the magnitude of the load current con-
 ducted through the load control circuit is determined
 to be above the threshold, the control circuit is
 configured not to disconnect power from the down-
 stream electrical outlet and from the electrical recep-
 tacle in response to the indication to disconnect
 power.

16. The electrical outlet of claim **15**, further comprising at
 least one actuator configured to be actuated;
 wherein the control circuit is further coupled to at least
 one actuator; and
 wherein the control circuit is further configured to:
 based at least in part on an actuation of the at least one
 actuator, control the load control circuit to connect
 power to or disconnect power from the downstream
 electrical outlet and the electrical receptacle.

17. The electrical outlet of claim **15**, further comprising at
 least one actuator configured to be actuated;
 wherein the control circuit is further coupled to the at least
 one actuator; and
 wherein the control circuit is further configured to:
 based at least in part on an actuation of the at least one
 actuator, associate the electrical outlet with a device
 such that the electrical outlet is responsive to mes-
 sages transmitted by the device; and
 wherein the received at least one message is transmitted
 by the device.

18. The electrical outlet of claim **17**, wherein the electrical
 outlet is configured to be mounted in an electrical wallbox;
 and
 wherein the at least one actuator is located on an outside
 of the electrical outlet such that the at least one actuator
 is accessible to a user when the electrical outlet is
 mounted in the electrical wallbox.

19. The electrical outlet of claim **15**, wherein the electrical
 outlet is configured to be mounted in an electrical wallbox.

20. The electrical outlet of claim **15**, further comprising a
 second electrical receptacle in electrical connection with the
 first connection and configured to receive a plug of a plug-in
 electrical load, and wherein the load control circuit is not
 configured to control power delivered to the second electri-
 cal receptacle.