



US010381707B2

(12) **United States Patent**  
**Lee et al.**

(10) **Patent No.:** **US 10,381,707 B2**  
(45) **Date of Patent:** **Aug. 13, 2019**

(54) **MULTIPLE WAVEGUIDE STRUCTURE WITH SINGLE FLANGE FOR AUTOMATIC TEST EQUIPMENT FOR SEMICONDUCTOR TESTING**

*H01P 3/16* (2013.01); *H01P 11/002* (2013.01);  
*H01Q 9/045* (2013.01); *H01Q 21/065*  
(2013.01); *G01R 1/24* (2013.01); *H01P 5/024*  
(2013.01)

(71) Applicant: **Advantest Corporation**, Tokyo (JP)

(58) **Field of Classification Search**

CPC .. *H01P 5/18*; *H01P 3/08*; *G01R 1/045*; *G01R 31/2834*

(72) Inventors: **Don Lee**, San Jose, CA (US); **Daniel Lam**, San Jose, CA (US); **Roger Mcaleenan**, San Jose, CA (US); **Kosuke Miyao**, San Jose, CA (US)

USPC ..... 333/1

See application file for complete search history.

(73) Assignee: **ADVANTEST CORPORATION**, Tokyo (JP)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 315 days.

3,643,261 A 2/1972 Kenworthy et al.  
3,902,785 A 9/1975 Matthews  
3,995,238 A 11/1976 Knox et al.  
4,020,875 A 5/1977 Akiba  
(Continued)

(21) Appl. No.: **15/016,133**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Feb. 4, 2016**

CN 201820177 U 5/2011  
EP 1317684 A2 6/2003  
JP 2005354368 12/2005

(65) **Prior Publication Data**

US 2017/0229753 A1 Aug. 10, 2017

*Primary Examiner* — Stephen E. Jones  
*Assistant Examiner* — Samuel S Outten

(51) **Int. Cl.**

*G01R 1/24* (2006.01)  
*G01R 31/28* (2006.01)  
*H01P 5/18* (2006.01)  
*H01P 3/16* (2006.01)  
*H01P 3/12* (2006.01)  
*H01P 3/08* (2006.01)  
*H01Q 21/06* (2006.01)  
*H01Q 9/04* (2006.01)  
*G01R 1/04* (2006.01)  
*H01P 11/00* (2006.01)  
*H01P 5/02* (2006.01)


(57) **ABSTRACT**

Embodiments of the present disclosure use customizable waveguides that can be positioned next to each other in a structure that contains one single flange to provide a physical connection for the waveguides. In this fashion, many waveguides can be positioned within a small area to accommodate a tightly packed patch antenna array so that the waveguides can be positioned very close to the socket. As such, embodiments of the present disclosure allow more waveguides to be packed into a small area by providing a single structure that houses many waveguides and share only a single flange connection element that can be sized appropriately.

(52) **U.S. Cl.**

CPC ..... *H01P 5/18* (2013.01); *G01R 1/045* (2013.01); *G01R 31/2834* (2013.01); *G01R 31/2886* (2013.01); *H01P 3/08* (2013.01); *H01P 3/12* (2013.01); *H01P 3/121* (2013.01);

**20 Claims, 17 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

4,564,260 A 1/1986 Dirmeyer et al.  
 4,848,866 A 7/1989 Feulner et al.  
 4,947,111 A 8/1990 Higman et al.  
 5,102,352 A 4/1992 Arisaka  
 5,181,025 A 1/1993 Ferguson et al.  
 5,488,380 A 1/1996 Harvey et al.  
 5,708,296 A 1/1998 Bhansali  
 5,886,671 A 3/1999 Riemer et al.  
 6,220,870 B1 4/2001 Barabi et al.  
 6,794,887 B1 9/2004 Nelson et al.  
 7,120,840 B1 10/2006 Shimanouchi  
 7,648,285 B2 1/2010 Maletzky et al.  
 8,600,309 B2 12/2013 Chang et al.  
 9,310,422 B2 4/2016 Nath et al.  
 9,490,540 B1 11/2016 Davies et al.  
 9,588,173 B2 3/2017 Isaac et al.  
 9,692,102 B2 6/2017 Herbsommer et al.  
 2003/0210067 A1 11/2003 Miller  
 2006/0097737 A1 5/2006 Parker et al.  
 2007/0066094 A1 3/2007 Kim et al.  
 2007/0152768 A1 7/2007 Mellitz et al.  
 2007/0154155 A1 7/2007 Brist et al.  
 2008/0048639 A1 2/2008 Sutono et al.  
 2009/0153158 A1 6/2009 Dunn et al.

2011/0018657 A1 1/2011 Cheng et al.  
 2011/0316734 A1 12/2011 Svensson  
 2012/0084968 A1 4/2012 Nath et al.  
 2012/0268153 A1 10/2012 Nickel et al.  
 2012/0313659 A1 12/2012 Hsu  
 2013/0016022 A1\* 1/2013 Heiks ..... G02B 6/4415  
 343/791  
 2013/0200912 A1 8/2013 Panagas  
 2013/0200915 A1 8/2013 Panagas  
 2013/0200917 A1 8/2013 Panagas  
 2014/0007674 A1\* 1/2014 Weinzierle ..... H01Q 13/02  
 73/290 V  
 2014/0111239 A1 4/2014 Blair et al.  
 2014/0239994 A1 8/2014 Alves Moreira et al.  
 2014/0285277 A1 9/2014 Herbsommer et al.  
 2014/0312987 A1\* 10/2014 Morita ..... H01P 3/121  
 333/137  
 2015/0168486 A1 6/2015 Isaac et al.  
 2016/0025788 A1 1/2016 Fujita et al.  
 2016/0276996 A1 9/2016 Tze-Meng et al.  
 2016/0356842 A1 12/2016 Lee  
 2017/0102409 A1 4/2017 Sarhad et al.  
 2017/0227598 A1 8/2017 Lam et al.  
 2017/0229754 A1 8/2017 Lee et al.  
 2017/0279491 A1 9/2017 Lam

\* cited by examiner







FIG. 1A





103-3

103-4

FIG. 1B






FIG. 1C






FIG. 1D






FIG. 1E






FIG. 1F






FIG. 1G






FIG. 1H






FIG. 11






FIG. 1J






FIG. 1K






FIG. 11L






FIG. 2A






FIG. 2B






FIG. 3







FIG. 4



**FIG. 5**



**1****MULTIPLE WAVEGUIDE STRUCTURE  
WITH SINGLE FLANGE FOR AUTOMATIC  
TEST EQUIPMENT FOR SEMICONDUCTOR  
TESTING****CROSS-REFERENCE TO RELATED  
APPLICATIONS**

This application is related to patent application: "WAVE INTERFACE ASSEMBLY FOR AUTOMATIC TEST EQUIPMENT FOR SEMICONDUCTOR TESTING," concurrently filed with this application, Ser. No. 15/016,124, which is herein incorporated by reference in its entirety. This application is also related to patent application: "PLATING METHODS FOR MODULE AND/OR GANGED WAVEGUIDES FOR AUTOMATIC TEST EQUIPMENT FOR SEMICONDUCTOR TESTING," concurrently filed with this application, Ser. No. 15/016,143, which is herein incorporated by reference in its entirety.

**FIELD OF THE INVENTION**

Embodiments of the present disclosure generally relate to Automatic Test Equipment (ATE) for testing electronic components.

**BACKGROUND**

Automatic Test Equipment (ATE) is commonly used within the field of electronic chip manufacturing for the purposes of testing electronic components. ATE systems both reduce the amount of time spent on testing devices to ensure that the device functions as designed and serve as a diagnostic tool to determine the presence of faulty components within a given device before it reaches the consumer.

ATE systems can perform a number of test functions on a device under test (DUT) through the use of test signals transmitted to and from the DUT. Conventional ATE systems are very complex electronic systems and generally include printed circuit boards (PCB), coax cables and waveguides to extend the signal path of test signals transmitted from the DUT to a tester diagnostic system during a test session. However, increases to the length of the signal path, particularly at millimeter frequencies, can result in the loss of signal strength which can degrade the integrity of test signals transmitted from the DUT at high frequencies.

Conventional ATE systems use PCBs that include several centimeters of microstrip transmission lines disposed on the surface of a PCB to convey test signals from a DUT to a tester diagnostic system. Furthermore, when waveguides are used in conventional ATE systems requiring high frequency signaling, and conventional waveguide flanges are used to mate the waveguide and tester electronics to the DUT, the general dimensions of these flanges, which are often circular in shape, can be a limiting factor to the total signal path of test signals. Accordingly, the elongation of the test signal path caused by use of longer microstrip transmission lines as well as other components, such as coax cables and conventional waveguide flanges (including any adaptors required by these components) by modern ATE systems can result in unnecessary signal loss at high frequencies.

Furthermore, the large size of the waveguide flanges means that they cannot be closely mounted together with adjacent waveguides when multiple signal paths need to converge on an integrated circuit with tightly aligned signal paths.

**2****SUMMARY OF THE INVENTION**

Accordingly, a need exists for an apparatus and/or method that can address the problems with the approaches described above. Using the beneficial aspects of the apparatus and/or method described, without their respective limitations, embodiments of the present disclosure provide a novel solution to address these problems.

Embodiments of the present disclosure use customizable waveguides that can be positioned next to each other in a structure that contains one single flange to provide a physical connection for the waveguides. In this fashion, many waveguides can be positioned within a small area to accommodate a tightly packed patch antenna array so that the waveguides can be positioned very close to the socket. As such, embodiments of the present disclosure allow more waveguides to be packed into a small area by providing a single structure that houses many waveguides and share only a single flange connection element that can be sized appropriately.

More specifically, in one embodiment, the present invention is implemented as an integrated structure for signal transmission. The integrated structure includes a plurality of waveguides tightly disposed together and disposed substantially in parallel with each other, each of the waveguides having a first opening and a second opening.

In one embodiment, the plurality of waveguides are integrated within a single plastic structure. In one embodiment, the plurality of waveguides are separate waveguide structures held together via mounting mechanisms. In one embodiment, the plurality of waveguides are integrated within a single metal structure.

The integrated structure also includes a single flange connected to the plurality of waveguides at the first openings, the single flange operable for securing the plurality of waveguides to a printed circuit board (PCB) including a plurality of patch antennae, and where a pitch of the first openings is operable to align with a pitch of the patch antennae, where the single flange includes a plurality of mounting mechanisms for securing the single flange to the PCB.

In one embodiment, the plurality of waveguides are integrated within a single plastic structure and where inner portions of the plastic structure are metal plated. In one embodiment, the plurality of waveguides are curved in shape. In one embodiment, the single plastic structure is mounted to the PCB using a fastening agent.

In one embodiment, the present invention is implemented as an integrated structure for signal transmission. The integrated structure includes a plurality of waveguides tightly disposed together and disposed substantially in parallel with each other, each of the waveguides having a first opening and a second opening.

In one embodiment, the plurality of waveguides are integrated within a single plastic structure. In one embodiment, the plurality of waveguides are separate waveguide structures held together via mounting mechanisms. In one embodiment, the plurality of waveguides are integrated within a single metal structure.

The integrated structure also includes a common flange structure connected to the plurality of waveguides at the first openings, the common flange structure operable for securing the plurality of waveguides to a printed circuit board (PCB) including a plurality of patch antennae, and where a pitch of the first openings is operable to align with a pitch of the patch antennae, where the common flange structure includes



3

a plurality of mounting mechanisms for securing the common flange structure to the PCB.

In one embodiment, the plurality of waveguides are integrated within a single plastic structure and where inner portions of the plastic structure are metal plated. In one embodiment, the plurality of waveguides are customized for integration onto the common flange structure. In one embodiment, the single plastic structure is mounted to the PCB through a plurality of fastening agents.

In one embodiment, the present invention is implemented as an integrated structure for signal transmission. The integrated structure includes a plurality of customizable waveguides tightly disposed together and disposed substantially in parallel with each other, each of the customizable waveguides having a first opening and a second opening.

In one embodiment, the plurality of customizable waveguides are integrated within a single plastic structure. In one embodiment, the plurality of customizable waveguides are separate waveguide structures held together via mounting mechanisms. In one embodiment, the plurality of customizable waveguides are integrated within a single metal structure.

The integrated structure also includes a single flange connected to the plurality of waveguides at the first openings, the single flange operable for securing the plurality of customizable waveguides to a printed circuit board (PCB) including a plurality of patch antennae, and where a pitch of the first openings is operable to align with a pitch of the patch antennae, where the single flange includes a plurality of mounting mechanisms for securing the single flange to the PCB to facilitate substantial signal traversal therefrom. In one embodiment, the plurality of customizable waveguides are integrated within a single plastic structure and where inner portions of the plastic structure are metal plated. In one embodiment, the single plastic structure is mounted to the PCB through a fastening agent.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and form a part of this specification and in which like numerals depict like elements, illustrate embodiments of the present disclosure and, together with the description, serve to explain the principles of the disclosure.

FIG. 1A is a perspective view of an exemplary wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 1B is another perspective view of an exemplary wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 1C is yet another perspective view of an exemplary wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 1D is a plan view of an exemplary wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 1E depicts an exemplary waveguide used by a wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 1F is a block diagram depicting an exemplary patch antenna used by a wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 1G is a block diagram depicting a cross-section view of a waveguide used by a wave interface assembly in accordance with embodiments of the present disclosure.

4

FIG. 1H is a block diagram depicting an exemplary mounting of a waveguide on to a patch antenna used by a wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 1I is a cross-sectional view of a waveguide undergoing an exemplary plating process for modular and/or ganged waveguides used by a wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 1J is another cross-sectional view of a waveguide undergoing an exemplary plating process for modular and/or ganged waveguides used by a wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 1K is another cross-sectional view of a waveguide undergoing an exemplary plating process for modular and/or ganged waveguides used by a wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 1L is yet another cross-sectional view of a waveguide undergoing an exemplary plating process for modular and/or ganged waveguides used by a wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 2A depicts an exemplary signal path through an exemplary wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 2B depicts an exemplary signal path through an exemplary wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 3 depicts an exemplary waveguide component integration scheme using a wave interface assembly in accordance with embodiments of the present disclosure.

FIG. 4 is a flowchart of an exemplary assembly of a wave interface for testing a device in accordance with embodiments of the present disclosure.

FIG. 5 is a flowchart of an exemplary plating process for modular and/or ganged waveguides used by a wave interface assembly in accordance with embodiments of the present disclosure.

#### DETAILED DESCRIPTION

Reference will now be made in detail to the various embodiments of the present disclosure, examples of which are illustrated in the accompanying drawings. While described in conjunction with these embodiments, it will be understood that they are not intended to limit the disclosure to these embodiments. On the contrary, the disclosure is intended to cover alternatives, modifications and equivalents, which may be included within the spirit and scope of the disclosure as defined by the appended claims. Furthermore, in the following detailed description of the present disclosure, numerous specific details are set forth in order to provide a thorough understanding of the present disclosure. However, it will be understood that the present disclosure may be practiced without these specific details. In other instances, well-known methods, procedures, components, and circuits have not been described in detail so as not to unnecessarily obscure aspects of the present disclosure.

FIG. 1A is a perspective view of an exemplary wave interface assembly in accordance with embodiments of the present disclosure. Wave interface assembly 100 may be implemented within any testing system capable of testing multiple electronic components individually or in parallel. According to one embodiment, wave interface assembly 100 can be utilized in auto-radar detection applications, systems or similar implementations as well as in devices capable of



performing operations using frequencies generally ranging from 20 to 300 GHz (e.g., auto radar operations performed at approximately 78.5 GHz).

Wave interface assembly **100** includes device under test (DUT) interface **106**. As illustrated by the embodiment depicted in FIG. 1A, DUT interface **106** may include holes or apertures for purposes of using fastening agents (e.g., screws) to couple DUT interface **106** to a side of a printed circuit board (PCB), such as PCB **101**. DUT interface **106** includes socket **106-1**. In one embodiment, socket **106-1** may include recessed portions and/or grooves of sufficient dimensions to support the placement of a DUT (e.g., devices capable of generating and/or receiving radar signals, etc.) within DUT interface **106** during a testing session.

As illustrated in FIG. 1A, socket **106-1** may include a first opening adapted to support the insertion of a device (e.g., transceivers, etc.) within DUT interface **106**. Socket **106-1** may also include a second opening adapted to mount the device placed within DUT interface **106** on to a ball grid array, such as BGA **107**. BGA **107** can be packaged as a set of interconnection balls or pins positioned on a side of PCB **101** for coupling to a device. As such, BGA **107** can be used for coupling a tester diagnostic system to a set of test points on a DUT installed within socket **106-1**.

PCB **101** can include one or more microstrip transmission lines (not pictured) for conveying signals of varying frequencies across PCB **101**. PCB **101** can be adapted to include circuitry capable of propagating signals received from a DUT in a manner that requires shorter microstrip lengths. According to one embodiment, wave interface assembly **100** can include balun circuitry adapted to convert differential signals into a single ended output signal for receipt by a tester diagnostic system. According to one embodiment, wave interface assembly **100** can include differential DUT pads and/or single-ended patch antenna ports. As such, PCB **101** can include electrical components with low profiles that are capable of being mounted on a flat surface.

For instance, with further reference to the embodiment depicted in FIG. 1A, PCB **101** can include one or more patch antennas capable of propagating signals at varying gain levels. As such, a set of different patch antennas (e.g., patch antennas **102-1**, **102-2**, **102-3**, **102-4**) can be adapted to electrically couple to microstrip transmission lines formed on PCB **101** to convey test signals received from a DUT to a tester diagnostic system or a different location point. Furthermore, the patch antennas may be used to generate differential signals to amplify test signals transmitted from a DUT. Differential signals can then be converted into a single ended output signal using a transformer device.

According to one embodiment, patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4** can be coupled to balun circuitry installed beneath DUT interface **106**. For instance, in one embodiment, patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4** can include single-ended patch antenna ports coupled to differential DUT pads through differential transformers. In this fashion, patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4** can be configured to convert differential signals into a single ended output signal for receipt by a tester diagnostic system.

As described herein, the profile and/or pitch (e.g., a minimum separation) of patch antennas enables a greater number of them to be installed within wave interface assembly **100**. Moreover, their profiles and/or pitches also enable them to be arranged in various patterns and configurations within wave interface assembly **100** based on a pre-determined wave interface and/or waveguide system scheme. As

such, the ease in which patch antennas can be arranged within wave interface assembly **100** allows them to be installed in a manner that requires shorter microstrip lengths and/or places them closer to the DUT.

With further reference to the embodiment depicted in FIG. 1A, the general shape of patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4** allow them to be proximately placed relative to each other in a manner that creates high density port spacing at PCB **101**. Also, as illustrated by the embodiment depicted in FIG. 1A, patch antennas can be positioned in a series and/or parallel to each other. Furthermore, as illustrated by the embodiment depicted in FIG. 1A, patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4** can be placed along or in proximity to an edge surface of PCB **101**. Accordingly, the arrangement of patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4** within wave interface assembly **100** allows them to be installed in a manner that requires shorter microstrip lengths and/or places them closer to DUT interface **106**. Thus, this arrangement can minimize the potential degradation of signals received from a DUT installed within DUT interface **106**.

Furthermore, each patch antenna can be coupled to a respective waveguide associated with a waveguide system. As will be described infra, waveguides used by wave interface assembly **100** may include customizable waveguides that can vary in dimensions. As such, each waveguide installed within wave interface assembly **100** can be mounted on to a respective patch antenna installed within wave interface assembly **100**. In this fashion, waveguides installed within wave interface assembly **100** can be fabricated in a manner that allows them to be tightly fitted to patch antennas installed within wave interface assembly **100**, thereby creating a tighter pitch between waveguides and the device under test.

Moreover, waveguides installed within wave interface assembly **100** can be positioned next to each into a single structure in a manner that allows a single flange to become a physical connection element to multiple waveguides. The single structure allows multiple waveguides to be positioned within a small area to accommodate a high density, tightly packed array of patch antennas, thereby allowing the waveguides to be positioned very close to DUT interface **106**.

For example, with reference to the embodiments depicted in FIGS. 1B, 1C and 1D, wave interface assembly **100** can include a covering structure (e.g., covering structure **105-1**, covering structure **105-2**) containing a set of different waveguides, such as waveguides **103-1**, **103-2**, **103-3**, and/or **103-4**. As illustrated in FIGS. 1B, 1C and 1D, waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** may be a set of parallel waveguides integrated within wave interface assembly **100** in a manner that allows flange **111** to become a physical connection element to multiple waveguides. In this fashion, flange **111** includes different waveguides that can each be used as separate, independent transmit channels that are each capable of providing separate tester resources to a DUT during a testing session. According to one embodiment, these channels can be used to transmit test signals between a DUT installed within socket **106-1** and a tester diagnostic system.

As depicted in FIGS. 1B, 1C and 1D, waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** can each be integrated within wave interface assembly **100** in a manner that allows them to be physically coupled to patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4** installed within wave interface assembly **100** sharing a common flange **111**. As such, waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** can be fabricated in a manner that allows them to propagate signals transmitted



from a DUT installed within DUT interface **106** to a tester diagnostic system or a different system. In this fashion, waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** can each be installed within wave interface assembly **100** can be sufficiently mounted on patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4**, respectively. Furthermore, as illustrated by the embodiments depicted in FIGS. **1B**, **1C** and **1D**, waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** can be placed along or in proximity to an edge surface of PCB **101**. In this fashion, waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** can be a tightly coupled waveguide assembly using a common flange **111** that eliminates the disadvantages normally attributed to conventional, individual waveguide flanges. In one embodiment the pitch between waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** and DUT interface **106** may be uniform. In one embodiment the pitch between waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** may be uniform.

As described herein, waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** can be adapted to conform to the profile and/or pitch of patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4**. For instance, waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** used by wave interface assembly **100** can include port openings that are adapted to allow waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** to be mounted on to the profiles of patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4**, respectively.

In this manner, integrated waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** can each be fabricated to conform to the dimensions and/or pitch of patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4**. Thus, the coupling of waveguides to patch antennas in this manner produces a plurality of miniaturized waveguide flanges that can be customizable based on the dimensions of a desirable ATE system or scheme. Accordingly, the increased number of patch antenna elements can correspondingly increase the number of waveguides that can be used by ATE when testing a device and allow high density waveguide placement.

Furthermore, the ability to install waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** in the manner depicted by the embodiments illustrated in FIGS. **1B**, **1C** and **1D** enables them to be placed in a position in close proximity to DUT interface **106** and/or socket **106-1** such that the length of microstrip transmission lines formed on PCB **101** are minimized or shortened. For instance, the length and/or width dimensions of microstrip transmission lines formed or disposed on PCB **101** can be shortened due to the tight pitch between waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** and DUT interface **106** and/or socket **106-1**. Thus, the positioning of waveguides **103-1**, **103-2**, **103-3**, and/or **103-4** in the manner depicted in FIGS. **1B**, **1C** and **1D** can minimize total signal path loss as well as signal degradation.

Furthermore, in one embodiment, waveguides **103-1**, **103-2**, **103-3**, **103-4** may be adapted or configured to be coupled to a different set of wave guides. In this fashion, a plurality of different wave guides comprising of different materials, such as metal, plastic, etc., can be coupled to each other thereby extending a particular system of waveguides used for a testing session. Also, although the sides of waveguides depicted in FIGS. **1A**, **1B**, **1C** and **1D** appear to have uniform dimensions, embodiments of the present disclosure are not limited as such. For instance, with reference to the embodiment depicted in FIG. **1E**, waveguide **103-6** may be fabricated in a manner such that the side dimensions of the waveguide are configured to expand or “fan out” in a direction that is away from the location of the high density, tightly packed array of patch antennas (see, e.g., location **109** in FIG. **1E** which depicts the location of patch antennas **102-1**, **102-2**, **102-3**, and/or **102-4**). According to one

embodiment, the one end of a waveguide can be fabricated to be of a dimension that is different from an opposite end. For instance, the end of waveguide **103-1** that is mounted to patch antenna **102-1** can be fabricated to be of different dimensions (e.g., narrower) than the opposite end of waveguide **103-1** (e.g., broader).

With further reference to the embodiments depicted in FIGS. **1A**, **1B**, **1C** and **1D**, structures used by wave interface assembly **100** to house waveguide systems, such as covering structures **105-1** and/or **105-2**, may be fabricated to include a single exterior layer or multiple layers. According to one embodiment, the exterior layers of covering structures **105-1** and/or **105-2** may comprise material (e.g., plastic, metal, or similar materials, etc.) suitable for propagating signals through waveguide systems described herein. In some embodiments, the inner portions of covering structures **105-1** and/or **105-2** may include materials such as plastic and/or metal. The covering structures **105-1** and/or **105-2** may include holes or apertures for purposes of using fastening agents (e.g., screws) to couple to one side of a PCB. Covering structures **105-1** and/or **105-2** may also include alignment pins which can be used to mate to a set of waveguides located on an opposite side of the PCB.

FIG. **1F** is a block diagram depicting an exemplary patch antenna used by a wave interface assembly in accordance with embodiments of the present disclosure. Patch antennas may be used to providing a mating interface to multiple waveguides used by a wave interface assembly in accordance with embodiments of the present disclosure. As such, the size of a patch antenna can be customized to act as a physical connection point for multiple waveguides.

For instance, patch antenna **102** may have a low profile and characteristics that enable patch antenna **102** to be mounted on a flat surface, such as PCB **101**. For instance, as depicted in FIG. **1F**, patch antenna **102** may include a conductive microstrip transmission line, such as microstrip transmission line **102a**, which may be disposed on a top surface of PCB **101**. Microstrip transmission lines can include at least one thin conducting strip (“trace”) capable of being separated from a ground plane conductor by a dielectric layer or substrate.

Microstrip transmission lines can be fabricated using conventional etching techniques that include photolithography or other forms of printed circuit board fabrication technology. As such, microstrip transmission lines can be fabricated with varying degrees of height, width, and/or dielectric constant values. Additionally, patch antenna **102** can include a conductive radiator patch **102b** having dimensions length **L1** and width **W1** and may be rectangular in shape. In this fashion, embodiments of the present disclosure may use the profile, pitch and/or conductive properties of patch antenna **102** to extend the bandwidth of test signals transmitted from a DUT to another point or location, such as a tester diagnostic system.

FIG. **1G** depicts a cross-section view of one end of an exemplary waveguide structure in accordance with embodiments of the present disclosure. The embodiment depicted in FIG. **1G** depicts an exemplary mating interface of a waveguide that can be used by a wave interface assembly in accordance with embodiments of the present disclosure. In one embodiment, waveguide **103** may be a WR12 waveguide or a suitable waveguide for the band required. Waveguide **103** may be customized in a manner that allows wave interface assembly **100** to utilize shorter microstrip transmission lines to propagate test signals transmitted from a DUT to a termination point, such as a tester diagnostic system. According to one embodiment, waveguide **103**, or



portions thereof (e.g., mating interface frame) can be fabricated using 3 dimensional (3D) printing technologies.

For instance, waveguide cross-section **103** may be fabricated to include generally flat interface portions, e.g., mating interface frame **103b**, which may be located on the ends of waveguide **103**. As depicted in FIG. 1G, mating interface frame **103b** can be fabricated to have dimensions length **L2** and width **W2** and may be rectangular in shape. Portions of mating interface frame **103b** may include port openings, e.g., port opening **103a**, that can be fabricated to have dimensions length **L1** and width **W1** and may be rectangular in shape. Port opening **103a** may be an entry or exiting point of waveguide **103** for signals traversing through waveguide **103**. As such, in one embodiment, when mating interface frame **103b** of waveguide **103** is placed in a flushed position against a similar mating interface frame of a different waveguide, each waveguide's respective port opening may be aligned in manner that allows for the traversal of signals between the two waveguides.

In this fashion, a port opening, such as port opening **103a**, can be coupled to other electrical components, such as patch antenna **102**, to extend the signal path of signals transmitted from a DUT and through a waveguide system. According to one embodiment, waveguide **103** may comprise metal, plastic or similar materials capable of minimizing signal degradation. According to one embodiment, waveguide **103** may include plated portions which are adapted to prevent signal degradation.

FIG. 1H is a block diagram depicting an exemplary mounting of a waveguide cross-section on to a patch antenna used by a wave interface assembly in accordance with embodiments of the present disclosure. As depicted in FIG. 1H, the dimensions of portions of a waveguide mating interface (e.g., port opening **103a** and/or radiator patch **102b**) can be fabricated or adapted in a manner that allows waveguide **103** to be sufficiently mounted on to patch antenna **102**. According to one embodiment, the dimensions (e.g., **L1** and/or **W1**) of port opening **103a** (depicted as beneath radiator patch **102b**) may be similar to that of radiator patch **102b** such that when aligning the two objects together and placing them in a flushed position against each other, the potential for signal loss between patch antenna **102** and waveguide **103** can be minimized.

According to one embodiment, and with further reference to the embodiments depicted in FIGS. 1G and 1H, the dimensions (e.g., **L2** and/or **W2**) of mating interface frame **103b** may be equivalent or slightly larger than the dimensions of radiator patch **102b** and/or port opening **103a** such that the potential for signal loss between patch antenna **102** and waveguide **103** can be minimized when patch antenna **102** and waveguide **103** are coupled to each other. As such, the dimensions of mating interface frame **103b** may be such that it allows waveguide **103** to be installed within wave interface assembly **100** in a manner that requires shorter microstrip lengths and/or places waveguides in positions that are closer to the location of DUT during a testing session.

Embodiments of the present disclosure also include waveguide surface reinforcement procedures and/or plating procedures for modular and/or ganged waveguides used by a wave interface assembly. Embodiments of the present disclosure include waveguides that can be divided in a manner such that the inner portions and/or outer portions of the waveguide can be plated. Plating procedures may include applying a layer of material (e.g., silver, copper, etc.) to the inner portions and/or outer portions of the waveguide. FIGS. 1I, 1J, 1K and 1L depict cross-sectional views of plated

waveguides produced through a plating process for modular and/or ganged waveguides used by a wave interface assembly in accordance with embodiments of the present disclosure. Although FIGS. 1I, 1J, 1K and 1L depict waveguides having a generally curved body, embodiments of the present disclosure are not limited to such configurations.

With reference to the embodiments depicted in FIGS. 1I, 1J, 1K and/or 1L, an incision (e.g., incision **103g**) can be made on a waveguide (e.g., waveguide **103-1**) along its longitudinal axis such that the waveguide is divided into two portions (e.g., waveguide portions **104a** and **104b**). For example, with reference to the embodiments depicted in FIGS. 1I and 1J, waveguide portions **104a** and **104b** may share equal dimensions or may have different dimensions. By dividing the waveguide in this manner, a trench structure is formed in both waveguide portions **104a** and **104b** (see, e.g., trench **103c** in FIG. 1K) having a respective width (e.g., width **W3**) that extends from the location of the incision (e.g., location of incision **103g**) to an inner wall (e.g., inner wall **103f**) of a waveguide portion (e.g., waveguide portion **104a**, waveguide portion **104b**).

In this fashion, both the outer surfaces of waveguide portions **104a** and/or **104b**, as well as their respective inner portions, can be exposed for plating procedures. For instance with reference to the embodiment depicted in FIG. 1L, portions of an inner surface (e.g., trench **103c**, inner wall **103f**, top portion **103j**, etc.) within waveguide portions **104a** and/or **104b** can be exposed for plating procedures.

In one embodiment, plating procedures may include applying a single layer of material capable of minimizing signal degradation (e.g., silver, copper, etc.) to the inner portions and/or outer portions of the waveguide. In one embodiment, plating procedures may include applying multiple layers of material capable of minimizing signal degradation to the inner portions and/or outer portions of the waveguide. The layers may be of the same material or may be different. In one embodiment, the same layer of material may be applied to trench structures, inner walls and/or top portions within the inner surfaces of waveguide portion **104a** and/or waveguide portion **104b**. In one embodiment, separate layers of material may be applied individually to trench structures, inner walls and/or top portions within the inner surfaces of waveguide portion **104a** and/or waveguide portion **104b**.

Thus, the respective inner surfaces of a waveguide can be reinforced or plated to a higher degree than conventional methods of plating waveguides. Upon completion of plating procedures, the separate parts of the waveguide may then be secured back together (e.g., mechanically or through automation) to restore the original waveguide structure. In one embodiment, fastening agents (e.g., screws) can be used to secure waveguide portions **104a** and **104b** together to a sufficient degree so that signal traversal through the waveguide can occur more efficiently. In this fashion, multiple portions can be cut and then subsequently secured back together for use as "building blocks" to create modular solutions that yield a number of different customizable waveguide structures.

According to one embodiment, waveguide portions can be fabricated to include mounting elements to mount a waveguide portion to a PCB and/or patch antenna. In one embodiment, incisions can be made near the ends of a waveguide along its longitudinal axis such that waveguide covers can be produced. Furthermore, waveguide incision procedures can be performed mechanically or through automation. For instance, in one embodiment, computer-imple-



mented procedures can be performed to create incisions while the waveguides are fabricated using 3D printer technology.

By performing incisions along the longitudinal axis, the waveguide can be divided along the direction of its electro-magnetic field. Thus, plating waveguides in the manner described herein does not significantly reduce waveguide functionality and/or facilitate signal degradation. In this fashion, embodiments of the present disclosure allow for less expensive and more customizable waveguide plating procedures.

FIGS. 2A and 2B depict exemplary signal paths through an exemplary wave interface assembly in accordance with embodiments of the present disclosure. With reference to the embodiment depicted in FIG. 2A, during a testing session using wave interface assembly 100, a device under test (e.g., DUT 107) may be loaded within a socket (e.g., socket 106-1) of a DUT interface that includes a BGA layer, such as BGA layer 106-2. As depicted in FIG. 2A, in some embodiments, wave interface assembly 100 may include a contactor layer, such as contactor layer 106-3.

Thus, when DUT 107 is loaded within socket 106-1 during the testing session, the DUT 107 can make contact with BGA layer 106-2 thereby generating test signals 106-4. A microstrip transmission line, such as microstrip transmission line 101-1, may be longitudinally formed along a top surface of PCB 101. As depicted in FIG. 2A, a patch antenna, such as patch antenna 102-1, can serve as a location where a waveguide (e.g., waveguide 103-1) is mounted onto a patch antenna (e.g., patch antenna 102-1) positioned flushed against the top surface of PCB 101 and electrically coupled to microstrip transmission line 101-1.

In this fashion, a mating interface (e.g., mating interface frame 103b of FIG. 1G and/or FIG. 1H) located at one end of wave guide 103-1 can be mounted on to a top surface of PCB 101 at a location that is perpendicular to the location of patch antenna 102-1. As depicted by the embodiment in FIG. 2A, patch antenna 102-1 can direct the propagation of test signals 106-4 received into and through an opening located at one end of waveguide 103-1. As such, patch antenna 102-1 can be configured to match impedance levels between waveguide 103-1 and microstrip transmission line 101-1 during the transmission of test signals 106-4 through wave interface assembly 100.

With reference to the embodiment depicted in FIG. 2B, wave interface assembly 100 may include waveguides placed on opposite sides of a socket 106-1 within DUT interface 106 (e.g., waveguide 103-1 and waveguide 103-5). As such, one end of wave guide 103-5 can be mounted on to a top surface of PCB 101 at a location that is perpendicular to the location of a separate patch antenna, such as patch antenna 102-5. Accordingly, patch antenna 102-5 can direct the propagation of test signals 106-5 received into and through an opening located at one end of waveguide 103-5 for further processing. In this fashion, wave interface assembly 100 includes the functionality to use different waveguide systems to transmit different sets of signals for processing.

Furthermore, as illustrated by the embodiments depicted in FIGS. 2A and 2B, wave interface assembly 100 can reduce wave signal path loss through use of waveguides while minimizing micro strip dimensions (e.g., height, width, dielectric constant values). According to one embodiment, an opposite end of a waveguide, such as waveguides 103-1 and 103-5, can be coupled to a tester diagnostic system. According to one embodiment, an opposite end of a waveguide can be coupled to a docking and/or blind mate system. Furthermore, as depicted in FIG. 2B, wave interface

assembly 100 may include a cover, such as covering structure 105-1, which can encapsulate integrated waveguides, such as waveguide 103-5.

FIG. 3 depicts an exemplary cross-section of waveguide component integration using a wave interface assembly in accordance with embodiments of the present disclosure. Integrated wave interface assembly 200 may include the same or similar objects and/or components described with respect to other wave interface assemblies described herein (e.g., wave interface assembly 100) in accordance with embodiments of the present disclosure. Integrated wave interface assembly 200 may include electrical components such as power splitters, directional couplers, terminations, eccosorb wedge and/or similar components. As illustrated in FIG. 3, a signal (e.g., test signals 106-2) may enter through a waveguide, (e.g., waveguide 103-1) installed within wave interface assembly 200. As the signal travels through waveguide 103-1, it may enter a power splitter (e.g., magic tee element 110) which can be used to divide the signal into 2 portions in which each portion of the signal can travel through separate, customizable waveguides, such as waveguides 103-6 and 103-7.

Furthermore, as illustrated in FIG. 3, portions of the signal traveling through waveguides 103-6 and 103-7 can be further divided using additional power splitters (e.g., magic tee elements 113 and 114), thereby dividing the signal into additional portions (e.g., 4 portions). These portions of the signal may also traverse additional separate, customizable waveguides, such as waveguides 103-8, 103-9, 103-10 and 103-11. Moreover, as depicted in FIG. 3, waveguides (e.g., waveguides 103-8, 103-9, 103-10, 103-11) can include port openings at one end (e.g., port openings 115, 116, 117, 118). Thus, port openings 115, 116, 117, and 118 may be positioned in tighter pitch configurations which can correspondingly allow for higher density port spacing at the PCB level.

According to one embodiment, port openings 115, 116, 117, and/or 118 can be configured as phase matched ports to a PCB (e.g., PCB 101). According to one embodiment, port openings 115, 116, 117, and/or 118 can be configured as phase matched ports to a base plate. In this fashion, port openings 115, 116, 117, and/or 118 may be adapted to include additional mounting holes.

As such, these port openings allow waveguides 103-8, 103-9, 103-10 and/or 103-11 to be used as separate, independent transmit channels that are each capable of providing separate tester resources to a DUT during a testing session. According to one embodiment, these channels can be used to propagate and/or amplify test signals (e.g., test signals 106-2) transmitted between a DUT installed within socket 106-1 and a tester diagnostic system (not pictured).

According to one embodiment, magic tee elements 110, 113 and/or 114 may include terminated ports. In one embodiment, terminated ports can be terminated through the use of termination wedges. Furthermore, according to one embodiment, wave interface assembly 200 can be enclosed or encased within a structure comprising material (e.g., plastic, metal, etc.) suitable for propagating signals through waveguide systems described herein.

FIG. 4 is a flowchart of an exemplary assembly of a wave interface for testing a device in accordance with embodiments of the present disclosure. The disclosure, however, is not limited to the description provided by flowchart 300. Rather, it will be apparent to persons skilled in the relevant art(s) from the teachings provided herein that other functional flows are within the scope and spirit of the present disclosure. Flowchart 300 will be described with continued



reference to exemplary embodiments described above, though the method is not limited to those embodiments.

At step **301**, a plurality of patch antennas are electrically coupled to a socket of a DUT interface to store a device for testing. Each patch antenna is proximately positioned relative to each other and the socket.

At step **302**, a plurality of waveguides are mounted on to a respective patch antenna from the plurality of patch antennas. Each waveguide is adapted to allow signal traversal from the device under test to a tester diagnostic system.

At step **303**, test signals are generated for the device under test by a tester diagnostic system. The test signals can traverse a signal path that includes the socket, at least one patch antenna of the plurality of patch antennas, and at least one waveguide of the plurality of waveguides.

At step **304**, upon traversal of the signal path, the test signals are received by a tester diagnostic system, where they can be further processed.

FIG. **5** is a flowchart of an exemplary method of plating a waveguide structure in accordance with embodiments of the present disclosure. The disclosure, however, is not limited to the description provided by flowchart **400**. Rather, it will be apparent to persons skilled in the relevant art(s) from the teachings provided herein that other functional flows are within the scope and spirit of the present disclosure. Flowchart **400** will be described with continued reference to exemplary embodiments described above, though the method is not limited to those embodiments.

At step **401**, an incision is made along an outer portion of a waveguide. The incision can be made down the middle of a waveguide along its longitudinal axis thereby dividing the waveguide into two portions and exposing both the outer and inner surfaces of each portion of the divided waveguide. The incision created during step **401** forms a respective trench in each divided portion of the waveguide. Each trench includes a width that extends from a location of the incision to an inner wall a waveguide portion.

At step **402**, the inner surfaces of each portion of the divided waveguide are plated. Plating procedures include applying a layer of material on top of the trenches, the inner wall, and a top portion within the waveguide. The applied material is capable of minimizing signal degradation to the inner portions of the waveguide.

At step **403**, the divided portions of the waveguide are secured together to restore the waveguide to its original structure prior to the incision procedure performed during step **401**.

While the foregoing disclosure sets forth various embodiments using specific block diagrams, flowcharts, and examples, each block diagram component, flowchart step, operation, and/or component described and/or illustrated herein may be implemented, individually and/or collectively, using a wide range of hardware configurations. In addition, any disclosure of components contained within other components should be considered as examples because many other architectures can be implemented to achieve the same functionality.

The process parameters and sequence of steps described and/or illustrated herein are given by way of example only. For example, while the steps illustrated and/or described herein may be shown or discussed in a particular order, these steps do not necessarily need to be performed in the order illustrated or discussed. The various example methods described and/or illustrated herein may also omit one or more of the steps described or illustrated herein or include additional steps in addition to those disclosed.

It should also be understood, of course, that the foregoing relates to exemplary embodiments of the invention and that modifications may be made without departing from the spirit and scope of the invention as set forth in the following claims.

The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as may be suited to the particular use contemplated.

Embodiments according to the invention are thus described. While the present disclosure has been described in particular embodiments, it should be appreciated that the invention should not be construed as limited by such embodiments, but rather construed according to the below claims.

What is claimed is:

**1.** An integrated structure for signal transmission, said integrated structure comprising:

a plurality of waveguides disposed together and disposed substantially in parallel with each other, each of said waveguides having a first opening and a second opening;

a covering structure; and

a single flange connected to said plurality of waveguides at said first openings, said single flange operable for securing said plurality of waveguides to a printed circuit board (PCB) comprising a plurality of patch antennae, and wherein a pitch of said first openings is operable to align with a pitch of said patch antennae, wherein said covering structure comprises said single flange at one end thereof, wherein said single flange comprises a plurality of mounting mechanisms for securing said single flange to said PCB, and wherein said plurality of waveguides is entirely disposed within the covering structure.

**2.** An integrated structure as claimed in claim **1** wherein said plurality of waveguides are integrated within a single plastic structure.

**3.** An integrated structure as claimed in claim **2** wherein said single plastic structure is mounted to said PCB using a fastening agent.

**4.** An integrated structure as claimed in claim **1** wherein said plurality of waveguides are separate waveguide structures held together via mounting mechanisms.

**5.** An integrated structure as claimed in claim **1** wherein said plurality of waveguides are integrated within a single metal structure.

**6.** An integrated structure as claimed in claim **1** wherein said plurality of waveguides are integrated within a single plastic structure and wherein inner portions of said plastic structure are metal plated.

**7.** An integrated structure as claimed in claim **1** wherein said plurality of waveguides are curved in shape.

**8.** An integrated structure for signal transmission, said integrated structure comprising:

a plurality of waveguides disposed together and disposed substantially in parallel with each other, each of said waveguides having a first opening and a second opening;

a covering structure; and



**15**

a common flange structure connected to said plurality of waveguides at said first openings, said common flange structure operable for securing said plurality of waveguides to a printed circuit board (PCB) comprising a plurality of patch antennae, and wherein a pitch of said first openings is operable to align with a pitch of said patch antennae,

wherein said covering structure comprises said common flange structure at one end thereof, wherein said common flange structure comprises a plurality of mounting mechanisms for securing said common flange structure to said PCB, and wherein said plurality of waveguides is entirely disposed within the covering structure.

**9.** An integrated structure as claimed in claim **8** wherein said plurality of waveguides are integrated within a single plastic structure.

**10.** An integrated structure as claimed in claim **9** wherein said single plastic structure is mounted to said PCB through a plurality of fastening agents.

**11.** An integrated structure as claimed in claim **8** wherein said plurality of waveguides are separate waveguide structures held together via mounting mechanisms.

**12.** An integrated structure as claimed in claim **8** wherein said plurality of waveguides are integrated within a single metal structure.

**13.** An integrated structure as claimed in claim **8** wherein said plurality of waveguides are integrated within a single plastic structure and wherein inner portions of said plastic structure are metal plated.

**14.** An integrated structure as claimed in claim **8** wherein said plurality of waveguides are customized for integration onto said common flange structure.

**15.** An integrated structure for signal transmission, said integrated structure comprising:

a plurality of customizable waveguides disposed together and disposed substantially in parallel with each other,

**16**

each of said customizable waveguides having a first opening and a second opening;

a covering structure; and

a single flange connected to said plurality of customizable waveguides at said first openings, said single flange operable for mounting said plurality of customizable waveguides to a printed circuit board (PCB) comprising a plurality of patch antennae, and wherein a pitch of said first openings is operable to align with a pitch of said patch antennae,

wherein said covering structure comprises said single flange at one end thereof, wherein said single flange comprises a plurality of mounting mechanisms for securing said single flange to said PCB to facilitate substantial signal traversal therefrom, and wherein said plurality of customizable waveguides is entirely disposed within the covering structure.

**16.** An integrated structure as claimed in claim **15** wherein said plurality of customizable waveguides are integrated within a single plastic structure.

**17.** An integrated structure as claimed in claim **16** wherein said single plastic structure is mounted to said PCB through a fastening agent.

**18.** An integrated structure as claimed in claim **15** wherein said plurality of customizable waveguides are separate waveguide structures held together via mounting mechanisms.

**19.** An integrated structure as claimed in claim **15** wherein said plurality of customizable waveguides are integrated within a single metal structure.

**20.** An integrated structure as claimed in claim **15** wherein said plurality of customizable waveguides are integrated within a single plastic structure and wherein inner portions of said plastic structure are metal plated.

\* \* \* \* \*