

(12) **United States Patent**
Lin

(10) **Patent No.: US 10,385,527 B2**
(45) **Date of Patent: Aug. 20, 2019**

(54) **METHOD FOR ELECTRIC POWER
CONSTRUCTION WARNING AND DEVICE
THEREOF**

(71) Applicant: **SINADENG
CLOTHING(HONGKONG)
LIMITED**, Hongkong (CN)

(72) Inventor: **Zebiao Lin**, Hongkong (CN)

(73) Assignee: **Shenzhen Oukeli Technology Co.,
Ltd.**, Shenzhen, Guangdong (CN)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 353 days.

(21) Appl. No.: **15/442,712**

(22) Filed: **Feb. 27, 2017**

(65) **Prior Publication Data**
US 2017/0167092 A1 Jun. 15, 2017

(51) **Int. Cl.**
E01F 13/02 (2006.01)
E01F 9/00 (2016.01)
(Continued)

(52) **U.S. Cl.**
CPC **E01F 13/022** (2013.01); **B60T 1/005**
(2013.01); **B60T 7/04** (2013.01); **E01F 9/692**
(2016.02);
(Continued)

(58) **Field of Classification Search**
CPC B60T 1/005; B60T 7/04; B62B 5/0433;
E01F 9/688; E01F 9/692; E01F 13/00;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,349,937 A * 9/1982 Fontana B60B 33/0078
16/35 R
5,407,178 A * 4/1995 Long E01F 13/028
160/354

(Continued)

FOREIGN PATENT DOCUMENTS

CN 03204955.2 1/2005
CN 200920138114.7 5/2010

(Continued)

OTHER PUBLICATIONS


“RollerPro 250—Portable Stanchion.” Discount Directionals. Feb.
28, 2015, [online], [retrieved on Feb. 27, 2019]. Retrieved from the
Internet <URL: <https://web.archive.org/web/20150228125639/https://www.discountdirectionals.com/product/rollerpro-250-portable-stanchion/>>.*

Primary Examiner — Josh Skroupa

(57) **ABSTRACT**

A device for electric power construction warning includes:
a guardrail body, a caution light and a second hook, wherein
a mobile firmware is provided under the guardrail body; the
caution light is provided on a top of the guardrail body, and
is covered by a shell; a solar power unit is provided on a top
of the shell, and is connected to the caution light; a pair of
handles are symmetrically provided on external faces at a
top portion of the guardrail body; a first ring is provided on
an external face at a bottom portion of the guardrail body;
two roller supports are separately provided on a left side of
the guardrail body, and a roller is provided on each of the
roller supports; a second ring is provided on a right side of
the firmware to cooperate with the second hook on a left side
of the firmware.

10 Claims, 1 Drawing Sheet




(51)	Int. Cl.								
	<i>B60T 1/00</i>	(2006.01)		6,969,050	B1 *	11/2005	Loebner	E01F 13/028
	<i>B60T 7/04</i>	(2006.01)							256/1
	<i>G08B 21/02</i>	(2006.01)		7,217,061	B2 *	5/2007	Stratton	E01F 13/028
	<i>E01F 9/692</i>	(2016.01)							256/1
	<i>G08B 5/36</i>	(2006.01)		7,538,688	B1 *	5/2009	Stewart	E01F 13/028
									116/63 C
(52)	U.S. Cl.			9,243,425	B2 *	1/2016	Scullion	E01F 13/022
	CPC	<i>E01F 13/028</i> (2013.01); <i>G08B 21/02</i>	9,650,060	B2 *	5/2017	Kopp	B62B 5/067
			(2013.01); <i>G08B 5/36</i> (2013.01)	9,947,250	B2 *	4/2018	Yang	E01F 13/028
(58)	Field of Classification Search			2008/0251656	A1 *	10/2008	Prismall	E01F 13/02
	CPC	E01F 13/02; E01F 13/022; E01F 13/028;						248/121
			E01F 13/04; G08B 5/36; G08B 21/02	2016/0215462	A1 *	7/2016	Marchetti	E01F 13/028
	USPC	256/1, 13.1; 49/34	2016/0221595	A1 *	8/2016	Hane	B62B 5/0433
	See application file for complete search history.								

(56) **References Cited**

U.S. PATENT DOCUMENTS									
6,375,164	B1 *	4/2002	Siegler	E01F 13/028	CN	201020201565.3	12/2010	
					256/1	CN	201320791498.9	7/2014	
6,485,225	B1 *	11/2002	Baker	E01F 13/028	CN	201520100514.4	9/2015	
					49/34	JP	2008274754 A	* 11/2008 E01F 13/028
						WO	WO-9713049 A1	* 4/1997 E01F 13/028

* cited by examiner

FOREIGN PATENT DOCUMENTS



1

METHOD FOR ELECTRIC POWER CONSTRUCTION WARNING AND DEVICE THEREOF

BACKGROUND OF THE PRESENT INVENTION

Field of Invention

The present invention relates to a field of electric power, and more particularly to a method for electric power construction warning and a device thereof

Description of Related Arts

With the development of society, electricity also experienced rapid development. People's demands for as well as dependence on electricity are increasing, and people want to have qualified and uninterrupted power supply services. Therefore, power repair and maintenance have been increasingly important. In the construction of electric power repair, only construction workers with full power safety knowledge know how to prevent electric shock. Unfortunately, during construction, many passers-by will unconsciously get close to the charged equipment under the impact of curiosity, bringing security risks. Therefore, the construction should be accompanied with safety warning or guardrail, in order to keep the passers-by away. Conventional guardrails are large, and are difficult to transport with a huge number.

SUMMARY OF THE PRESENT INVENTION

An object of the present invention is to provide a method for electric power construction warning and a device thereof, with a simple structure and convenient construction.

Accordingly, in order to accomplish the above object, the present invention provides a method for electric power construction warning and a device thereof, comprising: a guardrail body, a caution light and a second hook, wherein a mobile firmware is provided under the guardrail body; the caution light is provided on a top of the guardrail body, and is covered by a shell; a solar power unit is provided on a top of the shell, and is connected to the caution light; a pair of handles are symmetrically provided on external faces at a top portion of the guardrail body; a first ring is provided on an external face at a bottom portion of the guardrail body; two roller supports are separately provided on a left side of the guardrail body, and a roller is provided on each of the roller supports; a warning strip is wound on the roller, and one end of the warning strip is connected to a first hook through a connecting belt; a second ring is provided on a right side of the firmware; the second hook is vertically arranged with an opening thereof facing downwards, and the second ring is horizontally arranged.

Preferably, the second ring cooperates with the second hook for connection.

Preferably, the caution light comprises a switch.

The method for the electric power construction warning comprises steps of: providing a mobile firmware under a base of each of guardrail bodies; connecting a second ring of the mobile firmware to a second hook of an adjacent mobile firmware, in such a manner that the guardrail bodies are integrated and move as a whole; providing universal wheels under the mobile firmware for moving the guardrail bodies, and providing a foot break on each of the universal wheels for fixing the guardrail bodies; and isolating a construction site by pulling out two warning strips respectively wound on two separate rollers at a left side of each of the guardrail bodies and connecting the warning strips to an adjacent guardrail body.

2

Compared with conventional technologies, the present invention has a simple structure and is easy to use. The second hook and the second ring on the firmware are tough and connected, in such a manner that the guardrail bodies are integrated. The second hook is vertically arranged with an opening thereof facing downwards, and the second ring is horizontally arranged. As a result, for connecting or disconnecting the guardrail bodies, only the side where the second hook is placed needs to be slightly lifted, and then the second hook is directly connected to or disconnected from the second ring. The universal wheels are provided under the mobile firmware for moving the guardrail bodies as a whole, which solves technical problems such as rapid disconnection or connection, and convenient transportation.

Compared with conventional technologies, the warning strips may be connected to the adjacent guardrail body by workers in advance, then the guardrail bodies are arranged along a desired route, so as to reduce labor for repeatedly pulling the warning to strips and repeatedly moving the guardrail bodies, which improve working efficiency.

The caution light is provided for enhancing a caution effect.

These and other objectives, features, and advantages of the present invention will become apparent from the following detailed description, the accompanying drawings, and the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a sketch view of a method for electric power construction warning and a device thereof.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to the drawing, the present invention is further illustrated.

Referring to FIG. 1, a method for electric power construction warning and a device thereof comprise: a guardrail body 2, a caution light 7 and a second hook 3, wherein a mobile firmware 1 is provided under the guardrail body 2; the caution light 7 is provided on a top of the guardrail body 2, and is covered by a shell 8; a solar power unit 9 is provided on a top of the shell 8, and is connected to the caution light 7; a pair of handles 6 are symmetrically provided on external faces at a top portion of the guardrail body 2 for lifting the guardrail bodies 2 by worker hands, in such a manner that the device is able to be easily installed or transported; a first ring 13 is provided on an external face at a bottom portion of the guardrail body 2; two roller supports 16 are separately provided on a left side of the guardrail body 2, and a roller 15 is provided on each of the roller supports 16; a warning strip 12 is wound on the roller 15, and one end of the warning strip 12 is connected to a first hook 10 through a connecting belt 11; during working, two guardrail bodies 2 are placed with an interval; the upper first hook 10 of the right guardrail body 2 is connected to one of the handles 6 of the left guardrail body 2, and the lower first hook 10 of the right guardrail body 2 is connected to the first ring 13 of the left guardrail body 2; the warning strips 12 are used as a guardrail, and the caution light 7 is turned on for warning; the second hook 3 is provided on a left side of the firmware 1 and a second ring 5 is provided on a right side of the firmware 1; the second hook 3 is vertically arranged with an opening thereof facing downwards, and the second ring 5 is horizontally arranged; the second ring 5 cooperates with the second hook 3 for connection; four universal

3

wheels 4 are arranged under the mobile firmware 1, and each of the universal wheels 4 comprises a foot break 41; during working, the universal wheels 4 are used for moving the guardrail bodies 2, wherein after step down the foot break 41, the universal wheels are fixed, and the foot break 41 should be loosened for moving the guardrail bodies 2 again, which is convenient and saves effort; for moving a plurality of the guardrail bodies 2, the second rings 5 and the second hooks 3 of the guardrail bodies 2 are connected in sequence, in such a manner that the guardrail bodies 2 are integrated and move as a whole.

One skilled in the art will understand that the embodiment of the present invention as shown in the drawings and described above is exemplary only and not intended to be limiting.

It will thus be seen that the objects of the present invention have been fully and effectively accomplished. Its embodiments have been shown and described for the purposes of illustrating the functional and structural principles of the present invention and is subject to change without departure from such principles. Therefore, this invention includes all modifications encompassed within the spirit and scope of the following claims.

What is claimed is:

1. A method for electric power construction warning, comprising steps of: providing a mobile firmware (1) under a base of each of a plurality of guardrail bodies (2), so as to freely move the guardrail bodies (2); connecting a second ring (5) of the mobile firmware (1) to a second hook (3) of an adjacent mobile firmware (1), in such a manner that the guardrail bodies (2) are integrated and move as a whole; and isolating a construction site by pulling out two warning strips (12) respectively wound on two separate rollers (15) at a left side of each of the guardrail bodies (2) and connecting the warning strips (12) to an adjacent guardrail body (2).

2. The method, as recited in claim 1, wherein the second hook (3) is vertically arranged with an opening thereof facing downwards, and the second ring (5) is horizontally arranged.

3. The method, as recited in claim 1, wherein the warning strips (12) are connected to the adjacent guardrail body (2) before placing the guardrail bodies (2), then the guardrail bodies (2) are moved and fixed through moving the mobile

4

firmware (1) of each of the guardrail bodies (2) along a desired route, so as to complete arrangement of the guardrail bodies (2).

4. The method, as recited in claim 1, wherein four universal wheels (4) are arranged under the mobile firmware (1), and each of the universal wheels (4) comprises a foot brake (41) for fixing the guardrail bodies (2); a pair of handles (6) are symmetrically provided on external faces at a top portion of each of the guardrail bodies (2) for lifting the guardrail bodies (2) by worker hands.

5. The method, as recited in claim 1, wherein a solar power unit (9) and a caution light (7) are provided on each of the guardrail bodies (2) for warning.

6. A device for electric power construction warning, comprising: a guardrail body (2), a caution light (7) and a second hook (3), wherein a mobile firmware (1) is provided under the guardrail body (2); the second hook (3) is provided on a left side of the firmware (1), and a second ring (5) is provided on a right side of the firmware (1); a pair of handles (6) are symmetrically provided on external faces at a top portion of the guardrail body (2); a first ring (13) is provided on an external face at a bottom portion of the guardrail body (2); two roller supports (16) are separately provided on a left side of the guardrail body (2), and a roller (15) is provided on each of the roller supports (16); a warning strip (12) is wound on the roller (15), and one end of the warning strip (12) is connected to a first hook (10) through a connecting belt (11).

7. The device, as recited in claim 6, wherein the second hook (3) is vertically arranged with an opening thereof facing downwards, and the second ring (5) is horizontally arranged; the second ring (5) cooperates with the second hook (3) for connection.

8. The device, as recited in claim 6, wherein four universal wheels (4) are arranged under the mobile firmware (1), and each of the universal wheels (4) comprises a foot brake (41).

9. The device, as recited in claim 6, wherein the caution light (7) is provided on a top of the guardrail body (2), and is covered by a shell (8); a solar power unit (9) is provided on a top of the shell (8), and is connected to the caution light (7).

10. The device, as recited in claim 6, wherein the caution light (7) comprises a switch.

* * * * *