



US010385997B2

(12) **United States Patent**
Beagen, Jr.

(10) **Patent No.:** **US 10,385,997 B2**
(45) **Date of Patent:** ***Aug. 20, 2019**

(54) **SLIP-ON COUPLING GASKET**

(56) **References Cited**

(71) Applicant: **Anvil International, LLC**, Exeter, NH (US)

U.S. PATENT DOCUMENTS

(72) Inventor: **Joseph William Beagen, Jr.**, Providence, RI (US)

29,731 A 8/1860 Truss
815,581 A 3/1906 Dean

(Continued)

(73) Assignee: **Anvil International, LLC**, Exeter, NH (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 261 days.

CA 2732427 1/2015
DE 1051585 2/1959

(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

Schell, Ty; Applicant-Initiated Interview Summary for U.S. Appl. No. 13/667,786, filed Nov. 2, 2012, dated May 22, 2015, 3 pgs.

(Continued)

(21) Appl. No.: **15/281,663**

Primary Examiner — Nicholas L Foster

(22) Filed: **Sep. 30, 2016**

(74) *Attorney, Agent, or Firm* — Taylor English Duma LLP

(65) **Prior Publication Data**

US 2017/0016560 A1 Jan. 19, 2017

Related U.S. Application Data

(63) Continuation of application No. 13/354,470, filed on Jan. 20, 2012, now Pat. No. 9,500,307.

(51) **Int. Cl.**

F16J 15/02 (2006.01)

F16L 17/04 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F16L 21/065** (2013.01); **F16J 15/025** (2013.01); **F16L 17/025** (2013.01); **F16L 17/04** (2013.01); **F16L 21/02** (2013.01); **F16J 15/022** (2013.01)

(58) **Field of Classification Search**

CPC F16L 17/025; F16L 17/03; F16L 17/035; F16L 21/02; F16L 21/022; F16J 15/022; F16J 15/025; F16J 15/028; F16J 15/104


See application file for complete search history.

(57)

ABSTRACT

A method of installing a pipe coupling to connect a first pipe element to a second pipe element includes sliding the pipe coupling as a preassembled unit over an outermost surface of the first pipe element, the pipe coupling comprising a coupling segment and an annular gasket, the annular gasket comprising an annular body and a pair of sealing ribs extending substantially radially inward from the annular body, each sealing rib comprising a sealing ridge defining a sealing surface, the sealing surface of each sealing ridge being coannular in an undeformed state; introducing an end of the second pipe element to an end of the first pipe element to place the first pipe element and the second pipe element in end-facing relationship; aligning the pipe coupling over the first pipe element and the second pipe element; and securing the coupling to the first pipe element and the second pipe element.

16 Claims, 12 Drawing Sheets



(51)	Int. Cl.			3,680,619 A	8/1972	Sparks	
	<i>F16L 21/02</i>	(2006.01)		3,680,894 A	8/1972	Young	
	<i>F16L 21/06</i>	(2006.01)		3,695,638 A	10/1972	Blakeley	
	<i>F16L 17/025</i>	(2006.01)		RE27,736 E	8/1973	Muhlner et al.	
				3,794,361 A	2/1974	Westberg	
				3,797,078 A	3/1974	LaPointe	
				3,807,435 A	4/1974	Fenster et al.	
				3,856,245 A	12/1974	Byerly	
				3,877,733 A	4/1975	Straub	
				3,905,623 A	9/1975	Cassel	
				3,966,237 A	6/1976	Thiessen	
				3,977,705 A	8/1976	Thiessen et al.	
				4,034,788 A	7/1977	Melone	
				4,064,921 A	12/1977	Kose	
				4,108,479 A	8/1978	Straub	
				4,109,941 A	8/1978	Wood et al.	
				4,111,234 A	9/1978	Wells et al.	
				4,114,414 A	9/1978	Goodman	
				4,119,333 A *	10/1978	Straub	F16L 21/08 285/112
(56)	References Cited						
	U.S. PATENT DOCUMENTS						
	1,006,294 A	10/1911	Schubart				
	1,093,868 A	4/1914	Leighty				
	1,352,918 A	9/1920	Rohbock				
	1,541,601 A	6/1925	Tribe				
	1,851,574 A	3/1929	Fiederlein				
	1,930,194 A	10/1930	Dillon				
	1,833,776 A	11/1931	Dillon				
	1,867,891 A	7/1932	Baillie				
	1,881,508 A	10/1932	Gredell				
	1,905,324 A	4/1933	Waters				
	1,937,881 A	12/1933	Fisher	4,131,302 A	12/1978	Leonard, Jr.	
	1,970,078 A	8/1934	Dillon	4,137,610 A	2/1979	Hoen	
	1,987,235 A	1/1935	Janeway	4,176,865 A	12/1979	Felton et al.	
	2,020,156 A	11/1935	Muchnic	D256,046 S	7/1980	Perrin	
	2,041,132 A	5/1936	Johnson	4,258,361 A	3/1981	Hydes et al.	
	2,369,770 A	2/1945	Baxter	4,258,941 A	3/1981	Sands	
	2,377,510 A	6/1945	Newell	4,304,415 A	12/1981	Wolf et al.	
	2,426,423 A	8/1947	Woolsey	4,311,248 A	1/1982	Westerlund et al.	
	2,439,979 A	4/1948	Krooss	4,326,737 A	4/1982	Lehmann	
	2,449,795 A	9/1948	Sillwagon	4,350,350 A	9/1982	Blakeley	
	2,456,048 A	12/1948	Carpenter	4,377,894 A	3/1983	Yoshida	
	2,473,046 A	6/1949	Adams	4,391,458 A	7/1983	Blakeley	
	2,473,102 A	6/1949	Krooss	4,403,378 A	9/1983	Engman	
	2,486,120 A	10/1949	Colton et al.	4,408,788 A	10/1983	Beukema	
	2,616,946 A	11/1952	Scheer	4,417,755 A	11/1983	Gittleman	
	2,675,253 A	4/1954	Stade	4,432,558 A	2/1984	Westerlund et al.	
	2,688,170 A	9/1954	Balzer	4,438,958 A	3/1984	De Cenzo	
	2,688,500 A	9/1954	Scott	4,445,533 A	5/1984	Defrees	
	2,752,173 A	6/1956	Krooss	4,471,979 A	9/1984	Gibb et al.	
	2,754,136 A	7/1956	Newton	4,480,861 A	11/1984	Cann, Jr.	
	2,816,780 A	12/1957	Ross	4,506,418 A	3/1985	Viola et al.	
	2,821,415 A	1/1958	Race	4,518,177 A	5/1985	Deakins	
	2,944,839 A	7/1960	Anderson	4,522,433 A	6/1985	Valentine et al.	
	2,950,930 A	8/1960	Dunmire	4,522,434 A	6/1985	Vvebb	
	2,962,305 A	11/1960	McCarthy et al.	4,568,115 A	2/1986	Zimmerly	
	3,003,793 A	10/1961	Pitt	4,601,495 A	7/1986	Webb	
	3,004,781 A	10/1961	Morris	4,611,839 A	9/1986	Rung et al.	
	3,014,259 A	12/1961	Joseph	4,616,858 A	10/1986	Sauer	
	3,015,502 A	1/1962	Frost et al.	4,629,217 A *	12/1986	Straub	F16L 17/02 285/112
	3,024,046 A	3/1962	Frost et al.				
	3,054,629 A	9/1962	Piatek	4,639,020 A	1/1987	Rung et al.	
	D196,724 S	10/1963	Davis	4,643,461 A	2/1987	Thau, Jr.	
	3,107,108 A	10/1963	Greene	D289,078 S	3/1987	Vassallo et al.	
	3,134,612 A	5/1964	Glasgow	4,664,422 A *	5/1987	Straub	F16L 17/04 285/112
	3,135,154 A	6/1964	Zenzic				
	3,153,550 A	10/1964	Hollett	4,702,499 A	10/1987	Deraymond et al.	
	3,176,723 A	4/1965	Hodgeman et al.	4,702,500 A	10/1987	Thau, Jr. et al.	
	3,181,896 A	5/1965	Russell	4,717,299 A	1/1988	Underwood	
	3,189,969 A	6/1965	Sweet	4,722,561 A	2/1988	Heckelthorn et al.	
	3,201,149 A	8/1965	Bragg	4,726,611 A	2/1988	Sauer	
	3,207,538 A	9/1965	Pattillo	4,739,542 A	4/1988	Krzesicki	
	3,213,817 A	10/1965	Kish	4,776,362 A	10/1988	Domingue, Sr. et al.	
	3,251,615 A	5/1966	Short, III	4,861,075 A	8/1989	Pepi et al.	
	3,283,553 A	11/1966	Taylor	4,893,843 A	1/1990	Deraymond	
	3,285,568 A	11/1966	Biach	4,896,902 A	1/1990	Weston	
	3,291,506 A	12/1966	Blakeley	4,915,418 A	4/1990	Palatchy	
	3,298,698 A	1/1967	Condon	4,966,395 A	10/1990	Hendrickson	
	3,313,197 A	4/1967	Knohl	5,018,548 A	5/1991	McLennan	
	3,315,970 A	4/1967	Holloway	5,037,141 A	8/1991	Jardine	
	3,329,446 A	7/1967	Katis	5,039,137 A	8/1991	Cankovic et al.	
	3,351,352 A	11/1967	Blakeley et al.	5,056,833 A	10/1991	Webb et al.	
	3,362,730 A	1/1968	St. Clair et al.	5,058,931 A	10/1991	Bowsher	
	3,386,771 A	6/1968	Verdier et al.	5,080,400 A	1/1992	Adamek et al.	
	3,425,473 A	2/1969	Knowlton	5,094,492 A	3/1992	Levivier	
	3,464,722 A	9/1969	Larkin	5,104,153 A	4/1992	Corcoran	
	3,524,662 A	8/1970	Tolman et al.	5,137,305 A	8/1992	Straub	
	3,550,638 A	12/1970	Smith	5,190,324 A	3/1993	Bird et al.	
	3,658,367 A	4/1972	Pfeuffer	5,203,594 A	4/1993	Straub	
	3,664,691 A	5/1972	Nakamura	5,230,537 A	7/1993	Newman	

(56)

References Cited

U.S. PATENT DOCUMENTS

5,230,540	A	7/1993	Lewis et al.	D570,458	S	6/2008	Gibb et al.
5,240,294	A	8/1993	Corcoran	7,401,819	B2	7/2008	Gibb et al.
5,246,256	A	9/1993	Rung et al.	7,533,910	B2	5/2009	Ma
5,246,257	A	9/1993	Kojima et al.	D598,988	S	8/2009	Jaccoby
5,248,169	A	9/1993	Barbe et al.	D600,325	S	9/2009	Porter et al.
5,249,829	A	10/1993	Hendrickson	7,591,055	B2	9/2009	Gibb et al.
5,273,322	A	12/1993	Straub	D605,736	S	12/2009	Porter et al.
5,280,969	A	1/1994	Straub	D609,312	S	2/2010	Porter et al.
5,280,970	A	1/1994	Straub	7,654,587	B2	2/2010	Gibb et al.
5,291,769	A	3/1994	Miyano	D611,126	S	3/2010	Porter et al.
5,301,986	A	4/1994	Yehezkeili	D614,272	S	4/2010	Henry et al.
5,306,021	A	4/1994	Morvant	7,690,698	B1	4/2010	Curran
5,312,137	A	5/1994	Nee	D616,532	S	5/2010	Madara et al.
5,351,997	A	10/1994	Webb et al.	7,712,796	B2	5/2010	Gibb et al.
5,354,108	A	10/1994	Sandor	7,722,087	B2	5/2010	Dole et al.
5,387,017	A	2/1995	Gill	D618,312	S	6/2010	Madara et al.
5,450,738	A	9/1995	Chatterley et al.	D618,313	S	6/2010	Madara et al.
5,508,931	A	4/1996	Snider	D618,314	S	6/2010	Bowman et al.
5,509,702	A	4/1996	Warehime et al.	D618,315	S	6/2010	Bowman et al.
5,560,656	A	10/1996	Okamura et al.	7,726,703	B2	6/2010	Porter et al.
5,603,508	A	2/1997	Dole et al.	7,789,434	B2	9/2010	Nagle et al.
5,651,588	A	7/1997	Kato	D625,785	S	10/2010	Madara et al.
5,658,021	A	8/1997	Matsumoto et al.	D625,786	S	10/2010	Bowman et al.
5,697,650	A	12/1997	Brown	D625,787	S	10/2010	Bowman et al.
5,758,906	A	6/1998	Carlstrom et al.	D625,788	S	10/2010	Madara et al.
5,758,907	A	6/1998	Dole et al.	D626,201	S	10/2010	Madara et al.
5,772,257	A	6/1998	Webb et al.	7,818,869	B2	10/2010	Dole et al.
5,778,715	A	7/1998	Lippka et al.	D629,078	S	12/2010	Dole et al.
5,782,499	A	7/1998	Gfrerer et al.	D629,079	S	12/2010	Dole et al.
5,845,384	A	12/1998	Retzbach et al.	D629,080	S	12/2010	Dole et al.
5,873,611	A	2/1999	Munley et al.	D629,081	S	12/2010	Dole et al.
5,899,507	A	5/1999	Schroeder et al.	D629,496	S	12/2010	Madara et al.
5,901,601	A	5/1999	Fujimoto et al.	D633,991	S	3/2011	Nakagawa
5,911,446	A	6/1999	McLennan et al.	7,921,536	B2	4/2011	Dole
5,971,001	A	10/1999	Andersson	7,950,701	B2	5/2011	Dole et al.
6,070,911	A	6/2000	Namikawa et al.	D643,912	S	8/2011	Bowman et al.
6,070,914	A	6/2000	Schmidt	D646,764	S	10/2011	Rusconi
6,076,861	A	6/2000	Ikeda	8,038,176	B2	10/2011	Bowman et al.
6,139,069	A	10/2000	Radzik	D648,427	S	11/2011	Bowman
6,142,536	A	11/2000	Wolfsdorf	D651,290	S	12/2011	Shah et al.
6,170,884	B1	1/2001	McLennan et al.	8,069,547	B2	12/2011	Gibb et al.
6,171,039	B1	1/2001	Seurujarvi	8,079,129	B2	12/2011	Gibb et al.
6,206,434	B1	3/2001	Schreiter	8,136,847	B2	3/2012	Madara et al.
6,227,577	B1	5/2001	Ideka et al.	8,177,263	B2	5/2012	Dole et al.
6,231,286	B1	5/2001	Bogatz et al.	D665,056	S	8/2012	Cuvo et al.
6,302,450	B1	10/2001	Dole et al.	D665,057	S	8/2012	Madara et al.
6,305,719	B1	10/2001	Smith, Jr. et al.	D665,058	S	8/2012	Cuvo et al.
6,312,025	B1	11/2001	Wolfsdorf	D665,059	S	8/2012	Madara et al.
6,328,352	B1	12/2001	Geppert et al.	D665,060	S	8/2012	Wilk, Jr. et al.
6,361,085	B2	3/2002	Nguyen	D665,061	S	8/2012	Dole et al.
6,367,843	B1	4/2002	Fetzer	D665,888	S	8/2012	Wilk, Jr. et al.
6,371,491	B1	4/2002	Schultz et al.	D665,889	S	8/2012	Dole et al.
6,393,885	B1	5/2002	Cadena	8,267,432	B2	9/2012	Madara et al.
6,481,762	B1	11/2002	Rex et al.	8,282,136	B2	10/2012	Vandal et al.
6,502,865	B1	1/2003	Steele	8,312,616	B2	11/2012	Dole et al.
6,533,333	B1	3/2003	Radzik	D680,629	S	4/2013	Beagen, Jr.
6,565,129	B2	5/2003	Surjaatmadja	D680,630	S	4/2013	Beagen, Jr.
6,581,977	B1	6/2003	Dole et al.	8,424,918	B2	4/2013	Gibb et al.
6,619,094	B2	9/2003	Juhl	8,550,502	B2	10/2013	Vandal et al.
6,626,466	B1	9/2003	Dole	D696,751	S *	12/2013	Beagen, Jr. D23/269
6,749,232	B2	6/2004	Wachter et al.	8,615,865	B2	12/2013	Vandal et al.
6,752,359	B2	6/2004	Nagenkogl et al.	8,646,814	B2 *	2/2014	Lippka F16L 17/025 277/608
6,758,500	B2	7/2004	Lehnhardt	8,819,914	B2	9/2014	Porter et al.
6,758,501	B2	7/2004	Amedure et al.	9,039,046	B2 *	5/2015	Beagen, Jr. F16L 17/025 285/367
6,769,697	B1	8/2004	Ishikawa et al.	9,168,585	B2	10/2015	Schell et al.
6,834,892	B2	12/2004	Kornau et al.	9,194,516	B2 *	11/2015	Beagen, Jr. F16L 23/04
6,880,859	B2	4/2005	Breay et al.	9,239,123	B2	1/2016	Vandal et al.
6,908,123	B2	6/2005	Le	9,297,482	B2	3/2016	Vandal et al.
6,969,094	B2	11/2005	Frohling et al.	9,297,484	B2 *	3/2016	Beagen, Jr. F16L 23/04
D526,705	S	8/2006	Wortmann et al.	9,500,307	B2 *	11/2016	Beagen, Jr. F16L 21/065
7,086,131	B2	8/2006	Gibb et al.	9,534,715	B2 *	1/2017	Beagen, Jr. F16L 21/065
7,090,259	B2	8/2006	Dole	9,631,746	B2 *	4/2017	Beagen, Jr. F16L 17/025
7,118,317	B2	10/2006	Hofschneider	10,036,493	B2	7/2018	Vandal et al.
7,243,955	B2	7/2007	Krausz et al.	10,047,885	B2	8/2018	Vandal et al.
7,341,287	B2	3/2008	Gibb et al.	10,207,320	B2	2/2019	Schell et al.
				10,274,115	B2	4/2019	Beagen, Jr., et al.
				10,288,200	B2	5/2019	Beagen, Jr.

(56)

References Cited

U.S. PATENT DOCUMENTS

2002/0171244 A1 11/2002 Wachter et al.
 2002/0195820 A1 12/2002 Surjaatmadja
 2003/0062718 A1 4/2003 Radzik
 2003/0178850 A1 9/2003 Dole et al.
 2003/0234541 A1 12/2003 Thompson
 2004/0036291 A1 2/2004 Dole
 2005/0082831 A1 4/2005 Borland
 2005/0212284 A1 9/2005 Dole
 2005/0225087 A1 10/2005 McMahon et al.
 2005/0253380 A1 11/2005 Gibb et al.
 2005/0253382 A1 11/2005 Gibb et al.
 2005/0253383 A1 11/2005 Gibb et al.
 2005/0258641 A1 11/2005 Gibb
 2007/0040336 A1 2/2007 Sun et al.
 2007/0090646 A1 4/2007 Dole et al.
 2008/0007061 A1 1/2008 Gibb
 2008/0018057 A1 1/2008 Gibb et al.
 2008/0048444 A1 2/2008 Porter et al.
 2008/0272595 A1 11/2008 Gibb et al.
 2008/0284159 A1 11/2008 Krehl
 2008/0290652 A1 11/2008 Gibb et al.
 2009/0146417 A1* 6/2009 Lippka F16L 17/025
 285/112
 2009/0206598 A1 8/2009 Gibb et al.
 2009/0223031 A1 9/2009 Gibb et al.
 2009/0243291 A1 10/2009 Gibb et al.
 2010/0001521 A1 1/2010 Vandal et al.
 2010/0102549 A1 4/2010 Radzik
 2010/0148493 A1 6/2010 Madara et al.
 2010/0187812 A1 7/2010 Radzik et al.
 2010/0218362 A1 9/2010 Porter et al.
 2010/0289257 A1 11/2010 Madara et al.
 2010/0320756 A1 12/2010 Gibb et al.
 2011/0037250 A1 2/2011 Bowman et al.
 2011/0062706 A1 3/2011 Henry
 2011/0133415 A1 6/2011 Vu
 2011/0154646 A1 6/2011 Hagiya
 2012/0124804 A1 5/2012 Vandal
 2012/0139236 A1 6/2012 Novitsky et al.
 2012/0235405 A1 9/2012 Dole
 2012/0248767 A1 10/2012 Lippka
 2012/0256415 A1 10/2012 Dole
 2012/0256416 A1 10/2012 Ikeda et al.
 2012/0280494 A1 11/2012 Vandal et al.
 2013/0185919 A1* 7/2013 Beagen, Jr. F16L 17/025
 29/525.02
 2013/0187345 A1 7/2013 Beagen, Jr.
 2013/0187346 A1 7/2013 Beagen, Jr.
 2013/0187379 A1* 7/2013 Beagen, Jr. F16L 21/065
 285/337
 2014/0001753 A1 1/2014 Vandal
 2014/0076413 A1 3/2014 Vandal
 2014/0125054 A1 5/2014 Schell
 2015/0020371 A1 1/2015 Beagen, Jr.
 2015/0209919 A1 7/2015 Vandal
 2015/0211664 A1 7/2015 Vandal
 2015/0285417 A1 10/2015 Beagen
 2015/0369405 A1 12/2015 Vandal
 2015/0375298 A1 12/2015 Schell
 2017/0074433 A1* 3/2017 Beagen, Jr. F16L 21/065
 2017/0184233 A1* 6/2017 Beagen, Jr. F16L 17/025
 2018/0313483 A1 11/2018 Beagen, Jr.

FOREIGN PATENT DOCUMENTS

DE 972484 7/1959
 DE 1205348 11/1965
 DE 1798281 9/1971
 DE 2911575 9/1980
 DE 2950521 10/1980
 DE 3038491 4/1982
 DE 9103296 6/1991
 DE 4309330 9/1994
 DE 4427513 2/1996

DE 19534437 3/1997
 DE 10006029 8/2001
 DE 10230845 2/2003
 DK 108514 12/1967
 EP 0079457 5/1983
 EP 0178360 4/1986
 EP 0205896 12/1986
 EP 0360946 4/1990
 EP 0361765 4/1990
 EP 0386516 9/1990
 EP 396151 11/1990
 EP 0412642 2/1991
 EP 0427880 5/1991
 EP 0463424 1/1992
 EP 0531833 3/1993
 EP 1180630 2/2002
 EP 1260751 11/2002
 EP 2363367 9/2011
 ES 2172374 9/2002
 FR 1138312 6/1957
 FR 2761452 10/1998
 FR 2933474 1/2010
 GB 343781 2/1931
 GB 458441 12/1936
 GB 822025 10/1959
 GB 1322269 7/1973
 GB 1331236 9/1973
 GB 1489488 10/1977
 GB 2051213 1/1981
 GB 2098297 11/1982
 GB 2123904 2/1984
 GB 2143294 2/1985
 GB 2157785 10/1985
 GB 2161882 1/1986
 GB 2211255 6/1989
 GB 2218768 11/1989
 GB 2243659 11/1991
 GB 2253451 9/1992
 GB 2253452 9/1992
 GB 1019322 2/1996
 GB 2349189 10/2000
 GB 2367871 4/2002
 JP H427287 6/1990
 JP H4117978 4/1991
 JP H1154390 2/1999
 JP 2000257767 9/2000
 JP 2003074772 3/2003
 JP 2007278455 10/2007
 KR 10-1998-0012486 4/1998
 KR 10-1998-0025273 7/1998
 KR 10-2005-0121743 12/2005
 SE 8704187 4/1989
 WO 9317268 9/1993
 WO 9511402 4/1995
 WO 9843010 10/1998
 WO 0057093 9/2000
 WO 0077435 12/2000
 WO 0159350 8/2001
 WO 03029712 4/2003
 WO 2005114024 12/2005
 WO 07145995 12/2007
 WO 08104792 4/2008
 WO 2010002695 1/2010

OTHER PUBLICATIONS

Schell, Ty; Notice of Allowance for U.S. Appl. No. 13/667,786, filed Nov. 2, 2012, dated Jun. 29, 2015, 21 pgs.
 Schell, Ty; Issue Notification for U.S. Appl. No. 13/667,786, filed Nov. 2, 2012, dated Oct. 7, 2015, 1 pg.
 Schell, Ty; Non-Final Office Action for U.S. Appl. No. 13/667,786, filed Nov. 2, 2012, dated Oct. 16, 2014, 26 pgs.
 Schell, Ty; Final Office Action for U.S. Appl. No. 13/667,786, filed Nov. 2, 2012, dated Mar. 9, 2015, 14 pgs.
 Vandal, Peter Joseph; Final Office Action for U.S. Appl. No. 14/837,475, filed Aug. 27, 2015, dated Jun. 12, 2017, 14 pgs.
 Vandal; Issue Notification for U.S. Appl. No. 12/490,113, filed Jun. 23, 2009, dated Sep. 19, 2012; 1 pg.

(56)

References Cited

OTHER PUBLICATIONS

- Vandal; Non-Final Office Action for U.S. Appl. No. 12/490,113, filed Jun. 23, 2009, dated Dec. 8, 2011, 13 pages.
- Vandal; Notice of Allowance for U.S. Appl. No. 12/490,113, filed Jun. 23, 2009, dated Feb. 29, 2012; 39 pgs.
- Vandal; Notice of Allowance for U.S. Appl. No. 12/490,113, filed Jun. 23, 2009, dated Apr. 16, 2012; 6 pgs.
- Vandal; Notice of Allowance for U.S. Appl. No. 12/490,113, filed Jun. 23, 2009, dated May 31, 2012; 9 pgs.
- Vandal; Restriction Requirement for U.S. Appl. No. 12/490,113, filed Jun. 23, 2009, dated Oct. 26, 2011; 5 pgs.
- Vandal, Peter Joseph; Non-Final Office Action for U.S. Appl. No. 13/554,721, filed Jul. 20, 2012, dated Feb. 5, 2013; 54 pgs.
- Vandal, Peter Joseph; Notice of Allowance for U.S. Appl. No. 13/554,721, filed Jul. 20, 2012, dated Aug. 6, 2013, 18 pgs.
- Vandal, Peter Joseph; Issue Notification for U.S. Appl. No. 13/554,721, filed Jul. 20, 2012, dated Sep. 18, 2013, 1 pg.
- Vandal, Peter Joseph; Advisory Action for U.S. Appl. No. 14/019,182, filed Sep. 5, 2013, dated Jun. 23, 2014, 3 pgs.
- Vandal, Peter Joseph; Final Office Action for U.S. Appl. No. 14/019,182, filed Sep. 5, 2013, dated Apr. 8, 2014, 28 pgs.
- Vandal, Peter Joseph; Final Office Action for U.S. Appl. No. 14/019,182, filed Sep. 5, 2013, dated Jul. 11, 2014, 11 pgs.
- Vandal, Peter Joseph; Final Office Action for U.S. Appl. No. 14/019,182, filed Sep. 5, 2013, dated Oct. 24, 2014, 11 pgs.
- Vandal, Peter Joseph; Issue Notification for U.S. Appl. No. 14/019,182, filed Sep. 5, 2013, dated Oct. 28, 2015, 1 pg.
- Vandal, Peter Joseph; Issue Notification for U.S. Appl. No. 14/019,182, filed Sep. 5, 2013, dated Dec. 29, 2015, 1 pg.
- Vandal, Peter Joseph; Non-Final Office Action for U.S. Appl. No. 14/019,182, filed Sep. 5, 2013, dated Nov. 12, 2013, 54 pgs.
- Vandal, Peter Joseph; Non-Final Office Action for U.S. Appl. No. 14/019,182, filed Sep. 5, 2013, dated Mar. 23, 2015, 12 pgs.
- Vandal, Peter Joseph; Notice of Allowance for U.S. Appl. No. 14/019,182, filed Sep. 5, 2013, dated Nov. 18, 2015, 12 pgs.
- Vandal, Peter Joseph; Notice of Allowance for U.S. Appl. No. 14/019,182, filed Sep. 5, 2013, dated Jun. 1, 2015, 10 pgs.
- Vandal, Peter Joseph; Issue Notification for U.S. Appl. No. 14/677,507, filed Apr. 2, 2015, dated Mar. 9, 2016, 1 pg.
- Vandal, Peter Joseph; Non-Final Office Action for U.S. Appl. No. 14/677,507, filed Apr. 2, 2015, dated Jul. 30, 2015, 73 pgs.
- Vandal, Peter Joseph; Notice of Allowance for U.S. Appl. No. 14/677,507, filed Apr. 2, 2015, dated Feb. 2, 2016, 14 pgs.
- Vandal, Peter Joseph; Issue Notification for U.S. Appl. No. 13/300,718, filed Nov. 21, 2011, dated Dec. 11, 2013, 1 pg.
- Vandal, Peter Joseph; Non-Final Office Action for U.S. Appl. No. 13/300,718, filed Nov. 21, 2011, dated May 30, 2013; 59 pgs.
- Vandal, Peter Joseph; Notice of Allowance for U.S. Appl. No. 13/300,718, filed Nov. 21, 2011, dated Oct. 15, 2013; 14 pgs.
- Vandal, Peter Joseph; Supplemental Notice of Allowance for U.S. Appl. No. 13/300,718, filed Nov. 21, 2011, dated Dec. 4, 2013; 8 pgs.
- Vandal; International Search Report and Written Opinion for serial No. PCT/US09/48291, filed Jun. 23, 2009, dated Apr. 2, 2010; 11 pages.
- Vandal, Peter Joseph; Examiner's Answer to Appeal Brief for U.S. Appl. No. 14/088,865, filed Nov. 25, 2013, mailed Jun. 24, 2015, 24 pgs.
- Vandal, Peter Joseph; Final Office Action for U.S. Appl. No. 14/088,865, filed Nov. 25, 2013, dated Nov. 24, 2014, 11 pgs.
- Vandal, Peter Joseph; Non-Final Office Action for U.S. Appl. No. 14/088,865, filed Nov. 25, 2013, dated Aug. 14, 2014, 69 pgs.
- Vandal, Peter Joseph; Final Office Action for U.S. Appl. No. 14/677,490, filed Apr. 2, 2015, dated Mar. 8, 2016, 13 pgs.
- Vandal, Peter Joseph; Non-Final Office Action for U.S. Appl. No. 14/677,490, filed Apr. 2, 2015, dated Nov. 2, 2015, 76 pgs.
- Vandal; International Preliminary Report on Patentability for serial No. PCT/US/09/48637, filed Jun. 25, 2009, dated Jan. 5, 2011; 9 pgs.
- Vandal; International Search Report and Written Opinion for serial No. PCT/US/09/48637, filed Jun. 25, 2009, dated Jan. 4, 2010; 15 pgs.
- Gibb, John; Request for Ex Parte Reexamination under U.S. Appl. No. 90/012,656, filed Sep. 14, 2012; 143 pages.
<http://web.archive.org/web/20061024140046/http://www.romacindustries.com/Installation-instructions/XR501-install.pdf>; published on Oct. 24, 2006, 2 pgs.
- <http://web.archive.org/web/20061224052824/http://www.romacindustries.com/XR501.html>; published on Dec. 24, 2006, 2 pgs.
- Vandal, Peter Joseph; Canadian Office Action for serial No. 2,732,427, filed Jun. 25, 2009, dated Jul. 18, 2013, 3 pgs.
- Vandal, Peter; Office Action from Canadian Intellectual Property Office for Application No. 2,732,427, filed Jun. 25, 2009, dated Jul. 5, 2012; 4 pgs.
- Gibb, John; Request for Inter Partes Reexamination under U.S. Appl. No. 95/001,878, filed Jan. 27, 2012; 36 pages.
- Gibb, John; Request for Inter Partes Reexamination under U.S. Appl. No. 95/001,880, filed Feb. 1, 2012; 271 pages.
- Vandal; U.S. Appl. No. Entitled: Slip On Groove Coupling with Multiple Sealing Gasket, U.S. Appl. No. 61/133,300, filed Jun. 30, 2008; 9 pages.
- Beagen Jr., Joseph W.; Restriction Requirement for U.S. Appl. No. 13/354,459, filed Jan. 20, 2012, dated Oct. 31, 2014, 7 pgs.
- Beagen Jr., Joseph William; Final Office Action for U.S. Appl. No. 13/354,459, filed Jan. 20, 2012, dated Jun. 3, 2015, 16 pgs.
- Beagen Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 13/354,459, filed Jan. 20, 2012, dated Jan. 27, 2015, 71 pgs.
- Beagen Jr., Joseph William; Notice of Allowance for U.S. Appl. No. 13/354,459, filed Jan. 20, 2012, dated Sep. 17, 2015, 7 pgs.
- Beagen, Joseph William; Issue Notification for U.S. Appl. No. 13/354,459, filed Jan. 20, 2012, dated Nov. 4, 2015, 1 pg.
- Beagen, Joseph William; Issue Notification for U.S. Appl. No. 14/741,665, filed Jun. 17, 2015, dated Mar. 9, 2016, 1 pg.
- Beagen, Joseph William; Non-Final Office Action for U.S. Appl. No. 14/741,665, filed Jun. 17, 2015, dated Sep. 22, 2015, 59 pgs.
- Beagen, Joseph William; Notice of Allowance for U.S. Appl. No. 14/741,665, filed Jun. 17, 2015, dated Dec. 7, 2015, 7 pgs.
- Beagen, Jr., Joseph William; Requirement for Restriction/Election for U.S. Appl. No. 15/455,225, filed Mar. 10, 2017, dated May 16, 2018, 6 pgs.
- Vandal, Peter Joseph; Notice of Allowance for U.S. Appl. No. 14/837,475, filed Aug. 27, 2015, dated Apr. 11, 2018, 9 pgs.
- Vandal, Peter Joseph; Notice of Allowance for U.S. Appl. No. 14/088,865, filed Nov. 25, 2013, dated Apr. 5, 2018, 10 pgs.
- Beagen Jr, Joseph William; Office Action for Canadian application No. 2,776,206, filed May 7, 2012, dated May 14, 2018, 4 pgs.
- Vandal, Peter Joseph; Non-Final Office Action for U.S. Appl. No. 14/837,475, filed Aug. 27, 2015, dated Dec. 29, 2016, 90 pgs.
- Beagen Jr, Joseph William; Applicant Initiated Interview Summary for U.S. Appl. No. 14/506,307, filed Oct. 3, 2014, dated Oct. 31, 2016; 3 pgs.
- Beagen, Joseph William, Jr.; Notice of Allowance for U.S. Appl. No. 14/506,307, filed Oct. 3, 2014, dated Jan. 3, 2017, 9 pgs.
- Beagen, Jr.; Joseph William; Corrected Notice of Allowability for U.S. Appl. No. 13/354,466, filed Jan. 20, 2012, dated Dec. 6, 2016, 6 pgs.
- Beagen, Jr.; Joseph William; Issue Notification for U.S. Appl. No. 13/354,466, filed Jan. 20, 2012, dated Dec. 14, 2016, 1 pg.
- Beagen Jr., Joseph William; Issue Notification for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Nov. 2, 2016, 1 pg.
- Vandal, Peter Joseph; Non-Final Office Action for U.S. Appl. No. 14/837,475, filed Aug. 27, 2015, dated Dec. 20, 2017, 17 pgs.
- Vandal, Peter Joseph; Non Final Office Action for U.S. Appl. No. 14/088,865, filed Nov. 25, 2013, dated Nov. 14, 2017, 51 pgs.
- Schell, Ty; Non-Final Office Action for U.S. Appl. No. 14/848,641, filed Sep. 9, 2015, dated Jan. 11, 2018, 83 pgs.
- Beagen, Joseph William, Jr.; Issue Notification for U.S. Appl. No. 14/506,307, filed Oct. 3, 2014, dated Apr. 5, 2017, 1 page.
- Beagen, Joseph William, Jr.; Supplemental Notice of Allowability for U.S. Appl. No. 14/506,307, filed Oct. 3, 2014, dated Feb. 28, 2017, 6 pgs.

(56)

References Cited

OTHER PUBLICATIONS

- Vandal, Peter Joseph; Non-Final Office Action for U.S. Appl. No. 14/837,475, filed Aug. 27, 2015, dated Sep. 20, 2017, 15 pgs.
- Vandal, Peter Joseph; Decision of Appeal for U.S. Appl. No. 14/088,865, filed Nov. 25, 2013, mailed Aug. 18, 2017, 11 pgs.
- Beagen, Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 15/455,225, filed Mar. 10, 2017, dated Sep. 6, 2018, 88 pgs.
- Vandal, Peter Joseph; Issue Notification for U.S. Appl. No. 14/837,475, filed Aug. 27, 2015, dated Jul. 25, 2018, 1 pg.
- Vandal, Peter Joseph; Issue Notification for U.S. Appl. No. 14/088,865, filed Nov. 25, 2013, dated Jul. 11, 2018, 1 pg.
- Vandal, Peter Joseph; Notice of Allowability for U.S. Appl. No. 14/088,865, filed Nov. 25, 2013, dated Jul. 2, 2018, 7 pgs.
- Schell, Ty; Final Office Action for U.S. Appl. No. 14/848,641, filed Sep. 9, 2015, dated Aug. 8, 2018, 18 pgs.
- Gibb, John; Request for Inter Partes Reexamination under U.S. Appl. No. 95/002,401, filed Sep. 15, 2012; 147 pages.
- Gibb, John; Request for Inter Partes Reexamination under U.S. Appl. No. 95/002,410, filed Sep. 15, 2012; 85 pages.
- Beagen, Jr., Joseph William; Restriction Requirement for U.S. Appl. No. 13/354,464, filed Jan. 20, 2012, dated Oct. 4, 2013, 6 pgs.
- Beagen Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 13/354,464, filed Jan. 20, 2012, dated Jan. 28, 2014; 79 pgs.
- Beagen, Jr.; Joseph William; Final Office Action for U.S. Appl. No. 13/354,464, filed Jan. 20, 2012, dated Jul. 24, 2014, 20 pgs.
- Beagen Jr., Joseph William; Final Office Action for U.S. Appl. No. 13/354,464, filed Jan. 20, 2012, dated Oct. 15, 2014, 13 pgs.
- Beagen Jr., Joseph William; Notice of Allowance for U.S. Appl. No. 13/354,464, filed Jan. 20, 2012, dated Feb. 2, 2015, 9 pgs.
- Beagen Jr., Joseph William; Issue Notification for U.S. Appl. No. 13/354,464, filed Jan. 20, 2012, dated May 6, 2015, 1 pg.
- Schell, Ty; Advisory Action for U.S. Appl. No. 13/667,786, filed Nov. 2, 2012, dated May 14, 2015, 2 pgs.
- Beagen Jr., Joseph W.; Non-Final Office Action for U.S. Appl. No. 14/506,307, filed Oct. 3, 2014, dated Dec. 18, 2015, 80 pgs.
- Beagen Jr., Joseph W.; Applicant Interview Summary for U.S. Appl. No. 14/506,307, filed Oct. 3, 2014, dated Feb. 2, 2016, 3 pgs.
- Beagen Jr., Joseph W.; Final Office Action for U.S. Appl. No. 14/506,307, filed Oct. 3, 2014, dated May 12, 2016, 22 pgs.
- Beagen, Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 14/506,307, filed Oct. 3, 2014, dated Aug. 29, 2016; 19 pgs.
- Beagen, Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 13/354,466, filed Jan. 20, 2012, dated Jun. 13, 2014, 84 pgs.
- Beagen, Jr.; Joseph William; Final Office Action for U.S. Appl. No. 13/354,466, filed Jan. 20, 2012, dated Sep. 9, 2014, 18 pgs.
- Beagen Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 13/354,466, filed Jan. 20, 2012, dated Dec. 17, 2014, 12 pgs.
- Beagen Jr., Joseph William; Final Office Action for U.S. Appl. No. 13/354,466, filed Jan. 20, 2012, dated Apr. 7, 2015, 21 pgs.
- Beagen Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 13/354,466, filed Jan. 20, 2012, dated Jul. 30, 2015, 18 pgs.
- Beagen Jr., Joseph William; Final Office Action for U.S. Appl. No. 13/354,466, filed Jan. 20, 2012, dated Feb. 2, 2016, 22 pgs.
- Beagen, Joseph William; Advisory Action for U.S. Appl. No. 13/354,466, filed Jan. 20, 2012, dated Mar. 17, 2016, 5 pgs.
- Beagen, Jr., Joseph William; Notice of Allowance for U.S. Appl. No. 13/354,466, filed Jan. 2, 2012, dated Aug. 25, 2016, 21 pgs.
- Beagen, Jr.; Joseph William; Corrected Notice of Allowability for U.S. Appl. No. 13/354,466, filed Jan. 20, 2012, dated Oct. 4, 2016, 7 pgs.
- Beagen, Jr.; Joseph William; Non-Final Office Action for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Jun. 18, 2014, 97 pgs.
- Beagen Jr., Joseph William; Final Office Action for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Dec. 17, 2014, 20 pgs.
- Beagen Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Apr. 8, 2015, 16 pgs.
- Beagen Jr., Joseph William; Final Office Action for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Aug. 11, 2015, 28 pgs.
- Beagen Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Nov. 13, 2015, 28 pgs.
- Beagen Jr., Joseph William; Applicant Interview Summary for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Dec. 29, 2015, 3 pgs.
- Beagen Jr., Joseph William; Final Office Action for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Apr. 6, 2016, 28 pgs.
- Beagen Jr., Joseph William; Applicant Interview Summary for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Apr. 21, 2016, 3 pgs.
- Beagen Jr., Joseph William; Notice of Allowance for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Jun. 29, 2016, 13 pgs.
- Beagen Jr., Joseph William; Corrected Notice of Allowability for U.S. Appl. No. 13/354,470, filed Jan. 20, 2012, dated Oct. 24, 2016, 6 pgs.
- Beagan Jr.; Notice of Allowance for U.S. Appl. No. 29/406,887, filed Nov. 21, 2011, dated Dec. 6, 2012; 47 pgs.
- Beagen Jr, Joseph William; Supplemental Notice of Allowance for U.S. Appl. No. 29/406,887, filed Nov. 21, 2011, dated Jan. 10, 2013; 13 pgs.
- Beagen, Jr., Joseph William; Supplemental Notice of Allowance for U.S. Appl. No. 29/406,887, filed Nov. 21, 2011, dated Mar. 14, 2013, 6 pgs.
- Beagen, Jr., Joseph William; Issue Notification for U.S. Appl. No. 29/406,887, filed Nov. 21, 2011, dated Apr. 3, 2013, 1 pg.
- Beagan, Jr., Joseph William; Notice of Allowance for U.S. Appl. No. 29/405,039, filed Oct. 27, 2011, dated Oct. 2, 2013, 68 pgs.
- Beagan, Joseph William; Issue Notification for U.S. Appl. No. 29/405,039, filed Oct. 27, 2011, dated Dec. 11, 2013, 1 pg.
- Beagen Jr., Joseph William; Supplemental Notice of Allowance for U.S. Appl. No. 29/405,039, filed Oct. 27, 2011, dated Nov. 25, 2013, 9 pgs.
- Beagan Jr.; Notice of Allowance for U.S. Appl. No. 29/406,886, filed Nov. 21, 2011, dated Dec. 6, 2012; 50 pgs.
- Beagen Jr, Joseph William; Supplemental Notice of Allowance for U.S. Appl. No. 29/406,886, filed Nov. 21, 2011, dated Feb. 28, 2013; 6 pgs.
- Beagen, Jr., Joseph William; Issue Notification for U.S. Appl. No. 29/406,886, filed Nov. 21, 2011, dated Apr. 3, 2013, 1 pg.
- Beagen Jr., Joseph William; Supplemental Notice of Allowance for U.S. Appl. No. 29/406,886, filed Nov. 21, 2011, dated Jan. 11, 2013, 13 pgs.
- Schell, Ty; Restriction Requirement for U.S. Appl. No. 13/667,786, filed Nov. 2, 2012, dated Jan. 10, 2014, 6 pgs.
- Schell, Ty; Non-Final Office Action for U.S. Appl. No. 13/667,786, filed Nov. 2, 2012, dated Feb. 24, 2014; 74 pgs.
- Schell, Ty; Final Office Action for U.S. Appl. No. 13/667,786, filed Nov. 2, 2012, dated Jul. 3, 2014, 9 pgs.
- Schell, Ty; Applicant Initiated Interview Summary for U.S. Appl. No. 13/667,786, filed Nov. 2, 2012, dated Jul. 23, 2014, 3 pgs.
- Beagen, Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 16/026,659, filed Jul. 3, 2018, dated Dec. 17, 2018, 68 pgs.
- Schell, Ty; Notice of Allowance for U.S. Appl. No. 14/848,641, filed Sep. 9, 2015, dated Oct. 17, 2018, 9 pgs.
- Beagen, Joseph William; Office Action for Canadian application No. 2,776,206, filed May 7, 2012, dated Nov. 26, 2018, 5 pgs.
- Beagen, Joseph William; Office Action for Canadian application No. 3,020,576, filed May 7, 2012, dated Oct. 29, 2018, 5 pgs.
- Beagen, Jr., Joseph William; Office Action for Canadian serial No. 3,020,608, filed May 7, 2012, dated Nov. 2, 2018, 5 pgs.
- Beagen, Jr., Joseph William; Notice of Allowance for U.S. Appl. No. 15/455,255, filed Mar. 10, 2017, dated Jan. 15, 2019, 9 pgs.
- Beagen, Jr.; Joseph William; Corrected Notice of Allowance for U.S. Appl. No. 15/455,225, filed Mar. 10, 2017, dated Feb. 25, 2019, 6 pgs.
- Beagen, Jr., Joseph William; Notice of Allowance for U.S. Appl. No. 16/026,659, filed Jul. 3, 2018, dated Jan. 10, 2019, 9 pgs.
- Beagen, Jr.; Joseph William; Supplemental Notice of Allowance for U.S. Appl. No. 16/026,659, filed Jul. 3, 2018, dated Jan. 24, 2019, 6 pgs.
- Beagen, Jr., Joseph William; Requirement for Restriction/Election for U.S. Appl. No. 15/359,676, filed Nov. 23, 2016, dated Feb. 13, 2019, 6 pgs.
- Schell, Ty; Corrected Notice of Allowance for U.S. Appl. No. 14/848,641, filed Sep. 9, 2015, dated Jan. 15, 2019, 4 pgs.

(56)

References Cited

OTHER PUBLICATIONS

Schell, Ty; Issue Notification for U.S. Appl. No. 14/848,641, filed Feb. 9, 2015, dated Jan. 30, 2018, 1 pg.

Beagen, Joseph William; Issue Notification for U.S. Appl. No. 15/455,225, filed Mar. 10, 2017, dated Apr. 24, 2019, 1 pg.

Beagen, Jr., Joseph William; Supplemental Notice of Allowance for U.S. Appl. No. 15/455,225, filed Mar. 10, 2017, dated Apr. 3, 2019, 6 pgs.

Beagen, Jr., Joseph William; Issue Notification for U.S. Appl. No. 16/026,659, filed Jul. 3, 2018, dated Apr. 10, 2019, 1 pg.

Beagen, Jr., Joseph William; Supplemental Notice of Allowance for U.S. Appl. No. 16/026,659, filed Jul. 3, 2018, dated Mar. 26, 2019, 6 pgs.

Beagen, Jr., Joseph William; Office Action for Canadian serial No. 3,020,608, filed May 7, 2012, dated Feb. 20, 2019, 3 pgs.

Beagen, Jr., Joseph William; Non-Final Office Action for U.S. Appl. No. 15/359,676 filed Nov. 23, 2018, dated Jun. 13, 2019, 111 pgs.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6






FIG. 8A




FIG. 8B




FIG. 8D




FIG. 8C




FIG. 8E




FIG. 9




FIG. 10




FIG. 11

1**SLIP-ON COUPLING GASKET****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 13/354,470, filed Jan. 20, 2012, which is incorporated herein by reference in its entirety.

FIELD

This disclosure relates to piping. More specifically, this disclosure relates to pipe coupling.

BACKGROUND

Pipe elements such as pipes, valves, and meters typically are not made of one piece. Rather, such pipe elements are formed in finite lengths and must be joined. One way of joining such pipe elements is through the use of a coupling member. A sealing gasket is typically disposed in a central space of at least one coupling segment which is thereafter tightened around the pipe elements to be joined.

SUMMARY

Disclosed is a method of installing a pipe coupling to connect a first pipe element to a second pipe element comprising sliding the pipe coupling as a preassembled unit over an outermost surface of the first pipe element, the pipe coupling comprising a coupling segment and an annular gasket, the annular gasket comprising an annular body and a pair of sealing ribs extending substantially radially inward from the annular body, each sealing rib comprising a sealing ridge defining a sealing surface, the sealing surface of each sealing ridge being coannular in an undeformed state; introducing an end of the second pipe element to an end of the first pipe element to place the first pipe element and the second pipe element in end-facing relationship; aligning the pipe coupling over the first pipe element and the second pipe element; and securing the coupling to the first pipe element and the second pipe element.

Also disclosed is a method of installing a pipe coupling to connect a first pipe element to a second pipe element comprising sliding the pipe coupling as a preassembled unit over an outermost surface of the first pipe element, the pipe coupling comprising a coupling segment and an annular gasket having an innermost diameter greater than a diameter of the outermost surface of the first pipe element and a diameter of the outermost surface of the second pipe element, the annular gasket comprising an annular body and a pair of sealing ribs extending substantially radially inward from the annular body, each sealing rib comprising a sealing ridge defining a sealing surface, the annular gasket configured to slide over the diameters of the outermost surface of the first pipe element and the outermost surface of the second pipe element without contacting the outermost surfaces of the first pipe element and the second pipe element in an undeformed state; introducing an end of the second pipe element to an end of the first pipe element to place the first pipe element and the second pipe element in end-facing relationship; aligning the pipe coupling over the first pipe element and the second pipe element; and securing the coupling to the first pipe element and the second pipe element.

Various implementations described in the present disclosure may include additional systems, methods, features, and

2

advantages, which may not necessarily be expressly disclosed herein but will be apparent to one of ordinary skill in the art upon examination of the following detailed description and accompanying drawings. It is intended that all such systems, methods, features, and advantages be included within the present disclosure and protected by the accompanying claims.

DESCRIPTION OF THE FIGURES

The features and components of the following figures are illustrated to emphasize the general principles of the present disclosure and are not necessarily drawn to scale. Corresponding features and components throughout the figures may be designated by matching reference characters for the sake of consistency and clarity.

FIG. 1 is an exploded perspective view of a coupling in accord with one embodiment of the current disclosure.

FIG. 2 is an outer perspective view of a segment of the coupling of FIG. 1.

FIG. 3 is an inner perspective view of the segment of FIG. 2.

FIG. 4 is a cross-sectional view of the segment of FIG. 2.

FIG. 5 is a cross-sectional view of a gasket of the coupling of FIG. 1.

FIG. 6 is a side view of the coupling of FIG. 1 in an assembled and untightened position.

FIG. 7 is a side view of the coupling of FIG. 1 in an assembled and tightened position, including a cross-sectional view of pipe elements.

FIG. 8A is a cross-sectional view of the coupling of FIG. 1 before installation on pipe elements.

FIG. 8B is a cross-sectional view of the coupling of FIG. 1 during installation on pipe elements.

FIG. 8C is a cross-sectional view of the coupling of FIG. 1 during installation on pipe elements.

FIG. 8D is a cross-sectional view of the coupling of FIG. 1 during installation on pipe elements.

FIG. 8E is a cross-sectional view of the coupling of FIG. 1 after installation on pipe elements.

FIG. 9 is a cross-sectional view of the coupling taken in a plane indicated by line 9 in FIG. 6.

FIG. 10 is a partial cross-sectional view of the coupling of FIG. 1 assembled around pipe elements and in an untightened position.

FIG. 11 is a partial cross-sectional view of the coupling of FIG. 1 assembled around pipe elements and in a tightened position.

DETAILED DESCRIPTION

Disclosed is a pipe coupling and associated methods, systems, devices, and various apparatus. The pipe coupling includes at least one segment, at least one tightening element, and at least one gasket. The pipe coupling is adapted to seal pipe elements in end-to-end relationship. It would be understood by one of skill in the art that the disclosed pipe coupling is described in but a few exemplary embodiments among many. No particular terminology or description should be considered limiting on the disclosure or the scope of any claims issuing therefrom.

One embodiment of a pipe coupling **100** is disclosed and described in FIG. 1. The pipe coupling **100** of the current embodiment includes two segments **110, 110'** although any number of segments **110** may be used in various embodiments. The current embodiment includes tightening elements or fasteners that are nut and bolt fasteners. Two bolts

120a,b are disposed to interact with nuts **125a,b** in threaded engagement. Various types of tightening elements may be used in various embodiments, and the disclosure of bolts **120a,b**, and nuts **125a,b** should not be considered limiting. Fastener pads **130a,b** protrude from segment **110** and fastener pads **130a',b'** protrude from segment **110'**. Fastener holes **132a,b,a',b'** are defined in fastener pads **130a,b,a',b'**, respectively. In the current embodiment, the fastener holes **132a,b,a',b'** are about centered within the fastener pads **130a,b,a',b'**, although they may be offset in various embodiments. Although the fastener pads **130a,b,a',b'** and fastener holes **132a,b,a',b'** are described in the current configuration, various locations and configurations of fastener pads **130a,b,a',b'** and fastener holes **132a,b,a',b'** are included in various embodiments. A gasket **150** is included with the pipe coupling **100**. The gasket **150** of the current embodiment is annular and adapted to surround and to seal fluid piping, although various configurations will be included in various embodiments.

FIGS. 2, 3, and 4 show segment **110**. In the current embodiment, segment **110'** is substantially identical to segment **110**. As seen in FIG. 2, each segment **110** includes two ends **203,207** and a segment body **210** disposed between the two ends **203,207**. Each segment **110** in the current embodiment is about semicircular, although other configurations may be used in various embodiments. Proximate each end **203,207** is a shoulder **213,217** protruding outwardly from the segment **110**. Each shoulder **213,217** provides a connection point for a fastener which, in the current embodiment, is a bolt **120**. Each shoulder **213,217** includes fastener holes **132a,b** defined in fastener pads **130a,b**.

Each segment body **210** includes a central portion **215** and at least one edge portion **225b** (**225a** not shown in FIG. 2). In the current embodiment, the edge portions **225a,b** are designed to interact with a groove in the pipe elements to be sealed and joined, although some embodiments may be designed to interact with non-grooved pipe elements.

As can be seen in FIG. 2, each fastener hole **132a,b** includes a first linear extent or an axial length **233,237** and a second linear extent or transverse length **243,247**. The axial lengths **233,237** and the transverse lengths **243,247** are measured at top surfaces **364,314** of the fastener pads **130a,b**. These dimensions increase through the fastener pads **130a,b** in the current embodiment because they are cast, and a draft angle is used in casting. In various embodiments, these dimensions may remain constant if, for example, the fastener holes **132a,b** are made via a machining step. In the current embodiment, each fastener hole **132a,b** is about ovalar in shape, although other embodiments may include various shapes. The shape of the current embodiment of the fastener holes **132a,b** provides interference with the bolts **120a,b** to reduce rocking motion, as will be described later with reference to FIG. 9. Each segment **110** includes an outer surface **250** and an inner surface **260**. A contact surface **262b** (**262a** shown in FIG. 3) is included on the inside of each edge portion **225a,b**. Also seen in FIG. 2 is a tongue **280**, as will be described in more detail with reference to FIGS. 3, 4, and 6.

As seen more clearly in FIG. 3, the tongue **280** protrudes from the end **207** of the segment **110**. The shoulder **217** can be seen protruding outwardly from the segment **110**. In the current embodiment, the shoulder **217** includes a bottom surface **312** and a top surface **314**. The bottom surface **312** and the top surface **314** are substantially parallel in the current embodiment and are angled in order to ensure proper alignment upon deformable tightening of the pipe coupling **100**, as will be discussed later with reference to FIG. 4.

However, in some embodiments, the bottom surface **312** and the top surface **314** are not angled. A wall **317** of the shoulder **217** is seen along the outside of the shoulder **217**. The wall **317** in the current embodiment defines a draft portion **316** having a draft angle such that the thickness of the shoulder **217** at a beginning of the draft **318** is thicker than the thickness at an end of the draft **319**. The angle of the draft portion **316** is consistent between the beginning of the draft **318** and the end of the draft **319** so that the region defining the draft angle is a linear taper in the current embodiment, although other shapes may be used in various embodiments. A radiused portion **321** extends beyond the draft portion **316** to provide an end **334** of the shoulder **217** beyond the fastener hole **132b**. The wall **317** includes an outer surface **322**.

As can be seen from the view of FIG. 3, the shoulder **217** includes a taper portion **326**. The taper portion **326** terminates at the end **334** of the shoulder **217** and melds at the other end with a parallel portion **327** of the shoulder **217**. As previously described, the bottom surface **312** is parallel to the top surface **314** in the parallel portion **327**. A ledge surface **331a,b** provides a quick transition to the taper portion **326**, which includes a taper bottom surface **332** that is not parallel to the top surface **314**. An inner surface **335b** of the fastener hole **132b** can also be seen in the current view.

The tongue **280** includes three portions in the current embodiment: a central portion **342**, a first side portion **344**, and a second side portion **346**. The side portions **344,346** are oriented with respect to the central portion **342** such that an angle is formed between each. In the current embodiment, the angle is greater than ninety degrees. The tongue **280** includes an outer surface **352**, an inner surface **354**, and a mating surface **355**. The mating surface **355** is angled at a tip angle **430**, which is shown in FIG. 4. The mating surface **355** is located on a leading edge of the tongue **280**.

Shown along the other end **203** is the other shoulder **213**. The shoulder includes a bottom surface **362** and a top surface **364** that are substantially parallel. The shoulder **213** includes a draft portion **366** and a radiused portion **371**. A taper portion **376** is included just like with shoulder **203**. A parallel portion **377** is also included where the bottom surface **362** is parallel to the top surface **364** in the region. Ledge surfaces **381a,b** (not shown) are also included just like ledge surfaces **331a,b**, and a taper bottom surface **382** is also included.

A groove **380** is defined in the shoulder **213**. The groove **380** is sized to accept the tongue **280**. The groove **380** includes a central wall **392** and two side walls **394,396**. The groove **380** is further defined by a mating surface **395**. In assembly, the mating surface **395** contacts the mating surface **355'** of another segment **110'**. A groove shoulder surface **389** is included on the inside of the groove **380**. A draft portion **388** can be seen proximate the end of the segment **110** nearest the groove **380**. The draft portion **388** provides a relief from the inner surface **260** to the mating surface **395** to line up with the tongue **280'**, which is slightly set back from the inner surface **260'**. The draft portion **388** helps prevent the coupling **100** from pinching the gasket **150** during installation, as pinching of the gasket **150** can lead to failure of the gasket **150** including slicing and rupture of the gasket **150**. A draft portion shoulder surface **387a,b** (**387b** not shown) provides the part of the step-down from a shoulder surface **296a,b** (**296b** not shown) to the mating surface **395**.

Each edge portion **225a,b** of the segment **110** includes a contacting portion **292a,b** and a support portion **294a,b**. The

contact surface **262a,b** is included at the end of the contacting portion **292a,b**. The shoulder surface **296a** (**296b** not shown) can be seen at the inside end of the support portion **294a** (inside end of the support portion **294b** not shown). Three nodes **297a,298a** (**299a,b** and **297b,298b** not shown) protrude from the shoulder surface **296a,b** between the support portion **294a,b** and the contacting portion **292a,b**. Each node **297a,b** and **298a,b** include a width that decreases from the support portion **294a,b** to the contacting portion **292a,b**. Although the nodes **297a,b**, **298a,b**, and **299a,b** are pyramidal in the current embodiment, they may be various shapes in various embodiments.

The gasket **150** is designed to interact with the inner surface **260** of each segment **110** in the pipe coupling **100**, as will be discussed with reference to FIG. 5.

As seen in the cross-sectional view of FIG. 4, the top surfaces **314,364** and the bottom surfaces **312,362** are aligned at angles **415,416,417,418** with respect to a horizontal axis **420** of the segment **110**. A vertical axis **425** is shown for reference. The angles **415,416,417,418** allow for deflection of the segment **110** in use. In some embodiments, the angles **415,416,417,418** will be zero such that the top surfaces **314,364** are aligned with the horizontal axis **420** when no deflection is present. The tip angle **430** of the tongue **280** can be seen such that the mating surface **355** is aligned angularly with respect to the horizontal axis **420**. The tip angle **430** is greater than the other angles **415,416,417,418** in the current embodiment, although other configurations may be found in various embodiments. When the segment **110** is deflected, the mating surface **355** contacts the mating surface **395** of another segment **110**. In various embodiments, the tip angle **430** is approximately the same as the angles **415,417** of the top surface **314** and bottom surface **312**, respectively.

Also seen in cross-sectional view, each fastener hole **132a,b** is drafted such that each fastener hole **132a,b** defines a cone-shaped void that is approximately ovular in cross-section, although various cross-sectional shapes may be found in various embodiments. As such, each fastener hole **132a,b** includes a smaller aperture at the top surface **314,364** than where the fastener hole **132a,b** emerges into the taper bottom surface **332,382** and the bottom surface **312,362**. This configuration may be omitted in various embodiments.

As can be seen in FIG. 5, the gasket **150** is ring-shaped and includes an annular body **510** having a radially outer surface **515**. The radially outer surface **515** interacts with the inner surface **260** of each segment **110** in the pipe coupling **100**. The radially outer surface **515** of the annular body **510** includes a deformation groove **517**. The annular body **510** includes side portions proximate axial ends of the annular body **510**. Extending substantially radially inward from the side portions of the annular body **510** are a pair of sealing ribs **520a,b**. Each sealing rib **520a,b** extends substantially radially inwardly and increases in thickness from radially outside to radially inside. Each sealing rib **520a,b** also has an axially outer surface **521a,b** extending from the radially outer surface **515** to the start of an axially outer drafted edge **522a,b**. Each axially outer surface **521a,b** is angled with respect to a radial direction. The angle of each axially outer surface **521a,b** is consistent around the entirety of the annular body **510**, so that axially outer surfaces **521a,b** are shaped as a truncated cone. In the current embodiment, each axially outer surface **521a,b** is angled between nineteen and twenty-two degrees with respect to a radius of the gasket **150**, although other configurations may be present in various embodiments.

Each sealing rib **520a,b** has a sealing ridge **525a,b** extending axially inward from a radially inward end **551a,b** of each sealing rib **520a,b**. Each sealing ridge **525a,b** extends substantially axially inward from the radially inward end **551a,b** of each sealing rib **520a,b**, such that the two sealing ridges **525a,b** extend toward each other. The axially outer drafted edges **522a,b** extend from the radially inward end **551a,b** to a contact portion **555a,b**. Each axially outer drafted edge **522a,b** may be rounded, slanted, or various shapes in cross-section in various embodiments. Such cross-sectional shapes translate to conical and paraboloid shapes in various embodiments. Such shapes are truncated, as a full cone or paraboloid would not allow insertion of pipe elements in the gasket **150**. In the embodiment shown in FIG. 5, the axially outer drafted edges **522a,b** are slanted at an angle approximately between 27° and 28° from a radial direction, although various other angles may be present in various embodiments. Contact portions **555a,b** extend along the sealing ridges **525a,b** from the axially outer drafted edges **522a,b** to an axially inner drafted edge **527a,b**. Each contact portion **555a,b** includes a sealing surface **526a,b** facing radially inward and coplanar or collinear with each other in the cross-sectional view. The coplanar/collinear arrangement in cross-sectional view denotes a coannular surface profile of the sealing surfaces **526a,b** in the current embodiment, although the surfaces may be of different diameters in various embodiments. The sealing surfaces **526a,b** are intended to contact pipe elements placed inside of the gasket **150** to provide a fluid seal for the pipe elements. The sealing surfaces **526a,b** face radially inwardly and extend substantially axially at rest. In other words, by “face radially inwardly,” when the sealing surfaces **526a,b** are not in contact with pipe elements, the sealing surfaces **526a,b** approximate a cylinder that is about coaxial with the pipe elements intended to be used with the coupling **100**. Thus, the sealing surfaces **526a,b** appear as lines that are parallel with the axis of pipe elements **710** in cross-sectional view, as seen in FIGS. 8A-8E. Any angle with respect to the pipe elements **710** is minimal.

The orientation of the sealing surfaces **526a,b** is intended to ease the insertion of pipe elements into contact with the sealing surfaces **526a,b** of gasket **150**. Extending from each sealing surface **526a,b** is the axially inner drafted edge **527a,b**. The axially inner drafted edges **527a,b** may be rounded, slanted, or various shapes in cross-section in various embodiments. Such cross-sectional shapes translate to paraboloid and conical shapes in various embodiments. Such shapes are truncated, as a full cone or paraboloid would not allow insertion of pipe elements in the gasket **150**. The axially inner drafted edges **527a,b** define the termination of the sealing ridge **525a,b** along the axially inward direction.

A center rib **530** extends radially inward from the annular body **510**. The center rib **530** includes a central groove **531** and two sealing members **557a,b** which each include a sealing surface **532a,b**. Each sealing member **557a,b** in the current embodiment is a rounded protrusion from the central groove **531**. In various embodiments, various shapes and configurations of sealing members **557a,b** may be used, including flattened shapes, combinations of protrusions, and unconnected surfaces, among others. The sealing surface **532a,b** is included on the sealing member **557a,b**, respectively. The central groove **531** is positioned between the sealing surfaces **532a,b** such that the sealing surfaces **532a,b** of the sealing members **557a,b** are capable of contacting the pipe elements and providing additional sealing interaction therewith.

Each sealing rib **520a,b** has an innermost radial extent as measured from the annular body **510**. In addition, each sealing rib **520a,b** has an edge radial extent as measured from the annular body **510** to an axially innermost end of each of the axially inner drafted edges **527a,b**. The center rib **530** has an innermost radial extent as measured from the annular body **510**. The innermost radial extent of the center rib **530** is closer to the annular body **510** than the innermost radial extent of each of the pair of sealing ribs **520a,b**. Additionally, in the current embodiment, the innermost radial extent of the center rib **530** is closer to the annular body **510** than the edge radial extent of each of the pair of sealing ribs **520a,b**. The innermost radial extent of the center rib **530** may be as far from the annular body as, or farther from the annular body **510** than, the edge radial extent of each of the pair of sealing ribs **520a,b** in various embodiments. The innermost radial extent of the center rib **530** may also be equally as far from the annular body **510** as the innermost radial extent of each of the pair of sealing ribs **520a,b** in various embodiments.

The gasket **150** may be made of rubber, plastic, cork, wood, metal, ceramic, polymer, elastomer, rosin, foam, any combination of the foregoing materials, or any material suitable for sealing two pipe elements joined in end-to-end relationship. "Pipe elements" may mean pipes, valves, meters, or any other piping joint suitable to be sealed.

The annular body **510**, the sealing ribs **520a,b**, and the center rib **530** define gasket channels **540a,b** as seen in FIG. 5. The gasket channels **540a,b** are pockets into which fluid media may flow when the gasket **150** is in use. The gasket channels **540a,b** are tubular channels in the current embodiment but may be various shapes in various embodiments. When placed in sealing contact with an exterior surface of a pipe element, the gasket channels **540a,b** allow some fluid pressure to aid in sealing the sealing ridges **525a,b** against pipe elements, although such use is not necessary for successful sealing of the gasket **150**. The center rib **530** decreases in thickness from its radial outermost to its termination radially inward.

In addition, when the gasket **150** is in use, the sealing members **557a,b** and the groove **531** act to prevent substantial fluid media flow into the gasket channels **540a,b**. When placed in sealing contact with exterior surfaces of pipe elements, the sealing surfaces **532a,b** of the sealing members **557a,b** prevent substantial fluid media flow into gasket channels **540a,b**, retaining fluid media flow in the groove **531**. The gasket, in alternative embodiments, may include a plurality of center ribs, each with at least one sealing member and at least one sealing surface, which perform the same function as described above to prevent substantial fluid media flow into the gasket channels.

One problem that the center rib **530** can alleviate is the buildup of fluids in the gasket channels **540a,b**. For example, in applications where fluid media is water in cold temperature environments, preventing water buildup in the gasket channels **540a,b** can lead to damage to the gasket **150** if the water freezes and, thereby, expands.

FIG. 6 shows the coupling **100** in an assembled but untightened position. It can be seen in this view that each top surface **314,314'** is parallel to each bottom surface **312,312'**, respectively. Likewise, each top surface **364,364'** is parallel to each bottom surface **362,362'**, respectively. However, the fastener pads **130a,b,a',b'** are not aligned. In other words, the surfaces of adjacent fastener pads **130a,b,a',b'** are not parallel. As can be seen, top surface **314** is not parallel to top surface **364** because angles **415** and **416** do not align. This angular misalignment allows each segment **110,110'** to

deflect under tightening pressure of the bolts **120a,b** and nuts **125a,b** to provide so that the top surfaces **314,314'** and **364,364'** are substantially parallel when the segments **110,110'** are deformed. In various embodiments, the top surfaces **314,314'** and **364,364'** may be parallel before deforming the segments **110,110'**. In such embodiments, the top surfaces **314,314'** and **364,364'** may be non-parallel after deflection.

As can be seen in FIG. 6, the groove shoulder surface **389** of segment **110'** is angled so that it aligns with an outer surface **352'** of tongue **280'** of segment **110'** upon deformation of the segments **110,110'** as will be shown below in FIG. 7. Upon deformation of the segments **110,110'** (as described below), the grooved shoulder surface **389** of segment **110** becomes parallel and flush with outer surface **352'** of tongue **280'** of segment **110'**, and grooved shoulder surface **389'** of groove **380'** of segment **110'** becomes parallel and flush with outer surface **352** of segment **110**.

As can be seen in FIG. 6, the annular nature of the gasket **150** defines a coupling void **410** within the gasket **150** that is adapted for certain diameters of pipe elements. In practice, when pipe elements are introduced within the gasket **150**, they are placed inside the coupling void **410**. Also seen in FIG. 6, a central axis of each of the bolts **120a,b** is parallel to the vertical axis **425** such that heads **612a,b** of the bolts **120a,b** sit at an angle with the top surfaces **314, 316**. In alternative embodiments, the bolts **120a,b** may be angled with respect to the vertical axis **425** such that heads of the bolts **120a,b** sit flush against the top surfaces **314,364**. In the current embodiment, the gasket **150** sits within the segments **110,110'**. Each of the sealing surfaces **526a,b** of the gasket **150** has the same cylindrical profile and the same radius as the contact surfaces **262a,b,a',b'**. In alternative embodiments, the sealing surfaces **526a,b** of the gasket **150** may have a smaller or a larger radius than the contact surfaces **262a,b,a',b'**. In many embodiments, sealing surfaces **526a,b** are in contact with the outer surfaces of the pipe elements before the tightening elements (bolts **120a,b** and nuts **125a,b**) are engaged. In those embodiments, further compression of the gasket **150** will not necessarily produce a more effective seal. However, in other embodiments, it may be necessary for the segments **110,110'** to compress the gasket **150** to effectuate a useful seal against the outer surface of the pipe elements. In many embodiments, sealing surfaces **532a,b** are positioned in contact with or slightly above contact with the pipe elements. In those embodiments, deformation of the gasket **150** is necessary to seal the sealing surfaces **532a,b** against the pipe elements. In some embodiments, however, sealing surfaces **532a,b** are in sufficient engagement with the pipe elements prior to engagement of the tightening elements (bolts **120a,b** and nuts **125a,b**) so that further tightening does not necessarily effectuate a better seal.

Upon compression of the gasket **150** by the segments **110,110'**, the gasket **150** will most naturally deform from about circular in shape to an oblong shape. In most applications, compression by the segments **110,110'** on the gasket **150** will compress the gasket along the vertical axis **425**, but the gasket **150** will tend to extend along the horizontal axis **420**. This occurs particularly because the segments **110,110'** first contact the pipe elements—and, thus, first compress the gasket **150**—at a point central to the segments **110,110'**. As shown in FIGS. 4 and 6, the tongues **280,280'** of the segments **110,110'** extend beyond the horizontal axis **420**, thereby preventing the annular deformation of the gasket **150**. Deformation of the gasket **150** is properly directed to the deformation groove **517** by the tongue **280** and groove **380** configuration of the coupling **100**. The restraint against

oblong deformation provided by the tongues **280,280'** promotes more uniform compression of the gasket **150** against the pipe elements, thereby providing a more reliable seal.

Tightening of the tightening elements (bolts **120a,b** and nuts **125a,b**) seats the gasket **150** against the pipe elements. When the segments **110,110'** are properly deformed and the gasket **150** is properly seated, the coupling **100** restrains the pipe elements from pullout because the contacting portion **292a,b,a',b'** (not shown in FIG. 6) of each segment **110,110'** is seated inside at least one groove of at least one pipe element. The gasket **150** is compressed in sealed engagement with the pipe elements. In some embodiments, the sealing members **557a,b** may be replaced by a single sealing member that extends between the two pipes. Such deformation allows heads **612a,b** of the bolts **120a,b** to seat flush against the top surfaces **314,364** of segment **110** while nuts **125a,b** seat flush against the top surfaces **314',364'** of segment **110'**.

When properly seated, media (such as water, gas, or other fluid) may be allowed to flow through the pipe elements. The gasket **150** seals such media in at least one of two ways. If the gasket **150** is compressed so that sealing surfaces **532a,b** of the sealing members **557a,b** are properly seated against the outside of the pipe elements, such sealing interaction may be sufficient to contain the media inside the pipe elements without breaching the joint. In some applications, such sealing engagement may be impossible to attain, or the pressure of media within the pipe elements may be too great for such a sealing engagement to effectuate a proper seal. In such applications, media may travel past the sealing members **557a,b** and into the gasket channels **540a,b**.

If media passes into the gasket channels **540a,b**, there are two safeholds against leakage. First, in many applications, sealing surfaces **526a,b** are in sealing engagement with the pipe elements prior to compression of the gasket **150** by the segments **110,110'**, and further compression of the gasket **150** enhances such sealing engagement. In other applications, sealing engagement of the gasket **150** with the pipe elements is achieved by compression of the gasket **150** by the segments **110,110'**. Second, if media passes into the gasket channels **540a,b**, it is assumed that such media is of a higher pressure than atmospheric. As such, the higher pressure in the gasket channels **540a,b** further forces the sealing ridges **525a,b** against the pipe elements. The higher pressure results in an even more effective seal by using the pressure of the media inside the pipe elements to effectuate a more complete seal. If liquid media is found in the pipe, such liquid may provide additional air-tight seal to further aid the engagement of the gasket **150** with the pipe elements. In some embodiments, gas-proofing grease may be applied to the contact surfaces **526a,b** and **532a,b** to aid in sealing. In many embodiments, grease is unnecessary.

In the current embodiment, the coupling **100** is assembled in the untightened position of FIG. 6 before use. In other embodiments, the coupling **100** may be assembled in various pieces as part of the method of use.

The coupling **100** in FIG. 7 is shown tightened and deformed around a pair of pipe elements **710b,a** (**710a** not shown in FIG. 7). The segments **110,110'** in the current view are fully deformed in the current embodiment, and contact surfaces **262b,a'** touch a groove surface **714b,a** (**714a** not shown in FIG. 7), which is the outer surface of the pipe element **710** within the groove **720b,a** (not shown in FIG. 7). Contact surface **262a** of segment **110** and contact surface **262b'** of segment **110'** are not shown in FIG. 7 because they are obstructed by the view. As described above, in some embodiments, the shoulder surfaces **296a,b,a',b'** may con-

tact an outermost surface of each pipe element **710a,b** outside of the groove **720b,a** (not shown in FIG. 7), and the contact surfaces **262a,b,a',b'** may never contact the groove surface **714a,b** of each pipe element **710a,b** within each groove **720a,b**. In other embodiments, the contact surfaces **262a,b,a',b'** contact the groove surfaces **714a,b**.

When the segments **110,110'** travel toward each other and deform under the tightening of the tightening elements (nuts **120a,b** and bolts **125a,b**), the gasket **150** is deformed in accord therewith. In some embodiments, a rigid or semi-rigid gasket **150** may be included. The process for accommodating such a material may be altered from that described herein. The gasket **150** includes the deformation groove **517** to allow a place for material to go upon deformation of the gasket **150**.

Installation of the coupling **100** on the pair of pipe elements **710a,b** is illustrated in FIGS. 8A-8E. For the current embodiment, the coupling **100** is introduced to a pair of pipe elements **710a,b** in the preassembled but untightened position of FIG. 6. Each pipe element **710a,b** may include at least one groove **720a,b** for alignment with contact surfaces **262a,b,a',b'**. In the currently described method, the coupling **100** is aligned with an end **725a** of the first pipe element **710a** as shown in FIG. 8A. The coupling **100** is installed by placing the end **725a** of the first pipe element **710a** in the coupling void **410** and forcing the coupling **100** onto the first pipe element **710a** as shown in FIG. 8B. As seen in FIG. 8B, sealing surfaces **526a,b** and sealing surfaces **532a,b** are a small distance away from an outer surface **715a** of the first pipe element **710a**, although the sealing surfaces **526a,b** and **532a,b** may contact the outer surface **715a** in some embodiments. In the currently-described method, the entire coupling **100** is forced beyond the groove **720a** of the first pipe element **710a** so that the contact surfaces **262b,b'** have passed the groove **720a**. In some embodiments, it may not be necessary to force the entire coupling **100** beyond the groove **720a**. As seen in FIG. 8C, the second pipe element **710b** having an end **725b** is introduced in end-facing relationship to the end **725a** of the first pipe element **710a**. In the current embodiment, the pipe elements **710a,b** are approximately the same diameter, although non-uniform diameter pipe elements may be joined in various embodiments. In the current embodiment, each pipe element **710a,b** has ends **725a,b** that are flared slightly. Grooves **720a,b** can be formed in one of two ways: rolled or machined. If the grooves **720a,b** are machined, the pipe elements **710a,b** are unlikely to have flares on the ends **725a,b** as shown. However, if the grooves **720a,b** are rolled, the pipe elements **710a,b** are more likely to have flares on the ends **725a,b**. As such, the coupling **100** of the current embodiment is designed to accommodate the potential flaring of ends **725a,b**. The coupling **100** is sized to fit over the largest possible flare of the ends **725a,b** in the current embodiment based on standard tolerancing for creating the grooves **720a,b**.

When the second pipe element **710b** is about aligned with the first pipe element **710a**, the coupling **100** is moved so that the gasket **150** is aligned on outer surfaces **715a,b** over the ends **725a,b** of the pipe elements **710a,b** and with the contact surfaces **262a,b,a',b'** aligned with the grooves **720a,b**, as shown in FIG. 8D. As seen in FIG. 8E, when the segments **110,110'** are clamped down, the gasket **150** deforms into sealing engagement the outer surfaces **715a,b** of the pipe elements **710a,b** and the contact surfaces **262a,b,a',b'** sit within the grooves **720a,b** and touch groove surfaces **714a,b**. In various embodiments, the contact sur-

faces **262a,b,a'b'** may not touch groove surfaces **714a,b** upon clamping down the segments **110,110'**.

Several features of the gasket **150** ease installation as described. Friction can cause installation of rubber gaskets to bind against outer surfaces **715a,b** of pipe elements **710a,b**. With reference to FIG. 3, FIG. 5, FIG. 6, and the method previously described with FIGS. 8A-8E, axially outer drafted edges **522a,b** and axially inner drafted edges **527a,b** are both drafted to ease the pipe elements **710** into the coupling void **410**. Axially outer drafted edges **522a,b** and axially inner drafted edges **527a,b** also help to prevent rollover of the sealing ridges **525a,b** of the gasket **150** during sliding on and off, as the drafted profiles are less likely to bind against the outer surfaces **715a,b** of the pipe elements **710a,b**. Additionally, contact portions **555a,b** are substantially parallel to the outer surface **715a,b** of the pipe elements **710a,b** even when the gasket **150** is not seated on a pipe elements **710a,b**. Additionally, the configuration of the center rib **530** with respect to the sealing ribs **527a,b**, as discussed above with reference to FIG. 5, prevents the center rib **530** from obstructing the installation of the coupling **100** by providing limiting contact between the center rib **530** and the outer surface **715a,b** of pipe elements **710a,b** before deformation of the gasket **150**. When the segments **110,110'** are clamped down, the gasket **150** deforms, and the center rib **530** contacts the outer surface **715a,b** of pipe elements **710a,b**. This configuration allows the gasket **150** to slide onto the pipe elements **710a,b** without biasing the sliding in one direction and prevents binding of the sealing ridges **525a,b** during installation. These features prevent the gasket **150** from rolling over when the coupling **100** is installed on the pipe elements **710a,b** and allows the gasket **150** to be properly placed over the joint between the pipe elements **710a,b** for proper sealing, among other advantages. When the gasket **150** is properly aligned over the joint, each of the sealing members **557a,b** may contact the outer surface **715a,b** of one pipe element **710a,b** or may be aligned above the surface **710a,b** of the pipe elements **715a,b**. However, the alignment of the sealing members **557a,b** is not critical to effectuate a seal of the joint.

When the coupling **100** is aligned on the joint of the pipe elements **710a,b**, the tightening elements are used to draw the segments **110,110'** together. In the current embodiment, this takes the form of nuts **125a,b** tightening down on bolts **120a,b** to compress the fastener pads **130a,b,a',b'** toward each other. In some embodiments, the coupling **100** is rigid and includes no deflection of the segments **110,110'**. In the current embodiment, the engagement of the tightening elements (bolts **120a,b** and nuts **125a,b**) first cause the segments **110,110'** to travel toward each other. When the segments **110,110'** contact the pipe elements **710a,b**, the segments **110,110'** deform (deflection) until each segment **110,110'** is in the desired engagement with the pipe elements **710a,b**. The deformation of the segments **110,110'** can be seen by comparing FIGS. 6 and 7. The contact surfaces **262a,b,a',b'** contact groove surfaces **714a,b** of the grooves **720a,b** in the pipe elements, at which time the segments **110,110'** begin deflection. In some embodiments, shoulder surfaces **296a,b,a',b'** (refer to FIG. 4 for the location of shoulder surfaces **296a,b,a',b'**) contact the outer surface of the pipe elements such that the contact surfaces **262a,b,a',b'** never contact the groove surfaces **714a,b**.

As can be seen in FIG. 7, the segments **110,110'** may deflect so that bottom surfaces **362,362'** are in contact with bottom surfaces **312',312**, respectively, in some embodiments. This configuration need not be present in all embodiments. In some embodiments, the mating surfaces **355,355'**

will contact mating surfaces **395',395**, respectively, before the bottom surfaces **362,362'** contact bottom surfaces **312',312**, respectively. In some embodiments, bottom surfaces **362,362'** will contact bottom surfaces **312',312** before mating surfaces **355,355'** contact mating surfaces **395',395**, respectively. Because of the deflection and deformation of the segments **110,110'**, the angles **415,416,417,418**, as pointed out in FIG. 4 (angles **415',416',417',418'** not shown), are reduced as the top surfaces **314,314'** and **364,364'** and the bottom surfaces **312,312'** and **362,362'** approach a position parallel with the horizontal axis **420**. As shown, mating surfaces **355,355'** are in contact with mating surfaces **395',395**, respectively, as well.

Seen in the cross-sectional view of FIG. 9, each bolt **120a,b** (b not shown in FIG. 9) includes a head **612a,b** (b not shown in FIG. 9), a threaded portion **810a,b** (b not shown in FIG. 9), a shank portion **815a,b** (b not shown in FIG. 9), and a collar portion **820a,b** (b not shown in FIG. 9). Combined together, each threaded portion **810a,b**, shank portion **815a,b**, and collar portion **820a,b** is termed the shaft portion. Each shaft portion may omit any combination of the threaded portion **810**, shank portion **815**, and collar portion **820** in various embodiments. The nuts **125a,b** (b not shown in FIG. 9) engage the bolts **120a,b** (b not shown in FIG. 9) along part of the threaded portion **810a,b**. Tightening of the nuts **125a,b** compresses the fastener pads **130a,b,a',b'** and deforms the segments **110,110'** to conform to the shape of the pipe elements, as previously described.

As previously described, when the coupling **100** is installed onto pipe elements, the assembled and untightened coupling **100** is installed over the edge of the first pipe element **710a** until it passes completely over any groove **720a** in the first pipe element **710a** after which the second pipe element **710b** is placed end-facing to the first pipe element **710a**. The coupling **100** is then slid into position straddling the first and second pipe elements **710a,b**. Although (as previously described) it is common for gaskets to bind during such installation, it is also possible for friction to cause rocking of the segments **110,110'** not only against any gasket but also against the exterior of the pipe elements **710a,b**. If a leading edge of one segment **110,110'** catches against the exterior of the pipe element **710a,b**, the segments **110,110'** have a tendency to rock with respect to each other. Rocking of segments **110,110'** can cause additional binding of the gasket **150**, making installation of the coupling **100** difficult and potentially damaging to components of the coupling **100**, including the gasket **150**.

The shape of the fastener hole **132a** (see FIG. 2) includes an axial length **233** (axial length **237** of fastener hole **132b** not shown) that tends to prevent such rocking of the segments **110**. For the fasteners of the current embodiment, each of the heads **612a,b**, threaded portions **810a,b**, and shank portions **815a,b** are symmetrical about the center of the bolt **120a,b**, respectively. The shank portions **815a,b** are cylindrical, the threaded portions **810a,b** are cylindrical except that each has threading along its outermost edge, and the heads **612a,b** are cross-sectionally circular at cross-sections taken orthogonal to the center axis. However, the collar portions **820a,b** are not cylindrical but instead include a profile approximating that of the fastener holes **132a,b** as measured at the top surfaces **364,314**. Each collar portion **820a,b** includes an axial length **830a,b** that is about the same as the diameter of the shank portions **815a,b**. The collar portions **820a,b** also include a transverse length (not shown) that is proportionally larger than the axial length **830a,b**. The axial length **830a,b** of each collar portion **820a,b** may be smaller than the axial length **233,237** of each fastener hole

132a,b, the transverse length of each collar portion 820a,b may be smaller than the transverse length 243,247 of each fastener hole 132a,b, and the axial length 233,237 of each fastener hole 132a,b is smaller than the transverse length 830a,b of each collar portion 820a,b.

The arrangement of each collar portion 820a,b engages the fastener hole 132a,b in assembly and retains the bolt 120 in a fixed arrangement with respect to the segment 110 in each fastener hole 132a,b. This allows a user to tighten the nuts 125a,b without need to restrain the bolts 120a,b, as the collar portions 820a,b retain the bolts 120a,b through interaction with the fastener holes 132a,b. This result occurs because the axial length 233,237 of each fastener hole 132a,b is smaller than the transverse length 830a,b of each collar portion 820a,b. Such an arrangement would result even if the orientation of the fastener holes 132a,b were at a different angle.

However, the arrangement as displayed also prevents the rocking of the segments 110,110' by keeping the shank portions 815a,b, the collar portions 820a,b, and the threaded portions 810a,b in close proximity to the inner surfaces 335a,b,a',b' of the fastener holes 132a,b,a',b'. Should one of the segments 110,110' begin a rocking motion, at least one of the inner surfaces 335a,b,a',b' will contact at least one of the bolts 120a,b along at least one of the collar portions 820a,b, the shank portions 815a,b, and the threaded portions 810a,b thereby providing a mechanical stop to prevent further rotation of the segments 110,110' with respect to the bolts 120a,b and, thereby, with respect to the other segment 110',110.

Although all sides of the fastener holes 132a,b,a',b' are shown as drafted in the current embodiment, some sides may be drafted or may be parallel in various embodiments. For example, in the current embodiment, fastener holes 132a,b,a',b' are drafted because the segments 110,110' are cast. However, if fastener holes 132a,b,a',b' were machined, it would not be necessary to draft the fastener holes 132a,b,a',b'.

As seen in FIG. 10, each pair of contact surfaces 262a,b and 262a',b' (262b and 262b' shown in FIGS. 10 and 11) defines a predeformation radius 1001,1001'. Likewise, each pipe element 710a,b defines a radius 1002a,b. In the current embodiment, when the coupling 100 is in the untightened position, the predeformation radii 1001,1001' of each pair of contact surfaces 262a,b and 262a',b', respectively, is greater than the radii 1002a,b of the pipe elements 710a,b. Groove radii 1003a,b are also shown on the pipe elements 710a,b, respectively. Because the predeformation radii 1001,1001' are larger than the radii 1002a,b, the coupling 100 can be more easily maneuvered over each pipe element 710a,b as described more thoroughly with reference to FIGS. 8A-8E. Having larger predeformation radii 1001,1001' than radii 1002a,b allows the coupling 100 to be slid onto the pipe elements 710a,b as a preassembled unit. As described above, once the coupling 100 is aligned over the pipe elements 710a,b, no further assembly of the coupling 100 is required. Instead, the user need only tighten the nuts 125a,b on the bolts 120a,b to secure the coupling 100 in sealing engagement with the pipe elements 710a,b.

As seen in FIG. 11, once the nuts 125a,b are tightened onto the bolts 120a,b, each segment 110,110' of the coupling 100 deforms in conformity with the grooves 720a,b. Once deformed, a postdeformation radius 1101,1101' is defined by each pair of contact surfaces 262a,b and 262a',b' (262b and 262b' shown in FIGS. 10 and 11), respectively. In the current embodiment, each postdeformation radius 1101,1101' is equal to the groove radii 1003a,b because the contact

surfaces 262a,b,a',b' contact the groove surfaces 714a,b. In embodiments where the contact surfaces 262a,b,a',b' do not contact the groove surfaces 714a,b, the postdeformation radii 1101,1101' may be larger than the groove radii 1003a,b.

Although not required in all embodiments, the postdeformation radii 1101,1101' will likely be smaller than the radii 1002a,b even if the postdeformation radii 1101,1101' is larger than the groove radii 1003a,b.

This assembly configuration represents one of many possible assembly configurations. One skilled in the art will understand obvious variations of this assembly configuration are included within this disclosure, including variations of steps, combinations of steps, and dissections of steps, among others. Where materials are chosen for the elements of this assembly—particularly, rubber, metal, and cast iron—similar material choices may also be used and would be obvious to one in the art. As previously disclosed, the gasket 150 may be made of rubber, plastic, cork, wood, metal, ceramic, polymer, elastomer, rosin, foam, any combination of the foregoing materials, or any material suitable for sealing two pipe elements joined in end-to-end relationship. The segments 110,110' may be made of cast iron, steel, aluminum, titanium, copper, brass, various plastics, polymers, resins, or any material of sufficient strength to withstand the tightening load of the fasteners.

It should be emphasized that the embodiments described herein are merely possible examples of implementations, merely set forth for a clear understanding of the principles of the present disclosure. Many variations and modifications may be made to the described embodiment(s) without departing substantially from the spirit and principles of the present disclosure. Further, the scope of the present disclosure is intended to cover any and all combinations and sub-combinations of all elements, features, and aspects discussed above. All such modifications and variations are intended to be included herein within the scope of the present disclosure, and all possible claims to individual aspects or combinations of elements or steps are intended to be supported by the present disclosure.

One should note that conditional language, such as, among others, “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more particular embodiments or that one or more particular embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment.

Various implementations described in the present disclosure may include additional systems, methods, features, and advantages, which may not necessarily be expressly disclosed herein but will be apparent to one of ordinary skill in the art upon examination of the following detailed description and accompanying drawings. It is intended that all such systems, methods, features, and advantages be included within the present disclosure and protected by the accompanying claims.

That which is claimed is:

1. A method of installing a pipe coupling to connect a first pipe element to a second pipe element, the method comprising:

sliding the pipe coupling as a preassembled unit over an outermost surface of the first pipe element, the pipe

15

coupling comprising a coupling segment and an annular gasket, the annular gasket comprising an annular body and a pair of sealing ribs extending substantially radially inward from the annular body, each sealing rib comprising a sealing ridge defining a sealing surface, the sealing surface of each sealing ridge being coannular in an undeformed state, the sealing surfaces defining a pair of radially innermost surfaces of the annular gasket;

introducing an end of the second pipe element to an end of the first pipe element to place the first pipe element and the second pipe element in end-facing relationship; aligning the pipe coupling over the first pipe element and the second pipe element; and

securing the coupling to the first pipe element and the second pipe element; and

wherein the sealing surface of each sealing ridge defines a diameter greater than a diameter of the outermost surface of the first pipe element and a diameter of an outermost surface of the second pipe element; and

wherein sliding the pipe coupling as a preassembled unit over the outermost surface of the first pipe element comprises sliding the annular gasket over the outermost surface of the first pipe element without contacting the outermost surface of the first pipe element.

2. The method of claim 1, wherein each sealing rib increases in axial thickness from the annular body to a radially inward end of each sealing rib radially inside from the annular body, and wherein the sealing ridge of each sealing rib is connected to the radially inward end thereof.

3. The method of claim 1, wherein each sealing ridge decreases in axial thickness from a radially inward end of each sealing rib to the sealing surface of each sealing ridge.

4. The method of claim 1, wherein

the coupling segment is a first coupling segment;

the pipe coupling further comprises a second coupling segment secured end-to-end with the first coupling segment; and

securing the coupling comprises deforming and deflecting each coupling segment into engagement with each pipe element.

5. The method of claim 1, wherein sliding the pipe coupling comprises sliding the pipe coupling past the end of the first pipe element.

6. The method of claim 1, wherein the pair of sealing ribs extend from side portions of the annular body.

7. The method of claim 1, wherein the end of at least one of the first pipe element and the second pipe element is conically flared.

8. A method of installing a pipe coupling to connect a first pipe element to a second pipe element, the method comprising:

sliding the pipe coupling as a preassembled unit over an outermost surface of the first pipe element, the pipe coupling comprising a coupling segment and an annular gasket having an innermost diameter greater than a diameter of the outermost surface of the first pipe

16

element and a diameter of an outermost surface of the second pipe element, the annular gasket comprising an annular body and a pair of sealing ribs extending substantially radially inward from the annular body, each sealing rib comprising a sealing ridge defining a sealing surface, the sealing surfaces defining a pair of radially innermost surfaces of the annular gasket, the annular gasket configured to slide over the diameters of the outermost surface of the first pipe element and the outermost surface of the second pipe element without contacting the outermost surfaces of the first pipe element and the second pipe element in an undeformed state;

introducing an end of the second pipe element to an end of the first pipe element to place the first pipe element and the second pipe element in end-facing relationship; aligning the pipe coupling over the first pipe element and the second pipe element; and

securing the coupling to the first pipe element and the second pipe element; and,

wherein the sealing surface of each sealing ridge are coannular in the undeformed state; and

wherein each of the first pipe element and the second pipe element includes a flare.

9. The method of claim 8, wherein each sealing rib is increasing in axial thickness from the annular body to a radially inward end of each sealing rib radially inside from the annular body, and wherein the sealing ridge of each sealing rib is connected to the radially inward end thereof.

10. The method of claim 8, wherein each sealing ridge decreases in axial thickness from a radially inward end of each sealing rib to the sealing surface of each sealing ridge, and wherein each sealing ridge comprises an axially outer drafted edge angled at a non-zero angle with respect to a radial axis perpendicular to a main axis of revolution of the annular gasket.

11. The method of claim 10, wherein each axially outer drafted edge is conical.

12. The method of claim 8, wherein each sealing ridge includes an axially inner drafted edge.

13. The method of claim 8, wherein each sealing ridge extends axially inwardly from a radially inward end of each sealing rib.

14. The method of claim 13, wherein the sealing surface of each sealing ridge is cylindrical in the undeformed state.

15. The method of claim 8, wherein the annular gasket further comprises a center rib extending radially inward from the annular body, wherein the center rib decreases in axial thickness from radially outside to radially inside.

16. The method of claim 8, wherein an axially outer drafted edge of each sealing ridge extends from a radially inward end of each sealing rib to the sealing surface of each sealing ridge, and wherein each radially inward end is axially and radially outside compared to each of the sealing surfaces.

* * * * *