



US010408322B2

(12) **United States Patent**  
**Maeda et al.**

(10) **Patent No.:** **US 10,408,322 B2**  
(45) **Date of Patent:** **Sep. 10, 2019**

(54) **LOCK-UP DEVICE FOR TORQUE CONVERTER**

(58) **Field of Classification Search**  
None

See application file for complete search history.

(71) Applicant: **EXEDY Corporation**, Neyagawa-shi, Osaka (JP)

(56) **References Cited**

(72) Inventors: **Kazuhito Maeda**, Neyagawa (JP);  
**Keiichi Yasuda**, Neyagawa (JP)

U.S. PATENT DOCUMENTS

(73) Assignee: **EXEDY CORPORATION**, Neyagawa-Shi, Osaka (JP)

5,127,503 A 7/1992 Gratzer  
6,367,605 B1\* 4/2002 Middelmann ..... F16H 45/02  
192/103 FA

(Continued)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 52 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **15/567,476**

CN 104204616 A 12/2014  
CN 105339706 A 2/2016

(Continued)

(22) PCT Filed: **May 18, 2016**

OTHER PUBLICATIONS

(86) PCT No.: **PCT/JP2016/064706**

§ 371 (c)(1),  
(2) Date: **Oct. 18, 2017**

Decision of Grant of the corresponding Japanese patent application No. 2015-102488, dated Jan. 8, 2019, 3 pp.

(Continued)

(87) PCT Pub. No.: **WO2016/186125**

PCT Pub. Date: **Nov. 24, 2016**

*Primary Examiner* — Mark A Manley

(65) **Prior Publication Data**

US 2018/0163836 A1 Jun. 14, 2018

(74) *Attorney, Agent, or Firm* — United IP Counselors, LLC

(30) **Foreign Application Priority Data**

May 20, 2015 (JP) ..... 2015-102485  
May 20, 2015 (JP) ..... 2015-102486

(Continued)

(57) **ABSTRACT**

(51) **Int. Cl.**

**F16H 45/02** (2006.01)  
**F16D 25/08** (2006.01)

(Continued)


A lock-up device includes a clutch disc, a piston, a temperature detection member and a gap adjustment mechanism. The clutch disc is disposed between a front cover and a turbine. The piston is disposed in opposition to the front cover through the clutch disc so as to be movable in an axial direction, and presses the clutch disc toward the front cover. The deformation amount of the temperature detection member is adjusted in accordance with surrounding temperatures. In accordance with the deformation amount, the gap adjustment mechanism adjusts a gap between the front cover and the piston to be a first gap at a first temperature. Further, in accordance the deformation amount, the gap adjustment mechanism adjusts the gap between the front cover and the

(Continued)

(52) **U.S. Cl.**

CPC ..... **F16H 45/02** (2013.01); **F16D 13/40** (2013.01); **F16D 25/0635** (2013.01);

(Continued)



piston to be a second gap narrower than the first gap at a second temperature higher than the first temperature.

**7 Claims, 8 Drawing Sheets**

(30) **Foreign Application Priority Data**

May 20, 2015 (JP) ..... 2015-102487  
 May 20, 2015 (JP) ..... 2015-102488

(51) **Int. Cl.**

**F16H 41/24** (2006.01)  
**F16D 25/0635** (2006.01)  
**F16D 13/40** (2006.01)  
**F16F 15/121** (2006.01)

(52) **U.S. Cl.**

CPC ..... **F16D 25/082** (2013.01); **F16H 41/24**  
 (2013.01); **F16F 15/1216** (2013.01); **F16H**  
**2045/0205** (2013.01); **F16H 2045/0215**  
 (2013.01); **F16H 2045/0221** (2013.01); **F16H**  
**2045/0294** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2005/0211523 A1\* 9/2005 Takahashi ..... F16H 45/02  
 192/3.29  
 2015/0008086 A1 1/2015 Mototsune

FOREIGN PATENT DOCUMENTS

DE	4121555	A1	1/1992
JP	S5533949	A	3/1980
JP	S5794164	A	6/1982
JP	H04249619	A	9/1992
JP	H09126275	A	5/1997
JP	H09229159	A	9/1997
JP	2001065664	A	3/2001
JP	2005-282617	A	10/2005
JP	2010216529	A	9/2010
JP	2011190845	A	9/2011
JP	2012211707	A	11/2012
JP	2013217452	A	10/2013
JP	2015017671	A	1/2015
KR	1020140144678	A	12/2014
KR	1020160032091	A	3/2016
WO	2013154065	A1	10/2013
WO	2015005379	A1	1/2015

OTHER PUBLICATIONS

International Search Report dated Aug. 23, 2016 for foreign Application No. PCT/JP2016/064793, 1 pp.  
 International Search Report dated Jul. 5, 2016 for corresponding foreign Application No. PCT/JP2016/064706, 1 pp.  
 International Search Report dated Jul. 5, 2016 for foreign Application No. PCT/JP2016/064707, 2 pp.  
 International Search Report dated Aug. 9, 2016 for foreign Application No. PCT/JP2016/064794, 2 pp.  
 U.S. Appl. No. 15/567,672, filed Oct. 19, 2017, Exedy Corporation.  
 U.S. Appl. No. 15/567,757, filed Oct. 19, 2017, Exedy Corporation.  
 U.S. Appl. No. 15/567,784, filed Oct. 19, 2017, Exedy Corporation.

\* cited by examiner




FIG. 1






FIG. 2




FIG. 3

FIG. 4





FIG. 5






FIG. 6





FIG. 7



(a)



(b)




FIG. 8




FIG. 9



**1****LOCK-UP DEVICE FOR TORQUE  
CONVERTER****CROSS-REFERENCE TO RELATED  
APPLICATIONS**

This application is the U.S. National Phase of PCT International Application No. PCT/JP2016/064706, filed on May 18, 2016. That application claims priority to Japanese Patent Application No. 2015-102485, filed on May 20, 2015, Japanese Patent Application No. 2015-102486, filed on May 20, 2015, Japanese Patent Application No. 2015-102487, filed on May 20, 2015, and Japanese Patent Application No. 2015-102488, filed on May 20, 2015. The contents of all five applications are herein incorporated by reference in their entirety.

**BACKGROUND**

## Technical Field

The present disclosure relates to a lock-up device, and particularly to a lock-up device for a torque converter, which transmits a torque from a front cover to a transmission-side member through a turbine of the torque converter.

## Background Information

Torque converters are often equipped with a lock-up device that directly transmits a torque from a front cover to a turbine. The lock-up device described in Japan Laid-open Patent Application Publication No. H09-229159 includes a clutch part disposed between the front cover and the turbine and a piston disposed between the clutch part and the turbine.

The clutch part includes a hub fixed to the front cover, a clutch disc engaged with the hub, and a clutch drum coupled to the turbine. Additionally, a driven plate and a retainer plate are engaged with the clutch drum so as to interpose the clutch disc therebetween.

The piston is axially movable, and causes the driven plate and the retainer plate to interpose and hold the clutch disc therebetween whereby a lock-up on state (a power transmission activated state) is made. A bimetal plate having a disc shape is disposed sideward of the piston. At a temperature greater than a set temperature, the bimetal plate deforms so as not to make contact with the piston, and hence, does not affect the piston to be actuated by hydraulic pressure. On the other hand, at a temperature less than or equal to the set temperature, the bimetal plate deforms so as to press the piston in a direction that a lock-up off state (a power transmission deactivated state) is made.

**BRIEF SUMMARY**

In the device of Japan Laid-open Patent Application Publication No. H09-229159, with the bimetal plate provided, a clutch gap increases in size at low temperatures and reduces in size at normal temperatures. Therefore, drag torque can be reduced in magnitude at low temperatures.

However, the device of Japan Laid-open Patent Application Publication No. H09-229159 has a drawback of lack of flexibility in design because of limitations inevitably imposed on the place for disposing the bimetal plate.

It is an object of the present disclosure to make a gap of a clutch part appropriately settable in accordance with

**2**

temperatures, and in addition, to enhance flexibility in design of a mechanism for appropriately setting the gap of the clutch part.

(1) A lock-up device for a torque converter according to an aspect of the present disclosure is a device for transmitting a torque from a front cover to a transmission-side member through a turbine of the torque converter. The present lock-up device includes a clutch disc, a piston, a temperature detection member and a gap adjustment mechanism. The clutch disc is disposed between the front cover and the turbine. The piston is disposed in opposition to the front cover through the clutch disc so as to be movable in an axial direction, and presses the clutch disc toward the front cover. A deformation amount of the temperature detection member is adjusted in accordance with surrounding temperatures. In accordance with the deformation amount of the temperature detection member, the gap adjustment mechanism adjusts a gap between the front cover and the piston to be a first gap at a first temperature, and adjusts the gap between the front cover and the piston to be a second gap narrower than the first gap at a second temperature higher than the first temperature.

In the present device, the clutch disc is disposed between the front cover and the piston, and a lock-up on state is made when the clutch disc is pressed toward the front cover by the piston. On the other hand, the piston has been moved in a direction separating from the front cover when a lock-up off state is made, whereby the clutch disc is not being pressed toward the front cover.

When the lock-up off state is made, at the first temperature that is relatively low, the gap adjustment mechanism is actuated in accordance with the deformation amount of the temperature detection member, and the gap between the front cover and the piston is set to be the first gap that is relatively wide. Therefore, a drag torque to be generated by the clutch disc disposed between the front cover and the piston can be reduced in magnitude. On the other hand, at the second temperature (e.g., normal temperature) higher than the first temperature, the gap adjustment mechanism is actuated in accordance with the deformation amount of the temperature detection member, and the gap between the front cover and the piston is set to be the second gap narrower than the first gap. Therefore, responsiveness becomes better in transitioning from the lock-up off state to the lock-up on state.

Here, the gap adjustment mechanism is provided separately from the temperature detection member. Limitations are not imposed on the layout of the temperature detection member such as a bimetal. Therefore, flexibility in design is enhanced.

(2) Preferably, the temperature detection member and the gap adjustment mechanism are disposed between the front cover and the piston.

(3) Preferably, the present device further includes an oil chamber plate disposed between the piston and the turbine. Additionally, the piston and the oil chamber plate form a lock-up oil chamber therebetween, and the lock-up oil chamber is supplied with a hydraulic oil for moving the piston toward the front cover.

Here, the piston is actuated by supplying the hydraulic oil to the lock-up oil chamber, whereby the lock-up on state can be quickly made.

(4) Preferably, the front cover and the piston form a cancellation oil chamber therebetween so as to cancel a hydraulic pressure to be generated in the lock-up oil chamber in lock-up releasing. Additionally, the temperature detec-



## 3

tion member and the gap adjustment mechanism are disposed in the cancellation oil chamber.

(5) Preferably, the present device further includes a support boss having an annular shape. The support boss is fixed to an inner peripheral part of the front cover, and includes a piston support part and a coupling part. The piston support part supports an inner peripheral end surface of the piston such that the piston is slidable thereon. The coupling part receives an inner peripheral part of the oil chamber plate coupled thereto. Additionally, the support boss includes an oil passage communicated with the lock-up oil chamber and an oil passage communicated with the cancellation oil chamber.

(6) Preferably, the front cover includes a friction surface with which the clutch disc is pressed in contact. Additionally, the present device preferably further includes a pressure plate that is disposed in opposition to the friction surface through the clutch disc and is pressed by the piston.

(7) Preferably, the present device further includes a damper mechanism that transmits the torque from the clutch disc to the turbine, and also, absorbs and attenuates a torsional vibration.

According to the above, a gap of a clutch part can be appropriately set in accordance with temperatures, and in addition, flexibility in design of a mechanism for appropriately setting the gap of the clutch part can be enhanced.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a cross-sectional configuration diagram of a torque converter including a lock-up device according to an exemplary embodiment of the present disclosure.

FIG. 2 is a diagram showing part extracted from FIG. 1.

FIG. 3 is a diagram of a clutch disc shown in detail.

FIG. 4 is a partial front view of an engaging part between a pressure plate and a cover plate.

FIG. 5 is a partial front view of an engaging part between a piston and the cover plate.

FIG. 6 is an enlarged view of part extracted from FIG. 1.

FIG. 7 is an external perspective view of an engaging structure between the piston and the cover plate.

FIG. 8 is a cross-sectional plan view of a return mechanism.

FIG. 9 is a cross-sectional configuration diagram for explaining a damper mechanism.

## DETAILED DESCRIPTION OF EMBODIMENTS

## Entire Configuration of Torque Converter

FIG. 1 is a vertical cross-sectional view of a torque converter 1 employing an exemplary embodiment of the present disclosure. The torque converter 1 is a device that transmits a torque from a crankshaft of an engine to an input shaft of a transmission. In FIG. 1, the engine (not shown in the drawing) is disposed on the left side, whereas the transmission (not shown in the drawing) is disposed on the right side. Line O-O depicted in FIG. 1 is a rotational axis of the torque converter 1.

The torque converter 1 mainly includes a front cover 2, a torque converter body 6 composed of three types of bladed wheels (an impeller 3, a turbine 4 and a stator 5) and a lock-up device 7.

## Front Cover 2

The front cover 2 is a disc-shaped member and a center boss 8 is fixed to the inner peripheral end of the front cover

## 4

2 by welding. The center boss 8 is a cylindrical member extending in the axial direction, and is inserted into a center hole of the crankshaft (not shown in the drawings).

It should be noted that the front cover 2 is configured to be coupled to the crankshaft of the engine through a flexible plate, although the configuration is not shown in the drawings. In other words, a plurality of bolts 9 are fixed to the engine-side surface of the outer peripheral part of the front cover 2, while being aligned at equal intervals in the circumferential direction. The outer peripheral part of the flexible plate is fixed to the front cover 2 by nuts screwed onto the bolts 9.

The front cover 2 includes an outer peripheral side tubular part 2a in the outer peripheral part thereof. The outer peripheral side tubular part 2a extends axially toward the transmission. The impeller 3 is fixed to the distal end of the outer peripheral side tubular part 2a by welding. As a result, a fluid chamber, the interior of which is filled with hydraulic oil, is formed by the front cover 2 and the impeller 3.

Additionally, the front cover 2 includes a flat part 2b having an annular shape on the turbine-side lateral surface of the radially intermediate part thereof. The flat part 2b is shaped to protrude toward the turbine than parts located on the inner and outer peripheral sides thereof. The surface of the flat part 2b functions as a friction surface (the flat part 2b will be hereinafter referred to as "friction surface 2b").

## Impeller 3

The impeller 3 is mainly composed of an impeller shell 10 and a plurality of impeller blades 11 fixed to the inside of the impeller shell 10. Additionally, the outer peripheral side distal end of the impeller shell 10 is welded to the front cover 2 as described above. It should be noted that the impeller shell 10 includes a tubular part in the inner peripheral end thereof. The tubular part extends toward the transmission.

## Turbine 4

The turbine 4 is disposed in axial opposition to the impeller 3 within the fluid chamber. The turbine 4 is mainly composed of a turbine shell 14, a plurality of turbine blades 15 fixed to the inside of the turbine shell 14, and a turbine hub 16 fixed to the inner peripheral end of the turbine shell 14. The turbine shell 14 and the turbine hub 16 are fixed by a plurality of rivets 17.

The turbine hub 16 includes a flange part 16a, a tubular part 16b and a damper support part 16c. The flange part 16a is a disc-shaped part to which the inner peripheral end of the turbine shell 14 is fixed. The tubular part 16b is shaped to extend from the inner peripheral part of the flange part 16a toward the transmission. The tubular part 16b includes a spline hole 16d in the inner peripheral part thereof, and the spline hole 16d is capable of being meshed with a spline shaft provided on the tip of the input shaft of the transmission (not shown in the drawings). The damper support part 16c is formed by extending the outer peripheral part of the flange part 16a. The damper support part 16c will be described below in detail.

A collar 18 is fixed to the inner peripheral end of the turbine hub 16 on the opposite side (the engine side) of the tubular part 16b. On the inner peripheral end of the turbine hub 16, the collar 18 extends toward the engine from approximately the same radial position as the tubular part 16b.

## Stator 5

The stator 5 is a mechanism disposed between the inner peripheral part of the impeller 3 and that of the turbine 4 so



## 5

as to regulate the flow of hydraulic oil returning from the turbine 4 to the impeller 3. The stator 5 is made by integral casting of resin, aluminum alloy or so forth. The stator 5 mainly includes a stator shell 20 having a disc shape and a plurality of stator blades 21 integrated with the stator shell 20 on the outer peripheral side of the stator shell 20. The stator shell 20 is coupled to a stationary shaft (not shown in the drawings) through a one-way clutch 22.

A thrust bearing 23 is disposed between the stator shell 20 and the impeller shell 10, whereas a thrust bearing 24 is disposed between the stator shell 20 and the flange part 16a of the turbine hub 16.

## Lock-Up Device 7

The lock-up device 7 is a device disposed between the front cover 2 and the turbine 4 so as to directly transmit power from the front cover 2 to the turbine 4. As shown close-up in FIG. 2, the lock-up device 7 includes a clutch disc 28, a pressure plate 29, a piston 30, a piston actuation mechanism 31 and a damper mechanism 34.

## &lt;Clutch Disc 28&gt;

The clutch disc 28 has an annular shape and is capable of being pressed in contact with the friction surface 2b of the front cover 2. The clutch disc 28 includes a core plate 36 having an annular shape and friction members 37 that have an annular shape and are fixed to both lateral surfaces of the core plate 36. The core plate 36 has an outer peripheral part larger than the outer diameter of each friction member 37, and is bent at a predetermined angle toward the turbine at a part thereof protruding to the outer peripheral side beyond the friction members 37. Additionally, the bent part includes a plurality of engaging protrusions 36a.

Additionally, as shown close-up in FIG. 3, the clutch disc 28 is shaped to tilt in a free state that a lock-up off state (a power transmission deactivated state) is made. Specifically, the clutch disc 28 tilts such that the inner peripheral side part thereof is located closer to the front cover 2 than the outer peripheral side part thereof. Therefore, when the lock-up off state is made, the inner peripheral end of the clutch disc 28 annularly makes line contact with the friction surface 2b of the front cover 2, whereas the outer peripheral end of the clutch disc 28 annularly makes line contact with the pressure plate 29. With the configuration described above, a drag torque is lessened when the lock-up off state is made.

## &lt;Pressure Plate 29&gt;

The pressure plate 29 is disposed between the clutch disc 28 and the piston 30 so as to be movable in the axial direction. The pressure plate 29 is pressed by the piston 30, and thereby presses the clutch disc 28 toward the front cover 2. Additionally, the pressure plate 29 has an annular shape, and the outer diameter thereof is larger than that of each friction member 37 of the clutch disc 28, while the inner diameter thereof is smaller than that of each friction member 37. As shown close-up in FIG. 4, the pressure plate 29 includes a plurality of grooves 29a on the inner peripheral end thereof. The grooves 29a are aligned at predetermined intervals in the circumferential direction. Each groove 29a has a predetermined depth in the radial direction and is opened to the inner peripheral side. It should be noted that FIG. 4 is a view of the pressure plate 29 as seen from the front cover 2 side.

## &lt;Piston 30&gt;

As shown in FIGS. 1 and 2, the piston 30 is disposed between the front cover 2 and the turbine 4 and is movable in the axial direction. The piston 30 includes a pressure receiving part 30a having a disc shape, a first protruding part

## 6

30b, a second protruding part 30c and an outer peripheral disc part 30d. It should be noted that the body thereof is composed of the pressure receiving part 30a and the outer peripheral disc part 30d.

The pressure receiving part 30a is a part that receives the pressure of hydraulic oil, and the first protruding part 30b is included in the outer peripheral part of the pressure receiving part 30a so as to protrude toward the turbine 4. The outer peripheral end of the pressure receiving part 30a slantingly extends toward the front cover 2, and the second protruding part 30c is included in the distal end of this slantingly extending part so as to further protrude therefrom toward the front cover 2.

The outer peripheral disc part 30d is integrated with the pressure receiving part 30a, and is shifted (off-set) to the front cover side with respect to the pressure receiving part 30a. As shown in FIG. 5, the outer peripheral disc part 30d includes a plurality of openings 30e in the inner peripheral part thereof. The openings 30e are aligned at predetermined intervals in the circumferential direction. The plural openings 30e axially penetrate therethrough. It should be noted that FIG. 5 is a view of the piston 30 as seen from the front cover 2 side.

Additionally, the outer peripheral disc part 30d includes a pressure applying part 30f having an annular shape in the outer peripheral end thereof. The pressure applying part 30f is included in the outer peripheral end of the outer peripheral disc part 30d so as to protrude toward the front cover 2. The pressure applying part 30f is shaped to make contact with the approximately middle of the radial width of the pressure plate 29. Preferably, the pressure applying part 30f presses, through the pressure plate 29, a region of one friction member 37 ranging between a position shifted to the inner peripheral side from the middle of the radial width of the friction member 37 by 20% of the radial width and a position shifted to the outer peripheral side from the middle of the radial width of the friction member 37 by 10% of the radial width.

## &lt;Stiffness of Core Plate 36, Pressure Plate 29 and Piston 30&gt;

Regarding the bending stiffness of the core plate 36, that of the pressure plate 29, and that of the piston 30, the piston 30 is set to be the highest; the pressure plate 29 is set to be lower than the piston 30; and the core plate 36 is set to be the lowest. The specifications of the core plate 36, the pressure plate 29 and the piston 30 are set as described above. Hence, when pressed by the piston 30 while the front cover 2 (especially, the part thereof including the friction surface 2b) has been deformed, the pressure plate 29 and the clutch disc 28 are supposed to be deformed in accordance with the deformed front cover 2.

## &lt;Piston Actuation Mechanism 31&gt;

The piston 30 is axially actuated by the piston actuation mechanism 31. As shown in FIG. 2, the piston actuation mechanism 31 includes a support boss 40, a cover plate 41 (an oil chamber plate) and a return mechanism 42.

## —Support Boss 40—

As shown in FIGS. 2 and 6, the support boss 40 is fixed to the inner peripheral part of the front cover 2. Specifically, the support boss 40 is part of the center boss 8, and is made in the shape of a tube axially extending from the turbine 4-side end of the center boss 8. The support boss 40 includes a first fixation part 40a, a piston support part 40b, a second fixation part 40c, a first intermediate part 40d and a second intermediate part 40e. It should be noted that FIG. 6 is a partial enlarged view of FIG. 1.



The inner peripheral end surface of the front cover **2** is fixed to the outer peripheral surface of the first fixation part **40a** by welding. In other words, the inner peripheral end surface of the front cover **2** is inserted and fixed onto the outer peripheral surface of the first fixation part **40a**, whereby the front cover **2** is axis-aligned with respect to the center boss **8**.

The piston support part **40b** has an outer diameter larger than that of the first fixation part **40a**. The inner peripheral end surface of the piston **30** is supported by the outer peripheral surface of the piston support part **40b** so as to be slidable thereon. Additionally, a seal member **45** is attached to the outer peripheral surface of the piston support part **40b**. The seal member **45** seals between the outer peripheral surface of the piston support part **40b** and the inner peripheral end surface of the piston **30**. It should be noted that the front cover **2**-side lateral surface of the piston support part **40b** tilts to gradually separate away from the front cover **2** side to the inner peripheral side.

The second fixation part **40c** has an outer diameter smaller than that of the piston support part **40b**. In other words, the piston support part **40b** and the second fixation part **40c** compose a step. The inner peripheral end surface of the cover plate **41** is fixed to the outer peripheral surface of the second fixation part **40c** by welding. Even when the cover plate **41** is welded to the second fixation part **40c**, welding-related strain of the piston support part **40b** can be inhibited by setting the outer diameter of the second fixation part **40c** to be smaller than that of the piston support part **40b** to which the seal member **45** is attached. Therefore, sealing performance between the piston support part **40b** and the piston **30** is enhanced.

The first intermediate part **40d** is provided between the first fixation part **40a** and the piston support part **40b**. The outer peripheral surface of the first intermediate part **40d** tilts such that the diameter thereof gradually increases from the front cover **2** side to the turbine **4** side. The minimum diameter of the outer peripheral surface of the first intermediate part **40d** is larger than the diameter of the first fixation part **40a**, while the maximum diameter thereof is smaller than the diameter of the piston support part **40b**.

The second intermediate part **40e** is provided between the piston support part **40b** and the second fixation part **40c**. The outer peripheral surface of the second intermediate part **40e** tilts such that the diameter thereof gradually reduces from the front cover **2** side to the turbine **4** side. The maximum diameter of the outer peripheral surface of the second intermediate part **40e** is smaller than the diameter of the piston support part **40b**, while the minimum diameter thereof is larger than the diameter of the second fixation part **40c**.

It should be noted that a thrust washer **46** is disposed between the turbine **4**-side end surface of the support boss **40** and the turbine hub **16**. The thrust washer **46** includes at least one radially penetrating groove on a surface thereof.

#### —Cover Plate **41**—

The cover plate **41** is disposed such that the pressure receiving part **30a** of the piston **30** is interposed between the cover plate **41** and the front cover **2**. As shown in FIG. **2**, the cover plate **41** includes a body **41a**, a seal part **41b** and a torque transmission part **41c**.

The body **41a** has a disc shape, and as described above, the inner peripheral end surface thereof is fixed to the outer peripheral surface of the second fixation part **40c** of the support boss **40** by welding.

The seal part **41b** is included in the outer peripheral part of the body **41a**, and includes a recess **41d** dented therefrom

toward the turbine **4**. The first protruding part **30b** of the piston **30** is inserted into the recess **41d**. A seal member **47** is attached to the outer peripheral part of the first protruding part **30b**, and the outer peripheral part thereof makes contact with the inner peripheral surface of the recess **41d**. Therefore, a lock-up oil chamber **C1** is formed between the piston **30** and the cover plate **41** by the seal member **47**.

The torque transmission part **41c** is provided on the further outer peripheral side of the seal part **41b**. The torque transmission part **41c** is composed of a plurality of engaging protrusions (hereinafter referred to as “engaging protrusions **41c**”) extending from the outer peripheral part of the seal part **41b** to the front cover side. As shown in FIGS. **4** and **5**, the engaging protrusions **41c** penetrate the openings **30e** provided in the piston **30**, and are engaged with the grooves **29a** provided on the inner peripheral end of the pressure plate **29**. FIG. **7** shows a perspective view of the cover plate **41** and the piston **30** as seen from the turbine **4** side.

With the configuration described above, a torque transmitted to the cover plate **41** can be transmitted to the pressure plate **29**. Additionally, rotation of the piston **30** relative to the cover plate **41** can be restricted by appropriately setting the circumferential dimension of each of the engaging protrusions **41c** as the torque transmission part and the circumferential dimension of each of the openings **30e** of the piston **30**.

#### —Return Mechanism **42**—

As shown in FIGS. **2** and **8**, the return mechanism **42** is disposed between the front cover **2** and the piston **30**. FIG. **8** is a cross-sectional plan view showing part of both the front cover **2** and the piston **30**, in which the return mechanism **42** is disposed, as seen from the outer peripheral side. Specifically, the return mechanism **42** is disposed between a recess **2g** provided on the piston **30**-side lateral surface of the front cover **2** and a recess **30g** provided on the front cover **2**-side lateral surface of the piston **30**. The return mechanism **42** is a mechanism that urges the piston **30** in a direction separating from the friction surface of the front cover **2**. The return mechanism **42** urges the piston **30** in the direction separating from the front cover **2** and adjusts the gap between the friction surface **2b** of the front cover **2** and the pressure applying part **30f** of the piston **30**. As shown in FIG. **8**, the return mechanism **42** is composed of a return spring **50** made of bimetal (a temperature detection member) and a cam mechanism **51** (a gap adjustment mechanism).

The return spring **50** is disposed to extend in the right-and-left direction between a support member **52** fixed to the front cover **2** and one end of the cam mechanism **51**. As shown in FIG. **8(a)**, when the temperature of hydraulic oil is low, the return spring **50** deforms such that the spring length thereof becomes short. On the other hand, as shown in FIG. **8(b)**, when the temperature of hydraulic oil is high, the return spring **50** deforms such that the spring length thereof becomes long.

The cam mechanism **51** includes a first cam member **55** fixed to the recess **2g** of the front cover **2** and a second cam member **56** fixed to the recess **30g** of the piston **30**.

The first cam member **55** is a member made in the shape of a block extending in the right-and-left direction, and includes a first slope **55a**, a groove **55b** and a second slope **55c**. The first slope **55a** is provided on the outer peripheral surface of one end of the first cam member **55** and slants such that the thickness thereof gradually reduces from one end thereof to the other end thereof. The groove **55b** is provided on the other end side of the first slope **55a**, has a predetermined width, and penetrates in the radial direction. The second slope **55c** is provided on the inner peripheral



surface of a protruding part provided to cover part of the groove **55b** on the other end side. The second slope **55c** slants in the same direction as the first slope **55a**. One end of the return spring **50** is fixed to the other end surface of the first cam member **55**.

The second cam member **56** is a member made in the shape of a block extending in the right-and-left direction, and includes a first slope **56a**, an engaging part **56b** and a second slope **56c**. The engaging part **56b** is a part of the second cam member **56** and protrudes toward the first cam member **55**. The engaging part **56b** is capable of being inserted into the groove **55b** of the first cam member **55**. Additionally, the first slope **56a** is provided on the first cam member **55**-side part of the engaging part **56b**, and slants in the same direction at the same angle as the first slope **55a** of the first cam member **55**. Moreover, the first slopes **55a** and **56a** of both cam members **55** and **56** are slidable in contact with each other. On the other hand, the second slope **56c** is provided on the engaging part **56b** so as to be located on the opposite side of the first slope **56a**, and slants in the same direction at the same angle as the second slope **55c** of the first cam member **55**. Additionally, the second slopes **55c** and **56c** of both cam members **55** and **56** are slidable in contact with each other.

—Working of Return Mechanism **42**—

In the return mechanism **42** described above, when the atmosphere temperature is low, the return spring **50** contracts as shown in FIG. **8(a)**. Therefore, in FIG. **8(a)**, the first cam member **55** is moved rightward with respect to the second cam member **56**. Accordingly, the piston **30** is moved to separate from the front cover **2** by sliding between the first slopes **55a** and **56a** of the first and second cam members **55** and **56**. Therefore, the gap between the piston **30** and the front cover **2**, in other words, the gap of the part that the clutch disc **28** is provided (the release allowance of the clutch disc **28**) is increased. Consequently, the drag torque can be inhibited low in the part inclusive of the clutch disc **28**.

On the other hand, when the atmosphere temperature becomes high, and for instance, becomes a room temperature, the return spring **50** expands as shown in FIG. **8(b)**. Therefore, in FIG. **8(b)**, the first cam member **55** is moved leftward with respect to the second cam member **56**. Accordingly, the piston **30** is moved to approach to the front cover **2** by sliding between the second slopes **55c** and **56c** of the first and second cam members **55** and **56**. Therefore, the gap between the piston **30** and the front cover **2**, in other words, the gap of the part that the clutch disc **28** is provided (the release allowance of the clutch disc **28**) is reduced. Consequently, a lock-up on state can be quickly made.

<Hydraulic Circuit>

With the configuration of the piston actuation mechanism **31**, as shown in FIG. **2**, the lock-up oil chamber **C1** is formed between the pressure receiving part **30a** of the piston **30** and the body **41a** of the cover plate **41**. Additionally, the front cover **2** includes a step part **2c**, having an axially extending tubular shape, between the radially intermediate part thereof and the inner peripheral part thereof. A seal member **57** is attached to the outer peripheral surface of the step part **2c**. The seal member **57** makes contact with the inner peripheral surface of the second protruding part **30c** of the piston **30**. Therefore, a cancellation oil chamber **C2** is formed between the pressure receiving part **30a** of the piston **30** and the front cover **2** so as to cancel the hydraulic pressure to be generated in the lock-up oil chamber **C1** when the lock-up off state is made. It should be noted that the seal member **57**, attached to the step part **2c** of the front cover **2**, exerts sealing

performance inferior to that of a normal seal member (e.g., the seal member **47** attached to the first protruding part **30b**). Specifically, even when the seal member **57** is attached to the step part **2c**, the gap of the part that the seal member **57** is abutted to the object thereof is set to be wider than a normally set gap. Therefore, a larger amount of hydraulic oil leaks in the part that the seal member **57** is attached than in the other sealed parts.

As shown in FIGS. **2** and **6**, the support boss **40** includes a first oil passage **P1** and a second oil passage **P2**, both of which radially penetrate therethrough. The first oil passage **P1** is opened in the slope of the second intermediate part **40e** of the support boss **40**, and the lock-up oil chamber **C1** and the space of the inner peripheral part of the support boss **40** are communicated therethrough. The second oil passage **P2** is opened in the slope of the first intermediate part **40d**, and the cancellation oil chamber **C2** and the space of the inner peripheral part of the support boss **40** are communicated therethrough. The collar **18** includes a groove **18a** having an annular shape, and the groove **18a** includes a plurality of third oil passages **P3** radially penetrating therethrough. Additionally, the second oil passage **P2** is communicated with the third oil passages **P3**.

<Damper Mechanism **34**>

The damper mechanism **34** is a mechanism disposed between the clutch disc **28** and the turbine **4** so as to transmit a torque from the clutch disc **28** to the turbine **4**. As shown in FIG. **9**, the damper mechanism **34** includes an engaging member **60**, a drive plate **61**, a driven plate **62** and a plurality of torsion springs **63**.

The engaging member **60** includes a fixed part **60a**, a plurality of first engaging parts **60b** and a plurality of second engaging parts **60c**. The fixed part **60a** has an annular shape and is fixed to the drive plate **61** by rivets **65**. The plural first engaging parts **60b** are formed by bending the outer peripheral end of the fixed part **60a** toward the front cover **2**, and are meshed with the engaging protrusions **36a** provided on the outer periphery of the core plate **36** of the clutch disc **28**. The clutch disc **28** is axially movable with respect to the first engaging parts **60b**, but is prevented from rotating relatively thereto. The plural second engaging parts **60c** are formed by bending the outer peripheral end of the fixed part **60a** toward the turbine **4**.

The drive plate **61** has an annular shape, and is disposed between the piston **30** and the turbine **4**. The drive plate **61** transmits a torque, transmitted to the engaging member **60**, to the torsion springs **63**. The drive plate **61** includes a disc part **61a**, a plurality of support parts **61b** and a plurality of engaging parts **61c**.

The inner peripheral end surface of the disc part **61a** is bent toward the turbine **4**, and is provided as a positioning part **61d**. The positioning part **61d** is supported by the damper support part **16c** provided on the outer peripheral end of the turbine hub **16**, and is positioned in the radial direction and the axial direction. The disc part **61a** includes holes **61e** axially penetrating the outer peripheral part thereof. The second engaging parts **60c** of the engaging member **60** extend toward the turbine **4** while penetrating the holes **61e**.

The support parts **61b** are included in the outer peripheral part of the disc part **61a** and have a C-shaped cross-section. The plural torsion springs **63** are accommodated in the support parts **61b**, and are restricted from moving in the radial direction and from moving toward the front cover **2** by the support parts **61b**.

The engaging parts **61c** are included in the outer peripheral part of the disc part **61a**, and each is provided between



## 11

adjacent two of the support parts **61b**. The engaging parts **61c** are partially engaged with both end surfaces of the torsion springs **63** accommodated in the support parts **61b**.

The driven plate **62** has a roughly disc shape, and is disposed between the drive plate **61** and the turbine **4**. The driven plate **62** is a member that transmits a torque, transmitted to the torsion springs **63**, to the turbine hub **16**. The driven plate **62** is fixed at the inner peripheral end thereof to the turbine shell **14** and the turbine hub **16** by the rivets **17**. Additionally, the driven plate **62** extends to the outer peripheral side along the lateral surface of the turbine shell **14**. Engaging parts **62**, included in the outer peripheral part of the drive plate **62**, are engaged with both end surfaces of the torsion springs **63**.

## Actions

For lock-up releasing (the lock-up off state) in the lock-up device **7**, the lock-up oil chamber **C1** is connected to a drain. Therefore, the hydraulic oil inside the lock-up oil chamber **C1** is returned to a tank side through the first oil passage **P1**. In this condition, a pressing force applied to the pressure plate **29** from the pressure applying part **30f** of the piston **30** is released. Therefore, the lock-up off state (the power transmission deactivated state) is made, and the torque from the front cover **2** is transmitted from the impeller **3** to the turbine **4** through the hydraulic oil, and is transmitted to the input shaft of the transmission through the turbine hub **16**.

It should be noted that when the lock-up off state is made, chances are that a centrifugal force acts on the hydraulic oil remaining in the lock-up oil chamber **C1** whereby the piston **30** is pressed toward the front cover **2**. When the piston **30** is moved toward the front cover **2**, the drag torque due to the clutch disc **28** is increased.

To cope with this, in the present device, as described above, the amount of leakage through the seal member **57** is set to be larger than that through a normal seal member. With this setting, the hydraulic oil leaking through the seal member **57** intrudes into the cancellation oil chamber **C2**, whereby the piston **30** is inhibited from moving toward the front cover **2**. In other words, the pressing force acting on the piston **30** due to the centrifugal force acting on the hydraulic oil in the lock-up oil chamber **C1** is configured to be canceled by the hydraulic oil leaking through the seal member **57** into the cancellation oil chamber **C2**.

On the other hand, when the lock-up on state (a power transmission activated state) is made in the lock-up device **7**, the cancellation oil chamber **C2** is connected to the drain, and simultaneously, the hydraulic oil is supplied to the lock-up oil chamber **C1**. In other words, the hydraulic oil is supplied to the end surface of the collar **18**, and simultaneously, the hydraulic oil is supplied to the lock-up oil chamber **C1** through the first oil passage **P1**. The piston **30** is thereby moved toward the front cover **2**, and moves the pressure plate **29** toward the front cover **2**. Accordingly, the clutch disc **28** is interposed and held between the front cover **2** and the pressure plate **29**, and the lock-up on state is made.

When the lock-up on state is made, the torque from the front cover **2** is transmitted to the damper mechanism **34** through a path of “the support boss **40**→the cover plate **41**→the pressure plate **29**→the clutch disc **28**”, and is also transmitted from the front cover **2** to the damper mechanism **34** through the clutch disc **28**.

In the aforementioned torque transmission path, a torque is transmitted between the cover plate **41** and the pressure plate **29** by meshing between the engaging protrusions **41c** and the grooves **29a**. A gap exists between each engaging

## 12

protrusion **41c** and each groove **29a**, whereby clicking sound is produced. The clicking sound is supposed to be transmitted to the front cover **2** and then leak to the outside. However, in the device of the present exemplary embodiment, a long transmission path is set between the front cover **2** and the parts that the clicking sound is produced (engaging parts between the engaging protrusions **41c** and the grooves **29a**). Hence, the clicking sound is attenuated until transmitted to the front cover **2**. Therefore, the clicking sound becomes unlikely to leak to the outside.

In the damper mechanism **34**, the torque inputted to the engaging member **60** is transmitted to the turbine **4** through the torsion springs **63** and the driven plate **62**, and is further transmitted to the input shaft of the transmission through the turbine hub **16**.

During actuation of the lock-up device **7** described above, the front cover **2** has chances of being deformed by the pressure of hydraulic oil and/or the centrifugal force such that the inner peripheral part thereof further expands than the outer peripheral part thereof. When the clutch disc **28** is pressed in contact with the front cover **2** while the front cover **2** (especially, the friction surface **2b**) is deformed, it is concerned that the clutch disc **28** locally makes contact with the front cover **2** without entirely making contact therewith and is thereby abnormally abraded.

However, in the present device, the relation “the piston **30**>the pressure plate **29**>the core plate **36**” is set regarding the bending stiffness of the core plate **36**, that of the pressure plate **29**, and that of the piston **30**. Hence, even when the front cover **2** is deformed, the pressure plate **29** and the clutch disc **28** are configured to be deformed in accordance with deformation of the front cover **2** by pressing the pressure plate **29** and the clutch disc **28** with the piston **30**. With this configuration, the clutch disc **28** can be inhibited from being abnormally abraded.

## Other Exemplary Embodiments

The present disclosure is not limited to the exemplary embodiment described above, and a variety of changes or modifications can be made without departing from the scope of the present disclosure.

In the aforementioned exemplary embodiment, the clutch part is composed of the clutch disc **28**. However, for instance, a friction member may be fixed to the lateral surface of the pressure plate, and the friction member may be configured to be pressed in contact with the friction surface **2b** of the front cover **2**. In this case, a clutch disc can be omitted.

On the other hand, the return mechanism for separating the piston from the front cover may be disposed between the piston and the cover plate.

## INDUSTRIAL APPLICABILITY

In the lock-up device of the present disclosure, a gap of a clutch part can be appropriately set in accordance with temperatures, and in addition, flexibility in design of a mechanism for appropriately setting the gap of the clutch part can be enhanced.

## REFERENCE SIGNS LIST

- 2** Front cover
- 2b** Friction surface
- 4** Turbine
- 28** Clutch disc



29 Pressure plate  
 30 Piston  
 34 Damper mechanism  
 40 Support boss  
 40*b* Piston support part  
 40*c* Second fixation part (coupling part)  
 41 Cover plate (oil chamber plate)  
 50 Return spring made of bimetal (temperature detection member)  
 51 Cam mechanism (gap adjustment mechanism)  
 C1 Lock-up oil chamber  
 C2 Cancellation oil chamber  
 P1 First oil passage  
 P2 Second oil passage  
 P3 Third oil passage

The invention claimed is:

1. A lock-up device for a torque converter, the lock-up device for transmitting a torque from a front cover to a transmission-side member through a turbine of the torque converter, the lock-up device comprising:

a clutch disc disposed between the front cover and the turbine;

a piston disposed in opposition to the front cover through the clutch disc so as to be movable in an axial direction, the piston configured to press the clutch disc toward the front cover;

a temperature detection member that a deformation amount thereof is adjusted in accordance with surrounding temperatures; and

a gap adjustment mechanism including a first member fixed to the front cover and a second member fixed to the piston,

the gap adjustment mechanism configured to adjust a gap between the front cover and the piston to be a first gap at a first temperature in accordance with the deformation amount of the temperature detection member, the gap adjustment mechanism further configured to adjust the gap between the front cover and the piston to be a second gap narrower than the first gap at a second temperature higher than the first temperature in accordance with the deformation amount of the temperature detection member.

2. The lock-up device for a torque converter according to claim 1, wherein the temperature detection member and the gap adjustment mechanism are disposed between the front cover and the piston.

3. The lock-up device for a torque converter according to claim 1, further comprising:

an oil chamber plate disposed between the piston and the turbine, wherein

5 the piston and the oil chamber plate form a lock-up oil chamber therebetween, the lock-up oil chamber to be supplied with a hydraulic oil for moving the piston toward the front cover.

4. The lock-up device for a torque converter according to claim 3, wherein

10 the front cover and the piston form a cancellation oil chamber therebetween so as to cancel a hydraulic pressure to be generated in the lock-up oil chamber in lock-up releasing, and

15 the temperature detection member and the gap adjustment mechanism are disposed in the cancellation oil chamber.

5. The lock-up device for a torque converter according to claim 4, further comprising:

20 a support boss having an annular shape, the support boss fixed to an inner peripheral part of the front cover, the support boss including a piston support part and a coupling part, the piston support part configured to support an inner peripheral end surface of the piston such that the piston is slidable thereon, the coupling part configured to receive an inner peripheral part of the oil chamber plate coupled thereto, wherein

the support boss includes an oil passage communicated with the lock-up oil chamber and an oil passage communicated with the cancellation oil chamber.

6. The lock-up device for a torque converter according to claim 1, wherein

the front cover includes a friction surface with which the clutch disc is to be pressed in contact, and

35 the lock-up device further comprises a pressure plate disposed in opposition to the friction surface through the clutch disc, the pressure plate to be pressed by the piston.

7. The lock-up device for a torque converter according to claim 1, further comprising:

40 a damper mechanism configured to transmit the torque from the clutch disc to the turbine, the damper mechanism configured to absorb and attenuate a torsional vibration.

\* \* \* \* \*