



US010450758B2

(12) **United States Patent**
Burt et al.

(10) **Patent No.:** **US 10,450,758 B2**
(45) **Date of Patent:** **Oct. 22, 2019**

(54) **BRACKET FOR SUPPORTING ATTACHMENT OF THE END OF A RAILING MEMBER TO A VERTICAL MEMBER**

E04H 17/1417; E04H 17/1421; E04H 17/1434; E04H 17/1443; E04H 2017/1447; E04H 2017/1452; E04H 2017/146; E04H 2017/1491; Y10T 403/32122; Y10T 403/32131; Y10T 403/32163

(71) Applicant: **Fortress Iron, LP**, Garland, TX (US)

See application file for complete search history.

(72) Inventors: **Kevin T. Burt**, Dallas, TX (US); **Matthew Carlyle Sherstad**, Dallas, TX (US); **John David Irick**, Dallas, TX (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(73) Assignee: **Fortress Iron, LP**, Garland, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 691 days.

| | | | |
|-------------------|---------|------------------|---------------------------|
| 5,026,028 A | 6/1991 | Ooi et al. | |
| 5,547,169 A | 8/1996 | Russell | |
| 6,053,481 A * | 4/2000 | Scheide | E04H 17/1443 256/65.06 |
| 6,543,751 B1 * | 4/2003 | Spruill | E04F 11/1817 256/65.04 |
| 6,805,335 B2 * | 10/2004 | Williams | E04F 11/181 256/67 |
| 7,731,160 B2 | 6/2010 | Terrels et al. | |
| 9,322,180 B2 * | 4/2016 | Burt | E04F 11/1834 |
| 2003/0030048 A1 * | 2/2003 | Quaintance | E04F 11/181 256/59 |
| 2003/0127575 A1 | 7/2003 | Forbis | |

(21) Appl. No.: **15/078,866**

(22) Filed: **Mar. 23, 2016**

(65) **Prior Publication Data**

US 2016/0201335 A1 Jul. 14, 2016

Related U.S. Application Data

(63) Continuation of application No. 13/729,087, filed on Dec. 28, 2012, now Pat. No. 9,322,180.

(60) Provisional application No. 61/584,878, filed on Jan. 10, 2012.

(51) **Int. Cl.**
E04F 11/18 (2006.01)
E04H 17/14 (2006.01)

(52) **U.S. Cl.**
CPC *E04F 11/1834* (2013.01); *E04F 11/1836* (2013.01); *E04H 17/14* (2013.01); *E04F 2011/1819* (2013.01)

(58) **Field of Classification Search**
CPC ... E04F 11/18; E04F 11/1802; E04F 11/1804;


Primary Examiner — Michael P Ferguson

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(57) **ABSTRACT**

A railing bracket system includes a cup that has a cup bottom wall and two opposed cup side walls. The cup is adapted to receive an end of a railing member. A cap has a first cap wall disposed between two opposed cap side walls and a tab extending from at least one side wall. The cap is adapted to cover the cup. The cup is configured to receive the cap in both of a first orientation wherein the cap is installed over the cup and a second orientation wherein the cap is installed under the cup bottom wall. The tab secures the cap to the cup in both the first orientation and the second orientation.

7 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | |
|--------------|-----|---------|----------------|---------------------------|
| 2003/0164486 | A1 | 9/2003 | West | |
| 2005/0051761 | A1 | 3/2005 | Caissie et al. | |
| 2005/0285091 | A1 | 12/2005 | Ko | |
| 2006/0033093 | A1 | 2/2006 | Lo | |
| 2006/0175594 | A1* | 8/2006 | Burkart | E04F 11/1817 256/65.02 |
| 2007/0131920 | A1 | 6/2007 | Platt | |

* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10A




FIGURE 10B




FIGURE 10C




FIGURE 10D




FIGURE 10E




FIGURE 10F




FIGURE 10G




FIGURE 10H

1

**BRACKET FOR SUPPORTING
ATTACHMENT OF THE END OF A RAILING
MEMBER TO A VERTICAL MEMBER**

PRIORITY CLAIM

This application is a continuation of U.S. patent application Ser. No. 13/729,087, filed Dec. 28, 2012, pending, which claims priority from U.S. Provisional Application for Patent No. 61/584,878 filed Jan. 10, 2012, the disclosure of which is hereby incorporated by reference.

BACKGROUND

Technical Field

The present invention relates generally to hardware associated with attaching the end of a railing member to a vertical member and more particularly to a bracket for use in securing the end of a railing member to a vertical member with a user selectable vertical or horizontal angular position. The railing member can comprise a hand rail, a rail of a fence panel, or any other structural member.

Description of Related Art

When installing a railing, the end of the railing must be attached to a vertical member such as a post (or perhaps a wall). If the railing is horizontal and oriented perpendicular to the face of the vertical member, this attachment is quite easy to accomplish using conventional techniques requiring little skill. Difficulties in attachment arise, however, when the railing has a non-horizontal and/or non-perpendicular orientation. Measuring and making the proper angle cuts to the end of the railing can be tricky, and there may be difficulties or complications with respect to securely attaching the angle-cut end of the railing to the vertical member.

It is known in the art to use a bracket mounted to the vertical member to receive the end of the railing and assist in attaching the end of the railing to the vertical member. However, such a bracket (typically having a configuration and operation similar to that of a joist hanger used in housing construction) solely supports a horizontal and perpendicular orientation for attaching the end of the railing to the vertical member. The bracket is accordingly of little or no use when the railing installation requires attachment of the end of the railing to the vertical member at an angle formed in either the vertical or horizontal plane.

Another concern with such prior art brackets is that the mounting hardware (such as the bracket itself and its associated attachment screws) remains visible after installation. In many railing installation jobs, visibility of the mounting means and the bracket following completion of the installation is undesirable. It is for this reason that installers often prefer to use the conventional installation techniques when attaching the end of the railing to the vertical member. However, there is an associated increase in cost due to manpower skill and hours to achieve a more aesthetically pleasing installation through the use of conventional installation techniques (especially when the installation requires the making of an angle cut).

There would be an advantage if a bracket were available for attaching the end of a railing to a vertical member at a user selectable angle in either the vertical or horizontal plane. There would further be an advantage if the visibility of the mounting hardware for that bracket (in either an angled or perpendicular installation) could be minimized.

SUMMARY

In accordance with an embodiment, an apparatus comprises a cup adapted to receive an end of a railing member;

2

and a cap adapted to cover the cup. The cup is configured to receive the cap in both of a first orientation wherein the cap is installed over a top of the cup and a second orientation wherein the cap is installed under a bottom of the cup. The cup is mountable to a vertical member in a perpendicular configuration. Furthermore, through the use of a pivoting mechanism, the cup is mountable to the vertical member with a user selectable vertical or horizontal angular position.

In an embodiment, an adjustable railing bracket comprises a rail receiving member having a bottom wall, a plurality of side walls, and a back wall, the rail receiving member configured to support a rail therein; and a hinge assembly configured to be coupled to the rail receiving member in at least two orientations which allow for rotation of the rail receiving member about a hinge axis of the hinge assembly. The orientations include: a first orientation wherein rotation of the rail receiving member about the hinge axis of the hinge assembly is in a vertical plane; and a second orientation wherein rotation of the rail receiving member about the hinge axis of the hinge assembly is in a horizontal plane.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the method and apparatus of the present invention may be acquired by reference to the following Detailed Description when taken in conjunction with the accompanying Drawings wherein:

FIG. 1 shows an exploded perspective view of an adjustable-angle railing bracket;

FIG. 2 is an isometric view of an assembled adjustable-angle railing bracket to support selection of a vertical attachment angle between the railing member and vertical member;

FIG. 3 is an isometric view of an assembled adjustable-angle railing bracket to support selection of a horizontal attachment angle between the railing member and vertical member;

FIG. 4 illustrates an exploded view of a cup for the adjustable-angle railing bracket with a cap;

FIG. 5 illustrates a rear assembled view of a cup for the adjustable-angle railing bracket with a cap;

FIGS. 6 and 7 illustrate attachment of the adjustable-angle railing bracket to a vertical member;

FIGS. 8 and 9 show isometric views of the cup for the adjustable-angle railing bracket; and

FIGS. 10A-10H illustrate views of alternative implementations for the cap.

DETAILED DESCRIPTION OF THE DRAWINGS

Reference is first made to FIG. 2, which shows an isometric view of an assembled adjustable-angle railing bracket 10. The bracket 10 includes a cup 14 that is configured to receive an end of a railing member. The bracket 10 further includes a hinge assembly 12 that is configured to attach to a vertical member (such as a post or wall). The cup 14 is attached to the hinge assembly 12 in a configuration such that the bracket supports selection of a vertical attachment angle between the railing member and vertical member.

Reference is next made to FIG. 3, which shows an isometric view of an assembled adjustable-angle railing bracket 10. The bracket 10 includes a cup 14 that is configured to receive an end of a railing member. The bracket 10 further includes a hinge assembly 12 that is configured to attach to a vertical member (such as a post or

wall). The cup **14** is attached to the hinge assembly **12** in a configuration such that the bracket supports selection of a horizontal attachment angle between the railing member and vertical member.

The term “rail”, “railing” or “railing member” as used herein refers to any structural member to be attached to a vertical member. Examples of included railing members include a hand rail, a rail of a fence panel or other barrier, and the like.

It will be noted that the component parts of the bracket shown in FIGS. **2** and **3** are the same. The only difference between FIGS. **2** and **3** is the orientation with which the cup **14** has been attached to the hinge assembly **12**. In FIG. **2**, the attachment orientation configures the hinge assembly **12** to support pivoting movement of the cup **14** in a vertical plane. Conversely, the attachment orientation in FIG. **3** configures the hinge assembly **12** to support pivoting movement of the cup **14** in a horizontal plane. Thus, an installer can utilize the same bracket **10** in connection with making an angled attachment of the railing member to the vertical member where the angle of such angled attachment is formed in vertical plane (such as with a stair or ramp installation) or horizontal plane (such as with turning a non-perpendicular corner).

FIG. **1** shows an exploded perspective view of the bracket **10**. Specifically, FIG. **1** shows the orientation for attachment of the hinge assembly **12** relative to the cup **14** as shown in FIG. **2** for supporting pivoting movement of the cup **14** in a vertical plane. It will be understood that the attachment orientation of the hinge assembly **12** relative to the cup **14** as shown in FIG. **3** is accomplished by simply rotating the hinge assembly **12** by ninety degrees relative to the cup **14** so as to support pivoting movement of the cup **14** in a horizontal plane.

The cup **14** is formed from a sheet of material (for example, 12 gauge steel) that is stamp cut into a T-shape and folded along three lines to present four adjacent sides of a cube-like structure. The four adjacent sides of the cup **14** comprise a bottom wall **34**, a pair of opposed side walls **36**, and a back wall **38**. The pair of opposed side walls **36** and back wall **38** extend perpendicularly from the bottom wall **34** at the fold lines.

The bottom wall **34** provides a primary support for receiving the end of a railing member. The weight of the railing and any downward force on the railing is opposed, at least in part, by the bottom wall **34**.

The side walls **36** provide for lateral retention of the received end of the railing member. At least one of the side walls **36**, and in a preferred embodiment both side walls, includes a countersunk hole **40**. The hole **40** supports insertion of a mounting screw through the hole for attachment to a side of the railing member (not shown). This attachment may be made into and through the side of the railing member (using an opening therein) or alternatively against the side surface of the railing member (such as with the use of a set screw). Thus, using the hole **40** and associated mounting screw, the side walls **36** further function to restrain longitudinal movement of the received railing member (i.e., removal of the end of the railing member from the cup **14**).

The back wall **38** of the cup **14** includes a plurality of countersunk holes **42**. In certain embodiments, four countersunk holes **42** may be provided in the backwall **38**. The holes **42** support insertion of a mounting screw through each of two or more of the holes **42** so as to support attachment of the cup **14** to the hinge assembly **12**. In a perpendicular installation, the holes **42** are used to receive screws for

attachment of the cup **14** directly to a vertical member without need for the hinge assembly. It will be understood that in either implementation, mounting screw attachment is just one available means for attachment. It will thus be understood that the back wall **38** can be attached, for example, using permanent or non-permanent attachment means. An example of a permanent attachment means would comprise a weld (for example, a weld between the back wall **38** and the surface of a vertical member, or a weld between the back wall **38** and the hinge assembly **12**).

The hinge assembly **12** comprises a back plate **16**. The back plate **16** is formed from a sheet of material (for example, 12 gauge steel) that is stamp cut into a square or rectangular shape. A plurality of holes **18** are formed in the back plate **16**. The holes **18** support insertion of a mounting screw through each hole for attachment to a vertical member (not shown). In this way, the hinge assembly **12** of the bracket **10** can be securely attached to the vertical member.

The hinge assembly **12** further comprises a barrel **20** that is secured to a front surface of the back plate **16**. In an embodiment, the barrel **20** may comprise a cylindrical structure that is attached, for example by welding, to the front surface of the back plate **16**. In another embodiment, the barrel **20** may be formed integrally by the back plate **16**. In either configuration the barrel **20** defines a through hole **22** for supporting pivoting action by the hinge assembly **12**. Means other than the use of barrel can be used to define the through hole **22**.

The hinge assembly **12** still further comprises a pivoting member **26**. The pivoting member **26** is formed from a sheet of material (for example, 12 gauge steel) that is stamp cut into a generally elongate-shape and folded along two lines to present three adjacent sides of a U-shaped structure. The three adjacent sides of the pivoting member **26** comprise a pair of ears **28** and a center plate **30**. The ears **28** extend perpendicularly from the center plate **30** at the fold lines. The ears **28** have a tapered or triangular shape. An aligned pair of openings are formed in the pair of ears **28**. A distance between the ears **28** is slightly larger than a length of the barrel **20** and its through hole **22**. In the assembled hinge assembly **12**, the pair of openings in the ears **28** are aligned with the through hole **22**. A pivot pin **24** is inserted through the pair of openings in the ears **28** and through hole **22** to define a hinge mechanism which permits the pivoting member **26** to angularly pivot relative to the back plate **16**. The pivot pin may have any one of a number of configurations including a screw-like configuration as shown, or a more simple shaft with a cotter, hitchpin or hairpin securing mechanism.

It will accordingly be recognized that the tapered or triangular shape of the pair of ears **28** provides freedom of pivoting movement while simultaneously providing structural support and integrity of the hinge assembly **12**. In a preferred implementation, the tapered or triangular shape of the pair of ears **28** permits the pivoting member **26** to rotate from a center position (where the center plate **30** of the pivoting member is approximately parallel to the back plate **16**) plus or minus about forty-five degrees in the plane of movement relative to the back plate **16** (i.e., horizontal or vertical depending on the installed orientation of the cup **14** relative to the hinge assembly **12**). Thus, the pivoting member **26** has an approximate ninety degree angle of throw.

The center plate **30** of the pivoting member **26** includes a plurality of tapped holes **32**. In a preferred implementation, two diagonally offset holes **32** are provided. The holes **32** align with certain ones of the plurality of countersunk holes

5

42 found in the back wall 38 of the cup 14. The holes 42 support insertion of a mounting screw therethrough to engage the tapped holes 32 of the center plate 30 and thus permit the cup 14 to be securely attached to the hinge assembly 12. As shown, the tapped holes 32 are located proximate an opposite corner of the center plate 30 in order to secure opposite diagonal corners of the backwall 38 of the cup 14.

Importantly, the provision of aligned holes 42 and tapped holes 32 in the manner illustrated in FIG. 1 permits the attachment of the cup 14 to the hinge assembly 12 in either the orientation shown in FIG. 2 (which supports pivoting movement of the cup 14 in a vertical plane) or the orientation shown in FIG. 3 (which supports pivoting movement of the cup 14 in a horizontal plane). Changing the configuration of the bracket 10 between vertical and horizontal plane installation support simply requires removal of the mounting screws from the holes 42 and tapped holes 32, rotation of the cup 14 relative to the hinge assembly 12 by ninety degrees to a new orientation, and reinsertion and tightening of the mounting screws through the holes 42 and tapped holes 32 at the new orientation.

With reference once again to FIG. 2, the cup 14 is configured to pivot vertically with respect to the back plate 16 of the hinge assembly 12. This functionality may be particularly important when using the bracket 10 to secure a railing of a stairway. In this application, the cup 14 of the bracket 10 may be pivoted downward at a selected angle up to approximately 45 degrees to be in position to receive a top end of a stairway railing. Alternatively, the cup 14 of the bracket 10 may be pivoted upward at a selected angle up to approximately 45 degrees to be in position to receive a bottom end of a stairway railing. The pivot axis and the bottom wall are generally parallel to each other in this vertical adjustable-angle configuration.

With reference once again to FIG. 3, the same bracket 10 may be installed such that the pivot axis defined by the pivot pin 24 and the bottom wall 34 of the cup 14 may be generally perpendicular to each other. This configuration may be particularly useful in a miter railing installation where a horizontal railing may be secured to a fence post at a horizontal angle to turn a non-perpendicular corner. To create this configuration, the hinge assembly 12 may be rotated approximately 90 degrees with respect to the cup 14. The cup 14 may be secured with screws as received through the countersunk holes 42 into the tapped holes 32 of the pivoting member 26. Thus, the bottom wall 34 of the cup 14 may remain parallel to the ground, but the pivot axis of the hinge assembly may be perpendicular to the ground to enable side-to-side rotation of the cup 14 and its corresponding railing.

Reference is now made to FIG. 4 which illustrates an exploded view of an embodiment of the cup 14 for the bracket 10 with a cap 50. For the sake of clarity, the cup 14 is shown without the associated and attached hinge assembly 12 (see, FIGS. 1-3) and so as to emphasize that the cup 14 is further useful without the hinge assembly 12 for supporting a perpendicular railing installation. The cap 50 serves as a cover to hide the countersunk holes 40 and screws received therethrough to secure the received end of the railing (not shown). The cap 50 accordingly provides an aesthetically pleasing finished railing assembly covering the included attachment hardware. The cap 50 is made of any suitable material including molded plastic or stamped sheet metal. If made of stamped sheet metal, the stamped structure of the

6

cap 50 comprises a generally elongate-shape that is folded along two lines to present three adjacent sides of a U-shaped structure.

A front of the cap 50 includes an inwardly extending flange portion 52. A back of the cap 50, at a distal end corner of the side walls of the cap, includes one or more inwardly extending tab members 56. Each rear corner of the cup 14 is provided with a notch 54 (see, FIG. 5 illustrating a rear assembled view).

When the cap 50 is inserted over the cup 14, the inwardly extending flange portion 52 is provided to cover an edge of the cup 14 material, the walls of the cap are provided to cover the side walls 36 (openings 40 and associated screws) of the cap as well as the open top portion of the cup, and the inwardly extending tab members 56 engage the bottom notches 54 of the cup (with such engagement serving to securely attach the cap 50 to the cup 14). The combination of the inwardly extending tab members 56 and inwardly extending flange portion 52, when the cap 50 is attached to the cup 14, further serve to restrain back-and-forth motion of the cap with respect to the cup.

While FIG. 5 illustrates the attachment of the cap 50 over the top of the cup 14, it will be understood that the provision of notches 54 at each rear corner of the cup 14 supports attachment of the cap 50 under the cup 14. When the cap 50 is inserted under the cup 14, the inwardly extending flange portion 52 is still provided to cover an edge of the cup 14 material, and the inwardly extending tab members 56 instead engage the top notches 54 of the cup (with such engagement serving to securely attach the cap 50 to the cup 14). In this assembled configuration, the walls of the cap 50 are provided to cover the side walls 36 (openings 40 and associated screws) of the cap as well as the bottom wall 34 of the cup. The combination of the inwardly extending tab members 56 and inwardly extending flange portion 52, when the cap 50 is attached to the cup 14, further serve to restrain back-and-forth motion of the cap with respect to the cup. This particular assembly of the cap 50 to the cup 14 is particularly useful when an additional member is attached to a top of the received railing member (thus permitting a flush assembly without interference from the cap 50 will still permitting the cap to serve its aesthetic function of covering the hardware associated with the cup and retention of the received end of the railing member).

Reference is now made to FIGS. 6 and 7, which show a variety of attachment configurations for the adjustable-angle railing bracket 10 as secured to a vertical member, such as post 60.

FIG. 6 shows a configuration 62 of the bracket 10 as secured to the post 60 in a manner which permits adjustable angle positioning in the vertical plane. The configuration 62 further shows the cap 50 installed in an overhead position (i.e., attached over the top of the cup 14). It will be understood, according to alternative installations, that configuration 62 may not include a cap 50 or the cap 50 may instead be fitted to the cup in an underneath configuration (i.e., attached under the cup 14). The backplate 16 of the hinge assembly is secured, for example by screws, to the surface of the post 60. Alternatively, the backplate 16 is secured to the surface of the post 60 in a more permanent manner using, for example, a weld or adhesive.

FIG. 6 further illustrates a configuration 64 in which the cup 14 is secured directly to the post 60. The configuration 64 accordingly illustrates use of the cup 14 to support a horizontal installation perpendicular to the vertical surface of the post 60. Similar to configuration 62, the cap 50 is installed in an overhead position (i.e., attached over the top

of the cup 14). It will be understood, according to alternative installations, that configuration 64 may not include a cap 50 or the cap 50 may instead be fitted to the cup in an underneath configuration (i.e., attached under the cup 14). The back wall 38 of the cup is secured, for example by screws, to the surface of the post 60. Alternatively, the back wall 38 of the cup is secured to the surface of the post 60 in a more permanent manner using, for example, a weld or adhesive.

FIG. 7 shows a configuration 66 of the bracket 10 as secured to the post 60 in a manner which permits adjustable angle positioning in the horizontal plane. The configuration 66 further shows the cap 50 installed in an overhead position (i.e., attached over the top of the cup 14). It will be understood, according to alternative installations, that configuration 66 may not include a cap 50 or the cap 50 may instead be fitted to the cup in an underneath configuration (i.e., attached under the cup 14). The backplate 16 of the hinge assembly is secured, for example by screws, to the surface of the post 60. Alternatively, the backplate 16 is secured to the surface of the post 60 in a more permanent manner using, for example, a weld or adhesive.

FIG. 7 further illustrates a configuration 68 in which the cup 14 is secured directly to the post 60. The configuration 68 accordingly illustrates use of the cup 14 to support a horizontal installation perpendicular to the vertical surface of the post 60. The configuration 68 shows the cap 50 installed in an underneath position (i.e., attached under the cup 14). It will be understood, according to alternative installations, that configuration 68 may not include a cap 50 or the cap 50 may instead be fitted to the cup in an overhead position (i.e., attached over the top of the cup 14). The back wall 38 of the cup is secured, for example by screws, to the surface of the post 60. Alternatively, the back wall 38 of the cup is secured to the surface of the post 60 in a more permanent manner using, for example, a weld or adhesive.

Reference is now made to FIGS. 8 and 9 which show isometric views of the cup 14. In this alternate embodiment, the cup 14 is reinforced with a pair of tack welds 70 that connect a portion of the bottom wall 34 to each sidewall 36. This weld reinforces the cup 14 by providing additional structural strength where torque on the bottom wall 34 may be the greatest. Thus bending of the bottom wall downward away from the sidewalls is inhibited. In other embodiments, the entire bottom wall may be connected to the sidewalls or formed integrally therewith.

The cup 14 is sized to receive the end of the railing member. The railing may have a square, rectangular or circular cross-section. Exemplary sizes include inch to inch-and-a-half tubing of the type commonly used as railing members for outdoor fences and porch/stair railings.

Reference is now made to FIG. 10A-10H which show views of alternative implementations for the cap 50. For example, FIGS. 10A-10B show an alternative cap implementation including inwardly extending flange portions 52 to cover edges of the cup 14 material, and the use of inwardly extending tab members 56 positioned to extend from the center of the back edge of the cap side walls (rather than from the corners as discussed above). To use this cap configuration, the notches 54 formed in the rear of the cup 14 must be correspondingly aligned with the center of back edge of the cap side walls. FIGS. 10C-10D show an alternative cap implementation similar to FIGS. 10A-10B, but with a different configuration for the inwardly extending tab members 56. FIGS. 10E-10F show an alternative cap implementation wherein the inwardly extending tab members 56 are formed as dimple structures extending from the inside

surface of the cap side walls. To use this cap configuration, the notches 54 formed in the cup 14 will instead comprise apertures formed in the cup side walls 36 that correspondingly align with the location of the dimples. FIGS. 10G-10H show an alternative implementation where the cap 50 does not use inwardly extending tab members 56. In this implementation, the cap is preferably sized and shaped to be friction secured to cup. The included tab members 56 in any implementation may be formed in the cap by stamping, pressing, molding or other well known techniques.

The design disclosed herein presents the following advantages:

The bracket supports a drop in installation—this is a significant advantage for the installer as it allows the installer to set the vertical post members, install the brackets and then drop the railing, panel or other structure into place. This obviates concerns with having a loose panel and loose brackets, and having to fight to secure all the components. This also supports installation with the use of fewer personnel and with an easier and quicker installation and assembly time.

The use of the cap presents an installation with no visible fasteners. This also allows the cut ends of a railing, panel or other structure to be hidden along with the spaces that would exist between bracket and rails. The cap further has a “snap fit” assembly that locks securely in place with no need for fasteners, adhesive, welding or anything else. The cap can further be used from the top of the cup on installations without a wood top cap (over the railing) and from the bottom for installations with a wood top cap.

Universality—the same bracket is used for right, left, up, down and straight installation. The same bracket is used with a top cap and without. This is a significant benefit in distribution as well as ease of ordering for the installer or consumer.

Although preferred embodiments of the method and apparatus of the present invention have been illustrated in the accompanying Drawings and described in the foregoing Detailed Description, it will be understood that the invention is not limited to the embodiments disclosed, but is capable of numerous rearrangements, modifications and substitutions without departing from the spirit of the invention as set forth and defined by the following claims.

What is claimed is:

1. A railing bracket, comprising:

a cup having a cube shape and comprising a cup bottom wall, a cup rear wall extending perpendicularly from the cup bottom wall and a first bend disposed between the cup rear wall and the cup bottom wall, a first cup side wall extending perpendicularly from the cup rear wall and a second bend disposed between the cup rear wall and the first cup side wall, a second cup side wall extending perpendicularly from the cup rear wall and a third bend disposed between the cup rear wall and the second cup side wall, an end of a railing member being supportable primarily by the cup bottom wall, each of the cup side walls defining a through hole and the cup rear wall defining a plurality of through holes, the cup further comprising an upper notch and a lower notch disposed proximate the cup rear wall, each of the cup bottom wall, the cup rear wall, the first cup side wall and the second cup side wall forming a side of the cube shape;

a cap having a generally U-shape and comprising a cap wall and a first cap side wall extending perpendicularly from the cap wall and a first cap bend disposed between the cap wall and the first cap side wall, and a second cap

9

side wall extending perpendicularly from the cap wall and a second cap bend disposed between the cap wall and the second cap side wall, and a tab extending from at least one of the first and second cap side walls, the cap being adapted to cover the cup, and a flange portion extending inwardly from each of the cup wall, the first cap side wall and the second cap side wall, the cap wall, the first cap side wall, and the second cap side wall together forming the generally U-shape; and wherein the cup is configured to receive an end of a railing member that contacts the cup bottom wall, and the cup is configured to receive the cap in both of a first orientation wherein the cap wall is disposed over the end of the railing member and the at least one tab is received by the lower notch and a second orientation wherein the cap wall is disposed under the cup bottom wall and the tab is received by the upper notch; wherein in the first orientation the cap exposes the cup bottom wall and in the second orientation the cap exposes a top surface of the end of the railing member.

10

2. The railing bracket of claim 1 wherein in both the first and the second orientation the first and second cap side walls cover the through holes in the first and second cup side walls.

3. The railing bracket of claim 1 wherein the bottom wall is disposed at the perimeter of the rear wall.

4. The railing bracket of claim 1 wherein the cup and cap are formed of sheet metal.

5. The railing bracket of claim 4 wherein the cup and cap are formed of steel.

6. The railing bracket of claim 1 wherein the rear wall and each of the cup side walls has a same height.

7. The railing bracket of claim 1 wherein the cup further comprises a first tack weld connecting at least a portion of the first cup side wall to at least a portion of the cup bottom wall and a second tack weld connecting at least a portion of the second cup side wall to at least a portion of the cup bottom wall.

* * * * *