

US010481365B2

(12) **United States Patent  
Park**

(10) **Patent No.: US 10,481,365 B2**  
(45) **Date of Patent: Nov. 19, 2019**

(54) **OPTICAL SYSTEM**  
(71) Applicant: **Samsung Electro-Mechanics Co., Ltd.**,  
Suwon-si (KR)  
(72) Inventor: **Il Yong Park**, Suwon-si (KR)  
(73) Assignee: **Samsung Electro-Mechanics Co., Ltd.**,  
Suwon-si (KR)  
(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

2013/0335833 A1\* 12/2013 Liao ..... G02B 13/0045  
359/713  
2014/0078603 A1\* 3/2014 You ..... G02B 13/0045  
359/738  
2015/0029599 A1\* 1/2015 Huang ..... G02B 3/04  
359/713  
2015/0062721 A1\* 3/2015 Kim ..... G02B 13/0045  
359/713  
2015/0131172 A1 5/2015 Park et al.  
2016/0004044 A1\* 1/2016 Kubota ..... G02B 13/0045  
359/713

(Continued)

**FOREIGN PATENT DOCUMENTS**

(21) Appl. No.: **15/069,520**  
(22) Filed: **Mar. 14, 2016**

CN 104345431 A 2/2015  
CN 104635318 A 5/2015

(Continued)

(65) **Prior Publication Data**  
US 2017/0045717 A1 Feb. 16, 2017

**OTHER PUBLICATIONS**

(30) **Foreign Application Priority Data**

STIC search (Year: 2019).\*

(Continued)

Aug. 10, 2015 (KR) ..... 10-2015-0112493

(51) **Int. Cl.**  
**G02B 13/00** (2006.01)  
**G02B 9/62** (2006.01)  
(52) **U.S. Cl.**  
CPC ..... **G02B 13/0045** (2013.01); **G02B 9/62**  
(2013.01)

*Primary Examiner* — James R Greece

*Assistant Examiner* — Travis S Fissel

(74) *Attorney, Agent, or Firm* — NSIP Law

(58) **Field of Classification Search**  
CPC ..... G02B 21/0068; G02B 21/33; G02B  
13/0035; G02B 13/0045; G02B 9/62  
USPC ..... 359/658, 716, 752, 756, 780, 757, 713,  
359/759  
See application file for complete search history.


(57) **ABSTRACT**

An optical system includes a first lens including a positive refractive power, a second lens including a positive refractive power and a convex image-side surface, a third lens, and a fourth lens. The optical system includes a fifth lens including a concave object-side surface and a concave image-side surface, and a sixth lens including an inflection point formed on an image-side surface thereof. The first to sixth lenses are sequentially disposed from an object toward an imaging plane.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**

9,036,272 B2\* 5/2015 Huang ..... G02B 3/04  
359/713  
9,817,214 B2 11/2017 Kim et al.

**20 Claims, 24 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

2016/0054543 A1\* 2/2016 Nabeta ..... G02B 13/0045  
359/713  
2016/0124193 A1 5/2016 Kim et al.  
2016/0139368 A1 5/2016 You

FOREIGN PATENT DOCUMENTS

CN 105572852 A 5/2016  
CN 105607224 A 5/2016  
JP 2011-85733 A 4/2011  
JP 2013-195587 A 9/2013  
KR 20160051469 \* 11/2014  
KR 10-2016-0051469 A 5/2016

OTHER PUBLICATIONS

Korean office action dated Feb. 7, 2017 in corresponding Korean patent app. No. 10-2015-0112493 (10 pages in English, 6 pages in Korean).

Chinese Office Action dated May 28, 2018 in corresponding Chinese Patent Application No. 201610187342.8 (17 pages in English, 11 pages in Chinese).

\* cited by examiner




FIG. 1




FIG. 2

FIRST EMBODIMENT							
F number=		2.13	TTL =		4.632	f =	4.083
SURFACE NUMBER		RADIUS OF CURVATURE	THICKNESS/DISTANCE	REFRACTIVE INDEX	ABBE NUMBER	FOCAL LENGTH	
0	STOP		0.0000				
1	FIRST LENS	1.5012	0.4343	1.547	56.1	6.430	
2		2.3530	0.1041				
3	SECOND LENS	2.5486	0.4321	1.547	56.1	4.024	
4		-15.0835	0.0300				
5	THIRD LENS	26.1685	0.2200	1.657	21.5	-6.017	
6		3.4248	0.3770				
7	FOURTH LENS	-10.0835	0.3100	1.657	21.5	347.95	
8		-9.7755	0.4374				
9	FIFTH LENS	-86.0940	0.5630	1.657	21.5	-120.555	
10		1000.0000	0.1369				
11	SIXTH LENS	1.9813	0.4718	1.537	55.7	-9.940	
12		1.2690	0.2012				
13	FILTER	Infinity	0.2100	1.519	64.2		
14		Infinity	0.7041				
15	IMAGING PLANE	Infinity	0.0000				

FIG. 3



SURFACE NUMBER	1	2	3	4	5	6	7	8	9	10	11	12
RADIUS OF CURVATURE	1.5012	2.3530	2.5486	-15.0835	26.1635	3.4248	-10.0835	-2.7755	-86.0940	1000.0000	1.8813	1.2890
CONIC CONSTANT (Q)	-0.453	0.000	0.000	0.000	0.000	10.759	0.000	0.000	0.000	0.000	-0.564	-4.635
4-TH ORDER COEFFICIENT (A)	-0.014	-0.066	-0.075	-0.027	0.017	0.014	-0.083	-0.066	0.046	-0.004	-0.406	-0.182
6-TH ORDER COEFFICIENT (B)	0.061	-0.075	0.056	-0.052	0.054	-0.028	-0.040	-0.109	-0.228	-0.074	0.199	0.099
8-TH ORDER COEFFICIENT (C)	-0.328	0.102	-0.446	0.141	-0.289	0.190	0.173	0.373	0.223	0.062	-0.064	-0.040
10-TH ORDER COEFFICIENT (D)	0.754	-0.077	1.453	-0.211	0.616	-0.875	-0.129	-0.537	-0.144	-0.032	0.015	0.011
12-TH ORDER COEFFICIENT (E)	-1.014	0.001	-2.208	0.148	-0.841	1.699	-0.305	0.462	0.050	0.009	-0.002	-0.002
14-TH ORDER COEFFICIENT (F)	0.708	0.227	1.974	0.168	0.794	-1.594	0.579	-0.213	-0.009	-0.001	0.000	0.000
16-TH ORDER COEFFICIENT (G)	-0.200	-0.182	-0.789	-0.234	-0.358	0.628	-0.314	0.038	0.001	0.000	0.000	0.000
18-TH ORDER COEFFICIENT (H)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20-TH ORDER COEFFICIENT (I)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

FIG. 4




FIG. 5




FIG. 6



SECOND EMBODIMENT							
F number=		2.13	TTL =		4.632	f =	4.091
SURFACE NUMBER		RADIUS OF CURVATURE	THICKNESS/DISTANCE	REFRACTIVE INDEX	ABBE NUMBER	FOCAL LENGTH	
0	STOP	Infinity	0.0000				
1	FIRST LENS	1.4912	0.4317	1.547	56.1	6.479	
2		2.3126	0.1029				
3	SECOND LENS	2.5221	0.4331	1.547	56.1	4.032	
4		-16.3887	0.0300				
5	THIRD LENS	24.0000	0.2200	1.657	21.5	-6.104	
6		3.4255	0.3792				
7	FOURTH LENS	-11.2660	0.3100	1.657	21.5	-833.75	
8		-11.6280	0.4403				
9	FIFTH LENS	-1000.0000	0.5758	1.657	21.5	-279.864	
10		225.3182	0.1279				
11	SIXTH LENS	1.8859	0.4600	1.537	55.7	-9.708	
12		1.2667	0.2012				
13	FILTER	Infinity	0.2100	1.519	64.2		
14		Infinity	0.7100				
15	IMAGING PLANE	Infinity	0.0000				

FIG. 7

SURFACE NUMBER	1	2	3	4	5	6	7	8	9	10	11	12
RADIUS OF CURVATURE	1.4912	2.3126	2.5221	-16.3887	24.0000	3.4255	-11.2660	-11.6280	-1000.0000	225.3182	1.8859	1.2667
CONIC CONSTANT (K)	-0.455	0.000	0.000	0.000	0.000	10.850	0.000	0.000	0.000	0.000	-0.558	-4.789
4-TH ORDER COEFFICIENT (A)	-0.014	-0.064	-0.073	-0.047	-0.009	0.005	-0.089	-0.075	0.036	-0.004	-0.403	-0.178
6-TH ORDER COEFFICIENT (B)	0.066	-0.071	0.070	0.049	0.167	0.006	-0.034	-0.082	-0.215	-0.080	0.192	0.095
8-TH ORDER COEFFICIENT (C)	-0.349	0.070	-0.523	-0.054	-0.484	0.135	0.213	0.322	0.210	0.068	-0.060	-0.037
10-TH ORDER COEFFICIENT (D)	0.800	0.031	1.714	-0.103	0.668	-0.818	-0.311	-0.458	-0.134	-0.034	0.013	0.009
12-TH ORDER COEFFICIENT (E)	-1.073	-0.199	-2.716	0.238	-0.596	1.645	0.028	0.378	0.048	0.010	-0.002	-0.001
14-TH ORDER COEFFICIENT (F)	0.745	0.404	2.459	0.054	0.532	-1.521	0.266	-0.167	-0.010	-0.002	0.000	0.000
16-TH ORDER COEFFICIENT (G)	-0.209	-0.243	-0.971	-0.216	-0.291	0.593	-0.195	0.029	0.001	0.000	0.000	0.000
18-TH ORDER COEFFICIENT (H)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20-TH ORDER COEFFICIENT (I)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

FIG. 8




FIG. 9






FIG. 10



THIRD EMBODIMENT						
F number=	2.13	TTL =	4.632	i =	4.096	
SURFACE NUMBER		RADIUS OF CURVATURE	THICKNESS/DISTANCE	REFRACTIVE INDEX	ABBE NUMBER	FOCAL LENGTH
0	STOP	Infinity	0.0000			
1	FIRST LENS	1.4922	0.4352	1.547	56.1	6.362
2		2.3447	0.1123			
3	SECOND LENS	2.5379	0.4338	1.547	56.1	4.008
4		-15.0204	0.0300			
5	THIRD LENS	28.9334	0.2200	1.657	21.5	-6.002
6		3.4617	0.3860			
7	FOURTH LENS	-8.6033	0.3100	1.657	21.5	186.48
8		-8.1541	0.4539			
9	FIFTH LENS	-44.1018	0.5820	1.657	21.5	-63.924
10		896.5928	0.1058			
11	SIXTH LENS	1.8514	0.4600	1.537	55.7	-9.739
12		1.2484	0.2012			
13	FILTER	Infinity	0.2100	1.519	64.2	
14		Infinity	0.6916			
15	IMAGING PLANE	Infinity	0.0000			

FIG. 11

SURFACE NUMBER	1	2	3	4	5	6	7	8	9	10	11	12
RADIUS OF CURVATURE	1.4922	2.3447	2.5379	-15.0204	28.9334	3.4617	-8.6033	-8.1541	-44.1018	896.5926	1.8514	1.2484
CONIC CONSTANT (K)	-0.442	0.000	0.000	0.000	0.000	10.800	0.000	0.000	0.000	0.000	-0.579	-4.931
4-TH ORDER COEFFICIENT (A)	-0.013	-0.061	-0.071	-0.036	0.011	0.015	-0.081	-0.065	0.051	0.011	-0.412	-0.182
6-TH ORDER COEFFICIENT (B)	0.059	-0.066	0.058	0.005	0.090	-0.008	-0.076	-0.121	-0.248	-0.110	0.202	0.099
8-TH ORDER COEFFICIENT (C)	-0.316	0.078	-0.433	-0.026	-0.375	0.073	0.311	0.393	0.239	0.093	-0.064	-0.038
10-TH ORDER COEFFICIENT (D)	0.722	-0.021	1.434	0.129	0.747	-0.496	-0.450	-0.535	-0.145	-0.045	0.014	0.009
12-TH ORDER COEFFICIENT (E)	-0.965	-0.111	-2.270	-0.382	-1.060	1.012	0.145	0.426	0.050	0.013	-0.002	-0.001
14-TH ORDER COEFFICIENT (F)	0.667	0.310	2.077	0.686	1.076	-0.942	0.212	-0.182	-0.011	-0.002	0.000	0.000
16-TH ORDER COEFFICIENT (G)	-0.187	-0.199	-0.890	-0.452	-0.508	0.388	-0.183	0.030	0.001	0.000	0.000	0.000
18-TH ORDER COEFFICIENT (H)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20-TH ORDER COEFFICIENT (I)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

FIG. 12






FIG. 13




FIG. 14



FOURTH EMBODIMENT						
F number=	2.31	TTL =	4.650	f =	4.150	
SURFACE NUMBER		RADIUS OF CURVATURE	THICKNESS/DISTANCE	REFRACTIVE INDEX	ABBE NUMBER	FOCAL LENGTH
0	STOP	Infinity	0.0000			
1	FIRST LENS	1.6456	0.4118	1.547	56.1	5.410
2		3.3878	0.1598			
3	SECOND LENS	3.8660	0.4082	1.547	56.1	5.455
4		-12.4867	0.1000			
5	THIRD LENS	10.9800	0.2200	1.657	21.5	-6.393
6		3.0098	0.2752			
7	FOURTH LENS	-1000.0000	0.3100	1.657	21.5	15.92
8		-10.3344	0.5219			
9	FIFTH LENS	-1000.0000	0.7397	1.657	21.5	-762.392
10		1000.0000	0.1000			
11	SIXTH LENS	3.5396	0.4195	1.537	55.7	-5.537
12		1.5477	0.2295			
13	FILTER	Infinity	0.1100	1.516	55.1	
14		Infinity	0.6443			
15	IMAGING PLANE	Infinity	0.0000			

FIG. 15

SURFACE NUMBER	1	2	3	4	5	6	7	8	9	10	11	12
RADIUS OF CURVATURE	1.6456	3.3878	3.8660	-12.4867	10.9800	3.0098	-1000.0000	-10.3244	-1000.0000	1000.0000	3.5396	1.5477
CONIC CONSTANT (A)	-0.755	0.000	0.000	0.000	0.000	2.056	0.000	0.000	0.000	0.000	0.289	-7.783
4-TH ORDER COEFFICIENT (A)	-0.010	-0.068	-0.065	-0.162	-0.198	-0.108	-0.092	-0.087	-0.045	0.013	-0.310	-0.146
6-TH ORDER COEFFICIENT (B)	-0.034	0.003	0.053	0.221	0.413	0.260	0.169	0.095	-0.051	-0.081	0.130	0.060
8-TH ORDER COEFFICIENT (C)	0.065	0.021	-0.094	-0.184	-0.604	-0.312	-0.547	-0.166	-0.043	0.049	-0.029	-0.015
10-TH ORDER COEFFICIENT (D)	-0.174	-0.005	0.488	-0.120	0.528	0.121	1.489	0.335	0.108	-0.017	0.004	0.002
12-TH ORDER COEFFICIENT (E)	0.199	0.127	-0.666	0.660	-0.252	0.175	-2.255	-0.297	-0.094	0.004	0.000	0.000
14-TH ORDER COEFFICIENT (F)	-0.093	-0.117	0.465	-0.858	0.051	-0.247	1.729	0.114	0.038	0.000	0.000	0.000
16-TH ORDER COEFFICIENT (G)	0.012	0.025	-0.151	0.389	-0.006	0.127	-0.558	-0.016	-0.006	0.000	0.000	0.000
18-TH ORDER COEFFICIENT (H)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20-TH ORDER COEFFICIENT (I)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

FIG. 16




FIG. 17






FIG. 18



FIFTH EMBODIMENT						
F number=	2.25	TTL =	4.500	f =	4.059	
SURFACE NUMBER		RADIUS OF CURVATURE	THICKNESS/DISTANCE	REFRACTIVE INDEX	ABBE NUMBER	FOCAL LENGTH
0	STOP	Infinity	0.0000			
1	FIRST LENS	1.5269	0.4210	1.547	56.1	5.249
2		2.9502	0.1116			
3	SECOND LENS	3.0160	0.3964	1.547	56.1	6.964
4		13.9097	0.1000			
5	THIRD LENS	11.0146	0.2260	1.657	21.5	-8.818
6		3.7608	0.2662			
7	FOURTH LENS	-1000.0000	0.3100	1.657	21.5	17.91
8		-11.6079	0.4817			
9	FIFTH LENS	-1000.0000	0.5792	1.657	21.5	-686.904
10		819.7810	0.1000			
11	SIXTH LENS	3.3850	0.4722	1.537	55.7	-6.296
12		1.6077	0.2295			
13	FILTER	Infinity	0.1100	1.516	55.1	
14		Infinity	0.6963			
15	IMAGING PLANE	Infinity	0.0000			

FIG. 19

SURFACE NUMBER	1	2	3	4	5	6	7	8	9	10	11	12
RADIUS OF CURVATURE	1.5269	2.9502	3.0160	13.9097	11.0146	3.7608	-1000.0000	-11.6079	-1000.0000	519.7810	3.3850	1.6077
CONIC CONSTANT (K)	-0.690	0.000	0.000	0.000	0.000	4.678	0.000	0.000	0.000	0.000	0.308	-7.783
4-TH ORDER COEFFICIENT (A)	-0.006	-0.078	-0.057	-0.152	-0.211	-0.110	-0.103	-0.091	-0.015	0.029	-0.313	-0.149
6-TH ORDER COEFFICIENT (B)	-0.027	0.020	0.086	0.129	0.298	0.218	0.213	0.120	-0.131	-0.124	0.129	0.063
8-TH ORDER COEFFICIENT (C)	0.051	-0.045	-0.225	-0.020	-0.330	-0.107	-0.865	-0.290	0.052	0.082	-0.027	-0.016
10-TH ORDER COEFFICIENT (D)	-0.158	0.156	0.932	-0.363	0.250	-0.139	2.673	0.642	0.022	-0.032	0.003	0.002
12-TH ORDER COEFFICIENT (E)	0.181	-0.002	-1.387	1.122	-0.105	0.325	-4.407	-0.651	-0.038	0.008	0.000	0.000
14-TH ORDER COEFFICIENT (F)	-0.081	-0.106	1.101	-1.456	0.021	-0.304	3.663	0.299	0.016	-0.001	0.000	0.000
16-TH ORDER COEFFICIENT (G)	0.009	0.040	-0.395	0.706	-0.002	0.203	-1.275	-0.052	-0.003	0.000	0.000	0.000
18-TH ORDER COEFFICIENT (H)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20-TH ORDER COEFFICIENT (I)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

FIG. 20






FIG. 21




FIG. 22



SIXTH EMBODIMENT						
F number=	2.29	TTL =	4.600	f =	4.129	
SURFACE NUMBER		RADIUS OF CURVATURE	THICKNESS/DISTANCE	REFRACTIVE INDEX	ABBE NUMBER	FOCAL LENGTH
0	STOP	Infinity	0.0000			
1	FIRST LENS	1.5799	0.4185	1.547	56.1	5.238
2		3.2015	0.1402			
3	SECOND LENS	3.4645	0.4032	1.547	56.1	6.072
4		-73.5700	0.1000			
5	THIRD LENS	10.7493	0.2200	1.657	21.5	-7.313
6		3.2891	0.2762			
7	FOURTH LENS	-1000.0000	0.3100	1.657	21.5	20.74
8		-13.4188	0.4784			
9	FIFTH LENS	-1000.0000	0.6645	1.657	21.5	-762.404
10		1000.0000	0.1000			
11	SIXTH LENS	3.4707	0.4848	1.537	55.7	-6.090
12		1.6002	0.2295			
13	FILTER	Infinity	0.1100	1.519	64.2	
14		Infinity	0.6647			
15	IMAGING PLANE	Infinity	0.0000			

FIG. 23

SURFACE NUMBER	1	2	3	4	5	6	7	8	9	10	11	12
RADIUS OF CURVATURE	1.5799	3.2015	3.4645	-73.5700	10.7493	3.2891	-1000.0000	-13.4188	-1000.0000	1000.0000	3.4707	1.6002
CONIC CONSTANT (C)	-0.704	0.000	0.000	0.000	0.000	2.853	0.000	0.000	0.000	0.000	0.275	-7.783
4-TH ORDER COEFFICIENT (A)	-0.008	-0.060	-0.050	-0.161	-0.208	-0.108	-0.095	-0.088	-0.028	0.024	-0.286	-0.133
6-TH ORDER COEFFICIENT (B)	-0.008	-0.001	0.056	0.193	0.324	0.221	0.207	0.111	-0.102	-0.107	0.115	0.053
8-TH ORDER COEFFICIENT (C)	-0.047	0.000	-0.152	-0.256	-0.380	-0.179	-0.776	-0.241	0.020	0.070	-0.024	-0.013
10-TH ORDER COEFFICIENT (D)	0.096	0.076	0.669	0.287	0.303	-0.016	2.174	0.517	0.050	-0.027	0.003	0.002
12-TH ORDER COEFFICIENT (E)	-0.149	-0.002	-0.951	0.026	-0.136	0.208	-3.369	-0.506	-0.057	0.007	0.000	0.000
14-TH ORDER COEFFICIENT (F)	0.123	-0.041	0.702	-0.457	0.082	-0.216	2.641	0.222	0.026	-0.001	0.000	0.000
16-TH ORDER COEFFICIENT (G)	-0.039	0.012	-0.233	0.320	-0.003	0.130	-0.888	-0.037	-0.004	0.000	0.000	0.000
18-TH ORDER COEFFICIENT (H)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20-TH ORDER COEFFICIENT (I)	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

FIG. 24



# 1

## OPTICAL SYSTEM

### CROSS-REFERENCE TO RELATED APPLICATION

This application claims the priority and benefit under 35 USC 119(a) of Korean Patent Application No. 10-2015-0112493, filed on Aug. 10, 2015 with the Korean Intellectual Property Office, the disclosure of which is incorporated herein by reference.

### BACKGROUND

#### 1. Field

The following description relates to an optical system including lenses having refractive power.

#### 2. Description of Related Art

Over the years, camera modules have gradually been miniaturized. In addition, camera module performance has gradually improved. As an example, pixels of an image sensor have become small enough to enable realization of high resolution.

Typically, an optical system of a small camera module includes four lenses. However, it is difficult for the optical system including the four lenses to implement a clear image. Therefore, development of an optical system including five or more lenses is needed in order to enable realization of a clear image.

### SUMMARY

This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

In accordance with an embodiment, there is provided an optical system, including: a first lens including a positive refractive power; a second lens including a positive refractive power and a convex image-side surface; a third lens; a fourth lens; a fifth lens including a concave object-side surface and a concave image-side surface; and a sixth lens including an inflection point formed on an image-side surface thereof, wherein the first to sixth lenses are sequentially disposed from an object toward an imaging plane.

$f$ , an overall focal length of the optical system and,  $f_1$ , a focal length of the first lens may satisfy  $1.0 < f_1/f < 1.8$ .

$V_1$ , an Abbe number of the first lens and,  $V_2$ , an Abbe number of the second lens may satisfy  $V_1 - V_2 < 25$ .

$f$ , an overall focal length of the optical system and,  $f_2$ , a focal length of the second lens may satisfy  $0.5 < f_2/f < 2.0$ .

$f$ , an overall focal length of the optical system and,  $f_3$ , a focal length of the third lens may satisfy  $-3 < f_3/f < -1$ .

$f$ , an overall focal length of the optical system and,  $f_4$ , a focal length of the fourth lens may satisfy  $3 < |f_4/f|$ .

$f_1$ , a focal length of the first lens and,  $f_2$ , a focal length of the second lens may satisfy  $0.5 < f_1/f_2 < 2.0$ .

$f$ , an overall focal length of the optical system and,  $r_6$ , a radius of curvature of an image-side surface of the third lens may satisfy  $0.3 < r_6/f < 1.4$ .

$f$ , an overall focal length of the optical system and  $r_{10}$  a radius of curvature of an image-side surface of the fifth lens may satisfy  $30 < r_{10}/f$ .

# 2

EPD, a diameter of an entrance pupil of the optical system and,  $f_{12}$ , a synthetic focal length of the first lens and the second lens may satisfy  $0.18 < (EPD/2)/f_{12}$ .

In accordance with another embodiment, there is provided an optical system, including: a first lens including a positive refractive power; a second lens including a convex image-side surface; a third lens including a convex object-side surface; a fourth lens including a convex image-side surface; a fifth lens including a concave object-side surface and a concave image-side surface; and a sixth lens including an inflection point formed on an image-side surface thereof, wherein the first to sixth lenses are sequentially disposed from an object toward an imaging plane.

The first lens may include a convex object-side surface and a concave image-side surface.

The second lens may include a convex object-side surface.

The third lens may include a concave image-side surface.

The fourth lens may include a concave object-side surface.

The sixth lens may include a convex object-side surface and a concave image-side surface.

In accordance with another embodiment, there is provided an optical system, including: a first lens; a second lens including a convex image-side surface; a third lens including a convex object-side surface; a fourth lens including a convex image-side surface; a fifth lens including a concave object-side surface and a concave image-side surface; and a sixth lens including an inflection point formed on an image-side surface thereof, wherein the second lens has a same refractive power as a refractive power of the first lens, the third lens, the fourth lens, and the fifth lens have a refractive power higher than the refractive powers of the first and second lenses, and the sixth lens has a refractive power lower than the refractive powers of the first and second lenses.

$V_1$ , an Abbe number of the first lens,  $V_2$ , an Abbe number of the second lens,  $V_3$ , an Abbe number of the third lens, and,  $V_5$ , an Abbe number of the fifth lens may satisfy  $V_1 - V_2 < 25$ ,  $15 < |V_1 - V_3|$ , and  $25 < V_1 - V_5 < 45$ .

$f$ , an overall focal length of the optical system, and  $f_5$  a focal length of the fifth lens may satisfy  $f_5/f < -10$ .

$f$ , an overall focal length of the optical system, and TTL a distance from the object-side surface of the first lens to an imaging plane may satisfy  $TTL/f < 1.5$ .

$f_2$ , a focal length of the second lens, and,  $f_3$ , a focal length of the third lens may satisfy  $-1.2 < f_2/f_3 < 0$ .

$f$ , an overall focal length of the optical system, and, BFL, a distance from an object-side surface of the sixth lens to an imaging plane may satisfy  $BFL/f < 0.5$ .

$f$ , an overall focal length of the optical system, and,  $D_2$ , a distance from the image-side surface of the first lens to an object-side surface of the second lens may satisfy  $D_2/f < 0.1$ .

FOV, a field of view of the optical system may satisfy  $75 < FOV$ .

Other features and aspects will be apparent from the following detailed description, the drawings, and the claims.

### BRIEF DESCRIPTION OF DRAWINGS

These and/or other aspects will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings in which:

FIG. 1 is a view of an optical system, according to a first embodiment;



FIG. 2 is graphs having curves representing aberration of the optical system, according to the first embodiment;

FIG. 3 is a table representing characteristics of the optical system, according to the first embodiment;

FIG. 4 is a table representing aspherical characteristics of the optical system according to the first embodiment;

FIG. 5 is a view of an optical system, according to a second embodiment;

FIG. 6 is graphs having curves representing aberration of the optical system, according to the second embodiment;

FIG. 7 is a table representing characteristics of the optical system, according to the second embodiment;

FIG. 8 is a table representing aspherical characteristics of the optical system according to the second embodiment;

FIG. 9 is a view of an optical system, according to a third embodiment;

FIG. 10 is graphs having curves representing aberration of the optical system, according to the third embodiment;

FIG. 11 is a table representing characteristics of the optical system, according to the third embodiment;

FIG. 12 is a table representing aspherical characteristics of the optical system, according to the third embodiment;

FIG. 13 is a view of an optical system, according to a fourth embodiment;

FIG. 14 is graphs having curves representing aberration of the optical system, according to the fourth embodiment;

FIG. 15 is a table representing characteristics of the optical system, according to the fourth embodiment;

FIG. 16 is a table representing aspherical characteristics of the optical system, according to the fourth embodiment;

FIG. 17 is a view of an optical system, according to a fifth embodiment;

FIG. 18 is graphs having curves representing aberration of the optical system, according to the fifth embodiment;

FIG. 19 is a table representing characteristics of the optical system, according to the fifth embodiment;

FIG. 20 is a table representing aspherical characteristics of the optical system, according to the fifth embodiment;

FIG. 21 is a view of an optical system according to a sixth embodiment;

FIG. 22 is graphs having curves representing aberration of the optical system, according to the sixth embodiment;

FIG. 23 is a table representing characteristics of the optical system, according to the sixth embodiment; and

FIG. 24 is a table representing aspherical characteristics of the optical system, according to the sixth embodiment.

Throughout the drawings and the detailed description, unless otherwise described, the same drawing reference numerals will be understood to refer to the same elements, features, and structures. The relative size and depiction of these elements may be exaggerated for clarity, illustration, and convenience.

#### DETAILED DESCRIPTION

The following detailed description is provided to assist the reader in gaining a comprehensive understanding of the methods, apparatuses, and/or systems described herein. However, various changes, modifications, and equivalents of the methods, apparatuses, and/or systems described herein will be apparent to one of ordinary skill in the art. The sequences of operations described herein are merely examples, and are not limited to those set forth herein, but may be changed as will be apparent to one of ordinary skill in the art, with the exception of operations necessarily occurring in a certain order. Also, descriptions of functions

and constructions that are well known to one of ordinary skill in the art may be omitted for increased clarity and conciseness.

The features described herein may be embodied in different forms, and are not to be construed as being limited to the examples described herein. Rather, the examples described herein have been provided so that this disclosure will be thorough and complete, and will convey the full scope of the disclosure to one of ordinary skill in the art.

The features described herein may be embodied in different forms, and are not to be construed as being limited to the examples described herein. Rather, the examples described herein have been provided so that this disclosure will be thorough and complete, and will convey the full scope of the disclosure to one of ordinary skill in the art.

It will be understood that, although the terms first, second, third, etc. may be used herein to describe various lenses, these lenses should not be limited by these terms. These terms are only used to distinguish one lens from another lens. These terms do not necessarily imply a specific order or arrangement of the lenses. Thus, a first lens discussed below could be termed a second lens without departing from the teachings description of the various embodiments.

In addition, a surface of each lens closest to an object is referred to as a first surface or an object-side surface, and a surface of each lens closest to an imaging surface is referred to as a second surface or an image-side surface. Further, all numerical values of radii of curvature, thicknesses/distances, TTLs, and other parameters of the lenses are represented in millimeters (mm). A person skilled in the relevant art will appreciate that other units of measurement may be used. Further, in the present specification, all radii of curvature, thicknesses, OALs (optical axis distances from the first surface of the first lens to the image sensor (OALs), a distance on the optical axis between the stop and the image sensor (SLs), image heights (IMGHs) (image heights), and back focus lengths (BFLs) (back focus lengths) of the lenses, an overall focal length of an optical system, and a focal length of each lens are indicated in millimeters (mm). Further, thicknesses of lenses, gaps between the lenses, OALs, and SLs are distances measured based on an optical axis of the lenses.

In addition, in an embodiment, shapes of lenses are described and illustrated in relation to optical axis portions of the lenses.

A surface of a lens being convex means that an optical axis portion of a corresponding surface is convex, and a surface of a lens being concave means that an optical axis portion of a corresponding surface is concave. Therefore, in a configuration in which one surface of a lens is described as being convex, an edge portion of the lens may be concave. Likewise, in a configuration in which one surface of a lens is described as being concave, an edge portion of the lens may be convex. In other words, a paraxial region of a lens may be convex, while the remaining portion of the lens outside the paraxial region is either convex, concave, or flat. Further, a paraxial region of a lens may be concave, while the remaining portion of the lens outside the paraxial region is either convex, concave, or flat.

In addition, in an embodiment, thicknesses and radii of curvatures of lenses are measured in relation to optical axes of the corresponding lenses.

An optical system, according to an embodiment, includes six lenses. As an example, the optical system may include a first lens, a second lens, a third lens, a fourth lens, a fifth lens, and a sixth lens. The lens module may include from four lenses up to six lenses without departing from the scope



of the embodiments herein described. In accordance with an illustrative example, the embodiments described of the optical system include six lenses with a refractive power. However, a person of ordinary skill in the relevant art will appreciate that the number of lenses in the optical system may vary, for example, between two to six lenses, while achieving the various results and benefits described hereinbelow. Also, although each lens is described with a particular refractive power, a different refractive power for at least one of the lenses may be used to achieve the intended result. In the optical system, according to embodiments, the first to sixth lenses are formed of materials including glass, plastic or other similar types of polycarbonate materials. In another embodiment, at least one of the first through sixth lenses is formed of a material different from the materials forming the other first through sixth lenses.

The first lens has a refractive power. As an example, the first lens has a positive refractive power. An image-side surface of the first lens is concave. The first lens may have an aspherical surface. As an example, both of the object-side surface and an image-side surface of the first lens are aspherical. The first lens is formed of plastic. However, a material of the first lens is not limited to plastic.

The second lens has a refractive power. As an example, the second lens has a positive refractive power. An object-side surface or an image-side surface of the second lens is convex. The second lens may have an aspherical surface. As an example, both of the object-side surface and the image-side surface of the second lens are aspherical. The second lens may be formed of plastic. However, a material of the second lens is not limited to plastic.

The third lens has a refractive power, such as a positive refractive power or a negative refractive power. An object-side surface of the third lens is convex. The third lens may have an aspherical surface. As an example, both of the object-side surface and an image-side surface of the third lens are aspherical. The third lens may be formed of plastic. However, a material of the third lens is not limited to plastic.

The fourth lens has a refractive power. As an example, the fourth lens may have a positive refractive power. As another example, the fourth lens may also have a negative refractive power. An image-side surface of the fourth lens is convex. The fourth lens may have an aspherical surface. As an example, both of an object-side surface and the image-side surface of the fourth lens are aspherical. The fourth lens may be formed of plastic. However, a material of the fourth lens is not limited to plastic. In one example, the object-side surface of the fourth lens is concave in a paraxial region and gradually flattens at edge portions thereof.

The fifth lens has a refractive power. As an example, the fifth lens has a negative refractive power. Both surfaces of the fifth lens are concave. The fifth lens may have an aspherical surface. As an example, both of an object-side surface and an image-side surface of the fifth lens are aspherical. The fifth lens has an inflection point. As an example, one or more inflection points are formed on the image-side surface of the fifth lens. The fifth lens may be formed of plastic. However, a material of the fifth lens is not limited to plastic. In one example, the object-side surface of the fourth lens is concave in a paraxial region and gradually flattens at edge portions thereof.

The sixth lens has a refractive power. An image-side surface of the sixth lens is concave. The sixth lens may have an aspherical surface. As an example, both of an object-side surface and the image-side surface of the sixth lens are aspherical. The sixth lens has an inflection point. As an example, one or more inflection points are formed on the

image-side surface of the sixth lens. The sixth lens may be formed of plastic. However, a material of the sixth lens is not limited to plastic.

A person of ordinary skill in the relevant art will appreciate that each of the first through fifth lenses may be configured in an opposite refractive power from the configuration described above. For example, in an alternative configuration, the first lens has a negative refractive power, the second lens has a negative refractive power, the third lens has a negative refractive power, the fourth lens has a positive refractive power, the fifth lens has a positive refractive power, and the sixth lens has a negative refractive power.

The optical system includes a filter and an image sensor. The filter is disposed between the sixth lens and the image sensor. The filter may filter an infrared component from incident light refracted through the first to sixth lenses. The image sensor is disposed behind the filter, and converts the incident light refracted through the first to sixth lenses into electrical signals.

The optical system includes a stop. The stop may adjust an amount of light incident to the first to sixth lenses. As an example, the stop is disposed adjacently to the object-side surface of the first lens to adjust an amount of light incident to the first lens.

The optical system satisfies the following Conditional Expression 1:

$$1.0 < f_1/f < 1.8. \quad \text{[Conditional Expression 1]}$$

In one example,  $f$  is an overall focal length of the optical system, and  $f_1$  is a focal length of the first lens. The above Conditional Expression 1 indicates a condition that limits a magnitude of refractive power of the first lens to overall refractive power of the optical system. As an example, in a case in which  $f_1/f$  is outside of a lower limit value of the above Conditional Expression 1, the first lens has a significantly great refractive power, in such a manner that it is difficult to correct spherical aberration. As another example, in a case in which  $f_1/f$  is outside of an upper limit value of the above Conditional Expression 1, the first lens has significantly low refractive power, which is advantageous in correcting spherical aberration, but makes miniaturization of the optical system difficult.

The optical system satisfies one or more of the following Conditional Expressions 2 through 4:

$$V_1 - V_2 < 25 \quad \text{[Conditional Expression 2]}$$

$$15 < |V_1 - V_3| \quad \text{[Conditional Expression 3]}$$

$$25 < V_1 - V_5 < 45. \quad \text{[Conditional Expression 4]}$$

In an example,  $V_1$  is an Abbe number of the first lens,  $V_2$  is an Abbe number of the second lens,  $V_3$  is an Abbe number of the third lens, and  $V_5$  is an Abbe number of the fifth lens. The Conditional Expressions 2 through 4 represent or define limit conditions to correct chromatic aberration of the optical system. As an example, in a case in which  $V_1 - V_2$ ,  $|V_1 - V_3|$ , and  $V_1 - V_5$  are out of numerical ranges of the Conditional Expressions 2 through 4, respectively, the optical system has significantly high chromatic aberration, in such a manner that it is difficult to use the optical system in a camera module that needs to provide a high resolution.

The optical system satisfies the following Conditional Expression 5:

$$0.5 < f_2/f < 2.0. \quad \text{[Conditional Expression 5]}$$

In an example,  $f$  is the overall focal length of the optical system, and  $f_2$  is a focal length of the second lens. The



Conditional Expression 5 represents or defines a condition to limit a magnitude of refractive power of the second lens to the overall refractive power of the optical system. As an example, in a case in which  $f2/f$  is outside of a lower limit value of the Conditional Expression 5, the second lens has significantly great refractive power, in such a manner that it is difficult to correct spherical aberration. As another example, in a case in which  $f2/f$  is outside of an upper limit value of the Conditional Expression 5, the second lens has significantly low refractive power, which is advantageous to correct spherical aberration, but makes miniaturization of the optical system difficult.

The optical system satisfies the following Conditional Expression 6:

$$-3.0 < f3/f < -1.0. \quad [\text{Conditional Expression 6}]$$

In an example,  $f$  is the overall focal length of the optical system, and  $f3$  is a focal length of the third lens. The Conditional Expression 6 represents or defines a condition for limiting a magnitude of refractive power of the third lens to the overall refractive power of the optical system. As an example, in a case in which  $f3/f$  is outside of a lower limit value of the Conditional Expression 6, the third lens has significantly great refractive power making it difficult to correct spherical aberration. As another example, in a case in which  $f3/f$  is outside of an upper limit value of the Conditional Expression 6, the third lens has significantly low refractive power, which is advantageous in correcting spherical aberration, but makes miniaturization of the optical system difficult.

The optical system satisfies the following Conditional Expression 7:

$$3 < f4/f. \quad [\text{Conditional Expression 7}]$$

In an example,  $f$  is the overall focal length of the optical system, and  $f4$  is a focal length of the fourth lens. The Conditional Expression 7 represents or defines a condition for limiting a magnitude of refractive power of the fourth lens to the overall refractive power of the optical system. As an example, in a case in which  $f4/f$  is outside of a lower limit value of the Conditional Expression 7, the fourth lens has significantly great refractive power, in such a manner that it is difficult to correct spherical aberration.

The optical system satisfies the following Conditional Expression 8:

$$f5/f < -10. \quad [\text{Conditional Expression 8}]$$

In an embodiment,  $f$  is the overall focal length of the optical system, and  $f5$  is a focal length of the fifth lens. The Conditional Expression 8 represents or defines a condition to limit a magnitude of refractive power of the fifth lens to the overall refractive power of the optical system. As an example, in a case in which  $f5/f$  is outside of an upper limit value of the Conditional Expression 8, the fifth lens has significantly great refractive power making it difficult to correct spherical aberration.

The optical system satisfies the following Conditional Expression 9:

$$TTL/f < 1.5. \quad [\text{Conditional Expression 9}]$$

In an example,  $f$  is the overall focal length of the optical system, and  $TTL$  is a distance from the object-side surface of the first lens to an imaging plane. The Conditional Expression 9 represents or defines a condition for miniaturizing the optical system. As an example, in a case in which  $TTL/f$  is outside of an upper limit value of the Conditional Expression 9, it is difficult to mount the optical system in a small portable terminal.

The optical system satisfies the following Conditional Expression 10:

$$0.5 < f1/f2 < 2.0. \quad [\text{Conditional Expression 10}]$$

In one example,  $f1$  is the focal length of the first lens, and  $f2$  is the focal length of the second lens. The Conditional Expression 10 represents or defines a condition for limiting a ratio of refractive power between the first lens and the second lens. As an example, in a case in which  $f1/f2$  is outside of a numerical range of the Conditional Expression 10, refractive power of the first lens or the second lens is significantly great making it difficult to correct aberration.

The optical system satisfies the following Conditional Expression 11:

$$-1.2 < f2/f3 < 0. \quad [\text{Conditional Expression 11}]$$

In an embodiment,  $f2$  is the focal length of the second lens, and  $f3$  is the focal length of the third lens. The Conditional Expression 11 represents or defines a condition to limit a ratio of refractive power between the second lens and the third lens. As an example, in a case in which  $f2/f3$  is outside of a numerical range of the Conditional Expression 11, refractive power of the second lens or the third lens is significantly great, in such a manner that it is difficult to correct aberration.

The optical system satisfies the following Conditional Expression 12:

$$BFL/f < 0.5. \quad [\text{Conditional Expression 12}]$$

In one example,  $f$  is the overall focal length of the optical system, and  $BFL$  is a distance from the object-side surface of the sixth lens to the imaging plane. The Conditional Expression 12 represents or defines a condition for miniaturizing the optical system. As an example, in a case in which  $BFL/f$  is outside of an upper limit value of the Conditional Expression 12, it is difficult to miniaturize the optical system.

The optical system satisfies the following Conditional Expression 13:

$$D2/f < 0.1. \quad [\text{Conditional Expression 13}]$$

In an example,  $f$  is the overall focal length of the optical system, and  $D2$  is a distance from the image-side surface of the first lens to the object-side surface of the second lens.

The Conditional Expression 13 represents or defines a condition for improving longitudinal chromatic aberration characteristics. As an example, in a case in which  $D2/f$  is outside of an upper limit value of the Conditional Expression 13, longitudinal chromatic aberration characteristics of the first lens and the second lens deteriorate.

The optical system satisfies the following Conditional Expression 14:

$$0.3 < r6/f < 1.4. \quad [\text{Conditional Expression 14}]$$

In an embodiment,  $f$  is the overall focal length of the optical system, and  $r6$  is a radius of curvature of the image-side surface of the third lens. The above Conditional Expression 14 represents or defines a condition to limit refractive power of the third lens. As an example, in a case in which  $r6/f$  is outside of a numerical range of the Conditional Expression 14, it is not easy to manufacture the third lens, and it is difficult to secure the required refractive power.

The optical system satisfies the following Conditional Expression 15:

$$30 < r10/f. \quad [\text{Conditional Expression 15}]$$



In an example,  $f$  is the overall focal length of the optical system, and  $r_{10}$  is a radius of curvature of the image-side surface of the fifth lens. The above Conditional Expression represents or defines a condition for limiting refractive power of the fifth lens. As an example, in a case in which  $r_{10}/f$  is outside of a numerical range of the Conditional Expression 15, it is not easy to manufacture the fifth lens, and it is difficult to secure the required refractive power.

The optical system satisfies the following Conditional Expression 16:

$$0.18 < (EPD/2)/f_{12}. \quad [\text{Conditional Expression 16}]$$

In one embodiment, EPD is a diameter of an entrance pupil of the optical system, and  $f_{12}$  is a synthetic focal length of the first lens and the second lens. The above Conditional Expression represents or defines a condition for realizing an optical system capable of realizing bright images. As an example, in a case in which EPD/2 is outside of a lower limit value of the Conditional Expression 16, it is difficult to secure an amount of light incident to the image sensor, in such a manner that the optical system may not be adequately used in a camera module and produce high resolution.

The optical system satisfies one or more of the following Conditional Expressions 17 and 18:

$$75 < FOV \quad [\text{Conditional Expression 17}]$$

$$F \text{ number} < 2.3. \quad [\text{Conditional Expression 18}]$$

In an example, FOV is a field of view of the optical system.

In the optical system configured as described above, strong positive refractive power is dispersed to the first lens and the second lens. In addition, in the optical system according to an embodiment, tolerance sensitivity of the first lens is reduced, and a phenomenon that a radius of curvature of the object-side surface of the first lens becomes excessively low is alleviated.

Also, in one embodiment, each of the first to sixth lenses may be separate lenses configured as described above. A distance between lenses may vary. In another embodiment, at least one of the first to sixth lenses may be operatively connected or in contact with another one of the first to sixth lenses.

In a further alternative embodiment, two or more of the lenses of the first to sixth lenses may be configured as a group and in operative connection or contact with another lens. For instance, the first, second, and third lenses may be in contact with each other as a first group lens, while the fourth, fifth, and sixth lenses are configured separate from each other and from the first group lens. In the alternative, the first, second, and third lenses may be in contact with each other as a first group lens, the fourth and the fifth lenses may be in contact with each other as a second group lens, and the sixth lens is configured separate from the first and second group lenses.

Next, several embodiments will be described.

An optical system, according to a first embodiment will be described with reference to FIG. 1.

The optical system 100, according to an embodiment, includes first to sixth lenses 110 to 160. The first to sixth lenses 110 to 160 are sequentially disposed from an object toward an imaging plane.

The first lens 110 has a positive refractive power. An object-side surface of the first lens 110 is convex, and an image-side surface thereof is concave. For example, a first surface of the first lens 110 is convex in a paraxial region,

and a second surface of the first lens 110 is concave in the paraxial region. The first lens 110 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the first lens 110 are aspherical. In one example, the first lens 110 is formed of a material having a refractive index of 1.547. A focal length of the first lens 110 may be 6.430 mm.

The second lens 120 has a positive refractive power. An object-side surface of the second lens 120 is convex, and an image-side surface thereof is convex. In one example, the first and second surfaces of the second lens are convex in the paraxial region. The second lens 120 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the second lens 120 are aspherical. The second lens 120 is formed of a material that is substantially the same as or similar to that of the first lens. As an example, the second lens 120 has a refractive power of 1.547, which is the same as that of the first lens. A focal length of the second lens 120 may be 4.024 mm.

The third lens 130 has a negative refractive power. An object-side surface of the third lens 130 is convex, and an image-side surface thereof is concave. For example, a first surface of the third lens 130 is convex in the paraxial region, and a second surface of the third lens 130 is concave in the paraxial region. The third lens 130 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the third lens 130 are aspherical. The third lens 130 has a refractive power higher than those of the first and second lenses. As an example, the refractive power of the third lens 130 is 1.657, which is higher than those of the first and second lenses. A focal length of the third lens 130 may be  $-6.017$  mm.

The fourth lens 140 has a positive refractive power. An object-side surface of the fourth lens 140 is concave, and an image-side surface thereof may be convex. For example, a first surface of the fourth lens 140 is concave in the paraxial region, and a second surface of the fourth lens 140 is convex in the paraxial region. The fourth lens 140 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fourth lens 140 are aspherical. The fourth lens 140 has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fourth lens 140 is 1.657, which is higher than those of the first and second lenses. A focal length of the fourth lens 140 may be 347.95 mm.

The fifth lens 150 has a negative refractive power. An object-side surface of the fifth lens 150 is concave, and an image-side surface thereof is concave. For example, a first surface of the fifth lens 150 is concave in the paraxial region, and a second surface of the fifth lens 150 is concave in the paraxial region. The fifth lens 150 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fifth lens 150 are aspherical. An inflection point is formed on the fifth lens 150. As an example, one or more inflection points are formed on the image-side surface of the fifth lens 150. The fifth lens 150 has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fifth lens 150 is 1.657, which is higher than those of the first and second lenses. A focal length of the fifth lens 150 may be  $-120.555$  mm.

The sixth lens 160 has a negative refractive power. An object-side surface of the sixth lens 160 is convex, and an image-side surface thereof is concave. For example, a first surface of the sixth lens 160 is convex in the paraxial region, and a second surface of the sixth lens 160 is concave in the paraxial region. The sixth lens 160 has an aspherical shape.



## 11

As an example, both of the object-side surface and the image-side surface of the sixth lens **160** are aspherical. An inflection point is formed on the sixth lens **160**. As an example, one or more inflection points is formed on the object-side surface and the image-side surface of the sixth lens **160**. The sixth lens **160** has a low refractive power. As an example, the refractive index of the sixth lens **160** is 1.537, which is lower than those of the first and second lenses. A focal length of the sixth lens **160** may be  $-9.940$  mm.

The optical system **100** includes a filter **170** and an image sensor **180**.

The filter **170** is adjacently disposed to the image-side surface of the sixth lens **160**. The filter **170** has a substantially flat plate. The filter **170** filters infrared rays from light refracted from the sixth lens **160**.

The image sensor **180** is disposed behind the filter **170**. The image sensor **180** has a predetermined size. As an example, a distance (Img HT) (see FIG. 2) from an intersection point between an imaging plane of the image sensor **180** and an optical axis to a diagonal corner of the image sensor **180** may be 3.26 mm.

The optical system **100** includes a stop ST. The stop ST may be disposed adjacently to the object-side surface of the first lens **110**. However, a person skill in the art will appreciate that the stop ST may be positioned in between two of the lenses **110** to **160**.

The optical system **100** configured as described above represent aberration characteristics and optical characteristics as illustrated in FIGS. 2 and 3. As an example, an F number of the optical system **100** according to an embodiment may be 2.13, an overall length (TTL), which is a distance from the object-side surface of the first lens to the imaging plane of the optical system **100**, is 4.632 mm, an overall focal length of the optical system **100** is 4.083 mm, EPD/2 of the optical system **100** is 0.96 mm, and f12 is 2.68082 mm. For reference, FIG. 4 is a table representing aspherical coefficients of the optical system **100**.

An optical system, according to a second embodiment, will be described with reference to FIG. 5.

The optical system **200**, according to an embodiment, includes first to sixth lenses **210** to **260**. The first to sixth lenses **210** to **260** are sequentially disposed from an object toward an imaging plane.

The first lens **210** has a positive refractive power. An object-side surface of the first lens **210** is convex, and an image-side surface thereof is concave. The first lens **210** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the first lens **210** are aspherical. The first lens **210** may be formed of a material having a refractive index of 1.547. A focal length of the first lens **210** may be 6.479 mm.

The second lens **220** has a positive refractive power. An object-side surface of the second lens **220** is convex, and an image-side surface thereof is convex. The second lens **220** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the second lens **220** are aspherical. The second lens **220** is formed of a material that is substantially the same as or similar to that of the first lens. As an example, the second lens **220** has a refractive index of 1.547, which is the same as that of the first lens. A focal length of the second lens **220** may be 4.032 mm.

The third lens **230** has a negative refractive power. An object-side surface of the third lens **230** is convex, and an image-side surface thereof is concave. The third lens **230** has an aspherical shape. As an example, both of the object-side

## 12

surface and the image-side surface of the third lens **230** are aspherical. The third lens **230** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the third lens **230** may be 1.657, which is higher than those of the first and second lenses. A focal length of the third lens **230** may be  $-6.104$  mm.

The fourth lens **240** has a negative refractive power. An object-side surface of the fourth lens **240** is concave, and an image-side surface thereof is convex. The fourth lens **240** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fourth lens **240** are aspherical. The fourth lens **240** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fourth lens **240** is 1.657, which is higher than those of the first and second lenses. A focal length of the fourth lens **240** may be  $-833.75$  mm.

The fifth lens **250** has a negative refractive power. An object-side surface of the fifth lens **250** is concave, and an image-side surface thereof is concave. The fifth lens **250** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fifth lens **250** are aspherical. An inflection point is formed on the fifth lens **250**. As an example, one or more inflection points is formed on the image-side surface of the fifth lens **250**. The fifth lens **250** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fifth lens **250** is 1.657, which is higher than those of the first and second lenses. A focal length of the fifth lens **250** may be  $-279.664$  mm.

The sixth lens **260** has a negative refractive power. An object-side surface of the sixth lens **260** is convex, and an image-side surface thereof is concave. The sixth lens **260** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the sixth lens **260** are aspherical. An inflection point is formed on the sixth lens **260**. As an example, one or more inflection points is formed on the object-side surface and the image-side surface of the sixth lens **260**. The sixth lens **260** has a low refractive index. As an example, the refractive index of the sixth lens **260** may be 1.537, which is lower than those of the first and second lenses. A focal length of the sixth lens **260** may be  $-9.708$  mm.

The optical system **200** may include a filter **270** and an image sensor **280**.

The filter **270** may be disposed adjacently to the image-side surface of the sixth lens **260**. The filter **270** may have a substantially flat plate. The filter **270** filters infrared rays from light refracted from the sixth lens **260**.

The image sensor **280** may be disposed behind the filter **270**. The image sensor **280** has a predetermined size. As an example, a distance (Img HT) (see FIG. 6) from an intersection point between an imaging plane of the image sensor **280** and an optical axis to a diagonal corner of the image sensor **280** is 3.26 mm.

The optical system **200** may include a stop ST. The stop ST may be disposed adjacently to the object-side surface of the first lens **210**.

The optical system **200** configured as described above, represents aberration characteristics and optical characteristics as illustrated in FIGS. 6 and 7. As an example, an F number of the optical system **200**, according to an embodiment, may be 2.13, an overall length (TTL), which is a distance from the object-side surface of the first lens to the imaging plane, of the optical system **200** is 4.632 mm, an overall focal length of the optical system **200** is 4.091 mm, EPD/2 of the optical system **200** is 0.96 mm, and f12 is



2.69113 mm. For reference, FIG. 8 is a table representing aspherical coefficients of the optical system 200.

An optical system, according to a third embodiment, will be described with reference to FIG. 9.

The optical system 300, according to an embodiment, includes first to sixth lenses 310 to 360. The first to sixth lenses 310 to 360 are sequentially disposed from an object toward an imaging plane.

The first lens 310 has a positive refractive power. An object-side surface of the first lens 310 is convex, and an image-side surface thereof is concave. The first lens 310 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the first lens 310 are aspherical. The first lens 310 is formed of a material having a refractive index of 1.547. A focal length of the first lens 310 may be 6.362 mm.

The second lens 320 has a positive refractive power. An object-side surface of the second lens 320 is convex, and an image-side surface thereof is convex. The second lens 320 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the second lens 320 are aspherical. The second lens 320 is formed of a material that is substantially the same as or similar to that of the first lens. As an example, the second lens 320 has a refractive power of 1.547, which is the same as that of the first lens. A focal length of the second lens 320 may be 4.008 mm.

The third lens 330 has a negative refractive power. An object-side surface of the third lens 330 is convex, and an image-side surface thereof is concave. The third lens 330 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the third lens 330 are aspherical. The third lens 330 has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the third lens 330 is 1.657, which is higher than those of the first and second lenses. A focal length of the third lens 330 may be -6.002 mm.

The fourth lens 340 has a positive refractive power. An object-side surface of the fourth lens 340 is concave, and an image-side surface thereof is convex. The fourth lens 340 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fourth lens 340 are aspherical. The fourth lens 340 has a refractive index higher than those of the first and second lenses. As an example, refractive index of the fourth lens 340 is 1.657, which is higher than those of the first and second lenses. A focal length of the fourth lens 340 may be 186.48 mm.

The fifth lens 350 has a negative refractive power. An object-side surface of the fifth lens 350 is concave, and an image-side surface thereof is concave. The fifth lens 350 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fifth lens 350 are aspherical. An inflection point is formed on the fifth lens 350. As an example, one or more inflection points is formed on the image-side surface of the fifth lens 350. The fifth lens 350 has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fifth lens 350 is 1.657, which is higher than those of the first and second lenses. A focal length of the fifth lens 350 may be -63.924 mm.

The sixth lens 360 has a negative refractive power. An object-side surface of the sixth lens 360 is convex, and an image-side surface thereof is concave. The sixth lens 360 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the sixth lens 360 are aspherical. An inflection point is formed on the sixth lens 360. As an example, one or more inflection points is formed

on the object-side surface and the image-side surface of the sixth lens 360. The sixth lens 360 has a low refractive index. As an example, the refractive index of the sixth lens 360 is 1.537, which is lower than those of the first and second lenses. A focal length of the sixth lens 360 may be -9.739 mm.

The optical system 300 may include a filter 370 and an image sensor 380.

The filter 370 may be disposed adjacently to the image-side surface of the sixth lens 360. The filter 370 may have a substantially flat plate. The filter 370 may filter infrared rays from light refracted from the sixth lens 360.

The image sensor 380 may be disposed behind the filter 370. The image sensor 380 has a predetermined size. As an example, a distance (Img HT) (see FIG. 10) from an intersection point between an imaging plane of the image sensor 380 and an optical axis to a diagonal corner of the image sensor 380 may be 3.26 mm.

The optical system 300 may include a stop ST. The stop ST may be disposed adjacently to the object-side surface of the first lens 310.

The optical system 300 configured as described above represents aberration characteristics and optical characteristics as illustrated in FIGS. 10 and 11. As an example, an F number of the optical system 300, according to an embodiment, is 2.13, an overall length (TTL), which is a distance from the object-side surface of the first lens to the imaging plane, of the optical system 300 is 4.632 mm, an overall focal length of the optical system 300 is 4.096 mm, EPD/2 of the optical system 300 is 0.96 mm, and f12 is 2.66683 mm. For reference, FIG. 12 is a table representing aspherical coefficients of the optical system 300.

An optical system, according to a fourth embodiment, will be described with reference to FIG. 13.

The optical system 400, according to an embodiment, includes first to sixth lenses 410 to 460. The first to sixth lenses 410 to 460 are sequentially disposed from an object toward an imaging plane.

The first lens 410 has a positive refractive power. An object-side surface of the first lens 410 is convex, and an image-side surface thereof is concave. The first lens 410 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the first lens 410 are aspherical. The first lens 410 is formed of a material having a refractive index of 1.547. A focal length of the first lens 410 may be 5.410 mm.

The second lens 420 has a positive refractive power. An object-side surface of the second lens 420 is convex, and an image-side surface thereof is convex. The second lens 420 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the second lens 420 are aspherical. The second lens 420 is formed of a material that is substantially the same as or similar to that of the first lens. As an example, the second lens 420 has a refractive index of 1.547, which is the same as that of the first lens. A focal length of the second lens 420 may be 5.455 mm.

The third lens 430 has a negative refractive power. An object-side surface of the third lens 430 is convex, and an image-side surface thereof is concave. The third lens 430 has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the third lens 430 are aspherical. The third lens 430 has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the third lens 430 is 1.657, which is higher than those of the first and second lenses. A focal length of the third lens 430 may be -6.393 mm.



The fourth lens **440** has a positive refractive power. An object-side surface of the fourth lens **440** is concave, and an image-side surface thereof is convex. The fourth lens **440** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fourth lens **440** are aspherical. The fourth lens **440** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fourth lens **440** may be 1.657, which is higher than those of the first and second lenses. A focal length of the fourth lens **440** may be 15.92 mm.

The fifth lens **450** has a negative refractive power. An object-side surface of the fifth lens **450** is concave, and an image-side surface thereof is concave. The fifth lens **450** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fifth lens **450** are aspherical. An inflection point is formed on the fifth lens **450**. As an example, one or more inflection points is formed on the image-side surface of the fifth lens **450**. The fifth lens **450** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fifth lens **450** is 1.657, which is higher than those of the first and second lenses. A focal length of the fifth lens **450** may be -762.392 mm.

The sixth lens **460** has a negative refractive power. An object-side surface of the sixth lens **460** is convex, and an image-side surface thereof is concave. The sixth lens **460** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the sixth lens **460** are aspherical. An inflection point is formed on the sixth lens **460**. As an example, one or more inflection points is formed on the object-side surface and the image-side surface of the sixth lens **460**. The sixth lens **460** has a low refractive index. As an example, the refractive index of the sixth lens **460** is 1.537, which is lower than those of the first and second lenses. A focal length of the sixth lens **460** may be -5.537 mm.

The optical system **400** may include a filter **470** and an image sensor **480**.

The filter **470** may be disposed adjacently to the image-side surface of the sixth lens **460**. The filter **470** may have a substantially flat plate. The filter **470** may filter infrared rays from light refracted from the sixth lens **460**.

The image sensor **480** may be disposed behind the filter **470**. The image sensor **480** has a predetermined size. As an example, a distance (Img HT) (see FIG. 14) from an intersection point between an imaging plane of the image sensor **480** and an optical axis to a diagonal corner of the image sensor **480** is 3.43 mm.

The optical system **400** may include a stop ST. The stop ST may be disposed adjacently to the object-side surface of the first lens **410**.

The optical system **400** configured as described above represents aberration characteristics and optical characteristics as illustrated in FIGS. 14 and 15. As an example, an F number of the optical system **400**, according to an embodiment, is 2.31, an overall length (TTL), which is a distance from the object-side surface of the first lens to the imaging plane of the optical system **400** is 4.650 mm, an overall focal length of the optical system **400** is 4.150 mm, EPD/2 of the optical system **400** is 0.90 mm, and f12 is 2.90358 mm. For reference, FIG. 16 is a table representing aspherical coefficients of the optical system **400**.

An optical system, according to a fifth embodiment, will be described with reference to FIG. 17.

The optical system **500**, according to an embodiment, includes first to sixth lenses **510** to **560**. The first to sixth lenses **510** to **560** are sequentially disposed from an object toward an imaging plane.

The first lens **510** has a positive refractive power. An object-side surface of the first lens **510** is convex, and an image-side surface thereof is concave. The first lens **510** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the first lens **510** are aspherical. The first lens **510** may be formed of a material having a refractive index of 1.547. A focal length of the first lens **510** may be 5.249 mm.

The second lens **520** has a positive refractive power. An object-side surface of the second lens **520** is convex, and an image-side surface thereof is concave. In an alternative configuration, the second lens **520** includes an object-side surface that is convex, and an image-side surface thereof is flat or substantially flat.

The second lens **520** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the second lens **520** are aspherical. The second lens **520** is formed of a material that is substantially the same as or similar to that of the first lens. As an example, the second lens **520** has a refractive index of 1.547, which is the same as that of the first lens. A focal length of the second lens **520** may be 6.964 mm.

The third lens **530** has a negative refractive power. An object-side surface of the third lens **530** is convex, and an image-side surface thereof is concave. The third lens **530** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the third lens **530** are aspherical. The third lens **530** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the third lens **530** is 1.657, which is higher than those of the first and second lenses. A focal length of the third lens **530** may be -8.818 mm.

The fourth lens **540** has a positive refractive power. An object-side surface of the fourth lens **540** is concave, and an image-side surface thereof is convex. The fourth lens **540** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fourth lens **540** are aspherical. The fourth lens **540** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fourth lens **540** is 1.657, which is higher than those of the first and second lenses. A focal length of the fourth lens **540** may be 17.91 mm.

The fifth lens **550** has a negative refractive power. An object-side surface of the fifth lens **550** is concave, and an image-side surface thereof is concave. The fifth lens **550** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fifth lens **550** are aspherical. An inflection point is formed on the fifth lens **550**. As an example, one or more inflection points is formed on the image-side surface of the fifth lens **550**. The fifth lens **550** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fifth lens **550** is 1.657, which is higher than those of the first and second lenses. A focal length of the fifth lens **550** may be -686.904 mm.

The sixth lens **560** has a negative refractive power. An object-side surface of the sixth lens **560** is convex, and an image-side surface thereof is concave. The sixth lens **560** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the sixth lens **560** are aspherical. An inflection point is formed on the sixth lens **560**. As an example, one or more inflection points is formed on the object-side surface and the image-side surface of the



sixth lens **560**. The sixth lens **560** has a low refractive index. As an example, the refractive index of the sixth lens **560** is 1.537, which is lower than those of the first and second lenses. A focal length of the sixth lens **560** may be  $-6.296$  mm.

The optical system **500** may include a filter **570** and an image sensor **580**.

The filter **570** may be disposed adjacently to the image-side surface of the sixth lens **560**. The filter **570** may have a substantially flat plate. The filter **570** may filter infrared rays from light refracted from the sixth lens **560**.

The image sensor **580** may be disposed behind the filter **570**. The image sensor **580** may have a predetermined size. As an example, a distance (Img HT) (see FIG. **18**) from an intersection point between an imaging plane of the image sensor **580** and an optical axis to a diagonal corner of the image sensor **580** is  $3.43$  mm.

The optical system **500** may include a stop ST. The stop ST may be disposed adjacently to the object-side surface of the first lens **510**.

The optical system **500** configured as described above represents aberration characteristics and optical characteristics as illustrated in FIGS. **18** and **19**. As an example, an F number of the optical system **500**, according to an embodiment, is 2.25, an overall length (TTL), which is a distance from the object-side surface of the first lens to the imaging plane of the optical system **500**, is  $4.500$  mm, an overall focal length of the optical system **500** is  $4.059$  mm, EPD/2 of the optical system **500** is  $0.90$  mm, and f12 is  $3.13502$  mm. For reference, FIG. **20** is a table representing aspherical coefficients of the optical system **500**.

An optical system, according to a sixth embodiment, will be described with reference to FIG. **21**.

The optical system **600**, according to an embodiment, includes first to sixth lenses **610** to **660**. The first to sixth lenses **610** to **660** are sequentially disposed from an object toward an imaging plane.

The first lens **610** has a positive refractive power. An object-side surface of the first lens **610** is convex, and an image-side surface thereof is concave. The first lens **610** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the first lens **610** are aspherical. The first lens **610** is formed of a material having a refractive index of 1.547. A focal length of the first lens **610** may be  $5.236$  mm.

The second lens **620** has a positive refractive power. An object-side surface of the second lens **620** is convex, and an image-side surface thereof is convex. The second lens **620** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the second lens **620** are aspherical. The second lens **620** is formed of a material that is substantially the same as or similar to that of the first lens. As an example, the second lens **620** has a refractive index of 1.547, which is the same as that of the first lens. A focal length of the second lens **620** may be  $6.072$  mm.

The third lens **630** has a negative refractive power. An object-side surface of the third lens **630** is convex, and an image-side surface thereof is concave. The third lens **630** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the third lens **630** are aspherical. The third lens **630** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the third lens **630** is 1.657, which is higher than those of the first and second lenses. A focal length of the third lens **630** may be  $-7.313$  mm.

The fourth lens **640** has a positive refractive power. An object-side surface of the fourth lens **640** is concave, and an image-side surface thereof is convex. The fourth lens **640** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fourth lens **640** are aspherical. The fourth lens **640** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fourth lens **640** is 1.657, which is higher than those of the first and second lenses. A focal length of the fourth lens **640** may be  $20.74$  mm.

The fifth lens **650** has a negative refractive power. An object-side surface of the fifth lens **650** is concave, and an image-side surface thereof is concave. The fifth lens **650** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the fifth lens **650** are aspherical. An inflection point is formed on the fifth lens **650**. As an example, one or more inflection points is formed on the image-side surface of the fifth lens **650**. The fifth lens **650** has a refractive index higher than those of the first and second lenses. As an example, the refractive index of the fifth lens **650** is 1.657, which is higher than those of the first and second lenses. A focal length of the fifth lens **650** may be  $-762.404$  mm.

The sixth lens **660** has a negative refractive power. An object-side surface of the sixth lens **660** is convex, and an image-side surface thereof is concave. The sixth lens **660** has an aspherical shape. As an example, both of the object-side surface and the image-side surface of the sixth lens **660** are aspherical. An inflection point is formed on the sixth lens **660**. As an example, one or more inflection points is formed on the object-side surface and the image-side surface of the sixth lens **660**. The sixth lens **660** has a low refractive index. As an example, the refractive index of the sixth lens **660** is 1.537, which is lower than those of the first and second lenses. A focal length of the sixth lens **660** may be  $-6.090$  mm.

The optical system **600** may include a filter **670** and an image sensor **680**.

The filter **670** may be disposed adjacently to the image-side surface of the sixth lens **660**. The filter **670** may have a substantially flat plate. The filter **670** may filter infrared rays from light refracted from the sixth lens **660**.

The image sensor **680** may be disposed behind the filter **670**. The image sensor **680** has a predetermined size. As an example, a distance (Img HT) (see FIG. **22**) from an intersection point between an imaging plane of the image sensor **680** and an optical axis to a diagonal corner of the image sensor **680** is  $3.43$  mm.

The optical system **600** may include a stop ST. The stop ST may be disposed adjacently to the object-side surface of the first lens **610**.

The optical system **600** configured as described above represents aberration characteristics and optical characteristics as illustrated in FIGS. **22** and **23**. As an example, an F number of the optical system **600**, according to an embodiment, is 2.29, an overall length (TTL), which is a distance from the object-side surface of the first lens to the imaging plane of the optical system **600**, is  $4.600$  mm, an overall focal length of the optical system **600** is  $4.129$  mm, EPD/2 of the optical system **600** is  $0.90$  mm, and f12 is  $2.98069$  mm. For reference, FIG. **24** is a table representing aspherical coefficients of the optical system **600**.

The optical systems, according to the first to sixth embodiments configured as described above, satisfy all of the Conditional Expressions 1 through 18, as represented in Table 1.



TABLE 1

Remark	Conditional Expression	First Embodiment	Second Embodiment	Third Embodiment	Fourth Embodiment	Fifth Embodiment	Sixth Embodiment
1	$1 < f1/f < 1.8$	1.575	1.584	1.553	1.304	1.293	1.268
2	$V1-V2 < 25$	0.0	0.0	0.0	0.0	0.0	0.0
3	$15 <  V1-V3 $	34.60	34.60	34.60	34.60	34.60	34.60
4	$25 < V1-V5 < 45$	34.60	34.60	34.60	34.60	34.60	34.60
5	$0.5 < f2/f < 2.0$	0.986	0.986	0.978	1.315	1.716	1.470
6	$-3 < f3/f < -1$	-1.474	-1.492	-1.465	-1.541	-2.172	-1.771
7	$3 <  f4/f $	85.214	203.786	45.523	3.837	4.412	5.023
8	$f5/f < -10$	-29.525	-68.356	-15.605	-183.709	-169.238	-184.633
9	$TTL/f < 1.5$	1.134	1.132	1.131	1.120	1.109	1.114
10	$0.5 < f1/f2 < 2.0$	1.598	1.607	1.588	0.992	0.754	0.862
11	$-1.2 < f2/f3 < 0$	-0.669	-0.661	-0.668	-0.853	-0.790	-0.830
12	$BFL/f < 0.5$	0.273	0.274	0.269	0.237	0.255	0.243
13	$D2/f < 0.5$	0.025	0.025	0.027	0.039	0.027	0.034
14	$0.3 < r6/f < 1.4$	0.839	0.837	0.845	0.725	0.927	0.797
15	$30 < r10/f$	244.906	55.073	218.873	240.964	201.976	242.172
16	$0.18 < (EPD/2)/f12$	0.358	0.357	0.360	0.310	0.287	0.302
17	$75 < FOV$	75.30	75.10	75.10	77.40	78.70	77.70
18	$F \text{ number} < 2.3$	2.130	2.130	2.130	2.310	2.250	2.290

As set forth above, the optical system, according to an embodiment, photographs a clear image.

While this disclosure includes specific examples, it will be apparent to one of ordinary skill in the art that various changes in form and details may be made in these examples without departing from the spirit and scope of the claims and their equivalents. The examples described herein are to be considered in a descriptive sense only, and not for purposes of limitation. Descriptions of features or aspects in each example are to be considered as being applicable to similar features or aspects in other examples. Suitable results may be achieved if the described techniques are performed in a different order, and/or if components in a described system, architecture, device, or circuit are combined in a different manner and/or replaced or supplemented by other components or their equivalents. Therefore, the scope of the disclosure is defined not by the detailed description, but by the claims and their equivalents, and all variations within the scope of the claims and their equivalents are to be construed as being included in the disclosure.

What is claimed is:

1. An optical system, comprising:
  - a first lens comprising a positive refractive power;
  - a second lens comprising a positive refractive power and a convex image-side surface in a paraxial region;
  - a third lens;
  - a fourth lens;
  - a fifth lens comprising a concave object-side surface in a paraxial region and a concave image-side surface in the paraxial region; and
  - a sixth lens comprising an inflection point formed on an image-side surface thereof,
 wherein the first to sixth lenses are sequentially disposed from an object toward an imaging plane,
  - $f$ , an overall focal length of the optical system, and  $f1$ , a focal length of the first lens, satisfy  $1.0 < f1/f < 1.8$ ,
  - $f$ , and  $f5$  a focal length of the fifth lens, satisfy  $f5/f < -10$ ;
  - $f2$ , a focal length of the second lens, and,  $f3$ , a focal length of the third lens satisfy  $-1.2 < f2/f3 < 0$ , and
  - $f$ , and  $r10$ , a radius of curvature of an image-side surface of the fifth lens, satisfy  $30 < r10/f$ .
2. The optical system of claim 1, wherein,  $V1$ , an Abbe number of the first lens and,  $V2$ , an Abbe number of the second lens satisfy  $V1-V2 < 25$ .

3. The optical system of claim 1, wherein,  $f$ , an overall focal length of the optical system and,  $f2$ , a focal length of the second lens satisfy  $0.5 < f2/f < 2.0$ .

4. The optical system of claim 1, wherein,  $f$ , an overall focal length of the optical system and,  $f3$ , a focal length of the third lens satisfy  $-3 < f3/f < -1$ .

5. The optical system of claim 1, wherein,  $f$ , an overall focal length of the optical system and,  $f4$ , a focal length of the fourth lens satisfy  $3 < |f4/f|$ .

6. The optical system of claim 1, wherein,  $f1$ , a focal length of the first lens and,  $f2$ , a focal length of the second lens satisfy  $0.5 < f1/f2 < 2.0$ .

7. The optical system of claim 1, wherein,  $f$ , an overall focal length of the optical system and,  $r6$ , a radius of curvature of an image-side surface of the third lens satisfy  $0.3 < r6/f < 1.4$ .

8. The optical system of claim 1, wherein,  $EPD$ , a diameter of an entrance pupil of the optical system and,  $f12$ , a synthetic focal length of the first lens and the second lens satisfy  $0.18 < (EPD/2)/f12$ .

9. An optical system, comprising:

- a first lens comprising a positive refractive power;
  - a second lens comprising a convex image-side surface in a paraxial region;
  - a third lens comprising a convex object-side surface in the paraxial region;
  - a fourth lens comprising a convex image-side surface in the paraxial region;
  - a fifth lens comprising a concave object-side surface in the paraxial region and a concave image-side surface in the paraxial region; and
  - a sixth lens comprising an inflection point formed on an image-side surface thereof,
- wherein the first to sixth lenses are sequentially disposed from an object toward an imaging plane,
- $f$ , an overall focal length of the optical system, and  $f1$ , a focal length of the first lens, satisfy  $1.0 < f1/f < 1.8$ ,
  - $f$ , and  $f5$  a focal length of the fifth lens, satisfy  $f5/f < -10$ ;
  - $f2$ , a focal length of the second lens, and,  $f3$ , a focal length of the third lens satisfy  $-1.2 < f2/f3 < 0$ ,
  - $f$ , and  $r10$ , a radius of curvature of an image-side surface of the fifth lens, satisfy  $30 < r10/f$ .

10. The optical system of claim 9, wherein the first lens comprises a convex object-side surface and a concave image-side surface.

## 21

11. The optical system of claim 9, wherein the second lens comprises a convex object-side surface.

12. The optical system of claim 9, wherein the third lens comprises a concave image-side surface.

13. The optical system of claim 9, wherein the fourth lens 5 comprises a concave object-side surface.

14. The optical system of claim 9, wherein the sixth lens comprises a convex object-side surface and a concave image-side surface.

15. An optical system, comprising:

a first lens;

a second lens comprising a convex image-side surface in a paraxial region;

a third lens comprising a convex object-side surface in the paraxial region;

a fourth lens comprising a convex image-side surface in the paraxial region;

a fifth lens comprising a concave object-side surface in the paraxial region and a concave image-side surface in the paraxial region; and

a sixth lens comprising an inflection point formed on an image-side surface thereof, wherein

the second lens has a same refractive index as a refractive index of the first lens,

the third lens, the fourth lens, and the fifth lens have a refractive index higher than the refractive indexes of the first and second lenses, and

the sixth lens has a refractive index lower than the refractive indexes of the first and second lenses,

f, an overall focal length of the optical system, and f1, a focal length of the first lens, satisfy  $1.0 < f1/f < 1.8$ ,

## 22

f, and f5 a focal length of the fifth lens, satisfy  $f5/f < -10$ ; f2, a focal length of the second lens, and, f3, a focal length of the third lens satisfy  $-1.2 < f2/f3 < 0$ , and

f, and r10, a radius of curvature of an image-side surface of the fifth lens, satisfy  $30 < r10/f$ .

16. The optical system of claim 15, wherein, V1, an Abbe number of the first lens, V2, an Abbe number of the second lens, V3, an Abbe number of the third lens, and, V5, an Abbe number of the fifth lens satisfy

$$V1 - V2 < 25,$$

$$15 < |V1 - V3|, \text{ and}$$

$$25 < V1 - V5 < 45.$$

17. The optical system of claim 15, wherein, f, an overall focal length of the optical system, and TTL a distance from the object-side surface of the first lens to an imaging plane satisfy  $TTL/f < 1.5$ .

18. The optical system of claim 15, wherein, f, an overall focal length of the optical system, and, BFL, a distance from an object-side surface of the sixth lens to an imaging plane satisfy  $BFL/f < 0.5$ .

19. The optical system of claim 15, wherein, f, an overall focal length of the optical system, and, D2, a distance from the image-side surface of the first lens to an object-side surface of the second lens satisfy  $D2/f < 0.1$ .

20. The optical system of claim 15, wherein, FOV, a field of view of the optical system satisfy  $75 < FOV$ .

\* \* \* \* \*