

US010506325B1

(12) **United States Patent**
Koss et al.

(10) **Patent No.:** **US 10,506,325 B1**
(45) **Date of Patent:** ***Dec. 10, 2019**

(54) **SYSTEM WITH WIRELESS EARPHONES**

(71) Applicant: **Koss Corporation**, Milwaukee, WI (US)

(72) Inventors: **Michael J. Koss**, Milwaukee, WI (US); **Michael J. Pelland**, Princeton, WI (US); **Michael Sagan**, Fairfield, CA (US); **Steven R. Reckamp**, Crystal Lake, IL (US); **Gregory J. Hallingstad**, Deforest, WI (US); **Jeffery K. Bovee**, Sterling, IL (US); **Morgan J. Lowery**, Deforest, WI (US)

(73) Assignee: **KOSS CORPORATION**, Milwaukee, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/528,703**

(22) Filed: **Aug. 1, 2019**

Related U.S. Application Data

(63) Continuation of application No. 16/375,879, filed on Apr. 5, 2019, which is a continuation of application (Continued)

(51) **Int. Cl.**
H04R 1/10 (2006.01)
H04W 48/20 (2009.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04R 1/1041** (2013.01); **H03G 3/02** (2013.01); **H03K 17/9622** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC **H04R 2201/107**; **H04R 1/02**; **H04R 5/033**
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,784,685 A 7/1998 Stanford et al.
6,006,115 A 12/1999 Wingate
(Continued)

FOREIGN PATENT DOCUMENTS

JP 2004-320597 11/2004
JP 2008-67258 A 3/2008
(Continued)

OTHER PUBLICATIONS


Supplementary European Search Report for European Application No. 09731146.8 dated Jun. 10, 2011, 7 pages.
(Continued)

Primary Examiner — Kiet M Doan
(74) *Attorney, Agent, or Firm* — K&L Gates LLP

(57) **ABSTRACT**

Apparatus comprises adapter and speaker system. Adapter is configured to plug into port of personal digital audio player. Speaker system is in communication with adapter, and comprises multiple acoustic transducers, programmable processor circuit, and wireless communication circuit. In first operational mode, processor circuit receives, via adapter, and processes digital audio content from personal digital audio player into which adapter is plugged, and the multiple acoustic transducers output the received audio content from the personal digital audio player. In second operational mode, wireless communication circuit receives digital audio content from a remote digital audio source over a wireless network, processor circuit processes the digital audio content received from remote digital audio source, and the multiple acoustic transducers output the audio content received from the remote digital audio source.

18 Claims, 16 Drawing Sheets



Related U.S. Application Data

<p>No. 16/182,927, filed on Nov. 7, 2018, now Pat. No. 10,368,155, which is a continuation of application No. 15/962,305, filed on Apr. 25, 2018, now Pat. No. 10,206,025, which is a continuation of application No. 15/650,362, filed on Jul. 14, 2017, now Pat. No. 9,986,325, which is a continuation of application No. 15/293,785, filed on Oct. 14, 2016, now Pat. No. 9,729,959, which is a continuation of application No. 15/082,040, filed on Mar. 28, 2016, now Pat. No. 9,497,535, which is a continuation of application No. 14/695,696, filed on Apr. 24, 2015, now Pat. No. 9,438,987, which is a continuation of application No. 13/609,409, filed on Sep. 11, 2012, now Pat. No. 9,049,502, which is a continuation of application No. 13/459,291, filed on Apr. 30, 2012, now Pat. No. 8,571,544, which is a continuation of application No. 12/936,488, filed as application No. PCT/US2009/039754 on Apr. 7, 2009, now Pat. No. 8,190,203.</p> <p>(60) Provisional application No. 61/123,265, filed on Apr. 7, 2008.</p> <p>(51) Int. Cl. <i>H04M 1/02</i> (2006.01) <i>H04R 3/00</i> (2006.01) <i>H04R 5/033</i> (2006.01) <i>H04R 5/04</i> (2006.01) <i>H03G 3/02</i> (2006.01) <i>H04R 1/02</i> (2006.01) <i>H04L 29/12</i> (2006.01) <i>H04H 20/95</i> (2008.01) <i>H03K 17/96</i> (2006.01) <i>H04W 4/80</i> (2018.01) <i>H04W 84/12</i> (2009.01) <i>H04W 84/18</i> (2009.01) <i>H04R 25/00</i> (2006.01)</p> <p>(52) U.S. Cl. CPC <i>H04H 20/95</i> (2013.01); <i>H04L 61/6068</i> (2013.01); <i>H04M 1/0254</i> (2013.01); <i>H04R 1/02</i> (2013.01); <i>H04R 1/1091</i> (2013.01); <i>H04R 3/00</i> (2013.01); <i>H04R 5/033</i> (2013.01); <i>H04R 5/04</i> (2013.01); <i>H04W 4/80</i> (2018.02); <i>H04W 48/20</i> (2013.01); <i>H03K 2217/960785</i> (2013.01); <i>H04R 25/554</i> (2013.01); <i>H04R 2201/103</i> (2013.01); <i>H04R 2201/107</i> (2013.01); <i>H04R 2225/55</i> (2013.01); <i>H04R 2420/07</i> (2013.01); <i>H04W 84/12</i> (2013.01); <i>H04W 84/18</i> (2013.01)</p> <p>(58) Field of Classification Search USPC 381/74, 380, 375, 364, 381; 455/42, 557, 455/41.3, 573, 466, 569.1, 553.1 See application file for complete search history.</p> <p>(56) References Cited U.S. PATENT DOCUMENTS</p>	<p>7,120,388 B2 10/2006 Hall 7,139,585 B2 11/2006 Hachimura et al. 7,266,390 B2 9/2007 Mathews 7,337,027 B2 2/2008 Nishiguchi et al. 7,467,021 B2 12/2008 Yuen 7,512,414 B2 3/2009 Jannard et al. 7,599,679 B2 10/2009 Awiszus 7,650,168 B2 1/2010 Bailey 7,680,490 B2 3/2010 Bloebaum et al. 7,697,899 B2 4/2010 Rofougaran 7,734,055 B2 6/2010 Chiloyan 7,764,775 B2 7/2010 Tarkoff et al. 7,805,210 B2 9/2010 Cucos 7,861,312 B2 12/2010 Lee et al. 7,962,482 B2 6/2011 Handman 8,023,663 B2 9/2011 Goldberg 8,027,638 B2 9/2011 Sanguino 8,055,007 B2 11/2011 Kim 8,073,137 B2 12/2011 Weinans et al. 8,086,281 B2 12/2011 Rabu et al. 8,102,836 B2 1/2012 Jerlhagen 8,190,203 B2 5/2012 Pelland et al. 8,295,516 B2 10/2012 Kondo et al. 8,335,312 B2 12/2012 Gerhardt et al. 8,401,202 B2 3/2013 Brooking 8,478,880 B2 7/2013 Finkelstein et al. 8,483,755 B2 7/2013 Kumar 8,553,865 B2 10/2013 Menard et al. 8,571,544 B2 10/2013 Pelland et al. 8,655,420 B1 2/2014 Pelland et al. 8,792,945 B2 7/2014 Russell et al. 9,049,502 B2 6/2015 Pelland et al. 9,497,535 B1 11/2016 Koss et al. 9,729,959 B2 8/2017 Koss et al. 2003/0182003 A1 9/2003 Takashima 2004/0107271 A1 6/2004 Ahn et al. 2005/0064853 A1 3/2005 Radpour 2005/0136839 A1 6/2005 Seshadri et al. 2005/0198233 A1 9/2005 Manchester 2006/0083388 A1 4/2006 Rothschild 2006/0206487 A1 9/2006 Harada 2006/0212442 A1 9/2006 Conrad 2006/0212444 A1 9/2006 Handman et al. 2006/0238878 A1 10/2006 Miyake 2006/0268830 A1 11/2006 Evans 2007/0008984 A1 1/2007 Philips 2007/0037615 A1 2/2007 Glezerman 2007/0049198 A1 3/2007 Walsh et al. 2007/0053543 A1 3/2007 Lee 2007/0136446 A1 6/2007 Rezvani et al. 2007/0165875 A1 7/2007 Rezvani 2007/0253603 A1 11/2007 Kimura et al. 2007/0297618 A1 12/2007 Nurmi et al. 2008/0019557 A1 1/2008 Bevirt et al. 2008/0031470 A1 2/2008 Angelhag 2008/0062939 A1 3/2008 Van Horn 2008/0076489 A1* 3/2008 Rosener H04M 1/6066 455/575.2 2008/0194209 A1 8/2008 Haupt et al. 2008/0215777 A1 9/2008 Richenstein et al. 2008/0226094 A1 9/2008 Rutschman 2008/0242312 A1 10/2008 Paulson et al. 2008/0298606 A1 12/2008 Johnson et al. 2008/0311852 A1 12/2008 Hansen et al. 2009/0029743 A9 1/2009 Lair et al. 2009/0109054 A1* 4/2009 Ueda H04M 1/04 340/13.24 2009/0116678 A1 5/2009 Bevirt et al. 2009/0129605 A1 5/2009 Camp et al. 2009/0248178 A1 10/2009 Paulson et al. 2010/0290642 A1 11/2010 Haseagawa 2011/0275323 A1 11/2011 Goldman et al. 2013/0039510 A1 2/2013 Pelland et al. 2013/0099507 A1 4/2013 Moriya et al. 2015/0237439 A1 8/2015 Koss et al. 2017/0318378 A1 11/2017 Koss et al. 2018/0249240 A1 8/2018 Koss et al.</p>
---	---

(56)

References Cited

U.S. PATENT DOCUMENTS

2019/0075390 A1 3/2019 Koss et al.
2019/0238970 A1 8/2019 Koss et al.

FOREIGN PATENT DOCUMENTS

WO WO 2006/047724 A2 5/2006
WO WO 2007/136620 A2 11/2007
WO WO 2007/139578 A1 12/2007
WO WO 2008/033478 A1 3/2008
WO WO 2008/054985 A2 5/2008
WO WO 2009/086555 A1 7/2009

OTHER PUBLICATIONS

International Search Report for International Application No. PCT/US09/39754 dated Jun. 11, 2009, 2 pages.

International Preliminary Examination Report for International Application No. PCT/US09/39754 dated Oct. 28, 2010, 8 pages.

Written Opinion of the International Searching Authority for International Application No. PCT/US09/39754 dated Jun. 11, 2009, 5 pages.

IT Review, "LTB 802.11 WiFi Headphones", <http://itreview.belproject.com/item/1536> accessed on Mar. 13, 2008 (4 pages).

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

SYSTEM WITH WIRELESS EARPHONES

PRIORITY CLAIM

The present application claims priority as a continuation to U.S. nonprovisional patent application Ser. No. 16/375,879, filed Apr. 5, 2019, which is a continuation of U.S. nonprovisional patent application Ser. No. 16/182,927, filed Nov. 7, 2018, which is a continuation of U.S. nonprovisional patent application Ser. No. 15/962,305, filed Apr. 25, 2018, now U.S. Pat. No. 10,206,025, which is a continuation of U.S. nonprovisional patent application Ser. No. 15/650,362, filed Jul. 14, 2017, now U.S. Pat. No. 9,986,325, issued May 29, 2018, which is a continuation of U.S. nonprovisional patent application Ser. No. 15/293,785, filed Oct. 14, 2016, now U.S. Pat. No. 9,729,959, issued Aug. 8, 2017, which is a continuation of U.S. nonprovisional patent application Ser. No. 15/082,040, filed Mar. 28, 2016, now U.S. Pat. No. 9,497,535, issued Nov. 15, 2016, which is a continuation of U.S. nonprovisional patent application Ser. No. 14/695,696, filed Apr. 24, 2015, now U.S. Pat. No. 9,438,987, issued on Sep. 6, 2016, which is a continuation of U.S. nonprovisional patent application Ser. No. 13/609,409, filed Sep. 11, 2012, now U.S. Pat. No. 9,049,502, issued Jun. 2, 2015, which is a continuation of U.S. nonprovisional patent application Ser. No. 13/459,291, filed Apr. 30, 2012, now U.S. Pat. No. 8,571,544, issued Oct. 29, 2013, which is a continuation of U.S. patent application Ser. No. 12/936,488, filed Dec. 20, 2010, now U.S. Pat. No. 8,190,203, issued May 29, 2012, which is a national stage entry of PCT/US2009/039754, filed Apr. 7, 2009, which claims priority to U.S. provisional patent application Ser. No. 61/123,265, filed Apr. 7, 2008, all of which are incorporated herein by reference in their entireties.

CROSS-REFERENCE TO RELATED APPLICATIONS

U.S. nonprovisional patent application Ser. No. 14/031,938, filed Sep. 13, 2013, now U.S. Pat. No. 8,655,420, issued Feb. 18, 2014, is also a continuation of U.S. nonprovisional patent application Ser. No. 13/609,409, filed Sep. 11, 2012, now U.S. Pat. No. 9,049,502, mentioned above.

BACKGROUND

Digital audio players, such as MP3 players and iPods, that store and play digital audio files, are very popular. Such devices typically comprise a data storage unit for storing and playing the digital audio, and a headphone set that connects to the data storage unit, usually with a 1/4" or a 3.5 mm jack and associated cord. Often the headphones are in-ear type headphones. The cord, however, between the headphones and the data storage unit can be cumbersome and annoying to users, and the length of the cord limits the physical distance between the data storage unit and the headphones. Accordingly, some cordless headphones have been proposed, such as the Monster iFreePlay cordless headphones from Apple Inc., which include a docking port on one of the earphones that can connect directly to an iPod Shuffle. Because they have the docking port, however, the Monster iFreePlay cordless headphones from Apple are quite large and are not in-ear type phones. Recently, cordless headphones that connect wirelessly via IEEE 802.11 to a WLAN-ready laptop or personal computer (PC) have been proposed, but such headphones are also quite large and not in-ear type phones.

SUMMARY

In one general aspect, the present invention is directed to a wireless earphone that comprises a transceiver circuit for receiving streaming audio from a data source, such as a digital audio player or a computer, over an ad hoc wireless network. When the data source and the earphone are out of range via the ad hoc wireless network, they may transition automatically to a common infrastructure wireless network (e.g., a wireless LAN). If there is no common infrastructure wireless network for both the data source and the earphone, the earphone may connect via an available infrastructure wireless network to a host server. The host server may, for example, broadcast streaming audio to the earphone and/or transmit to the earphone a network address (e.g., an Internet Protocol (IP) address) for a network-connected content server that streams digital audio. The earphone may then connect to the content server using the IP address. The content server may be an Internet radio server, including, for example, an Internet radio server that broadcasts streaming audio from the data source or some other content.

These and other advantageous, unique aspects of the wireless earphone are described below.

FIGURES

Various embodiments of the present invention are described herein by way of example in conjunction with the following figures, wherein:

FIGS. 1A-1E are views of a wireless earphone according to various embodiments of the present invention;

FIGS. 2A-2D illustrate various communication modes for a wireless earphone according to various embodiments of the present invention;

FIG. 3 is a block diagram of a wireless earphone according to various embodiments of the present invention;

FIGS. 4A-4B show the wireless earphone connected to another device according to various embodiments of the present invention;

FIG. 5 is a diagram of a process implemented by a host server according to various embodiments of the present invention;

FIG. 6 is a diagram of a process implemented by the wireless earphone to transition automatically between wireless networks according to various embodiments of the present invention;

FIGS. 7, 8 and 10 illustrate communication systems involving the wireless earphone according to various embodiments of the present invention;

FIG. 9 is a diagram of a headset including a wireless earphone and a microphone according to various embodiments of the present invention; and

FIG. 11 is a diagram of a pair of wireless earphones with a dongle according to various embodiments of the present invention.

DESCRIPTION

In one general aspect, the present invention is directed to a wireless earphone that receives streaming audio data via ad hoc wireless networks and infrastructure wireless networks, and that transitions seamlessly between wireless networks. The earphone may comprise one or more in-ear, on-ear, or over-ear speaker elements. Two exemplary in-ear earphone shapes for the wireless earphone 10 are shown in FIGS. 1A and 1B, respectively, although in other embodiments the earphone may take different shapes and the exemplary

shapes shown in FIGS. 1A and 1B are not intended to be limiting. In one embodiment, the earphone transitions automatically and seamlessly, without user intervention, between communication modes. That is, the earphone may transition automatically from an ad hoc wireless network to an infrastructure wireless network, without user intervention. As used herein, an “ad hoc wireless network” is a network where two (or more) wireless-capable devices, such as the earphone and a data source, communicate directly and wirelessly, without using an access point. An “infrastructure wireless network,” on the other hand, is a wireless network that uses one or more access points to allow a wireless-capable device, such as the wireless earphone, to connect to a computer network, such as a LAN or WAN (including the Internet).

FIGS. 1A and 1B show example configurations for a wireless earphone 10 according to various embodiments of the present invention. The examples shown in FIGS. 1A and 1B are not limiting and other configurations are within the scope of the present invention. As shown in FIGS. 1A and 1B, the earphone 10 may comprise a body 12. The body 12 may comprise an ear canal portion 14 that is inserted in the ear canal of the user of the earphone 10. In various embodiments, the body 12 also may comprise an exterior portion 15 that is not inserted into user’s ear canal. The exterior portion 15 may comprise a knob 16 or some other user control (such as a dial, a pressure-activated switch, lever, etc.) for adjusting the shape of the ear canal portion 14. That is, in various embodiments, activation (e.g. rotation) of the knob 16 may cause the ear canal portion 14 to change shape so as to, for example, radially expand to fit snugly against all sides of the user’s ear canal. Further details regarding such a shape-changing earbud earphone are described in application PCT/US08/88656, filed 31 Dec. 2008, entitled “Adjustable Shape Earphone,” which is incorporated herein by reference in its entirety. The earphone 10 also may comprise a transceiver circuit housed within the body 12. The transceiver circuit, described further below, may transmit and receive the wireless signals, including receive streaming audio for playing by the earphone 10. The transceiver circuit may be housed in the exterior portion 15 of the earphone 10 and/or in the ear canal portion 14.

Although the example earphones 10 shown in FIGS. 1A and 1B include a knob 16 for adjusting the shape of the ear canal portion 14, the present invention is not so limited, and in other embodiments, different means besides a knob 16 may be used to adjust the ear canal portion 14. In addition, in other embodiments, the earphone 10 may not comprise a shape-changing ear canal portion 14.

In various embodiments, the user may wear two discrete wireless earphones 10: one in each ear. In such embodiments, each earphone 10 may comprise a transceiver circuit. In such embodiments, the earphones 10 may be connected by a string or some other cord-type connector to keep the earphones 10 from being separated.

In other embodiments, as shown in FIG. 1C, a headband 19 may connect the two (left and right) earphones 10. The headband 19 may be an over-the-head band, as shown in the example of FIG. 1C, or the headband may be a behind-the-head band. In embodiments comprising a headband 19, each earphone 10 may comprise a transceiver circuit; hence, each earphone 10 may receive and transmit separately the wireless communication signals. In other embodiments comprising a headband 19, only one earphone 10 may comprise the transceiver circuit, and a wire may run along the headband 19 to the other earphone 10 to connect thereby the transceiver circuit to the acoustic transducer in the earphone that

does not comprise the transceiver circuit. The embodiment shown in FIG. 1C comprises on-ear earphones 10; in other embodiments, in-ear or over-ear earphones may be used.

In other embodiments, the earphone 10 may comprise a hanger bar 17 that allows the earphone 10 to clip to, or hang on, the user’s ear, as shown in the illustrated embodiment of FIGS. 1D-1E. FIG. 1D is a perspective view of the earphone and FIG. 1E is a side view according to one embodiment. As shown in the illustrated embodiment, the earphone 10 may comprise dual speaker elements 106-A, 106-B. One of the speaker elements (the smaller one) 106-A is sized to fit into the cavum concha of the listener’s ear and the other element (the larger one) 106-B is not. The listener may use the hanger bar to position the earphone on the listener’s ear. In that connection, the hanger bar may comprise a horizontal section that rests upon the upper external curvature of the listener’s ear behind the upper portion of the auricula (or pinna). The earphone may comprise a knurled knob that allows the user to adjust finely the distance between the horizontal section of the hanger bar and the speaker elements, thereby providing, in such embodiments, another measure of adjustability for the user. More details regarding such a dual element, adjustable earphone may be found in U.S. provisional patent application Ser. No. 61/054,238, which is incorporated herein by reference in its entirety.

FIGS. 2A-2D illustrate various communication modes for a wireless data communication system involving the earphone 10 according to embodiments of the present invention. As shown in FIG. 2A, the system comprises a data source 20 in communication with the earphone 10 via an ad hoc wireless network 24. The earphone 10, via its transceiver circuit (described in more detail below), may communicate wirelessly with a data source 20, which may comprise a wireless network adapter 22 for transmitting the digital audio wirelessly. For example, the data source 20 may be a digital audio player (DAP), such as an mp3 player or an iPod, or any other suitable digital audio playing device, such as a laptop or personal computer, that stores and/or plays digital audio files. In other embodiments, the data source 20 may generate analog audio, and the wireless network adapter 22 may encode the analog audio into digital format for transmission to the earphone 10.

The wireless network adapter 22 may be an integral part of the data source 20, or it may be a separate device that is connected to the data source 20 to provide wireless connectivity for the data source 20. For example, the wireless network adapter 22 may comprise a wireless network interface card (WNIC) or other suitable transceiver that plugs into a USB port or other port or jack of the data source 20 (such as a TRS connector) to stream data, e.g., digital audio files, via a wireless network (e.g., the ad hoc wireless network 24 or an infrastructure wireless network). The digital audio transmitted from the data source 20 to the earphone 10 via the wireless networks may comprise compressed or uncompressed audio. Any suitable file format may be used for the audio, including mp3, lossy or lossless WMA, Vorbis, Musepack, FLAC, WAV, AIFF, AU, or any other suitable file format.

When in range, the data source 20 may communicate with the earphone 10 via the ad hoc wireless network 24 using any suitable wireless communication protocol, including Wi-Fi (e.g., IEEE 802.11a/b/g/n), WiMAX (IEEE 802.16), Bluetooth, Zigbee, UWB, or any other suitable wireless communication protocol. For purposes of the description to follow, it is assumed that the data source 20 and the earphone 10 communicate using a Wi-Fi protocol, although the invention is not so limited and other wireless communication

5

protocols may be used in other embodiments of the invention. The data source **20** and the earphone **10** are considered in range for the ad hoc wireless network **24** when the signal strengths (e.g., the RSSI) of the signals received by the two devices are above a threshold minimum signal strength level. For example, the data source **20** and the earphone **10** are likely to be in range for an ad hoc wireless network when then are in close proximity, such as when the wearer of the earphone **10** has the data source **20** on his/her person, such as in a pocket, strapped to their waist or arm, or holding the data source in their hand.

When the earphone **10** and the data source **20** are out of range for the ad hoc wireless network **24**, that is, when the received signals degrade below the threshold minimum signal strength level, both the earphone **10** and the data source **20** may transition automatically to communicate over an infrastructure wireless network (such as a wireless LAN (WLAN)) **30** that is in the range of both the earphone **10** and the data source **20**, as shown in FIG. 2B. The earphone **10** and the data source **20** (e.g., the wireless network adapter **22**) may include firmware, as described further below, that cause the components to make the transition to a common infrastructure wireless network **30** automatically and seamlessly, e.g., without user intervention. The earphone **10** may cache the received audio in a buffer or memory for a time period before playing the audio. The cached audio may be played after the connection over the ad hoc wireless network is lost to give the earphone **10** and the data source **20** time to connect via the infrastructure wireless network.

For example, as shown in FIG. 2B, the infrastructure network may comprise an access point **32** that is in the range of both the data source **20** and the earphone **10**. The access point **32** may be an electronic hardware device that acts as a wireless access point for, and that is connected to, a wired and/or wireless data communication network **33**, such as a LAN or WAN, for example. The data source **20** and the earphone **10** may both communicate wirelessly with the access point **32** using the appropriate network data protocol (a Wi-Fi protocol, for example). The data source **20** and the earphone **10** may both transition automatically to an agreed-upon WLAN **30** that is in the range of both devices when they cannot communicate satisfactorily via the ad hoc wireless network **24**. A procedure for specifying an agreed-upon infrastructure wireless network **30** is described further below. Alternatively, the infrastructure wireless network **30** may have multiple access points **32a-b**, as shown in FIG. 2C. In such an embodiment, the data source **20** may communicate wirelessly with one access point **32b** and the earphone **10** may communicate wirelessly with another access point **32a** of the same infrastructure wireless network **30**. Again, the data source **20** and the earphone **10** may transition to an agreed-upon WLAN.

If there is no suitable common infrastructure wireless network over which the earphone **10** and the data source **20** can communicate, as shown in FIG. 2D, the earphone **10** may transition to communicate with an access point **32a** for an available (first) wireless network (e.g., WLAN) **30a** that is in the range of the earphone **10**. In this mode, the earphone **10** may connect via the wireless network **30a** to a network-enabled host server **40**. The host server **40** may be connected to the wireless network **30a** via an electronic data communication network **42**, such as the Internet. In one mode, the host server **40** may transmit streaming digital audio via the networks **33a**, **42** to the earphone **10**. In another mode, the host server **40** may transmit to the earphone **10** a network address, such as an Internet Protocol (IP) address, for a streaming digital audio content server **70** on the network **42**.

6

Using the received IP address, the earphone **10** may connect to the streaming digital audio content server **70** via the networks **30a**, **42** to receive and process digital audio from the streaming digital audio content server **70**.

The digital audio content server **70** may be, for example, an Internet radio station server. The digital audio content server **70** may stream digital audio over the network **42** (e.g., the Internet), which the earphone **10** may receive and process. In one embodiment, the streaming digital audio content server **70** may stream digital audio received by the streaming digital audio content server **70** from the data source **20**. For example, where the data source **20** is a wireless-capable device, such as a portable DAP, the data source **20** may connect to the streaming digital audio content server **70** via a wireless network **30b** and the network **42**. Alternatively, where for example the data source **20** is non-wireless-capable device, such as a PC, the data source **20** may have a direct wired connection to the network **42**. After being authenticated by the streaming digital audio content server **70**, the data source **20** may stream digital audio to the streaming digital audio content server **70**, which may broadcast the received digital audio over the network **42** (e.g., the Internet). In such a manner, the user of the earphone **10** may listen to audio from the data source **20** even when (i) the earphone **10** and the data source **20** are not in communication via an ad hoc wireless network **24** and (ii) the earphone **10** and the data source **20** are not in communication via a common local infrastructure wireless network **30**.

FIG. 3 is a block diagram of the earphone **10** according to various embodiments of the present invention. In the illustrated embodiment, the earphone **10** comprises a transceiver circuit **100** and related peripheral components. As shown in FIG. 3, the peripheral components of the earphone **10** may comprise a power source **102**, a microphone **104**, one or more acoustic transducers **106** (e.g., speakers), and an antenna **108**. The transceiver circuit **100** and some of the peripheral components (such as the power source **102** and the acoustic transducers **106**) may be housed within the body **12** of the earphone **10** (see FIG. 1). Other peripheral components, such as the microphone **104** and the antenna **108** may be external to the body **12** of the earphone **10**. In addition, some of the peripheral components, such as the microphone **104**, are optional in various embodiments.

In various embodiments, the transceiver circuit **100** may be implemented as a single integrated circuit (IC), such as a system-on-chip (SoC), which is conducive to miniaturizing the components of the earphone **10**, which is advantageous if the earphone **10** is to be relatively small in size, such as an in-ear earphone (see FIGS. 1A-1B for example). In alternative embodiments, however, the components of the transceiver circuit **100** could be realized with two or more discrete ICs or other components, such as separate ICs for the processors, memory, and RF (e.g., Wi-Fi) module, for example.

The power source **102** may comprise, for example, a rechargeable or non-rechargeable battery (or batteries). In other embodiments, the power source **102** may comprise one or more ultracapacitors (sometimes referred to as supercapacitors) that are charged by a primary power source. In embodiments where the power source **102** comprises a rechargeable battery cell or an ultracapacitor, the battery cell or ultracapacitor, as the case may be, may be charged for use, for example, when the earphone **10** is connected to a docking station or computer. The docking station may be connected to or part of a computer device, such as a laptop computer or PC. In addition to charging the rechargeable

power source **102**, the docking station and/or computer may facilitate downloading of data to and/or from the earphone **10**. In other embodiments, the power source **102** may comprise capacitors passively charged with RF radiation, such as described in U.S. Pat. No. 7,027,311. The power source **102** may be coupled to a power source control module **103** of transceiver circuit **100** that controls and monitors the power source **102**.

The acoustic transducer(s) **106** may be the speaker element(s) for conveying the sound to the user of the earphone **10**. According to various embodiments, the earphone **10** may comprise one or more acoustic transducers **106**. For embodiments having more than one transducer, one transducer may be larger than the other transducer, and a crossover circuit (not shown) may transmit the higher frequencies to the smaller transducer and may transmit the lower frequencies to the larger transducer. More details regarding dual element earphones are provided in U.S. Pat. No. 5,333,206, assigned to Koss Corporation, which is incorporated herein by reference in its entirety.

The antenna **108** may receive and transmit the wireless signals from and to the wireless networks **24**, **30**. A RF (e.g., Wi-Fi) module **110** of the transceiver circuit **100** in communication with the antenna **108** may, among other things, modulate and demodulate the signals transmitted from and received by the antenna **108**. The RF module **110** communicates with a baseband processor **112**, which performs other functions necessary for the earphone **10** to communicate using the Wi-Fi (or other communication) protocol.

The baseband processor **112** may be in communication with a processor unit **114**, which may comprise a microprocessor **116** and a digital signal processor (DSP) **118**. The microprocessor **116** may control the various components of the transceiver circuit **100**. The DSP **114** may, for example, perform various sound quality enhancements to the digital audio received by the baseband processor **112**, including noise cancellation and sound equalization. The processor unit **114** may be in communication with a volatile memory unit **120** and a non-volatile memory unit **122**. A memory management unit **124** may control the processor unit's access to the memory units **120**, **122**. The volatile memory **122** may comprise, for example, a random access memory (RAM) circuit. The non-volatile memory unit **122** may comprise a read only memory (ROM) and/or flash memory circuits. The memory units **120**, **122** may store firmware that is executed by the processor unit **114**. Execution of the firmware by the processor unit **114** may provide various functionality for the earphone **10**, such as the automatic transition between wireless networks as described herein. The memory units **120**, **122** may also cache received digital audio.

A digital-to-analog converter (DAC) **125** may convert the digital audio from the processor unit **114** to analog form for coupling to the acoustic transducer(s) **106**. An I²S interface **126** or other suitable serial or parallel bus interface may provide the interface between the processor unit **114** and the DAC **125**. An analog-to-digital converter (ADC) **128**, which also communicates with the I²S interface **126**, may convert analog audio signals picked up by the microphone **104** for processing by the processor unit **114**.

The transceiver circuit **100** also may comprise a USB or other suitable interface **130** that allows the earphone **10** to be connected to an external device via a USB cable or other suitable link. As shown in FIG. 4A, the external device may be a docking station **200** connected to a computer device **202**. Also, in various embodiments, the earphone **10** could be connected directly to the computer **202** without the

docking station **200**. In addition, the external device may be a DAP **210**, as shown in FIG. 4B. In that way, the earphone **10** could connect directly to a data source **20**, such as the DAP **210** or the computer **202**, through the USB port **130**. In addition, through the USB port **130**, the earphone **10** may connect to a PC **202** or docking station **202** to charge up the power source **102** and/or to get downloads (e.g., data or firmware).

According to various embodiments, the earphone **10** may have an associated web page that a user may access through the host server **40** (see FIG. 2D) or some other server. An authenticated user could log onto the website from a client computing device **50** (e.g., laptop, PC, handheld computer device, etc., including the data source **20**) (see FIG. 2D) to access the web page for the earphone **10** to set various profile values for the earphone **10**. For example, at the web site, the user could set various content features and filters, as well as adjust various sound control features, such as treble, bass, frequency settings, noise cancellation settings, etc. In addition, the user could set preferred streaming audio stations, such as preferred Internet radio stations or other streaming audio broadcasts. That way, instead of listening to streaming audio from the data source **20**, the user could listen to Internet radio stations or other streaming audio broadcasts received by the earphone **10**. In such an operating mode, the earphone user, via the web site, may prioritize a number of Internet radio stations or other broadcast sources (hosted by streaming digital audio content servers **70**). With reference to FIG. 7, the host server **40** may send the IP address for the earphone user's desired (e.g., highest priority) Internet radio station to the earphone **10**. A button **11** on the earphone **10**, such as on the rotating dial **16** as shown in the examples of FIGS. 1A and 1B, may allow the user to cycle through the preset preferred Internet radio stations. That is, for example, when the user presses the button **11**, an electronic communication may be transmitted to the host server **40** via the wireless network **30**, and in response to receiving the communication, the host server **40** may send the IP address for the user's next highest rated Internet radio station via the network **42** to the earphone **10**. The earphone **10** may then connect to the streaming digital audio content server **70** for that Internet radio station using the IP address provided by the host server **40**. This process may be repeated, e.g., cycled through, for each preset Internet radio station configured by the user of the earphone **10**.

At the web site for the earphone **10** hosted on the host server **40**, in addition to establishing the identification of digital audio sources (e.g., IDs for the user's DAP or PC) and earphones, the user could set parental or other user controls. For example, the user could restrict certain Internet radio broadcasts based on content or parental ratings, etc. That is, for example, the user could configure a setting through the web site that prevents the host server **40** from sending an IP address for a streaming digital audio content server **70** that broadcasts explicit content based on a rating for the content. In addition, if a number of different earphones **10** are registered to the same user, the user could define separate controls for the different earphones **10** (as well as customize any other preferences or settings particular to the earphones **10**, including Internet radio stations, sound quality settings, etc. that would later be downloaded to the earphones **10**). In addition, in modes where the host server **40** streams audio to the earphone **10**, the host server **40** may log the files or content streamed to the various earphones **10**, and the user could view at the web site the

files or content that were played by the earphones **10**. In that way, the user could monitor the files played by the earphones **10**.

In addition, the host server **40** may provide a so-called eavesdropping function according to various embodiments. The eavesdropping service could be activated via the web site. When the service is activated, the host server **40** may transmit the content that it is delivering to a first earphone **10a** to another, second earphone **10b**, as shown in FIG. **8**. Alternatively, the host server **40** may transmit to the second earphone **10b** the most recent IP address for a streaming digital audio content server **70** that was sent to the first earphone **10a**. The second earphone **10b** may then connect to the streaming digital audio content server **70** that the first earphone **10a** is currently connected. That way, the user of the second earphone **10b**, which may be a parent, for example, may directly monitor the content being received by the first earphone **10a**, which may belong to a child of the parent.

This function also could be present in the earphones **10** themselves, allowing a parent (or other user) to join an ad-hoc wireless network and listen to what their child (or other listener) is hearing. For example, with reference to FIG. **10**, a first earphone **10a** may receive wireless audio, such as from the data source **20** or some other source, such as the host server **40**. The first earphone **10a** may be programmed with firmware to broadcast the received audio to a second earphone **10b** via an ad hoc wireless network **24**. That way, the wearer of the second earphone **10b** can monitor in real-time the content being played by the first earphone **10a**.

At the web site, the user may also specify the identification number (“ID”) of their earphone(s) **10**, and the host server **40** may translate the ID to the current internet protocol (IP) addresses for the earphone **10** and for the data source **20**. This allows the user to find his or her data source **20** even when it is behind a firewall or on a changing IP address. That way, the host server **40** can match the audio from the data source **20** to the appropriate earphone **10** based on the specified device ID. The user also could specify a number of different data sources **20**. For example, the user’s DAP may have one specified IP address and the user’s home (or work) computer may have another specified IP address. Via the web site hosted by the host server **40**, the user could specify or prioritize from which source (e.g., the user’s DAP or computer) the earphone **10** is to receive content.

The host server **40** (or some other server) may also push firmware upgrades and/or data updates to the earphone **10** using the IP addresses of the earphone **10** via the networks **30**, **42**. In addition, a user could download the firmware upgrades and/or data updates from the host server **40** to the client computing device **202** (see FIG. **4A**) via the Internet, and then download the firmware upgrades and/or data updates to the earphone **10** when the earphone **10** is connected to the client computer device **202** (such as through a USB port and/or the docking station **200**).

Whether the downloads are transmitted wirelessly to the earphone **10** or via the client computing device **202** may depend on the current data rate of the earphone **10** and the quantity of data to be transmitted to the earphone **10**. For example, according to various embodiments, as shown in the process flow of FIG. **5**, the host server **40** may be programmed, at step **50**, to make a determination, based on the current data rate for the earphone **10** and the size of the update, whether the update should be pushed to the earphone **10** wirelessly (e.g., via the WLAN **30a** in FIG. **2D**). If the update is too large and/or the current data rate is too low that

the performance of the earphone **10** will be adversely affected, the host server **40** may refrain from pushing the update to the earphone **10** wirelessly and wait instead to download the update to the client computing device **202** at step **51**. Conversely, if the host server **40** determines that, given the size of the update and the current data rate for the earphone **10** that the performance of the earphone **10** will not be adversely affected, the host server **40** may transmit the update wirelessly to the earphone **10** at step **52**.

As mentioned above, the processor unit **114** of the speakerphones **14** may be programmed, via firmware stored in the memory **120**, **122**, to have the ability to transition automatically from the ad hoc wireless network **24** to an infrastructure wireless network **30** (such as a WLAN) when the quality of the signal on the ad hoc wireless network **24** degrades below a suitable threshold (such as when the data source **20** is out of range for an ad hoc wireless network). In that case, the earphone **10** and the data source **20** may connect to a common infrastructure wireless network (e.g., WLAN) (see, for example, FIGS. **2B-2C**). Through the web site for the earphone **10**, described above, the user could specify a priority of infrastructure wireless networks **30** for the data source **20** and the earphone **10** to connect to when the ad hoc wireless network **24** is not available. For example, the user could specify a WLAN servicing his/her residence first, a WLAN servicing his/her place of employment second, etc. During the time that the earphone **10** and the data source **20** are connected via the ad hoc wireless network **24**, the earphone **10** and the data source **20** may exchange data regarding which infrastructure networks are in range. When the earphone **10** and the data source **20** are no longer in range for the ad hoc wireless network **24** (that is, for example, the signals between the device degrade below an acceptable level), they may both transition automatically to the highest prioritized infrastructure wireless network whose signal strength is above a certain threshold level. That way, even though the earphone **10** and the data source **20** are out of range for the ad hoc wireless network **24**, the earphone **10** may still receive the streaming audio from the data source **20** via the infrastructure wireless network **30** (see FIGS. **2B-2C**).

When none of the preferred infrastructure networks is in range, the earphone **10** may connect automatically to the host server **40** via an available infrastructure wireless network **30** (see FIG. **2D**), e.g., the infrastructure wireless network **30** having the highest RSSI and to which the earphone **10** is authenticated to use. The host server **40**, as mentioned above, may transmit IP addresses to the earphone **10** for streaming digital audio content servers **70** or the host sever **40** may stream digital audio to the earphone **10** itself when in this communication mode.

FIG. **6** is a diagram of the process flow, according to one embodiment, implemented by the transceiver circuit **100** of the earphone **10**. The process shown in FIG. **6** may be implemented in part by the processor unit **114** executing firmware stored in a memory unit **120**, **122** of the transceiver circuit **100**. At step **61**, the earphone **10** may determine if it can communicate with the data source **20** via an ad hoc wireless network **24**. That is, the earphone **10** may determine if the strength of the wireless signals from the data source **20** exceed some minimum threshold. If so, the data source **20** and the earphone **10** may communicate wirelessly via the ad hoc wireless network **24** (see FIG. **2A**). While in this communication mode, at step **62**, the data source **20** and the earphone **10** also may exchange data regarding the local infrastructure wireless networks, if any, in the range of the data source **20** and the earphone **10**, respectively. For

11

example, the earphone **10** may transmit the ID of local infrastructure wireless networks **30** that the earphone **10** can detect whose signal strength (e.g., RSSI) exceeds some minimum threshold level. Similarly, the data source **20** may transmit the ID the local infrastructure wireless networks **30** that the data source **20** can detect whose signal strength (e.g., RSSI) exceeds some minimum threshold level. The earphone **10** may save this data in a memory unit **120**, **122**. Similarly, the data source **20** may store in memory the wireless networks that the earphone **10** is detected.

The data source **20** and the earphone **10** may continue to communicate via the ad hoc wireless network mode **24** until they are out of range (e.g., the signal strengths degrade below a minimum threshold level). If an ad hoc wireless network **24** is not available at block **61**, the transceiver circuit **100** and the data source **20** may execute a process, shown at block **63**, to connect to the user's highest prioritized infrastructure wireless network **30**. For example, of the infrastructure wireless networks whose signal strength exceeded the minimum threshold for both the earphone **10** and the data source **20** determined at step **62**, the earphone **10** and the data source **20** may both transition to the infrastructure wireless network **30** having the highest priority, as previously set by the user (seen FIGS. **2B-2C**, for example). For example, if the user's highest prioritized infrastructure wireless network **30** is not available, but the user's second highest prioritized infrastructure wireless network **30** is, the earphone **10** and the data source **20** may both transition automatically to the user's second highest prioritized infrastructure wireless network **30** at block **64**. As shown by the loop with block **65**, the earphone **10** and the data source **20** may continue to communicate via one of the user's prioritized infrastructure wireless networks **30** as long as the infrastructure wireless network **30** is available. If the infrastructure wireless network becomes unavailable, the process may return to block **61**.

If, however, no ad hoc wireless network and none of the user's prioritized infrastructure wireless networks are available, the earphone **10** may transition automatically to connect to the host server **40** at block **66** (see FIG. **2D**) using an available infrastructure wireless network **30**. At block **67**, the host server **40** may transmit an IP address to the earphone **10** for one of the streaming digital audio content servers **70**, and at block **68** the earphone **10** may connect to the streaming digital audio content server **70** using the received IP address. At step **69**, as long as the earphone **10** is connected to the streaming digital audio content server **70**, the earphone **10** may continue to communicate in this mode. However, if the earphone **10** loses its connection to the digital audio content server **70**, the process may return to block **61** in one embodiment. As mentioned above, at block **67**, instead of sending an IP address for a streaming digital audio content server **70**, the host server **40** may stream digital audio to the earphone **10**. The user, when configuring their earphone **10** preferences via the web site, may specify and/or prioritize whether the host server **40** is to send IP addresses for the streaming digital audio content servers **70** and/or whether the host server **40** is to stream audio to the earphone **10** itself.

In another embodiment, the earphone **10** may be programmed to transition automatically to the host server **40** when the earphone **10** and the data source **20** are not in communication via the ad hoc wireless network **24**. That is, in such an embodiment, the earphone **10** may not try to connect via a local infrastructure wireless network **30** with the data source **20**, but instead transition automatically to connect to the host server **40** (see FIG. **2D**).

12

In various embodiments, as shown in FIG. **1B**, the button **11** or other user selection device that allows the wearer of the earphone **10** to indicate approval and/or disapproval of songs or other audio files listened to by the wearer over an Internet radio station. The approval/disapproval rating, along with metadata for the song received by the earphone **10** with the streaming audio, may be transmitted from the transceiver circuit **100** of the earphone **10** back to the host server **40**, which may log the songs played as well as the ratings for the various songs/audio files. In addition to being able to view the logs at the website, the host server **40** (or some other server) may send an email or other electronic communication to the earphone user, at a user specified email address or other address, which the user might access from their client communication device **50** (see FIG. **2D**). The email or other electronic communication may contain a listing of the song/audio files for which the user gave approval ratings using the button **11** or other user selection device. Further, the email or other electronic communication may provide a URL link for a URL at which the user could download song/audio files that the user rated (presumably song/audio files for which the user gave an approval rating). In some instances, the user may be required to pay a fee to download the song/audio file.

The user song ratings also may be used by the host server **40** to determine the user's musical preferences and offer new music that the user might enjoy. More details about generating user play lists based on song ratings may be found in published U.S. patent applications Pub. No. 2006/0212444, Pub. No. 2006/0206487, and Pub. No. 2006/0212442, and U.S. Pat. No. 7,003,515, which are incorporated herein by reference in their entirety.

In addition or alternatively, the user could log onto a web site hosted by the host server **40** (or some other server) to view the approval/disapproval ratings that the user made via the button **11** on the earphone **10**. The web site may provide the user with the option of downloading the rated songs/audio files (for the host server **40** or some other server system) to their client computer device **50**. The user could then have their earphone **10** connect to their client computer device **50** as a data source **20** via an ad hoc wireless network **24** (see FIG. **2A**) or via an infrastructure wireless network (see FIGS. **2B-2D**) to listen to the downloaded songs. In addition, the user could download the song files from their client computer device **50** to their DAP and listen to the downloaded song files from their DAP by using their DAP as the data source **20** in a similar manner.

Another application of the headsets may be in vehicles equipped with Wi-Fi or other wireless network connectivity. Published PCT application WO 2007/136620, which is incorporated herein by reference, discloses a wireless router for providing a Wi-Fi or other local wireless network for a vehicle, such as a car, truck, boat, bus, etc. In a vehicle having a Wi-Fi or other local wireless network, the audio for other media systems in the vehicle could be broadcast over the vehicle's wireless network. For example, if the vehicle comprises a DVD player, the audio from the DVD system could be transmitted to the router and broadcast over the vehicle's network. Similarly, the audio from terrestrial radio stations, a CD player, or an audio cassette player could be broadcast over the vehicle's local wireless network. The vehicle's passengers, equipped with the earphones **10**, could cycle through the various audio broadcasts (including the broadcasts from the vehicle's media system as well as broadcasts from the host server **40**, for example) using a selection button **11** on the earphone **10**. The vehicle may also be equipped with a console or terminal, etc., through which

a passenger could mute all of the broadcasts for direct voice communications, for example.

As described above, the earphones **10** may also include a microphone **104**, as shown in the example of FIG. **9**. The headset **90** shown in FIG. **9** includes two earphones **10**, both of which may include a transceiver circuit **100** or only one of which may include the transceiver circuit, as discussed above. The microphone **104** could be used to broadcast communications from one earphone wearer to another earphone wearer. For example, one wearer could activate the microphone by pressing a button **92** on the headset **90**. The headset **90** may then transmit a communication via an ad hoc wireless network **24** or other wireless network to a nearby recipient (or recipients) equipped with a headset **90** with a transceiver circuit **100** in one or both of the earphones **10**. When such communication is detected by the recipient's headset **90**, the streaming audio received over the wireless network by the recipient's headset **90** may be muted, and the intercom channel may be routed to the transducer(s) of the recipient's headset **90** for playing for the recipient. This functionality may be valuable and useful where multiple wearers of the headsets **90** are in close proximity, such as on motorcycles, for example.

Another exemplary use of the earphones **10** is in a factory, warehouse, construction site, or other environment that might be noisy. Persons (e.g., workers) in the environment could use the earphones **10** for protection from the surrounding noise of the environment. From a console or terminal, a person (e.g., a supervisor) could select a particular recipient for a communication over the Wi-Fi network (or other local wireless network). The console or terminal may have buttons, dials, or switches, etc., for each user/recipient, or it could have one button or dial through which the sender could cycle through the possible recipients. In addition, the console or terminal could have a graphical user interface, through which the sender may select the desired recipient(s).

As mentioned above, the earphones **10** may comprise a USB port. In one embodiment, as shown in FIG. **11**, the user may use an adapter **150** that connects to the USB port of each earphone **10**. The adapter **150** may also have a plug connector **152**, such as a 3.5 mm jack, which allows the user to connect the adapter **150** to devices having a corresponding port for the connector **152**. When the earphones **10** detect a connection via their USB interfaces in such a manner, the Wi-Fi (or other wireless protocol) components may shut down or go into sleep mode, and the earphones **10** will route standard headphone level analog signals to the transducer(s) **106**. This may be convenient in environments where wireless communications are not permitted, such as airplanes, but where there is a convenient source of audio contact. For example, the adapter **150** could plug into a person's DAP. The DSP **118** of the earphone **10** may still be operational in such a non-wireless mode to provide noise cancellation and any applicable equalization.

The examples presented herein are intended to illustrate potential and specific implementations of the embodiments. It can be appreciated that the examples are intended primarily for purposes of illustration for those skilled in the art. No particular aspect of the examples is/are intended to limit the scope of the described embodiments.

According to various embodiments, therefore, the present invention is directed to an earphone **10** that comprises a body **12**, where the body **12** comprises: (i) at least one acoustic transducer **106** for converting an electrical signal to sound; (ii) an antenna **108**; and (iii) a transceiver circuit **100** in communication with the at least one acoustic transducer **106** and the antenna **108**. The transceiver circuit **100** is for

receiving and transmitting wireless signals via the antenna **108**, and the transceiver circuit **100** is for outputting the electrical signal to the at least one acoustic transducer **106**. The wireless transceiver circuit also comprises firmware, which when executed by the transceiver circuit, causes the transceiver circuit to: (i) receive digital audio wirelessly from a data source **20** via an ad hoc wireless network **24** when the data source **20** is in wireless communication range with the earphone **10** via the ad hoc wireless network **24**; and (ii) when the data source **20** is not in wireless communication range with the earphone **10** via the ad hoc wireless network **24**, transition automatically to receive digital audio via an infrastructure wireless network **30**.

According to various implementations, the data source may comprise a portable digital audio player, such as an MP3 player, iPod, or laptop computer, or a nonportable digital audio player, such as a personal computer. In addition, the transceiver circuit **100** may comprise: (i) a wireless communication module **110** (such as a Wi-Fi or other wireless communication protocol module); (ii) a processor unit **114** in communication with the wireless communication module **110**; (iii) a non-volatile memory unit **122** in communication with the processor unit **114**; and (iv) a volatile memory **120** unit in communication with the processor unit **114**. The infrastructure wireless network may comprise a WLAN. The transceiver circuit **100** may receive digital audio from the data source **20** via the infrastructure wireless network **30** when the data source **20** is not in wireless communication range with the earphone **10** via the ad hoc wireless network **24**. The transceiver circuit firmware, when executed by the transceiver circuit **100**, may cause the transceiver circuit **100** of the earphone **10** to transition automatically to a pre-set infrastructure wireless network **30** that the data source **20** transitions to when the data source **20** is not in wireless communication range with the earphone **10** via the ad hoc wireless network **24** and when the pre-set infrastructure wireless network **30** is in range of both the earphone **10** and the data source **20**. In addition, the transceiver circuit firmware, when executed by the transceiver circuit **100**, may cause the transceiver circuit **100** of the earphone **10** to transmit data via the ad hoc wireless network **24** to the data source **20** regarding one or more infrastructure wireless networks **30** detected by the transceiver circuit **100** when the earphone **10** and the data source **20** are communicating via the ad hoc wireless network **24**.

In addition, the transceiver circuit firmware, when executed by the transceiver circuit **100**, may cause the transceiver circuit **100** of the earphone **10** to connect to a host server **40** via an available infrastructure wireless network **30** when the data source **20** is not in wireless communication range with the earphone **10** via the ad hoc wireless network **24**. The earphone **10** may receive streaming digital audio from the host server **40** via the infrastructure wireless network **30**. In addition, the earphone **10** may receive a first network address for a first streaming digital audio content server **70** from the host server **40** via the infrastructure wireless network **30**. In addition, the earphone **10** may comprise a user control, such as button **11**, dial, pressure switch, or other type of user control, that, when activated, causes the earphone **10** to transmit an electronic request via the infrastructure wireless network **30** to the host server **40** for a second network address for a second streaming digital audio content server **70**.

In other embodiments, the present invention is directed to a system that comprises: (i) a data source **20** for wirelessly transmitting streaming digital audio; and (ii) a wireless earphone **10** that is in wireless communication with the data

15

source 20. In yet other embodiments, the present invention is directed to a communication system that comprises: (i) a host server 40; (ii) a first streaming digital audio content server 70 that is connected to the host server 40 via a data network 42; and (iii) a wireless earphone 10 that is in communication with the host server 40 via a wireless network 30. The host server 40 is programmed to transmit to the earphone 10 a first network address for the first streaming digital audio content server 70 on the data network 42. The host server 40 and the streaming digital audio content server(s) 70 each may comprise one or more processor circuits and one or more memory circuits (e.g., ROM circuits and/or RAM circuits).

In yet another embodiment, the present invention is directed to a headset that comprises: (i) a first earphone 10a that comprises one or more acoustic transducers 10b for converting a first electrical signal to sound; and (ii) a second earphone 10b, connected to the first earphone 10a, wherein the second earphone 10b comprises one or more acoustic transducers 10b for converting a second electrical signal to sound. In one embodiment, the first earphone 10a comprises: (i) a first antenna 108; and (ii) a first transceiver circuit 100 in communication with the one or more acoustic transducers 106 of the first earphone 10a and in communication with the first antenna 108. The first transceiver circuit 100 is for receiving and transmitting wireless signals via the first antenna 108, and for outputting the first electrical signal to the one or more acoustic transducers 10b of the first earphone 10a. The first transceiver circuit 100 also may comprise firmware, which when executed by the first transceiver circuit 100, causes the first transceiver circuit 100 to: (i) receive digital audio wirelessly from a data source 20 via an ad hoc wireless network 24 when the data source 20 is in wireless communication range with the first earphone 10a via the ad hoc wireless network 24; and (ii) when the data source 20 is not in wireless communication range with the first earphone 10a via the ad hoc wireless network 24, transition automatically to receive digital audio via an infrastructure wireless network 30.

In various implementations, the headset further may comprise a head band 19 that is connected to the first and second earphones 10. In addition, the headset 19 further may comprise a microphone 104 having an output connected to the first transceiver circuit 100. In one embodiment, the first transceiver circuit 100 is for outputting the second electrical signal to the one or more acoustic transducers 106 of the second earphone 10b. In another embodiment, the second earphone 10b comprises: (i) a second antenna 108; and (ii) a second transceiver circuit 100 in communication with the one or more acoustic transducers 106 of the second earphone 10b and in communication with the second antenna 108. The second transceiver circuit 100 is for receiving and transmitting wireless signals via the second antenna 108, and for outputting the second electrical signal to the one or more acoustic transducers 106 of the second earphone 10b. The second transceiver circuit 100 may comprise firmware, which when executed by the second transceiver circuit 100, causes the second transceiver circuit 100 to: (i) receive digital audio wirelessly from the data source 20 via the ad hoc wireless network 24 when the data source 20 is in wireless communication range with the second earphone 10b via the ad hoc wireless network 24; and (ii) when the data source 20 is not in wireless communication range with the second earphone 10b via the ad hoc wireless network 24, transition automatically to receive digital audio via the infrastructure wireless network 30.

16

In addition, according to various embodiments, the first earphone 10a may comprise a first data port and the second earphone 10b may comprise a second data port. In addition, the headset may further comprise an adapter or dongle 150 connected to the first data port of the first earphone 10a and to the second data port of the second earphone 10b, wherein the adapter 150 comprises an output plug connector 152 for connecting to a remote device.

In addition, according to other embodiments, the present invention is directed to a method that comprises the steps of: (i) receiving, by a wireless earphone, via an ad hoc wireless network, digital audio from a data source when the data source is in wireless communication with the earphone via the ad hoc wireless network; (ii) converting, by the wireless earphone, the digital audio to sound; and (iii) when the data source is not in wireless communication with the earphone, transitioning automatically, by the earphone, to receive digital audio via an infrastructure wireless network.

In various implementations, the step of transitioning automatically by the earphone to receive digital audio via an infrastructure wireless network may comprise transitioning automatically to receive digital audio from the data source via an infrastructure wireless network when the data source is not in wireless communication range with the earphone via the ad hoc wireless network. In addition, the method may further comprise the step of receiving by the wireless earphone from the data source via the ad hoc wireless network data regarding one or more infrastructure wireless networks detected by data source when the earphone and the data source are communicating via the ad hoc wireless network.

In addition, the step of transitioning automatically by the earphone to receive digital audio via an infrastructure wireless network may comprise transitioning automatically to receive digital audio from a host sever via the infrastructure wireless network when the data source is not in wireless communication range with the earphone via the ad hoc wireless network. Additionally, the step of transitioning automatically by the earphone to receive digital audio via an infrastructure wireless network may comprise: (i) receiving, by the wireless earphone via the infrastructure wireless network, from a host server connected to the infrastructure wireless network, a network address for a streaming digital audio content server; and (ii) connecting, by the wireless earphone, to the streaming digital audio content server using the network address received from the host server.

It is to be understood that the figures and descriptions of the embodiments have been simplified to illustrate elements that are relevant for a clear understanding of the embodiments, while eliminating, for purposes of clarity, other elements. For example, certain operating system details for the various computer-related devices and systems are not described herein. Those of ordinary skill in the art will recognize, however, that these and other elements may be desirable in a typical processor or computer system. Because such elements are well known in the art and because they do not facilitate a better understanding of the embodiments, a discussion of such elements is not provided herein.

In general, it will be apparent to one of ordinary skill in the art that at least some of the embodiments described herein may be implemented in many different embodiments of software, firmware and/or hardware. The software and firmware code may be executed by a processor or any other similar computing device. The software code or specialized control hardware that may be used to implement embodiments is not limiting. For example, embodiments described herein may be implemented in computer software using any

suitable computer software language type. Such software may be stored on any type of suitable computer-readable medium or media, such as, for example, a magnetic or optical storage medium. The operation and behavior of the embodiments may be described without specific reference to specific software code or specialized hardware components. The absence of such specific references is feasible, because it is clearly understood that artisans of ordinary skill would be able to design software and control hardware to implement the embodiments based on the present description with no more than reasonable effort and without undue experimentation.

Moreover, the processes associated with the present embodiments may be executed by programmable equipment, such as computers or computer systems and/or processors. Software that may cause programmable equipment to execute processes may be stored in any storage device, such as, for example, a computer system (nonvolatile) memory, an optical disk, magnetic tape, or magnetic disk. Furthermore, at least some of the processes may be programmed when the computer system is manufactured or stored on various types of computer-readable media.

A “computer,” “computer system,” “host,” “host server,” “server,” or “processor” may be, for example and without limitation, a processor, microcomputer, minicomputer, server, mainframe, laptop, personal data assistant (PDA), wireless e-mail device, cellular phone, pager, processor, fax machine, scanner, or any other programmable device configured to transmit and/or receive data over a network. Such components may comprise: one or more processor circuits; and one more memory circuits, including ROM circuits and RAM circuits. Computer systems and computer-based devices disclosed herein may include memory for storing certain software applications used in obtaining, processing, and communicating information. It can be appreciated that such memory may be internal or external with respect to operation of the disclosed embodiments. The memory may also include any means for storing software, including a hard disk, an optical disk, floppy disk, ROM (read only memory), RAM (random access memory), PROM (programmable ROM), EEPROM (electrically erasable PROM) and/or other computer-readable media.

In various embodiments disclosed herein, a single component may be replaced by multiple components and multiple components may be replaced by a single component to perform a given function or functions. Except where such substitution would not be operative, such substitution is within the intended scope of the embodiments. Any servers described herein, such as the host server **40**, for example, may be replaced by a “server farm” or other grouping of networked servers (such as server blades) that are located and configured for cooperative functions. It can be appreciated that a server farm may serve to distribute workload between/among individual components of the farm and may expedite computing processes by harnessing the collective and cooperative power of multiple servers. Such server farms may employ load-balancing software that accomplishes tasks such as, for example, tracking demand for processing power from different machines, prioritizing and scheduling tasks based on network demand and/or providing backup contingency in the event of component failure or reduction in operability.

While various embodiments have been described herein, it should be apparent that various modifications, alterations, and adaptations to those embodiments may occur to persons skilled in the art with attainment of at least some of the advantages. The disclosed embodiments are therefore

intended to include all such modifications, alterations, and adaptations without departing from the scope of the embodiments as set forth herein.

What is claimed is:

1. Headphones comprising:

a pair of first and second wireless earphones to be worn simultaneously by a user, wherein the first and second earphones are separate such that when the headphones are worn by the user, the first and second earphones are not physically connected, wherein each of the first and second earphones comprises:

a body portion;

an earbud extending from the body portion that is inserted into an ear of the user when worn by the user;

a curved hanger bar connected to the body portion, wherein the curved hanger bar comprises a portion that rests upon an upper external curvature of an ear of the user behind an upper portion of an auricula of the ear of the user;

a wireless communication circuit for receiving and transmitting wireless signals;

a processor circuit connected to the wireless communication circuit;

at least one acoustic transducer for producing audible sound from the earbud;

a microphone for picking up utterances of a user of the headphones;

an antenna connected to the wireless communication circuit; and

a rechargeable power source; and

a docking station for holding at least the first wireless earphone, wherein the docking station comprises a power cable for connecting to an external device to power the docking station, and wherein the docking station is for charging at least the first wireless earphone when the first wireless earphone is placed in the docking station.

2. The headphones of claim **1**, wherein:

the wireless communication circuits are for receiving, wirelessly, streaming audio content;

the at least one acoustic transducers are for playing the streaming audio content; and

each of the first and second earphones comprises a buffer for caching the streaming audio content prior to being played by the at least one acoustic transducer.

3. The headphones of claim **1**, wherein the processor circuit for the first earphone is for, upon activation of a user control of the headphones, initiating transmission of a request to a remote network server that is remote from the headphones.

4. The headphones of claim **3**, wherein the processor circuit of the first earphone is further for receiving a response to the request.

5. The headphones of claim **1**, wherein the processor circuits are configured to transition from playing streaming audio content received wirelessly from a first digital audio source via a first communication link to playing streaming audio content received wirelessly from a second digital audio source via a second communication link based on, at least in part, a signal strength for the second wireless communication link.

6. The headphones of claim **5**, wherein:

the wireless communication circuits are for receiving, wirelessly, streaming audio content;

the at least one acoustic transducers are for playing the streaming audio content; and

19

each of the first and second earphones comprises a buffer for caching the streaming audio content prior to being played by the at least one acoustic transducer.

7. The headphones of claim 6, wherein the processor circuit of each of the first and second earphones comprises: 5
 a digital signal processor that provides a sound quality enhancement for the audio content played by the at least one acoustic transducers of the earphone; and
 a baseband processor circuit that is in communication with the wireless communication circuit of the ear- 10
 phone.

8. The headphones of claim 7, wherein the rechargeable power source comprises a passive, wireless rechargeable power source.

9. The headphones of claim 1, the processor circuits of the headphones are configured to receive firmware upgrades transmitted from a remote network server. 15

10. The headphones of claim 9, wherein the headphone are configured to receive the firmware upgrades wirelessly. 20

11. The headphones of claim 10, wherein the processor circuits are configured to transition from playing streaming audio content received wirelessly from a first digital audio source via a first communication link to playing streaming audio content received wirelessly from a second digital audio source via a second communication link based on, at least in part, a signal strength for the second wireless communication link. 25

12. The headphones of claim 11, wherein the processor circuit of each of the first and second earphones comprises: 30
 a digital signal processor that provides a sound quality enhancement for the audio content played by the at least one acoustic transducers of the earphone; and
 a baseband processor circuit that is in communication with the wireless communication circuit of the ear- 35
 phone.

20

13. The headphones of claim 12, wherein:
 the wireless communication circuits are for receiving, wirelessly, streaming audio content;
 the at least one acoustic transducers are for playing the streaming audio content; and

each of the first and second earphones comprises a buffer for caching the streaming audio content prior to being played by the at least one acoustic transducer.

14. The headphones of claim 10, wherein:
 the wireless communication circuits are for receiving, wirelessly, streaming audio content;
 the at least one acoustic transducers are for playing the streaming audio content; and

each of the first and second earphones comprises a buffer for caching the streaming audio content prior to being played by the at least one acoustic transducer. 15

15. The headphones of claim 1, wherein the processor circuit of the first earphone is configured to:

process audible utterances by the user picked by the microphone in response to activation of the microphone by the user; and

transmit a communication based on the audible utterances via the Bluetooth wireless communication links.

16. The headphones of claim 1, wherein the rechargeable power source comprises wirelessly chargeable circuit components. 25

17. The headphones of claim 1, wherein the rechargeable power source comprises a passive, wireless rechargeable power source.

18. The headphones of claim 1, wherein the processor circuit of each of the first and second earphones comprises: 30
 a digital signal processor that provides a sound quality enhancement for the audio content played by the at least one acoustic transducers of the earphone; and
 a baseband processor circuit that is in communication with the wireless communication circuit of the ear- 35
 phone.

* * * * *