

US010507081B2

(12) **United States Patent**  
**Blaisdell et al.**

(10) **Patent No.:** **US 10,507,081 B2**  
(45) **Date of Patent:** **Dec. 17, 2019**

(54) **METHODS FOR TAKING AN IMPRESSION OR SCANNING WITHOUT REQUIRING REMOVAL OF A TEMPORARY HEALING ABUTMENT**

(71) Applicants: **Mark H. Blaisdell**, Bountiful, UT (US); **Todd C. Liston**, Ogden, UT (US)

(72) Inventors: **Mark H. Blaisdell**, Bountiful, UT (US); **Todd C. Liston**, Ogden, UT (US)

(73) Assignee: **ESTHETIC IMPLANT SOLUTIONS, LLC**, Bountiful, UT (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 315 days.

(21) Appl. No.: **15/270,804**

(22) Filed: **Sep. 20, 2016**

(65) **Prior Publication Data**

US 2017/0007372 A1 Jan. 12, 2017

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 14/485,351, filed on Sep. 12, 2014, now Pat. No. 10,016,260, and (Continued)

(51) **Int. Cl.**  
**A61C 8/00** (2006.01)  
**A61B 6/03** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **A61C 8/0001** (2013.01); **A61B 6/032** (2013.01); **A61B 6/14** (2013.01); **A61C 8/008** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... **A61C 8/0001**; **A61C 5/77**; **A61C 8/008**; **A61C 9/0046**; **A61B 6/032**; **A61B 6/14**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

512,840 A 1/1894 Phelps  
1,335,372 A 3/1920 Fredericks  
(Continued)

FOREIGN PATENT DOCUMENTS

WO 20100077130 7/2010  
WO 20100141342 12/2010  
WO 20110157762 12/2011

OTHER PUBLICATIONS

PreFormance Post Cement-retained provisional option (Based on information and belief, available at least as as Jan. 15, 2012).  
(Continued)


*Primary Examiner* — Yogesh P Patel

(74) *Attorney, Agent, or Firm* — Workman Nydegger

(57) **ABSTRACT**

Methods of taking an impression or scan of a patient's oral cavity without requiring removal of a healing cap coupled within the implant in the subgingival void. The method may include providing an anatomical healing cap received within the subgingival void of a given tooth position, where the anatomical healing cap is coupled into an implant in the void. A scanning body or an impression post is inserted into an open end (e.g., the hollow core) of the anatomical healing cap, in-situ, with the anatomical healing cap positioned in the subgingival void, and the implant thereunder (or thereover for a maxillary tooth position). The scanning body or impression post is used as a reference in making the impression or scan. Because this is done without requiring removal of the healing cap, further collapse of the gingival tissue surrounding the void is prevented.

**19 Claims, 36 Drawing Sheets**



**Related U.S. Application Data**

a continuation-in-part of application No. 14/327,869, filed on Jul. 10, 2014, now Pat. No. 9,895,209, which is a continuation-in-part of application No. 14/152,369, filed on Jan. 10, 2014, now Pat. No. 9,572,640, and a continuation-in-part of application No. PCT/US2013/020992, filed on Jan. 10, 2013, which is a continuation-in-part of application No. 13/633,387, filed on Oct. 2, 2012, now Pat. No. 8,628,327, which is a continuation-in-part of application No. 13/347,127, filed on Jan. 10, 2012, now abandoned.

- (51) **Int. Cl.**  
*A61B 6/14* (2006.01)  
*A61C 9/00* (2006.01)  
*A61B 90/00* (2016.01)
- (52) **U.S. Cl.**  
 CPC .... *A61C 9/0046* (2013.01); *A61B 2090/3966* (2016.02)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,475,599	A	7/1949	Erdle	
3,286,350	A	11/1966	Cooper	
4,001,938	A	1/1977	Cooper	
4,975,059	A	12/1990	Sendax	
4,986,753	A	1/1991	Sellers	
5,071,345	A	12/1991	Rosen	
5,180,303	A	1/1993	Hornburg et al.	
5,324,186	A	6/1994	Bakanowski	
5,338,196	A	8/1994	Beaty et al.	
5,431,567	A	7/1995	Daftary	
5,469,908	A	11/1995	Chmel et al.	
5,492,471	A	2/1996	Singer	
5,651,675	A	7/1997	Singer	
5,658,147	A	8/1997	Phimmasone	
5,674,069	A	10/1997	Osorio	
5,695,337	A	12/1997	Tyszblat Sodoun	
5,735,692	A	4/1998	Berger	
5,738,518	A	4/1998	Nowak	
5,813,858	A	9/1998	Singer	
5,839,898	A *	11/1998	Fernandes .....	A61C 8/005 433/173
5,846,079	A	12/1998	Knodel	
5,871,358	A	2/1999	Ingber et al.	
RE36,126	E	3/1999	Beaty et al.	
5,899,695	A *	5/1999	Lazzara .....	A61C 8/008 433/173
5,911,580	A	6/1999	Sharp et al.	
RE36,689	E	5/2000	Beaty et al.	
6,120,292	A	9/2000	Buser	
6,155,828	A	12/2000	Lazzara	
6,217,326	B1	4/2001	Hahn	
6,244,867	B1	6/2001	Aravena et al.	
6,283,753	B1	9/2001	Willoughby	
6,290,499	B1	9/2001	Lazzara et al.	
6,299,448	B1	10/2001	Zdrahala et al.	
6,300,390	B1	10/2001	Angeletakis	
6,361,721	B1	3/2002	Stern	
6,386,876	B1	5/2002	Lee	
6,431,867	B1	8/2002	Gittelton	
6,537,069	B1	3/2003	Simmons	
6,626,671	B2	9/2003	Klardie et al.	
RE38,630	E	10/2004	Lazzara et al.	
7,018,207	B2	3/2006	Prestipino	
7,156,660	B2	1/2007	Huffman	
7,179,089	B2	2/2007	Sims et al.	
7,287,983	B2	10/2007	Ilan	
7,347,689	B2	3/2008	Huffman	
7,429,175	B2	9/2008	Gittelton	
7,563,397	B2	7/2009	Schulman et al.	
7,632,095	B2	12/2009	Ostman et al.	

D611,148	S	3/2010	White, III	
7,762,814	B2	7/2010	van der Zel	
7,798,812	B2	9/2010	Last-Pollak	
7,816,423	B2	10/2010	Karim et al.	
7,922,488	B2	4/2011	Falk et al.	
7,922,490	B2	4/2011	Wen	
8,048,345	B2	11/2011	Feith	
8,105,081	B2	1/2012	Bavar	
8,382,477	B2	2/2013	Philibin	
8,628,327	B1	1/2014	Blaisdell et al.	
8,831,322	B2	9/2014	Abboud	
9,452,032	B2	9/2016	Hochman et al.	
9,572,640	B2	2/2017	Blaisdell	
9,763,753	B2	9/2017	Wang	
9,820,831	B2	11/2017	Cho	
10,136,974	B2	11/2018	Vergoullis et al.	
2001/0005575	A1	6/2001	Kanomi	
2002/0064758	A1 *	5/2002	Lee .....	A61C 8/0001 433/172
2003/0170593	A1	9/2003	Dorfman	
2005/0040551	A1	2/2005	Biegler et al.	
2005/0048440	A1	3/2005	Feng	
2005/0084821	A1	4/2005	Sims et al.	
2006/0046229	A1	3/2006	Teich	
2006/0105296	A1	5/2006	Linder et al.	
2006/0263749	A1	11/2006	Koide	
2006/0286508	A1	12/2006	Bassett	
2007/0092853	A1	4/2007	Liu et al.	
2007/0111165	A1	5/2007	Wallick	
2007/0281278	A1 *	12/2007	Jorneus .....	A61C 8/0001 433/173
2008/0081317	A1	4/2008	White	
2008/0293013	A1	11/2008	Lussi	
2008/0293016	A1	11/2008	Lussi	
2008/0293017	A1	11/2008	Lussi	
2009/0081618	A1	3/2009	LaMar	
2009/0208906	A1	8/2009	Callan	
2010/0266985	A1	10/2010	Yau et al.	
2010/0279254	A1	11/2010	White	
2011/0008754	A1	1/2011	Bassett et al.	
2011/0081627	A1	4/2011	Sun et al.	
2011/0111368	A1	5/2011	Arnold et al.	
2011/0200968	A1	8/2011	Laizure, Jr.	
2011/0229859	A1	9/2011	White	
2011/0024426	A1	10/2011	Amber et al.	
2012/0022648	A1	1/2012	Vult Von Steyern	
2012/0052465	A1	3/2012	Von Both et al.	
2012/0164593	A1	6/2012	Bavar	
2013/0101964	A1	4/2013	Fudim	
2013/0177872	A1	7/2013	Blaisdell	
2013/0288202	A1	10/2013	Hochman et al.	
2014/0319713	A1	10/2014	Blaisdell	
2015/0004563	A1	1/2015	Blaisdell	
2017/0128176	A1	5/2017	Vergoullis	
2017/0172714	A1	6/2017	Blaisdell	
2018/0161134	A1	6/2018	Liston	

OTHER PUBLICATIONS

Custom Temporary Components—<https://www.inclusivedental.com/ToothReplacementSolutions/PartiallyEdentulous/InclusiveToothReplacementSolution/CustomTemporaryComponents.aspx> (Accessed Apr. 11, 2012).  
 “Contour Healer, The Superior Choice for Restorative Healing”, <http://contourhealer.com/about-us>, Based on information and believe—Available at least as early as Dec. 13, 2012.  
 International Search Report and Written Opinion cited in PCT Application No. PCT/US2013/020992 dated Apr. 25, 2013.  
 U.S. Appl. No. 13/347,127, dated Mar. 25, 2013, Non-Final Office Action.  
 U.S. Appl. No. 13/633,387, dated Sep. 10, 2013, Notice of Allowance.  
 U.S. Appl. No. 13/347,127, dated Sep. 24, 2013, Final Office Action.  
 U.S. Appl. No. 13/347,127, dated Apr. 3, 2014, Non-Final Office Action.



(56)

**References Cited**

OTHER PUBLICATIONS

U.S. Appl. No. 13/347,127, dated Aug. 19, 2014, Final Office Action.

U.S. Appl. No. 14/152,369, dated Sep. 12, 2016, Office Action.

U.S. Appl. No. 14/152,369, dated Oct. 13, 2016, Notice of Allowance.

U.S. Appl. No. 14/485,351, dated Mar. 2, 2017, Office Action.

U.S. Appl. No. 14/327,869, dated Mar. 6, 2017, Office Action.

Biomet 3i Brochure “The BellaTek Encode Impression System”.

VP Innovato Holdings, Cervico Guide, [accessed online Feb. 4, 2019] URL: <http://innovatoholdings.com/cervico-guide/>.

Nobel Biocare [accessed Feb. 4, 2019] URL: <http://www.nobelbiocare.com/international/en/home.html>.

VP Innovato Holdings, Cervico Mold, [accessed offline Nov. 27, 2018] URL: <http://innovatoholdings.com/cervico-mold/>.

“The BellaTek® Encode® Impression System—Optimization by Design®: Product Brochure”, BioMet 3i, 2013, pp. 1-8, accessed

via <[www.biomet3i.com/.../BellaTek%20Encode%20Brochure\\_ART1059\\_eu.pdf](http://www.biomet3i.com/.../BellaTek%20Encode%20Brochure_ART1059_eu.pdf)> on Jul. 9, 2019.

“OsseoGuard® Non-Resorbables: Product Brochure”, Zimmer Biomet Dental, 2018, pp. 1-12 accessed via <[https://www.zimmerbiometdental.com/en-US/wps/wcm/connect/dental/629fb5b5-7fc3-42b3-8237-ad95294cadee/ZBINST0033\\_REV\\_A\\_OsseoGuard\\_PTFE\\_Brochure\\_final\\_SECURED.pdf?MOD=AJPERES&CACHEID=ROOTWORKSPACE.Z18\\_1O041O02L8PAF0A9JPRUH520H7629fb5b5-7fc3-42b3-8237-ad96294cadee](https://www.zimmerbiometdental.com/en-US/wps/wcm/connect/dental/629fb5b5-7fc3-42b3-8237-ad95294cadee/ZBINST0033_REV_A_OsseoGuard_PTFE_Brochure_final_SECURED.pdf?MOD=AJPERES&CACHEID=ROOTWORKSPACE.Z18_1O041O02L8PAF0A9JPRUH520H7629fb5b5-7fc3-42b3-8237-ad96294cadee)> on Jul. 9, 2019.

U.S. Appl. No. 15/952,064, filed Apr. 12, 2018, Liston.

U.S. Appl. No. 16/030,055, filed Jul. 9, 2018, Liston.


U.S. Appl. No. 14/485,351, dated Oct. 19, 2017, Final Office Action.

U.S. Appl. No. 14/327,869, dated Oct. 30, 2017, Notice of Allowance.


U.S. Appl. No. 14/485,351, dated Feb. 23, 2018, Office Action.

U.S. Appl. No. 14/485,351, dated May 16, 2018, Notice of Allowance.

\* cited by examiner




**FIG. 1A**




**FIG. 1B**





**FIG. 1E**



**FIG. 1F**







FIG. 2A


FIG. 2B










**FIG. 2F**



**FIG. 2G**



**FIG. 2H**








FIG. 4A







FIG. 4B




**FIG. 4C**



**FIG. 4D**



**FIG. 4E**



**FIG. 5**






FIG. 6





FIG. 7



**FIG. 8**






FIG. 9A




FIG. 9B













FIG. 9D



**FIG. 10**



**FIG. 11**



**FIG. 12**






FIG. 13A

FIG. 13B

FIG. 13C




FIG. 14A




FIG. 14B




FIG. 15A





FIG. 15B





**FIG. 16**







FIG. 17A








**FIG. 18A**




**FIG. 18B**




**FIG. 19**







**FIG. 20**



**FIG. 21A**



**FIG. 21B**



**FIG. 21C**




FIG. 22A




FIG. 22B




FIG. 22C









FIG. 23




**FIG. 24A**



**FIG. 24B**




**FIG. 25A**




**FIG. 25B**





**FIG. 26A**



**FIG. 26B**

**METHODS FOR TAKING AN IMPRESSION  
OR SCANNING WITHOUT REQUIRING  
REMOVAL OF A TEMPORARY HEALING  
ABUTMENT**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

The present application is continuation-in-part of U.S. patent application Ser. No. 14/327,869 filed Jul. 10, 2014, which is a continuation-in-part of U.S. patent application Ser. No. 14/152,369, filed Jan. 10, 2014, which is a continuation-in-part of U.S. patent application Ser. No. 13/633,387 filed Oct. 2, 2012, now U.S. Pat. No. 8,628,327. U.S. patent application Ser. No. 14/327,869 is also a continuation in part of International Application No. PCT/US2013/020992, filed Jan. 10, 2013, which claims priority to U.S. patent application Ser. No. 13/347,127, filed Jan. 10, 2012. The disclosure of each of the above patents and applications is herein incorporated by reference in its entirety. U.S. patent application Ser. No. 14/485,351, filed Sep. 12, 2014 is also incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

1. The Field of the Invention

This invention relates to casting jigs and associated methods for manufacturing healing caps or cuffs used in any stage of oral surgery where a tooth is extracted or missing. Such an example of oral surgery includes first stage oral surgery, for example, when an implant is initially placed into a tooth void (e.g., whether the tooth is extracted or was congenitally or otherwise missing). The inventive healing caps or cuffs may also be used in any other dental surgery where it is desired to preserve the emergence profile of gingival tissue surrounding one or more teeth (e.g., second stage surgery, immediate or delayed implant placement, etc.).

2. Background and Relevant Art

In modern dentistry, when one or more teeth are removed it is desirable to eventually replace the tooth or teeth with a prosthesis (e.g., a crown, bridge, etc.), although this is typically accomplished weeks later. Once the tooth is removed or missing, a dental implant is placed into the bone tissue of the jaw to provide a secure foundation upon which a prosthesis can be supported. Typically, the site is allowed to heal for a period of time prior to installation of the permanent prosthesis. Currently, a device known as a healing cap, abutment, or cuff is coupled into the dental implant while the site is allowed to heal, to cap or cover the inside of the dental implant and to preserve the ability to re-access the dental implant once the site has sufficiently healed, when it is desired to install a prosthesis. Once the site has healed (e.g., typically 1.5 to 6 months after implant placement), the healing cap, abutment, or cuff is removed, and a custom prosthesis (e.g., a crown) may be installed, supported by the dental implant anchored within the jaw bone.

Existing dental healing caps, abutments, or cuffs, as well as the methods employed in their installation during immediate or subsequent dental placement and oral surgery exhibit several shortcomings. In addition, it would be advantageous to provide for the ability of a practitioner to manufacture his or her own healing caps exhibiting improved characteristics.

BRIEF SUMMARY

The present invention is directed to casting jigs, methods, and kits that may be used in chair-side or small-scale

manufacture of customizable sculptable anatomical healing caps by a practitioner for installation into a patient. A casting jig may include a body having one or more wells within the body, each well being open at a proximal end thereof and having a negative shape corresponding to an anatomical healing cuff body of a given tooth position. Each respective anatomical healing cuff body negative shape includes an asymmetrical cross-section and an irregular surface so that an anatomical healing cuff body having said shape is configured to provide a substantially custom filling of at least an emergence portion of a void where a natural tooth once emerged or should have emerged from the void (e.g., in the case of a congenitally missing tooth). The casting jig may further include a socket at a distal end of each well that is configured to releasably receive therein a dental implant or dental implant analog.

A related method of manufacture may include providing a casting jig (e.g., as described above). A dental implant or dental implant analog may be releasably received within a corresponding socket of the casting jig. A curable or otherwise settable material is introduced into the well of the casting jig (e.g., while in a flowable state), which material is allowed to set or cure so as to become rigid or hard. Upon setting or curing, the resulting rigid material is in the shape of an anatomical healing cuff body having the desired asymmetrical cross-section and irregular surface so that the anatomical healing cuff body is configured to provide substantially custom filling of at least the emergence portion of a void where a natural tooth once emerged or should have emerged. The cured or set rigid anatomical healing cuff body can be easily removed from the casting jig for subsequent installation into a dental implant which is in the jaw of a patient. In one embodiment, the practitioner may further customize the anatomical healing cuff body by applying additional material thereto or removing material therefrom (e.g., immediately prior to installation).

A related kit for use in manufacture of customizable sculptable anatomical healing caps may include a casting jig (e.g., as described above) and a curable or otherwise settable material for introduction into a well of the casting jig to form an anatomical healing cuff body of an anatomical healing cap. Such a material may be flowable prior to setting or curing, so as to allow its easy introduction into the well prior to becoming rigid as a result of curing or setting.

Because the emergence portion of the various tooth positions are not identical to one another (but they do remain substantially the same from one person to another person when considering the same tooth position), different customizable sculptable anatomical healing caps can be provided for the various tooth positions, which differ in the particular configuration of the enlarged cuff body of the respective healing cap. Use of such anatomical healing caps greatly improves the ability of the practitioner to preserve desirable aesthetic characteristics of the gingival tissue surrounding the location of the dental implant and associated crown or other prosthesis.

Furthermore, the presently described casting jigs and associated kits and methods allow a practitioner to manufacture such anatomical healing caps himself or herself, e.g., within one's own office. This may allow the practitioner to reduce costs associated with purchase of expensive state of the art healing caps, while providing a superior product which provides an anatomical, improved fit for better preservation of the gingival tissue.

Another embodiment is directed to a casting jig system including a casting jig having a body including one or more wells, each being open at a proximal end thereof and having



a negative shape corresponding to the anatomical healing cuff body of a given tooth position. Each negative shape may include an asymmetrical cross-section and irregular surface so that an anatomical healing cuff body having the shape provides substantially custom filling of at least an emergence portion of a void where a natural tooth once emerged from the void or where a tooth would have emerged from the void. A socket may be provided at the distal end of each well, and an opening may be provided in the bottom surface of the casting jig for accessing the socket. An elongate handle is provided with the casting jig, which handle is insertable through an opening in the bottom surface of the casting jig, up into the socket at the bottom of the well. The handle includes a recessed connection in a distal end thereof (e.g., similar to a dental implant analog). This allows a temporary abutment (e.g., commercially available) to be inserted into the well, and coupled into the distal end of the elongate handle, within the jig. The temporary abutment may serve as a core about which the anatomical healing cuff body is to be formed, in the well, as a curable or otherwise settable dental material is introduced into the well, around the temporary abutment core.

Once the cast anatomical cuff body hardens, a screw coupling the core to the elongate handle may be backed out (e.g., through the hollow temporary abutment core), and the elongate handle removed from below (through the opening in the bottom of the casting jig). The formed anatomical healing cap, including the anatomical cuff body may be removed from above, through the open top of the well.

A crown forming jig and associated method for forming an inexpensive, chair-side prepared bis-acrylic temporary crown that may be easily and quickly installed over the anatomical healing cuff body is also disclosed. Such a crown forming jig may include a body including one or more wells in the body, each well being open at a proximal end thereof and having a negative shape corresponding to a crown portion of a given tooth position. The body may further include a first portion of an alignment mechanism disposed on or within the proximal top surface of the body of the crown forming jig. A slug including a displacement body (e.g., formed of polycarboxylate) is also provided, which slug includes the second portion of the alignment mechanism. An uncured bis-acrylic material is introduced into the well, the displacement body of the slug is aligned over the crown forming casting jig body, and the two are brought together. The displacement body penetrates the well, pushing the bis-acrylic material outwardly, towards the sidewalls of the well. The alignment mechanism also serves as a stop to limit advancement of the displacement body into the well to a desired point, so as to ensure that the resulting hollow crown is of the desired thickness once the bis-acrylic sets. The cured bis-acrylic material advantageously will not bond to the polycarboxylate displacement body, allowing the formed hollow crown to be easily and quickly removed from the casting jig. The crown can be formed chair-side, and quickly installed as a temporary crown over the anatomical healing cap.

The present invention is also directed to methods of taking an impression or scan of a patient's oral cavity without requiring removal of a healing cap coupled within the implant in the subgingival void. For example, such a method may include providing an anatomical healing cap received within the subgingival void of a given tooth position, where the anatomical healing cap is coupled into an implant disposed adjacent (e.g., over for a mandibular tooth position) the anatomical healing cap. A scanning body or an impression post is inserted into an open end (e.g., the hollow

core) of the anatomical healing cap, in-situ, with the anatomical healing cap positioned in the subgingival void, and the implant thereunder (or thereover for a maxillary tooth position). Such allows the scanning body or impression post used as a reference in making the impression or scan to be inserted without first having to remove the anatomical healing cap. Such is advantageous as it thus prevents further collapse of the gingival tissue surrounding the void that may occur when removal occurs, and during any period where the anatomical healing cap were not in place.

The scanning body or impression post may be keyed to the interior surface of the healing cap (e.g., grooves and mating protrusions) to ensure proper orientation of the scanning body, and to aid in ensuring that the scanning body or impression post is fully seated to the bottom of the healing cap. Where a scan is being taken, radiopaque markers may be provided within the anatomical healing cap and/or scanning body for use as reference points when building the scanned model or image from the scan data.

These and other advantages and features of the present invention will become more fully apparent from the following description and appended claims, or may be learned by the practice of the invention as set forth hereinafter.

#### BRIEF DESCRIPTION OF THE DRAWINGS

To further clarify the above and other advantages and features of the present invention, a more particular description of the invention will be rendered by references to specific embodiments thereof, which are illustrated in the appended drawings. It is appreciated that these drawings depict only typical embodiments of the invention and are therefore not to be considered limiting of its scope. The invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

FIG. 1A is a perspective view of an exemplary upper dental arch;

FIG. 1B is a perspective view of the dental arch of FIG. 1A in which a central incisor has been removed, leaving a void;

FIG. 1C is a perspective view of the dental arch of FIG. 1B in which a dental implant surgical drill is used to prepare an anchor hole in the underlying bone for anchoring a dental implant;

FIG. 1D is a perspective view of the arch of FIG. 1C as an implant is being inserted (e.g., with the aid of a transfer coping);

FIG. 1E is a perspective view of the arch and into the void showing the implant anchored into the bottom of the void;

FIG. 1F is a perspective view of the arch showing a state of the art healing cuff coupled into the implant;

FIG. 2A is an exploded perspective view of an exemplary anatomical healing cap configured for filling the emergence portion of the void formed when an upper central incisor is removed or is missing;

FIG. 2B is an assembled perspective view of the anatomical healing cap of FIG. 2A;

FIG. 2C is a side elevation view of the anatomical healing cap of FIG. 2B;

FIG. 2D is a top view of the anatomical healing cap of FIG. 2B;

FIG. 2E is a cross-sectional view through the anatomical healing cap of FIG. 2B;

FIG. 2F is a perspective view similar to that of FIG. 2B, but showing an alternative configuration at the distal dental implant end;



## 5

FIG. 2G is a perspective view similar to that of FIG. 2B, but showing another alternative configuration at the distal dental implant end;

FIG. 2H is a perspective view similar to that of FIG. 2B, but showing an alternative configuration including a removable grippable handle;

FIG. 3A is an exploded perspective view showing a related system including an anatomical healing cap and an associated temporary crown form;

FIG. 3B is a perspective view showing the system of FIG. 3A with the temporary crown form coupled over the anatomical healing cap;

FIG. 4A is a perspective view showing a portion of the cuff body of the healing cap being customized by removal with a dental burr;

FIG. 4B is a perspective view showing the cuff body being customized by building up with application of a dental material;

FIG. 4C is a perspective view of the arch of FIG. 1E in which an anatomical healing cap has been coupled into the implant, leaving no gap between the cuff body of the healing cap and the gingival tissue surrounding the emergence portion of the void;

FIG. 4D is another perspective view of the arch of FIG. 4C;

FIG. 4E is another perspective view of the arch of FIG. 4C in which a temporary crown has been formed over the healing cap;

FIG. 5 is a perspective view of an exemplary casting jig for manufacturing anatomical healing caps;

FIG. 6 is a cross-sectional view through the casting jig of FIG. 5;

FIG. 7 is a cross-sectional view similar to FIG. 6, but in which the dental implant analog and the implant housing have been removed from the socket below the well of the casting jig;

FIG. 8 is a perspective view showing positioning of an elongate body (e.g., a straw, an implant wrench, a temporary abutment, etc.) into the recessed connection of the implant or implant analog and introduction of the curable or otherwise settable material around the elongate body so as to form an anatomical healing cuff body while preserving access through the cuff body to the implant or implant analog;

FIG. 9A is a cross-sectional view through the casting jig of FIG. 8 as the anatomical healing cap is being formed;

FIG. 9B is a cross-sectional view through the casting jig of FIG. 8 in which a temporary abutment is used as a core around which the anatomical healing cap is being formed;

FIG. 9C is a cross-sectional view through the casting jig of FIG. 8 in which a temporary abutment having a lower profile than that of FIG. 9B is used as a core around which the anatomical healing cap is being formed;

FIG. 9D is a cross-sectional view through the casting jig of FIG. 8, similar to that of FIG. 9B, but illustrating an alternative embodiment;

FIG. 10 is an exploded perspective view of the anatomical healing cap manufactured using the casting jig next to the associated implant analog;

FIG. 11 is a view of an anatomical healing cap formed using the casting jig and a coupling screw as the elongate body;

FIG. 12 is a view of a pontic configured similar to the anatomical healing caps formed using the casting jig, but which does not include a central access channel 138 or locking structure 150;

## 6

FIG. 13A illustrates an exemplary elongate handle for insertion through the opening in the bottom surface of a casting jig during manufacture of an anatomical healing cap;

FIG. 13B illustrates another exemplary elongate handle, similar to that of FIG. 13A;

FIG. 13C illustrates another exemplary elongate handle, similar to that of FIG. 13A, but with a generic recessed connection, rather than a keyed structure;

FIGS. 14A-14B illustrate perspective and cross-sectional views, respectively, of an exemplary temporary abutment core;

FIGS. 15A-15B illustrate perspective and cross-sectional views, respectively, of the temporary abutment core and an associated screw for retaining the core in the distal end of the elongate handle during manufacture of the anatomical healing cap;

FIG. 16 illustrates a practitioner gripping the proximal end of the elongate handle with a temporary abutment core retained in the distal end thereof;

FIG. 17A illustrates the elongate handle and retained abutment core inserted through the opening in the bottom surface of a casting jig, positioning the abutment core in the well of the jig;

FIG. 17B illustrates injection of a curable or settable material into the well, surrounding the abutment core, which material hardens to form the desired anatomical healing cuff body surrounding the abutment core;

FIGS. 18A-18B illustrate perspective and cross-sectional views, respectively, of the formed anatomical healing cap separated from the elongate handle, as the screw is backed out, allowing the anatomical healing cap to be removed through the top of the well of the casting jig, and the elongate handle to be removed through the bottom of the casting jig;

FIG. 19 illustrates the finished anatomical healing cap ready for placement into the void where a tooth once emerged or would have emerged;

FIG. 20 illustrates how a curable or otherwise settable material may be injected into a generic recessed connection of the handle, between the circular wall of the handle and a keyed locking member of the abutment core inserted into the handle, converting the generic recessed connection so as to be keyed to the particular abutment core inserted therein;

FIGS. 21A-21C illustrate an exemplary crown forming casting jig for use in forming a bis-acrylic crown for placement over the anatomical healing cap;

FIG. 22A illustrates the crown forming casting jig of FIGS. 21A-21C with uncured bis-acrylic material placed in the well thereof;

FIG. 22B illustrates a polycarboxylate slug being pressed into the well of the crown forming casting jig of FIG. 22A, seating the alignment mechanism of the casting jig and slug, while displacing the bis-acrylic material from the central portion of the well, so as to form a bis-acrylic hollow crown;

FIG. 22C illustrates a cross-section through the finished hollow crown after it has hardened and been removed from the casting jig;

FIG. 23 illustrates an exemplary bis-acrylic hollow crown after it has hardened and been removed from the casting jig;

FIG. 24A illustrates a scanning body or impression post being inserted into an open end of an anatomical healing cap, such that the body or post is atop the healing cap, and the healing cap is atop an implant, all in-situ;

FIG. 24B is a cross-sectional view of the stacked implant, anatomical healing cap, and scanning body as seen in FIG. 24A;



FIG. 25A-25B are perspective and cross-sectional views, respectively, of an anatomical healing cap, such as that seen in FIG. 24A; and

FIGS. 26A-26B are perspective and cross-sectional views, respectively, of an impression post or scanning body as seen in FIG. 24A.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

##### I. Introduction

One problem with conventional healing caps and related methods of oral surgery is that those features of the gingiva that provide much of the characteristic natural aesthetic appearance of natural teeth and adjacent gum tissue are almost always lost once a tooth is pulled and replaced with a prosthesis. In particular, the gingival tissue surrounding the crown of a natural tooth where it emerges (i.e., its emergence profile) is lost during such procedures.

The gingival cuff refers to the generally scalloped pattern of the gingival tissue that is most prominently seen along the buccal surface of the teeth. The height of contour of the gingival cuff refers to the difference between the most occlusal extension of the gingiva (i.e., between teeth) as compared to its location at the center of a tooth. Generally, the height of contour of the gingival cuff is greatest at a location between two adjacent teeth. In other words, the location of the gingival cuff extends occlusally to its greatest extent at this location between the teeth. At a location corresponding to a buccal center face of a tooth, the location of the gingival cuff exhibits its lowest occlusal extension.

When a natural tooth is pulled and eventually replaced with a custom crown or other prosthesis, much of the dynamic range of the previous height of contour is lost because the gingival tissue between adjacent teeth recedes, and is lost.

Gingival tissue disposed between adjacent teeth is often referred to as the interdental papilla. This tissue resides between the void resulting from the pulled tooth and the adjacent remaining tooth. As a result of the loss of the tooth, the interdental papilla may atrophy and fill the void over time. As a result, much of the interdental papilla tissue, particularly the initial and desirable aesthetic characteristics of this tissue, also tends to be lost upon removal of the natural tooth.

At the extreme gingival edge of the gingival cuff there is gingival tissue that overlies the underlying jaw bone. This gingival tissue typically exhibits a prominence in the buccal direction (i.e., it sticks out or protrudes buccally) and is often referred to as buccal prominence. While the gingival tissue over this bony tissue is not necessarily lost, the prominence by which the tissue sticks out buccally is typically lost when a natural tooth is pulled.

The present invention is directed to devices, kits, and methods allowing small-scale manufacture of customizable sculptable anatomical healing caps, allowing the practitioner to chair-side manufacture the needed anatomical healing caps for use with any given patient. Because the healing caps anatomically match the given tooth position where they are placed, they provide custom filing of at least the emergence portion of the void resulting from removal of a selected tooth (or where a tooth should be in the case of a congenitally missing tooth). Because of the anatomical features of the healing cap, use of the healing cap advantageously allows the practitioner to better preserve the desirable aesthetic features of the gingival tissue surrounding and associated with natural teeth.

FIGS. 1A-1F illustrate an upper dental arch, as well as typical steps employed in removal of a tooth, installation of an implant, and placement of a state of the art healing cuff or cap. For example, FIG. 1A shows a person's upper dental arch **100** including central incisors **102**. Also apparent in FIG. 1A is the gingival cuff **104** where the natural teeth emerge from the gingival tissue, and the typical height of contour where the highest contour  $H_2$  is between two adjacent teeth, while the lowest contour or point along the gingival cuff is  $H_1$ , at the center of the buccal face of the teeth. The difference  $H$  between  $H_2$  and  $H_1$  represents the height of contour associated with the natural teeth and gingival cuff prior to removal of the natural tooth.

In addition to the gingival cuff, a buccal prominence **106** is associated with the gingival edge of gingival cuff **104**, disposed gingivally relative to the crown of each respective tooth (e.g., labeled buccal prominence **106** corresponds to tooth **102**). FIG. 1B shows the dental arch **100** after central incisor **102** has been removed, leaving a void **108** once occupied by the root of tooth **102**. The top or most gingival portion of void **108** is the emergence portion **110** of void **108**, whose contours are defined by the shape of the emergence portion of the tooth **102**, just below the crown portion of the tooth. Also apparent in FIG. 1B is the interdental papilla **112**.

As shown in FIG. 1C, the void **108** is prepared to receive a dental implant **114** by drilling into the bone tissue of the underlying jaw bone at the bottom of void **108**, after which a dental implant **114** may be inserted therein, as shown in FIG. 1D-1E. FIG. 1D shows a transfer coping **115** or similar structure being used to aid in seating the implant **114** into void **108**. FIG. 1E illustrates a view down into void **108** once dental implant **114** has been fully seated within the prepared underlying bony tissue (and transfer coping **115** has been uncoupled from implant **114**). Much of the lower portion of void **108** may be filled by dental implant **114**, while the emergence portion **110** remains unfilled. FIG. 1F shows installation of a state of the art healing cap or cuff **116**, which couples into dental implant **114**. Healing cap or cuff **116** is typically provided in various sizes, each of which is cylindrical (e.g., each of a different diameter and/or height). A healing cap or cuff is selected from the available sizes and coupled into dental implant **114**. Healing cap or cuff **116** may remain in place for several weeks (e.g., 1.5 to 6 months) while the site heals. As shown in FIG. 1F, because the healing cap or cuff **116** is not anatomically shaped to fill the emergence portion **110** of void **108**, gaps **118** remain between healing cap or cuff **116** and the gingival walls defining emergence portion **110**. Placement of the healing cap or cuff **116** may be the end of what is termed the first stage procedure. It will be understood that while described in terms of various stages, healing caps or cuffs **116** may be placed in various other oral surgery procedures (e.g., second stage, immediate placement, subsequent placement, etc.). Similarly, the inventor's anatomical healing cap devices, systems and methods may be employed in various oral surgery procedures (e.g., during a first or second stage procedure, in an immediate placement procedure, in a delayed placement procedure, or in any other appropriate oral surgery procedure). The greatest benefit may be obtained where the anatomical healing cap devices are placed immediately or soon after placement of the implant, so that the gingival tissue is immediately supported, and loss of desired gingival tissue features is minimized.

By way of example, in a subsequent second stage procedure, after a healing period of at least several weeks, the person may return to the practitioner's office, the healing cap



or cuff **116** may be removed, and a permanent prosthesis may be installed by coupling into implant **114**. During the healing period, the gingival tissue surrounding healing cap or cuff **116** progressively adapts to the shape provided by healing cap or cuff **116**, collapsing into, growing into, or otherwise filling gaps **118**. In addition, the height of contour of the gingival cuff tends to be compressed (i.e., reduced) as the tissue between adjacent teeth recedes, the interdental papilla fall or otherwise fill gaps **118**, and the buccal prominence **106** recedes so as to be less prominent buccally. As a result, the emergence profile and other desirable gingival features are compromised. At this stage, even if one were to install a crown or other prosthesis that were a perfect match to the natural tooth, including the subgingival emergence portion, it is often too late to recapture the prior characteristics of the surrounding gingival tissue, which have been lost. Furthermore, when installing such a prosthesis at this later stage, the gingival tissue that has grown into gaps **118** is often cut away or compressed in order to make space for the prosthesis. Such activity can lead to subsequent necrosis of the gingival tissue.

Customizable sculptable anatomical healing caps specifically configured to preserve or restore or create (in the case of missing teeth) as much of this gingival tissue, its emergence profile, and other features as possible are disclosed in the inventors' earlier U.S. patent application Ser. No. 13/347,127 filed Jan. 10, 2012 and entitled CUSTOMIZABLE SCULPTABLE ANATOMICAL HEALING CAPS, SYSTEMS, AND RELATED METHODS, herein incorporated by reference in its entirety. The present application discloses casting jigs, and related kits and methods for use in manufacture of the anatomical healing caps. The casting jigs, kits, and methods advantageously allow a practitioner to manufacture such anatomical healing caps himself or herself. Manufacture may be easily achieved chair-side, on a small scale, or both. Of course, such casting jigs could also be employed in a large-scale manufacture process.

### III. Exemplary Customizable Sculptable Anatomical Healing Caps

FIGS. 2A-2E illustrate various views of an exemplary sculptable anatomical healing cap **130a** configured to fill the emergence portion of a void resulting from removal of an upper central incisor. Sculptable anatomical healing cap **130a** includes an elongate body **132** extending between a proximal end **134** and a distal dental implant insertion end **136**. Body **132** may be advantageously hollow, including a hollow channel **138** with open ends and extending generally along longitudinal axis A so as to allow insertion of coupling screw member **140** into hollow channel **138**, by which external threads **142** can be coupled into corresponding internal threads of a dental implant **114**.

Sculptable healing cap **130a** advantageously includes an enlarged cuff body **144a** extending laterally outward from hollow elongate body **132**. In one embodiment, body **132** and body **144a** are integral. In other words, they may be one and the same, such that no separate body **132** is present. This is particularly so where the cuff body **144a** is formed by casting a curable or otherwise settable dental material within a casting jig. Of course, a separate body **132** may be provided in such a casting jig manufactured embodiment, by casting the cuff body about body **132** (e.g., body **132** may initially comprise a straw or temporary abutment inserted into the well of the casting jig, about which the cuff body **144a** is formed. Enlarged cuff body **144a** is disposed between proximal end **134** and distal end **136**, and advantageously is shaped, as manufactured, to provide a substantially custom fit so as to fill emergence portion **110** of void

**108**. In the illustrated configuration, cuff body **144a** includes a subgingival or lower portion **146a** and an exposed or upper portion **148a**. Subgingival portion **146a** becomes inserted within emergence portion **110** of void **108** during use, while exposed portion **148a** resides gingivally above void **108**.

Both portions **146a** and **148a** may be shaped to mimic the shape of the natural tooth which may have immediately prior resided within void **108**. In particular, subgingival portion **146a** is shaped to mimic that portion of the natural tooth which resides immediately below the gingival surface, so that this portion **146a** mimics the emergence portion including the emergence profile of the natural tooth. In order to mimic the natural tooth contours just below the gingival surface, the subgingival portion **146a** includes an asymmetrical cross-section and an irregular surface which mimic the emergence portion and emergence profile of the natural tooth. This allows portion **146a** to provide substantial custom filling of emergence portion **110** of void **108** resulting from removal of an upper central incisor **102**.

Portion **148a** may also be shaped to mimic the shape and contour of the natural tooth, although portion **148a** resides above void **108**. The emergence profile is defined by the interface between the subgingival portion **146a** and exposed portion **148a**. In some embodiments, exposed portion **148a** may be omitted, although it may be preferable to include an exposed portion so as to provide a surface that extends somewhat above the gingival tissue around the emergence profile, to better preserve the natural features of the emergence profile gingiva. For example, this provides support structure against which the gingival tissue can be supported and prevented from collapsing, even where the particular person's emergence profile may differ somewhat from the as manufactured subgingival portion **146a** that approximates a custom fit. In one embodiment, the exposed portion **148a** does not extend occlusally to the same extent that a normal natural tooth would. For example, occlusal features, including cusp features of the natural tooth may simply be omitted (e.g., the occlusal or top surface of the exposed portion **148a** may simply be a generally flat surface, with a hole therein where hollow channel **138** intersects the generally flat surface.

In one embodiment, hollow channel **138** of body **132** may be bounded by a cylindrical or other shaped wall, which may or may not extend proximally above exposed portion **148a**.

At least subgingival portion **146a** of cuff body **144a** comprises a sculptable material so that a practitioner can easily remove select areas of portion **146a**, can add to (i.e., build up) portion **146a** with a dental material that will adhere (e.g., a curable dental material), or both so that portion **146a** can be chair-side fully customized to provide an exact, custom fit that fills emergence portion **110** of void **108**. Sculptability is advantageous because while the shape and size of the emergence portion **110** of void **108** is more or less the same for different persons for a particular given tooth position (e.g., generally all persons will have very similar emergence portions for their upper central incisors), individual people do vary somewhat from individual to individual, and the ability to easily remove material, add material, or both relative to portion **146a** allows the practitioner to fully customize portion **146a** for a given emergence portion **110** of void **108**.

Of course, in some embodiments, more than a single size cuff body may be provided for any given tooth position. For example, children may exhibit differently sized emergence portions as compared to adults for a given tooth position. Similarly, some individuals may have particularly large or small teeth, so that their emergence portions may vary



somewhat from the normal or average size. As such, in one embodiment, different sizes (e.g., normal adult size, a “large” adult size, a “small” adult size, and/or a child size) may be provided, such that the practitioner may choose the most appropriate size, which may then be fully customized by sculpting. Such differences in sizing can be provided within the casting jigs of the present invention. Because the cuff body is sculptable, a practitioner may simply add to or remove material as needed to achieve the desired size.

In one embodiment, subgingival portion **146a** may intentionally be sized to be slightly larger than the typical average emergence profile, so that the practitioner may shave or otherwise remove portions therefrom (e.g., with a dental burr, scalpel or other suitable tool) immediately prior to placement. This may be advantageous as it may be easier and less time consuming to typically require removal of material rather than supplementation, where material must be added to fully customize the subgingival portion **146a**. In some embodiments, it may be expected that little or no modification (either removal or adding to) may be required. As such, the size and shape provided is already substantially configured to fill the person’s emergence portion **110** of void **108** (with substantially no gaps), providing the same emergence profile as was provided by the natural tooth to thereby support the gingival tissue.

In one embodiment, the subgingival portion **146a**, and preferably the entire cuff body **144a** is therefore not formed of metal, but comprises a material that may be easily and conveniently shaved or cut away, as well as added to. Such suitable materials include any of various plastic materials, dental composite materials, or other materials that can be readily customizable through use of a dental burr, scalpel, or other suitable tool. When manufactured with use of the present inventive dental jigs, cuff body **144a** may be formed from a curable or otherwise settable dental material (e.g., dental composite, etc.) that may be dispensed into the well of the casting jig so as to form the desired cuff body **144a**. In one embodiment a radiopaque filler may be incorporated into the plastic or composite so that the subgingival structures of the healing cap can be viewed by x-ray or other imaging technique. Such materials also advantageously will readily bond to curable or other suitable adhering dental materials applied thereto where it is desired to add size or adjust contour to the as mass-manufactured cuff body. In one embodiment, the entire elongate body and enlarged cuff body may comprise a single piece of material (e.g., plastic or composite material).

In one embodiment, the exterior surface of cuff body **144a**, particularly subgingival portion **146a**, may be treated for stimulation of bone or other tissue growth. For example, the material of body **144a** or portion **146a** may be particularly selected so as to stimulate growth (e.g., a calcium containing material such as hydroxyapatite or similar bone growth promoting material), or the surface may be mechanically (e.g., roughened, smoothed, specific texture patterned), chemically, or otherwise treated to stimulate desired growth. While stimulation of bone growth may be desired, in another embodiment, material selection or treatment may be specifically configured to promote soft tissue growth.

In one embodiment, the distal dental implant insertion end **136** of sculptable anatomical healing cap **130a** may include a locking member **150** with a non-circular perimeter configured for insertion into a correspondingly shaped proximal end of a dental implant **114**. In the illustrated configuration, the locking member **150** is hexagonal. Other configurations similarly configured to lock against rotation will be readily apparent to one of skill in the art (e.g., triangular, 4-sided,

5-sided, use of non-circular curved sides (e.g., an oval), combination of straight and curved sides, etc.). This locks the healing cap **130a** against rotation once inserted within dental implant **114**. Any suitable anti-rotation locking mechanism, including those proprietary to various dental implant manufacturers within the art, may be employed. Indeed, as will be explained below, the casting jigs of the present invention may provide for the ability to cast such a proprietary shaped locking mechanism as a part of the as manufactured healing cap through use of a corresponding dental implant during casting.

In another embodiment, the distal dental implant insertion end **136** may include a circular locking member **150'** (see FIG. 2F). In another embodiment, no locking member at all is provided (see FIG. 2G). Any such embodiments may be prepared through use of the inventive casting jigs. In the embodiment of FIG. 2G, external threads **142** are simply coupled into corresponding internal threads of dental implant **114**, and the shape of subgingival portion **146a** itself can serve to prevent rotation, as this portion is non-circular and engages against the gingival tissue bounding emergence portion **110** of void **108**. Other coupling mechanisms between the healing cap and dental implant **114** are possible. For example, the location of internal and external threads may be switched (i.e., internal threads on healing cap, and corresponding external threads on dental implant). Various other suitable coupling mechanisms will be apparent to one of skill in the art in light of the present disclosure.

In one embodiment, a removable grippable handle may be provided at the proximal end **134** of body **132**. As shown in FIG. 2H, a grippable handle **152** may be provided. Handle **152** may include a shaft **154** extending laterally outwards from elongate body **132**, cuff body **144a**, or both. In one embodiment, shaft **154** may be disposed adjacent the buccal surface of body **132**, cuff body **144a**, or both, which advantageously orients the handle in the most suitable position during insertion into void **108**. As shown, handle **152** may be generally T-shaped, including a cross-bar **156** atop or near end of shaft **154**. Another shaft **154'** may be provided opposite shaft **154**, providing two points disposed laterally outward for easy gripping. Shaft **154**, shaft **154'** and/or cross-bar **156** provide surfaces that can be easily gripped by dental pliers or another suitable tool available to the practitioner. Shaft **154'** and T-shaped handle **152** may be cast in the inventive casting jig by simply providing these extensions at a top surface of the well used in forming the cuff body, as will be shown and described below in conjunction with FIG. 5. Once the healing cap is placed within void **108**, handle **152** (including shaft **154'**) may be removed (e.g., cut away).

While the illustrated configuration is shown with cuff body **144a** generally aligned with axis A of channel **138**, in another embodiment, the axis A of channel **138** may be offset relative to an axis of cuff body **144a**. Similarly, cuff body **144a** may not be “on center” relative to axis A of threaded portion **142**. This may be beneficial where the natural tooth (and thus void **108**) is mis-aligned relative to what would be “normal”. Such configurations allow the practitioner to account for such situations.

It will be understood that anatomical healing caps may also be provided for other tooth positions, such as upper lateral incisors, upper cuspids, upper bicuspid, upper molars, lower incisors, lower cuspids, lower bicuspid, and lower molars. It will be apparent that a single configuration may sometimes be suitable for two or more different tooth positions (e.g., a single bicuspid configuration may be used for both first and second bicuspid, a single molar configura-



ration may be used for both first and second molars, a single lower incisor configuration may be used for all lower incisors, etc.). Additional details of the anatomical healing caps are disclosed in U.S. patent application Ser. No. 13/347, 127 filed Jan. 10, 2012 and entitled CUSTOMIZABLE SCULPTABLE ANATOMICAL HEALING CAPS, SYSTEMS, AND RELATED METHODS, already incorporated by reference in its entirety.

FIGS. 3A-3B illustrate healing cap **130a** of FIG. 2B in combination with a temporary crown form **160** that may be used with the healing cap in chair-side manufacture and placement of a temporary provisional crown or other prosthesis.

FIGS. 1A-1E discussed above show the same steps to be taken when installing the anatomical healing caps. As shown in FIGS. 1A-1E, the tooth is removed, the void **108** is prepared to receive dental implant **114**, and dental implant **114** is anchored into the underlying bony tissue of the jaw bone. Rather than installing the cylindrical state of the art healing cap or cuff shown in FIG. 1F, the appropriate sculptable anatomical healing cap is selected (e.g., healing cap **130a** configured for filling the emergence portion **110** of void **108** of an upper central incisor).

The as manufactured shape and contours, which are a very close fit to the actual emergence portion **110** and emergence profile of the void **110** and tooth **102**, may be custom modified as shown in FIG. 4A by removing select portions of cuff body **144a** (particularly subgingival portion **146a**) with a dental burr **180** or other suitable tool. As shown in FIG. 4B, if necessary, the practitioner may build up portions of cuff body **144a** (particularly subgingival portion **146a**) by applying and curing a dental material (e.g., light-curable, chemically-curable, heat curable, or other adhering dental material) **182**. This is possible because at least the subgingival portion **146a** of cuff body **144a** is formed of a curable or otherwise settable material that is easily removed with the aid of a dental burr **180** or similar tool. Similarly, the material of body **144a** strongly bonds to curable material **182**, should such additions be desired. For example, one may employ the same curable or otherwise settable dental material employed in casting the cuff body **144a** in the casting jig to add material, if desired. By removing material, adding material, or both, the practitioner is advantageously able to relatively quickly customize at least the subgingival portion **146a** of the cuff body **144a** so that it provides a perfect or near perfect fit, filling the emergence portion **110** of void **108**, with substantially no gaps.

As shown in FIG. 4C, the healing cap **130a** is placed within void **108** so that subgingival portion **146a** fills the emergence portion **110** with substantially no gaps, and provides an emergence profile between the gingival tissue emergence portion **110** that is substantially identical to that provided by the natural tooth prior to its removal. The exposed portion **148a** resides just above the gingival tissue, which is helpful in ensuring that all gingival tissue is fully supported, particularly where there may be some small degree of variability in the contours of this gingival tissue between one patient and another for a given tooth position.

FIG. 4D shows the exposed portion **148a** having been completely removed (e.g., it may be easily cut away with a burr or other convenient dental tools if desired). This view perhaps best shows how the emergence profile **111** surrounding the location where the healing cap **130a** emerges from the void **108** is perfectly or nearly perfectly matched to the gingival tissue so that substantially no gaps are present (compare with the gaps that are common with state of the art healing caps shown in FIG. 1F). Because subgingival por-

tion **146a** is provided with the anatomical shape of the emergence portion **110** of void **108**, the various characteristic features of gingival cuff **104** are preserved, including preservation of the full height of contour of gingival cuff **104**, the interdental papilla **112**, and the buccal prominence **106**.

As shown in FIG. 4E, a temporary or provisional crown **190** may be chair-side formed over the sculptable anatomical healing cap **130a**, while preserving access to underlying hollow channel **138** of healing cap **130a**.

When a permanent crown (typically custom prepared in an off-site dental lab) is ready for installation, the healing cap (and any temporary crown formed thereon) may simply be removed from void **108** by accessing coupling screw member **140** through hollow channel **138**. The permanent crown may then be inserted within void **108**, taking the place of healing cap **130a**. Of course, the permanent crown may be provided with the necessary shape to fill emergence portion **110**, so that the gingival tissue surrounding void **108** which has been preserved through the use of sculptable anatomical healing cap **130a** can continue to be preserved.

The use of the anatomical sculptable healing cap provides for the preservation of various gingival features that are characteristic of natural teeth, including the gingival cuff, height of contour, the emergence profile, the interdental papilla, and the buccal prominence. These features are typically progressively lost over the weeks and/or months following first stage treatment where insufficient structure is provided for supporting the gingival tissue at the site where the tooth once was. Use of the healing caps, systems, and methods allow these features to be maintained, rather than progressively lost following first stage treatment and before placement of a custom permanent crown.

### III. Exemplary Casting Jigs

FIG. 5 shows an exemplary casting jig **200** for use in manufacture of the customizable sculptable anatomical healing caps. Casting jig **200** includes body **202**, which includes one or more wells **204** formed therein. Each well **204** is open at a proximal end **206** and may include a socket **210** at a distal end **208** (FIG. 6). Open proximal end **206** allows introduction of a curable or otherwise settable dental material from which an anatomical healing cuff body (e.g., body **144a**) is formed. Distal end **208** may include a socket **210**, which allows a dental implant or dental implant analog **212** to be releasably received therein. Each well **204** includes a negative shape corresponding to an anatomical healing cuff body of a given tooth position. As described above relative to the anatomical healing caps and cuff bodies, each such corresponding negative shape has an asymmetrical cross-section and an irregular surface so that an anatomical healing cuff body having said shape (and formed by filling said well with a curable or otherwise settable dental material) is configured to provide substantially custom filling of at least an emergence portion of a void where a natural tooth once emerged from a void or where a tooth would have emerged from a void.

Casting jig **200** is shown as including a plurality of wells, each differently configured. For example, one or more wells may be configured to produce healing caps configured for molar placement, one or more may be configured to produce healing caps configured for bisuspid placement, one or more may be configured to produce healing caps configured for cuspid placement, one or more may be configured for upper lateral incisor placement, one or more may be configured for upper central incisor placement. Similarly, wells may be configured to produce healing caps specifically configured for placement in the various lower tooth positions. By way



of example, one casting jig may include all the needed wells for producing all of the upper tooth positions, while a separate casting jig may be provided for producing all of the lower tooth positions. In another embodiment, all positions may be provided within a single casting jig. In another embodiment, only a single well may be provided in a casting jig, specific to tooth configuration. Thus, it will be readily apparent that any number and configuration of wells may be provided within the inventive casting jigs.

While FIG. 6 shows an embodiment in which well 204 is vertically aligned over implant or implant analog 212, this is not required. For example, in some embodiments, a longitudinal axis of healing cuff body 144a (and thus well 204) may be off center and/or out of axial alignment relative to the longitudinal axis of implant or implant analog 212. Such off center or out of axial alignment configurations may be desirable where teeth are crowded, or where space for anchor placement is otherwise not optimal (e.g., where the void for implant placement is not axially aligned and centered below the healing cap to be placed). Such configurations provide flexibility in void preparation and implant placement to the practitioner.

As seen in FIG. 6, implant or implant analog 212 may be retained within socket 210 in the desired position and orientation relative to well 204 by an implant housing 214 that serves as a cage, holding implant or implant analog 212 in place. As perhaps best seen in FIG. 6, casting jig 200 may include an upper portion 216 and a lower portion 218. Upper portion 216, which defines at least a portion of well 204, may be formed of any suitable material (e.g., plastic, metal, stone, an elastomeric material, etc.). In one embodiment, upper portion 216 is formed of an elastomeric material (e.g., rubber, silicone, etc.) so as to provide upper portion 216 adjacent well 204 with the ability to “give”, facilitating easier removal of a cast healing cap (e.g., cap 130a). In another embodiment, upper portion may comprise a more rigid material (e.g., rigid plastic, stone, metal, etc.). Use of an elastomeric material may facilitate easier removal of cast healing caps from wells 204, and may also prevent or otherwise minimize any tendency of upper portion 216 adjacent wells 204 to chip or crack, which might otherwise tend to occur with some materials (e.g., stone).

Lower portion 218 may be formed of the same or a different material as compared to upper portion 216. In one embodiment, lower portion 218 may comprise a material that is more rigid than upper portion 216. For example, lower portion 218 may comprise stone, metal, or a rigid plastic, while upper portion 216 may comprise an elastomeric material.

Another embodiment may not necessarily include discrete upper and lower portions formed of different materials, but may include an elastomeric material surrounding wells 204 (although the entire upper portion 216 may not be formed of the elastomeric material). In other words, portions of casting jig 200 adjacent to wells 204 (and defining the bounds of wells 204) may comprise an elastomeric material, while other portions of casting jig 200 may be formed of a more rigid material. In one such embodiment, the elastomeric material may be surrounded by the more rigid material.

Implant housing 214 advantageously holds implant or implant analog 212 in a desired position and orientation relative to distal end 208 of well 204. Implant housing 214 may also advantageously allow removal and interchange of one implant or implant analog 212 with another implant or implant analog. For example, there exist scores of dental implant manufacturers, each often including proprietary structural features (e.g., proprietary locking recess shapes).

In addition, where a healing cap is to be seated within and coupled to a given implant, the healing cap should preferably have corresponding shaped locking structure to correspond to that of the implant. For this reason, one typically purchases implants and healing caps from the same manufacturer so that they are compatible with one another. Because the present casting jigs allow a practitioner to manufacture their own anatomical healing caps, it would be advantageous to provide a mechanism by which the anatomical healing caps may be manufactured so as to be compatible with a desired manufacturer implant to be employed. Use of the manufacturer’s implant or implant analog in socket 210 of casting jig 200 provides the produced healing cap with the desired corresponding locking structure (e.g., locking structure 150 of FIG. 2A).

Implant housing 214 allows one to remove implant or implant analog 212 through an opening 221 in bottom surface 220 of casting jig 200, after which an implant or implant analog of another manufacturer may be inserted into socket 210, housed within implant housing 214. Thus, the practitioner or other user of casting jig 200 is free to employ whichever implant or implant analog manufacturer he or she desires. Placement of the desired implant or implant analog 212 within socket 210 allows one to cast the produced healing cap so as to include the desired locking structure that corresponds to locking recess 225 of implant or implant analog 212.

Separate, specifically configured implant housings may be provided for each implant. For example, the exterior surface and profile of each implant or implant analog 212 may differ from manufacturer to manufacturer. Thus, a different implant housing may be provided for each manufacturer’s implants and implant analogs. Different, specifically configured implant housings 214 may be provided to correspond to each implant or implant analog. For example, an interior profile 222 of a given implant housing 214 may be specifically configured to mate with or otherwise retain the corresponding implant or implant analog 212. The exterior profile 224 of all implant housings 214 may be identical, allowing any of the implant housings to be inserted into socket 210, for use within casting jig 200 for a desired tooth position. Thus, the system allows one to employ any of dozens of various implant or implant analog configurations (e.g., all configured for use with a given tooth position) within the socket adjacent the well configured to produce a healing cap for that given tooth position.

In another embodiment, implant housing 214 may be suitable for use across multiple differently configured implants or implant analogs 212. For example, where implant housing 214 is formed of an elastomeric material, so long as the various implants or implant analogs include roughly similar sizing, the elastomeric deformation ability of the implant housing 214 may allow housing 214 to deform to accept and appropriately “cage” similar, but differently configured implants or implant analogs 212.

The configuration of casting jig 200 thus provides great flexibility in allowing the practitioner to manufacture anatomical healing caps for use with any desired dental implant. All that is required is that the user insert the desired implant or implant analog 212 into socket 210 (with accompanying housing 214), and the formed anatomical healing cap will automatically include the necessary structural features so as to allow its use with that particular implant.

Stated another way, while currently a practitioner is required to purchase healing caps from a manufacturer for perhaps as much as \$40 to \$80 each, the casting jig allows one to make their own healing caps, reducing the cost of



components to be purchased. In addition, the practitioner manufactured anatomical healing caps provide vastly improved results with respect to preservation of the desirable aesthetic gingival features as compared to existing healing caps. All this is possible at substantially reduced cost. For example, a practitioner may make his or her own anatomical healing cap for significantly reduced cost as compared to the large purchase price of an inferior state of the art healing cap.

For example, implants typically include an anti-rotational locking recessed connection **225** (e.g., a hex recess) in the head of dental implant or implant analog **212**. No matter the specific configuration of such a proprietary locking recess of a given implant or implant analog, the produced healing cap can be formed so as to include the corresponding mating feature as a result of the locking recess of the implant or implant analog being used to close the distal end of well **204** during casting. In other words, the shape defined by locking recess connection **225** can be cast into the distal end of the manufactured healing cap. By way of example, if a given dental implant or implant analog **212** includes a hex recess (e.g., recessed connection **225**), the formed anatomical healing cap will include the corresponding hex locking member **150** (see FIG. 2A) at its distal end, as a result of the curable or otherwise settable material being introduced into the hex recess **225** of the implant as well as the adjacent well **204**, disposed thereabove. As will be described below, insertion of an elongate body (e.g., a wrench, a Q-tip, a hollow straw or other suitable tool) can be used to form and preserve a hollow access channel **138** through the practitioner manufactured healing cap to allow subsequent coupling of the produced healing cap to a dental implant with a screw **140**.

While shown with implant housing **214**, it will be understood that in some embodiments, implant or implant analog **212** may be directly retained by the exterior walls and any retaining features (e.g., a snap fit, etc.) of socket **210**. In another embodiment, retention of dental implant or dental implant analog **212** by socket **210** is indirect, (e.g., through implant housing **214**), as described above in conjunction with FIGS. 6-7. Other retention mechanisms may alternatively be employed to releasably retain dental implant or implant analog **212** within socket **210**, and such mechanisms are within the scope of the present invention.

For example, in one embodiment, the socket may include an elastomeric lining, so as to allow one to simply press a desired implant or implant analog **212** through opening **221** in bottom surface **220** up into position relative to well **204**. Such a configuration may appear similar to that shown in FIG. 6, but in which implant housing **214** is glued or otherwise fixedly retained within socket **210**. The bottom portion of housing **214** shown closed in FIG. 6 (where the two halves of housing **214** come together) might be open, allowing one to insert therein a desired implant or implant analog **212**. The elastomeric nature of such a lining or housing may hold the implant or implant analog **212** in place during casting.

Housing **214** may include a projection (e.g., an annular ring) **226** that snap fits within a corresponding annular groove **228** formed within socket **210** in lower portion **218**. Other retention mechanisms for retaining housing **214** within socket **210** will be apparent to one of skill in the art. In a similar manner, interior surface **222** of housing **214** may include a projection **230** configured to snap fit within a corresponding annular groove **232** formed within implant or implant analog **212**. Where housing **214** comprises an elastomeric material, no specific coupling structure (e.g., projection **230** and corresponding groove **232**) may be required,

as the elastomeric characteristics of housing **214** may be sufficient to grip and hold the exterior surface of implant or implant analog **212** in place, particularly once the assembly (implant analog **212** and housing **214**) is inserted into socket **210**. Similarly, such gripping characteristics of implant housing **214** or of adjacent lower portion **218** may be sufficient to hold implant housing **214** and implant or implant analog **212** within socket **210** by friction fit, so that no annular ring **226** or corresponding groove **228** may be present.

Housing **214** may include a handle adjacent bottom surface **220** or other means to facilitate gripping and removal of housing **214** from socket **210**. For example, in the illustrated configuration, socket **210** widens adjacent bottom surface **220** at **234**, allowing one to grip the exterior sides **224** of housing **214** and pull it out of socket **210**. Such an embodiment may advantageously preserve the ability of casting jig **200** to lay flat (e.g., bottom surface **220**), without any handles extending beyond bottom surface **220**. Another embodiment may include one or more grippable handles on a bottom surface of housing **214**, which handles may be recessed within socket **210**, so as to preserve the ability of the casting jig to lay flat.

FIGS. 8-9A illustrate introduction of curable or otherwise settable dental material **236** into well **204**. Prior to introduction of flowable dental material **236** into well **204**, an elongate body (e.g., wrench **238**) may be inserted into screw **140**, which prevents flowable dental material **236** from filling threaded portion **227** of implant or implant analog **212**. In another embodiment, where no screw is present, the elongate body may be directly inserted into threaded portion **227**. For example, elongate body **238** may have a diameter or thickness adjacent its distal end that is sized so as to cover or plug threaded portion **227**, while not being so large in diameter or thickness to cover or plug the entirety of recessed connection **225**. In either case, as perhaps best seen in FIG. 9A, flowable dental material **236** may be allowed to enter recessed connection **225** so that the produced healing cap includes a hexagonal locking member **150** (or other anti-rotational shape), but in which the central portion of the locking member **150** is hollow, preserving hollow access channel **138** therethrough. FIG. 10 shows a produced healing cap **130a**, in exploded view with coupling screw **140** and implant analog **212**. Where a screw is present, the screw may actually become integral with the healing cap, so that it cannot be later removed (e.g., similar to as shown in FIG. 11). Once material **236** is cured, backing out of screw **140** with wrench **238** may serve to unseat healing cap **130a** from well **204**.

While the method is illustrated in FIG. 9A with elongate body **238** comprising an implant wrench, it will be understood that other elongate bodies may be alternatively employed. For example, even a Q-tip, an appropriately dimensioned hollow straw, or solid rod may be inserted to achieve a similar result. Where a wrench or other solid elongate member is employed, it may be important that the cured or set dental material **236** not adhere strongly to wrench **238** to allow its removal. Where a hollow straw is employed, removal of the straw may not be required. Once the wrench or other elongate body **238** has been removed, one may employ a dental burr or similar tool to widen central access channel **138**, if desired. In another embodiment, one may place a removable collar about elongate body **238** prior to filling well **204**, which collar can be removed with elongate body **238** after curing or setting, similarly resulting in a wider central channel **138**.



In one embodiment, the elongate body inserted into well **204** may comprise a temporary abutment **238'** purchased from a dental product manufacturer (e.g., the same manufacturer who provided the implant or implant analog). Such a temporary abutment may be configured similar to body **132** shown in FIGS. **2A-2E**. Such an embodiment is shown in FIG. **9B**. The abutment **238'** may already include any needed locking structure (e.g., hex head **150**) corresponding to recess **225**. Thus, in such a case, the introduced curable or otherwise settable dental material **236** need not enter into recess **225** (which recess may conveniently be entirely blocked by corresponding locking structure already disposed on temporary abutment **238'**, and seated within recess **225** implant or implant analog **212**).

In other words, temporary abutment **238'** may be used as a core around which the anatomical healing cuff body **144a** is cast within well **204**. The abutment **238'** may be coupled to implant **212** by screw **140**. In another embodiment, no screw may be employed. Where screw **140** is present, the screw may be removed through channel **138**. Thus, in this embodiment, screw **140** may not become bonded and integral with cured or set dental material **236** of the anatomical healing cap. Use of a temporary abutment may be particularly suitable when producing anatomical healing caps having relatively large, wide healing cuff bodies (e.g., bicuspid or molars). For smaller teeth, one may find the temporary abutment to large to be readily insertable into well **204** while allowing introduction of curable or otherwise settable dental material **236** therearound. For example, many such commercially available temporary abutments include some lateral extension beyond the simple cylindrical core body **132** shown in FIGS. **2A-2E** (e.g., compare FIG. **9B**). A straw configured as cylindrical core body **132** could similarly be employed.

FIG. **9C** shows another alternative similar to that shown in FIG. **9B**, but in which temporary abutment **238''** is of a lower profile, so that it does not extend out the top of well **204**. In order to preserve an access channel **138**, wrench **238** is inserted therein, after which the curable or settable dental material **236** is introduced into well **204**. Similar to the embodiment shown in FIG. **9B**, removal of screw **140** may be possible following fabrication of the anatomical healing cap.

Examples of such temporary abutments that may be used as a core about which an anatomical healing cuff body is formed are available from various manufacturers, including Glidewell Laboratories, located in Newport Beach, Calif. Such temporary abutments employed as a core may be formed of any of various materials (e.g., including, but not limited to plastics, such as polyether ether ketone (PEEK), metal, ceramic (e.g., alumina, zirconia), etc.). Such temporary abutments may be formed by any suitable technique (e.g., casting, molding, machining, etc.)

In some embodiments (e.g., as shown in FIG. **9A**), a screw may engage threaded portion **227** of implant or implant analog **212**. An implant wrench may be inserted in conjunction with such a screw to preserve an access channel **138**. Such a screw may be retained within the produced healing cap, providing a healing cap with a screw already incorporated therein. In one embodiment, the head of any such screw may extend through the length of any locking member (e.g., **150**) to reinforce this otherwise relatively thin neck region of the produced healing cap. For example, one may simply back a typical coupling screw out a couple of turns or use a screw that is sufficiently long so as to extend through the narrow neck associated with locking member **150**, into body **144a**. Such an embodiment including a

longer screw is shown in FIG. **11**. An example of such a screw **140'** may include an enlarged head **240**, an undercut central portion **242** of decreased diameter relative to the enlarged head, and a distal threaded end **244**, in which the threaded end defines a diameter that is intermediate the diameter of the enlarged head and the central portion. Such screw configurations (or backing out of a standard coupling screw, which is relatively shorter) reinforces the more fragile portion of healing cap **130a** to prevent a break from occurring adjacent locking member **150**.

Any suitable curable or otherwise settable dental material may be employed. Examples of such composite materials include, but are not limited to, glass ionomer cements, zinc polycarboxylate cements, and acrylic based curable compositions, for example, ACCESS CROWN, available from Centrix, located in Shelton, Conn. In one embodiment, the curable or otherwise settable dental material may comprise a radiopaque filler, e.g., a zirconia filled dental composite material. In addition to zirconia fillers, fillers including compounds of lanthanum, strontium, barium, zinc (e.g., zinc oxide), or combinations thereof may also be provided in order to provide radiopacity.

In one embodiment, radiographic and/or position markers may be incorporated into the anatomical healing cap **130a**. For example, such markers could be inserted into a well of a casting jig, which marker may become incorporated into the resulting anatomical healing cuff body that is cast. In another embodiment, such markers may be included within a temporary abutment employed as a core about which the anatomical healing cap is formed. The markers would thus become a part of the healing cap. Such markers may be used to determine orientation, position, or other spatial information through a digital scanning or imaging process (e.g., CT scan, ultrasound, etc.) of the patient. Such markers may comprise any of the described radiopaque materials described above, or other suitable radiopaque materials (e.g., radiopaque metal alloys).

While it has been described that the casting jig may be employed to manufacture anatomical healing caps, and such manufacture may be achieved chair-side, it will be readily understood that a practitioner may choose to manufacture any number of anatomical healing caps prior to needing them, thus, "chair-side" is to be broadly construed, including where one may manufacture the anatomical healing cap prior to requiring its use. For example, a practitioner may choose to manufacture a small inventory of anatomical healing caps, which are kept and used as needed. That said, many curable or otherwise settable dental compositions cure or set up within about 3 minutes or less, such that true chair-side manufacture of a desired anatomical healing cap is certainly possible.

Another embodiment may not necessarily employ a socket at a distal end of the well configured to releasably receive therein a dental implant or dental implant analog. For example, for manufacture of a pontic **130a'**, no coupling to a dental implant is needed. Thus, one may simply cast a desired pontic having the shape of the anatomical cuff body, and the pontic may be positioned into the prepared void in the patient's jaw bone (without the need for any anchoring implant). The pontic may rather be anchored to adjoining teeth on one or both sides of the pontic. Such pontics would be similar to the described healing caps, but would not require any mechanism for coupling to a dental implant. In addition, because no coupling to an implant is required, no central access channel **138** may be needed. Thus, the pontic may be solid, without any hollow access channel. Such an embodiment is shown in FIG. **12**.



9B

Another embodiment similar to that shown in FIG. 9B is described in conjunction with FIG. 9D. For example, the entire casting jig 200 (e.g., both upper and lower portions 216 and 218) may be formed of the same material, e.g., comprising a single integral piece of material. Such a casting jig 200 may be formed of an elastomeric material (e.g., silicone or polyvinyl siloxane), or a single piece of plastic. The casting jig could be molded around the implant analog 212 (e.g., by introducing silicone resin into a container around the analog, and allowing the silicone to set). Rather than including an implant housing 214 that serves as a cage (see FIG. 9B) and the implant analog 212 being inserted from the bottom of the casting jig, the analog may be removed or inserted into the casting jig 200 from above, at the top of the casting jig (e.g., through well 204). A hole or opening 221 in bottom surface 220 of casting jig 200, may be provided through which an implement may be inserted to push implant analog 212 upwards, into well 204, where it may be removed, as desired (e.g., when it is desired to remove a formed anatomical healing cap, the assembly of the healing cap and coupled analog may be upwardly pressed out).

As described in conjunction with FIG. 9B, a commercially available temporary or interim abutment 238' may be used as a core about which the anatomical healing cap is formed. Temporary abutment 238' may be inserted from above into analog 212. The typically keyed recess 225 of analog 212 may have been removed (e.g., drilled out), making the analog 212 generic to any given key. The screw 140 may be screwed down tightly into threaded portion 227 of analog 212, securing the two together. Bis-acrylic or any other suitable curable or otherwise settable material may be introduced into drilled out recess 225 at the head of analog 212, to form a keyed recess structure within analog recess 225 that corresponds to the keyed protrusion structure provided by temporary abutment 238'. In this way, a generic analog 212 may be used with any proprietary keyed structure provided with commercially available temporary abutments 238'. Analog 212 may include a transverse through-hole 246 or similar transverse recess that fills with such a settable material, helping to retain the bis-acrylic within analog recess 225 once the settable material sets or cures. The above procedures may be carried out with the analog and temporary abutment 238' located outside of the casting jig.

At this stage, the analog 212 and temporary abutment 238' are placed within casting jig 200 if not already there, with analog 212 in socket 210 of casting jig 200. Both may be introduced through the top of casting jig, via well 204. Where the casting jig is formed of an elastomeric material, the flexibility and elastic nature of the material surrounding socket 210 may allow easy insertion and withdrawal of analog 212, as needed. With analog 212 in socket 210 and temporary abutment 238' screwed into analog 212, bis-acrylic or another suitable settable dental material 236 may be introduced into well 204 to form the desired anatomical healing cap, including the buccal and lingual side handle lateral extensions 152, and 154'. Providing the T-shaped buccal side handle 152, and an oppositely disposed lingual handle extension 154' is quite advantageous, as it provides two points disposed laterally outward, on the buccal and lingual sides for easy gripping and positioning. Integrally formed handle portions 152 and 154' may easily be removed (e.g., cut away) once the healing cap is placed within the void 108, in implant 114. The presence of buccal and lingual handle extensions 152 and 154' is further advantageous as

they provide a readily visible indicator of the correct orientation of the healing cap as it is seated within implant 114.

FIGS. 13A-13C illustrate an exemplary elongate handle that may be used with a casting jig system of the present invention. For example, a casting jig as described above (e.g., as shown in FIG. 5) may be provided, including a body 202 including one or more wells 204 formed within the body. Each well may be open at a proximal end 206 and may include a negative shape corresponding to an anatomical healing cuff body of a given tooth position. Each respective anatomical healing cuff body negative shape may include an asymmetrical cross-section and an irregular surface so that an anatomical healing cuff body having that shape provides substantially custom filling of at least an emergence portion of a void where a natural tooth once emerged from the void, or where a tooth would have emerged from the void.

A socket 210 may be provided at distal end 208 of each well, and an opening 221 in bottom surface 220 of the casting jig 200, which opening 221 opens into the bottom of socket 210 (e.g., socket 210 may simply be the top of the opening 221—where opening 221 extends from bottom surface 220 to the bottom of well 204). As shown in FIGS. 13A-13C, the system may further comprise an elongate handle 250 that is insertable through opening 221 in bottom surface 220 of casting jig 200. Of course, handle 250 could also be inserted through the top surface of jig 200 (e., through well 204). Elongate handle 250 may include a recessed connection 225' in a distal end 252 thereof, so that handle 250 may hold a temporary abutment used as a core 238' (i.e., a temporary abutment core) within well 204 of casting jig 200 as an anatomical healing cuff body (e.g., 144a) is formed about core 238'.

Handle 250 further includes a proximal grippable end 254 that may be grasped by the practitioner during use, as handle 250 is inserted through bottom opening 221. As seen in FIG. 13A, handle 250 may further include a generally vertical alignment marking 256 that may extend along a length (e.g., at least a portion of the full length) of handle 250. In an embodiment, vertical alignment marking is present at least at distal end 252, adjacent recessed connection 225', as it is used to assess alignment of the abutment core 238' that is retained within connection 225'. For example, as seen in FIG. 16, generally vertical alignment marking 256 is aligned with a corresponding alignment marking (e.g., a mark or flat, planar portion 241 on abutment core 238'), when core 238' is retained in distal end 252 of handle 250. These markings may correspond to the buccal side of the healing cuff body to be formed (i.e., T-shaped handle 152 seen in FIG. 18A may be on this side, aligned with marking 256 and flat 241).

Handle 250 may further include a generally horizontal alignment marking 258 extending along a width (e.g., around a perimeter) of the elongate handle 250. Marking 258 may extend around the entire perimeter, or just a portion (e.g., a buccal front portion, as typically viewed by the practitioner) thereof. Marking 256 (which also may extend the entire length, or only a part of the handle) is disposed on the buccal front portion. Marking 258 may advantageously be aligned with bottom surface 220 of casting jig 200 during insertion into the casting jig, signifying to the practitioner that elongate handle 250 is fully seated within casting jig 200. This is shown in FIG. 17A. For example, when so flushly aligned, such alignment may signify that the abutment 238' retained within recessed connection 225' is properly aligned vertically within well 204 of casting jig 200, so that when the curable or otherwise settable material 236 is introduced into well 204 (e.g., between the sidewalls of the well defining the negative space and abutment 238'), the structures are prop-



erly positioned to produce the anatomical healing cuff body about core **238'**. Thus, the practitioner may easily and quickly verify that core **238'** is in the proper rotation relative to marking **256**, and that core **238'** and handle **250** are inserted into jig **200** to the proper degree relative to marking **258**.

As seen in FIG. **13A**, distal end **252** of handle **250** may include an internal threaded connection **227'** disposed proximal relative to recessed connection **225'** so that a screw **140** advanced through hollow abutment core **238'** seated in recessed connection **225'** may be secured to handle **250** by screw **140**, as screw **140** is threaded into internal threaded connection **227'**. Thus, screw **140** may be used to secure core **238'** to handle **250**.

FIG. **13A** illustrates distal end **252** including both a flared end (e.g., so that distal end **252** is of a greater width or diameter than grippable proximal end **254**), and a keyed structure within recess **225'**. For example, such a keyed structure may be any suitable non-circular perimeter shape that requires a particular orientation of the abutment core **238'** being inserted into recess **225'**. In the illustrated configuration of FIG. **13A**, the keyed structure is a hexagonal recess into which a correspondingly shaped and sized hexagonal locking member (e.g., **150**) may be inserted. It will be appreciated that other configurations similarly configured to lock against rotation will be readily apparent to one of skill in the art (e.g., triangular, 4-sided, 5-sided, use of non-circular curved sides, etc.), as described herein.

Flared end **252** of FIG. **13A** provides sufficient length for internally threaded portion **227'**. Of course, such a threaded portion may also be provided without a flared end, as seen in FIG. **13B**.

FIG. **13B** shows a similar configuration **250a** to that of FIG. **13A**, but which does not include a flared end at distal end **252**. This may allow the vertical seating of the abutment **238'** coupled therein to be more easily adjusted, in the jig. FIG. **13C** shows a configuration **250b**, also similar to handle **250**, but which includes a generic recessed connection **225b**. As will be described in conjunction with FIG. **20**, the generic recessed connection **225b** of FIG. **13C** may be employed with an abutment core of any desired manufacturer, allowing the practitioner to key the generic connection **225b** to whatever specific geometry the selected abutment core may include.

FIGS. **14A-14B** and **15A-15B** illustrate an exemplary temporary abutment core **238'** about which the anatomical healing cuff body may be formed. Such an abutment core **238'** may be coupled into distal end **252** of handle **250**, within casting jig **200**, to allow introduction of curable or otherwise settable dental material **236** into well, forming a cuff body having the desired anatomical shape provided by the negative shape defined by the sidewall of well **204**. In an embodiment, core **238'** may include structure in the exterior surface to aid in retaining the cuff body which is cast around core **238'**. For example, the illustrated embodiment includes dimpled recesses **243**, as well as perimeter grooves **245**. Protruding structures could alternatively be provided. In an embodiment, a structure providing an undercut (e.g., a dovetail) may be provided, providing excellent mechanical retention between the cast cuff body and core **238'** about which it is cast. The temporary abutment core **238'** may be any temporary abutment commercially available from various manufacturers (e.g., Glidewell Laboratories, located in Newport Beach, Calif.). Any such temporary abutments, available from any of the various manufacturers may be employed as a core about which the anatomical healing cuff body is to be formed.

Elongate handle **250** may be of any desired length. In an embodiment, as will be apparent from FIGS. **16-17B**, handle **250** may advantageously be longer than the height or "thickness" of the associated casting jig it is employed with. For example, where casting jig may be about 1 to 2 inches thick, handle **250** may be longer than the jig, e.g., more than 2 inches, e.g., about 2.5 to about 3.5 inches in length. Of course, any suitable length may be employed (e.g., which is longer than the thickness of the associated jig).

As seen in FIGS. **14A-15B**, the distal end of abutment **238'** adjacent the end including locking member **150** may include a flared flange portion **239**. Other employed abutments may be more similar to the hollow core body **132** seen in FIGS. **2A-2H**, which may not necessarily include such a flared distal flange. As is apparent from FIG. **9B-9D**, such a flared flange **239** may, depending on the extent to which it extends radially outwardly from the longitudinal central axis of abutment **238'**, form part of an exterior surface of the finished anatomical healing cap that is formed employing the presently described casting jigs. In any case, an anatomical cuff body is formed about (e.g., surrounding) abutment **238'**, so as to provide the desired anatomical healing cuff body shape, which is particularly important in the emergence portion of the void (e.g., that portion of the void that is near the top of the void, where there is the greatest danger of the gingiva collapsing into the void if the void is not substantially filled). Thus, although the flared flange **239** may provide some small degree of the filling of the void (e.g., at its bottom, adjacent the dental implant), the emergence portion of the void (e.g., at the top of the void), and likely most of the void, is filled as a result of the anatomical cuff body **144a** formed about abutment **238'**, which augments the temporary abutment core so that all of the void **108** is filled.

FIGS. **16-19** illustrate an exemplary method by which the presently described casting jig systems including elongate handle **250** may be employed in manufacture of the desired anatomical healing cap (e.g., **130a**). FIG. **16** illustrates how abutment core **238'** may be coupled into and retained within recess **225'** of handle **250**. For example, locking member **150** of abutment core **238'** may be inserted into recess **225'**, and screw **140** advanced, so as to secure core **238'** to distal end **252** of handle **250**. While FIG. **16** illustrates such coupling outside of casting jig **200**, it will be appreciated that this may be accomplished within the casting jig by inserting handle **250** through the opening **221** in the bottom **220** of the casting jig **200**, from below, while also inserting core **238'** into well **204**, from above. Once core **238'** meets handle **250** (e.g., locking member **150** slides into corresponding recess **225'**), screw **140** may be tightened, as shown in FIG. **17A**. In some embodiments, it may be easier to insert core **238'** from above and handle **250** from below casting jig **200**, e.g., where flared portion **239** of core **238'** would otherwise make it difficult or impossible to introduce core **238'** into well **204** from opening **221** and socket **210**. As such, handle **250** may be inserted into socket **210** from below, while core **238'** may be inserted into well **204** from above. Of course, both core **238'** and handle **250** may also be inserted from the top of jig **200** (e.g., through well **204**). This may be accomplished with core **238'** coupled into recess **225'**.

It will be apparent from FIGS. **17A** and **17B** that handle **250** takes the place of any implant or implant analog, as handle **250** includes the recessed connection **225'** in its distal end **252**, effectively becoming the implant analog. Thus, in such embodiments, no other dental implant analog (e.g., analog **212**) may be needed. FIG. **17B** illustrates how once core **238'** has been properly seated into recess **225'** (e.g.,



using screw **140** the curable or otherwise settable dental casting material **236** may be introduced into well **204**, between the sidewall of well **204** and wall **132** of core **238'**. Before so doing, the practitioner may verify that an alignment marking (e.g., flat portion **241**) of core **238'** is aligned with generally vertical alignment marking **256**, and the bottom **220** of casting jig **200** is aligned with generally horizontal alignment marking **258**. While flat portion **241** is shown as an example of a marking on core **238'** that corresponds to line **256**, it will be apparent that any suitable structure or mark may be employed, so long as the practitioner may recognize that the two structures or marks are aligned axially with one another. As such, the term "alignment marking" is to be broadly construed to include any such marks or structures.

In an embodiment, the markings **256** and **258** may include a scribed line, groove or raised ridge. They may include a colored portion therein or thereon, so as to provide contrast relative to the adjacent portions of handle **250** (e.g., red or black on a white or lightly colored handle, or white or red on a black or darkly colored handle, etc.). Such colored markings may be printed, painted, or otherwise applied. The marking could similarly comprise a flat elongate or planar portion **241** in an otherwise curved surface, as shown with flat **241** with respect to core **238'**. Core **238'** could similarly comprise a colored or shaped marking (e.g., a protrusion, groove, recess, etc.), other than the illustrated flat portion **241** (e.g., a printed or painted dot, line, or other mark of a color contrasting with the background). Any of the described markings employed on the handle may alternately be employed on core **238'**, and vice versa.

Because of the alignment between marking **256** and **241**, the practitioner is assured that core **238'** is rotated properly within recess **225'**. Because of the alignment between marking **258** and bottom surface **220**, the practitioner is assured that core **238'** is advanced into well **204** to the proper degree. Markings **256** and **241** may correspond to the buccal side of the finished anatomical healing cap **130** (e.g., the T-shaped handle **152** may also be disposed on the buccal side, as seen in FIG. **18A**).

In some circumstances, the practitioner may wish to counter-rotate the handle **250** relative to core **238'**, e.g., to compensate for a dental implant that is misaligned, to accommodate crowding of adjacent teeth, etc. This may be easily achieved by deliberately mis-aligning marking **256** relative to marking **241**, in order to make such a compensation for mis-alignment within the patient's anatomy or the implant.

The practitioner may maintain handle **250** and core **238'** within casting jig **200** until material **236** has hardened to the desired degree (e.g., about 3 minutes or less). Once material **236** has hardened, screw **140** may be accessed through channel **138**. Loosening screw **140** allows the formed anatomical healing cap **130a** to be removed from the casting jig **200**. For example, anatomical healing cap **130a** may be removed through the top, through well **104**, while handle **250** may be removed through the bottom opening **221**. FIG. **18B** illustrates a cross-sectional view of the handle **250** and formed anatomical healing cap **130a**. FIG. **19** illustrates the anatomical healing cap **130a**.

FIG. **20** shows how a generic recessed connection **225b** (e.g., such as that of FIG. **13C**) may be employed with an abutment core of any desired manufacturer, allowing the practitioner to key the generic connection **225b** to whatever specific geometry the selected abutment core **238'** may include. This may be achieved in a similar manner as described above relative to FIG. **9D**. For example, a core

**238'** including a keyed locking member (e.g., hexagonal member **150**) may be inserted into circular recess **225b**, and a curable or otherwise settable composition **247** (e.g., the same as used in forming cuff body **144a**) may be injected into the space between circular sidewall of recess **225b** and locking member **150**. This effectively converts the distal end of handle **250b** so as to be specifically keyed to the temporary abutment inserted therein, used as a core about which the cuff body is later formed. The sidewall defining recess **225b** may include a recess or through-hole **246'** or similar transverse (e.g., radially or sideways extending) recess that fills with such a settable material, helping to retain the injected material **247** within analog recess **225b** once the injected settable material sets or cures.

FIGS. **21A-23** illustrate a crown forming jig that may be used to form chair-side manufactured temporary crowns from, e.g., a bis-acrylic material or other suitable temporary crown forming material for use when installing the above described anatomical healing caps. FIGS. **22C** and **23** show the finished crown **320**. Crown forming casting jig **300** includes a body **302** including one or more wells **304** disposed within body **302**. Each well **304** may be open at a proximal end **306**, and include a negative shape corresponding to the exterior surface and contour of a crown portion of a given tooth position. In other words, just as the casting jig **200** described above includes a negative shape that when filled with a settable dental material provides a healing cuff having the anatomical shape needed to provide substantially custom filling of the void, this casting jig **300** includes a negative shape that when filled with a settable dental material (e.g., bis-acrylic), it provides a crown that has the shape and contours of the exterior surfaces of the crown portion of a natural tooth.

The casting jig further includes a first portion **308a** of an alignment mechanism. Portion **308a** may be disposed on or in the proximal top surface **306** of body **302** of crown forming casting jig **300**. For example, in the illustrated embodiment, first portion **308a** of the alignment mechanism may comprise one or more recesses arranged about well **304**, which recesses may accept and mate with a corresponding second portion **308b** of the alignment mechanism (e.g., configured as a mating protrusion).

The second portion **308b** may comprise a portion of a slug **310** (e.g., a polycarboxylate slug) that is pressed into the uncured bis-acrylic during use, displacing a portion of the bis-acrylic material so that the bis-acrylic material in well **304** assumes the shape of a hollow crown. The slug **310** includes a central downwardly protruding displacement body **312**, which is axially aligned over well **304**, and pressed into well **304**, displacing the bis-acrylic material outwardly, towards the sidewall defining well **304**, so that as the bis-acrylic hardens, it includes a hollow central portion or core where the displacement body **312** is.

Slug **310** includes second portions **308b** of the alignment mechanism, which second portions may comprise protrusions at the ends of extension arms **314** extending laterally outward (i.e., sideways) from the central displacement body **312** of slug **310**. As slug **310** is pressed downwardly towards casting jig body **302**, displacement body **312** is introduced into well **304**, displacing the bis-acrylic material from the center, towards the outside wall of well **304**. Slug **310** may include a generally vertical, upwardly oriented handle **311** to facilitate its insertion and removal. The practitioner is able to visually align protrusions **308b** with corresponding recesses **308a** of body **302**, which aids in guiding displacement body **312** into well **304** under proper alignment. Downward advancement of slug **310** relative to body **302**



may proceed until protrusions **308b** contact the bottom surface of corresponding recesses **308a** (i.e., they act as a stop). At this position, slug **310** is fully inserted, as seen in FIG. **22B**.

This position may be configured so as to ensure that the exterior surface **316** of displacement body **312** is a given distance from the adjacent interior surface **318** of well **304**, defining a casting cavity therebetween of desired thickness. In an embodiment, the casting cavity may have a substantially uniform thickness, e.g., providing about 0.5 mm all around body **312** and sidewall **318**. Such a thickness provides the finished hollow crown **320** formed from the bis-acrylic with a substantially uniform thickness corresponding to that provided by the cavity, e.g., about 0.5 mm. For example, the casting cavity and crown thickness may be from about 0.1 mm to about 2 mm, from about 0.25 mm to about 1 mm, or from about 0.3 mm to about 0.75 mm.

As seen in FIGS. **21A-21B**, the well **304** of crown forming jig **300** may include a portion of the void of the well that forms a handle **321** (e.g., a T-shaped handle) that extends from the buccal side of the resulting finished crown **320**, as seen in FIG. **23**. Such a T-shaped handle may be similar to handle **152** (e.g., including a shaft and cross-bar similar to shaft **154** and cross bar **156** as seen in FIG. **2H**). As shown, such a handle **321** may extend laterally (i.e., sideways) from the buccal side of crown **320**, making it more easily graspable by the practitioner as the practitioner positions and holds the crown in the desired position (e.g., as it is bonded to the anatomical healing cap).

Displacement body **312** of slug **310** may provide an exterior surface **316** that is also in the shape of the crown, i.e., the negative shape provided by the sidewall **318** of well **304**. Thus, when fully inserted, exterior **316** of body **312** and sidewall **318** may be substantially concentric with one another, with exterior **316** following the contour of sidewall **318**, so as to provide the finished crown **320** with a substantially uniform thickness. For example, the shape of body **312** may be that of a polycarboxylate crown former. In another embodiment, the thickness may not be uniform. For example, body **312** could simply be a cylinder, pyramid or other shape that is inserted into well **304**, although substantially uniform thickness and the corresponding shape of body **312** may be preferred.

The method and crown forming casting jig may be particularly advantageous where the curable or otherwise settable casting material does not adhere to the sidewall **318** of well **304**, or to displacement body **312** during manufacture. This allows the finished crown to be easily retrieved from jig **300** and slug **310**. In an example, the curable or otherwise settable casting material comprises an initially uncured bis-acrylic dental material, and the displacement body comprises polycarboxylate. Such materials are relatively inexpensive, and will not adhere to one another as the bis-acrylic cures, but are advantageously easily separable. The crown casting jig **300** may be formed of an elastomeric material (e.g., silicone, a polyether, etc.). Any of the materials described above relative to casting jig **200** may be employed (e.g., whether rigid, flexible, or elastomeric). It will be appreciated that other materials that are similarly non-adhesive to one another may also be used for displacement body **312** and injectable material **319**, other than polycarboxylate and bis-acrylic, respectively.

Once the finished crown **320** has hardened (e.g., about 1 minute), it may be luted or otherwise bonded to an appropriate anatomical healing cap (e.g., as much of the proximal exposed portion top end of the anatomical healing cap may be removed as desired). For example, the prepared anatomi-

cal healing cap positioned within the void and anchored to the dental implant may have the crown placed thereover, a luting cement or other suitable bonding material may be disposed therebetween, the patient may be instructed to gently bite down on the crown seated on the anatomical healing cap, and the bonding material (e.g., a light curable adhesive) may be exposed to a dental curing light, securing the temporary crown in place. As shown in FIG. **23**, the practitioner may wish to cut off any burrs, flashing, or perform any quick preparation or shaping of the crown after hardening with a dental burr **180** or other tool, before placement over the anatomical healing cap.

Such a procedure allows a practitioner to easily and quickly manufacture a temporary crown from an inexpensive bis-acrylic material, and quickly secure the crown over the installed anatomical healing cap. If desired, a VITA-SHADE colored resin or other material may be injected into the hollow crown **320** before placement over the anatomical healing cap (e.g., **130a**) to provide a more aesthetically accurate crown, with some degree of tooth coloring (e.g., as teeth are not stark white—but include shades of yellow, red, brown, gray, etc.).

Although principally described and illustrated in a configuration where the insertion of the displacement body **312** into well **304** results in a hollow crown **320**, it will be appreciated that a slug with any configuration may alternatively be inserted into well **304** (or none at all), which may result in a solid, rather than a hollow temporary crown. Such a crown may be demolded from well **304**, and luted or similarly bonded to the anatomical healing cap in-situ (e.g., by placing the temporary crown over the healing cap and having the patient bite down thereon, and exposing a light cure adhesive between the crown and cap to a dental curing light. Such solid crowns may be inexpensively and easily formed using bis-acrylic or a similar temporary crown material introduced in a flowable condition into the well **304**, after which it is allowed to cure or otherwise set. Such a solid crown may be aided in removal from the well by inserting an appropriately dimensioned hollow straw, or solid rod (e.g., similar to a toothpick) into the material before or as it cures to aid in its removal from the well. Such may be cut or otherwise removed before placement in the patient's mouth.

The provisional crown **320** may be removed (e.g., by loosening the screw coupling the anatomical healing cap into the dental implant) at a later stage (e.g., weeks later) when a permanent crown (or other restoration) has been prepared and is ready for installation. Of course, it could also be removed by breaking or cutting it off. In any case, at this point, because the anatomical healing cap has been in the void of the alveolar ridge for this period of time (e.g., several weeks), the gingival tissue surrounding the void has not collapsed into the void, but has been supported by the anatomical healing cap for the entire healing time. It will be apparent that temporary restorations other than crowns (e.g., bridges, inlays) may be formed using an appropriately configured crown forming casting jig where the well of the casting jig includes a negative shape corresponding to the desired bridge, inlay, etc.

As used herein, the terms “proximal” and “distal” may generally refer to the orientation or position of the given structure relative to the end of the device being manipulated. Thus, the end **254** of handle **250** may be “proximal”, while locking member **150** of core **238'** may be “distal”, even though the distal end of core **238'** may be coupled into the distal end of handle **250**. This is because when the anatomical healing cap that may include core **238'** is installed into a



patient's mouth, the end including locking member **250** is "distal" as it is being installed.

#### IV. Methods for Taking a Scan or Impression

As mentioned herein, a practitioner may wish to take an impression, or make a scan (e.g., a digital or other scan such as a CT scan, x-ray, or the like) of the structures and surfaces surrounding the anatomical healing cap once it has been placed into the subgingival void **108**. Under existing methods, the practitioner typically removes the cap or cuff **116** (seen in FIG. 1F), and couples an impression post or scanning body into the implant. With the impression post or scanning body in place, the impression or digital scan is taken. The impression post or scanning body may then be removed, and the cap or cuff **116** replaced. It will be apparent that such methods are undesirable, as they require removal of the cap or cuff, followed by its eventual replacement.

The present disclosure provides an alternative method which allows the impression post or scanning body (depending on whether an impression or a scan is being taken) to be seated directly into the anatomical healing caps described herein, resulting in a stack of 3 structures (the implant **114**, the anatomical healing cap **430**, with the impression post or scanning body **462** on top). For example, the anatomical healing cap itself may make provision for receipt of the impression post or scanning body therein. Mechanisms for keying the interior of the hollow anatomical healing cap with the scanning body (or impression post) may be provided.

FIGS. 24A-24B show how scanning body or impression post **462** may be inserted into open end **137** associated with hollow channel **138** of healing cap **430**. As described above, it will be appreciated that healing cap **430** may be formed around a temporary abutment **238'** as described (e.g., see FIGS. 14A-19). The terms scanning body and impression post may be used interchangeably herein (e.g., where one may be selected if a scan is to be made, the other to be selected if an impression is to be taken). The two structures may generally be similar to one another in shape, size, etc. Typically, an impression post may be formed of metal, while a scanning body may typically be plastic. Such structures are typically too weak to serve as a permanent post supporting a crown or the like.

Scanning body or impression post **462** and anatomical healing cap **430** may be keyed to one another, to ensure desired rotative orientation of body or post **462** within anatomical healing cap **430**. FIGS. 25A-25B show perspective and cross-sectional views of an anatomical healing cap **430**. It will be appreciated that any of the anatomical healing caps described herein may be provided with keyed or other features described in conjunction with anatomical healing cap **430**. For example, one or more grooves **464a** may be provided within channel **138**, where the grooves **464a** extend from the open end **137**, vertically downward some given length. A plurality of such grooves may be provided, of different lengths relative to one another. Scanning body or impression post **462** may include one or more mating protrusions **464b** which are configured to mate within grooves **464a**. FIGS. 26A-26B show perspective and cross-sectional views of impression post or scanning body **462**.

Different length grooves **464a** may ensure proper orientation of scanning body or impression post **462** in channel **138** of anatomical healing cap **430**, as if the scanning body **462** is mis-rotated, it will either not slid down into channel **138**, or it will not slide down so that each protrusion **464b** seats within the bottom of each respective groove **464a**. For example, if the grooves **464a** and protrusions **464b** are

aligned with one another, but mis-matched (not of the same length), then the scanning body or impression post **462** will slide down into channel **138** only until the bottom of the shortest groove is reached. At such position, it will be apparent that the scanning body or impression post **462** sits too high in channel **138**, and the practitioner will realize that further rotation within channel **138** is needed, such that body or post **462** may be withdrawn, rotated, and reinserted. The grooves (and protrusions) may be of differing widths if it is desired to ensure that insertion may only occur at the correct rotated orientation. Such grooves (and protrusions) may be equally spaced around the perimeter of body or post **462** and the interior surface of channel **138**, or otherwise arranged, as desired (e.g., 3 protrusions/grooves 120° apart, or 4 protrusions/grooves 90° apart). Color coding, numbering, or other matching indicia may be used to aid the practitioner in achieving correct rotational alignment of the protrusion(s) and groove(s).

With the body or post **462** fully seated in channel **138**, the practitioner may then proceed to take an impression or scan, as is the preference of the practitioner. In order to provide a further check to the practitioner that seating of the body or post **462** in channel **138** is complete, a marking (e.g., dot, groove, protrusion, horizontal line, or the like) may be provided, e.g., on the exterior of the body **462**, e.g., which may align vertically with the top **137** or channel **138**. Seeing a horizontal line or other marking aligned with top **137** may serve to inform the practitioner that full seating has occurred, much like horizontal line **258** informs the practitioner of correct seating in the casting jig as described in conjunction with FIGS. 13A-17B, above.

It is not necessary that the body or post **462** be coupled by screw or similar mechanism into the anatomical healing cap **430**, although such could be provided for, if desired. In a preferred embodiment, no such screw is provided, such that the anatomical healing cap may be screw coupled into the implant (e.g., implant **114**), but where no screw coupling is provided between anatomical healing cap **430** and body or post **462**. In some embodiments, body or post **462** may be provided with a mechanism that allows the received portion of the body or post **462** to exert an outward pressure onto channel **138**, aiding to hold it in place while being used. Such mechanism may be selective, e.g., allowing the practitioner to lock the body or post **462** in place, and then to release such mechanism when the impression or scan has been completed, and body or post **462** is to be removed. Such a mechanism could provide a mechanical switch, trigger, or button (e.g., at the top of post **462**) which upon actuation may cause a perimeter portion of body or post **462** to extend laterally or radially outward, exerting increased pressure against the interior of channel **138**. Release of such mechanism may cause retraction to the initial (e.g., default) position, making it easier for the practitioner to then pull body or post **462** from channel **138**.

Where a scan is being taken rather than an impression, the practitioner may find it helpful for the anatomical healing cap, the scanning body, or both to include radiopaque markers incorporated therein, providing a reference about which the image derived from the scan can be created. For example, the protrusions **464b** may comprise a radiopaque material, and/or grooves **464a** may be coated with a radiopaque material. Where such protrusions or grooves are of different lengths, the difference in lengths may aid in compiling the image from the scan data, as the different length protrusions and/or grooves are unique to one another, each creating a reference point for the scanner.



Before conducting such a scan, the practitioner may apply a radiopaque powder (e.g., any of the radiopaque materials identified herein, in powdered form) around the gingival cuff and any other surrounding surfaces, so that these surface contours better show up in the scan.

It will be appreciated that such embodiments simplify the overall process required by the practitioner, by allowing taking of an impression, or taking a scan without actually having to remove the healing cap, but by providing the ability to seat the scanning body or impression post into the healing cap itself. This allows the practitioner to take the desired impression or scan while leaving the healing cap in-situ, in place in the subgingival void.

As used in this specification and the appended claims, the singular forms “a,” “an” and “the” include plural referents unless the context clearly dictates otherwise.

The present invention can be embodied in other specific forms without departing from its spirit or essential characteristics. Thus, the described implementations are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes that come within the meaning and range of equivalency of the claims are to be embraced within their scope.

The invention claimed is:

1. A method of taking an impression or scan of a patient's oral cavity, the method comprising:

providing an anatomical healing abutment/cap received within a subgingival void of a given tooth position, the anatomical healing abutment/cap being threadably coupled into an implant disposed adjacent the anatomical healing abutment/cap; and

providing a scanning body or impression post that is initially separate from the anatomical healing abutment/cap, and inserting the scanning body or impression post into an open end of the anatomical healing abutment/cap with the anatomical healing abutment/cap positioned in the subgingival void, such that insertion of the scanning body or impression post occurs without requiring removal of the anatomical healing abutment/cap;

wherein the scanning body or the impression post is selectively removable from the open end of the anatomical healing abutment/cap, and a screw is not required to selectively secure the scanning body or the impression post to the open end of the anatomical healing abutment/cap, such that the scanning body or impression post is slidably received into the open end of the anatomical healing abutment/cap, and the anatomical healing abutment/cap is threadably coupled into the implant;

wherein the anatomical healing abutment/cap and the scanning body or impression post are keyed to one another;

wherein the anatomical healing abutment/cap comprises one or more vertical grooves formed into an interior surface of the anatomical healing abutment/cap;

wherein an exterior surface of the scanning body or impression post inserted into the anatomical healing abutment/cap includes one or more vertical protrusions which mate with the one or more vertical grooves of the anatomical healing abutment/cap; and wherein:

the one or more vertical grooves comprise a plurality of vertical grooves which are of different lengths and/or widths relative to one another; and

the one or more vertical protrusions comprise a plurality of vertical protrusions which are of different lengths and/or widths relative to one another.

2. The method as recited in claim 1, wherein the one or more vertical grooves formed into an interior surface of the anatomical healing abutment/cap are formed into an interior surface of a hollow core about which the anatomical healing abutment/cap is formed.

3. The method as recited in claim 1, wherein the anatomical healing abutment/cap comprises one or more radiopaque markers.

4. The method as recited in claim 3, the method further comprising taking a scan of the patient's oral cavity, using an imaging device.

5. The method as recited in claim 4, wherein the scan of the patient's oral cavity is taken using CT scan.

6. The method as recited in claim 4, wherein the scan of the patient's oral cavity is taken using x-ray.

7. The method as recited in claim 4, the method further comprising applying a radiopaque powder around a gingival cuff surrounding the anatomical healing abutment/cap so that the powdered surface better shows up on the scan.

8. The method as recited in claim 1, wherein inserting the scanning body or the impression post into the anatomical healing abutment/cap comprises inserting the impression post into the anatomical healing abutment/cap, the method further comprising taking an impression of the impression post, the anatomical healing abutment/cap, and surrounding surfaces.

9. The method as recited in claim 1, wherein the plurality of vertical grooves are of different lengths relative to one another; and the plurality of vertical protrusions are of different lengths relative to one another.

10. The method as recited in claim 1, wherein the plurality of vertical grooves are of different widths relative to one another; and the plurality of vertical protrusions are of different widths relative to one another.

11. A method of taking an impression or scan of a patient's oral cavity, the method comprising:

providing an anatomical healing abutment/cap received within a subgingival void of a given tooth position, the anatomical healing abutment/cap being threadably coupled into an implant disposed adjacent the anatomical healing abutment/cap; and

providing a scanning body or impression post that is initially separate from the anatomical healing abutment/cap, and inserting the scanning body or impression post into an open end of the anatomical healing abutment/cap with the anatomical healing abutment/cap positioned in the subgingival void, such that insertion of the scanning body or impression post occurs without requiring removal of the anatomical healing abutment/cap;

wherein the scanning body or the impression post is selectively removable from the open end of the anatomical healing abutment/cap, and a screw is not required to selectively secure the scanning body or the impression post to the open end of the anatomical healing abutment/cap, such that the scanning body or impression post is slidably received into the open end of the anatomical healing abutment/cap, and the anatomical healing abutment/cap is threadably coupled into the implant;

wherein the anatomical healing abutment/cap and the scanning body or impression post are keyed to one another;



33

wherein the anatomical healing abutment/cap comprises one or more vertical protrusions formed into an interior surface of the anatomical healing abutment/cap;  
 wherein an exterior surface of the scanning body or impression post inserted into the anatomical healing abutment/cap includes one or more vertical grooves which mate with the one or more vertical protrusions of the anatomical healing abutment/cap; and wherein:  
 the one or more vertical grooves comprise a plurality of vertical grooves which are of different lengths and/or widths relative to one another; and  
 the one or more vertical protrusions comprise a plurality of vertical protrusions which are of different lengths and/or widths relative to one another.

12. The method as recited in claim 11, wherein the anatomical healing abutment/cap comprises one or more radiopaque markers.

13. The method as recited in claim 12, the method further comprising taking a scan of the patient's oral cavity, using an imaging device.

14. The method as recited in claim 13, wherein the scan of the patient's oral cavity is taken using CT scan.

34

15. The method as recited in claim 13, wherein the scan of the patient's oral cavity is taken using x-ray.

16. The method as recited in claim 13, the method further comprising applying a radiopaque powder around a gingival cuff surrounding the anatomical healing abutment/cap so that the powdered surface better shows up on the scan.

17. The method as recited in claim 11, wherein inserting the scanning body or the impression post into the anatomical healing abutment/cap comprises inserting the impression post into the anatomical healing abutment/cap, the method further comprising taking an impression of the impression post, the anatomical healing abutment/cap, and surrounding surfaces.

18. The method as recited in claim 11, wherein the plurality of vertical grooves are of different lengths relative to one another; and the plurality of vertical protrusions are of different lengths relative to one another.

19. The method as recited in claim 11, wherein the plurality of vertical grooves are of different widths relative to one another; and the plurality of vertical protrusions are of different widths relative to one another.

\* \* \* \* \*