

US010507514B2

(12) **United States Patent**
Wilcox

(10) **Patent No.:** **US 10,507,514 B2**
(45) **Date of Patent:** **Dec. 17, 2019**

(54) **RIVET FEEDING APPARATUS**

(71) Applicant: **Arconic Inc.**, Pittsburgh, PA (US)
(72) Inventor: **Robert Wilcox**, Port Ewen, NY (US)
(73) Assignee: **Arconic Inc.**, Pittsburgh, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 406 days.

(21) Appl. No.: **15/266,331**

(22) Filed: **Sep. 15, 2016**

(65) **Prior Publication Data**
US 2017/0072454 A1 Mar. 16, 2017

Related U.S. Application Data
(60) Provisional application No. 62/219,206, filed on Sep. 26, 2015.

(51) **Int. Cl.**
B21J 15/32 (2006.01)
B23K 11/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B21J 15/32** (2013.01); **B23K 11/0053** (2013.01); **B23K 11/115** (2013.01); **B23K 11/36** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B21J 15/32; B21J 15/323; B25C 1/001; B23K 11/36; B23K 11/115;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,333,414 A 3/1920 Havener
1,730,750 A * 10/1929 Stimpson A43D 69/02
227/139

(Continued)

FOREIGN PATENT DOCUMENTS

CN 101375066 A 2/2009
CN 101653861 A 2/2010

(Continued)

OTHER PUBLICATIONS

Extended European Search Report dated Jan. 5, 2018, issued by the European Patent Office in European Patent Application No. 15788691.2.


(Continued)

Primary Examiner — Robert F Long
(74) *Attorney, Agent, or Firm* — Greenberg Traurig, LLP

(57) **ABSTRACT**

A fastener feed apparatus includes a mounting portion and a feed portion attached movably thereto. The feed portion includes a feed body having first and second ends and an internal track extending therethrough. The internal track is sized and shaped to convey a fastener through the feed body. The feed portion also includes a feeding block attached to the second end of the feed body and including a body and a pair of feed fingers, each of which includes a first end attached to the body and a second end. A track is formed between the feed fingers, is sized and shaped to convey the fastener from its first end to its second end, and is contiguous with the internal track of the feed body. The second end of the track includes a retention point. The feed fingers are sized and shaped to retain the fastener at the retention point.

34 Claims, 4 Drawing Sheets



US 10,507,514 B2

(51)	Int. Cl.				
	<i>B23P 19/00</i>	(2006.01)	8,552,332	B2	10/2013 Aoyama
	<i>B23K 11/11</i>	(2006.01)	8,595,914	B2	12/2013 Koppitz et al.
	<i>B23K 11/36</i>	(2006.01)	8,920,095	B2	12/2014 Baugh, Sr.
	<i>B23K 103/04</i>	(2006.01)	8,973,248	B2	3/2015 Honnikoppa
	<i>B23K 103/10</i>	(2006.01)	9,012,029	B2	4/2015 Lang et al.
	<i>B23K 103/16</i>	(2006.01)	9,021,688	B2	5/2015 Krejci
			9,067,276	B2	6/2015 Koppitz et al.
			9,174,298	B2	11/2015 Kasukawa et al.
			2001/0054635	A1*	12/2001 Schmitz B25C 5/1693 227/15
(52)	U.S. Cl.				
	CPC	<i>B23P 19/006</i> (2013.01); <i>B23K 2103/04</i> (2018.08); <i>B23K 2103/10</i> (2018.08); <i>B23K</i> <i>2103/16</i> (2018.08)	2002/0134817	A1	9/2002 Shepard
			2003/0102350	A1*	6/2003 Liu B25C 5/1693 227/18
			2004/0022603	A1	2/2004 Litwinski et al.
(58)	Field of Classification Search				
	CPC	B23K 11/0053; B23K 2103/16; B23K 2103/10; B23K 2103/04; B23P 19/006	2004/0169017	A1	9/2004 Sakoda
	USPC	173/1–2, 13, 31, 38–39, 45–56, 90, 130, 173/133, 121, 162, 170–171; 227/107–156	2004/0217144	A1*	11/2004 Matthews B21J 15/025 227/119
	See application file for complete search history.		2005/0133483	A1	6/2005 Hou et al.
			2005/0161442	A1	7/2005 Bradley
			2005/0284910	A1*	12/2005 Craythorn B21J 15/32 227/112
			2006/0213954	A1	9/2006 Ruther et al.
			2007/0158383	A1*	7/2007 Cheng B25C 5/06 227/30
(56)	References Cited				
	U.S. PATENT DOCUMENTS				
	2,302,772	A	11/1942	Huck	
	2,319,455	A	5/1943	Hardman et al.	
	2,563,107	A	8/1951	Fanger	
	2,569,059	A	9/1951	Huff et al.	
	3,095,951	A	7/1963	Rood et al.	
	3,104,312	A	9/1963	Gentry	
	3,400,509	A	9/1968	Setzer	
	3,576,964	A	5/1971	Williams	
	3,774,009	A	11/1973	Hodges	
	3,858,024	A	12/1974	Hinden et al.	
	4,119,827	A	10/1978	Lenox	
	4,650,951	A	3/1987	Koga et al.	
	4,677,473	A	6/1987	Okamoto et al.	
	4,736,861	A	4/1988	Basili	
	5,030,814	A	7/1991	Tange et al.	
	5,273,386	A	12/1993	Luhm	
	5,339,984	A *	8/1994	Schmidt A41H 37/00 221/124	
	5,426,838	A *	6/1995	Korb A41H 37/02 227/18	
	5,473,134	A	12/1995	Susgin	
	5,697,521	A	12/1997	Dixon	
	5,739,498	A	4/1998	Sunamoto et al.	
	5,939,498	A	8/1999	Sutton, Jr. et al.	
	6,037,559	A	3/2000	Okabe et al.	
	6,054,668	A	4/2000	Van Otteren et al.	
	6,244,899	B1 *	6/2001	Bogursky H01R 12/57 206/713	
	6,291,792	B1	9/2001	Fussnegger	
	6,414,261	B1	7/2002	Maetschke	
	6,515,251	B1	2/2003	Wind	
	6,796,454	B1	9/2004	Matthews et al.	
	6,908,022	B2 *	6/2005	Schmitz B25C 5/1693 227/119	
	6,926,186	B2 *	8/2005	Wells B25C 5/11 173/90	
	6,942,134	B2 *	9/2005	Naito B21J 15/025 227/107	
	7,030,333	B2	4/2006	Bradley	
	7,176,401	B2	2/2007	Sakoda	
	7,267,736	B2	9/2007	Hou et al.	
	7,344,058	B2 *	3/2008	Bruins B25C 5/1693 227/119	
	7,645,105	B2	1/2010	Hengel et al.	
	7,870,656	B2	1/2011	Eberlein	
	7,880,112	B2	2/2011	Hengel et al.	
	8,413,740	B2 *	4/2013	Rodenhouse B25B 21/002 173/213	
	8,424,961	B2	4/2013	Carsley et al.	
	8,461,484	B2	6/2013	Tetzlaff et al.	
	8,466,386	B2	6/2013	Wang	
					FOREIGN PATENT DOCUMENTS
				CN	101890564 A 11/2010
				CN	101590598 A 3/2015
				CN	204221184 U 3/2015
				DE	42 40 823 10/1993
				DE	4237361 9/1996
				DE	100 59 659 6/2002
				DE	102004025493 12/2005
				DE	102005006253 3/2007
				DE	102007036416 2/2009

(56)

References Cited

FOREIGN PATENT DOCUMENTS

DE	102004025492	8/2009
DE	102009044888	6/2011
DE	102010006670	8/2011
DE	102010026040	1/2012
DE	102010034183	2/2012
DE	10060390	4/2012
DE	102011055044	5/2013
DE	10 2012 010 870 A1	12/2013
DE	102012013589	1/2014
DE	10 2012 018 866 A1	3/2014
DE	102012013325	10/2014
DE	102014211222	12/2015
EP	0865860 A1	9/1998
EP	2671662	12/2013
EP	2722124	4/2014
EP	3031564	6/2016
EP	3023650 B1	9/2017
GB	964117	7/1964
GB	1528730 A	10/1979
JP	H07-185832	7/1995
JP	7-214338	8/1995
JP	8-132252	5/1996
JP	H11-13395	1/1999
JP	11-209837	8/1999
JP	11-315335	11/1999
JP	2000-117458	4/2000
JP	2000-144290 A	5/2000
JP	2001-274271 A	10/2001
JP	2001-274548 A	10/2001
JP	2003-293060 A	10/2003
JP	2005-161352 A	6/2005
JP	2007-7731 A	1/2007
JP	2009-183975	8/2009
JP	2009-285678 A	12/2009
JP	20100025615	2/2010
JP	2010-168622 A	8/2010
JP	2010207898 A	9/2010
JP	2011-50977 A	3/2011
JP	2012103136	5/2012
JP	2012-204692 A	10/2012
JP	2015-62916	4/2015
JP	2016-183217	10/2016
WO	2006084609	8/2006
WO	2009135553 A1	11/2009
WO	2011095191	8/2011
WO	2012041515	4/2012

WO	2012041516	4/2012
WO	2013064618	5/2013
WO	2013/096669 A2	6/2013
WO	2013102572	7/2013
WO	2013/178542 A1	12/2013
WO	2014/048885 A2	4/2014
WO	2014/167566	10/2014
WO	2014210266	12/2014
WO	2014210278	12/2014
WO	2015117059	8/2015
WO	2016100179	6/2016

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Nov. 15, 2017, issued by the European Patent Office in International Application No. PCT/US2017/024093 (22 pages).

European Aluminum Association, The Aluminum Automotive Manual, Joining Dissimilar Materials, (2015), pp. 1-31.

Meschut, G. et al., Hybrid technologies for joining ultra-high-strength boron steels with aluminum alloys for lightweight car body structures, Procedia CIRP, 23, (2014), pp. 19-23.

International Search Report and Written Opinion of the International Searching Authority dated Feb. 16, 2016, regarding International Patent Application No. PCT/US2015/065491.

International Search Report and Written Opinion of the International Searching Authority dated Jun. 10, 2015 in reference to International Patent Application No. PCT/US2015/014062.

International Search Report and Written Opinion of the International Searching Authority dated Oct. 30, 2014 in reference to International Patent Application No. PCT/US2014/044267.

International Search Report and Written Opinion of the International Searching Authority dated Oct. 30, 2014 in reference to International Patent Application No. PCT/US2014/044286.

PCT Application No. PCT/US15/65491 filed Dec. 14, 2015.

Weickum, B., "Friction Bit Joining of 5754 Aluminum to DP980 Ultra-High-Strength Steel: A Feasibility Study, All Theses and Dissertations", (2011), Paper 2789.

FDS, Produkte, Verbindungstechnik, EJOT Industrie, <http://www.industrie.ejot.de/Verbindungstechnik/Produkte/FDS%3Csup%3E%26reg%3B%3C-sup%3E/p/VBT_FDS>.

International Search Report and Written Opinion of the International Searching Authority dated Dec. 21, 2016 in reference to International Patent Application No. PCT/US2016/051870.

Main Alloys Cast and Chemical Composition, <http://www.sssmile.com.tw/>.

* cited by examiner




FIG. 1







FIG. 2






FIG. 6




FIG. 7

1**RIVET FEEDING APPARATUS****CROSS-REFERENCE TO RELATED APPLICATION**

This application is a Section 111(a) application relating to and claiming the benefit of commonly owned, U.S. Provisional Patent Application No. 62/219,206, titled "RIVET FEEDING APPARATUS," having a filing date of Sep. 16, 2015, which is incorporated by reference herein in its entirety.

FIELD OF THE INVENTION

The present invention relates to a rivet feeding apparatus and, more particularly, a feeder for resistance spot weld rivets.

BACKGROUND OF THE INVENTION

Current methods of fastening workpieces such as sheets to one another include conventional spot welding, the use of self-piercing rivets, and the use of flow drill rivets. The latter two methods require feeding systems for the rivets. What is needed is a compact rivet feeding apparatus that fits within a limited space and does not employ complicated actuators and mechanisms, as well as an apparatus that provides robust means to hold a rivet in place that is not sensitive to environmental factors, such as dirt, carbon build-up, clogging, dust, and sparks.

SUMMARY OF THE INVENTION

In an embodiment, a fastener feed apparatus includes a mounting portion and a feed portion attached movably to the mounting portion. The feed portion includes a feed body and a feeding block. The feed body has a first end, a second end opposite the first end, and an internal track extending through the feed body from the first end to the second end. The internal track is sized and shaped to enable conveyance of a fastener therethrough from the first end to the second end. The feeding block includes a body and a pair of feed fingers, each of which includes a first end attached to the body and a free, second end opposite the first end of the feed finger. A track is formed between the feed fingers. The track includes a first end adjacent the first ends of the feed fingers and a second end adjacent the second ends of the feed fingers. The track is sized and shaped to convey the fastener from the first end of the track to the second end of the track. The track is contiguous with the internal track of the feed body. The second end of the track includes a retention point. The feed fingers are sized and shaped to enable retention of the fastener at the retention point.

In an embodiment, each of the feed fingers of the feeding block includes an inner guiding diameter portion located proximate to the second end thereof. The inner guiding diameter portions define a first distance therebetween. In an embodiment, the retention point of the track of the feeding block includes the inner guiding diameter portions. In an embodiment, each of the feed fingers of the feeding block includes an inner wall located proximate to the first end thereof. The inner walls of the feed fingers face one another and define a second distance therebetween. The second distance is greater than the first distance. In an embodiment, each of the feed fingers of the feeding block includes a stop point located proximate to the inner guiding diameter portions of the feed fingers and intermediate the inner guiding

2

diameter portions and the second ends of the feed fingers. The stop points define a third distance therebetween. In an embodiment, the third distance is less than the first distance. In an embodiment, the feed fingers are sized and shaped to prevent them from flexing away from one another to an extent such that the fastener is free to pass between the stop points of the feed fingers when the fastener impacts the stop points after traveling along the internal track of the feed body from the first end of the feed body to the second end of the feed body and along the track of the feeding block from the first end of the feeding block to the second end of the feeding block. In an embodiment, the feed fingers are sized and shaped so as to enable them to flex away from one another to an extent such that the fastener is permitted to pass between the stop points of the feed fingers when the feed portion is operated to move away from a workpiece along first and second axes thereof.

In an embodiment, each of the feed fingers of the feeding block includes an anti-return point located proximate to the inner guiding diameter portions and intermediate the inner guiding diameter portions and the first ends of the feed fingers. The anti-return points of the feed fingers define a fourth distance therebetween. In an embodiment, the fourth distance is less than the first distance. In an embodiment, the feed fingers are sized and shaped so as to allow them to flex away from one another to an extent such that the fastener is permitted to pass between the anti-return points of the feed fingers.

In an embodiment, the feed portion includes a finger cover overlaying the second ends of the feed fingers. In an embodiment, the finger cover includes a bowl-shaped cavity overlaying the retention point of the feeding block. In an embodiment, the cavity is sized and shaped to receive a first fastening arm of a fastening apparatus. In an embodiment, the fastener feed apparatus also includes a linear actuator configured to move the feed portion relative to the mounting portion. In an embodiment, the fastener includes a rivet. In an embodiment, the fastener includes a plurality of rivets stacked among one another.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a rivet feed system attached to a welding apparatus;

FIG. 2 illustrates a close-up view of the rivet feed system of FIG. 1;

FIG. 3 illustrates a top perspective view of a feeding block employed by the rivet feed system shown in FIG. 2;

FIG. 4 illustrates a close-up view of one end of the feeding block shown in FIG. 3;

FIG. 5 illustrates a top perspective view of a finger cover employed by the rivet feed system shown in FIG. 2;

FIG. 6 illustrates a close-up view of portions of the rivet feed system and welding apparatus shown in FIG. 1; and

FIG. 7 illustrates a sectional view of a portion of the rivet feed system shown in FIG. 5.

DETAILED DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an embodiment of a rivet feed system 10 attached to a welding apparatus W, positioned with respect to a workpiece WP. FIG. 2 illustrates the rivet feed system 10, the workpiece WP, and a portion of the welding apparatus W of FIG. 1, with the rivet feed system 10 shown in solid lines and the workpiece WP and welding apparatus W shown in dashed lines. In an embodiment, the welding apparatus W is a pinch welder utilized in connection with

resistance spot weld rivets (RSRs). In an embodiment, the welding apparatus W includes upper and lower resistance welding arms UA, LA that are spaced apart and opposed to one another. The resistance welding arm UA includes a corresponding upper welding electrode UE, while the resistance welding arm LA includes a corresponding lower welding electrode LE. When the welding apparatus W is in use, the upper welding electrode UE and the lower welding electrode LE are positioned on opposite sides of a workpiece WP.

Referring to FIGS. 1 and 2, the rivet feed system 10 includes a feed portion 12 and a mounting portion 14 (e.g., a mounting block). In an embodiment, the rivet feed system 10 is mounted to the welding apparatus W by attaching the mounting portion 14 to the upper resistance welding arm UA. In an embodiment, the feed portion 12 is generally "S"-shaped and includes a feed body 16 having a first (i.e., upper) end 18, a second (i.e., lower) end 20, a top curved portion 22 located at the first end 18, a horizontal bottom portion 24 located at the second end 20, and an intermediate vertical linear portion 26 extending from the top curved portion 22 to the horizontal bottom portion 24. In an embodiment, a feed track 27 (shown in FIG. 7) is located in the interior of the feed body 16 and extends from the first end 18 to the second end 20. In an embodiment, the feed track 27 is sized and shaped so as to allow the passage of a rivet R therethrough and to maintain the rivet R in a desired orientation during such passage. In one or more embodiments, the feed body 16 includes a pivoting mechanism or a linkage 29 that enables motion of the feed body 16 along the Y-axis in FIG. 2 (i.e., across the surface of a workpiece WP).

Referring now to FIGS. 1 through 4, in an embodiment, the rivet feed system 10 includes a feeding block 28 attached to the bottom portion 24 of the feed body 16. Referring to FIGS. 3 and 4, in an embodiment, the feeding block 28 includes a base 30 having a pair of mounting brackets 32, 34 extending outwardly for mounting the feeding block 28 to the bottom portion 24 of the feed portion 12 by fasteners 36 (which are shown in FIGS. 6 and 7). A pair of feed fingers 38, 40 extends longitudinally from the base 30 and are opposed and spaced apart from one another, forming a space 42 therebetween. In an embodiment, and as will be further discussed in detail below, the feed fingers 38, 40 are adapted to flex laterally and apart from one another (i.e., away from the space 42). Each of the feed fingers 38, 40 includes a first end 44 formed integrally with the base 30 and a free, second end 46 opposite the first end 44. Each of the feed fingers 38, 40 includes an inner wall 48 and a lower wall 50. The lower wall 50 of each of the feed fingers 38, 40 includes a ramped portion 52 located proximate to the first end 44. The inner wall 48 and the lower wall 50 of each of the feed fingers 38, 40 cooperate to form a track 54 extending from the ramped portion 52 to the second end 46. In an embodiment, when the feeding block 28 is mounted to the feed body 16, the track 54 is adjacent to and contiguous with the feed track 27 of the feed body 16.

Proximate to the second end 46, the inner wall 48 of each of the feed fingers 38, 40 includes an inner guiding diameter portion 56, which forms an anti-return point 58 at one end thereof and a stop point 60 at the other end thereof. In an embodiment, the anti-return points 58 and the stop points 60 cooperate to act as a retention means for rivets R, and are positioned such that one of the rivets R may be held in position therebetween. In other embodiments, the feed body 16 includes a retention detent or a leaf spring that provides an anti-return feature, either rather than or in addition to the

anti-return points 58. In an embodiment, the width between the inner guiding diameter portions 56 is narrower than the width of between the inner walls 48 of the feed fingers 38, 40. As to be discussed in greater detail below, the fingers 38, 40 are adapted to receive and maintain in position one of the rivets R for welding to a workpiece WP. The inner guiding diameter portion 56, the anti-return point 58, and the stop point 60 thereby cooperate to define a retention point at which one of the rivets R may be retained prior to fastening.

Referring now to FIGS. 5 and 6, in an embodiment, the rivet feed system 10 includes a finger cover 62, which is mounted to the second end 20 of the feed body 16 by fasteners 64. The finger cover 62 is positioned on top of the feed fingers 38, 40 of the feeding block 28 at the second ends 46 thereof. In an embodiment, the finger cover 62 includes a bowl-shaped cavity 66 that is aligned with the guiding diameter portions 56 of the feed fingers 38, 40, and is sized and shaped to receive a tip of the upper welding electrode UE.

Referring now to FIGS. 5 through 7, in an embodiment, a rivet R includes a disc-shaped head RH and a central pin RP (shown in FIG. 7) extending therefrom. When the rivet feed system 10 is in operation, rivets R are fed into the portion of the feed track 27 located at the first end 18 of the feed body 16 with air pressure applied by a further device (not shown). In an embodiment, the rivets R are fed one at a time. In other embodiments, the rivets R may be fed in a stack. In an embodiment, each rivet R travels along the feed track 27 as it passes through each of the portions 24, 26, 28 of the feed body 16, with the head RH of the rivet R sliding along the feed track 27 and the pin RP being positioned in the associated space within the track. When the rivet R reaches the bottom portion 24 of the feed body 16 (i.e., the end of the feed track 27), it leaves the feed track 27, travels along the track 54 formed by the feed fingers 38, 40, and stops at the ends 46 of the feed fingers 38, 40. As shown in FIGS. 2 and 6, motion along the Y-axis and Z-axis is used to move the feeding block 28 down and over so that the rivet R is positioned under the tip of the upper welding electrode UE. Motion along the Y-axis and Z-axis may be provided by any type of linear actuator. In an embodiment, the linear actuator is a pneumatic actuator.

In an embodiment, the feed fingers 38, 40 employ a momentum-based retention system. In this regard, the rivet R travels through the feed body 16 and along the feed track 27 at a relatively high velocity (i.e., as induced by air pressure that feeds the rivet R into the feed track 27, as described above). The velocity of the rivet R is such that when the rivet R engages the track 54 of the feeding block 28, the momentum of the rivet R causes the feed fingers 38, 40 to flex open laterally and outwardly (i.e., away from the space 42) as the rivet R passes the anti-return points 58 on the feed fingers 38, 40. However, the momentum of the rivet R is not high enough for the feed fingers 38, 40 to flex apart from one another to such an extent that the rivet R is able to travel completely past the second ends 46 of the feed fingers 38, 40. This is the case because the width between the inner guiding diameter portions 56 of the feed fingers 38, 40 is narrower than the width between the inner walls 48. As a result, more force than is provided due to the momentum of the rivet R would be required to flex the feed fingers 38, 40 apart from one another to a great enough extent to allow the rivet R to travel past the second ends 46 of the feed fingers 38, 40. Consequently, the rivet R is stopped by the stop points 60 of the feed fingers 38, 40 and is prevented from traveling completely past the second ends 46 of the feed fingers 38, 40. When the rivet R has reached the stop points

5

60, it is nestled within the guiding diameter portions 56 of the feed fingers 38, 40, and is in position and ready to be fed under the upper welding electrode UE by the Y-axis and Z-axis motions of the feeding block 28.

The electrode UE of the welding arm UA is positioned to pin the rivet R to the workpiece WP. In an embodiment, the workpiece WP can be steel, aluminum or carbon fiber. Once the rivet R is pinned to the workpiece WP by the electrode UE, the feed portion 12 is retracted in the directions of the Y-axis and Z-axis to leave the rivet R behind. Current is applied by the electrodes UE, LE to weld the rivet R to the workpiece WP. Afterwards, the feed portion 12 is moved to the next location to be riveted, next rivet R is fed into the feed portion 12 with pressurized air, and the cycle repeats.

The rivet feed system 10 may accommodate rivets R having various depths of the rivet pin RP without the need to change the feed portion 12. In an embodiment, the rivet feed system 10 is used for resistance spot weld rivets. In other embodiments, the rivet feed system 10 can be utilized for other types of rivets or fasteners.

It should be understood that the embodiments described herein are merely exemplary and that a person skilled in the art may make many variations and modifications without departing from the spirit and scope of the invention. All such variations and modifications are intended to be included within the scope of the invention as exemplified by the appended claims.

The invention claimed is:

1. A fastener feed apparatus, comprising:

a mounting portion; and

a feed portion attached to the mounting portion, the feed portion including

a feed body having a first end, a second end spaced from the first end, and a track extending from the first end to the second end, the track being sized and shaped to enable conveyance of a fastener from the first end to the second end, and

a feed block attached to the second end of the feed body and including a body and a pair of feed fingers extending from the body, each of which includes a first end formed integrally with the body and a second end opposite the first end of the feed finger such that the feed fingers are moveable between a relaxed position, in which the feed fingers are juxtaposed with one another, and a biased position, in which the feed fingers are resiliently biased away from one another at the second ends of the feed fingers, a track formed between the feed fingers, the track of the feed block including a first end adjacent the first ends of the feed fingers and a second end adjacent the second ends of the feed fingers, the track of the feed block being sized and shaped to convey the fastener from the first end of the track of the feed block to the second end of the track of the feed block, the track of the feed block being aligned with the track of the feed body, the second end of the track of the feed block including a retention area, and the feed fingers being sized and shaped to enable retention of the fastener at the retention area,

wherein the feed fingers, when in their biased positions, provide a lateral force against the fastener to enable retention of the fastener at the retention area and prevent the fastener from traveling past the second ends of the feed fingers.

2. The fastener feed apparatus of claim 1, wherein each of the feed fingers of the feed block includes a guiding portion located proximate to the second end thereof, and wherein the guiding portions define a first distance therebetween.

6

3. The fastener feed apparatus of claim 2, wherein the retention area of the track of the feed block includes the guiding portions.

4. The fastener feed apparatus of claim 3, wherein each of the feed fingers of the feed block includes a wall located proximate to the first end thereof, wherein the walls of the feed fingers face one another, wherein the walls of the feed fingers define a second distance therebetween, and wherein the second distance is greater than the first distance.

5. The fastener feed apparatus of claim 4, wherein each of the feed fingers of the feed block includes a stop located proximate to the guiding portions of the feed fingers and intermediate the guiding portions and the second ends of the feed fingers, and wherein the stops define a third distance therebetween.

6. The fastener feed apparatus of claim 5, wherein the third distance is less than the first distance.

7. The fastener feed apparatus of claim 5, wherein the feed fingers are sized and shaped to prevent them from biasing away from one another to an extent such that the fastener is free to pass between the stops of the feed fingers when the fastener impacts the stops after traveling along the track of the feed body from the first end of the feed body to the second end of the feed body and along the track of the feed block from the first end of the feed block to the second end of the feed block.

8. The fastener feed apparatus of claim 7, wherein the feed fingers are sized and shaped so as to enable them to resiliently bias away from one another to an extent such that the fastener is permitted to pass between the stops of the feed fingers when the feed portion is operated to move away from a workpiece along first and second axes thereof.

9. The fastener feed apparatus of claim 3, wherein each of the feed fingers of the feed block includes an anti-return area located proximate to the guiding portions and intermediate the guiding portions and the first ends of the feed fingers, and wherein the anti-return areas of the feed fingers define a fourth distance therebetween.

10. The fastener feed apparatus of claim 9, wherein the fourth distance is less than the first distance.

11. The fastener feed apparatus of claim 9, wherein the feed fingers are sized and shaped so as to allow them to resiliently bias away from one another to an extent such that the fastener is permitted to pass between the anti-return areas of the feed fingers.

12. The fastener feed apparatus of claim 1, wherein the feed portion includes a finger cover overlaying the second ends of the feed fingers.

13. The fastener feed apparatus of claim 12, wherein the finger cover includes a bowl-shaped cavity overlaying the retention area of the feed block.

14. The fastener feed apparatus of claim 13, wherein the cavity is sized and shaped to receive a first fastening arm of a fastening apparatus.

15. The fastener feed apparatus of claim 1, further comprising an actuator configured to move the feed portion relative to the mounting portion.

16. The fastener feed apparatus of claim 1, wherein the fastener includes a rivet.

17. The fastener feed apparatus of claim 1, wherein the fastener includes a plurality of rivets stacked among one another.

18. A fastener feed apparatus, comprising:
a feed body having a first end, a second end spaced from the first end, and a track extending from the first end to

the second end, the track being sized and shaped to enable conveyance of a fastener from the first end to the second end, and

a feed block attached to the second end of the feed body and including a body and a pair of feed fingers extending from the body, each of which includes a first end formed integrally with the body and a second end opposite the first end of the feed finger, a track formed between the feed fingers, the track of the feed block including a first end adjacent the first ends of the feed fingers and a second end adjacent the second ends of the feed fingers such that the feed fingers are moveable between a relaxed position, in which the feed fingers are juxtaposed with one another, and a biased position, in which the feed fingers are resiliently biased away from one another at the second ends of the feed fingers, the track of the feed block being sized and shaped to convey the fastener from the first end of the track of the feed block to the second end of the track of the feed block, the track of the feed block being aligned with the track of the feed body, the second end of the track of the feed block including a retention areas, and the feed fingers being sized and shaped to enable retention of the fastener at the retention areas, and wherein the feed fingers, when in their biased position, provide a lateral force against the fastener to enable retention of the fastener at the retention area and prevent the fastener from traveling past the second ends of the feed fingers.

19. The fastener feed apparatus of claim **18**, wherein each of the feed fingers of the feed block includes a guiding portion located proximate to the second end thereof, and wherein the guiding portions define a first distance therebetween.

20. The fastener feed apparatus of claim **19**, wherein the retention area of the track of the feed block includes the guiding portions.

21. The fastener feed apparatus of claim **20**, wherein each of the feed fingers of the feed block includes a wall located proximate to the first end thereof, wherein the walls of the feed fingers face one another, wherein the walls of the feed fingers define a second distance therebetween, and wherein the second distance is greater than the first distance.

22. The fastener feed apparatus of claim **21**, wherein each of the feed fingers of the feed block includes a stop located proximate to the guiding portions of the feed fingers and intermediate the guiding portions and the second ends of the feed fingers, and wherein the stops define a third distance therebetween.

23. The fastener feed apparatus of claim **22**, wherein the third distance is less than the first distance.

24. The fastener feed apparatus of claim **22**, wherein the feed fingers are sized and shaped to prevent them from biasing away from one another to an extent such that the fastener is free to pass between the stops of the feed fingers when the fastener impacts the stops after traveling along the track of the feed body from the first end of the feed body to the second end of the feed body and along the track of the feed block from the first end of the feed block to the second end of the feed block.

25. The fastener feed apparatus of claim **24**, wherein the feed fingers are sized and shaped so as to enable them to resiliently bias away from one another to an extent such that the fastener is permitted to pass between the stops of the feed fingers when the feed portion is operated to move away from a workpiece along first and second axes thereof.

26. The fastener feed apparatus of claim **20**, wherein each of the feed fingers of the feed block includes an anti-return area located proximate to the guiding portions and intermediate the guiding portions and the first ends of the feed fingers, and wherein the anti-return areas of the feed fingers define a fourth distance therebetween.

27. The fastener feed apparatus of claim **26**, wherein the fourth distance is less than the first distance.

28. The fastener feed apparatus of claim **26**, wherein the feed fingers are sized and shaped so as to allow them to resiliently bias away from one another to an extent such that the fastener is permitted to pass between the anti-return areas of the feed fingers.

29. The fastener feed apparatus of claim **18**, further comprising a finger cover overlaying the second ends of the feed fingers.

30. The fastener feed apparatus of claim **29**, wherein the finger cover includes a bowl-shaped cavity overlaying the retention area of the feed block.

31. The fastener feed apparatus of claim **30**, wherein the cavity is sized and shaped to receive a first fastening arm of a fastening apparatus.

32. The fastener feed apparatus of claim **18**, further comprising an actuator configured to move the feed portion.

33. The fastener feed apparatus of claim **18**, wherein the fastener includes a rivet.

34. The fastener feed apparatus of claim **18**, wherein the fastener includes a plurality of rivets stacked among one another.

* * * * *