



US010512436B2

(12) **United States Patent**  
**Muhsin et al.**

(10) **Patent No.:** **US 10,512,436 B2**  
(45) **Date of Patent:** **\*Dec. 24, 2019**

(54) **SYSTEM FOR DISPLAYING MEDICAL MONITORING DATA**

(71) Applicant: **MASIMO CORPORATION**, Irvine, CA (US)

(72) Inventors: **Bilal Muhsin**, San Clemente, CA (US); **Ammar Al-Ali**, San Juan Capistrano, CA (US); **Massi Joe E. Kiani**, Laguna Niguel, CA (US); **Peter Scott Housel**, Irvine, CA (US)

(73) Assignee: **Masimo Corporation**, Irvine, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/919,792**

(22) Filed: **Mar. 13, 2018**

(65) **Prior Publication Data**

US 2018/0242921 A1 Aug. 30, 2018

**Related U.S. Application Data**

(63) Continuation of application No. 14/512,237, filed on Oct. 10, 2014, now Pat. No. 9,943,269, which is a (Continued)

(51) **Int. Cl.**  
**A61B 5/00** (2006.01)  
**H04Q 9/00** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **A61B 5/742** (2013.01); **A61B 5/0002** (2013.01); **A61B 5/002** (2013.01); **A61B 5/021** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC . A61B 5/742; A61B 5/14551; A61B 5/14552; A61B 5/1455; G06F 19/3406; G06F 19/3418  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,646,606 A 2/1972 Buxton et al.  
3,690,313 A 9/1972 Weppner et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 735 499 10/1996  
EP 2 335 569 6/2011

(Continued)

OTHER PUBLICATIONS

US 8,845,543 B2, 09/2014, Diab et al. (withdrawn)  
(Continued)


*Primary Examiner* — Brian T Misiura

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

(57) **ABSTRACT**

A first medical device can receive a physiological parameter value from a second medical device. The second physiological parameter value may be formatted according to a protocol not used by the first medical device such that the first medical device is not able to process the second physiological parameter value to produce a displayable output value. The first medical device can pass the physiological parameter data from the first medical device to a separate translation module and receive translated parameter data from the translation module at the first medical device. The translated parameter data can be processed for display by the first medical device. The first medical device can output a value from the translated parameter data for display on the first medical device or an auxiliary device.

**21 Claims, 99 Drawing Sheets**



**Related U.S. Application Data**

continuation-in-part of application No. 13/651,167, filed on Oct. 12, 2012, now Pat. No. 9,436,645.

(60) Provisional application No. 61/889,972, filed on Oct. 11, 2013, provisional application No. 61/703,773, filed on Sep. 20, 2012, provisional application No. 61/597,120, filed on Feb. 9, 2012, provisional application No. 61/547,577, filed on Oct. 14, 2011, provisional application No. 61/547,017, filed on Oct. 13, 2011.

(51) **Int. Cl.**

*A61B 5/08* (2006.01)  
*A61B 5/1455* (2006.01)  
*A61B 5/021* (2006.01)  
*A61B 5/0205* (2006.01)  
*A61M 16/00* (2006.01)  
*G06F 21/84* (2013.01)  
*G16H 40/63* (2018.01)  
*A61M 5/172* (2006.01)

(52) **U.S. Cl.**

CPC ..... *A61B 5/02055* (2013.01); *A61B 5/0816* (2013.01); *A61B 5/14551* (2013.01); *A61B 5/743* (2013.01); *A61M 16/0051* (2013.01); *A61M 16/021* (2017.08); *G06F 21/84* (2013.01); *G16H 40/63* (2018.01); *H04Q 9/00* (2013.01); *A61B 5/4821* (2013.01); *A61B 5/4836* (2013.01); *A61B 2560/0214* (2013.01); *A61B 2560/045* (2013.01); *A61B 2562/08* (2013.01); *A61B 2562/227* (2013.01); *A61M 5/172* (2013.01); *A61M 2205/18* (2013.01); *A61M 2205/3368* (2013.01); *A61M 2205/3375* (2013.01); *A61M 2205/3561* (2013.01); *A61M 2205/3569* (2013.01); *A61M 2205/3584* (2013.01); *A61M 2205/3592* (2013.01); *A61M 2205/505* (2013.01); *A61M 2209/086* (2013.01); *A61M 2230/04* (2013.01); *A61M 2230/10* (2013.01); *A61M 2230/201* (2013.01); *A61M 2230/202* (2013.01); *A61M 2230/205* (2013.01); *A61M 2230/208* (2013.01); *A61M 2230/30* (2013.01); *A61M 2230/42* (2013.01); *A61M 2230/432* (2013.01); *A61M 2230/50* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,810,102 A 5/1974 Parks, III et al.  
 3,815,583 A 6/1974 Scheidt  
 3,972,320 A 8/1976 Kalman  
 3,978,849 A 9/1976 Geneen  
 4,108,166 A 8/1978 Schmid  
 4,231,354 A 11/1980 Kurtz et al.  
 4,589,415 A 5/1986 Haaga  
 4,662,378 A 5/1987 Thomis  
 4,838,275 A 6/1989 Lee  
 4,852,570 A 8/1989 Levine  
 4,960,128 A 10/1990 Gordon et al.  
 4,964,408 A 10/1990 Hink et al.  
 5,041,187 A 8/1991 Hink et al.  
 5,069,213 A 12/1991 Polczynski  
 5,092,340 A 3/1992 Yamaguchi et al.  
 5,140,519 A 8/1992 Friesdorf et al.  
 5,159,932 A 11/1992 Zanetti et al.  
 5,161,539 A 11/1992 Evans et al.  
 5,163,438 A 11/1992 Gordon et al.  
 5,262,944 A 11/1993 Weisner et al.

5,277,189 A 1/1994 Jacobs  
 5,278,627 A 1/1994 Aoyagi et al.  
 5,282,474 A 2/1994 Valdes Sosa et al.  
 5,296,688 A 3/1994 Hamilton et al.  
 5,309,918 A 5/1994 Schraag  
 5,318,037 A 6/1994 Evans et al.  
 5,319,355 A 6/1994 Russek  
 5,331,549 A 7/1994 Crawford, Jr.  
 5,333,106 A 7/1994 Lanpher et al.  
 5,337,744 A 8/1994 Branigan  
 5,341,805 A 8/1994 Stavridi et al.  
 5,348,008 A 9/1994 Bornn et al.  
 5,358,519 A 10/1994 Grandjean  
 D353,195 S 12/1994 Savage et al.  
 D353,196 S 12/1994 Savage et al.  
 5,375,599 A 12/1994 Shimizu  
 5,375,604 A 12/1994 Kelly et al.  
 5,377,676 A 1/1995 Vari et al.  
 5,400,794 A 3/1995 Gorman  
 D357,982 S 5/1995 Dahl et al.  
 5,416,695 A 5/1995 Stutman et al.  
 D359,546 S 6/1995 Savage et al.  
 5,431,170 A 7/1995 Mathews  
 5,434,611 A 7/1995 Tamura  
 D361,840 S 8/1995 Savage et al.  
 D362,063 S 9/1995 Savage et al.  
 5,452,717 A 9/1995 Branigan et al.  
 D363,120 S 10/1995 Savage et al.  
 5,456,252 A 10/1995 Vari et al.  
 5,479,934 A 1/1996 Imran  
 5,482,036 A 1/1996 Diab et al.  
 5,483,968 A 1/1996 Adam et al.  
 5,490,505 A 2/1996 Diab et al.  
 5,494,041 A 2/1996 Wilk  
 5,494,043 A 2/1996 O'Sullivan et al.  
 5,503,149 A 4/1996 Beavin  
 5,505,202 A 4/1996 Mogi et al.  
 5,533,511 A 7/1996 Kaspari et al.  
 5,534,851 A 7/1996 Russek  
 5,537,289 A 7/1996 Dahl  
 5,544,649 A 8/1996 David et al.  
 5,553,609 A 9/1996 Chen et al.  
 5,558,638 A 9/1996 Evers et al.  
 5,561,275 A 10/1996 Savage et al.  
 5,562,002 A 10/1996 Lalin  
 5,566,676 A 10/1996 Rosenfeldt et al.  
 5,576,952 A 11/1996 Stutman et al.  
 5,579,001 A 11/1996 Dempsey et al.  
 5,590,649 A 1/1997 Caro et al.  
 5,602,924 A 2/1997 Durand et al.  
 5,619,991 A 4/1997 Sloane  
 5,632,272 A 5/1997 Diab et al.  
 5,638,816 A 6/1997 Kiani-Azarbayjany et al.  
 5,638,818 A 6/1997 Diab et al.  
 5,640,953 A 6/1997 Bishop et al.  
 5,640,967 A 6/1997 Fine et al.  
 5,645,440 A 7/1997 Tobler et al.  
 5,685,299 A 11/1997 Diab et al.  
 5,685,314 A 11/1997 Geheb et al.  
 5,687,717 A 11/1997 Halpern et al.  
 5,694,020 A 12/1997 Lang et al.  
 5,724,580 A 3/1998 Levin et al.  
 5,724,983 A 3/1998 Selker et al.  
 5,725,308 A 3/1998 Smith et al.  
 5,734,739 A 3/1998 Sheehan et al.  
 D393,830 S 4/1998 Tobler et al.  
 5,743,262 A 4/1998 Lepper, Jr. et al.  
 5,758,079 A 5/1998 Ludwig et al.  
 5,758,644 A 6/1998 Diab et al.  
 5,760,910 A 6/1998 Lepper, Jr. et al.  
 5,769,785 A 6/1998 Diab et al.  
 5,772,585 A 6/1998 Lavin et al.  
 5,782,757 A 7/1998 Diab et al.  
 5,782,805 A 7/1998 Meinzer  
 5,785,659 A 7/1998 Caro et al.  
 5,791,347 A 8/1998 Flaherty et al.  
 5,801,637 A 9/1998 Lomholt  
 5,810,734 A 9/1998 Caro et al.  
 5,813,403 A 9/1998 Soller et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,822,544 A	10/1998	Chaco et al.	6,253,097 B1	6/2001	Aronow et al.
5,822,546 A	10/1998	George	6,256,523 B1	7/2001	Diab et al.
5,823,950 A	10/1998	Diab et al.	6,263,222 B1	7/2001	Diab et al.
5,829,723 A	11/1998	Brunner	6,267,723 B1	7/2001	Matsumura et al.
5,830,131 A	11/1998	Caro et al.	6,269,262 B1	7/2001	Kandori et al.
5,833,618 A	11/1998	Caro et al.	6,278,522 B1	8/2001	Lepper, Jr. et al.
5,855,550 A	1/1999	Lai et al.	6,280,213 B1	8/2001	Tobler et al.
5,860,919 A	1/1999	Kiani-Azarbayjany et al.	6,285,896 B1	9/2001	Tobler et al.
5,876,351 A	3/1999	Rohde	6,301,493 B1	10/2001	Marro et al.
5,885,214 A	3/1999	Monroe et al.	6,304,767 B1	10/2001	Soller et al.
5,890,929 A	4/1999	Mills et al.	6,308,089 B1	10/2001	von der Ruhr et al.
5,904,654 A	5/1999	Wohltmann et al.	6,312,378 B1	11/2001	Bardy
5,910,139 A	6/1999	Cochran et al.	6,317,627 B1	11/2001	Ennen et al.
5,919,134 A	7/1999	Diab	6,321,100 B1	11/2001	Parker
5,921,920 A	7/1999	Marshall et al.	6,322,502 B1	11/2001	Schoenberg et al.
5,924,074 A	7/1999	Evans	6,325,761 B1	12/2001	Jay
5,931,160 A	8/1999	Gilmore et al.	6,329,139 B1	12/2001	Nova et al.
5,931,791 A	8/1999	Saltzstein et al.	6,334,065 B1	12/2001	Al-Ali et al.
5,934,925 A	8/1999	Tobler et al.	6,338,039 B1	1/2002	Lonski et al.
5,940,182 A	8/1999	Lepper, Jr. et al.	6,343,224 B1	1/2002	Parker
5,942,986 A	8/1999	Shabot et al.	6,349,228 B1	2/2002	Kiani et al.
5,987,343 A	11/1999	Kinast	6,352,504 B1	3/2002	Ise
5,987,519 A	11/1999	Peifer et al.	6,354,235 B1	3/2002	Davies
5,995,855 A	11/1999	Kiani et al.	6,360,114 B1	3/2002	Diab et al.
5,997,343 A	12/1999	Mills et al.	6,364,834 B1	4/2002	Reuss et al.
6,002,952 A	12/1999	Diab et al.	6,364,839 B1	4/2002	Little et al.
6,006,119 A	12/1999	Soller et al.	6,368,283 B1	4/2002	Xu et al.
6,011,986 A	1/2000	Diab et al.	6,371,921 B1	4/2002	Caro et al.
6,014,346 A	1/2000	Malone	6,377,829 B1	4/2002	Al-Ali
6,018,673 A	1/2000	Chin et al.	6,385,476 B1	5/2002	Osadchy et al.
6,024,699 A	2/2000	Surwit et al.	6,385,589 B1	5/2002	Trusheim et al.
6,027,452 A	2/2000	Flaherty et al.	6,388,240 B2	5/2002	Schulz et al.
6,032,678 A	3/2000	Rottem	6,397,091 B2	5/2002	Diab et al.
6,035,230 A	3/2000	Kang et al.	6,407,335 B1	6/2002	Franklin-Lees
6,036,642 A	3/2000	Diab et al.	6,430,437 B1	8/2002	Marro
6,036,718 A	3/2000	Ledford et al.	6,430,525 B1	8/2002	Weber et al.
6,045,509 A	4/2000	Caro et al.	6,463,311 B1	10/2002	Diab
6,045,527 A	4/2000	Appelbaum et al.	6,470,199 B1	10/2002	Kopotic et al.
6,057,758 A	5/2000	Dempsey et al.	6,470,893 B1	10/2002	Boesen
6,067,462 A	5/2000	Diab et al.	6,501,975 B2	12/2002	Diab et al.
6,081,735 A	6/2000	Diab et al.	6,505,059 B1	1/2003	Kollias et al.
6,088,607 A	7/2000	Diab et al.	6,515,273 B2	2/2003	Al-Ali
6,093,146 A	7/2000	Filangeri	6,516,289 B2	2/2003	David et al.
6,101,478 A	8/2000	Brown	6,519,487 B1	2/2003	Parker
6,106,463 A	8/2000	Wilk	6,524,240 B1	2/2003	Thede
6,110,522 A	8/2000	Lepper, Jr. et al.	6,525,386 B1	2/2003	Mills et al.
6,124,597 A	9/2000	Shehada	6,526,300 B1	2/2003	Kiani et al.
6,128,521 A	10/2000	Marro et al.	6,541,756 B2	4/2003	Schulz et al.
6,129,675 A	10/2000	Jay	6,542,764 B1	4/2003	Al-Ali et al.
6,132,218 A	10/2000	Benja-Athon	6,544,173 B2	4/2003	West et al.
6,139,494 A	10/2000	Cairnes	6,544,174 B2	4/2003	West et al.
6,144,868 A	11/2000	Parker	6,551,243 B2	4/2003	Bocionek et al.
6,151,516 A	11/2000	Kiani-Azarbayjany et al.	6,570,592 B1	5/2003	Sajdak et al.
6,152,754 A	11/2000	Gerhardt et al.	6,578,428 B1	6/2003	Dromms et al.
6,157,850 A	12/2000	Diab et al.	6,580,086 B1	6/2003	Schulz et al.
6,165,005 A	12/2000	Mills et al.	6,584,336 B1	6/2003	Ali et al.
6,167,258 A	12/2000	Schmidt et al.	6,595,316 B2	7/2003	Cybulski et al.
D437,058 S	1/2001	Gozani	6,597,932 B2	7/2003	Tian et al.
6,168,563 B1	1/2001	Brown	6,597,933 B2	7/2003	Kiani et al.
6,171,237 B1	1/2001	Avitall et al.	6,606,511 B1	8/2003	Ali et al.
6,175,752 B1	1/2001	Say et al.	6,616,606 B1	9/2003	Peterson et al.
6,183,417 B1	2/2001	Gehab et al.	6,632,181 B2	10/2003	Flaherty et al.
6,184,521 B1	2/2001	Coffin, IV et al.	6,639,668 B1	10/2003	Trepagnier
6,185,448 B1	2/2001	Borovsky	6,640,116 B2	10/2003	Diab
6,195,576 B1	2/2001	John	6,641,533 B2	11/2003	Causey et al.
6,206,830 B1	3/2001	Diab et al.	6,643,530 B2	11/2003	Diab et al.
6,221,012 B1	4/2001	Maschke et al.	6,646,556 B1	11/2003	Smith et al.
6,224,553 B1	5/2001	Nevo	6,650,917 B2	11/2003	Diab et al.
6,229,856 B1	5/2001	Diab et al.	6,650,939 B2	11/2003	Takpke, II et al.
6,230,142 B1	5/2001	Benigno et al.	6,654,624 B2	11/2003	Diab et al.
6,232,609 B1	5/2001	Snyder et al.	D483,872 S	12/2003	Cruz et al.
6,236,872 B1	5/2001	Diab et al.	6,658,276 B2	12/2003	Kianl et al.
6,241,683 B1	6/2001	Macklem et al.	6,661,161 B1	12/2003	Lanzo et al.
6,241,684 B1	6/2001	Amano et al.	6,663,570 B2	12/2003	Mott et al.
6,251,113 B1	6/2001	Appelbaum	6,671,531 B2	12/2003	Al-Ali et al.
			6,678,543 B2	1/2004	Diab et al.
			6,684,090 B2	1/2004	Ali et al.
			6,684,091 B2	1/2004	Parker
			6,694,180 B1	2/2004	Boesen

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,697,656 B1	2/2004	Al-Ali	7,033,761 B2	4/2006	Shafer
6,697,657 B1	2/2004	Shehada et al.	7,035,686 B2	4/2006	Hogan
6,697,658 B2	2/2004	Al-Ali	7,039,449 B2	5/2006	Al-Ali
RE38,476 E	3/2004	Diab et al.	7,041,060 B2	5/2006	Flaherty et al.
6,699,194 B1	3/2004	Diab et al.	7,044,918 B2	5/2006	Diab
6,707,476 B1	3/2004	Hochstedler	7,044,930 B2	5/2006	Stromberg
6,714,804 B2	3/2004	Al-Ali et al.	7,048,687 B1	5/2006	Reuss et al.
RE38,492 E	4/2004	Diab et al.	7,059,769 B1	6/2006	Potega
6,719,694 B2	4/2004	Weng et al.	7,063,666 B2	6/2006	Weng et al.
6,721,582 B2	4/2004	Trepagnier et al.	7,067,893 B2	6/2006	Mills et al.
6,721,585 B1	4/2004	Parker	7,079,035 B2	7/2006	Bock et al.
6,725,075 B2	4/2004	Al-Ali	7,096,052 B2	8/2006	Mason et al.
6,725,086 B2	4/2004	Marinello	7,096,054 B2	8/2006	Abdul-Hafiz et al.
6,728,560 B2	4/2004	Kollias et al.	7,132,641 B2	11/2006	Schulz et al.
6,735,459 B2	5/2004	Parker	7,142,901 B2	11/2006	Kiani et al.
6,745,060 B2	6/2004	Diab et al.	7,149,561 B2	12/2006	Diab
6,746,406 B2	6/2004	Lia et al.	7,186,966 B2	3/2007	Al-Ali
6,750,463 B1	6/2004	Riley	7,188,621 B2	3/2007	DeVries et al.
6,751,492 B2	6/2004	Ben-haim	7,190,261 B2	3/2007	Al-Ali
6,760,607 B2	7/2004	Al-Ali	7,208,119 B1	4/2007	Kurtock et al.
6,766,188 B2	7/2004	Soller	7,215,984 B2	5/2007	Diab
6,770,028 B1	8/2004	Ali et al.	7,215,986 B2	5/2007	Diab
6,771,994 B2	8/2004	Kiani et al.	7,221,971 B2	5/2007	Diab
6,773,396 B2	8/2004	Flach et al.	7,225,006 B2	5/2007	Al-Ali et al.
6,783,492 B2	8/2004	Dominguez	7,225,007 B2	5/2007	Al-Ali
6,790,178 B1	9/2004	Mault et al.	RE39,672 E	6/2007	Shehada et al.
6,792,300 B1	9/2004	Diab et al.	7,229,415 B2	6/2007	Schwartz
6,795,724 B2	9/2004	Hogan	7,239,905 B2	7/2007	Kiani-Azarbayjany et al.
6,796,186 B2	9/2004	Lia et al.	7,241,287 B2	7/2007	Shehada et al.
6,804,656 B1	10/2004	Rosenfeld	7,244,251 B2	7/2007	Shehada et al.
6,807,050 B1	10/2004	Whitehorn et al.	7,245,373 B2	7/2007	Soller et al.
6,813,511 B2	11/2004	Diab et al.	7,245,953 B1	7/2007	Parker
6,816,741 B2	11/2004	Diab	7,252,659 B2	8/2007	Shehada et al.
6,817,979 B2	11/2004	Nihtila et al.	7,254,429 B2	8/2007	Schurman et al.
6,822,564 B2	11/2004	Al-Ali	7,254,431 B2	8/2007	Al-Ali
6,826,419 B2	11/2004	Diab et al.	7,254,433 B2	8/2007	Diab et al.
6,830,711 B2	12/2004	Mills et al.	7,254,434 B2	8/2007	Schulz et al.
6,837,848 B2	1/2005	Bonner et al.	7,256,708 B2	8/2007	Rosenfeld
6,841,535 B2	1/2005	Divita et al.	7,261,697 B2	8/2007	Berstein
6,850,787 B2	2/2005	Weber et al.	7,264,616 B2	9/2007	Shehada et al.
6,850,788 B2	2/2005	Al-Ali	7,267,671 B2	9/2007	Shehada et al.
6,852,083 B2	2/2005	Caro et al.	7,272,425 B2	9/2007	Al-Ali
6,855,112 B2	2/2005	Kao et al.	7,274,955 B2	9/2007	Kiani et al.
6,860,266 B2	3/2005	Blike	D554,263 S	10/2007	Al-Ali
6,861,639 B2	3/2005	Al-Ali	7,280,858 B2	10/2007	Al-Ali et al.
6,897,788 B2	5/2005	Khair et al.	7,285,090 B2	10/2007	Stivoric
6,898,452 B2	5/2005	Al-Ali et al.	7,289,835 B2	10/2007	Mansfield et al.
6,907,237 B1	6/2005	Dorenbosch et al.	7,292,883 B2	11/2007	De Felice et al.
6,915,149 B2	7/2005	Ben-haim	7,295,866 B2	11/2007	Al-Ali
6,920,345 B2	7/2005	Al-Ali et al.	7,307,543 B2	12/2007	Rosenfeld
6,931,268 B1	8/2005	Kiani-Azarbayjany et al.	7,313,423 B2	12/2007	Griffin et al.
6,934,570 B2	8/2005	Kiani et al.	7,314,446 B2	1/2008	Byrd et al.
6,939,305 B2	9/2005	Flaherty et al.	7,315,825 B2	1/2008	Rosenfeld
6,943,348 B1	9/2005	Coffin, IV	7,321,862 B2	1/2008	Rosenfeld
6,950,687 B2	9/2005	Al-Ali	7,322,971 B2	1/2008	Shehada et al.
6,952,340 B2	10/2005	Son	7,328,053 B1	2/2008	Diab et al.
6,961,598 B2	11/2005	Diab	7,332,784 B2	2/2008	Mills et al.
6,970,792 B1	11/2005	Diab	7,340,287 B2	3/2008	Mason et al.
6,979,812 B2	12/2005	Al-Ali	7,341,559 B2	3/2008	Schulz et al.
6,980,419 B2	12/2005	Smith et al.	7,343,186 B2	3/2008	Lamego et al.
6,983,179 B2	1/2006	Ben-haim	D566,282 S	4/2008	Al-Ali et al.
6,985,764 B2	1/2006	Mason et al.	7,355,512 B1	4/2008	Al-Ali
6,988,989 B2	1/2006	Weiner et al.	7,356,178 B2	4/2008	Ziel et al.
6,990,087 B2	1/2006	Rao et al.	7,356,365 B2	4/2008	Schurman
6,993,371 B2	1/2006	Kiani et al.	7,371,981 B2	5/2008	Abdul-Hafiz
6,996,427 B2	2/2006	Ali et al.	7,373,193 B2	5/2008	Al-Ali et al.
6,997,884 B2	2/2006	Ulmsten	7,373,194 B2	5/2008	Weber et al.
6,999,904 B2	2/2006	Weber et al.	7,376,453 B1	5/2008	Diab et al.
7,003,338 B2	2/2006	Weber et al.	7,377,794 B2	5/2008	Al Ali et al.
7,003,339 B2	2/2006	Diab et al.	7,377,899 B2	5/2008	Weber et al.
7,015,451 B2	3/2006	Dalke et al.	7,378,975 B1	5/2008	Smith et al.
7,024,233 B2	4/2006	Ali et al.	7,382,247 B2	6/2008	Welch et al.
7,025,729 B2	4/2006	De Chazal et al.	7,383,070 B2	6/2008	Diab et al.
7,027,849 B2	4/2006	Al-Ali	7,390,299 B2	6/2008	Weiner et al.
7,030,749 B2	4/2006	Al-Ali	7,395,216 B2	7/2008	Rosenfeld
			7,411,509 B2	8/2008	Rosenfeld
			7,413,546 B2	8/2008	Agutter et al.
			7,415,297 B2	8/2008	Al-Ali et al.
			7,419,483 B2	9/2008	Shehada

(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,428,432 B2	9/2008	Ali et al.	7,794,407 B2	9/2010	Rothenberg
7,433,827 B2	10/2008	Rosenfeld	7,801,581 B2	9/2010	Diab
7,438,683 B2	10/2008	Al-Ali et al.	7,806,830 B2	10/2010	Bernstein
7,439,856 B2	10/2008	Weiner et al.	7,820,184 B2	10/2010	Strizker et al.
7,440,787 B2	10/2008	Diab	7,822,452 B2	10/2010	Schurman et al.
7,454,240 B2	11/2008	Diab et al.	RE41,912 E	11/2010	Parker
7,454,359 B2	11/2008	Rosenfeld	7,831,450 B2	11/2010	Schoenberg
7,454,360 B2	11/2008	Rosenfeld	7,841,986 B2	11/2010	He et al.
7,462,151 B2	12/2008	Childre et al.	7,844,313 B2	11/2010	Kiani et al.
7,467,002 B2	12/2008	Weber et al.	7,844,314 B2	11/2010	Al-Ali
7,467,094 B2	12/2008	Rosenfeld	7,844,315 B2	11/2010	Al-Ali
7,469,157 B2	12/2008	Diab et al.	7,848,935 B2	12/2010	Gotlib
7,471,969 B2	12/2008	Diab et al.	7,858,322 B2	12/2010	Tymianski et al.
7,471,971 B2	12/2008	Diab et al.	7,865,222 B2	1/2011	Weber et al.
7,475,019 B2	1/2009	Rosenfeld	7,865,232 B1	1/2011	Krishnaswamy et al.
7,483,729 B2	1/2009	Al-Ali et al.	7,873,497 B2	1/2011	Weber et al.
7,483,730 B2	1/2009	Diab et al.	7,880,606 B2	2/2011	Al-Ali
7,489,250 B2	2/2009	Bock et al.	7,880,626 B2	2/2011	Al-Ali et al.
7,489,958 B2	2/2009	Diab et al.	7,881,892 B2	2/2011	Soyemi et al.
7,496,391 B2	2/2009	Diab et al.	7,884,314 B2	2/2011	Hamada
7,496,393 B2	2/2009	Diab et al.	7,890,156 B2	2/2011	Ooi et al.
D587,657 S	3/2009	Al-Ali et al.	7,891,355 B2	2/2011	Al-Ali et al.
7,497,828 B1	3/2009	Wilk et al.	7,894,868 B2	2/2011	Al-Ali et al.
7,499,741 B2	3/2009	Diab et al.	7,899,507 B2	3/2011	Al-Ali et al.
7,499,835 B2	3/2009	Weber et al.	7,899,518 B2	3/2011	Trepagnier et al.
7,500,950 B2	3/2009	Al-Ali et al.	7,904,132 B2	3/2011	Weber et al.
7,509,154 B2	3/2009	Diab et al.	7,909,772 B2	3/2011	Popov et al.
7,509,494 B2	3/2009	Al-Ali	7,910,875 B2	3/2011	Al-Ali
7,510,849 B2	3/2009	Schurman et al.	7,914,514 B2	3/2011	Calderon
7,515,043 B2	4/2009	Welch et al.	7,919,713 B2	4/2011	Al-Ali et al.
7,515,044 B2	4/2009	Welch et al.	7,937,128 B2	5/2011	Al-Ali
7,526,328 B2	4/2009	Diab et al.	7,937,129 B2	5/2011	Mason et al.
7,530,942 B1	5/2009	Diab	7,937,130 B2	5/2011	Diab et al.
7,530,949 B2	5/2009	Al Ali et al.	7,941,199 B2	5/2011	Kiani
7,530,955 B2	5/2009	Diab et al.	7,951,086 B2	5/2011	Flaherty et al.
7,532,919 B2	5/2009	Soyemi et al.	7,957,780 B2	6/2011	Lamego et al.
7,549,961 B1	6/2009	Hwang	7,962,188 B2	6/2011	Kiani et al.
7,551,717 B2	6/2009	Tome et al.	7,962,190 B1	6/2011	Diab et al.
7,559,520 B2	7/2009	Quijano et al.	7,963,927 B2	6/2011	Kelleher et al.
7,563,110 B2	7/2009	Al-Ali et al.	7,967,749 B2	6/2011	Hutchinson et al.
7,577,475 B2	8/2009	Consentino et al.	7,976,472 B2	7/2011	Kiani
7,590,950 B2	9/2009	Collins et al.	7,988,637 B2	8/2011	Diab
7,596,398 B2	9/2009	Al-Ali et al.	7,988,639 B2	8/2011	Starks
7,597,665 B2	10/2009	Wilk et al.	7,990,382 B2	8/2011	Kiani
7,612,999 B2	11/2009	Clark et al.	7,991,446 B2	8/2011	Al-Ali et al.
7,616,303 B2	11/2009	Yang et al.	7,991,463 B2	8/2011	Kelleher et al.
7,618,375 B2	11/2009	Flaherty	7,991,625 B2	8/2011	Rosenfeld
D606,659 S	12/2009	Kiani et al.	8,000,761 B2	8/2011	Al-Ali
7,639,145 B2	12/2009	Lawson et al.	8,008,088 B2	8/2011	Bellott et al.
7,647,083 B2	1/2010	Al-Ali et al.	RE42,753 E	9/2011	Kiani-Azarbayjany et al.
7,650,291 B2	1/2010	Rosenfeld	8,019,400 B2	9/2011	Diab et al.
D609,193 S	2/2010	Al-Ali et al.	8,027,846 B2	9/2011	Schoenberg
7,654,966 B2	2/2010	Westinskow et al.	8,028,701 B2	10/2011	Al-Ali et al.
7,684,845 B2	3/2010	Juan	8,029,765 B2	10/2011	Bellott et al.
7,689,437 B1	3/2010	Teller et al.	8,033,996 B2	10/2011	Behar
RE41,236 E	4/2010	Seely	8,036,727 B2	10/2011	Schurman et al.
D614,305 S	4/2010	Al-Ali et al.	8,036,728 B2	10/2011	Diab et al.
7,693,697 B2	4/2010	Westinskow et al.	8,036,736 B2	10/2011	Snyder et al.
RE41,317 E	5/2010	Parker	8,038,625 B2	10/2011	Afonso et al.
7,722,542 B2	5/2010	Lia et al.	8,046,040 B2	10/2011	Ali et al.
7,729,733 B2	6/2010	Al-Ali et al.	8,046,041 B2	10/2011	Diab et al.
7,734,320 B2	6/2010	Al-Ali	8,046,042 B2	10/2011	Diab et al.
7,736,318 B2	6/2010	Consentino et al.	8,048,040 B2	11/2011	Kiani
7,740,590 B2	6/2010	Bernstein	8,050,728 B2	11/2011	Al-Ali et al.
7,761,127 B2	7/2010	Al-Ali et al.	8,068,104 B2	11/2011	Rampersad
7,761,128 B2	7/2010	Al-Ali et al.	8,073,707 B2	12/2011	Teller et al.
7,763,420 B2	7/2010	Strizker et al.	8,094,013 B1	1/2012	Lee et al.
7,764,982 B2	7/2010	Dalke et al.	8,107,397 B1	1/2012	Bagchi et al.
D621,515 S	8/2010	Chua et al.	RE43,169 E	2/2012	Parker
D621,516 S	8/2010	Kiani et al.	8,118,620 B2	2/2012	Al-Ali et al.
7,766,818 B2	8/2010	Iketani et al.	8,126,528 B2	2/2012	Diab et al.
7,772,799 B2	8/2010	Wu	8,128,572 B2	3/2012	Diab et al.
7,774,060 B2	8/2010	Westenskow et al.	8,130,105 B2	3/2012	Al-Ali et al.
7,778,851 B2	8/2010	Schoenberg et al.	8,145,287 B2	3/2012	Diab et al.
7,791,155 B2	9/2010	Diab	8,150,487 B2	4/2012	Diab et al.
			D659,836 S	5/2012	Bensch et al.
			8,170,887 B2	5/2012	Rosenfeld
			8,175,672 B2	5/2012	Parker
			8,175,895 B2	5/2012	Rosenfeld

(56)

## References Cited

## U.S. PATENT DOCUMENTS

8,180,420 B2	5/2012	Diab et al.	8,489,167 B2	7/2013	Buxton et al.
8,182,429 B2	5/2012	Mason	8,489,364 B2	7/2013	Weber et al.
8,182,443 B1	5/2012	Kiani	8,498,684 B2	7/2013	Weber et al.
8,185,180 B2	5/2012	Diab et al.	8,504,128 B2	8/2013	Blank et al.
8,190,223 B2	5/2012	Al-Ali et al.	8,509,867 B2	8/2013	Workman et al.
8,190,227 B2	5/2012	Diab et al.	8,515,509 B2	8/2013	Bruinsma et al.
8,200,308 B2	6/2012	Zhang et al.	8,523,781 B2	9/2013	Al-Ali
8,203,438 B2	6/2012	Kiani et al.	8,529,301 B2	9/2013	Al-Ali et al.
8,203,704 B2	6/2012	Merritt et al.	8,532,727 B2	9/2013	Ali et al.
8,204,566 B2	6/2012	Schurman et al.	8,532,728 B2	9/2013	Diab et al.
8,206,312 B2	6/2012	Farquhar	D692,145 S	10/2013	Al-Ali et al.
8,214,007 B2	7/2012	Baker et al.	8,547,209 B2	10/2013	Kiani et al.
8,219,172 B2	7/2012	Schurman et al.	8,548,548 B2	10/2013	Al-Ali
8,224,411 B2	7/2012	Al-Ali et al.	8,548,549 B2	10/2013	Schurman et al.
8,228,181 B2	7/2012	Al-Ali	8,548,550 B2	10/2013	Al-Ali et al.
8,229,533 B2	7/2012	Diab et al.	8,560,032 B2	10/2013	Al-Ali et al.
8,233,955 B2	7/2012	Al-Ali et al.	8,560,034 B1	10/2013	Diab et al.
8,235,907 B2	8/2012	Wilk et al.	8,565,847 B2	10/2013	Buxton et al.
8,239,780 B2	8/2012	Manetta et al.	8,570,167 B2	10/2013	Al-Ali
8,241,213 B2	8/2012	Lynn et al.	8,570,503 B2	10/2013	Vo et al.
8,244,325 B2	8/2012	Al-Ali et al.	8,571,617 B2	10/2013	Reichgott et al.
8,249,815 B2	8/2012	Taylor	8,571,618 B1	10/2013	Lamego et al.
8,255,026 B1	8/2012	Al-Ali	8,571,619 B2	10/2013	Al-Ali et al.
8,255,027 B2	8/2012	Al-Ali et al.	8,577,431 B2	11/2013	Lamego et al.
8,255,028 B2	8/2012	Al-Ali et al.	8,578,082 B2	11/2013	Medina et al.
8,260,577 B2	9/2012	Weber et al.	8,579,813 B2	11/2013	Causey, III et al.
8,265,723 B1	9/2012	McHale et al.	8,581,732 B2	11/2013	Al-Ali et al.
8,274,360 B2	9/2012	Sampath et al.	8,584,345 B2	11/2013	Al-Ali et al.
8,280,473 B2	10/2012	Al-Ali	8,588,880 B2	11/2013	Abdul-Hafiz et al.
8,294,588 B2	10/2012	Fisher et al.	8,588,924 B2	11/2013	Dion
8,294,716 B2	10/2012	Lord et al.	8,597,287 B2	12/2013	Benamou et al.
8,301,217 B2	10/2012	Al-Ali et al.	8,600,467 B2	12/2013	Al-Ali et al.
8,306,596 B2	11/2012	Schurman et al.	8,600,777 B2	12/2013	Schoenberg
8,310,336 B2	11/2012	Muhsin et al.	8,606,342 B2	12/2013	Diab
8,311,747 B2	11/2012	Taylor	8,620,678 B2	12/2013	Gotlib
8,311,748 B2	11/2012	Taylor et al.	8,626,255 B2	1/2014	Al-Ali et al.
8,315,683 B2	11/2012	Al-Ali et al.	8,630,691 B2	1/2014	Lamego et al.
8,315,812 B2	11/2012	Taylor	8,634,889 B2	1/2014	Al-Ali et al.
8,315,813 B2	11/2012	Taylor et al.	8,641,631 B2	2/2014	Sierra et al.
8,315,814 B2	11/2012	Taylor et al.	8,652,060 B2	2/2014	Al-Ali
8,321,150 B2	11/2012	Taylor	8,663,107 B2	3/2014	Kiani
RE43,860 E	12/2012	Parker	8,666,468 B1	3/2014	Al-Ali
8,326,649 B2	12/2012	Rosenfeld	8,667,967 B2	3/2014	Al-Ali et al.
8,328,793 B2	12/2012	Birkenbach et al.	8,670,811 B2	3/2014	O'Reilly
8,337,403 B2	12/2012	Al-Ali et al.	8,670,814 B2	3/2014	Diab et al.
8,346,330 B2	1/2013	Lamego	8,676,286 B2	3/2014	Weber et al.
8,353,842 B2	1/2013	Al-Ali et al.	8,682,407 B2	3/2014	Al-Ali
8,355,766 B2	1/2013	MacNeish, III et al.	RE44,823 E	4/2014	Parker
8,359,080 B2	1/2013	Diab et al.	RE44,875 E	4/2014	Kiani et al.
8,360,936 B2	1/2013	Dibenedetto et al.	8,690,771 B2	4/2014	Wekell et al.
8,364,223 B2	1/2013	Al-Ali et al.	8,690,799 B2	4/2014	Telfort et al.
8,364,226 B2	1/2013	Diab et al.	8,700,112 B2	4/2014	Kiani
8,374,665 B2	2/2013	Lamego	8,702,627 B2	4/2014	Telfort et al.
8,385,995 B2	2/2013	Al-Ali et al.	8,706,179 B2	4/2014	Parker
8,385,996 B2	2/2013	Smith et al.	8,712,494 B1	4/2014	MacNeish, III et al.
D679,018 S	3/2013	Fullerton et al.	8,715,206 B2	5/2014	Telfort et al.
8,388,353 B2	3/2013	Kiani et al.	8,718,735 B2	5/2014	Lamego et al.
8,399,822 B2	3/2013	Al-Ali	8,718,737 B2	5/2014	Diab et al.
8,401,602 B2	3/2013	Kiani	8,718,738 B2	5/2014	Blank et al.
8,401,874 B2	3/2013	Rosenfeld	8,720,249 B2	5/2014	Al-Ali
8,405,608 B2	3/2013	Al-Ali et al.	8,721,541 B2	5/2014	Al-Ali et al.
8,414,499 B2	4/2013	Al-Ali et al.	8,721,542 B2	5/2014	Al-Ali et al.
8,418,524 B2	4/2013	Al-Ali	8,723,677 B1	5/2014	Kiani
8,423,106 B2	4/2013	Lamego et al.	8,740,792 B1	6/2014	Kiani et al.
8,428,967 B2	4/2013	Olsen et al.	8,753,274 B2	6/2014	Ziv et al.
8,430,817 B1	4/2013	Al-Ali et al.	8,754,776 B2	6/2014	Poeze et al.
8,437,825 B2	5/2013	Dalvi et al.	8,755,535 B2	6/2014	Telfort et al.
8,455,290 B2	6/2013	Siskavich	8,755,856 B2	6/2014	Diab et al.
8,457,703 B2	6/2013	Al-Ali	8,755,872 B1	6/2014	Marinow
8,457,707 B2	6/2013	Kiani	8,758,020 B2	6/2014	Burdea et al.
8,463,349 B2	6/2013	Diab et al.	8,761,850 B2	6/2014	Lamego
8,466,286 B2	6/2013	Bellot et al.	D709,846 S	7/2014	Oswaks
8,471,713 B2	6/2013	Poeze et al.	8,764,671 B2	7/2014	Kiani
8,473,020 B2	6/2013	Kiani et al.	8,768,423 B2	7/2014	Shakespeare et al.
8,483,787 B2	7/2013	Al-Ali et al.	8,771,204 B2	7/2014	Telfort et al.
			8,777,634 B2	7/2014	Kiani et al.
			8,781,543 B2	7/2014	Diab et al.
			8,781,544 B2	7/2014	Al-Ali et al.
			8,781,549 B2	7/2014	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,788,003 B2	7/2014	Schurman et al.	9,167,995 B2	10/2015	Lamego et al.
8,790,268 B2	7/2014	Al-Ali	9,176,141 B2	11/2015	Al-Ali et al.
8,792,950 B2	7/2014	Larsen et al.	9,186,102 B2	11/2015	Bruinsma et al.
8,801,613 B2	8/2014	Al-Ali et al.	9,192,312 B2	11/2015	Al-Ali
8,818,477 B2	8/2014	Soller	9,192,329 B2	11/2015	Al-Ali
8,821,397 B2	9/2014	Al-Ali et al.	9,192,351 B1	11/2015	Telfort et al.
8,821,415 B2	9/2014	Al-Ali et al.	9,195,385 B2	11/2015	Al-Ali et al.
8,830,449 B1	9/2014	Lamego et al.	D745,167 S	12/2015	Canas et al.
8,831,700 B2	9/2014	Schurman et al.	9,211,072 B2	12/2015	Kiani
8,840,549 B2	9/2014	Al-Ali et al.	9,211,095 B1	12/2015	Al-Ali
8,847,740 B2	9/2014	Kiani et al.	9,218,454 B2	12/2015	Kiani et al.
8,849,365 B2	9/2014	Smith et al.	9,226,696 B2	1/2016	Kiani
8,852,094 B2	10/2014	Al-Ali et al.	9,241,662 B2	1/2016	Al-Ali et al.
8,852,994 B2	10/2014	Wojtczuk et al.	9,245,668 B1	1/2016	Vo et al.
8,866,620 B2	10/2014	Amir	9,259,185 B2	2/2016	Abdul-Hafiz et al.
8,868,147 B2	10/2014	Stippick et al.	9,262,586 B2	2/2016	Steiger et al.
8,868,150 B2	10/2014	Al-Ali et al.	9,267,572 B2	2/2016	Barker et al.
8,870,792 B2	10/2014	Al-Ali et al.	9,277,880 B2	3/2016	Poeze et al.
8,873,035 B2	10/2014	Yang et al.	9,289,167 B2	3/2016	Diab et al.
8,878,888 B2	11/2014	Rosenfeld	9,295,421 B2	3/2016	Kiani et al.
8,886,271 B2	11/2014	Kiani et al.	9,307,928 B1	4/2016	Al-Ali et al.
8,888,539 B2	11/2014	Al-Ali et al.	9,323,894 B2	4/2016	Kiani
8,888,708 B2	11/2014	Diab et al.	D755,392 S	5/2016	Hwang et al.
8,892,180 B2	11/2014	Weber et al.	9,326,712 B1	5/2016	Kiani
8,897,847 B2	11/2014	Al-Ali	9,333,316 B2	5/2016	Kiani
8,907,287 B2	12/2014	Vanderpohl	9,339,220 B2	5/2016	Lamego et al.
8,909,310 B2	12/2014	Lamego et al.	9,341,565 B2	5/2016	Lamego et al.
8,909,330 B2	12/2014	McCombie et al.	9,351,673 B2	5/2016	Diab et al.
8,911,377 B2	12/2014	Al-Ali	9,351,675 B2	5/2016	Al-Ali et al.
8,912,909 B2	12/2014	Al-Ali et al.	9,364,181 B2	6/2016	Kiani et al.
8,920,317 B2	12/2014	Al-Ali et al.	9,368,671 B2	6/2016	Wojtczuk et al.
8,921,699 B2	12/2014	Al-Ali et al.	9,370,325 B2	6/2016	Al-Ali et al.
8,922,382 B2	12/2014	Al-Ali et al.	9,370,326 B2	6/2016	McHale et al.
8,929,964 B2	1/2015	Al-Ali et al.	9,370,335 B2	6/2016	Al-Ali et al.
8,942,777 B2	1/2015	Diab et al.	9,375,185 B2	6/2016	Ali et al.
8,948,834 B2	2/2015	Diab et al.	9,386,953 B2	7/2016	Al-Ali
8,948,835 B2	2/2015	Diab	9,386,961 B2	7/2016	Al-Ali et al.
8,951,248 B2	2/2015	Messerly et al.	9,392,945 B2	7/2016	Al-Ali et al.
8,956,292 B2	2/2015	Wekell et al.	9,397,448 B2	7/2016	Al-Ali et al.
8,965,471 B2	2/2015	Lamego	9,408,542 B1	8/2016	Kinast et al.
8,983,564 B2	3/2015	Al-Ali	9,414,784 B1	8/2016	Berme et al.
8,989,831 B2	3/2015	Al-Ali et al.	9,436,645 B2	9/2016	Al-Ali et al.
8,996,085 B2	3/2015	Kiani et al.	9,445,759 B1	9/2016	Lamego et al.
8,998,809 B2	4/2015	Kiani	9,466,919 B2	10/2016	Kiani et al.
9,028,429 B2	5/2015	Telfort et al.	9,474,474 B2	10/2016	Lamego et al.
9,037,207 B2	5/2015	Al-Ali et al.	9,480,422 B2	11/2016	Al-Ali
9,057,689 B2	6/2015	Soller	9,480,435 B2	11/2016	Olsen
9,060,721 B2	6/2015	Reichgott et al.	9,492,110 B2	11/2016	Al-Ali et al.
9,066,666 B2	6/2015	Kiani	9,510,779 B2	12/2016	Poeze et al.
9,066,680 B1	6/2015	Al-Ali et al.	9,517,024 B2	12/2016	Kiani et al.
9,072,474 B2	7/2015	Al-Ali et al.	9,529,762 B2	12/2016	Gisler et al.
9,078,560 B2	7/2015	Schurman et al.	9,532,722 B2	1/2017	Lamego et al.
9,084,569 B2	7/2015	Weber et al.	9,538,949 B2	1/2017	Al-Ali et al.
9,095,291 B2	8/2015	Soller	9,538,980 B2	1/2017	Telfort et al.
9,095,316 B2	8/2015	Welch et al.	9,549,696 B2	1/2017	Lamego et al.
9,104,789 B2	8/2015	Gross et al.	9,554,737 B2	1/2017	Schurman et al.
9,106,038 B2	8/2015	Telfort et al.	9,560,996 B2	2/2017	Kiani
9,107,625 B2	8/2015	Telfort et al.	9,560,998 B2	2/2017	Al-Ali et al.
9,107,626 B2	8/2015	Al-Ali et al.	9,566,019 B2	2/2017	Al-Ali et al.
9,113,831 B2	8/2015	Al-Ali	9,579,039 B2	2/2017	Jansen et al.
9,113,832 B2	8/2015	Al-Ali	9,591,975 B2	3/2017	Dalvi et al.
9,119,595 B2	9/2015	Lamego	9,622,692 B2	4/2017	Lamego et al.
9,125,578 B2	9/2015	Grunwald	9,622,693 B2	4/2017	Diab
9,131,881 B2	9/2015	Diab et al.	D788,312 S	5/2017	Al-Ali et al.
9,131,882 B2	9/2015	Al-Ali et al.	9,636,055 B2	5/2017	Al-Ali et al.
9,131,883 B2	9/2015	Al-Ali	9,636,056 B2	5/2017	Al-Ali
9,131,917 B2	9/2015	Telfort et al.	9,649,054 B2	5/2017	Lamego et al.
9,138,180 B1	9/2015	Coverston et al.	9,662,052 B2	5/2017	Al-Ali et al.
9,138,182 B2	9/2015	Al-Ali et al.	9,668,679 B2	6/2017	Schurman et al.
9,138,192 B2	9/2015	Weber et al.	9,668,680 B2	6/2017	Bruinsma et al.
9,142,117 B2	9/2015	Muhsin et al.	9,668,703 B2	6/2017	Al-Ali
9,153,112 B1	10/2015	Kiani et al.	9,675,286 B2	6/2017	Diab
9,153,121 B2	10/2015	Kiani et al.	9,687,160 B2	6/2017	Kiani
9,161,696 B2	10/2015	Al-Ali et al.	9,693,719 B2	7/2017	Al-Ali et al.
9,161,713 B2	10/2015	Al-Ali et al.	9,693,737 B2	7/2017	Al-Ali
			9,697,928 B2	7/2017	Al-Ali et al.
			9,717,425 B2	8/2017	Kiani et al.
			9,717,458 B2	8/2017	Lamego et al.
			9,724,016 B1	8/2017	Al-Ali et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

9,724,024 B2	8/2017	Al-Ali	10,123,726 B2	11/2018	Al-Ali et al.
9,724,025 B1	8/2017	Kiani et al.	10,130,289 B2	11/2018	Al-Ali et al.
9,730,640 B2	8/2017	Diab et al.	10,130,291 B2	11/2018	Schurman et al.
9,743,887 B2	8/2017	Al-Ali et al.	D835,282 S	12/2018	Barker et al.
9,749,232 B2	8/2017	Sampath et al.	D835,283 S	12/2018	Barker et al.
9,750,442 B2	9/2017	Olsen	D835,284 S	12/2018	Barker et al.
9,750,443 B2	9/2017	Smith et al.	D835,285 S	12/2018	Barker et al.
9,750,461 B1	9/2017	Telfort	10,149,616 B2	12/2018	Al-Ali et al.
9,775,545 B2	10/2017	Al-Ali et al.	10,154,815 B2	12/2018	Al-Ali et al.
9,775,546 B2	10/2017	Diab et al.	10,159,412 B2	12/2018	Lamego et al.
9,775,570 B2	10/2017	Al-Ali	10,188,296 B2	1/2019	Al-Ali et al.
9,778,079 B1	10/2017	Al-Ali et al.	10,188,331 B1	1/2019	Al-Ali et al.
9,782,077 B2	10/2017	Lamego et al.	10,188,348 B2	1/2019	Kiani et al.
9,782,110 B2	10/2017	Kiani	RE47,218 E	2/2019	Ali-Ali
9,787,568 B2	10/2017	Lamego et al.	RE47,244 E	2/2019	Kiani et al.
9,788,735 B2	10/2017	Al-Ali	RE47,249 E	2/2019	Kiani et al.
9,788,768 B2	10/2017	Al-Ali et al.	10,194,847 B2	2/2019	Al-Ali
9,795,300 B2	10/2017	Al-Ali	10,194,848 B1	2/2019	Kiani et al.
9,795,310 B2	10/2017	Al-Ali	10,201,298 B2	2/2019	Al-Ali et al.
9,795,358 B2	10/2017	Telfort et al.	10,205,272 B2	2/2019	Kiani et al.
9,795,739 B2	10/2017	Al-Ali et al.	10,205,291 B2	2/2019	Scruggs et al.
9,801,556 B2	10/2017	Kiani	10,213,108 B2	2/2019	Al-Ali
9,801,588 B2	10/2017	Weber et al.	10,219,706 B2	3/2019	Al-Ali
9,808,188 B1	11/2017	Perea et al.	10,219,746 B2	3/2019	McHale et al.
9,814,418 B2	11/2017	Weber et al.	10,226,187 B2	3/2019	Al-Ali et al.
9,820,691 B2	11/2017	Kiani	10,226,576 B2	3/2019	Kiani
9,833,152 B2	12/2017	Kiani et al.	10,231,657 B2	3/2019	Al-Ali et al.
9,833,180 B2	12/2017	Shakespeare et al.	10,231,670 B2	3/2019	Blank et al.
9,839,379 B2	12/2017	Al-Ali et al.	10,231,676 B2	3/2019	Al-Ali et al.
9,839,381 B1	12/2017	Weber et al.	RE47,353 E	4/2019	Kiani et al.
9,847,002 B2	12/2017	Kiani et al.	10,251,585 B2	4/2019	Al-Ali et al.
9,847,749 B2	12/2017	Kiani et al.	10,251,586 B2	4/2019	Lamego
9,848,800 B1	12/2017	Lee et al.	10,255,994 B2	4/2019	Sampath et al.
9,848,806 B2	12/2017	Al-Ali et al.	10,258,265 B1	4/2019	Poeze et al.
9,848,807 B2	12/2017	Lamego	10,258,266 B1	4/2019	Poeze et al.
9,861,298 B2	1/2018	Eckerbom et al.	10,271,748 B2	4/2019	Al-Ali
9,861,304 B2	1/2018	Al-Ali et al.	10,278,626 B2	5/2019	Schurman et al.
9,861,305 B1	1/2018	Weber et al.	10,278,648 B2	5/2019	Al-Ali et al.
9,867,578 B2	1/2018	Al-Ali et al.	10,279,247 B2	5/2019	Kiani
9,872,623 B2	1/2018	Al-Ali	10,292,628 B1	5/2019	Poeze et al.
9,876,320 B2	1/2018	Coverston et al.	10,292,657 B2	5/2019	Abdul-Hafiz et al.
9,877,650 B2	1/2018	Muhsin et al.	10,292,664 B2	5/2019	Al-Ali
9,877,686 B2	1/2018	Al-Ali et al.	10,299,708 B1	5/2019	Poeze et al.
9,891,079 B2	2/2018	Dalvi	10,299,709 B2	5/2019	Perea et al.
9,895,107 B2	2/2018	Al-Ali et al.	10,305,775 B2	5/2019	Lamego et al.
9,913,617 B2	3/2018	Al-Ali et al.	10,307,111 B2	6/2019	Muhsin et al.
9,924,893 B2	3/2018	Schurman et al.	10,325,681 B2	6/2019	Sampath et al.
9,924,897 B1	3/2018	Abdul-Hafiz	10,327,337 B2	6/2019	Triman et al.
9,936,917 B2	4/2018	Poeze et al.	10,335,033 B2	7/2019	Al-Ali
9,943,269 B2	4/2018	Al-Ali et al.	10,354,504 B2	7/2019	Kiani et al.
9,949,676 B2	4/2018	Al-Ali	2001/0011355 A1	8/2001	Kawai
9,955,937 B2	5/2018	Telfort	2001/0031922 A1	10/2001	Weng et al.
9,965,946 B2	5/2018	Al-Ali et al.	2001/0039199 A1	11/2001	Shinzaki
9,980,667 B2	5/2018	Kiani et al.	2001/0046366 A1	11/2001	Susskind
D820,865 S	6/2018	Muhsin et al.	2001/0046862 A1	11/2001	Coppinger et al.
9,986,919 B2	6/2018	Lamego et al.	2001/0055978 A1	12/2001	Herrod et al.
9,986,952 B2	6/2018	Dalvi et al.	2002/0038392 A1	3/2002	De La Huerga
9,989,560 B2	6/2018	Poeze et al.	2002/0045836 A1	4/2002	Alkawwas
9,993,207 B2	6/2018	Al-Ali et al.	2002/0052311 A1	5/2002	Solomon et al.
10,007,758 B2	6/2018	Al-Ali et al.	2002/0063690 A1	5/2002	Chung et al.
D822,215 S	7/2018	Al-Ali et al.	2002/0140675 A1	10/2002	Ali et al.
D822,216 S	7/2018	Barker et al.	2002/0177758 A1	11/2002	Schoenberg
10,010,276 B2	7/2018	Al-Ali et al.	2002/0198445 A1	12/2002	Dominguez et al.
10,032,002 B2	7/2018	Kiani et al.	2003/0027326 A1	2/2003	Ulmsten et al.
10,039,482 B2	8/2018	Al-Ali et al.	2003/0052787 A1	3/2003	Zerhusen et al.
10,052,037 B2	8/2018	Kinast et al.	2003/0058838 A1	3/2003	Wengrovitz
10,058,275 B2	8/2018	Al-Ali et al.	2003/0158466 A1	8/2003	Lynn et al.
10,064,562 B2	9/2018	Al-Ali	2003/0216670 A1	11/2003	Beggs
10,086,138 B1	10/2018	Novak, Jr.	2004/0013647 A1	1/2004	Solomon et al.
10,092,200 B2	10/2018	Al-Ali et al.	2004/0122787 A1	6/2004	Avinash et al.
10,092,249 B2	10/2018	Kiani et al.	2004/0126007 A1	7/2004	Ziel et al.
10,098,550 B2	10/2018	Al-Ali et al.	2004/0139571 A1	7/2004	Chang et al.
10,098,591 B2	10/2018	Al-Ali et al.	2004/0147818 A1	7/2004	Levy et al.
10,098,610 B2	10/2018	Al-Ali et al.	2004/0186357 A1	9/2004	Soderberg et al.
D833,624 S	11/2018	DeJong et al.	2004/0230118 A1	11/2004	Shehada et al.
			2004/0230132 A1	11/2004	Shehada et al.
			2004/0230179 A1	11/2004	Shehada et al.
			2004/0243017 A1	12/2004	Causevic
			2004/0249670 A1	12/2004	Noguchi et al.



(56)

## References Cited

U.S. PATENT DOCUMENTS							
2004/0254431	A1	12/2004	Shehada et al.	2008/0221396	A1	9/2008	Garces et al.
2004/0254432	A1	12/2004	Shehada et al.	2008/0228077	A1	9/2008	Wilk et al.
2004/0267103	A1	12/2004	Li et al.	2008/0275309	A1	11/2008	Stivoric et al.
2005/0020918	A1	1/2005	Wilk et al.	2008/0281167	A1	11/2008	Soderberg et al.
2005/0038332	A1	2/2005	Saidara et al.	2008/0281168	A1	11/2008	Gibson et al.
2005/0038680	A1	2/2005	McMahon	2008/0281181	A1	11/2008	Manziona et al.
2005/0080336	A1	4/2005	Byrd et al.	2008/0287751	A1	11/2008	Stivoric et al.
2005/0096542	A1	5/2005	Weng et al.	2008/0292172	A1	11/2008	Assmann et al.
2005/0113653	A1	5/2005	Fox et al.	2008/0300020	A1	12/2008	Nishizawa et al.
2005/0124864	A1	6/2005	Mack et al.	2008/0319275	A1	12/2008	Chiu et al.
2005/0125256	A1	6/2005	Schoenberg	2008/0319354	A1	12/2008	Bell et al.
2005/0164933	A1	7/2005	Tymianski et al.	2009/0005651	A1	1/2009	Ward et al.
2005/0188083	A1	8/2005	Biondi et al.	2009/0018808	A1	1/2009	Bronstein et al.
2005/0191294	A1	9/2005	Arap et al.	2009/0024008	A1	1/2009	Brunner et al.
2005/0268401	A1	12/2005	Dixon et al.	2009/0043172	A1	2/2009	Zagorchev et al.
2005/0277872	A1	12/2005	Colby, Jr. et al.	2009/0052623	A1	2/2009	Tome et al.
2006/0049936	A1	3/2006	Collins, Jr. et al.	2009/0054735	A1	2/2009	Higgins et al.
2006/0058647	A1	3/2006	Strommer et al.	2009/0062682	A1	3/2009	Bland et al.
2006/0089543	A1	4/2006	Kim et al.	2009/0069642	A1	3/2009	Gao et al.
2006/0094936	A1	5/2006	Russ	2009/0099480	A1	4/2009	Salgo et al.
2006/0149393	A1	7/2006	Calderon	2009/0119330	A1	5/2009	Sampath et al.
2006/0155175	A1	7/2006	Ogino et al.	2009/0119843	A1	5/2009	Rodgers et al.
2006/0161054	A1	7/2006	Reuss et al.	2009/0124867	A1	5/2009	Hirsch et al.
2006/0217684	A1	9/2006	Shehada et al.	2009/0131759	A1	5/2009	Sims et al.
2006/0217685	A1	9/2006	Shehada et al.	2009/0143832	A1	6/2009	Saba
2006/0224413	A1	10/2006	Kim et al.	2009/0157058	A1	6/2009	Ferren et al.
2006/0235300	A1	10/2006	Weng et al.	2009/0171170	A1	7/2009	Li et al.
2006/0253042	A1	11/2006	Stahmann et al.	2009/0171225	A1	7/2009	Gadodia et al.
2007/0000490	A1	1/2007	DeVries et al.	2009/0177090	A1	7/2009	Grunwald et al.
2007/0002533	A1	1/2007	Kogan et al.	2009/0182287	A1	7/2009	Kassab
2007/0021675	A1	1/2007	Childre et al.	2009/0226372	A1	9/2009	Ruoslahti et al.
2007/0027368	A1	2/2007	Collins et al.	2009/0247984	A1	10/2009	Lamego et al.
2007/0032733	A1	2/2007	Burton et al.	2009/0264778	A1	10/2009	Markowitz et al.
2007/0055116	A1	3/2007	Clark et al.	2009/0275813	A1	11/2009	Davis
2007/0055544	A1	3/2007	Jung et al.	2009/0275844	A1	11/2009	Al-Ali
2007/0060798	A1	3/2007	Krupnik et al.	2009/0281462	A1	11/2009	Heliot et al.
2007/0088406	A1	4/2007	Bennett et al.	2009/0299157	A1	12/2009	Telfort et al.
2007/0096897	A1	5/2007	Weiner	2009/0309755	A1	12/2009	Williamson et al.
2007/0100222	A1	5/2007	Mastrototaro et al.	2009/0322540	A1	12/2009	Richardson et al.
2007/0118399	A1	5/2007	Avinash et al.	2010/0004518	A1	1/2010	Vo et al.
2007/0140475	A1	6/2007	Kurtock et al.	2010/0030040	A1	2/2010	Poeze et al.
2007/0156033	A1	7/2007	Causey et al.	2010/0030094	A1	2/2010	Lundback
2007/0157285	A1	7/2007	Frank et al.	2010/0036209	A1	2/2010	Ferren et al.
2007/0159332	A1	7/2007	Koblasz	2010/0060747	A1	3/2010	Woodman
2007/0163589	A1	7/2007	DeVries et al.	2010/0069725	A1	3/2010	Al-Ali
2007/0180140	A1	8/2007	Welch et al.	2010/0081895	A1	4/2010	Zand
2007/0185390	A1	8/2007	Perkins et al.	2010/0125217	A1	5/2010	Kuo et al.
2007/0232941	A1	10/2007	Rabinovich	2010/0144627	A1	6/2010	Vitek et al.
2007/0244724	A1	10/2007	Pendergast et al.	2010/0145146	A1	6/2010	Melder
2007/0254593	A1	11/2007	Jollota et al.	2010/0177100	A1	7/2010	Carnes et al.
2007/0255114	A1	11/2007	Ackermann et al.	2010/0185101	A1	7/2010	Sakai et al.
2007/0255116	A1	11/2007	Mehta et al.	2010/0198622	A1	8/2010	Gajic et al.
2007/0255250	A1	11/2007	Moberg et al.	2010/0210958	A1	8/2010	Manwaring et al.
2007/0282478	A1	12/2007	Al-Ali et al.	2010/0240945	A1	9/2010	Bikko
2008/0000479	A1	1/2008	Elaz et al.	2010/0249540	A1	9/2010	Lisogurski
2008/0003200	A1	1/2008	Arap et al.	2010/0298659	A1	11/2010	McCombie et al.
2008/0021854	A1	1/2008	Jung et al.	2010/0298661	A1	11/2010	McCombie et al.
2008/0033661	A1	2/2008	Syroid et al.	2010/0298742	A1	11/2010	Perlman et al.
2008/0039701	A1	2/2008	Ali et al.	2010/0305412	A1	12/2010	Darrah et al.
2008/0053438	A1	3/2008	DeVries et al.	2010/0312103	A1	12/2010	Gorek et al.
2008/0058657	A1	3/2008	Schwartz et al.	2010/0317936	A1	12/2010	Al-Ali et al.
2008/0090626	A1	4/2008	Griffin et al.	2010/0317951	A1	12/2010	Rutkowski et al.
2008/0091089	A1	4/2008	Guillory et al.	2011/0021930	A1	1/2011	Mazzeo et al.
2008/0091090	A1	4/2008	Guillory et al.	2011/0023130	A1	1/2011	Gudgel et al.
2008/0091471	A1	4/2008	Michon et al.	2011/0028809	A1	2/2011	Goodman
2008/0097167	A1	4/2008	Yudkovitch et al.	2011/0046495	A1	2/2011	Osympka
2008/0099366	A1	5/2008	Niemiec et al.	2011/0066051	A1	3/2011	Moon et al.
2008/0119412	A1	5/2008	Tymianski et al.	2011/0077473	A1	3/2011	Lisogurski
2008/0138278	A1	6/2008	Scherz et al.	2011/0078596	A1	3/2011	Rawlins et al.
2008/0169922	A1	7/2008	Issokson	2011/0080294	A1	4/2011	Tanishima et al.
2008/0171919	A1	7/2008	Stivoric et al.	2011/0082711	A1	4/2011	Poeze et al.
2008/0188795	A1	8/2008	Katz et al.	2011/0087083	A1	4/2011	Poeze et al.
2008/0194918	A1	8/2008	Kulik et al.	2011/0087084	A1	4/2011	Jeong et al.
2008/0208912	A1	8/2008	Garibaldi	2011/0087117	A1	4/2011	Tremper et al.
2008/0215627	A1	9/2008	Higgins et al.	2011/0087756	A1	4/2011	Biondi
				2011/0098583	A1	4/2011	Pandia et al.
				2011/0105854	A1	5/2011	Kiani et al.
				2011/0105956	A1	5/2011	Hirth
				2011/0118573	A1	5/2011	Mckenna

(56)

## References Cited

U.S. PATENT DOCUMENTS			
2011/0125060	A1	5/2011	Telfort et al.
2011/0152629	A1	6/2011	Eaton et al.
2011/0172967	A1	7/2011	Al-Ali et al.
2011/0184252	A1	7/2011	Archer et al.
2011/0184253	A1	7/2011	Archer et al.
2011/0208015	A1	8/2011	Welch et al.
2011/0208018	A1	8/2011	Kiani
2011/0208073	A1	8/2011	Matsukawa et al.
2011/0209915	A1	9/2011	Telfort et al.
2011/0212090	A1	9/2011	Pedersen et al.
2011/0213212	A1	9/2011	Al-Ali
2011/0227739	A1	9/2011	Gilham et al.
2011/0230733	A1	9/2011	Al-Ali
2011/0237911	A1	9/2011	Lamego et al.
2011/0237969	A1	9/2011	Eckerbom et al.
2011/0257544	A1	10/2011	Kaasinenet et al.
2011/0263950	A1	10/2011	Larson et al.
2011/0288383	A1	11/2011	Diab
2011/0295094	A1	12/2011	Doyle et al.
2011/0301444	A1	12/2011	Al-Ali
2011/0307274	A1	12/2011	Thompson et al.
2012/0004579	A1	1/2012	Luo et al.
2012/0029300	A1	2/2012	Paquet
2012/0029879	A1	2/2012	Sing et al.
2012/0041316	A1	2/2012	Al-Ali et al.
2012/0046557	A1	2/2012	Kiani
2012/0059230	A1	3/2012	Teller et al.
2012/0059267	A1	3/2012	Lamego et al.
2012/0071771	A1	3/2012	Behar
2012/0075464	A1	3/2012	Derenne et al.
2012/0088984	A1	4/2012	Al-Ali et al.
2012/0101353	A1	4/2012	Reggiardo et al.
2012/0116175	A1	5/2012	Al-Ali et al.
2012/0123799	A1	5/2012	Nolen et al.
2012/0136221	A1	5/2012	Killen et al.
2012/0165629	A1	6/2012	Merritt et al.
2012/0179006	A1	7/2012	Jansen et al.
2012/0184120	A1	7/2012	Basta et al.
2012/0197619	A1	8/2012	Namer Yelin et al.
2012/0203078	A1	8/2012	Sze et al.
2012/0209082	A1	8/2012	Al-Ali
2012/0209084	A1	8/2012	Olsen et al.
2012/0221634	A1	8/2012	Treu et al.
2012/0226160	A1	9/2012	Kudoh
2012/0227739	A1	9/2012	Kiani
2012/0239434	A1	9/2012	Breslow et al.
2012/0242501	A1	9/2012	Tran et al.
2012/0265039	A1	10/2012	Kiani
2012/0282583	A1	11/2012	Thaler et al.
2012/0283524	A1	11/2012	Kiani et al.
2012/0284053	A1	11/2012	Rosenfeld
2012/0286955	A1	11/2012	Welch et al.
2012/0294801	A1	11/2012	Scherz et al.
2012/0296178	A1	11/2012	Lamego et al.
2012/0302894	A1	11/2012	Diab et al.
2012/0303476	A1	11/2012	Krzyzanowski et al.
2012/0319816	A1	12/2012	Al-Ali
2012/0330112	A1	12/2012	Lamego et al.
2013/0006131	A1	1/2013	Narayan et al.
2013/0006151	A1	1/2013	Main et al.
2013/0023775	A1	1/2013	Lamego et al.
2013/0035603	A1	2/2013	Jarausch et al.
2013/0041591	A1	2/2013	Lamego
2013/0046197	A1	2/2013	Dlugos, Jr. et al.
2013/0046204	A1	2/2013	Lamego et al.
2013/0060108	A1	3/2013	Schurman et al.
2013/0060147	A1	3/2013	Welch et al.
2013/0079610	A1	3/2013	Al-Ali
2013/0092805	A1	4/2013	Funk et al.
2013/0096405	A1	4/2013	Garfio
2013/0096936	A1	4/2013	Sampath et al.
2013/0109929	A1	5/2013	Menzel
2013/0109935	A1	5/2013	Al-Ali et al.
2013/0123616	A1	5/2013	Merritt et al.
2013/0162433	A1	6/2013	Muhsin et al.
2013/0178749	A1	7/2013	Lamego
2013/0190581	A1	7/2013	Al-Ali et al.
2013/0197328	A1	8/2013	Diab et al.
2013/0197364	A1	8/2013	Han
2013/0211214	A1	8/2013	Olsen
2013/0243021	A1	9/2013	Siskavich
2013/0253334	A1	9/2013	Al-Ali et al.
2013/0261494	A1	10/2013	Bloom et al.
2013/0267793	A1	10/2013	Meador et al.
2013/0267804	A1	10/2013	Al-Ali
2013/0274571	A1	10/2013	Diab et al.
2013/0274572	A1	10/2013	Al-Ali et al.
2013/0279109	A1	10/2013	Lindblad et al.
2013/0296672	A1	11/2013	O'Neil et al.
2013/0296713	A1	11/2013	Al-Ali et al.
2013/0317327	A1	11/2013	Al-Ali et al.
2013/0317370	A1	11/2013	Dalvi et al.
2013/0317393	A1	11/2013	Weiss et al.
2013/0324804	A1	12/2013	McKeown et al.
2013/0324808	A1	12/2013	Al-Ali et al.
2013/0324817	A1	12/2013	Diab
2013/0331660	A1	12/2013	Al-Ali et al.
2013/0331670	A1	12/2013	Kiani
2013/0338461	A1	12/2013	Lamego et al.
2013/0340176	A1	12/2013	Stevens et al.
2014/0012100	A1	1/2014	Al-Ali et al.
2014/0022081	A1	1/2014	Ribble et al.
2014/0025306	A1	1/2014	Weber et al.
2014/0031650	A1	1/2014	Weber et al.
2014/0034353	A1	2/2014	Al-Ali et al.
2014/0046674	A1	2/2014	Rosenfeld
2014/0051952	A1	2/2014	Reichgott et al.
2014/0051953	A1	2/2014	Lamego et al.
2014/0051954	A1	2/2014	Al-Ali et al.
2014/0058230	A1	2/2014	Abdul-Hafiz et al.
2014/0066783	A1	3/2014	Kiani et al.
2014/0073167	A1	3/2014	Al-Ali et al.
2014/0077956	A1	3/2014	Sampath et al.
2014/0081097	A1	3/2014	Al-Ali et al.
2014/0081100	A1	3/2014	Muhsin et al.
2014/0081175	A1	3/2014	Telfort
2014/0094667	A1	4/2014	Schurman et al.
2014/0100434	A1	4/2014	Diab et al.
2014/0114199	A1	4/2014	Lamego et al.
2014/0120564	A1	5/2014	Workman et al.
2014/0121482	A1	5/2014	Merritt et al.
2014/0121483	A1	5/2014	Kiani
2014/0127137	A1	5/2014	Bellott et al.
2014/0128696	A1	5/2014	Al-Ali
2014/0128699	A1	5/2014	Al-Ali et al.
2014/0129702	A1	5/2014	Lamego et al.
2014/0135588	A1	5/2014	Al-Ali et al.
2014/0142399	A1	5/2014	Al-Ali et al.
2014/0142401	A1	5/2014	Al-Ali et al.
2014/0142402	A1	5/2014	Al-Ali et al.
2014/0152673	A1	6/2014	Lynn et al.
2014/0155712	A1	6/2014	Lamego et al.
2014/0163344	A1	6/2014	Al-Ali
2014/0163402	A1	6/2014	Lamego et al.
2014/0166076	A1	6/2014	Kiani et al.
2014/0171763	A1	6/2014	Diab
2014/0180038	A1	6/2014	Kiani
2014/0180154	A1	6/2014	Sierra et al.
2014/0180160	A1	6/2014	Brown et al.
2014/0187973	A1	7/2014	Brown et al.
2014/0188516	A1	7/2014	Kamen
2014/0194709	A1	7/2014	Al-Ali et al.
2014/0194711	A1	7/2014	Al-Ali
2014/0194766	A1	7/2014	Al-Ali et al.
2014/0200422	A1	7/2014	Weber et al.
2014/0206963	A1	7/2014	Al-Ali
2014/0213864	A1	7/2014	Abdul-Hafiz et al.
2014/0243627	A1	8/2014	Diab et al.
2014/0257057	A1	9/2014	Reis Cunha et al.
2014/0266787	A1	9/2014	Tran
2014/0266790	A1	9/2014	Al-Ali et al.
2014/0275808	A1	9/2014	Poeze et al.
2014/0275835	A1	9/2014	Lamego et al.
2014/0275871	A1	9/2014	Lamego et al.



(56)

References Cited

U.S. PATENT DOCUMENTS

2018/0069776 A1 3/2018 Lamego et al.  
 2018/0070867 A1 3/2018 Smith et al.  
 2018/0082767 A1 3/2018 Al-Ali et al.  
 2018/0085068 A1 3/2018 Telfort  
 2018/0087937 A1 3/2018 Al-Ali et al.  
 2018/0103874 A1 4/2018 Lee et al.  
 2018/0103905 A1 4/2018 Kiani  
 2018/0110478 A1 4/2018 Al-Ali  
 2018/0116575 A1 5/2018 Perea et al.  
 2018/0125368 A1 5/2018 Lamego et al.  
 2018/0125430 A1 5/2018 Al-Ali et al.  
 2018/0125445 A1 5/2018 Telfort et al.  
 2018/0130325 A1 5/2018 Kiani et al.  
 2018/0132769 A1 5/2018 Weber et al.  
 2018/0132770 A1 5/2018 Lamego  
 2018/0146901 A1 5/2018 Al-Ali et al.  
 2018/0146902 A1 5/2018 Kiani et al.  
 2018/0153442 A1 6/2018 Eckerbom et al.  
 2018/0153446 A1 6/2018 Kiani  
 2018/0153447 A1 6/2018 Al-Ali et al.  
 2018/0153448 A1 6/2018 Weber et al.  
 2018/0161499 A1 6/2018 Al-Ali et al.  
 2018/0168491 A1 6/2018 Al-Ali et al.  
 2018/0174679 A1 6/2018 Sampath et al.  
 2018/0174680 A1 6/2018 Sampath et al.  
 2018/0182484 A1 6/2018 Sampath et al.  
 2018/0184917 A1 7/2018 Kiani  
 2018/0192924 A1 7/2018 Al-Ali  
 2018/0192953 A1 7/2018 Shreim et al.  
 2018/0192955 A1 7/2018 Al-Ali et al.  
 2018/0199871 A1 7/2018 Pauley et al.  
 2018/0206795 A1 7/2018 Al-Ali  
 2018/0206815 A1 7/2018 Telfort  
 2018/0213583 A1 7/2018 Al-Ali  
 2018/0214031 A1 8/2018 Kiani et al.  
 2018/0214090 A1 8/2018 Al-Ali et al.  
 2018/0218792 A1 8/2018 Muhsin et al.  
 2018/0225960 A1 8/2018 Al-Ali et al.  
 2018/0238718 A1 8/2018 Dalvi  
 2018/0242853 A1 8/2018 Al-Ali  
 2018/0242923 A1 8/2018 Al-Ali et al.  
 2018/0242924 A1 8/2018 Barker et al.  
 2018/0242926 A1 8/2018 Muhsin et al.  
 2018/0247353 A1 8/2018 Al-Ali et al.  
 2018/0247712 A1 8/2018 Muhsin et al.  
 2018/0249933 A1 9/2018 Schurman et al.  
 2018/0253947 A1 9/2018 Muhsin et al.  
 2018/0256087 A1 9/2018 Al-Ali et al.  
 2018/0256113 A1 9/2018 Weber et al.  
 2018/0285094 A1 10/2018 Housel et al.  
 2018/0289325 A1 10/2018 Poeze et al.  
 2018/0289337 A1 10/2018 Al-Ali et al.  
 2018/0296161 A1 10/2018 Shreim et al.  
 2018/0300919 A1 10/2018 Muhsin et al.  
 2018/0310822 A1 11/2018 Indorf et al.  
 2018/0310823 A1 11/2018 Al-Ali et al.  
 2018/0317826 A1 11/2018 Muhsin  
 2018/0317841 A1 11/2018 Novak, Jr.  
 2018/0333055 A1 11/2018 Lamego et al.  
 2018/0333087 A1 11/2018 Al-Ali  
 2019/0000317 A1 1/2019 Muhsin et al.  
 2019/0000362 A1 1/2019 Kiani et al.  
 2019/0015023 A1 1/2019 Monfre  
 2019/0021638 A1 1/2019 Al-Ali et al.  
 2019/0029574 A1 1/2019 Schurman et al.  
 2019/0029578 A1 1/2019 Al-Ali et al.  
 2019/0058280 A1 2/2019 Al-Ali et al.  
 2019/0058281 A1 2/2019 Al-Ali et al.  
 2019/0069813 A1 3/2019 Al-Ali  
 2019/0069814 A1 3/2019 Al-Ali  
 2019/0076028 A1 3/2019 Al-Ali et al.  
 2019/0082979 A1 3/2019 Al-Ali et al.  
 2019/0090760 A1 3/2019 Kinast et al.  
 2019/0090764 A1 3/2019 Al-Ali  
 2019/0104973 A1 4/2019 Poeze et al.

2019/0110719 A1 4/2019 Poeze et al.  
 2019/0117070 A1 4/2019 Muhsin et al.  
 2019/0117139 A1 4/2019 Al-Ali et al.  
 2019/0117140 A1 4/2019 Al-Ali et al.  
 2019/0117141 A1 4/2019 Al-Ali  
 2019/0117930 A1 4/2019 Al-Ali  
 2019/0122763 A1 4/2019 Sampath et al.  
 2019/0133525 A1 5/2019 Al-Ali et al.  
 2019/0142283 A1 5/2019 Lamego et al.  
 2019/0142344 A1 5/2019 Telfort et al.  
 2019/0150856 A1 5/2019 Kiani et al.  
 2019/0167161 A1 6/2019 Al-Ali et al.  
 2019/0175019 A1 6/2019 Al-Ali et al.  
 2019/0192076 A1 6/2019 McHale et al.

FOREIGN PATENT DOCUMENTS

JP 02-050694 2/1990  
 JP 09-187428 7/1997  
 JP 10-336064 12/1998  
 JP 2000-312668 11/2000  
 JP 2002-513602 5/2002  
 JP 2002-165764 6/2002  
 JP 2002-172096 6/2002  
 JP 2002-233512 8/2002  
 JP 2002-535026 10/2002  
 JP 2002-542493 12/2002  
 JP 2004-513732 5/2004  
 JP 2005-038417 2/2005  
 JP 2005-218036 8/2005  
 JP 2005-295375 10/2005  
 JP 2007-021213 2/2007  
 JP 2007-095365 4/2007  
 JP 2007-174051 7/2007  
 JP 2008-519635 6/2008  
 JP 2008-541045 11/2008  
 JP 2009-017959 1/2009  
 JP 2009-207836 9/2009  
 JP 2010-503134 1/2010  
 JP 2010-093543 4/2010  
 JP 2010-524510 7/2010  
 JP 2011-519607 7/2011  
 JP 2011-519684 7/2011  
 JP 2011-152261 8/2011  
 JP 2012-519547 8/2012  
 WO WO 98/029790 7/1998  
 WO WO 99/013766 3/1999  
 WO WO 99/056613 11/1999  
 WO WO 00/063713 10/2000  
 WO WO 2004/056266 7/2004  
 WO WO 2004/059551 7/2004  
 WO WO 2006/051461 5/2006  
 WO WO 2010/054409 5/2010  
 WO WO 2011/001302 1/2011  
 WO WO 2011/002904 1/2011  
 WO WO 2011/021948 2/2011  
 WO WO 2011/025549 3/2011  
 WO WO 2011/041017 4/2011  
 WO WO 2013/056160 4/2013  
 WO WO 2013/119982 8/2013  
 WO WO 2015/054665 4/2015

OTHER PUBLICATIONS

U.S. Appl. No. 15/448,989, Arm Mountable Portable Patient Monitor, filed Mar. 3, 2017.  
 U.S. Appl. No. 16/157,643, Physiological Measurement Device, filed Oct. 11, 2018.  
 U.S. Appl. No. 16/198,057, Physiological Measurement Device, filed Nov. 21, 2018.  
 U.S. Appl. No. 15/814,227, Modular Patient Monitor, filed Nov. 15, 2017.  
 U.S. Appl. No. 14/834,169, Wireless Patient Monitoring Device, filed Aug. 24, 2015.  
 International Search Report & Written Opinion in PCT Application No. PCT/US2013/025384, dated Aug. 6, 2013.

(56)

**References Cited**

## OTHER PUBLICATIONS

International Preliminary Report on Patentability & Written Opinion in PCT Application No. PCT/US2013/025384, dated Aug. 21, 2014.

International Search Report & Written Opinion in PCT Application No. PCT/US2012/060109, dated Jun. 5, 2013.

International Preliminary Report on Patentability in PCT Application No. PCT/US2012/060109, dated Apr. 24, 2014.

International Search Report & Written Opinion in PCT Application No. PCT/US2014/060177, dated Dec. 19, 2014.

International Preliminary Report on Patentability & Written Opinion in PCT Application No. PCT/US2014/060177, dated Apr. 21, 2016.

U.S. Appl. No. 13/762,270, Wireless Patient Monitoring Device, filed Feb. 7, 2013.

U.S. Appl. No. 15/214,156, Medical Monitoring Hub, filed Jul. 19, 2016.

U.S. Appl. No. 15/214,186, Medical Monitoring Hub, filed Jul. 19, 2016.

U.S. Appl. No. 14/512,237, System for Displaying Medical Monitoring Data, filed Oct. 10, 2014.

U.S. Appl. No. 14/511,972, Alarm Notification System, filed Oct. 10, 2014.

Capuano et al., "Remote Telemetry—New Twists for Old Technology", *Nursing Management*, Jul. 1995, vol. 26, No. 7, pp. 26-32.

Elmer-Dewitt, Philip, "Apple's iWatch: The killer apps may be in hospitals, not health clubs", *Fortune.com*, Feb. 3, 2014, <http://fortune.com/2014/02/03/apples-iwatch-the-killer-apps-may-be-in-hospitals-not-health-clubs/>, 4 pages.

Grundy et al., "Telemedicine in Critical Care: An Experiment in Health Care Delivery", *JACEP*, Oct. 1977, vol. 6, No. 10, pp. 439-444.

Grundy et al., "Telemedicine in Critical Care: Problems in Design, Implementation and Assessment", Jul. 1982, vol. 10, No. 7, pp. 471-475.

Rysavy, Peter, "Making the Call with Two-Way Paging", *Network Computing*, Published Jan. 15, 1997, [www.rysavy.com/Articles/twoway.htm](http://www.rysavy.com/Articles/twoway.htm), pp. 5.

Wachter et al., "The Employment of an Iterative Design Process to Develop a Pulmonary Graphical Display", *Journal of the American Medical Informatics Association*, vol. 10, No. 4, Jul./Aug. 2003, pp. 363-372.

U.S. Pat. No. 6,850,788, Physiological Measurement Communications Adapter, Feb. 1, 2005.

U.S. Pat. No. 7,844,314, Physiological Measurement Communications Adapter, Nov. 30, 2010.

U.S. Pat. No. 7,844,315, Physiological Measurement Communications Adapter, Nov. 30, 2010.

U.S. Pat. No. 8,548,548, Physiological Measurement Communications Adapter, Oct. 1, 2013.

U.S. Pat. No. 9,113,831, Physiological Measurement Communications Adapter, Aug. 25, 2015.

U.S. Pat. No. 9,113,832, Wrist-Mounted Physiological Measurement Device, Aug. 25, 2015.

U.S. Pat. No. 10,213,108, Arm Mountable Portable Patient Monitor, Feb. 26, 2019.

U.S. Pat. No. 9,872,623, Arm Mountable Portable Patient Monitor, Jan. 23, 2018.

U.S. Pat. No. 9,788,735, Body Worn Mobile Medical Patient Monitor, Oct. 17, 2017.

U.S. Pat. No. 9,795,300, Wearable Portable Patient Monitor, Oct. 24, 2017.

U.S. Pat. No. 10,219,706, Physiological Measurement Device, Mar. 5, 2019.

U.S. Pat. No. 10,335,033, Physiological Measurement Device, Jul. 2, 2019.

U.S. Pat. No. 8,840,549, Modular Patient Monitor, Sep. 23, 2014.

U.S. Pat. No. 9,161,696, Modular Patient Monitor, Oct. 20, 2015.

U.S. Pat. No. 9,153,112, Modular Patient Monitor, Oct. 6, 2015.

U.S. Pat. No. 9,847,002, Modular Patient Monitor, Dec. 19, 2017.

U.S. Pat. No. 10,354,504, Modular Patient Monitor, Jul. 16, 2019.

U.S. Pat. No. 10,149,616, Wireless Patient Monitoring Device, Dec. 11, 2018.

U.S. Pat. No. 10,188,296, Wireless Patient Monitoring Device, Jan. 29, 2019.

U.S. Pat. No. D. 788,312, Wireless Patient Monitoring Device, May 30, 2017.

U.S. Pat. No. 9,436,645, Medical Monitoring Hub, Sep. 6, 2016.

U.S. Pat. No. 9,993,207, Medical Monitoring Hub, Jun. 12, 2018.

U.S. Pat. No. 9,913,617, Medical Monitoring Hub, Mar. 13, 2018.

U.S. Pat. No. 9,943,269, System for Displaying Medical Monitoring Data, Apr. 17, 2018.

U.S. Appl. No. 14/815,232, Physiological Measurement Communications Adapter, filed Jul. 31, 2015.

U.S. Appl. No. 15/878,172, Arm Mountable Portable Patient Monitor, filed Jan. 23, 2018.

U.S. Appl. No. 16/411,689, Physiological Measurement Device, filed May 14, 2019.

U.S. Appl. No. 14/464,560, Modular Patient Monitor, filed Aug. 20, 2014.

U.S. Appl. No. 12/973,392, Modular Patient Monitor, filed Dec. 20, 2010.

U.S. Appl. No. 16/432,240, Modular Patient Monitor, filed Jun. 5, 2019.

U.S. Appl. No. 16/182,427, Wireless Patient Monitoring Device, filed Nov. 6, 2018.

U.S. Appl. No. 16/182,457, Wireless Patient Monitoring Device, filed Nov. 6, 2018.

U.S. Appl. No. 15/968,392, Medical Monitoring Hub, filed May 1, 2018.

U.S. Appl. No. 15/214,276, Medical Monitoring Hub, filed Jul. 19, 2016.

U.S. Appl. No. 15/919,792, System for Displaying Medical Monitoring Data, filed Mar. 3, 2018.




FIG. 1A




FIG. 1B




FIG. 1C






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

700




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10






FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 11E





FIG. 11F






FIG. 11G2

SECTION A-A





FIG. 11H



EPROM




FIG. 11J




FIG. 11I




FIG. 11K




FIG. 12




FIG. 13




FIG. 14






FIG. 15




FIG. 16




FIG. 17A




FIG. 17B




FIG. 18




FIG. 19A




FIG. 19B




FIG. 19C






FIG. 19D




FIG. 19E




FIG. 19F




FIG. 19G




FIG. 19H




FIG. 19I




FIG. 19J




FIG. 20A






FIG. 20B




FIG. 20C




FIG. 21A




FIG. 21B




FIG. 22A




FIG. 22B




FIG. 23A




FIG. 23B




FIG. 23C






FIG. 23D




FIG. 23E




FIG. 23F





FIG. 24






FIG. 26




FIG. 27




FIG. 28






FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36







FIG. 37



2210

FIG. 38




FIG. 39




FIG. 40A




FIG. 40B



```
<?xml version="1.0" encoding="UTF-8" standalone="no" ?>
<ev7>
  <MSH>
    <MSH.1>^</MSH.1>
    <MSH.2>~ | \ & amp; </MSH.2>
    <MSH.3>VAFC PIMS</MSH.3>
    <MSH.4>50</MSH.4>
    <MSH.5>NPTF-508</MSH.5>
    <MSH.6>200</MSH.6>
    <MSH.7>20091120104609-0600</MSH.7>
    <MSH.9>
      <component n="1">ADT</component>
      <component n="2">ADT</component>
    <MSH.9>
    <MSH.10>58103</MSH.10>
    <MSH.11>P</MSH.11>
    <MSH.17>USA</MSH.17>
  </MSH>
  <EVN>
    <EVN.1>A01</EVN.1>
    <EVN.2>20091120104517-0600</EVN.2>
    <EVN.4>05</EVN.4>
  </EVN>
  ...
</ev7>
```

FIG. 41B

```
<?xml version="1.0" encoding="UTF-8"?>
<ADT_A01>
  <MSH>
    <MSH.1>^</MSH.1>
    <MSH.2>~ |\&amp;</MSH.2>
    <MSH.3>
      <HD.1>VAFC PIMS</HD.1>
    </MSH.3>
    <MSH.4>
      <HD.1>50</HD.1>
    </MSH.4>
    <MSH.5>
      <HD.1>NPTF-508</HD.1>
    </MSH.5>
    <MSH.6>
      <HD.1>200</HD.1>
    </MSH.6>
    <MSH.7>
      <TS.1>20091120104609-0600</TS.1>
    </MSH.7>
    <MSH.9>
      <MSG.1>ADT</MSG.1>
      <MSG.2>A01</MSG.2>
    </MSH.9>
    <MSH.10>58103</MSH.10>
    <MSH.11>
      <PT.1>P</PT.1>
    </MSH.11>
    <MSH.17>USA</MSH.17>
  </MSH>
```

FIG. 41C



```
<output-message>
  <ACK>
    <MSH>
      <MSH.1>^</MSH.1>
      <MSH.2>~|\&amp;lt;&lt;/MSH.2>
      <MSH.3>
        <HD.1>NPTF-508</HD.1>
      </MSH.3>
      <MSH.4>
        <HD.1>200</HD.1>
      </MSH.4>
      <MSH.5>
        <HD.1>VAFC PIMS</HD.1>
      </MSH.5>
      <MSH.6>
        <HD.1>50</HD.1>
      </MSH.6>
      <MSH.7>
        <TS.1>20091120104609-0600</TS.1>
      </MSH.7>
      <MSH.9>
        <MSG.1>ACK</MSG.1>
        <MSG.3>ACK</MSG.2>
      </MSH.9>
      <MSH.10>856bc9bd-97c8-4aa5-b411-3cd6fe2edd86</MSH.10>
    <MSH>
    <MSA>
      <MSA.1>AA</MSA.1>
      <MSA.2>58103</MSA.2>
    </MSA>
  </ACK>
</output-message>
```

FIG. 41D




FIG. 42




FIG. 43A





FIG. 43B



2800

FIG. 44




FIG. 45A




FIG. 45B




FIG. 45C




FIG. 45D




FIG. 46




FIG. 47






FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55






FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63






FIG. 64




FIG. 65




FIG. 66




FIG. 67




FIG. 68




FIG. 69




FIG. 70




FIG. 71



## SYSTEM FOR DISPLAYING MEDICAL MONITORING DATA

### RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 14/512,237, filed Oct. 10, 2014, titled "System for Displaying Medical Monitoring Data," which application is a non-provisional of U.S. Provisional Application No. 61/889,972, filed Oct. 11, 2013, titled "System for Displaying Medical Monitoring Data," and is also a continuation-in-part of U.S. application Ser. No. 13/651,167, filed Oct. 12, 2012, titled "Medical Monitoring Hub," which is a non-provisional of each of the following U.S. Provisional Patent Applications:

Ser. No.	Date	Title
61/547,017,	Oct. 13, 2011,	Visual Correlation of Physiological Information,
61/547,577,	Oct. 14, 2011,	Visual Correlation of Physiological Information,
61/597,120,	Feb. 9, 2012,	Visual Correlation of Physiological Information,
61/703,773,	Sep. 20, 2012,	Medical Monitoring Hub

All of the above applications are incorporated by reference herein in their entirety.

### FIELD OF THE DISCLOSURE

The present disclosure relates generally to patient monitoring devices and specifically to a patient monitor and medical data communication hub.

### BACKGROUND OF THE DISCLOSURE

Today's patient monitoring environments are crowded with sophisticated and often electronic medical devices servicing a wide variety of monitoring and treatment endeavors for a given patient. Generally, many if not all of the devices are from differing manufactures, and many may be portable devices. The devices may not communicate with one another and each may include its own control, display, alarms, configurations and the like. Complicating matters, caregivers often desire to associate all types of measurement and use data from these devices to a specific patient. Thus, patient information entry often occurs at each device. Sometimes, the disparity in devices leads to a need to simply print and store paper from each device in a patient's file for caregiver review.

The result of such device disparity is often a caregiver environment scattered with multiple displays and alarms leading to a potentially chaotic experience. Such chaos can be detrimental to the patient in many situations including surgical environments where caregiver distraction is unwanted, and including recovery or monitoring environments where patient distraction or disturbance may be unwanted.

Various manufacturers produce multi-monitor devices or devices that modularly expand to increase the variety of monitoring or treatment endeavors a particular system can accomplish. However, as medical device technology expands, such multi-monitor devices begin to be obsolete the moment they are installed.

### SUMMARY

This disclosure describes embodiments of a medical monitoring hub as the center of monitoring for a monitored

patient. The hub can include configurable medical ports and serial ports for communicating with other medical devices in the patient's proximity. Moreover, the hub can communicate with a portable patient monitor. The monitor, when docked with the hub, may provide display graphics different from when undocked. The display graphics can include anatomical information. The hub can assemble the often vast amount of electronic medical data, associate it with the monitored patient, and in some embodiments, communicate the data to the patient's medical records.

Some aspects of the disclosure describe a first medical device having digital logic circuitry receives a physiological signal associated with a patient from a physiological sensor, obtains a first physiological parameter value based on the physiological signal, and outputs the first physiological parameter value for display. The first medical device can also receive a second physiological parameter value from a second medical device other than the first medical device, where the second physiological parameter value is formatted according to a protocol not used by the first medical device, such that the first medical device is not able to process the second physiological parameter value to produce a displayable output value. The first medical device can pass the physiological parameter data from the first medical device to a separate translation module, receive translated parameter data from the translation module at the first medical device, where the translated parameter data is able to be processed for display by the first medical device, and output a second value from the translated parameter data for display. The first medical device may be, for example, a monitoring hub, a portable physiological monitor, or a multi-patient monitoring system, and the second medical device may be an infusion pump, ventilator, or the like.

For purposes of summarizing the disclosure, certain aspects, advantages and novel features are discussed herein. It is to be understood that not necessarily all such aspects, advantages or features will be embodied in any particular embodiment of the invention and an artisan would recognize from the disclosure herein a myriad of combinations of such aspects, advantages or features.

### BRIEF DESCRIPTION OF THE DRAWINGS

The following drawings and the associated descriptions are provided to illustrate embodiments of the present disclosure and do not limit the scope of the claims.

FIGS. 1A-1C illustrate perspective views of an exemplary medical monitoring hub according to an embodiment of the disclosure. For example, FIG. 1A illustrates the hub with an exemplary docked portable patient monitor, FIG. 1B illustrates the hub with a set of medical ports and a noninvasive blood pressure input, and FIG. 1C illustrates the hub with various exemplary temperature sensors attached thereto, all according to various embodiments of the disclosure.

FIG. 2 illustrates a simplified block diagram of an exemplary monitoring environment including the hub of FIG. 1, according to an embodiment of the disclosure.

FIG. 3 illustrates a simplified exemplary hardware block diagram of the hub of FIG. 1, according to an embodiment of the disclosure.

FIG. 4 illustrates a perspective view of an exemplary removable docking station of the hub of FIG. 1, according to an embodiment of the disclosure.

FIG. 5 illustrates a perspective view of exemplary portable patient monitors undocked from the hub of FIG. 1, according to an embodiment of the disclosure. Moreover, FIG. 5 illustrates an exemplary alternative docking station.

FIG. 6 illustrates a simplified block diagram of traditional patient device electrical isolation principles.

FIG. 7A illustrates a simplified block diagram of an exemplary optional patient device isolation system according to an embodiment of the disclosure, while FIG. 7B adds exemplary optional non-isolation power levels for the system of FIG. 7A, also according to an embodiment of the disclosure.

FIG. 8 illustrates a simplified exemplary universal medical connector configuration process, according to an embodiment of the disclosure.

FIGS. 9A-9B, 10, 11A-11F, 11G1-11G2, and 11H-11K illustrate simplified block diagrams of exemplary universal medical connectors having a size and shape smaller in cross section than traditional isolation requirements.

FIG. 10 illustrates a perspective view of a side of the hub of FIG. 1, showing exemplary instrument-side channel inputs for exemplary universal medical connectors, according to an embodiment of the disclosure.

FIGS. 11A-11F, 11G1-11G2, and 11H-11K illustrate various views of exemplary male and mating female universal medical connectors, according to embodiments of the disclosure.

FIG. 12 illustrates a simplified block diagram of a channel system for the hub of FIG. 1, according to an embodiment of the disclosure.

FIG. 13 illustrates an exemplary logical channel configuration, according to an embodiment of the disclosure.

FIG. 14 illustrates a simplified exemplary process for constructing a cable and configuring a channel according to an embodiment of the disclosure.

FIG. 15 illustrates a perspective view of the hub of FIG. 1, including an exemplary attached board-in-cable to form an input channel, according to an embodiment of the disclosure.

FIG. 16 illustrates a perspective view of a back side of the hub of FIG. 1, showing an exemplary instrument-side serial data inputs, according to an embodiment of the disclosure.

FIG. 17A illustrates an exemplary monitoring environment with communication through the serial data connections of FIG. 16, according to embodiments of the disclosure.

FIG. 17B illustrates an exemplary connectivity display of the hub of FIG. 1, according to embodiments of the disclosure.

FIG. 18 illustrates a simplified exemplary patient data flow process, according to an embodiment of the disclosure.

FIGS. 19A-19J illustrate exemplary displays of anatomical graphics for the portable patient monitor of FIG. 1 docked with the hub of FIG. 1, according to embodiments of the disclosure.

FIGS. 20A-20C illustrate exemplary displays of measurement data showing data separation and data overlap on a display of the hub of FIG. 1, respectively, according to embodiments of the disclosure.

FIGS. 21A and 21B illustrate exemplary displays of measurement data showing data separation and data overlap on a display of the portable patient monitor of FIG. 1, respectively, according to embodiments of the disclosure.

FIGS. 22A and 22B illustrate exemplary analog display indicia according to an embodiment of the disclosure.

FIGS. 23A-23F illustrate exemplary displays of measurement data showing, for example, data presentation in FIGS. 23A-23D when a depth of consciousness monitor is connected to a channel port of the hub of FIG. 1, data presentation in FIG. 23E when temperature and blood pressure sensors communicate with the hub of FIG. 1 and data

presentation in FIG. 23F when an acoustic sensor is also communicating with the hub of FIG. 1, according to embodiments of the disclosure.

FIG. 24 illustrates another embodiment of a monitoring environment including the hub of FIG. 1.

FIG. 25 illustrates an embodiment of a translation message handling process.

FIGS. 26-39 illustrate additional example hub displays, including displays of measurement data.

FIG. 40A illustrates an example first medical device and an example second medical device that communicate with one another via a translation module.

FIG. 40B illustrates an example first medical device and an example second medical device that communicate with one another via a translation module and a communication bus.

FIG. 41A illustrates an example input message received by the translation module.

FIG. 41B illustrates an example message header segment of an input message that has been parsed into fields.

FIG. 41C illustrates an example encoded version of the parsed message header segment of FIG. 41B.

FIG. 41D illustrates an example output message of the translation module based on the input message of FIG. 41A.

FIG. 42 illustrates an example translation process for generating an output message based on an input message and a comparison with translation rules associated with the translation module.

FIG. 43A illustrates an example translation process in which the translation module facilitates communication of an HL7 message from a Hospital Information System ("HIS") having a first HL7 format to an intended recipient medical device having a second HL7 format.

FIG. 43B illustrates an example translation process in which the translation module facilitates communication of an HL7 message from a medical device having a first HL7 format to a HIS having a second HL7 format.

FIG. 44 illustrates an example screenshot from a messaging implementation tool for manually configuring translation rules to be used by the translation module.

FIGS. 45A and 45B illustrate example automatic rule configuration processes that can be performed by the translation module.

FIGS. 45C and 45D illustrate example automatic rule configuration processes that can be performed by the translation module for messages utilizing the HL7 protocol.

FIGS. 46-71 illustrate additional example hub displays, including displays of measurement data.

While the foregoing "Brief Description of the Drawings" references generally various embodiments of the disclosure, an artisan will recognize from the disclosure herein that such embodiments are not mutually exclusive. Rather, the artisan would recognize a myriad of combinations of some or all of such embodiments.

## DETAILED DESCRIPTION

### I. Introduction

Based on at least the foregoing, a solution is needed that coordinates the various medical devices treating or monitoring a patient. Embodiments of such a solution should provide patient identification seamlessly across the device space and embodiments of such a solution should expand for future technologies without necessarily requiring repeated software upgrades. In addition, embodiments of such a solution may include patient electrical isolation where desired.

## 5

Therefore, the present disclosure relates to a patient monitoring hub that is the center of patient monitoring and treatment activities for a given patient. Embodiments of the patient monitoring hub interface with legacy devices without necessitating legacy reprogramming, provide flexibility for interfacing with future devices without necessitating software upgrades, and offer optional patient electrical isolation. In an embodiment, the hub includes a large display dynamically providing information to a caregiver about a wide variety of measurement or otherwise determined parameters. Additionally, in an embodiment, the hub includes a docking station for a portable patient monitor. The portable patient monitor may communicate with the hub through the docking station or through various wireless paradigms known to an artisan from the disclosure herein, including WiFi, Bluetooth, Zigbee, or the like.

In still other embodiments, the portable patient monitor modifies its screen when docked. The undocked display indicia is in part or in whole transferred to a large dynamic display of the hub and the docked display presents one or more anatomical graphics of monitored body parts. For example, the display may present a heart, lungs, a brain, kidneys, intestines, a stomach, other organs, digits, gastrointestinal systems or other body parts when it is docked. In an embodiment, the anatomical graphics may advantageously be animated. In an embodiment, the animation may generally follow the behavior of measured parameters, such as, for example, the lungs may inflate in approximate correlation to the measured respiration rate and/or the determined inspiration portion of a respiration cycle, and likewise deflate according to the expiration portion of the same. The heart may beat according to the pulse rate, may beat generally along understood actual heart contraction patterns, and the like. Moreover, in an embodiment, when the measured parameters indicate a need to alert a caregiver, a changing severity in color may be associated with one or more displayed graphics, such as the heart, lungs, brain, or the like. In still other embodiments, the body portions may include animations on where, when or how to attach measurement devices to measurement sites on the patient. For example, the monitor may provide animated directions for CCHD screening procedures or glucose strip reading protocols, the application of a forehead sensor, a finger or toe sensor, one or more electrodes, an acoustic sensor, and ear sensor, a cannula sensor or the like.

The present disclosure relates to a medical monitoring hub configured to be the center of monitoring activity for a given patient. In an embodiment, the hub comprises a large easily readable display, such as an about ten (10) inch display dominating the majority of real estate on a front face of the hub. The display could be much larger or much smaller depending upon design constraints. However, for portability and current design goals, the preferred display is roughly sized proportional to the vertical footprint of one of the dockable portable patient monitors. Other considerations are recognizable from the disclosure herein by those in the art.

The display provides measurement data for a wide variety of monitored parameters for the patient under observation in numerical or graphic form, and in various embodiments, is automatically configured based on the type of data and information being received at the hub. In an embodiment, the hub is moveable, portable, and mountable so that it can be positioned to convenient areas within a caregiver environment. For example, the hub is collected within a singular housing.

## 6

In an embodiment, the hub may advantageously receive data from a portable patient monitor while docked or undocked from the hub. Typical portable patient monitors, such as oximeters or co-oximeters can provide measurement data for a large number of physiological parameters derived from signals output from optical and/or acoustic sensors, electrodes, or the like. The physiological parameters include, but not limited to oxygen saturation, carboxy hemoglobin, methemoglobin, total hemoglobin, glucose, pH, bilirubin, fractional saturation, pulse rate, respiration rate, components of a respiration cycle, indications of perfusion including perfusion index, signal quality and/or confidences, plethysmograph data, indications of wellness or wellness indexes or other combinations of measurement data, audio information responsive to respiration, ailment identification or diagnosis, blood pressure, patient and/or measurement site temperature, depth of sedation, organ or brain oxygenation, hydration, measurements responsive to metabolism, combinations of the same or the like, to name a few. In other embodiments, the hub may output data sufficient to accomplish closed-loop drug administration in combination with infusion pumps or the like.

In an embodiment, the hub communicates with other devices in a monitoring environment that are interacting with the patient in a number of ways. For example, the hub advantageously receives serial data from other devices without necessitating their reprogramming or that of the hub. Such other devices include pumps, ventilators, all manner of monitors monitoring any combination of the foregoing parameters, ECG/EEG/EKG devices, electronic patient beds, and the like. Moreover, the hub advantageously receives channel data from other medical devices without necessitating their reprogramming or that of the hub. When a device communicates through channel data, the hub may advantageously alter the large display to include measurement information from that device. Additionally, the hub accesses nurse call systems to ensure that nurse call situations from the device are passed to the appropriate nurse call system.

The hub also communicates with hospital systems to advantageously associate incoming patient measurement and treatment data with the patient being monitored. For example, the hub may communicate wirelessly or otherwise to a multi-patient monitoring system, such as a server or collection of servers, which in turn many communicate with a caregiver's data management systems, such as, for example, an Admit, Discharge, Transfer ("ADT") system and/or an Electronic Medical Records ("EMR") system. The hub advantageously associates the data flowing through it with the patient being monitored thereby providing the electronic measurement and treatment information to be passed to the caregiver's data management systems without the caregiver associating each device in the environment with the patient.

In an embodiment, the hub advantageously includes a reconfigurable and removable docking station. The docking station may dock additional layered docking stations to adapt to different patient monitoring devices. Additionally, the docking station itself is modularized so that it may be removed if the primary dockable portable patient monitor changes its form factor. Thus, the hub is flexible in how its docking station is configured.

In an embodiment, the hub includes a large memory for storing some or all of the data it receives, processes, and/or associates with the patient, and/or communications it has with other devices and systems. Some or all of the memory may advantageously comprise removable SD memory.

The hub communicates with other devices through at least (1) the docking station to acquire data from a portable monitor, (2) innovative universal medical connectors to acquire channel data, (3) serial data connectors, such as RJ ports to acquire output data, (4) Ethernet, USB, and nurse call ports, (5) Wireless devices to acquire data from a portable monitor, (6) other wired or wireless communication mechanisms known to an artisan. The universal medical connectors advantageously provide optional electrically isolated power and communications, are designed to be smaller in cross section than isolation requirements. The connectors and the hub communicate to advantageously translate or configure data from other devices to be usable and displayable for the hub. In an embodiment, a software developers kit (“SDK”) is provided to a device manufacturer to establish or define the behavior and meaning of the data output from their device. When the output is defined, the definition is programmed into a memory residing in the cable side of the universal medical connector and supplied as an original equipment manufacture (“OEM”) to the device provider. When the cable is connected between the device and the hub, the hub understands the data and can use it for display and processing purposes without necessitating software upgrades to the device or the hub. In an embodiment, the hub can negotiate the schema and even add additional compression and/or encryption. Through the use of the universal medical connectors, the hub organizes the measurement and treatment data into a single display and alarm system effectively and efficiently bringing order to the monitoring environment.

As the hub receives and tracks data from other devices according to a channel paradigm, the hub may advantageously provide processing to create virtual channels of patient measurement or treatment data. In an embodiment, a virtual channel may comprise a non-measured parameter that is, for example, the result of processing data from various measured or other parameters. An example of such a parameter includes a wellness indicator derived from various measured parameters that give an overall indication of the wellbeing of the monitored patient. An example of a wellness parameter is disclosed in U.S. patent application Ser. Nos. 13/269,296, 13/371,767 and 12/904,925, by the assignee of the present disclosure and incorporated by reference herein. By organizing data into channels and virtual channels, the hub may advantageously time-wise synchronize incoming data and virtual channel data.

The hub also receives serial data through serial communication ports, such as RJ connectors. The serial data is associated with the monitored patient and passed on to the multi-patient server systems and/or caregiver backend systems discussed above. Through receiving the serial data, the caregiver advantageously associates devices in the caregiver environment, often from varied manufactures, with a particular patient, avoiding a need to have each individual device associated with the patient and possible communicating with hospital systems. Such association is vital as it reduces caregiver time spent entering biographic and demographic information into each device about the patient. Moreover, in an embodiment, through the SDK the device manufacturer may advantageously provide information associated with any measurement delay of their device, thereby further allowing the hub to advantageously time-wise synchronize serial incoming data and other data associated with the patient.

In an embodiment, when a portable patient monitor is docked, and it includes its own display, the hub effectively increases its display real estate. For example, in an embodi-

ment, the portable patient monitor may simply continue to display its measurement and/or treatment data, which may be now duplicated on the hub display, or the docked display may alter its display to provide additional information. In an embodiment, the docked display, when docked, presents anatomical graphical data of, for example, the heart, lungs, organs, the brain, or other body parts being measured and/or treated. The graphical data may advantageously animate similar to and in concert with the measurement data. For example, lungs may inflate in approximate correlation to the measured respiration rate and/or the determined inspiration/expiration portions of a respiration cycle, the heart may beat according to the pulse rate, may beat generally along understood actual heart contraction patterns, the brain may change color or activity based on varying depths of sedation, or the like. In an embodiment, when the measured parameters indicate a need to alert a caregiver, a changing severity in color may be associated with one or more displayed graphics, such as the heart, lungs, brain, organs, circulatory system or portions thereof, respiratory system or portions thereof, other body parts or the like. In still other embodiments, the body portions may include animations on where, when or how to attach measurement devices.

The hub may also advantageously overlap parameter displays to provide additional visual information to the caregiver. Such overlapping may be user definable and configurable. The display may also incorporate analog-appearing icons or graphical indicia.

In the interest of clarity, not all features of an actual implementation are described in this specification. An artisan will of course be appreciate that in the development of any such actual implementation (as in any development project), numerous implementation-specific decisions must be made to achieve a developers’ specific goals and sub-goals, such as compliance with system- and business-related constraints, which will vary from one implementation to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking of device engineering for those of ordinary skill having the benefit of this disclosure.

To facilitate a complete understanding of the disclosure, the remainder of the detailed description describes the disclosure with reference to the drawings, wherein like reference numbers are referenced with like numerals throughout.

## II. Example Hub Embodiments

FIG. 1A illustrates a monitoring environment including a perspective view of an exemplary medical monitoring hub **100** with an exemplary docked portable patient monitor **102** according to an embodiment of the disclosure. The hub **100** includes a display **104**, and a docking station **106**, which in an embodiment is configured to mechanically and electrically mate with the portable patient monitor **102**, each housed in a movable, mountable and portable housing **108**. The housing **108** includes a generally upright inclined shape configured to rest on a horizontal flat surface, although the housing **108** can be affixed in a wide variety of positions and mountings and comprise a wide variety of shapes and sizes.

In an embodiment, the display **104** may present a wide variety of measurement and/or treatment data in numerical, graphical, waveform, or other display indicia **110**. In an embodiment, the display **104** occupies much of a front face of the housing **108**, although an artisan will appreciate the display **104** may comprise a tablet or tabletop horizontal configuration, a laptop-like configuration or the like. Other embodiments may include communicating display informa-

tion and data to a table computer, smartphone, television, or any display system recognizable to an artisan. The upright inclined configuration of FIG. 1A presents display information to a caregiver in an easily viewable manner.

FIG. 1B shows a perspective side view of an embodiment of the hub 100 including the housing 108, the display 104, and the docking station 106 without a portable monitor docked. Also shown is a connector for noninvasive blood pressure.

In an embodiment, the housing 108 may also include pockets or indentations to hold additional medical devices, such as, for example, a blood pressure monitor or temperature sensor 112, such as that shown in FIG. 1C.

The portable patient monitor 102 of FIG. 1A may advantageously comprise an oximeter, co-oximeter, respiratory monitor, depth of sedation monitor, noninvasive blood pressure monitor, vital signs monitor or the like, such as those commercially available from Masimo Corporation of Irvine, Calif., and/or disclosed in U.S. Pat. Pub. Nos. 2002/0140675, 2010/0274099, 2011/0213273, 2012/0226117, 2010/0030040; U.S. Pat. App. Ser. Nos. 61/242,792, 61/387457, 61/645,570, 13/554,908 and U.S. Pat. Nos. 6,157,850, 6,334,065, and the like. The monitor 102 may communicate with a variety of noninvasive and/or minimally invasive devices such as optical sensors with light emission and detection circuitry, acoustic sensors, devices that measure blood parameters from a finger prick, cuffs, ventilators, and the like. The monitor 102 may include its own display 114 presenting its own display indicia 116, discussed below with reference to FIGS. 19A-19J. The display indicia may advantageously change based on a docking state of the monitor 102. When undocked, the display indicia may include parameter information and may alter orientation based on, for example, a gravity sensor or accelerometer.

In an embodiment, the docking station 106 of the hub 100 includes a mechanical latch 118, or mechanically releasable catch to ensure that movement of the hub 100 doesn't mechanically detach the monitor 102 in a manner that could damage the same.

Although disclosed with reference to particular portable patient monitors 102, an artisan will recognize from the disclosure herein a large number and wide variety of medical devices that may advantageously dock with the hub 100. Moreover, the docking station 106 may advantageously electrically and not mechanically connect with the monitor 102, and/or wirelessly communicate with the same.

FIG. 2 illustrates a simplified block diagram of an exemplary monitoring environment 200 including the hub 100 of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 2, the environment may include the portable patient monitor 102 communicating with one or more patient sensors 202, such as, for example, oximetry optical sensors, acoustic sensors, blood pressure sensors, respiration sensors or the like. In an embodiment, additional sensors, such as, for example, a NIBP sensor or system 211 and a temperature sensor or sensor system 213 may communicate directly with the hub 100. The sensors 202, 211 and 213 when in use are typically in proximity to the patient being monitored if not actually attached to the patient at a measurement site.

As disclosed, the portable patient monitor 102 communicates with the hub 100, in an embodiment, through the docking station 106 when docked and, in an embodiment, wirelessly when undocked, however, such undocked communication is not required. The hub 100 communicates with one or more multi-patient monitoring servers 204 or server

systems, such as, for example, those disclosed with in U.S. Pat. Pub. Nos. 2011/0105854, 2011/0169644, and 2007/0180140. In general, the server 204 communicates with caregiver backend systems 206 such as EMR and/or ADT systems. The server 204 may advantageously obtain through push, pull or combination technologies patient information entered at patient admission, such as demographical information, billing information, and the like. The hub 100 accesses this information to seamlessly associate the monitored patient with the caregiver backend systems 206. Communication between the server 204 and the monitoring hub 100 may be any recognizable to an artisan from the disclosure herein, including wireless, wired, over mobile or other computing networks, or the like.

FIG. 2 also shows the hub 100 communicating through its serial data ports 210 and channel data ports 212. As disclosed in the forgoing, the serial data ports 210 may provide data from a wide variety of patient medical devices, including electronic patient bed systems 214, infusion pump systems 216 including closed loop control systems, ventilator systems 218, blood pressure or other vital sign measurement systems 220, or the like. Similarly, the channel data ports 212 may provide data from a wide variety of patient medical devices, including any of the foregoing, and other medical devices. For example, the channel data ports 212 may receive data from depth of consciousness monitors 222, such as those commercially available from SEDLine, brain or other organ oximeter devices 224, noninvasive blood pressure or acoustic devices 226, or the like. In an embodiment, channel device may include board-in-cable ("BIC") solutions where the processing algorithms and the signal processing devices that accomplish those algorithms are mounted to a board housed in a cable or cable connector, which in some embodiments has no additional display technologies. The BIC solution outputs its measured parameter data to the channel port 212 to be displayed on the display 104 of hub 100. In an embodiment, the hub 100 may advantageously be entirely or partially formed as a BIC solution that communicates with other systems, such as, for example, tablets, smartphones, or other computing systems.

Although disclosed with reference to a single docking station 106, the environment 200 may include stacked docking stations where a subsequent docking station mechanically and electrically docks to a first docking station to change the form factor for a different portable patient monitor as discussed with reference to FIG. 5. Such stacking may include more than 2 docking stations, may reduce or increase the form fact for mechanical compliance with mating mechanical structures on a portable device.

FIG. 3 illustrates a simplified exemplary hardware block diagram of the hub 100 of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 3, the housing 108 of the hub 100 positions and/or encompasses an instrument board 302, the display 104, memory 304, and the various communication connections, including the serial ports 210, the channel ports 212, Ethernet ports 305, nurse call port 306, other communication ports 308 including standard USB or the like, and the docking station interface 310. The instrument board 302 comprises one or more substrates including communication interconnects, wiring, ports and the like to enable the communications and functions described herein, including inter-board communications. A core board 312 includes the main parameter, signal, and other processor(s) and memory, a portable monitor board ("RIB") 314 includes patient electrical isolation for the monitor 102 and one or more processors, a channel board ("MID") 316 controls the communication with the channel

ports **212** including optional patient electrical isolation and power supply **318**, and a radio board **320** includes components configured for wireless communications. Additionally, the instrument board **302** may advantageously include one or more processors and controllers, busses, all manner of communication connectivity and electronics, memory, memory readers including EPROM readers, and other electronics recognizable to an artisan from the disclosure herein. Each board comprises substrates for positioning and support, interconnect for communications, electronic components including controllers, logic devices, hardware/software combinations and the like to accomplish the tasks designated above and others.

An artisan will recognize from the disclosure herein that the instrument board **302** may comprise a large number of electronic components organized in a large number of ways. Using different boards such as those disclosed above advantageously provides organization and compartmentalization to the complex system.

FIG. **4** illustrates a perspective view of an exemplary removable docking station **400** of the hub **100** of FIG. **1**, according to an embodiment of the disclosure. As shown in FIG. **4**, the docking station **400** provides a mechanical mating to portable patient monitor **102** to provide secure mechanical support when the monitor **102** is docked. The docking station **400** includes a cavity **402** shaped similar to the periphery of a housing of the portable monitor **102**. The station **400** also includes one or more electrical connectors **404** providing communication to the hub **100**. Although shown as mounted with bolts, the docking station **400** may snap fit, may use movable tabs or catches, may magnetically attach, or may employ a wide variety or combination of attachment mechanisms known to an artisan from the disclosure herein. In an embodiment, the attachment of the docking station **400** should be sufficiently secure that when docked, the monitor **102** and docking station cannot be accidentally detached in a manner that could damage the instruments, such as, for example, if the hub **100** was accidentally bumped or the like, the monitor **102** and docking station **400** should remain intact.

The housing **108** of the hub **100** also includes cavity **406** housing the docking station **400**. To the extent a change to the form factor for the portable patient monitor **102** occurs, the docking station **400** is advantageously removable and replaceable. Similar to the docking station **400**, the hub **100** includes within the cavity **406** of the housing **108** electrical connectors **408** providing electrical communication to the docking station **400**. In an embodiment, the docking station **400** includes its own microcontroller and processing capabilities, such as those disclosed in U.S. Pat. Pub. No. 2002/0140675. In other embodiments, the docking station **400** passes communications through to the electrical connector **408**.

FIG. **4** also shows the housing **108** including openings for channel ports **212** as universal medical connectors discussed in detail below.

FIG. **5** illustrates a perspective view of exemplary portable patient monitors **502** and **504** undocked from the hub **100** of FIG. **1**, according to an embodiment of the disclosure. As shown in FIG. **5**, the monitor **502** may be removed and other monitors, like monitor **504** may be provided. The docking station **106** includes an additional docking station **506** that mechanically mates with the original docking station **106** and presents a form factor mechanically mateable with monitor **504**. In an embodiment, the monitor **504** mechanically and electrically mates with the stacked docking stations **506** and **106** of hub **100**. As can be readily

appreciated by and artisan from the disclosure herein, the stackable function of the docking stations provides the hub **100** with an extremely flexible mechanism for charging, communicating, and interfacing with a wide variety of patient monitoring devices. As noted above, the docking stations may be stacked, or in other embodiments, removed and replaced.

FIG. **6** illustrates a simplified block diagram of traditional patient electrical isolation principles. As shown in FIG. **6**, a host device **602** is generally associated with a patient device **604** through communication and power. As the patient device **604** often comprises electronics proximate or connected to a patient, such as sensors or the like, certain safety requirements dictate that electrical surges of energy from, for example, the power grid connected to the host device, should not find an electrical path to the patient. This is generally referred to a "patient isolation" which is a term known in the art and includes herein the removing of direct uninterrupted electrical paths between the host device **602** and the patient device **604**. Such isolation is accomplished through, for example, isolation devices **606** on power conductors **608** and communication conductors **610**. Isolation devices **606** can include transformers, optical devices that emit and detect optical energy, and the like. Use of isolation devices, especially on power conductors, can be expensive component wise, expensive size wise, and drain power. Traditionally, the isolation devices were incorporated into the patient device **604**, however, the patient devices **604** are trending smaller and smaller and not all devices incorporate isolation.

FIG. **7A** illustrates a simplified block diagram of an exemplary optional patient isolation system according to an embodiment of the disclosure. As shown in FIG. **7A**, the host device **602** communicates with an isolated patient device **604** through isolation devices **606**. However, a memory **702** associated with a particular patient device informs the host **602** whether that device needs isolated power. If a patient device **708** does not need isolated power, such as some types of cuffs, infusion pumps, ventilators, or the like, then the host **602** can provide non-isolated power through signal path **710**. This power may be much higher than what can cost-effectively be provided through the isolated power conductor **608**. In an embodiment, the non-isolated patient devices **708** receive isolated communication as such communication is typically at lower voltages and is not cost prohibitive. An artisan will recognize from the disclosure herein that communication could also be non-isolated. Thus, FIG. **7A** shows a patient isolation system **700** that provides optional patient isolation between a host **602** and a wide variety of potential patient devices **604**, **708**. In an embodiment, the hub **100** includes the channel ports **212** incorporating similar optional patient isolation principles.

FIG. **7B** adds an exemplary optional non-isolation power levels for the system of FIG. **7A** according to an embodiment of the disclosure. As shown in FIG. **7B**, once the host **602** understands that the patient device **604** comprises a self-isolated patient device **708**, and thus does not need isolated power, the host **602** provides power through a separate conductor **710**. Because the power is not isolated, the memory **702** may also provide power requirements to the host **602**, which may select from two or more voltage or power levels. In FIG. **7B**, the host **602** provides either high power, such as about 12 volts, but could have a wide range of voltages or very high power such as about 24 volts or more, but could have a wide range of voltages, to the patient device **708**. An artisan will recognize that supply voltages can advantageously be altered to meet the specific needs of

virtually any device 708 and/or the memory could supply information to the host 602 which provided a wide range of non-isolated power to the patient device 708.

Moreover, using the memory 702, the host 602 may determine to simply not enable any unused power supplies, whether that be the isolated power or one or more of the higher voltage non-isolated power supplies, thereby increasing the efficiency of the host.

FIG. 8 illustrates a simplified exemplary universal medical connector configuration process 800, according to an embodiment of the disclosure. As shown in FIG. 8, the process includes step 802, where a cable is attached to a universal medical connector incorporating optional patient isolation as disclosed in the foregoing. In step 804, the host device 602 or the hub 100, more specifically, the channel data board 316 or EPROM reader of the instrument board, reads the data stored in the memory 702 and in step 806, determines whether the connecting device requires isolated power. In step 808, when the isolated power is required, the hub 100 may advantageously enable isolated power and in step 810, enable isolated communications. In step 806, when isolated power is not needed, the hub 100 may simply in optional step 812 enable non-isolated power and in embodiments where communications remain isolated, step 810 enable isolated communications. In other optional embodiments, in step 806, when isolated power is not needed, the hub 100 in step 814 may use information from memory 702 to determine the amount of power needed for the patient device 708. When sufficient power is not available, because for example, other connected devices are also using connected power, in step 816 a message may be displayed indicating the same and power is not provided. When sufficient power is available, optional step 812 may enable non-isolated power. Alternatively, optional step 818 may determine whether memory 702 indicates higher or lower power is desired. When higher power is desired, the hub 100 may enable higher power in step 820 and when not, may enable lower power in step 822. The hub 100 in step 810 then enables isolated communication. In an embodiment, the hub 100 in step 818 may simply determine how much power is needed and provide at least sufficient power to the self-isolated device 708.

An artisan will recognize from the disclosure herein that hub 100 may not check to see if sufficient power is available or may provide one, two or many levels of non-isolated voltages based on information from the memory 702.

FIGS. 9A and 9B illustrate simplified block diagrams of exemplary universal medical connectors 900 having a size and shape smaller in cross section than tradition isolation requirements. In an embodiment, the connector 900 physically separates non-isolated signals on one side 910 from isolated signals on another side 920, although the sides could be reversed. The gap between such separations may be dictated at least in part by safety regulations governing patient isolation. In an embodiment, the distance between the sides 910 and 920 may appear to be too small.

As shown from a different perspective in FIG. 9B, the distance between connectors “x” appears small. However, the gap causes the distance to include a non-direct path between conductors. For example, any short would have to travel path 904, and the distance of such path is within or beyond such safety regulations, in that the distance is greater than “x.” It is noteworthy that the non-straight line path 904 occurs throughout the connector, such as, for example, on the board connector side where solder connects various pins to a PCB board.

FIG. 10 illustrates a perspective view of a side of the hub 100 of FIG. 1, showing exemplary instrument-side channel inputs 1000 as exemplary universal medical connectors. As shown in FIG. 10, the inputs include the non-isolated side 910, the isolated side 920, and the gap. In an embodiment, the memory 710 communicates through pins on the non-isolated side.

FIGS. 11A-11K illustrate various views of exemplary male and mating female universal medical connectors, according to embodiments of the disclosure. For example, FIGS. 11G1 and 11G2 shows various preferred but not required sizing, and FIG. 11H shows incorporation of electronic components, such as the memory 702 into the connectors. FIGS. 11I-11K illustrate wiring diagrams and cabling specifics of the cable itself as it connects to the universal medical connectors.

FIG. 12 illustrates a simplified block diagram of a channel system for the hub of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 12, a male cable connector, such as those shown in FIG. 11 above, includes a memory such as an EPROM. The memory advantageously stores information describing the type of data the hub 100 can expect to receive, and how to receive the same. A controller of the hub 100 communicates with the EPROM to negotiate how to receive the data, and if possible, how to display the data on display 104, alarm when needed, and the like. For example, a medical device supplier may contact the hub provider and receive a software developers’ kit (“SDK”) that guides the supplier through how to describe the type of data output from their device. After working with the SDK, a map, image, or other translation file may advantageously be loaded into the EPROM, as well as the power requirements and isolation requirements discussed above. When the channel cable is connected to the hub 100 through the channel port 212, the hub 100 reads the EPROM and the controller of the hub 100 negotiates how to handle incoming data.

FIG. 13 illustrates an exemplary logical channel configuration that may be stored in the EPROM of FIG. 12. As shown in FIG. 13, each incoming channel describes one or more parameters. Each parameter describes whatever the hub 100 should know about the incoming data. For example, the hub 100 may want to know whether the data is streaming data, waveform data, already determined parameter measurement data, ranges on the data, speed of data delivery, units of the data, steps of the units, colors for display, alarm parameters and thresholds, including complex algorithms for alarm computations, other events that are parameter value driven, combinations of the same or the like. Additionally, the parameter information may include device delay times to assist in data synchronization or approximations of data synchronization across parameters or other data received by the hub 100. In an embodiment, the SDK presents a schema to the device supplier which self-describes the type and order of incoming data. In an embodiment, the information advantageously negotiates with the hub 100 to determine whether to apply compression and/or encryption to the incoming data stream.

Such open architecture advantageously provides device manufacturers the ability to port the output of their device into the hub 100 for display, processing, and data management as disclosed in the foregoing. By implementation through the cable connector, the device manufacturer avoids any reprogramming of their original device; rather, they simply let the hub 100 know through the cable connector how the already existing output is formatted. Moreover, by describing the data in a language already understood by the

hub 100, the hub 100 also avoids software upgrades to accommodate data from “new-to-the-hub” medical devices.

FIG. 14 illustrates a simplified exemplary process for configuring a channel according to an embodiment of the disclosure. As shown in FIG. 14, the hub provider provides a device manufacturer with an SDK in step 1402, who in turn uses the SDK to self-describe the output data channel from their device in step 1404. In an embodiment, the SDK is a series of questions that guide the development, in other embodiments, the SDK provides a language and schema to describe the behavior of the data.

Once the device provider describes the data, the hub provider creates a binary image or other file to store in a memory within a cable connector in step 1405; however, the SDK may create the image and simply communicated it to the hub provider. The cable connector is provided as an OEM part to the provider in step 1410, who constructs and manufactures the cable to mechanically and electrically mate with output ports on their devices in step 1412.

Once a caregiver has the appropriately manufactured cable, with one end matching the device provider’s system and the other OEM’ed to match the hub 100 at its channel ports 212, in step 1452 the caregiver can connect the hub between the devices. In step 1454, the hub 100 reads the memory, provides isolated or non-isolated power, and the cable controller and the hub 100 negotiate a protocol or schema for data delivery. In an embodiment, a controller on the cable may negotiated the protocol, in an alternative embodiment, the controller of the hub 100 negotiates with other processors on the hub the particular protocol. Once the protocol is set, the hub 100 can use, display and otherwise process the incoming data stream in an intelligent manner.

Through the use of the universal medical connectors described herein, connection of a myriad of devices to the hub 100 is accomplished through straightforward programming of a cable connector as opposed to necessitating software upgrades to each device.

FIG. 15 illustrates a perspective view of the hub of FIG. 1 including an exemplary attached board-in-cable (“BIC”) to form an input channel according to an embodiment of the disclosure. As shown in FIG. 15, a SEDLine depth of consciousness board communicates data from an appropriate patient sensor to the hub 100 for display and caregiver review. As described, the provider of the board need only use the SDK to describe their data channel, and the hub 100 understands how to present the data to the caregiver.

FIG. 16 illustrates a perspective view of a back side of the hub 100 of FIG. 1, showing an exemplary serial data inputs. In an embodiment, the inputs include such as RJ 45 ports. As is understood in the art, these ports include a data ports similar to those found on computers, network routers, switches and hubs. In an embodiment, a plurality of these ports are used to associate data from various devices with the specific patient identified in the hub 100. FIG. 16 also shows a speaker, the nurse call connector, the Ethernet connector, the USBs, a power connector and a medical grounding lug.

FIG. 17A illustrates an exemplary monitoring environment with communication through the serial data connections of the hub 100 of FIG. 1, according to an embodiment of the disclosure. As shown and as discussed in the foregoing, the hub 100 may use the serial data ports 210 to gather data from various devices within the monitoring environment, including an electronic bed, infusion pumps, ventilators, vital sign monitors, and the like. The difference between the data received from these devices and that received through the channel ports 212 is that the hub 100 may not know the format or structure of this data. The hub

100 may not display information from this data or use this data in calculations or processing. However, porting the data through the hub 100 conveniently associates the data with the specifically monitored patient in the entire chain of caregiver systems, including the foregoing server 214 and backend systems 206. In an embodiment, the hub 100 may determine sufficient information about the incoming data to attempt to synchronize it with data from the hub 100.

In FIG. 17B, a control screen may provide information on the type of data being received. In an embodiment, a green light next to the data indicates connection to a device and on which serial input the connection occurs.

FIG. 18 illustrates a simplified exemplary patient data flow process, according to an embodiment of the disclosure. As shown, once a patient is admitted into the caregiver environment at step 1802, data about the patient is populated on the caregiver backend systems 206. The server 214 may advantageously acquire or receive this information in step 1804, and then make it accessible to the hub 100. When the caregiver at step 1806 assigns the hub 100 to the patient, the caregiver simply looks at the presently available patient data and selects the particular patient being currently monitored. The hub 100 at step 1808 then associates the measurement, monitoring and treatment data it receives and determines with that patient. The caregiver need not again associate another device with the patient so long as that device is communicating through the hub 100 by way of (1) the docking station, (2) the universal medical connectors, (3) the serial data connectors, or (4) other communication mechanisms known to an artisan. At step 1810, some or the entirety of the received, processed and/or determined data is passed to the server systems discussed above.

FIGS. 19A-19J illustrate exemplary displays of anatomical graphics for the portable patient monitor docked with the hub 100 of FIG. 1, according to embodiments of the disclosure. As shown in FIG. 19A, the heart, lungs and respiratory system are shown while the brain is not highlighted. Thus, a caregiver can readily determine that depth of consciousness monitoring or brain oximetry systems are not currently communicating with the hub 100 through the portable patient monitor connection or the channel data ports. However, it is likely that acoustic or other respiratory data and cardiac data is being communicated to or measured by the hub 100. Moreover, the caregiver can readily determine that the hub 100 is not receiving alarming data with respect to the emphasized body portions. In an embodiment, the emphasized portion may animate to show currently measured behavior or, alternatively, animate in a predetermined fashion.

FIG. 19B shows the addition of a virtual channel showing an indication of wellness. As shown in FIG. 19B, the indication is positive as it is a “34” on an increasingly severity scale to “100.” The wellness indication may also be shaded to show problems. In contrast to FIG. 19B, FIG. 19C shows a wellness number that is becoming or has become problematic and an alarming heart graphic. Thus, a caregiver responding to a patient alarm on the hub 100 or otherwise on another device or system monitoring or treating the patient can quickly determine that a review of vital signs and other parameters relating to heart function is needed to diagnose and/or treat the patient.

FIGS. 19D and 19E show the brain included in the emphasized body portions meaning that the hub 100 is receiving data relevant to brain functions, such as, for example, depth of sedation data or brain oximetry data. FIG. 19E additionally shows an alarming heart function similar to FIG. 19C.



In FIG. 19F, additional organs, such as the kidneys are being monitored, but the respiratory system is not. In FIG. 19G, an alarming hear function is shown, and in FIG. 19H, an alarming circulatory system is being shown. FIG. 19I shows the wellness indication along with lungs, heart, brain and kidneys. FIG. 19J shows alarming lungs, heart, and circulatory system as well as the wellness indication. Moreover, FIG. 19J shows a severity contrast, such as, for example, the heart alarming red for urgent while the circulatory system alarms yellow for caution. An artisan will recognize other color schemes that are appropriate from the disclosure herein.

FIGS. 20A-20C illustrate exemplary displays of measurement data showing data separation and data overlap, respectively, according embodiments of the disclosure. FIGS. 21A and 21B illustrate exemplary displays of measurement data also showing data separation and data overlap, respectively, according embodiments of the disclosure.

For example, acoustic data from an acoustic sensor may advantageously provide breath sound data, while the plethysmograph and ECG or other signals can also be presented in separate waveforms (FIG. 20A, top of the screen capture). The monitor may determine any of a variety of respiratory parameters of a patient, including respiratory rate, expiratory flow, tidal volume, minute volume, apnea duration, breath sounds, riles, rhonchi, stridor, and changes in breath sounds such as decreased volume or change in airflow. In addition, in some cases a system monitors other physiological sounds, such as heart rate to help with probe off detection, heart sounds (S1, S2, S3, S4, and murmurs), and change in heart sounds such as normal to murmur or split heart sounds indicating fluid overload.

Providing a visual correlation between multiple physiological signals can provide a number of valuable benefits where the signals have some observable physiological correlation. As one example of such a correlation, changes in morphology (e.g., envelope and/or baseline) of the plethysmographic signal can be indicative of patient blood or other fluid levels. And, these changes can be monitored to detect hypovolemia or other fluid-level related conditions. A pleth variability index may provide an indication of fluid levels, for example. And, changes in the morphology of the plethysmographic signal are correlated to respiration. For example, changes in the envelope and/or baseline of the plethysmographic signal are correlated to breathing. This is at least in part due to aspects of the human anatomical structure, such as the mechanical relationship and interaction between the heart and the lungs during respiration.

Thus, superimposing a plethysmographic signal and a respiratory signal (FIG. 20B) can give operators an indication of the validity of the plethysmographic signal or signals derived therefrom, such as a pleth variability index. For example, if bursts in the respiration signal indicative of inhalation and exhalation correlate with changes in peaks and valleys of the plethysmographic envelope, this gives monitoring personnel a visual indication that the plethysmographic changes are indeed due to respiration, and not some other extraneous factor. Similarly, if the bursts in the respiration signal line up with the peaks and valleys in the plethysmographic envelope, this provides monitoring personnel an indication that the bursts in the respiration signal are due to patient breathing sounds, and not some other non-targeted sounds (e.g., patient non-breathing sounds or non-patient sounds).

The monitor may also be configured to process the signals and determine whether there is a threshold level of correlation between the two signals, or otherwise assess the

correlation. However, by additionally providing a visual indication of the correlation, such as by showing the signals superimposed with one another, the display provides operators a continuous, intuitive and readily observable gauge of the particular physiological correlation. For example, by viewing the superimposed signals, users can observe trends in the correlation over time, which may not be otherwise ascertainable.

The monitor can visually correlate a variety of other types of signals instead of, or in addition to plethysmographic and respiratory signals. For example, FIG. 20C depicts a screen shot of another example monitoring display. As shown in the upper right portion of FIG. 20C, the display superimposes a plethysmographic signal, an ECG signal, and a respiration signal. In other configurations, more than three different types of signals may be overlaid onto one another.

In one embodiment, the hub 100 nothing provides an interface through which the user can move the signals together to overlay on one another. For example, the user may be able to drag the respiration signal down onto the plethysmographic signal using a touch screen interface. Conversely, the user may be able to separate the signals, also using the touch screen interface. In another embodiment, the monitor includes a button the user can press, or some other user interface allowing the user to overlay and separate the signals, as desired. FIGS. 21A and 21B show similar separation and joining of the signals.

In certain configurations, in addition to providing the visual correlation between the plethysmographic signal and the respiratory signal, the monitor is additionally configured to process the respiratory signal and the plethysmographic signal to determine a correlation between the two signals. For example, the monitor may process the signals to determine whether the peaks and valleys in the changes in the envelope and/or baseline of the plethysmographic signal correspond to bursts in the respiratory signal. And, in response to the determining that there is or is not a threshold level of correlation, the monitor may provide some indication to the user. For example, the monitor may provide a graphical indication (e.g., a change in color of pleth variability index indicator), an audible alarm, or some other indication. The monitor may employ one or more envelope detectors or other appropriate signal processing componentry in making the determination.

In certain embodiments, the system may further provide an audible indication of the patient's breathing sounds instead of, or in addition to the graphical indication. For example, the monitor may include a speaker, or an earpiece (e.g., a wireless earpiece) may be provided to the monitoring personnel providing an audible output of the patient sounds. Examples of sensors and monitors having such capability are described in U.S. Pat. Pub. No. 2011/0172561 and are incorporated by reference herein.

In addition to the above described benefits, providing both the acoustic and plethysmographic signals on the same display in the manner described can allow monitoring personnel to more readily detect respiratory pause events where there is an absence of breathing, high ambient noise that can degrade the acoustic signal, improper sensor placement, etc.

FIGS. 22A-22B illustrate exemplary analog display indicia, according to an embodiment of the disclosure. As shown in FIGS. 22A and 22B, the screen shots displays health indicators of various physiological parameters, in addition to other data. Each health indicator can include an analog indicator and/or a digital indicator. In embodiments where the health indicator includes an analog and a digital indicator, the analog and digital indicators can be positioned in any

number of formations, such as side-by-side, above, below, transposed, etc. In the illustrated embodiment, the analog indicators are positioned above and to the sides of the digital indicators. As shown more clearly in FIG. 22B, the analog displays may include colored warning sections, dashes indicating position on the graph, and digital information designating quantitative information from the graph. In FIG. 22B, for example, the pulse rate PR graph shows that from about 50 to about 140 beats per minute, the graph is either neutral or beginning to be cautionary, whereas outside those numbers the graph is colored to indicate a severe condition. Thus, as the dash moves along the arc, a caregiver can readily see where in the range of acceptable, cautionary, and extreme the current measurements fall.

Each analog indicator of the health indicator can include a dial that moves about an arc based on measured levels of monitored physiological parameters. As the measured physiological parameter levels increase the dial can move clockwise, and as the measured physiological parameter levels decrease, the dial can move counter-clockwise, or vice versa. In this way, a user can quickly determine the patient's status by looking at the analog indicator. For example, if the dial is in the center of the arc, the observer can be assured that the current physiological parameter measurements are normal, and if the dial is skewed too far to the left or right, the observer can quickly assess the severity of the physiological parameter levels and take appropriate action. In other embodiments, normal parameter measurements can be indicated when the dial is to the right or left, etc.

In some embodiments, the dial can be implemented as a dot, dash, arrow, or the like, and the arc can be implemented as a circle, spiral, pyramid, or other shape, as desired. Furthermore, the entire arc can be lit up or only portions of the arc can be lit up based on the current physiological parameter measurement level. Furthermore, the arc can turn colors or be highlighted based on the current physiological parameter level. For example, as the dial approaches a threshold level, the arc and/or dial can turn from green, to yellow, to red, shine brighter, flash, be enlarged, move to the center of the display, or the like.

Different physiological parameters can have different thresholds indicating abnormal conditions. For example, some physiological parameters may upper a lower threshold levels, while others only have an upper threshold or a lower threshold. Accordingly, each health indicator can be adjusted based on the physiological parameter being monitored. For example, the SpO<sub>2</sub> health indicator can have a lower threshold that when met activates an alarm, while the respiration rate health indicator can have both a lower and upper threshold, and when either is met an alarm is activated. The thresholds for each physiological parameter can be based on typical, expected thresholds and/or user-specified thresholds.

The digital indicator can provide a numerical representation of the current levels of the physiological parameter the digital indicator may indicate an actual level or a normalized level and can also be used to quickly assess the severity of a patient condition. In some embodiments, the display includes multiple health indicators for each monitored physiological parameter. In certain embodiments, the display includes fewer health indicators than the number of monitored physiological parameters. In such embodiments, the health indicators can cycle between different monitored physiological parameters.

FIGS. 23A-23F illustrate exemplary displays of measurement data showing, for example, data presentation in FIGS. 23A-23D when a depth of consciousness monitor is con-

nected to a channel port of the hub of FIG. 1. As shown in FIGS. 23A-23C, the hub 100 advantageously roughly bifurcates its display 104 to show various information from the, for example, SEDLine device, commercially available from Masimo Corp. of Irvine, Calif. In FIG. 23D, the hub 100 includes an attached PhaseIn device, commercially available by PHASEIN AB of Sweden, providing, for example, information about the patient's respiration. The hub 100 also includes the SEDLine information, so the hub 100 has divided the display 104 appropriately. In FIG. 23E, temperature and blood pressure sensors communicate with the hub of FIG. 1 and the hub 100 creates display real estate appropriate for the same. In FIG. 23F, an acoustic sensor is also communicating with the hub of FIG. 1, as well as the forgoing blood pressure and temperature sensor. Accordingly, the hub 100 adjust the display real estate to accommodate the data from each attached device.

The term "and/or" herein has its broadest least limiting meaning which is the disclosure includes A alone, B alone, both A and B together, or A or B alternatively, but does not require both A and B or require one of A or one of B. As used herein, the phrase "at least one of" A, B, "and" C should be construed to mean a logical A or B or C, using a non-exclusive logical or.

The term "plethysmograph" includes its ordinary broad meaning known in the art which includes data responsive to changes in volume within an organ or whole body (usually resulting from fluctuations in the amount of blood or air it contains).

### III. Additional Monitoring Environment Embodiments

FIG. 24 illustrates another embodiment of a monitoring environment 2000 including the hub 100 of FIG. 1. The monitoring environment 2000 may include all the features of the monitoring environment 200 of FIG. 2, as well as any of the other features described above. In addition, the monitoring environment 2000 depicts another embodiment of the multi-patient monitoring system 204, namely, the multi-patient monitoring system (MMS) 2004. The MMS 2004 includes a translation module 2005 that can receive serial data, translate the serial data into a format recognizable by the monitoring hub 100, and provide the serial data to the monitoring hub 100 (among possibly other devices). Also shown is an auxiliary device 2040 that may communicate with the MMS 2004, the monitoring hub 100, or the PPM 102, wired or wirelessly.

As described above, the hub 100 may receive serial data from a variety of medical equipment, including the patient's bed 214, infusion pumps 216, a ventilator 218, and other vital signs monitors 220. The hub 100 can pass serial data from these sources on to the MMS 2004. As described above, the MMS 2004 may then store the serial data in a caregiver backend system 206 such as an EMR system or ADT system.

The medical equipment providing this serial data may use a variety of different proprietary protocols, messaging infrastructure, and the like that may not be natively recognizable by the hub 100. Accordingly, the hub 100 may not have native capability to read parameter values or other data from this medical equipment, and as a result, may not have the capability to display parameter values or other data from these devices. Advantageously, however, the translation module 2005 at the MMS 2004 can receive serial data from these devices, translate the serial data into a format recognizable by the monitoring hub 100, and provide the serial data to the monitoring hub 100. The monitoring hub 100 can then read parameter values and other data from the trans-

lated information and output these values or data to a display, such as any of the displays described above.

In an embodiment, the translation module **2005** applies one or more translation rules to the serial data to translate or transform the serial data from one format to another format. The serial data may be formatted according to a Health Level Seven (“HL7”) protocol in one embodiment. The HL7 protocol has been developed to provide a messaging framework for the communication of clinical messages between medical computer systems and devices. However, the HL7 standard is quite flexible and merely provides a framework of guidelines. Consequently, medical devices or clinical computer systems that are all HL7 -compliant may still be unable to communicate with each other. For example, the medical equipment **214-220** may each implement a version of the HL7 protocol, but these implementations may be different from an HL7 protocol implemented by the monitoring hub **100**. Accordingly, the monitoring hub **100** may not be able to parse or read messages from the medical equipment **214-220**, even though both use the HL7 standard. Further, the translation module **2005** may translate between different implementations of a common standard other than the HL7 protocol implemented by the hub **100** and medical equipment **214-220** in some embodiments.

In addition to translating between different implementations of a common electronic medical communication protocol (e.g., different formatting of HL7 messages), the translation module **2005** can also translate between input and output messages adhering to different communication protocols. In some embodiments, the translation module **2005** is capable of responding to and translating messages from, for example, one medical communication protocol to a separate medical communication protocol. For example, the translation module **2005** can facilitate communication between messages sent according to the HL7 protocol, the ISO 11073 protocol, other open protocols, or proprietary protocols. Accordingly, the translation module **2005** can translate an input message sent according to the HL7 protocol to an output message according to a different protocol, or vice-versa. In certain embodiments, the translation module **2005** can implement any of the translation features described below in greater detail under the section entitled “Translation Module Embodiments,” as well as further in U.S. application Ser. No. 14/032,132, filed Sep. 19, 2013, titled “Medical Monitoring System,” the disclosure of which is hereby incorporated by reference in its entirety.

Advantageously, in certain embodiments, the translation module **2005** can pass translated serial data back to the hub **100** or PPM **102**. Since the translated data is in a format readable by the hub **100** or PPM **102**, the hub **100** or PPM **102** can output the data from the medical equipment **214-220** on the display of the hub **100** or PPM **102**. In addition, the translation module **2005** can provide the translated data to devices other than the hub **100**, including clinician devices (such as cell phones, tablets, or pagers) and an auxiliary device **2040** that will be described below. Moreover, since the serial data provided by the medical equipment **214-220** may include alarm notifications, the translation module **2005** can pass these alarm notifications to the hub **100** or PPM **102**. The hub **100** or PPM **102** can therefore generate visual or audible alarms responsive to these alarm notifications. Further, the translation module **2005** can provide the alarm notifications to clinician devices, e.g., over a hospital network or wide area network (such as the Internet). In addition, the translation module **2005** can provide the alarm notifications to the auxiliary device **2040**.

The translation module **2005** is shown as implemented in the MMS **2004** because it may be beneficial to maintain and update the translation rules of the translation module **2005** in a single location. However, in other embodiments, the translation module **2005** may also be (or instead be) implemented in the hub **100** or PPM **102**. Accordingly, the hub **100** or PPM **102** can access an internal translation module **2005** to translate serial data for output to the display of the hub **100** or PPM **102**.

The auxiliary device **2040** can be a computing device having physical computer hardware, a display, and the like. For example, the auxiliary device **2040** may be a handheld computing device used by a clinician, such as a tablet, laptop, cellphone or smartphone, personal digital assistant (PDA), a wearable computer (such as a smart watch or glasses), or the like. The auxiliary device **2040** may also be simply a display device, such as a computer monitor or digital television. In an embodiment, the auxiliary device **2040** provides second screen functionality for the hub **100**, PPM **102**, or MMS **2004**. As such, the auxiliary device **2040** can communicate wirelessly or through a wired connection with the hub **100**, MMS **2004**, or PPM **102**.

As a second screen device, the auxiliary device **2040** can depict a copy of at least a portion of the display of the hub **100** (or the PPM **102**) or a different version of the hub **100** (or the PPM **102**) display. For instance, the auxiliary device **2040** can receive physiological parameter data, trend data, or waveforms from the hub **100**, PPM **102**, or MMS **2004** and display the parameter data, trend data, or waveforms. The auxiliary device **2040** can output any information available to the hub **100**, PPM **102**, or MMS **2004**. One use of the auxiliary device **2040** is as a clinician device usable by a clinician to view data from the hub **100**, PPM **102**, or MMS **2004** while away from a patient’s room (or even while in a patient’s room). A clinician can use the auxiliary device **2040** to view more detailed information about physiological parameters than is displayed on the hub **100** or PPM **102** in an embodiment (see, e.g., FIG. 39). For instance, the auxiliary device **2040** may include zoom functionality or the like that enables a clinician to zoom into trends or waveforms to more closely inspect parameter activity.

One example reason for copying at least a portion of the display of the hub **100** or PPM **102** is to enable different clinicians to have the same view of the data during a surgical procedure. In some surgical procedures, for instance, two anesthesiologists monitor a patient, one anesthesiologist monitoring the brain function and brain oxygenation of the patient, while the other monitors peripheral oxygenation of the patient. A brain sensor, such as has been described above, may be attached to the patient and provide brain monitoring and oxygenation data that is output to the hub **100** or the PPM **102** for presentation to the first anesthesiologist. A finger or toe/foot optical sensor can also be attached to the patient and output data to the hub **100** or PPM **102**. The hub **100** or PPM **102** can transmit this data to the auxiliary device **2040**, which the second anesthesiologist can monitor to observe oxygenation in the patient’s peripheral limbs. The second anesthesiologist may also need to know the oxygenation at the brain to help interpret the seriousness or lack thereof of poor peripheral oxygenation values. However, in many surgical procedures, a curtain or screen is placed over the patient as part of the procedure, blocking the second anesthesiologist’s view of the hub **100** or PPM **102**. Accordingly, the hub **100** or PPM **102** can output a copy of at least a portion of its display to the auxiliary device **2040** so that the second anesthesiologist can monitor brain function or oxygenation.

In one embodiment, the auxiliary device has a larger display area than the display of the hub **100**. For instance, the hub **100** may have a relatively smaller display, such as about 10 inches, while the auxiliary device **2040** may be a television monitor or the like that has a 40 inch or larger display (although any size display may be used for the auxiliary device **2040**). In an embodiment, the auxiliary device **2040** as a television can include a hardware module that includes a processor, memory, and a wireless or wired networking interface or the like. The processor can execute programs from the memory, including programs for displaying physiological parameters, trends, and waveforms on the display of the television. Since a television monitor is larger than embodiments of the hub **100**, the television monitor version of the auxiliary device **2040** can display more fine detail of patient waveforms and trends in some embodiments (see, e.g., FIG. **39**).

In another embodiment, the auxiliary device **2040** may display one portion of any of the displays described herein while the hub **100** displays another portion thereof. For instance, the auxiliary device **2040** may display any of the anatomical graphics described above with respect to FIGS. **19A-19J**, while the hub **100** displays any of the parameter displays described above with respect to FIGS. **20A-23F** (or vice versa). Likewise, the auxiliary device **2040** may display the translated data received from the translation module **2005** while the hub **100** displays channel data (or vice versa). In another embodiment, the auxiliary device **2040** can display both translated data and channel data (see., e.g., FIG. **38**).

In still other embodiments, the auxiliary device **2040** can perform at least some processing of physiological parameters, including any of the functionality of the monitoring hub **100**. For instance, the auxiliary device **2040** may include the translation module **2005** and perform the features thereof.

FIG. **25** illustrates an embodiment of a translation message handling process **2100**. The process **2100** can be implemented by the translation module **2005** described above or by any other computing system. In an embodiment, at block **2502**, the translation module **2005** receives a message from the hub **100** (or PPM **102**) that includes a message from a medical device not natively compatible with the hub **100** (or PPM **102**). At block **2504**, the translation module **2005** translates the message based on one or more translation rules to produce a translated output message that can be processed by the hub **100** (or PPM **102**). At block **2506**, the translation module provides the translated output message to the hub **100** for display at the hub **100** (or PPM **102**) or at an auxiliary device **2040**. The hub **100** (or PPM **102**) may route the translated data to the auxiliary device **2040**, or the auxiliary device **2040** may receive the translated data directly from the translation module **2005**.

For example, in one embodiment, a first medical device having digital logic circuitry receives a physiological signal associated with a patient from a physiological sensor, obtains a first physiological parameter value based on the physiological signal, and outputs the first physiological parameter value for display. The first medical device can also receive a second physiological parameter value from a second medical device other than the first medical device, where the second physiological parameter value is formatted according to a protocol not used by the first medical device, such that the first medical device is not able to process the second physiological parameter value to produce a displayable output value. The first medical device can pass the physiological parameter data from the first medical device to

a separate translation module, receive translated parameter data from the translation module at the first medical device, where the translated parameter data is able to be processed for display by the first medical device, and output a second value from the translated parameter data for display. The first medical device may be, for example, the hub **100**, PPM **102**, or MMS **2004**, and the second medical device may be the infusion pump **216** or ventilator **218** or the like.

FIGS. **26-38** and **46-71** illustrate additional example hub displays, including displays of measurement data. Each of these displays may be implemented by the auxiliary device **2040**, although similar displays may also be output on the hub **100** (or PPM **102**) directly. The example Figures shown are depicted as being implemented for a tablet computer that includes touchscreen functionality. Touchscreen functionality is optional and be replaced by other suitable input devices, such as keyboards, mice, track wheels, and the like.

Turning to FIG. **26**, the user interface shown depicts a device connected to the auxiliary device **2040**. The device shown is "Omar's Hawk," which can be an embodiment of the monitoring hub **100**. The auxiliary device **2040** is connected wirelessly to the hub **100** in this embodiment so as to receive data from the hub **100**. The auxiliary device could also connect wirelessly to the MMS **2004** or PPM **102** in other embodiments.

FIG. **27** depicts a default parameter view on the auxiliary device **2040**. Parameter values are shown together with waveforms in an upper portion of the display, and other parameters (such as SpHb, SpMet, PVI, etc.) are shown at the bottom of the display without their corresponding waveforms. Any of these parameters at the bottom of the display may be dragged and dropped onto the upper portion of the display to cause their waveforms to be shown. For instance, FIG. **28** depicts a similar display as in FIG. **27** except that the SpHb parameter has been dragged and dropped onto the upper portion of the display, causing the SpHb waveform and additional details on alarm limits (**18** and **7**) to be shown. Similarly, FIG. **29** shows the same display as FIG. **28** except that the SpMet parameter has been dragged and dropped on the upper portion of the display, causing its waveform and alarm limit (**3**) to be shown.

In each of the displays of FIGS. **27-29**, a time window button is shown in the upper right corner. This time window button says "1 hr" in FIGS. **27-29** but may be selected by a user to change the time window, which can affect the window of trend or waveform data shown in the display. A user selection of this time window button and change to a 10 minute window is shown in FIG. **30**. As can be seen, the waveforms in FIG. **30** are shown in a smaller window of time than in the previous Figures.

FIG. **31** shows another version of the display of FIG. **29** with stacked waveforms, including a stacked SpO2 and respiratory waveform, similar to other stacked waveforms described elsewhere herein. FIG. **32** shows a similar display to FIG. **29** with the pulse rate (PR) and SpMet (methemoglobin) parameters highlighted as being in alarm condition. The alarm condition can be represented as a red box around the parameter values and waveforms in an embodiment, or with red transparency coloring at least a portion of the box. The red box or transparency may also flash in an embodiment, and an audible alarm may sound. Other ways to represent an alarm condition are used in other embodiments.

FIG. **33** shows a popup interface that enables a user to adjust alarm limits for a parameter (in this embodiment, SpHb or total hemoglobin). The popup interface includes scroll wheels that allow a user to quickly scroll among and select possible parameter limit values.

FIGS. 34-38 show landscape display views in contrast to the portrait-oriented displays of FIGS. 26-33. These landscape display views may be accessed by rotating the auxiliary device 2040 (such as tablet etc.) to a landscape orientation. FIG. 34 shows a first set of parameters, while FIGS. 35 and 36 add additional drag-and-dropped parameters with their waveforms and additional alarm limit details, similar to those described above with respect to FIGS. 27-29. FIG. 37 depicts stacked parameter waveforms, stacking SpO2 and respiratory waveforms. FIG. 38 depicts both channel parameters (such as SpO2, PR (pulse rate), and RRA (acoustically-measured respiratory rate)) while also showing translated serial data parameters 2210, including parameters from a pump and a vent. These translated serial data parameters 2210 may have been received from the translation module 2005, either through the hub 100 or directly from the MMS 2004.

Referring again to FIG. 24, as described above, the hub 100 or PPM 102 can output a copy of at least a portion of the display to the auxiliary device 2040. In other embodiments, the hub 100 or PPM 102 can output data with respect to a subset of the full parameters shown on the hub 100 or PPM 102 to the auxiliary device 2040. For instance, the hub 100 or PPM 102 may provide functionality for a clinician to select one or more of the parameters displayed thereon to see just that one or more parameters displayed on the auxiliary device 2040. Doing so may allow the auxiliary device 2040 to show more detail about the selected one or more parameters because fewer parameters may be shown on the auxiliary device's 2040 display than on the hub 100 or PPM 102.

FIG. 39 depicts one example display of an auxiliary device 2040 that depicts data with respect to one parameter, respiratory rate. Unlike the main display of the hub 100 or PPM 102, the display shown in FIG. 39 includes more than just the current value 2215, a recent trend 2230, and small waveform of the respiratory rate. In addition, the display depicts a histogram 2220 of historical highs and lows (e.g., for the past several days) of the patient being monitored. In addition, a detailed waveform 2240 is shown, which may be larger than the waveforms shown on the main display of the hub 100 or PPM 102, which may give the user more detailed insight into the patient's respiratory condition. A user may choose to zoom into the waveform 2240 (or other aspects of the display), causing the waveform 2242 to be enlarged to fill the display in place of the other elements of the display, or the like. Other graphs, tables, waveforms, and data may be shown for the respiratory parameter on the auxiliary device display 2040. Of course, parameters other than respiratory rate may also be selected for detailed display on the auxiliary device 2040.

#### IV. Translation Module Embodiments

Any of the following features described with respect to FIGS. 40A through 45D can be implemented by the translation module 2005 of FIG. 24 or together with any of the devices described above with respect to FIG. 24.

Healthcare costs have been increasing and the demand for reasonably-priced, high-quality patient care is also on the rise. Health care costs can be reduced by increasing the effectiveness of hospital information systems. One factor which may affect the efficacy of a health institution is the extent to which the various clinical computer systems employed at the health institution can interact with one another to exchange information.

Hospitals, patient care facilities, and healthcare provider organizations typically include a wide variety of different clinical computer systems for the management of electronic

healthcare information. Each of the clinical computer systems of the overall IT or management infrastructure can help fulfill a particular category or aspect of the patient care process. For example, a hospital can include patient monitoring systems, medical documentation and/or imaging systems, patient administration systems, electronic medical record systems, electronic practice management systems, business and financial systems (such as pharmacy and billing), and/or communications systems, etc.

The quality of care in a hospital or other patient care facility could be improved if each of the different clinical computer systems across the IT infrastructure (or even within the same hospital room; see, e.g., FIGS. 1 and 24) were able to effectively communicate with each other. This could allow for the exchange of patient data that is collected by one clinical computer system with another clinical computer system that could benefit from such patient data. For example, this may allow decisions relating to patient care to be made, and actions to be taken, based on a complete analysis of all the available information.

In current practice, individual clinical computer systems can be, and often are, provided by different vendors. As a result, individual clinical computer systems may be implemented using a proprietary network or communication infrastructure, proprietary communication protocols, etc.; the various clinical computer systems used in the hospital cannot always effectively communicate with each other.

Medical device and medical system vendors sometimes develop proprietary systems that cannot communicate effectively with medical devices and systems of other vendors in order to increase their market share and to upsell additional products, systems, and/or upgrades to the healthcare provider. Thus, healthcare providers are forced to make enterprise or system-wide purchase decisions, rather than selecting the best technology available for each type of individual clinical computer system in use.

One example where this occurs is in the area of life-saving technology available for patient monitoring. For example, many different bedside devices for monitoring various physiological parameters are available from different vendors or providers. One such provider may offer a best-in-class device for monitoring a particular physiological parameter, while another such provider may offer the best-in-class device for another physiological parameter. Accordingly, it may be desirable in some circumstances for a hospital to have the freedom to use monitoring devices from more than one manufacturer, but this may not be possible if devices from different manufacturers are incapable of interfacing and exchanging patient information. Accordingly, the ability to provide reasonably-priced, high-quality patient care can be compromised. In addition, since each hospital or patient care facility may also implement its own proprietary communication protocols for its clinical computer network environment, the exchange of information can be further hindered.

As described above, the Health Level Seven ("HL7") protocol has been developed to provide a messaging framework for the communication of clinical messages between medical computer systems and devices. The HL7 communication protocol specifies a number of standards, guidelines, and methodologies which various HL7-compliant clinical computer systems can use to communicate with each other.

The HL7 communication protocol has been adopted by many medical device manufacturers. However, the HL7 standard is quite flexible, and merely provides a framework of guidelines (e.g., the high-level logical structure of the

messages); consequently, each medical device or medical system manufacturer or vendor may implement the HL7 protocol somewhat differently while still remaining HL7-compliant. For example, the format of the HL7 messages can be different from implementation to implementation, as described more fully herein. In some cases, the HL7 messages of one implementation can also include information content that is not included in messages according to another HL7 implementation. Accordingly, medical devices or clinical computer systems that are all HL7-compliant still may be unable to communicate with each other.

Consequently, a translation module can be provided that can improve the communication of medical messages between medical devices or systems that use different allowed implementations of an established communication protocol (e.g., HL7), thereby increasing the quality of patient care through the integration of multiple clinical computer systems.

FIG. 40A illustrates a first medical device **2405** and a second medical device **2410** that communicate with one another via a translation module **2415**. The first medical device **2405** is configured to transmit and receive messages according to a first allowed format or implementation of an accepted electronic medical communication protocol, while the second medical device **2410** is configured to transmit and receive messages according to a second allowed format or implementation of the electronic medical communication protocol. In some embodiments, the first and second protocol formats are different implementations of the HL7 communication protocol. Other electronic medical communication protocols besides HL7 can also be used.

The translation module **2415** receives input messages having the first protocol format from the first medical device **2405** and generates output messages to the second medical device **2410** having the second protocol format. The translation module **2415** also receives input messages having the second protocol format from the second medical device **2410** and generates output messages to the first medical device **2405** having the first protocol format. Thus, the translation module **2415** can enable the first and second medical devices **2405**, **2410** to effectively and seamlessly communicate with one another without necessarily requiring modification to the communication equipment or protocol implemented by each device.

In certain embodiments, the translation module **2415** determines the protocol format expected by an intended recipient of the input message based on, for example, the information in the input message or by referencing a database that stores the protocol format used by various devices, and then generates the output message based on the protocol format used by the intended recipient device or system. The output message can be generated based upon a comparison with, and application of, a set of translation rules **2420** that are accessible by the translation module **2415**.

The translation rules **2420** can include rules that govern how to handle possible variations between formatting implementations within a common protocol. Examples of variations in formatting implementation of an electronic medical communication protocol include, for example, the delimiter or separator characters that are used to separate data fields, whether a particular field is required or optional, the repeatability of portions of the message (e.g., segments, fields, components, sub-components), the sequence of portions of the message (e.g., the order of fields or components), whether a particular portion of a message is included, the length of the message or portions of the message, and the data type used for the various portions of the message.

In certain embodiments, the translation rules **2420** define additions, deletions, swappings, and/or modifications that should be performed in order to “translate” an input message that adheres to a first HL7 implementation into an output message that adheres to a second HL7 implementation. The output message can have, for example, different formatting than the input message, while maintaining all, or a portion of, the substance or content of the input message.

In addition to translating between different implementations of a common electronic medical communication protocol (e.g., different formatting of HL7 messages), the translation module **2415** can also translate between input and output messages adhering to different communication protocols. In some embodiments, the translation module **2415** is capable of responding to and translating messages from, for example, one medical communication protocol to a separate medical communication protocol. For example, the translation module **2415** can facilitate communication between messages sent according to the HL7 protocol, the ISO 11073 protocol, other open protocols, and/or proprietary protocols. Accordingly, an input message sent according to the HL7 protocol can be translated to an output message according to a different protocol, or vice-versa.

The operation of the translation module **2415** and the translation rules **2420** will be described in more detail below. Various embodiments of system architectures including the translation module **2415** will now be described.

In certain embodiments, the first medical device **2405**, the second medical device **2410**, and the translation module **2415** are communicatively coupled via connection to a common communications network or directly (via cables or wirelessly), for example, through the hub **100**, PPM **102**, and/or MMS **2004**. In some embodiments, the translation module **2415** can be communicatively coupled between the first medical device **2405** and the second medical device **2410** (with or without a communications network) such that all messages between the first and second medical devices **2405**, **2410** are routed through the translation module **2415**. Other architectures are also possible.

The first and second medical devices **2405**, **2410** and the translation module **2415** can be included in, for example, a portion of the monitoring environments of FIG. 1 or 24 described above. The first medical device **2405** may be, for example, the infusion pump(s) **216** or ventilator **218**, while the second medical device **2410** may be, for example, the monitoring hub **100**, PPM **102**, MMS **2004**, or auxiliary device **2040**. The translation module **2415** is an example implementation of the translation module **2005**.

In certain embodiments, the translation module **2415** can facilitate communication across multiple networks within a hospital environment. In other embodiments, the translation module **2415** can facilitate communication of messages across one or more networks extending outside of the hospital or clinical network environment. For example, the translation module **2415** can provide a communications interface with banking institutions, insurance providers, government institutions, outside pharmacies, other hospitals, nursing homes, or patient care facilities, doctors’ offices, and the like.

In some embodiments, the translation module **2415** of FIG. 40 can be a component of, for example, the environment **2000** described above with respect to FIG. 24. For example, the translation module **2415** can be communicatively coupled with a hospital network or other networks or monitoring environments described above. In such embodiments, the translation module **2415** can facilitate the exchange of patient monitoring information, including, for

example, physiological parameter measurements, physiological parameter trend information, and physiological parameter alarm conditions between bedside medical monitor devices, nurses' monitoring stations, a Hospital or Clinical Information System (which may store Electronic Medical Records), and/or many other medical devices and systems. The translation module **2415** can enable seamless communication between different medical devices and systems, each of which may use a different implementation of an electronic medical communication protocol such as, for example, the HL7 communication protocol, within a clinical or hospital network environment.

In certain embodiments, the translation module **2415** can also facilitate communication between a first medical device that is part of the patient monitoring sub-system and a second medical device that is not part of, or is external to, the patient monitoring system **200**. As such, the translation module **2415** can be capable of responding to externally-generated medical messages (such as patient information update messages, status query messages, and the like from an HIS or CIS) and generating external reporting messages (such as event reporting messages, alarm notification messages, and the like from patient monitors or nurses' monitoring stations).

In another embodiment, first and second medical devices **2405**, **2410** communicate with each other over a communication bus **2421**. Communication bus **2421** can include any one or more of the communication networks, systems, and methods described above, including the Internet, a hospital WLAN, a LAN, a personal area network, etc. For example, any of the networks describe above can be used to facilitate communication between a plurality of medical devices, including first and second medical devices **2405**, **2410**, discussed above. One such embodiment is illustrated in FIG. **40B**.

In FIG. **40B**, first medical device **2405** provides a message to the communication bus **2421**. The message is intended for receipt by the second medical device **2410**; however, because first and second medical devices **2405**, **2410** communicate according to different communication protocol format, second medical device **2410** is unable to process the message.

Translation module **2415** monitors the communication bus **2421** for such messages. Translation module receives the message and determines that first medical device **2405** is attempting to communicate with second medical device **2410**. Translation module **2415** determines that message translation would facilitate communication between first and second medical devices **2405**, **2410**. Translation module **2415** therefore utilizes an appropriate translation rule stored in a translation module **2420**. Translation module **2420** can include a memory, EPROM, RAM, ROM, etc.

The translation module **2415** translates the message from the first medical device **2405** according to any of the methods described herein. Once translated, the translation module **2415** delivers the translated message to the communication bus **2421**. The second medical device **2410** receives the translated message and responds appropriately. For example, the second medical device may perform a function and/or attempt to communication with the first medical device **2405**. The translation module **2415** facilitates communication from the second medical device **2410** to the first medical device **2405** in a similar manner.

The first medical device **2405** and the second medical device **2410** can be, for example, any of the medical devices or systems communicatively coupled to a hospital network or hub **100**, PPM **102**, and/or MMS **2004**. These medical

devices or systems can include, for example, point-of-care devices (such as bedside patient monitors), data storage units or patient record databases, hospital or clinical information systems, central monitoring stations (such as a nurses' monitoring station), and/or clinician devices (such as pagers, cell phones, smart phones, personal digital assistants (PDAs), laptops, tablet PCs, personal computers, pods, and the like).

In some embodiments, the first medical device **2405** is a patient monitor for communicatively coupling to a patient for tracking a physiological parameter (e.g., oxygen saturation, pulse rate, blood pressure, etc.), and the second medical device **2410** is a hospital information system ("HIS") or clinical information system ("CIS"). In some embodiments, the patient monitor can communicate physiological parameter measurements, physiological parameter alarms, or other physiological parameter measurement information generated during the monitoring of a patient to the HIS or CIS for inclusion with the patient's electronic medical records maintained by the HIS or CIS.

In some embodiments, the first medical device **2405** is an HIS or CIS and the second medical device **2410** is a nurses' monitoring station, as described herein. However, the translation module **2415** can facilitate communication between a wide variety of medical devices and systems that are used in hospitals or other patient care facilities. For example, the translation module **2415** can facilitate communication between patient physiological parameter monitoring devices, between a monitoring device and a nurses' monitoring station, etc.

Using the translation module **2415**, a patient monitoring sub-system, such as those described herein (e.g., physiological monitoring system **200**), can push data to the HIS or pull data from the HIS even if the HIS uses a different implementation of the HL7 protocol, or some other electronic medical communication protocol.

In certain embodiments, the patient monitoring sub-system can be configured to push/pull data at predetermined intervals. For example, a patient monitor or clinician monitoring station can download patient data automatically from the HIS at periodic intervals so that the patient data is already available when a patient is connected to a patient monitor. The patient data sent from the HIS can include admit/discharge/transfer ("ADT") information received upon registration of the patient. ADT messages can be initiated by a hospital information system to inform ancillary systems that, for example, a patient has been admitted, discharged, transferred or registered, that patient information has been updated or merged, or that a transfer or discharge has been canceled.

In other embodiments, the patient monitoring sub-system can be configured to push/pull data to/from the HIS only when the HIS is solicited by a query. For example, a clinician may make a request for information stored in a patient's electronic medical records on the HIS.

In still other embodiments, the patient monitoring sub-system can be configured to push/pull data to/from the HIS in response to an unsolicited event. For example, a physiological parameter of a patient being monitored can enter an alarm condition, which can automatically be transmitted to the HIS for storing in the patient's electronic medical records. In yet other embodiments, any combination of the above methods or alternative methods for determining when to communicate messages to and from the HIS can be employed.

Example system architectures and example triggers for the communication of messages involving the translation

module **2415** have been described. Turning now to the operation of the translation module, FIGS. **25A-25D** illustrate an example medical message at different phases or steps of a translation process. The translation process will be described in more detail below in connection with FIGS. **26**, **27A** and **27B**.

FIG. **41A** illustrates an example ADT input message **2505** received by the translation module **2415** from an HIS. The ADT input message **2505** is implemented according to the HL7 communication protocol and contains information related to the admission of a patient to a hospital. The ADT message **2505** includes multiple segments, including a message header segment **2506**, an event segment, a patient identification segment, a patient visit segment, role segments, a diagnosis segment, and multiple custom segments.

In some embodiments, the message header (“MSH”) segment **2506** defines how the message is being sent, the field delimiters and encoding characters, the message type, the sender and receiver, etc. The first symbol or character after the MSH string can define the field delimiter or separator (in this message, a “caret” symbol). The next four symbols or characters can define the encoding characters. The first symbol defines the component delimiter (“~”), the second symbol defines the repeatable delimiter (“|”), the third symbol defines the escape delimiter (“\”), and the fourth symbol defines the sub-component delimiter (“&”). All of these delimiters can vary between HL7 implementations.

In some embodiments, the example header segment **2506** further includes the sending application (“VAFC PIMS”), the receiving application (“NPTF-508”), the date/time of the message (“20091120104609-0600”), the message type (“ADT~A01”), the message control ID (“58103”), the processing ID (“P”), and the country code (“USA”). As represented by the consecutive caret symbols, the header segment also contains multiple empty fields.

FIG. **41B** illustrates the message header segment **2506** after it has been parsed into fields or elements based on an identified field delimiter (the caret symbol). In certain embodiments, the parsed input message comprises an XML message that is configured to be transformed according to extensible stylesheet language transformation (XSLT) rules.

In certain embodiment, the parsed input message can be encoded. FIG. **41C** illustrates the parsed message header segment of the input message after being encoded (e.g., using a Unicode Transformation Format-8 (“UTF-8”) encoding scheme).

The encoded message header segment shows some of the various data types that can be used in the message. For example, the sending application (“VAFC PIMS”) of the third parsed field and the receiving application (“NPTF-508”) of the fifth parsed field are represented using a hierarchic designator (“HD”) name data type. The date/time field (the seventh parsed field) is represented using the time stamp (“TS”) data type. The processing ID field (the eleventh parsed field) is represented using the processing type (“PT”) data type. The fields that do not include a data type identifier are represented using the string (“ST”) data type. Other possible data types include, for example, coded element, structured numeric, timing quantity, text data, date, entry identifier, coded value, numeric, and sequence identification. The data types used for the various fields or attributes of the segments can vary between formatting implementations.

FIG. **41D** illustrates an example output message **2510** from the translation module **2415** based on the example

input message **2505** of FIG. **41A**. The output message **2510** includes a message acknowledgement segment **2512**.

Turning to the operation of the translation module, the translation module **2415** can, for example, create, generate, or produce an output message that is reflective of the input message based on an application of the set of translation rules **2420**. In some embodiments, the translation module **2415** can, for example, translate, transform, convert, reformat, configure, change, rearrange, modify, adapt, alter, or adjust the input message based on a comparison with, and application of, the set of translation rules **2420** to form the output message. In some embodiments, the translation module **2415** can, for example, replace or substitute the input message with an output message that retains the content of the input message but has a new formatting implementation based upon a comparison with, and application of, the set of translation rules **2420**.

FIG. **42** illustrates a translation process **2600** for generating an output message based on an input message and a comparison with the set of translation rules **2420** associated with the translation module **2415**. The translation process **2600** starts at block **2602** where the translation module **2415** receives an input message from a first medical device.

At block **2604**, the translation module **2415** determines the formatting implementation of the input message and the formatting implementation to be used for the output message. In certain embodiments, the input message can include one or more identifiers indicative of the formatting implementation. In some embodiments, the determination of the formatting implementation can be made, for example, by analyzing the message itself by identifying the delimiter or encoding characters used, the field order, the repeatability of segments, fields, or components, the data type of the fields, or other implementation variations. In certain embodiments, the translation module **2415** can separate or parse out the formatting from the content of the message (as shown in FIG. **41B**) to aid in the determination of the formatting implementation. In some embodiments, the translation module **2415** determines the formatting implementation of the input message by referencing a database that stores the implementation used by each device with which the translation module **2415** has been configured to interface.

In certain embodiments, the determination of the formatting implementation used by the output message can also be determined from the input message. For example, the input message can include a field that identifies the intended recipient application, facility, system, device, and/or destination. The input message can alternatively include a field that identifies the type of message being sent (e.g., ADT message) and the translation module **2415** can determine the appropriate recipient from the type of message being sent and/or the sending application, device, or system. The translation module **2415** can then determine the formatting implementation required by the intended recipient of the input message.

At decision block **2605**, the translation module **2415** determines whether a rule set has been configured for the translation from the identified formatting implementation of the input message to the identified formatting implementation to be used for the output message. The rule set may have been manually configured prior to installation of the translation module software or may have been automatically configured prior to receipt of the input message. If a rule set has already been configured, then the translation process **2600** continues to block **2606**. If a rule set has not been configured, then a rule set is configured at block **2607**. The configuration of the rule set can be performed as described



below in connection with FIGS. 44 and 45A-2459D. The translation process 2600 then continues to block 2608.

At block 2606, the translation module 2415 identifies the pre-configured rules from the set of translation rules 2420 that govern translation between the determined formatting implementation of the input message and the formatting implementation of the output message. In some embodiments, the identification of the pre-configured rules can be made manually.

At block 2608, the translation module 2415 generates an output message based on the configured rule set(s) of the translation rules 2420. In certain embodiments, the output message retains all, or at least a portion of, the content of the input message but has the format expected and supported by the intended recipient of the input message.

The translation rules 2420 can include, for example, unidirectional rules and/or bidirectional rules. A unidirectional rule can be one, for example, that may be applied in the case of a message from a first medical device (e.g., 2405) to a second medical device (e.g., 2410) but is not applied in the case of a message from the second medical device to the first medical device. For example, a unidirectional rule could handle a difference in the delimiters used between fields for two different formatting implementations of, for example, the HL7 communication protocol. The translation module 2415 can apply a field delimiter rule to determine if the field delimiter is supported by the intended recipient of the input message. If the field delimiter of the input message is not supported by the intended recipient, the field delimiter rule can replace the field delimiter of the input message with a field delimiter supported by the intended recipient.

For example, an input message from an input medical device can include a formatting implementation that uses a "caret" symbol ("A") as the field delimiter or separator. However, the formatting implementation recognized by the intended recipient medical device may use a "pipe" symbol ("I") as the field delimiter. The translation module 2415 can identify the field delimiter symbol used in the formatting implementation recognized by the intended recipient medical device from the set of translation rules 2420 and generate an output message based on the input message that uses the pipe field delimiter symbol instead of the caret field delimiter symbol used in the input message. The rule to substitute a pipe symbol for a caret symbol would, in this case, only apply to messages that are sent to a recipient device that recognizes the pipe symbol as a field delimiter. This rule could be accompanied by a complementary rule that indicates that a caret symbol should be substituted for a pipe symbol in the case of a message that is intended for a recipient device that is known to recognize the caret symbol as the field delimiter.

Another unidirectional rule can handle the presence or absence of certain fields between different formatting implementations. For example, an input message from an input medical device can include fields that would not be recognized by the intended recipient medical device. The translation module 2415 can generate an output message that does not include the unrecognized or unsupported fields. In situations where an input message does not include fields expected by the intended recipient medical device, the set of translation rules 2420 can include a rule to insert null entries or empty " " strings in the fields expected by the intended recipient medical device and/or to alert the recipient device of the absence of the expected field. The sender device may also be notified by the translation module 2415 that the recipient device does not support certain portions of the message.

Other unidirectional rules can facilitate, for example, the conversion of one data type to another (for example, string ("ST") to text data ("TX") or structured numeric ("SN") to numeric ("NM")), and the increase or decrease in the length of various portions of the message. Unidirectional rules can also be used to handle variations in repeatability of portions of the message. For example, the translation module 2415 can apply a field repeatability rule to repeated instances of a segment, field, component, or sub-component of the message to determine how many such repeated instances are supported by the recipient device, if any, and deleting or adding any repeated instances if necessary. For example, a phone number field of a patient identification segment can be a repeatable field to allow for entry of home, work, and cell phone numbers.

Bidirectional rules can also be used. Such rules may apply equally to messages between first and second medical devices (e.g., 2405, 2410) regardless of which device is the sender and which is the recipient. A bidirectional rule can be used to handle changes in sequence, for example. In certain implementations, an input message from an input medical device can include a patient name field, or fields, in which a first name component appears before a last name component. However, the intended recipient medical device may be expecting an implementation where the last name component appears before the first name component. Accordingly, the set of translation rules 2420 can include a bidirectional rule to swap the order of the first and last name components when communicating between the two medical devices, or between the two formatting implementations. In general, field order rules can be applied to determine whether the fields, components, or sub-components are in the correct order for the intended recipient and rearranging them if necessary. Other bidirectional rules can be included to handle, for example, other sequential variations between formatting implementations or other types of variations.

The translation rules 2420 can also include compound rules. For example, a compound rule can include an if-then sequence of rules, wherein a rule can depend on the outcome of another rule. Some translation rules 2420 may employ computations and logic (e.g., Boolean logic or fuzzy logic), etc.

As discussed above, the messages communicated over the hospital-based communication network can employ the HL7 protocol. FIGS. 43A and 43B illustrate translation processes 2700A, 2700B in which HL7 messages are communicated between a HIS and a medical device over a hospital-based communications network or a clinical network. The translation processes 2700A, 2700B will be described with the assumption that the rules governing "translation" between the first and second HL7 formats have already been configured.

FIG. 43A illustrates a translation process 2700A in which the translation module 2415 facilitates communication of an HL7 message, such as the ADT message of FIG. 41A, from an HIS having a first HL7 format to an intended recipient medical device, such as a patient monitor or a clinician monitoring station, having a second HL7 format.

The translation process 2700A starts at block 2701, where the translation module 2415 receives an input message having a first HL7 format from the HIS. In certain embodiments, the input message includes information regarding, for example, the admission of a patient and/or patient identification and patient medical history information from an electronic medical records database.

At block 2703, the translation module 2415 determines the formatting implementation of the input message and the

formatting implementation to be used for the output message. These determinations can be made in a similar manner to the determinations discussed above in connection with block 2604 of FIG. 42.

At block 2705, the translation module 2415 identifies the rules that govern translation between the determined HL7 format of the input message and the HL7 format of the output message and generates an output message having the second HL7 format based on the identified rules. In certain embodiments, the output message retains the content of the input message sent by the HIS but has the format expected and supported by the intended recipient of the input message.

At block 2707, the translation module 2415 can output the output message to the intended recipient over the hospital-based communications network. In certain embodiments, the intended recipient can transmit an acknowledgement message back to the hospital information system acknowledging successful receipt or reporting that an error occurred.

FIG. 43B illustrates a translation process 2700B in which the translation module 2415 facilitates communication of an HL7 message from a medical device, such as a patient monitor, having a first HL7 format to an HIS having a second HL7 format. For example, the patient monitor can transmit reporting event data such as patient alarm data, to the HIS to store in the patient's electronic medical records.

The translation process 2700B starts at block 2702, where the translation module 2415 receives an input message having a first HL7 format from the medical device. In certain embodiments, the input message includes patient monitoring data or alarm data regarding one or more physiological parameters of the patient being monitored for storage in an electronic medical records database associated with the HIS.

At block 2704, the translation module 2415 determines the formatting implementation of the input message and the formatting implementation to be used for the output message. These determinations can be made in a similar manner to the determinations discussed above in connection with block 2604 of FIG. 42.

At block 2706, the translation module 2415 identifies the rules that govern translation between the determined HL7 format of the input message and the HL7 format of the output message and generates an output message having the second HL7 format based on the identified rules. In certain embodiments, the output message retains the content of the input message sent by the medical device but has the format expected and supported by the HIS.

At block 2708, the translation module 2415 can output the output message to the hospital information system over the hospital-based communications network. In certain embodiments, the HIS can transmit an acknowledgement message back to the medical device acknowledging successful receipt or reporting that an error occurred.

FIGS. 42, 43A and 43B described the operation of the translator module 2415. FIGS. 44 and 45A-45D will be used to illustrate the description of the configuration of the translation rules 2420.

The translation rules 2420 can be implemented as one or more stylesheets, hierarchical relationship data structures, tables, lists, other data structures, combinations of the same, and/or the like. In certain embodiments, the translation rules 2420 can be stored in local memory within the translation module 2415. In other embodiments, the translation rules 2420 can be stored in external memory or on a data storage device communicatively coupled to the translation module 2415.

The translation module 2415 can include a single rule set or multiple rule sets. For example, the translation module 2415 can include a separate rule set for each medical device/system and/or for each possible communication pair of medical devices/systems coupled to the network or capable of being coupled to the network. In some embodiments, the translation module 2415 can include a separate rule set for each possible pair of formatting implementations that are allowed under a medical communication protocol such as, for example, the HL7 protocol.

In certain embodiments, the translation rules 2420 can be manually inputted using, for example, the messaging implementation software tool 2800 illustrated in FIG. 44. For example, the software developer for a particular hospital network can determine the protocol message formats used by the devices and/or systems that are or can be coupled to the hospital network and then manually input rules to facilitate "translation" between the various protocol message formats supported or recognized by the devices and/or systems.

FIG. 44 illustrates an example screenshot from a messaging implementation software tool 2800 for manually configuring translation rules 2420 to be used by the translation module 2415. The screenshot from the messaging implementation software tool 2800 illustrates various parameters that may differ between formatting implementations of an electronic medical communication protocol, such as HL7. The screenshot also includes areas where a user can input information that defines, or is used to define, translation rules for converting between different HL7 implementations. In some embodiments, the messaging implementation software tool 2800 stores a variety of pre-configured rule sets based, for example, on known communication protocol implementations of various medical devices. In such embodiments, a user may configure one or more translation rules 2420 to be used in communications involving such devices by entering identification information, such as the device manufacturer, model number, etc. Based on this identification information, the messaging implementation tool 2800 can identify a pre-configured set of translation rules for communication with that device.

In other embodiments, the translation rules 2420 can be automatically generated. For example, the automatic generation of a new set, or multiple sets, of rules can be triggered by the detection of a newly recognized "communicating" medical device or system on a network. In certain embodiments, the automatic generation of a new set or multiple sets of rules can occur at the time a first message is received from or sent to a new "communicating" medical device or system coupled to the network. In still other embodiments, the automatic generation of rule sets includes updating or dynamically modifying a pre-existing set of rules.

The automatic generation of translation rule sets can be carried out in a variety of ways. For example, in some embodiments, the translation module 2415 can automatically initiate usage of a pre-configured set of translation rules 2420 based upon, for example, the make and model of a new device that is recognized on the network. In certain embodiments, the translation module 2415 can request one or more messages from the new device or system and then analyze the messages to determine the type of formatting being implemented, as illustrated by the automatic rule configuration process 2900A of FIG. 45A. The automatic rule configuration process 2900A starts at block 2901, where the translation module 2415 receives one or more messages from a detected medical device or system on the network.

The messages can be received upon transmission to an intended recipient medical device or system or in response to a query sent by the translation module **2415** or another medical device or system coupled to the network.

At block **2903**, the translation module **2415** determines the protocol of the one or more received messages by, for example, analyzing the message or by consulting a database that indicates what communication protocol/format is implemented by each medical device or system on the network. In certain embodiments, the translation module **2415** is configured to handle medical messages implemented using a single common protocol, such as HL7. Accordingly, if a determination is made that the received messages are implemented using a non-supported or non-recognized protocol, the translation module can ignore the messages received from the detected medical device or system, output an alert or warning, or allow the messages to be sent without being translated.

At block **2905**, the translation module **2415** determines the formatting implementation of the received message(s). In certain embodiments, the received messages can include one or more identifiers indicative of the formatting implementation. In other embodiments, the determination of the formatting implementation can be made, for example, by analyzing the message itself by checking field order, the delimiter or encoding characters used, or other implementation variations. In certain embodiments, the translation module **2415** can separate or parse out the formatting from the content of the message to aid in the determination of the formatting implementation.

At block **2907**, the translation module **2415** configures one or more rules or rule sets to handle messages received from and/or sent to the detected medical device or system. In certain embodiments, the configuration of the rules involves the creation or generation of new rules. In other embodiments, the configuration of the rules involves the alteration or updating of existing rules. The configured rules or rule sets can be included with the translation rules **2420**. If a set of rules already exists for the formatting implementation used by the new device or system, then the configuration of new translation rules may not be required. Instead, existing translation rules can be associated with the new device or system for use in communication involving that device or system. In other embodiments, the translation module **2415** can create a new set of rules geared specifically for the new device or system or can modify an existing set of rules based on subtle formatting variations identified.

In other embodiments, the translation module **2415** can generate test message(s) that may be useful in identifying the communication protocol and implementation used by a device or system. For example, the translation module can generate test messages to cause the newly detected device or system to take a particular action (e.g., store information) and then query information regarding the action taken by the newly detected device to determine whether or how the test message was understood. This is illustrated by the automatic rule configuration process **2900B** of FIG. **45B**.

The automatic rule configuration process **2900B** starts at block **2902**, where the translation module **2415** transmits one or more test, or initialization, messages to a remote device or system detected on a network. The test messages can be configured, for example, to instruct the remote device or system to take a particular action (e.g., store patient information). In certain embodiments, the test messages can be configured to generate a response indicative of the type of formatting recognized or supported by the remote device or system. In other embodiments, the test messages can be

configured such that only devices or systems supporting a particular formatting implementation will understand and properly act on the test messages.

At block **2904**, the translation module **2415** queries the remote device or system to receive information regarding the action taken based on the test message sent to the remote device or system to determine whether the test message was understood. For example, if the test message instructed the remote device or system to store patient information in a particular location, the translation module **2415** can query the information from the location to determine whether the test message was understood. If the test message was not understood, the translation module **2415** can, for example, continue sending test messages of known formatting implementations until a determination is made that the test message has been understood.

At block **2906**, the translation module **2415** determines the protocol and formatting implementation based on the information received. As an example, in certain embodiments, the test message can include an instruction to store patient name information. The test message can include a patient name field having a first name component followed by a surname component. The translation module **2415** can then query the remote device or system to return the patient surname. Depending on whether the patient surname or the first name is returned, this query can be useful in determining information about the order of fields in the formatting implementation being used by the remote device or system. As another example, the test messages can instruct the detected device or system to store repeated instances of a component. The translation module **2415** can then query the device or system to return the repeated instances to see which, if any, were stored. This repeatability information can also be useful in determining whether certain fields are allowed to be repeated in the formatting implementation being used by the remote device for system, and, if so, how many repeated instances are permitted.

At block **2908**, the translation module **2415** configures one or more rules to handle messages received from and/or sent to the detected medical device or system. For example, the rules can convert messages from the message format used by a first medical device to that used by a second medical device, as described herein. In certain embodiments, the configuration of the rules involves the creation or generation of new rules. In other embodiments, the configuration of the rules involves the alteration or updating of existing rules. If a set of rules already exists for the formatting implementation used by the new device or system, then the configuration of new translation rules may not be required. Instead, existing translation rules can be associated with the new device or system for use in communication involving that device or system.

FIGS. **29C** and **29D** illustrate automatic rule configuration processes performed by the translation module **2415** for messages utilizing the HL7 protocol. The HL7 protocol can be used, for example, to communicate electronic messages to support administrative, logistical, financial, and clinical processes. For example, HL7 messages can include patient administration messages, such as ADT messages, used to exchange patient demographic and visit information across various healthcare systems.

The automatic rule configuration process **2900C** illustrated in FIG. **45C** is similar to the process **2900A** illustrated in FIG. **45A**. At block **2911**, the translation module **2415** receives one or more messages from an HL7 medical device. At block **2915**, the translation module **2415** determines the formatting implementation of the HL7 medical device from

the one or more messages received. As discussed above, the determination of the formatting implementation can be made, for example, by checking field order or sequence, field delimiter characters, repeatability, cardinality, and other HL7 implementation variations.

At block **2917**, the translation module **2415** configures one or more rules to handle messages received from and/or sent to the HL7 medical device. In certain embodiments, the configuration of the rules involves the creation or generation of new rules for the detected formatting implementation. In other embodiments, the configuration of the rules involves the dynamic alteration or updating of existing rules. If a set of rules already exists for the formatting implementation used by the new HL7 medical device, then the configuration of new translation rules may not be required. Instead, existing translation rules can be associated with the new HL7 medical device for use in communication involving that device.

The automatic rule configuration process **2900D** illustrated in FIG. **45D** is similar to the process **2900B** illustrated in FIG. **45B**. At block **2912**, the translation module **2415** transmits one or more test, dummy, or initialization messages to an HL7 medical device. In other embodiments, the translation module **2415** can cause one or more test messages to be transmitted to the new HL7 medical device from another HL7 medical device. As described above, the test messages can include messages having known HL7 formats configured to determine whether the HL7 device understands the test messages. The test messages can include test ADT messages, for example.

At block **2914**, the translation module **2415** queries the HL7 medical device to receive information regarding an action taken or information stored in response to the test message. At block **2916**, the translation module **2415** determines the formatting implementation of the HL7 device based on the information received. In certain embodiments, the translation module **2415** can analyze the information received to determine whether the test message or messages were properly understood. If none of the test messages were properly understood, the translation module **2415** can send additional test messages having other known HL7 formats and repeat blocks **2914** and **2916**.

At block **2918**, the translation module **2415** configures one or more translation rules to handle messages received from and/or sent to the detected HL7 medical device. In certain embodiments, the configuration of the translation rules involves the creation or generation of new translation rules. In other embodiments, the configuration of the rules involves the alteration or updating of existing rules. If a set of translation rules already exists for the formatting implementation used by the new HL7 medical device, then the configuration of new translation rules may not be required. Instead, existing translation rules can be associated with the new HL7 medical device for use in communication involving that HL7 medical device.

The automatic rule configuration processes described above can be triggered by the detection of a network device or system by the translation module **2415**. The medical devices referred to in FIGS. **45A-45D** can include any of the devices or systems illustrated in FIG. **1** or **24**.

In some embodiments, the automatic generation of translation rules can advantageously occur post-installation and post-compilation of the messaging sub-system software, which includes the translation module **2415**. In certain embodiments, the automatic generation or dynamic modification of the translation rules **2420** can occur without having to recompile or rebuild the translation module soft-

ware. This feature can be advantageous in terms of efficiently complying with U.S. Food and Drug Administration ("FDA") requirements regarding validation of software used in healthcare environments.

Take, for example, a situation where a medical device manufacturer plans to use the translation module **2415** to facilitate communication between a particular medical device or system that is to be installed in a hospital (e.g., a patient monitoring system, as described herein), or other patient care facility, and other devices or systems that are already installed at the hospital (e.g., the HIS or CIS). Any software required for the operation of the new medical device to be installed may be at least partially validated for FDA compliance prior to installation at the hospital despite the fact that, for example, the HL7 implementations of other existing devices or systems at the hospital may still be unknown. For example, any aspects of the software for the new medical device that are dependent upon receiving messages from other hospital devices can be validated pre-installation as being capable of fully and correctly operating when the expected message format is received. Then, once the medical device is installed at the hospital, the validation of the software can be completed by showing that the translation module **2415** is able to provide messages of the expected format to the newly installed device. In this way, FDA validation tasks can be apportioned to a greater extent to the pre-installation timeframe where they can be more easily carried out in a controlled manner rather than in the field.

In addition, the translation module **2415** can further help streamline FDA validation, for example, when a medical device or system is expected to be installed at different hospitals whose existing devices use, for example, different implementations of the HL7 protocol. Normally, this type of situation could impose the requirement that the entire functionality of the software for the new medical device be completely validated at each hospital. However, if the translation module **2415** is used to interface between the new medical device and the hospital's existing devices, then much of the software functionality could possibly be validated a single time prior to installation, as just described. Then, once installed at each hospital, the software validation for the medical device can be completed by validating that correct message formats are received from the translation module (the translation rules for which are field-customizable). This may result in making on-site validation procedures significantly more efficient, which will advantageously enable more efficient FDA compliance in order to bring life-saving medical technology to patients more quickly by the use of field-customizable translation rules.

#### V. Example Embodiments

In certain embodiments, a system for providing medical data translation for output on a medical monitoring hub can include a portable physiological monitor comprising a processor that can: receive a physiological signal associated with a patient from a physiological sensor, calculate a physiological parameter based on the physiological signal, and provide a first value of the physiological parameter to a monitoring hub for display. The monitoring hub can include a docking station that can receive the portable physiological monitor. The monitoring hub can: receive the first value of the physiological parameter from the portable physiological monitor; output the first value of the physiological parameter for display; receive physiological parameter data from a medical device other than the portable physiological monitor, the physiological parameter data formatted according to a protocol other than a protocol natively readable or dis-

playable by the monitoring hub; pass the physiological parameter data to a translation module; receive translated parameter data from the translation module, where the translated parameter data can be readable and displayable by the monitoring hub; and output a second value from the translated parameter data for display.

The system of the preceding paragraph can be combined with any subcombination of the following features: the monitoring hub is further configured to output the first value of the physiological parameter and the second value from the translated parameter data on separate displays; the monitoring hub is further configured to output the second value from the translated parameter data to an auxiliary device having a separate display from a display of the monitoring hub; the auxiliary device is selected from the group consisting of a television, a tablet, a phone, a wearable computer, and a laptop; the physiological parameter data comprises data from an infusion pump; the physiological parameter data comprises data from a ventilator; and the translation module is configured to translate the physiological parameter data from a first Health Level 7 (HL7) format to a second HL7 format.

In certain embodiments, a method of providing medical data translation for output on a medical monitoring hub can include: under the control of a first medical device comprising digital logic circuitry, receiving a physiological signal associated with a patient from a physiological sensor; obtaining a first physiological parameter value based on the physiological signal; outputting the first physiological parameter value for display; receiving a second physiological parameter value from a second medical device other than the first medical device, where the second physiological parameter value is formatted according to a protocol not used by the first medical device, such that the first medical device is not able to process the second physiological parameter value to produce a displayable output value; passing the physiological parameter data from the first medical device to a separate translation module; receiving translated parameter data from the translation module at the first medical device, the translated parameter data able to be processed for display by the first medical device; and outputting a second value from the translated parameter data for display.

The method of the preceding paragraph can be combined with any subcombination of the following features: further including translating the message by at least translating the message from a first Health Level 7 (HL7) format to a second HL7 format; the message can include data from a physiological monitor; the message can include data from an infusion pump or a ventilator; and the message can include data from a hospital bed.

In certain embodiments, a system for providing medical data translation for output on a medical monitoring hub can include a first medical device including electronic hardware that can: obtain a first physiological parameter value associated with a patient; output the first physiological parameter value for display; receive a second physiological parameter value from a second medical device other than the first medical device, the second physiological parameter value formatted according to a protocol not used by the first medical device, such that the first medical device is not able to process the second physiological parameter value to produce a displayable output value; pass the physiological parameter data from the first medical device to a translation module; receive translated parameter data from the translation module at the first medical device, the translated param-

eter data able to be processed for display by the first medical device; and output a second value from the translated parameter data for display.

The system of the preceding paragraph can be combined with any subcombination of the following features: the first medical device can also output the first value of the physiological parameter and the second value from the translated parameter data on the same display; the first medical device can also output the first value of the physiological parameter and the second value from the translated parameter data on separate displays; the first medical device can also output the second value from the translated parameter data to an auxiliary device; the auxiliary device can be a television monitor; the auxiliary device can be selected from the group consisting of a tablet, a phone, a wearable computer, and a laptop; the first medical device can include the translation module; the first medical device can also pass the physiological parameter data to the translation module over a network; and the physiological parameter data can include data from an infusion pump or a ventilator.

#### VI. Terminology

Many other variations than those described herein will be apparent from this disclosure. For example, depending on the embodiment, certain acts, events, or functions of any of the algorithms described herein can be performed in a different sequence, can be added, merged, or left out altogether (e.g., not all described acts or events are necessary for the practice of the algorithms). Moreover, in certain embodiments, acts or events can be performed concurrently, e.g., through multi-threaded processing, interrupt processing, or multiple processors or processor cores or on other parallel architectures, rather than sequentially. In addition, different tasks or processes can be performed by different machines and/or computing systems that can function together.

It is to be understood that not necessarily all such advantages can be achieved in accordance with any particular embodiment of the embodiments disclosed herein. Thus, the embodiments disclosed herein can be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

The various illustrative logical blocks, modules, and algorithm steps described in connection with the embodiments disclosed herein can be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. The described functionality can be implemented in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the disclosure.

The various illustrative logical blocks and modules described in connection with the embodiments disclosed herein can be implemented or performed by a machine, such as a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor can be a microprocessor, but in the alternative, the processor can be a controller, microcontroller, or state

machine, combinations of the same, or the like. A processor can include electrical circuitry or digital logic circuitry configured to process computer-executable instructions. In another embodiment, a processor includes an FPGA or other programmable device that performs logic operations without processing computer-executable instructions. A processor can also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. A computing environment can include any type of computer system, including, but not limited to, a computer system based on a microprocessor, a mainframe computer, a digital signal processor, a portable computing device, a device controller, or a computational engine within an appliance, to name a few.

The steps of a method, process, or algorithm described in connection with the embodiments disclosed herein can be embodied directly in hardware, in a software module stored in one or more memory devices and executed by one or more processors, or in a combination of the two. A software module can reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of non-transitory computer-readable storage medium, media, or physical computer storage known in the art. An example storage medium can be coupled to the processor such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium can be integral to the processor. The storage medium can be volatile or nonvolatile. The processor and the storage medium can reside in an ASIC.

Conditional language used herein, such as, among others, “can,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or states. Thus, such conditional language is not generally intended to imply that features, elements and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment. The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. Further, the term “each,” as used herein, in addition to having its ordinary meaning, can mean any subset of a set of elements to which the term “each” is applied.

Disjunctive language such as the phrase “at least one of X, Y, or Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to present that an item, term, etc., may be either X, Y, or Z, or any combination thereof (e.g., X, Y, and/or Z). Thus, such disjunctive language is not generally intended to, and should not, imply that certain embodiments require at least one of X, at least one of Y, or at least one of Z to each be present.

Unless otherwise explicitly stated, articles such as “a” or “an” should generally be interpreted to include one or more described items. Accordingly, phrases such as “a device configured to” are intended to include one or more recited

devices. Such one or more recited devices can also be collectively configured to carry out the stated recitations. For example, “a processor configured to carry out recitations A, B and C” can include a first processor configured to carry out recitation A working in conjunction with a second processor configured to carry out recitations B and C.

While the above detailed description has shown, described, and pointed out novel features as applied to various embodiments, it will be understood that various omissions, substitutions, and changes in the form and details of the devices or algorithms illustrated can be made without departing from the spirit of the disclosure. As will be recognized, certain embodiments of the inventions described herein can be embodied within a form that does not provide all of the features and benefits set forth herein, as some features can be used or practiced separately from others.

Additionally, all publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference.

What is claimed is:

1. A system for providing medical data for display on a medical monitoring hub, the system comprising:
  - a first medical device comprising a processor configured to:
    - receive a physiological signal associated with a patient from a physiological sensor;
    - calculate first physiological parameter data based on the physiological signal; and
    - provide the first physiological parameter data to a monitoring hub; and
  - the monitoring hub configured to:
    - receive the first physiological parameter data from the first medical device;
    - receive second physiological parameter data from a second medical device, wherein the second physiological parameter data is formatted according to a protocol other than a protocol natively readable or displayable by the monitoring hub;
    - translate the second physiological parameter data to be readable and displayable by the monitoring hub;
    - receive measurement synchronization data associated with the second medical device;
    - determine, based at least in part on the measurement synchronization data, a time-wise synchronization of the first physiological parameter data and the second physiological parameter data; and
    - display physiological parameter measurements based on the first physiological parameter data and the second physiological parameter data, wherein the physiological parameter measurements are time-wise synchronized.
2. The system of claim 1, wherein the monitoring hub is further configured to output the physiological parameter measurements to an auxiliary device having a separate display from a display of the monitoring hub.
3. The system of claim 2, wherein the auxiliary device is at least one of: a television, a tablet, a phone, a wearable computer, or a laptop.
4. The system of claim 3, wherein the monitoring hub is further configured to output the physiological parameter measurements to the auxiliary device for display on the separate display of the auxiliary device in an interactive user interface.

## 45

5. The system of claim 4, wherein the interactive user interface comprises interactive controls for adjusting physiological parameter alarm limits.

6. The system of claim 5, wherein the physiological parameter measurements are organized in the interactive user interface according to sources of the first physiological parameter data and the second physiological parameter data.

7. The system of claim 6, wherein the physiological parameter measurements in the interactive user interface are highlighted based on alarm conditions or other patient wellness indicators.

8. The system of claim 7, wherein highlighting the physiological parameter measurements comprises coloring the portions of the physiological parameter measurements.

9. The system of claim 1, wherein the measurement synchronization data comprises measurement delay information.

10. The system of claim 1, wherein the monitoring hub is further configured to translate the second physiological parameter data by:

passing the second physiological parameter data to a translation module separate from the monitoring hub; and

receiving translated second physiological parameter data from the translation module.

11. The system of claim 1, wherein the second physiological parameter data is translated from a first Health Level 7 (HL7) format to a second HL7 format.

12. The system of claim 1, wherein the second medical device comprises at least one of: an infusion pump or a ventilator.

13. The system of claim 1, wherein the monitoring hub is further configured to:

display an interactive user interface including the physiological parameter measurements, wherein:

at least some of the physiological parameter measurements are displayed as waveforms,

the waveforms are interactive and zoomable, and

the waveforms are time-wise synchronized and stackable on one another to display multiple overlapping waveforms within a same area of the interactive user interface.

14. The system of claim 13, wherein the interactive user interface comprises interactive controls for adjusting physiological parameter alarm limits.

15. A medical monitoring hub for displaying medical data, the medical monitoring hub comprising:

one or more processors configured to execute software instructions to cause the medical monitoring hub to:

receive first physiological parameter data from a first medical device;

receive second physiological parameter data from a second medical device, wherein the second physiological parameter data is formatted according to a protocol other than a protocol natively readable or displayable by the monitoring hub;

translate the second physiological parameter data to be readable and displayable by the monitoring hub;

receive measurement synchronization data associated with the second medical device;

determine, based at least in part on the measurement synchronization data, a time-wise synchronization of the first physiological parameter data and the second physiological parameter data; and

display physiological parameter measurements based on the first physiological parameter data and the

## 46

second physiological parameter data, wherein the physiological parameter measurements are time-wise synchronized.

16. The medical monitoring hub of claim 15, wherein the monitoring hub is further configured to output the physiological parameter measurements to an auxiliary device having a separate display from a display of the monitoring hub.

17. The medical monitoring hub of claim 16, wherein the auxiliary device is at least one of: a television, a tablet, a phone, a wearable computer, or a laptop.

18. The medical monitoring hub of claim 17, wherein: the monitoring hub is further configured to output the physiological parameter measurements to the auxiliary device for display on the separate display of the auxiliary device in an interactive user interface, the interactive user interface comprises interactive controls for adjusting physiological parameter alarm limits, and

the physiological parameter measurements are organized in the interactive user interface according to sources of the first physiological parameter data and the second physiological parameter data.

19. A method of providing medical data for display on a medical monitoring hub, the method comprising:

under the control of one or more processors comprising digital logic circuitry,

receiving first physiological parameter data from a first medical device;

receiving second physiological parameter data from a second medical device, wherein the second physiological parameter data is formatted according to a protocol other than a protocol natively readable or displayable by the monitoring hub;

translating the second physiological parameter data to be readable and displayable by the monitoring hub;

receiving measurement synchronization data associated with the second medical device;

determining, based at least in part on the measurement synchronization data, a time-wise synchronization of the first physiological parameter data and the second physiological parameter data; and

displaying physiological parameter measurements based on the first physiological parameter data and the second physiological parameter data, wherein the physiological parameter measurements are time-wise synchronized.

20. The method of claim 19 further comprising: further under the control of the one or more processors comprising digital logic circuitry,

outputting the physiological parameter measurements to an auxiliary device having a separate display from a display of the monitoring hub, wherein the auxiliary device is at least one of: a television, a tablet, a phone, a wearable computer, or a laptop.

21. The method of claim 20 further comprising: further under the control of the one or more processors comprising digital logic circuitry,

outputting the physiological parameter measurements to the auxiliary device for display on the separate display of the auxiliary device in an interactive user interface, wherein:

the interactive user interface comprises interactive controls for adjusting physiological parameter alarm limits, and

the physiological parameter measurements are organized in the interactive user interface according to sources of the first physiological parameter data and the second physiological parameter data.

\* \* \* \* \*