



US010518914B2

(12) **United States Patent**
Neeser et al.

(10) **Patent No.:** **US 10,518,914 B2**
(45) **Date of Patent:** **Dec. 31, 2019**

(54) **STRAPPING DEVICE**

(71) Applicant: **Signode Industrial Group LLC**,
Glenview, IL (US)

(72) Inventors: **Mirco Neeser**, Ehrendingen (CH);
Roland Widmer, Bremgarten (CH);
Flavio Finzo, Wurenlos (CH)

(73) Assignee: **Signode Industrial Group LLC**,
Glenview, IL (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1107 days.

(21) Appl. No.: **14/918,167**

(22) Filed: **Oct. 20, 2015**

(65) **Prior Publication Data**
US 2016/0046398 A1 Feb. 18, 2016

Related U.S. Application Data

(63) Continuation of application No. 12/989,112, filed as
application No. PCT/CH2009/000001 on Jan. 6,
(Continued)

(30) **Foreign Application Priority Data**

Apr. 23, 2008 (CH) 645/08
Apr. 23, 2008 (CH) 646/08
(Continued)

(51) **Int. Cl.**
B65B 13/18 (2006.01)
B65B 13/32 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B65B 13/187** (2013.01); **B65B 13/025**
(2013.01); **B65B 13/22** (2013.01); **B65B**
13/322 (2013.01)

(58) **Field of Classification Search**

CPC B65B 13/32; B65B 13/322; B65B 13/327;
B65B 13/22; B65B 13/02; B65B 13/025;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,013,589 A 12/1961 Holford
3,367,374 A 2/1968 Meier et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2 432 353 12/2003
CH 705 745 5/2013
(Continued)

OTHER PUBLICATIONS

Intellectual Property India, Examination Report in Corresponding
Pending Indian Application No. 6713/CHENP/2010 dated Jan. 15,
2018 (7 pages).


(Continued)

Primary Examiner — Jimmy T Nguyen

(74) *Attorney, Agent, or Firm* — Neal, Gerber &
Eisenberg LLP

(57) **ABSTRACT**

A strapping device including a tensioner operable to apply a
strap tension to a loop of wrapping strap, a friction welder
operable to produce a friction weld connection at two areas
of the loop of wrapping strap disposed one on top of the
other, a motor operable in a first rotational direction to drive
the tensioner and in a second opposite rotational direction to
drive the friction welder, and a control device. The control
device is configured to, in response to receiving a first
designated input: (1) operate the motor in the first rotational
direction to drive the tensioner until a predetermined strap
tension is reached in the loop of wrapping strap; and (2)
afterwards, automatically operate the motor in the second
(Continued)



different rotational direction to drive the friction welder to produce the friction weld connection.

34 Claims, 9 Drawing Sheets

Related U.S. Application Data

2009, now Pat. No. 9,174,752, application No. 14/918,167, which is a continuation of application No. 12/989,142, filed as application No. PCT/CH2009/000002 on Jan. 6, 2009, now Pat. No. 9,284,080, application No. 14/918,167, which is a continuation of application No. 12/989,181, filed as application No. PCT/CH2009/000003 on Jan. 6, 2009, now Pat. No. 9,315,283, application No. 14/918,167, which is a continuation of application No. 12/989,281, filed as application No. PCT/CH2009/000004 on Jan. 6, 2009, now Pat. No. 9,193,486, application No. 14/918,167, which is a continuation of application No. 12/989,355, filed as application No. PCT/CH2009/000005 on Jan. 6, 2009, now Pat. No. 9,254,932.

(30) Foreign Application Priority Data

Apr. 23, 2008 (CH) 647/08
Apr. 23, 2008 (CH) 648/08
Apr. 23, 2008 (CH) 649/08

(51) Int. Cl.

B65B 13/22 (2006.01)
B65B 13/02 (2006.01)

(58) Field of Classification Search

CPC B65B 13/18; B65B 13/187; B65B 13/24;
B65B 13/30; B65B 13/305; B29C
66/1122; B29C 66/4324; B29C 66/344;
B29C 66/8324; B29C 66/8618
USPC 100/29, 32; 58/589; 53/399, 582, 589;
156/73.5
See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,442,733 A 5/1969 Vilcins
3,586,572 A 6/1971 Ericsson
3,654,033 A 4/1972 Angarola et al.
3,674,972 A 7/1972 Stahnke
3,755,045 A 8/1973 Takami
4,011,807 A 3/1977 Kobiella
4,015,643 A 4/1977 Cheung
4,037,073 A 7/1977 Becker
4,050,372 A 9/1977 Kobiella
4,079,667 A 3/1978 Lems et al.
4,080,082 A 3/1978 Angarola
4,161,910 A 7/1979 Leslie et al.
4,240,865 A 12/1980 Kyts
4,305,774 A * 12/1981 Wedeking B65B 13/327
156/494
4,313,779 A 2/1982 Nix
4,450,032 A 5/1984 Wehr
4,488,926 A 12/1984 Rauch et al.
4,495,972 A 1/1985 Walker
4,516,488 A 5/1985 Bartzick et al.
4,534,817 A 8/1985 O'Sullivan
4,535,730 A 8/1985 Allen
4,572,064 A 2/1986 Burton et al.
4,707,390 A 11/1987 Cheung

4,776,905 A 10/1988 Cheung et al.
4,820,363 A 4/1989 Fischer
4,912,912 A 4/1990 Tagomori
4,952,271 A 8/1990 Cheung et al.
5,083,412 A 1/1992 Sakaki et al.
5,133,532 A 7/1992 Figiel et al.
5,140,126 A 8/1992 Ishibashi
5,141,591 A 8/1992 Boek et al.
5,146,847 A 9/1992 Lyon et al.
5,155,982 A 10/1992 Boek et al.
5,159,218 A 10/1992 Murry et al.
5,165,532 A 11/1992 Pipich et al.
5,226,461 A 7/1993 Macartney et al.
5,299,407 A 4/1994 Schuttler et al.
5,333,438 A 8/1994 Gurak et al.
5,350,472 A 9/1994 Koblella
5,379,576 A 1/1995 Koyama et al.
5,380,393 A 1/1995 Drabarek et al.
5,509,594 A 4/1996 Maggioni
5,516,022 A 5/1996 Annis, Jr.
5,560,187 A 10/1996 Nagashima et al.
5,653,059 A * 8/1997 Wecke E05D 1/04
16/260
5,653,095 A 8/1997 Stamm
5,689,943 A 11/1997 Wehr
5,690,023 A 11/1997 Stamm et al.
5,791,238 A 8/1998 Garbotz
5,798,596 A 8/1998 Lordo
5,809,873 A 9/1998 Chak et al.
5,853,524 A 12/1998 Nix
5,880,424 A 3/1999 Katoh
5,944,064 A 8/1999 Saito et al.
5,947,166 A 9/1999 Doyle et al.
5,954,899 A * 9/1999 Figiel B65B 13/327
100/33 PB
6,003,578 A 12/1999 Chang
6,032,440 A 3/2000 Luedtke
6,041,698 A 3/2000 Chin-Chang et al.
6,109,325 A 8/2000 Chang
6,131,634 A 10/2000 Chang
6,145,286 A 11/2000 Huber
6,173,557 B1 1/2001 Kuei
6,260,337 B1 7/2001 Cheung
6,305,277 B1 10/2001 Witezak et al.
6,308,745 B1 10/2001 Angarola et al.
6,308,760 B1 10/2001 Finzo et al.
6,328,087 B1 12/2001 Finzo et al.
6,332,306 B1 12/2001 Finzo et al.
6,334,563 B1 1/2002 Schwede
6,338,184 B1 1/2002 Angarola et al.
6,338,375 B1 1/2002 Harada
6,345,648 B1 2/2002 Cheung
6,401,764 B1 6/2002 Bell
6,405,766 B1 6/2002 Benjey
6,405,917 B1 6/2002 Mann
6,463,848 B1 10/2002 Haberstroh et al.
6,478,065 B1 11/2002 Haberstroh et al.
6,516,715 B1 2/2003 Reiche
6,532,722 B2 3/2003 Gerhart et al.
6,533,013 B1 3/2003 Nix
6,543,341 B2 4/2003 Lopez
6,568,158 B2 5/2003 Shibazaki et al.
6,571,531 B2 6/2003 Kasel
6,575,086 B2 6/2003 Pearson et al.
6,578,337 B2 6/2003 Scholl et al.
6,584,891 B1 7/2003 Smith et al.
6,584,892 B2 7/2003 Flaum et al.
6,606,766 B2 8/2003 Ko
6,607,158 B1 8/2003 Fischer
6,629,398 B2 10/2003 Pearson et al.
6,644,713 B2 11/2003 Del Pozo Abejon et al.
6,668,516 B2 12/2003 Sakaki et al.
6,698,460 B2 3/2004 Marsche
6,708,606 B1 3/2004 Bell et al.
6,715,375 B2 4/2004 Nestler
6,729,357 B2 5/2004 Marsche
6,732,638 B1 5/2004 Rometty et al.
6,745,677 B2 6/2004 Pearson et al.
6,817,159 B2 11/2004 Sakaki et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,820,402 B1 11/2004 Haberstroh et al.
 6,848,239 B2 2/2005 Shibazaki et al.
 6,848,241 B2 2/2005 Lopez
 6,857,252 B2 2/2005 Haberstroh et al.
 6,871,584 B2 3/2005 Pearson
 6,904,841 B2 6/2005 Bobren et al.
 6,907,717 B2 6/2005 Nix
 6,911,799 B2 6/2005 Jensen
 6,918,235 B2 7/2005 Nix
 6,923,113 B2 8/2005 Bobren et al.
 6,935,227 B2 8/2005 Lopez et al.
 6,945,164 B2 9/2005 Kobiella et al.
 6,951,170 B2 10/2005 Lininger et al.
 6,955,119 B2 10/2005 Bobren et al.
 6,962,109 B2 11/2005 Bobren et al.
 6,981,353 B2 1/2006 Haberstroh et al.
 7,007,597 B1 3/2006 Thas et al.
 7,011,000 B2 3/2006 Kushida et al.
 7,073,431 B1 7/2006 Chen
 7,121,193 B2 10/2006 Balling et al.
 7,128,099 B2 10/2006 Finzo
 7,234,394 B1 6/2007 Bell et al.
 7,237,478 B1 7/2007 Gosis et al.
 7,249,862 B2 7/2007 Shirane
 7,270,055 B1 9/2007 Haberstroh et al.
 7,312,609 B2 12/2007 Schmollngruber et al.
 7,377,213 B1 5/2008 Haberstroh et al.
 7,383,765 B2 6/2008 Kirar et al.
 7,395,754 B1 7/2008 Bobren et al.
 7,428,865 B1 9/2008 Kasel et al.
 7,428,867 B1 9/2008 Bell
 7,454,877 B2 11/2008 Morrison
 7,456,608 B2 11/2008 Kageler et al.
 7,497,068 B2 3/2009 Nasiatka et al.
 7,549,198 B2 6/2009 Gosis et al.
 7,681,496 B2 3/2010 Takidis et al.
 7,798,060 B2 9/2010 Pearson et al.
 8,198,839 B2 6/2012 Katou et al.
 8,287,672 B2 10/2012 Neeser et al.
 8,378,600 B2 2/2013 Katou et al.
 8,516,780 B2 8/2013 Derks
 9,174,752 B2 11/2015 Neeser et al.
 9,193,486 B2 11/2015 Neeser et al.
 9,254,932 B2 2/2016 Neeser et al.
 9,284,080 B2 3/2016 Neeser et al.
 9,315,283 B2 4/2016 Neeser et al.
 2002/0100146 A1 8/2002 Ko
 2002/0129717 A1 9/2002 Helland et al.
 2002/0134811 A1 9/2002 Napier et al.
 2003/0010225 A1 1/2003 Pearson et al.
 2003/0028289 A1 2/2003 Daniel et al.
 2003/0145900 A1 8/2003 Jensen et al.
 2004/0060259 A1 4/2004 Shibazaki et al.
 2004/0206251 A1 10/2004 Nix
 2004/0255552 A1 12/2004 Haberstroh et al.
 2005/0279198 A1 12/2005 Kushida et al.
 2006/0108180 A1 5/2006 Grach et al.
 2006/0192527 A1 8/2006 Kageler et al.
 2009/0013656 A1 1/2009 Nasiatka et al.
 2009/0114308 A1 5/2009 Marelin et al.
 2010/0107573 A1 5/2010 Neeser et al.
 2011/0056392 A1 3/2011 Neeser et al.
 2011/0100233 A1 5/2011 Neeser et al.
 2011/0253480 A1 10/2011 Goodman et al.
 2012/0017780 A1 1/2012 Haberstroh et al.
 2012/0160364 A1 6/2012 Katou et al.
 2012/0210682 A1 8/2012 Gardner

FOREIGN PATENT DOCUMENTS

CN 1151129 6/1997
 CN 2266566 11/1997
 CN 1203878 1/1999
 CN 1253099 5/2000
 CN 1418163 5/2003

CN 1558842 12/2004
 CN 1660675 8/2005
 CN 1859999 11/2006
 CN 101134308 3/2008
 CN 101164416 4/2008
 CN 101287578 10/2008
 CN 100460284 C 2/2009
 CN 101486329 7/2009
 CN 101585244 A 11/2009
 CN 201411061 2/2010
 CN 101678903 3/2010
 CN 101870367 10/2010
 CN 102026873 4/2011
 CN 102026874 4/2011
 CN 102026875 4/2011
 CN 202100012 1/2012
 DE 39 16 355 12/1989
 DE 40 14 305 11/1991
 DE 4204420 A1 8/1993
 DE 19751861 1/1999
 DE 10026200 11/2001
 DE 20321137 1/2006
 DE 10 2005 049130 4/2007
 DE 10 2006 007990 8/2007
 DE 10 2009 047443 6/2011
 DE 202011050797 11/2011
 EP 0095643 12/1983
 EP 0480627 4/1992
 EP 0603868 6/1994
 EP 0659525 6/1995
 EP 0744343 11/1996
 EP 0949146 10/1999
 EP 0997377 5/2000
 EP 0999133 5/2000
 EP 1177978 2/2002
 EP 1316506 6/2003
 EP 1413519 4/2004
 EP 1837279 A1 9/2007
 EP 2271553 4/2013
 GB 489050 A 7/1938
 GB 1136845 A 12/1968
 GB 1136846 A 12/1968
 GB 1136847 A 12/1968
 GB 1 161 827 8/1969
 GB 2 041 869 9/1980
 GB 2 481 724 1/2012
 JP S5290398 7/1977
 JP S541238 1/1979
 JP S5638220 4/1981
 JP S6322320 1/1988
 JP 01213109 A 8/1989
 JP H05198241 8/1993
 JP H0711508 U 2/1995
 JP H07300108 11/1995
 JP H08258808 10/1996
 JP H08324506 12/1996
 JP H09283103 10/1997
 JP 3054566 U 12/1998
 JP 3044132 5/2000
 JP 2000128113 5/2000
 JP 2000128115 5/2000
 JP 3227693 11/2001
 JP 3242081 12/2001
 JP 2002235830 8/2002
 JP 2003170906 6/2003
 JP 2003231291 8/2003
 JP 2003348899 12/2003
 JP 2004108593 4/2004
 JP 3548622 7/2004
 JP 2004241150 8/2004
 JP 2004323111 11/2004
 JP 2007276042 10/2007
 JP 4095817 B2 3/2008
 JP 4366208 B2 8/2009
 JP 4405220 B2 11/2009
 JP 4406016 1/2010
 JP 4627598 B2 11/2010
 JP 4814577 B2 9/2011
 KR 840002211 12/1984

(56)

References Cited

FOREIGN PATENT DOCUMENTS

KR	20000029337	5/2000
RU	1772784	10/1992
RU	2118277	8/1998
RU	2161773	1/2001
RU	2004115639	1/2006
RU	2355821	5/2009
SU	1134117	1/1985
WO	9627526 A1	9/1996
WO	WO 01/89929	11/2001
WO	2004039676 A1	5/2004
WO	WO 2006/048738	5/2006
WO	WO 2007/116914	10/2007
WO	WO 2009/129633	10/2009
WO	WO 2009/129636	10/2009

OTHER PUBLICATIONS

Orgapack GMBH, "OR-T 100, Battery-Hand Tool for Plastic Strapping" Operating and Safety Instructions (53 pages) Nov. 1, 2004.

Orgapack GMBH, "OR-T 200, Battery-Hand Tool for Plastic Strapping" Operating and Safety Instructions (53 pages) Feb. 1, 2004.

Orgapack GMBH, "OR-T 300, Battery-Hand Tool for Plastic Strapping" Operating and Safety Instructions (53 pages) Mar. 1, 2005.

Orgapack GMBH, "OR-T 50, Hand Tool for Plastic Strapping" Operating and Safety Instructions (53 pages) May 1, 2006.

Orgapack GMBH, "OR-T 83, Hand Tool for Plastic Strapping" Operating Instructions (58 pages) Aug. 1, 2000.

Orgapack GMBH, "OR-T 85, Hand Tool for Plastic Strapping" Operating Instructions (58 pages) Jun. 1, 2000.

Orgapack GMBH, "OR-T 86, Hand Tool for Plastic Strapping" Operating Instructions (58 pages) Aug. 1, 1999.

Orgapack GMBH, "OR-T 87, Hand Tool for Plastic Strapping" Operating and Safety Instructions (63 pages) May 1, 2002.

Brushless DC Motor Drives, by Ali Emandi, in Energy-Efficient Electrical Motors, 3rd ed., Aug. 2004, ¶. 270-272, CRC Press & Marcel Dekker.

Lithium ion technology: shaping power tool. By Bender, in Air conditioning, heating, and refrigeration news. vol. 228, Issue 14, p. 18 Jul. 31, 2006.

ISR for PCT/CH2009/000001 dated Jun. 22, 2009.

ISR for PCT/CH2009/000002 dated Jun. 22, 2009.

ISR for PCT/CH2009/000003 dated Jun. 22, 2009.

ISR for PCT/CH2009/000004 dated Apr. 6, 2009.

ISR for PCT/CH2009/000005 dated Jun. 22, 2009.

Japanese Office Action issued in corresponding Application No. JP-2011-505337, dated Mar. 27, 2013.

Japanese Office Action issued in corresponding Application No. JP-2011-505339, dated Mar. 27, 2013.

Korean Office Action dated May 18, 2015 for Korean Application No. 10-2010-7023709 (7 pages).

Korean Office Action dated May 18, 2015 for Korean Application No. 10-2010-7023729 (8 pages).

Korean Office Action dated May 18, 2015 for Korean Application No. 10-2010-7023730 (6 pages).


Korean Office Action dated Apr. 6, 2015 for Korean Application No. 10-2010-7023734 (6 pages).


Korean Office Action dated May 18, 2015 for Korean Application No. 10-2010-7023737(7 pages).


Russian Decision to Grant, dated Aug. 31, 2012, issued in RU Application No. 2010147639.

Russian Decision to Grant, dated Sep. 6, 2012, issued in RU Application No. 2010147640.

* cited by examiner



















Fig. 4











STRAPPING DEVICE

PRIORITY CLAIM

This application is:

a continuation of, and claims priority to and the benefit of, U.S. patent application Ser. No. 12/989,112, filed on Nov. 23, 2010, which issued as U.S. Pat. No. 9,174,752 on Nov. 3, 2015, which is a national stage entry of PCT/CH2009/000001, filed on Jan. 6, 2009, which claims priority to and the benefit of Switzerland Patent Application No. 645/08, filed on Apr. 23, 2008, the entire contents of each of which are incorporated herein by reference;

a continuation of, and claims priority to and the benefit of, U.S. patent application Ser. No. 12/989,142, filed on Nov. 23, 2010, which is a national stage entry of PCT/CH2009/000002, filed on Jan. 6, 2009, which claims priority to and the benefit of Switzerland Patent Application No. 646/08, filed on Apr. 23, 2008, the entire contents of each of which are incorporated herein by reference;

a continuation of, and claims priority to and the benefit of, U.S. patent application Ser. No. 12/989,181, filed on Nov. 23, 2010, which is a national stage entry of PCT/CH2009/000003, filed on Jan. 6, 2009, which claims priority to and the benefit of Switzerland Patent Application No. 647/08, filed on Apr. 23, 2008, the entire contents of each of which are incorporated herein by reference;

a continuation of, and claims priority to and the benefit of, U.S. patent application Ser. No. 12/989,281, filed on Nov. 23, 2010, which is a national stage entry of PCT/CH2009/000004, filed on Jan. 6, 2009, which claims priority to and the benefit of Switzerland Patent Application No. 648/08, filed on Apr. 23, 2008, the entire contents of each of which are incorporated herein by reference; and

a continuation of, and claims priority to and the benefit of, U.S. patent application Ser. No. 12/989,355, filed on Nov. 23, 2010, which is a national stage entry of PCT/CH2009/000005, filed on Jan. 6, 2009, which claims priority to and the benefit of Switzerland Patent Application No. 649/08, filed on Apr. 23, 2008, the entire contents of each of which are incorporated herein by reference.

Certain embodiments of the invention relate to a mobile strapping device for strapping packaged goods with a wrap-around strap, comprising a tensioner for applying a strap tension to a loop of a wrapping strap, as well as a friction welder for producing a friction weld at two areas of the loop of wrapping strap disposed one on top of the other, and a chargeable energy storage means for storing energy that can be released as drive energy at least for the friction welder for producing a friction weld.

Such mobile strapping devices are used for strapping packaged goods with a plastic strap. For this a loop of the plastic strap is placed around the packaged goods. Generally the plastic strap is obtained from a storage roll. After the loop has been completely placed around the packaged goods, the end area of the strap overlaps a section of the strap loop. The strapping device is then applied at this dual-layer area of the strap, the strap clamped into the strapping device, a strap tension applied to the strap loop by the strapping device and a seal produced on the loop between the two strap layers by the friction welding. Here a friction shoe moving in an oscillating manner is pressed onto

the area of two ends of the strap loop. The pressure and the heat produced by the movement briefly locally melt the strap which generally contains a plastic. This produces a durable connection between the two strap layers which can only be broken with a large amount of force. The loop is then separated from the storage roll. The packaged goods are thus strapped.

Strapping devices of this type are intended for mobile use, whereby the devices are taken by a user to the location of use and are not reliant on the provision of external supply energy. The energy required for the envisaged use of such strapping device to strap a wrapping strap around any packaged goods and to produce the seal, is general provided in previously known strapping device by an electrical storage battery or by compressed air. Strapping devices of this type are often in continuous use in industry for packaging goods. Therefore as simple operation of the strapping devices as possible is aimed for. In this way on the one hand a high level of functional reliability, associated with high-quality strapping, and on the other hand as little effort as possible for the operator should be assured

Strapping devices have already become known in which production of the seal and production of the strap tension are largely automated. However, automation of the processes has the disadvantage that the strapping devices have a large number of components and generally also several motors. This results in heavy and voluminous strapping devices. Also, strapping devices provided with a large number of components tend to be top heavy in terms of their weight distribution. Automation also had disadvantages in terms of maintenance costs and the functional reliability of such strapping devices.

One aim of certain embodiments of the invention is therefore to create a mobile strapping device which in spite of the possibility of at least largely automated production of wrapped straps, exhibits a high level of functional reliability and good handling properties.

In accordance with certain embodiments of the invention this objective is achieved with a mobile strapping device by means of a planetary gear system for transferring and changing the rotational speed of a drive movement provided by an electrical drive of the friction welder. In accordance with certain embodiments of the invention the strapping device has at least one planetary gear system which is arranged in the drive train of the friction welder. It has been shown planetary gear in combination with an electrical drive motor provide particularly advantages in friction welders. For example, with planetary gears, in spite of high initial speeds and compact design, high torques can be produced.

This can also be advantageously used for the particularly functionally reliable, possibly automated transfer movement of the friction welder from a rest position into a welding position, in which the friction welder is in contact with the strap to be welded and produces a friction weld by way of an oscillating motion. This can be of particular advantage if, as is the case in certain embodiments of the invention, both the actual friction welding movement of a friction welding element as well as the transfer movement can be generated by the same drive. Such an embodiment with only one drive for these functions is, despite the high degree of automation, particularly compact, and, with its weight being advantageously distributed, nevertheless functionally reliable.

These advantages can be improved further by way of certain embodiments of the invention in which the same drive, designed to bring about the oscillating friction welding motion, also generates the tensioning movement of the strapping device. In order to be able to make the strapping

device as compact as possible despite the high torque, a planetary gear system can also be arranged in the drive train of the strapping device.

In accordance with another embodiment of the present invention, which is also of independent relevance, the strapping device is provided with a brushless direct current motor. More particularly, this motor can be envisaged as the sole motor in the strapping device. Unlike in the case of brush-based direct current motors, such a motor can over a broad speed range produce a rotational movement with an essentially constant and comparatively high torque. Such a high torque is advantageous more particularly for motor-driven transfer movements of the friction welder from a rest position into a welding position and possibly back again. If high torques can be provided by the strapping device, it is possible to make the start of the transfer movement dependent on overcoming high forces. This increases the reliability, more particularly the functional reliability, as the friction welder cannot be accidentally moved from its envisaged position by external influences.

By using a brushless direct current motor as the drive for the tensioner, further advantages can be achieved, as in this way it is possible to control the rotational speed of the tensioning procedure. For example, in contrast to hitherto possible torques, even at low speeds this allows a comparatively high tensioning device torque. Thus, with such mobile strapping device it is for the first time possible to place a strap around packaged goods at low speed but towards the end of the tensioning procedure. In previous tensioners, in order to achieve sufficient strap tensioning, the strap had to be moved at high speed at the start of the tensioning procedure, so that the required strap tension can be achieved towards the end of the tensioning procedure. In doing so the strap is whipped against the packaged goods which involves a high risk of damaging the packaged goods. Even sensitive packaged goods can thus be strapped all-round with considerably less danger of damage.

Furthermore, a speed-dependent/speed-controlled tensioning procedure also allows rapid initial tensioning, i.e. tensioning at high strap retraction speed, followed by second tensioning procedure with a reduced strap retraction speed compared with the first tensioning procedure. In such brushless motors, due to the possibility of setting the rotational speed of the motor shaft and the motor torque separately within certain ranges, the strap retraction speeds can be adjusted to the required/desired circumstances during both tensioning procedures. Particularly high strap tensions can be achieved with the described division into a first and at least a second tensioning procedure.

In accordance with another embodiment of the present invention, which may also be independently relevant, the strapping device is provided with means with which the rotation position of the motor shaft or the positions of components of the strapping device dependent on the motor shaft can be determined. The information about one or more rotational positions can preferably be used by a strapping device controller to control components of the strapping device, such as the friction welder and/or the tensioner. If a brushless direct current motor is used as the device, this can be done in a particularly simple way. For their commutation such motors must already determine information about momentary positions of the rotating component of the motor, which is generally designed as rotating anchor. For this, detectors/sensors, such as Hall sensors, are provided on the motor which determine the rotational positions of the rotating motor components and make them available to the

motor control unit. This information can also advantageously be used to control the friction welder.

Thus, in one embodiment of the strapping device it can be envisaged that a number of rotations of the rotating components of the motor are determined in order, on reaching a given value or rotations, to carry out a switching operation. More particularly, this switching operation can involve switching off the friction welder to terminate the production of a friction weld connection. In a further advantageous embodiment of the invention it can be envisaged that at one or at several determined rotational positions the motor is not switched off, or is only switched off at one or more determined rotation positions.

It has proven to be advantageous if a device with a toggle lever system is provided to move the welding device from the rest position into the welding position and back. The levers of the toggle lever joint, which are connected to each other via one joint, can, by overcoming two dead point positions, be brought into both end positions at which they hold the welding device in the rest position or in the welding position. Advantageously the toggle lever device is held in both end positions by a force, preferably a force exerted by a mechanical spring. Only by overcoming this force should the toggle lever device be able to move from one end position into the other. The toggle lever device achieves the advantage that end positions of the welding device are only changed by overcoming comparatively high torques. As this applies especially to the welding position, the toggle lever system contributes to further increasing the functional reliability of the strapping device. Furthermore, the toggle lever system advantageously supplements the drive train of the strapping device, which in one form of embodiment of the invention also has a brushless motor and a planetary gear system in addition to the toggle lever system, for automated movement of the welding device into its welding position, as all the components are able to produce high torques or carry out movements when high torques are applied.

Certain embodiments of the invention relate to a mobile strapping device for strapping packaged goods with a wrap-around strap, comprising a tensioner for applying a strap tension to a loop of a wrapping strap, as well as a friction welder for producing a friction weld connection at two areas of the loop of wrapping strap disposed one on top of the other, and a chargeable energy storage means for storing energy, more particularly electrical, elastic or potential energy, that can be released as drive energy at least for the friction welder for producing a friction weld connection.

Such strapping devices have a tensioner, with which sufficiently great strap tension can be applied to a loop of strapping placed around the packaged goods. By means of preferably one clamping device of the strapping device the strap loop can then be affixed to the packaged good for the following connection procedure. In strapping device of this type the connection procedure takes place by way of a friction welder. The pressure and the heat produced by the movement briefly locally melt the strap which generally contains a plastic. This produces a durable connection between the two strap layers which can only be broken with a large amount of force.

Strapping devices of this type are envisaged for mobile use, whereby the devices are taken by a user to the deployment site and should not be reliant on the use of externally supplied energy. In previously known strapping devices the energy required for the intended use of such strapping devices for strapping a wrapping strap around any type of packed goods and for producing the connection, is generally provided by an electrical storage battery or by compressed

5

air. With this energy the strap tension applied to the strap by the tensioner and the connection on the strap are produced. Strapping devices of this type are also designed to connect only weldable plastic straps to each other.

In mobile devices a low weight is of particular importance in order to put as little physical strain on the user of the strapping device as possible when using the device. Also, for ergonomic reasons the weight of the strapping device should be distributed as evenly as possible, in order to avoid concentration of the weight in the head area of the strapping device. Such concentration results in unfavorable handling properties of the device. As ergonomic and user-friendly handling of the strapping device as possible are always striven for. More particularly the possibility of incorrect use or faulty operation should be minimal.

One aim of certain embodiments of the invention is therefore to improve the handling and operating properties of a strapping device.

In accordance with certain embodiments of the invention this objective is achieved in a mobile strapping device of this type by a means of a common drive for the tensioner for producing a tensioning movement as well as for the friction welder for producing an oscillating friction welding movement and for a transitioning device for bringing about a transfer movement of the friction welder from a rest position into a welding position.

In accordance with certain embodiments of the invention a mobile strapping device is provided with a motor-driven tensioner and friction welder. In order to be able to use such as strapping device at least approximately as a hand-held strapping device, it also has a motor-drive transitioning device for the friction welder. In terms of the weight, and in order to avoid a concentration of the weight in the head area of the device, in spite of the high degree of automation of the strapping device in accordance with certain embodiments of the invention, all these functional units of the strapping device are driven by just one common drive.

Preferably this just one drive can be designed as an electric motor, the drive movement of which can be used to consecutively drive the tensioner and the friction welder. In an expedient embodiment of the invention means are provided with which a functional connection can be produced either between the just one drive and the tensioner, or between the drive and the friction welder, for example reversing the rotational direction of the motor shaft of the drive.

Preferably with this just one motor not only is the drive movement of the welding procedure itself produced, but also a movement of the friction welder from a rest position into a welding position. In the welding position a welding element of the friction welder is pressed onto the strap layers to be welded to each other and through an oscillating movement produces a friction weld on the strap layers. Here, the welding element is preferably inactive in the rest position and is only started up at the beginning of the movement from the rest position.

The drive of the portable strapping device can preferably be a single electric motor. It has been shown that the motor can advantageously be a brushless direct current motor. Such a motor can be operated in such a way that at different rotational speeds it produces an essentially constant torque.

By using a brushless direct current motor as the drive for the tensioner further advantages can be achieved, as in this way it is possible to control the tensioning procedure in dependence on the rotational speed. For example, in contrast to hitherto possible torques, even at low speeds this allows a comparatively high tensioning device torque. Thus, with

6

such mobile strapping devices it is for the first time possible to place a strap around packaged goods at low speed but towards the end of the tensioning procedure. In previous tensioners, in order to achieve sufficient strap tensioning, the strap had to be moved at high speed at the start of the tensioning procedure, so that the required strap tension can be achieved towards the end of the tensioning procedure. In doing so the strap is whipped against the packaged goods which involves a high risk of damaging the packaged goods. Even sensitive packaged goods can thus be strapped with considerably less danger of damage.

Furthermore, a speed-dependent/speed-controlled tensioning procedure also allows rapid initial tensioning, i.e. tensioning at high strap retraction speed, followed by second tensioning procedure with a reduced strap retraction speed compared with the first tensioning procedure. In such brushless motors, due to the possibility of setting the rotational speed of the motor shaft and the motor torque separately within certain ranges, the strap retraction speeds can be adjusted to the required/desired circumstances during both tensioning procedures. Particularly high strap tensions can be achieved with the described division into a first and at least a second tensioning procedure.

Advantageously at least one planetary gear system is arranged in the force flow between the common drive for the friction welder and for the tensioning device. With regard to the weight of the strapping device and its weight distribution this makes it possible to produce the generally considerably different rotational speeds for the tensioner and the friction welder.

The degree of automation of the strapping device in accordance with certain embodiments of the invention can advantageously be improved with as small a number of required components as possible, in that the coordination between the transmission device and friction welder takes place by means of the same single drive. It can be envisaged that the drive motion of the motor is used both as the drive source for the automatic transmission device as well as to achieve the at least approximately synchronous start of the oscillating movement of the friction welder and the transfer movement of the transitioning device. For this a gearing device can be envisaged which transforms the motorized drive movement into different step-down or step-up gear ratios and releases these at two different points, preferably simultaneously, namely at one point for the friction welder and at another point for the transitioning device.

The common gear system device of the friction welder and its transitioning device can advantageously be arranged on a free wheel, which in a certain rotational direction of a drive shaft of the motor transmits the drive movement to the gear system device. Preferably this rotational direction is different from the rotational direction with which the tensioner is operated. It has proven to be beneficial if, seen in the direction of transmission of the drive movement, splitting of the drive movement on the one hand in the direction of the friction welding element of the friction welder, and on the other hand to transitioning device, only takes place after the free wheel. The gear system device can have a first gear section for the friction welder and a second gear section for the transitioning device, whereby both gear sections perform different step-down or step-ups of the drive movement.

It has proven to be particularly advantageous, if in the drive train of the transitioning device, as a component of the gear system device a gear is provided with which a step down ratio in a range of 100:1 to 30:1, preferably 40:1 to 80:1 and particularly preferably 50:1 to 70:1 can be achieved. Such a step-down ratio can be advantageously

attained with a planetary gear, more particularly a multiple stage planetary gear. However other types of gear can also be provided, such as bevel gears.

An expedient form of one embodiment of the invention provided with a planetary gear system can be cam controlled, whereby a rotating cam is used for switching the device on and off. It can be envisaged that through mechanical operation the cam brings about a movement of the friction welder from a rest position into a welding position.

An embodiment of the strapping device can also be of independent relevance in which an operating means for the joint operation of the tensioner and the friction welder is provided, by means of which the tensioner and friction welder can be consecutively started up. Here it is preferable if in the strapping device optionally either the tensioner or the friction welder are activated by just one operation of the operating means in order to consecutively perform their functions, or tensioner and friction welder can be operated separately of each other. In joint activation, through a common activation manipulation, for example by pressing just one switch, the tensioner is initially started and after completion of the tensioning procedure, without further manual operation of the device, the welding procedure is automatically started and carried out. On the other hand, in the case of separate operation the user can determine the times at which the tensioner is operated and at which time intervals separate operation of the friction welder is started independently of the tensioner. For this, separate operation of an operating element is envisaged, which then also allows at least largely automated welding procedure to take place.

In a possible further development of the invention an adjustable and operating switch means for both of these modes can be envisaged, with which the operating means are provided with the joint activation function but also with the possibility of independent and separate operation the tensioner and friction welder.

Certain embodiments of the invention relate to a mobile strapping device for strapping packaged goods with a wrap-around strap, comprising a tensioner for applying a strap tension to a loop of a wrapping strap, as well as a connector for producing a connection at two areas of the loop of wrapping strap disposed one on top of the other, and a chargeable energy storage means for storing energy that can be released as drive energy at least for the connector and/or tensioner.

Such mobile strapping devices are used for strapping packaged goods with a plastic strap. For this a loop of the plastic strap is placed around the packaged goods. Generally the plastic strap is obtained from a storage roll. After the loop has been completely placed around the packaged goods, the end area of the strap overlaps a section of the strap loop. The strapping device is then applied at this dual-layer area of the strap, the strap clamped into the strapping device, a strap tension applied to the strap loop by the strapping device and a seal produced on the loop between the two strap layers by the connector. For this various connecting technologies are possible, including friction welding. In the case of the latter, a friction shoe moving in an oscillating manner is pressed onto the area of two ends of the strap loop. The pressure and the heat produced by the movement briefly locally melt the strap which generally contains a plastic. This produces a durable connection between the two strap layers which can only be broken with a large amount of force. The loop is then separated from the storage roll. The packaged goods are thus strapped.

For their energy supply strapping devices of this type generally have a chargeable and possibly interchangeable

storage battery with which direct current motors are supplied with electrical energy. In the portable mobile strapping devices the direct current motors envisaged for producing drive movements of the tensioner and/or welding device.

Strapping devices of this type are often in continuous use in industry for packaging goods. Therefore as simple operation of the strapping devices as possible is aimed for. In this way on the one hand a high level of functional reliability, associated with high-quality strapping, and on the other hand as little effort as possible for the operator should be assured. Previously known strapping device cannot fully satisfy these requirements.

One aim of certain embodiments of the invention is therefore to create a mobile strapping device which in spite of the possibility of at least largely automated production of wrapped straps, exhibits a high level of functional reliability and good handling properties.

In accordance with certain embodiments of the invention this objective is achieved with a mobile strapping device in that the energy storage means has a lithium-ion storage battery which provides energy to drive a connector designed in the form of a friction welder. It has been shown that particularly good functional reliability can be achieved with such storage batteries as these storage batteries provide sufficient energy to carry out a large number of strapping cycles with mobile strapping device, even if strap tensions are applied and at least largely automated strapping procedures with motorized drive movements are carried out.

In order to weld PP or PET straps, welding shoe frequencies of approximately 250-350 Hz with a pressing pressure of 300-350 N are required. In order to achieve these values a drive-side rotational speed of an eccentric tappet driving the welding shoe of approximately 6000 rpm to 7000 rpm is necessary. Ideally with these initial values a welding procedure takes place over a duration of 1.5 seconds to 2 seconds. If the eccentric shaft speed falls below the value of 6000 rpm, the band seal quality deteriorates considerably.

Within the framework of the invention it has been shown that the prematurely deteriorating connection quality observed in conventional manual strapping device, even though the storage batteries are not even 60% discharged, does not occur in this manner with lithium ion storage batteries.

Lithium ion storage batteries can provide the voltage require for a high speed for considerably longer. In this way, compared with other storage batteries of similar size, lithium ion storage batteries provide the desired reliability for considerably longer i.e. in the case of a much higher of strapping procedure and friction weld. Only shortly before full consumption of the storage energy does the supply voltage provided by lithium ion storage batteries fall to values at which friction welding should not be carried out. As the time at which the user is requested to charge the storage battery shortly before full discharge by a corresponding signal on the strapping device corresponds with the time at which the storage battery no longer produces good quality friction weld, in contrast to conventional storage batteries the recharging signal can be seen by the user as an indication that as of then the required quality of subsequent strappings is no longer given.

As lithium ion storage batteries have a much higher energy density than conventional storage batteries, these advantages can even be achieved in relation to the dimensions of smaller storage batteries. The resulting reduced weight of the used storage batteries is a further significant advantage for use in mobile portable strapping devices.

Particular advantages can be achieved with lithium ion storage batteries in conjunction with at least one brushless direct current motor as the drive for the tensioner and/or friction welder. This can be further increased by means of a planetary gear system, particularly if the planetary gear system together with the brushless direct current motor and the lithium ion storage batteries are arranged in the drive train for the tensioner and/or friction welder.

Furthermore, a speed-dependent/speed-controlled tensioning procedure also allows rapid initial tensioning, i.e. tensioning at high strap retraction speed, followed by second tensioning procedure with a reduced strap retraction speed compared with the first tensioning procedure. In such brushless motors, due to the possibility of setting the rotational speed of the motor shaft and the motor torque separately within certain ranges, the strap retraction speeds can be adjusted to the required/desired circumstances during both tensioning procedures. Particularly high strap tensions can be achieved with the described division into a first and at least a second tensioning procedure.

An embodiment of strapping device can also be of independent relevance in which the tensioner and the welding device are only provided with one common drive. This just one drive can preferably be designed as an electric motor, with the drive movement of which the tensioner and the friction welder can be consecutively driven. Preferably, with this just one motor, not only is the drive movement of the welding procedure itself produced, but also a movement of the friction welder from a rest position into a welding position in which a welding element of the friction weld is pressed onto the layers of strap to be welded and a friction weld is produced through an oscillating movement on the strap layers. Here, the welding element of the friction welder is in active in the rest position and is preferably only started up at the start of movement from the rest position.

In accordance with another embodiment of the present invention, which may also be of independent relevance, the strapping device is provided with means with which the rotational position of the motor shaft or the position of components of the strapping device dependent on the motor shaft can be determined. The information about one or more rotational positions can preferably be used by a control device of the strapping device to control components of the strapping device, such as the friction welder and/or the tensioner. If a brushless direct current motor is used as the drive, this can be done in a particularly simple manner. For their commutation, such motors must determine current positions of the rotating component of the motor, which is generally a rotating anchor. For this, detectors/sensor, such as Hall sensors, are provided, which determine rotational positions of the rotating motor components and make them available to the motor control device. This information can also be used to advantage for control the friction welder.

Thus, in one embodiment of the strapping device it can be envisaged that a number of rotations of the rotating components of the motor are determined in order, on reaching a given value or rotations, to carry out a switching operation. More particularly, this switching operation can involve switching off the friction welder to terminate the production of a friction weld connection. In a further advantageous embodiment of the invention it can be envisaged that at one or at several determined rotational positions the motor is not switched off, or is only switched off at one or more determined rotation positions.

It has proven to be advantageous if a device with a toggle lever system is provided to move the welding device from the rest position into the welding position and back. The

levers of the toggle lever joint, which are connected to each other via one joint, can, by overcoming two dead point positions, be brought into both end positions at which they hold the welding device in the rest position or in the welding position. Advantageously the toggle lever device is held in both end positions by a force, preferably a force exerted by a mechanical spring. Only by overcoming this force should the toggle lever device be able to move from one end position into the other. The toggle lever device achieves the advantage that end positions of the welding device are only changed by overcoming comparatively high torques. As this applies especially to the welding position, the toggle lever system contributes to further increasing the functional reliability of the strapping device. Furthermore, the toggle lever system advantageously supplements the drive train of the strapping device, which in one form of embodiment of the invention also has a brushless motor and a planetary gear system in addition to the toggle lever system, for automated movement of the welding device into its welding position, as all the components are able to produce high torques or carry out movements when high torques are applied.

Certain embodiments of the invention relate to a strapping device, more particularly a mobile strapping device, for strapping packaged goods with a wrapping strap, comprising a tensioner for applying a strap tension to a loop of a wrapping strap, a rotationally drivable tensioning wheel as well as tensioning rocker that can be pivoted relative to the tensioning wheel and acts together with the tensioning wheel, whereby a tensioning plate is arranged on the tensioning rocker for applying a wrapping strap and a distance between the tensioning plate and the tensioning wheel can be changed in order to apply a tension force to the strap, and a connector, more particularly a welding device, such as a friction welder, for producing a connection at two areas of the loop of wrapping strap disposed one on top of the other.

In strapping devices of this type a rotationally drivable tensioning wheel works in conjunction with a toothed and generally concavely curved tensioning plate which is arranged on a pivotable rocker. In order to apply a tension force to a strap loop the rocker can be pivoted in the direction of the tensioning wheel and pressed against the tensioning wheel. As a rule a pivoting axis of the rocker does not correspond with the rotational axis of the tensioning wheel. This allows the rocker to be "opened" and "closed" with regard to the tensioning wheel, whereby the strap to be tensioned can be placed in the strapping device, held and tensioned by the tensioner and then removed again. In the area between the tensioning wheel and the tensioning plate the strap loop is in two layers. The lower layer is grasped by the tensioning plate of the rocked pivoted towards the tensioning wheel, and through its surface structure or other suitable means for producing friction, held on the tensioning plate by the pressure exerted by the tensioning plate on the lower strap layer. In this way it is possible to grasp and retract the upper layer with the rotationally driven tensioning wheel. In the strap loop this brings about or increases the strap tension and straps the loop tightly around the packaged goods.

Such strapping devices are mainly used in conjunction with plastic straps, loops of which are connected by means of a friction weld. The strapping device therefore has a friction welder with which the strap loops in the area of the two layers of strap one on top of the other can be heated in the strapping device by means of an oscillating friction welding element until the plastic strap melts locally, the materials of the two strap layers flow into each other and are firmly connected on cooling.

11

It has been shown that in such strapping devices the applied strap tension can vary considerably, particularly in the case of various strap thicknesses. One aim of certain embodiments of the invention is therefore to create a strap-

pung device with which even with different strap thicknesses, as equally good tension properties as possible can be achieved.

This is achieved in the strapping device in that the tensioning plate is movably arranged on the tensioning rocker.

Within the framework of the invention it was seen that the fluctuating strap tension in the case of different strap widths is due to the fact that the position of the tensioning plate changes in relation to the tensioning wheel. In this way, depending on the strap thicknesses involved, different engaging and pressing conditions occur between the two strap layers on the one hand, and the tensioning plate and tensioning wheel on the other hand. The invention therefore envisages means of compensating for the displacement of the engaging points. This at least one means can involve a relative mobility of the tensioning plate with regard to the tensioning rocker, more particularly floating bearing of the tensioning plate on the tensioning rocker. Alternatively, or in addition thereto, a change in the position of the tensioning wheel in relation to the pivoting axis of the rocker can be envisaged.

The preferably envisaged relative mobility of the tensioning plate with regard to the tensioning rocker should, in particular, be present in a direction in which a position of the tensioning plate can be changed with regard to the circumference of the tensioning wheel. This direction corresponds at least approximately to the longitudinal direction along which a wrapping strap placed in the strapping device extends within the strapping device, or the direction along which the tensioning plate moved as a result of the rocker movement. Such an embodiment has the advantage that the pressing pressure, more particularly an essentially evenly distributed pressing pressure is made possible by the tensioning plate on the strap and/or the strap on the tensioning wheel, irrespective of the strap thickness, essentially over the entire length of the tensioning plate.

Alternatively, or in addition to the mobility of the tensioning plate, the engaging conditions can be further improved, even for different strap thicknesses, in that the tensioning plate is concavely curved in one radius, which advantageously approximately corresponds with or can be slightly larger than the outer radius of the tensioning wheel. During the tensioning procedure such a concave design of the tensioning surface contributes to providing a gap with an approximately constant gap height between the tensioning surface of the tensioning plate and the external surface of the tensioning wheel over preferably the entire length of the tensioning surface—in relation to the tensioning direction.

In contrast to the solution in accordance with certain embodiments of the invention, in the previous solution a distribution of the pressing pressure on a surface section of the wrapping strap was essentially only possible at a certain strap thickness, through which the rocker took up a position at which the curvature of the tensioning plate runs parallel to the circumference of the tensioning radius. The gap between the tensioning wheel and the tensioning plate therefore only had a constant gap height over the entire length of the tensioning plate at a certain strap thickness. The more the strap thickness differed from a strap thickness fitting this gap, the smaller surface of the upper and lower strap layer, on which the tensioning plate/tensioning wheel could act. With the embodiment in accordance with certain

12

embodiments of the invention it is now possible to compensate for the different pivoting positions of the rocker in relation to the tensioning wheel due to the different strap thicknesses in such a way that despite the different positions of the tensioning rocker, the tensioning plate can always be essentially arranged so that over the entire length of the tensioning plate there is a gap with an essentially constant gap height over the entire, or at least with less gap height variation than in previous solution. Over the entire length of the tensioning plate this allows more even pressure application on the wrapping strap than hitherto.

The solution according to the invention exhibits advantages to a particular extent in the case of small packaged goods (edge length approximately 750 mm and less) as well as round packaged goods (diameter approximately 500-1000 mm) in connection with high tensile forces. In these conditions the then comparatively small strap loop had resulted in shock-like stressing of the lower strap layer, i.e. the strap end, through which the lower strap layer is pulled against the tensioning plate. Due to very different pressing conditions over the entire length of the tensioning plate, securing holding of the strap end in the strapping device could not be guaranteed in previous solutions. The movable tensioning plate exhibits decisive advantages here, which are essentially seen in the fact that even at shock-like tensile stresses in connection with high tensile forces, the straps can be held by the toothed plate, which is optimally arranged because of its mobility.

In one embodiment of the invention, the relative mobility of the tensioning plate can be realized by arranging the tensioning plate on the rocker using bearing surfaces of the tensioning plate that are not parallel to each other. On the basis of this principle the tensioning plate can be provided with a convex contact surface which rests on an essentially level contact surface of the rocker. This allows pivoting of the tensioning plate, whereby self-alignment and clinging of the tensioning plate to the circumference of the tensioning wheel can take place. In one embodiment measures can be envisaged through which self-alignment of the tensioning plate in a direction perpendicular to the direction of the strap can be achieved. Such a measure can for example be a convex shaping of the bearing surface of the tensioning plate perpendicularly to the direction of the strap.

A further advantageous embodiment of the invention can also envisage the tensioning plate being provided with a guide, through which a movement in one or several predetermined directions takes place. The guide direction can in particular be a direction which is essentially parallel to the direction of the strap within the strapping device. In an expedient embodiment, the guide for the tensioning plate can also be produced by an elongated hold and a guide means, such as a screw, arranged therein.

Certain embodiments of the invention relate to a mobile strapping device for strapping packaged goods with a wrap-around strap, comprising a tensioner for applying a strap tension to a loop of a wrapping strap, as well as a connector for producing a connection at two areas of the loop of wrapping strap disposed one on top of the other, and a chargeable energy storage means for storing energy that can be released as drive energy at least for the connector and/or tensioner.

Such mobile strapping devices are used for strapping packaged goods with a plastic strap. For this a loop of the plastic strap is placed around the packaged goods. Generally the plastic strap is obtained from a storage roll. After the loop has been completely placed around the packaged goods, the end area of the strap overlaps a section of the

strap loop. The strapping device is then applied at this dual-layer area of the strap, the strap clamped into the strapping device, a strap tension applied to the strap loop by the strapping device and a seal produced on the loop between the two strap layers by the connector. For this various connecting technologies are possible, including friction welding. In the case of the latter, a friction shoe moving in an oscillating manner is pressed onto the area of two ends of the strap loop. The pressure and the heat produced by the movement briefly locally melt the strap which generally contains a plastic. This produces a durable connection between the two strap layers which can only be broken with a large amount of force. The loop is then separated from the storage roll. The packaged goods are thus strapped.

Such mobile strapping devices are used for strapping packaged goods with a plastic strap. For this a loop of the plastic strap is placed around the packaged goods. Generally the plastic strap is obtained from a storage roll. After the loop has been completely placed around the packaged goods, the end area of the strap overlaps a section of the strap loop. The strapping device is then applied at this dual-layer area of the strap, the strap clamped into the strapping device, a strap tension applied to the strap loop by the strapping device and a seal produced on the loop between the two strap layers by the connector. For this various connecting technologies are possible, including friction welding. In the case of the latter, a friction shoe moving in an oscillating manner is pressed onto the area of two ends of the strap loop. The pressure and the heat produced by the movement briefly locally melt the strap which generally contains a plastic. This produces a durable connection between the two strap layers which can only be broken with a large amount of force. The loop is then separated from the storage roll. The packaged goods are thus strapped.

Strapping devices of this type are often in continuous use in industry for packaging goods. Therefore as simple operation of the strapping devices as possible is aimed for. In this way on the one hand a high level of functional reliability, associated with high-quality strapping, and on the other hand as little effort as possible for the operator should be assured. Previously known strapping device cannot fully satisfy these requirements.

One aim of certain embodiments of the invention is therefore to create a mobile strapping device which in spite of the possibility of at least largely automated production of wrapped straps, exhibits a high level of functional reliability and good handling properties.

In accordance with certain embodiments of the invention this objective is achieved with a mobile strapping device by means of a brushless direct current motor as the drive for the tensioner and/or connector. As will be explained in more detail below, brushless direct current motors have electrical and mechanical properties which result in particular advantages in conjunction with mobile strapping devices. In addition, such motors are largely wear and maintenance-free, which contributes to a high level of functional reliability of the strapping devices.

Furthermore, a speed-dependent/speed-controlled tensioning procedure also allows rapid initial tensioning, i.e. tensioning at high strap retraction speed, followed by a second tensioning procedure with a reduced strap retraction speed compared with the first tensioning procedure. In such brushless motors, due to the possibility of setting the rotational speed of the motor shaft and the motor torque separately within certain ranges, the strap retraction speeds can be adjusted to the required/desired circumstances during both tensioning procedures. Particularly high strap tensions

can be achieved with the described division into a first and at least a second tensioning procedure.

A strapping device in accordance with certain embodiments of the invention can also have energy storage means in the form of a lithium ion storage battery, with which energy can be provided to drive a connector in the form of a friction welder. It has been shown that with such storage batteries particularly good functional reliability can also be achieved as these storage batteries provide sufficient energy to carry out a large number of strapping cycles with mobile strapping devices, even if high strap tensions are applied and at least largely automated strapping procedures with motorized drive movements take place.

It has also been shown that lithium ion storage batteries in combination with friction welders can be seen as the ideal addition compared with other electrical energy storage means. The friction welding process itself is dependent on the pressure of the two straps on each other as well as the frequency of the oscillating welding shoe/welding element. In order to weld PP or PET straps, welding shoe frequencies of approximately 250-350 Hz with a pressing pressure of 300-350 N are required. In order to achieve these values a drive-side rotational speed of an eccentric tappet driving the welding shoe of approximately 6000 rpm to 7000 rpm is necessary. Ideally with these initial values a welding procedure takes place over a duration of 1.5 seconds to 2 seconds. If the eccentric shaft speed falls below the value of 6000 rpm, the band seal quality deteriorates considerably.

Within the framework of the invention it has been shown that the prematurely deteriorating connection quality observed in conventional manual strapping device, even though the storage batteries are not even 60% discharged, does not occur in this manner with lithium ion storage batteries. Lithium ion storage batteries can provide the voltage required for a high speed for considerably longer. In this way, compared with other storage batteries of similar size, lithium ion storage batteries provide the desired reliability for considerably longer i.e. in the case of a much higher of strapping procedure and friction weld. Only shortly before full consumption of the storage energy does the supply voltage provided by lithium ion storage batteries fall to values at which friction welding should not be carried out. As the time at which the user is requested to charge the storage battery shortly before full discharge by a corresponding signal on the strapping device corresponds with the time at which the storage battery no longer produces good quality friction weld, in contrast to conventional storage batteries the recharging signal can be seen by the user as an indication that as of then the required quality of subsequent strappings is no longer given.

As lithium ion storage batteries have a much higher energy density than conventional storage batteries, these advantages can even be achieved in relation to the dimensions of smaller storage batteries. The resulting reduced weight of the used storage batteries is a further significant advantage for use in mobile portable strapping devices.

Particular advantages can be achieved with lithium ion storage batteries in conjunction with at least one brushless direct current motor as the drive for the tensioner and/or friction welder. This can be further increased by means of a planetary gear system, particularly if the planetary gear system together with the brushless direct current motor and the lithium ion storage batteries are arranged in the drive train for the tensioner and/or friction welder.

An embodiment of strapping device can also be of independent relevance in which the tensioner and the welding device are only provided with one common drive. This just

15

one drive can preferably be designed as an electric motor, with the drive movement of which the tensioner and the friction welder can be consecutively driven. Preferably, with this just one motor, not only is the drive movement of the welding procedure itself produced, but also a movement of the friction welder from a rest position into a welding position in which a welding element of the friction weld is pressed onto the layers of strap to be welded and a friction weld is produced through an oscillating movement on the strap layers. Here, the welding element of the friction welder is in active in the rest position and is preferably only started up at the start of movement from the rest position.

In accordance with another embodiment of the present invention, which may also be of independent relevance, the strapping device is provided with means with which the rotational position of the motor shaft or the position of components of the strapping device dependent on the motor shaft can be determined. The information about one or more rotational positions can preferably be used by a control device of the strapping device to control components of the strapping device, such as the friction welder and/or the tensioner. If a brushless direct current motor is used as the drive, this can be done in a particularly simple manner. For their commutation, such motors must determine current positions of the rotating component of the motor, which is generally a rotating anchor. For this, detectors/sensor, such as Hall sensors, are provided, which determine rotational positions of the rotating motor components and make them available to the motor control device. This information can also be used to advantage for control the friction welder.

Thus, in one embodiment of the strapping device it can be envisaged that a number of rotations of the rotating components of the motor are determined in order, on reaching a given value or rotations, to carry out a switching operation. More particularly, this switching operation can involve switching off the friction welder to terminate the production of a friction weld connection. In a further advantageous embodiment of the invention it can be envisaged that at one or at several determined rotational positions the motor is not switched off, or is only switched off at one or more determined rotation positions.

It has proven to be advantageous if a device with a toggle lever system is provided to move the welding device from the rest position into the welding position and back. The levers of the toggle lever joint, which are connected to each other via one joint, can, by overcoming two dead point positions, be brought into both end positions at which they hold the welding device in the rest position or in the welding position. Advantageously the toggle lever device is held in both end positions by a force, preferably a force exerted by a mechanical spring. Only by overcoming this force should the toggle lever device be able to move from one end position into the other. The toggle lever device achieves the advantage that end positions of the welding device are only changed by overcoming comparatively high torques. As this applies especially to the welding position, the toggle lever system contributes to further increasing the functional reliability of the strapping device. Furthermore, the toggle lever system advantageously supplements the drive train of the strapping device, which in one form of embodiment of the invention also has a brushless motor and a planetary gear system in addition to the toggle lever system, for automated movement of the welding device into its welding position, as all the components are able to produce high torques or carry out movements when high torques are applied.

Further preferred embodiments of the invention are set out in the claims, the description and the drawing.

16

The invention will be described in more detail by way of the examples of embodiment which are shown purely schematically.

FIG. 1 is a perspective view of a strapping device in accordance with certain embodiments of the invention;

FIG. 2 shows the strapping device in FIG. 1 with the casing;

FIG. 3 shows a partial section view of the motor of the strapping device in FIG. 1, together with components arranged on the motor shaft;

FIG. 4 shows a very schematic view of the motor along with its electronic commutation switch;

FIG. 5 shows a perspective partial view of the drive train of the strapping device in FIG. 1;

FIG. 6 shows the drive train in FIG. 5 from another direction of view;

FIG. 7 shows a side view of the drive train in FIG. 5 with the welding device in the rest position;

FIG. 8 shows a side view of the drive train in FIG. 6 with the welding device in a position between two end positions;

FIG. 9 shows a side view of the drive train in FIG. 5 with the welding device in a welding position;

FIG. 10 shows a side view of the tensioner of the strapping device without the casing, in which a tensioning rocker is in a rest position;

FIG. 11 shows a side view of the tensioner of the strapping device without the casing in which a tensioning rocker is in a tensioning position;

FIG. 12 a side view of the tensioning rocker of the strapping device in FIG. 10 shown in a partial section;

FIG. 13 shows a front view of the tensioning rocker in FIG. 12;

FIG. 14 shows a detail from FIG. 12 along line C-C;

The exclusively manually operated strapping device 1 in accordance with the invention shown in FIGS. 1 and 2 has a casing 2, surrounding the mechanical system of the strapping device, on which a grip 3 for handling the device is arranged. The strapping device also has a base plate 4, the underside of which is intended for placing on an object to be packed. All the functional units of the strapping device 1 are attached on the base plate 4 and on the carrier of the strapping device which is connected to the base plate and is not shown in further detail.

With the strapping device 1 a loop of plastic strap, made for example of polypropylene (PP) or polyester (PET), which is not shown in more detail in FIG. 1 and which has previously been placed around the object to be packed, can be tensioned with a tensioner 6 of the strapping device. For this the tensioner has a tensioning wheel 7 with which the strap can be held for a tensioning procedure. The tensioning wheel 7 operates in conjunction with a rocker 8, which by means of a rocker lever 9 can be pivoted from an end position at a distance from the tensioning wheel into a second end position about a rocker pivoting axis 8a, in which the rocker 8 is pressed against the tensioning wheel 7. The strap located between the tensioning wheel 7 and the rocker 8 is also pressed against the tensioning wheel 7. By rotating the tensioning wheel 7 it is then possible to provide the strap loop with a strap tension that is high enough for the purpose of packing. The tensioning procedure, and the rocker 8 advantageously designed for this, is described in more detail below.

Subsequently, at a point on the strap loop on which two layers of the wrapping strap are disposed one on top of the other, welding of the two layers can take place by means of the friction welder 8 of the strapping device. In this way the strap loop can be durably connected. For this the friction

17

welder **10** is provided with a welding shoe **11**, which through mechanical pressure on the wrapping strap and simultaneous oscillating movement at a predefined frequencies starts to melt the two layers of the wrapping strap. The plastified or melted areas flow into each other and after cooling of the strap a connection is formed between the two strap layers. If necessary the strap loop can be separated from a strap storage roll by means of a strapping device **1** cutter which is not shown.

Operation of the tensioner **6**, assignment of the friction welder **10** by means of a transitioning device **19** (FIG. 6) of the friction welder as well as the operation of the friction welder itself and operation of the cutter all take place using only one common electric motor **14**, which provides a drive movement for each of these components. For its power supply, an interchangeable storage battery **15**, which can be removed for charging, is arranged on the strapping device. The supply of other external auxiliary energies, such as compressed air or additional electricity, is not envisaged in accordance with FIGS. 1 and 2.

The portable mobile strapping device **1** has an operating element **16**, in the form of a press switch, which is intended for starting up the motor. Via a switch **17**, three operating modes can be set for the operating element **16**. In the first mode by operating the operating element **16**, without further action being required by the operator, the tensioner **6** and the friction welder **10** are started up consecutively and automatically. To set the second mode the switch **17** is switched over to a second switching mode. In the second possible operating mode, by operating the operating element **16**, only the tensioner **6** is started up. To separately start the friction welder **10** a second operating element **18** must be activated by the operator. In alternative forms of embodiment it can also be envisaged that in this mode the first operating element **16** has to be operated twice in order to activate the friction welder. The third mode is a type of semi-automatic operation in which the tensioning button **16** must be pressed until the tension force/tensile force which can preset in stages is achieved in the strap. In this mode it is possible to interrupt the tensioning process by releasing the tensioning button **16**, for example in order to position edge protectors on the goods to be strapped under the wrapping strap. By pressing the tensioning button the tensioning procedure can then be continued. This third mode can be combined with a separately operated as well as an automatic subsequent friction welding procedure.

On a motor shaft **27**, shown in FIG. 3, of the brushless, grooved rotor direct current motor **14** a gearing system device **13** is arranged. In the example of embodiment shown here a type EC140 motor manufactured by Maxon Motor AG, Brünigstrasse 20, 6072 Sachseln is used. The brushless direct current motor **14** can be operated in both rotational directions, whereby one direction is used as the drive movement of the tensioner **6** and the other direction as the drive movement of the welding device **10**.

The brushless direct current motor **14**, shown purely schematically in FIG. 4, is designed with a grooved rotor **20** with three Hall sensors HS1, HS2, HS3. In its rotor **20**, this EC motor (electronically commutated motor) has a permanent magnet and is provided with an electronic control **22** intended for electronic commutation in the stator **24**. Via the Hall sensors, HS1, HS2, HS3, which in the example of embodiment also assume the function of position sensors, the electronic control **22** determines the current position of the rotor **20** and controls the electrical magnetic field in the windings of the stator **24**. The phases (phase 1, phase 2, phase 3) can thus be controlled depending in the position of

18

the rotor **20**, in order to bring about a rotational movement of the rotor in a particular rotational direction with a predeterminable variable rotational speed and torque. In this present case a "1st quadrant motor drive intensifier" is used, which provides the motor with the voltage as well as peak and continuous current and regulates these. The current flow for coil windings of the stator **24**, which are not shown in more detail, is controlled via a bridge circuit **25** (MOSFET transistors), i.e. commutated. A temperature sensor, which is not shown in more detail, is also provided on the motor. In this way the rotational direction, rotational speed, current limitation and temperature can be monitored and controlled. The commutator is designed as a separate print component and is accommodated in the strapping device separately from the motor.

The power supply is provided by the lithium-ion storage battery **15**. Such storage batteries are based on several independent lithium ion cells in each of which essentially separate chemical processes take place to generate a potential difference between the two poles of each cell. In the example of embodiment the lithium ion storage battery is manufactured by Robert Bosch GmbH, D-70745 Leinfelden-Echterdingen. The battery in the example of embodiment has eight cells and has a capacity of 2.6 ampere-hours. Graphite is used as the active material/negative electrode of the lithium ion storage battery. The positive electrode often has lithium metal oxides, more particularly in the form of layered structures. Anhydrous salts, such as lithium hexafluorophosphate or polymers are usually used as the electrolyte. The voltage emitted by a conventional lithium ion storage battery is usually 3.6 volts. The energy density of such storage batteries is around 100 Wh/kg to 120 Wh/kg.

On the motor side drive shaft, the gearing system device **13** has a free wheel **36**, on which a sun gear **35** of a first planetary gear stage is arranged. The free wheel **36** only transfers the rotational movement to the sun gear **35** in one of the two possible rotational directions of the drive. The sun gear **35** meshes with three planetary gears **37** which in a known manner engage with a fixed gear **38**. Each of the planetary gears **37** is arranged on a shaft **39** assigned to it, each of which is connected in one piece with an output gear **40**. The rotation of the planetary gears **37** around the motor shaft **27** produces a rotational movement of the output gear **40** around the motor shaft **27** and determines a rotational speed of this rotational movement of the output gear **40**. In addition to the sun gear **35** the output gear **40** is also on the free wheel **36** and is therefore also arranged on the motor shaft. This free wheel **36** ensures that both the sun gear **35** and the output gear **40** only also rotate in one rotational direction of the rotational movement of the motor shaft **27**. The free wheel **29** can for example be of type INA HFL0615 as supplied by the company Schaeffler KG, D-91074 Herzogenaurach,

On the motor-side output shaft **27** the gear system device **13** also has a toothed sun gear **28** belonging to a second planetary gear stage, through the recess of which the shaft **27** passes, though the shaft **27** is not connected to the sun gear **28**. The sun gear is attached to a disk **34**, which in turn is connected to the planetary gears. The rotational movement of the planetary gears **37** about the motor-side output shaft **27** is thus transferred to the disk **34**, which in turn transfers its rotational movement at the same speed to the sun gear **28**. With several planetary gears, namely three, the sun gear **28** meshes with cog gears **31** arranged on a shaft **30** running parallel to the motor shaft **27**. The shafts **30** of the three cog gears **31** are fixed, i.e. they do not rotate about the motor shaft **27**. In turn the cog gears **21** engage with an internal-

19

tooth sprocket, which on its outer side has a cam 32 and is hereinafter referred to as the cam wheel 33. The sun gear 28, the three cog gears 31 as well as the cam wheel 33 are components of the second planetary gear stage. In the planetary gear system the input-side rotational movement of the shaft 27 and the rotational movement of the cam wheel are at a ratio of 60:1, i.e. a 60-fold reduction takes place through the second-stage planetary gear system.

At the end of the motor shaft 27, on a second free wheel 42 a bevel gear 43 is arranged, which engages in a second bevel gear, which is not shown in more detail. This free wheel 42 also only transmits the rotational movement in one rotational direction of the motor shaft 27. The rotational direction in which the free wheel 36 of the sun gear 35 and the free wheel 42 transmit the rotational movement of the motor shaft 27 is opposite. This means that in one rotational direction only free wheel 36 turns, and in the other rotational direction only free wheel 42.

The second bevel gear is arranged on one of a, not shown, tensioning shaft, which at its other end carries a further planetary gear system 46 (FIG. 2). The drive movement of the electric motor in a particular rotational direction is thus transmitted by the two bevel gears to the tensioning shaft. Via a sun gear 47 as well as three planetary gears 48 the tensioning wheel 49, in the form of an internally toothed sprocket, of the tensioner 6 is rotated. During rotation the tensioning wheel 7, provided with a surface structure on its outer surface, moves the wrapping strap through friction, as a result of which the strap loop is provided with the envisaged tension.

In the area of its outer circumference the output gear 40 is designed as a cog gear on which is a toothed belt 50 of an envelope drive (FIGS. 5 and 6). The toothed belt 50 also goes round pinion 51, smaller in diameter than the output gear 40, the shaft of which drive an eccentric drive 52 for producing an oscillating to and fro movement of the welding shoe 53. Instead of toothed belt drive any other form of envelope drive could be provided, such as a V-belt or chain drive. The eccentric drive 52 has an eccentric shaft 54 on which an eccentric tappet 55 is arranged on which in turn a welding shoe arm 56 with a circular recess is mounted. The eccentric rotational movement of the eccentric tappet 55 about the rotational axis 57 of the eccentric shaft 54 results in a translator oscillating to and fro movement of the welding shoe 53. Both the eccentric drive 52 as well as the welding shoe 53 it can be designed in any other previously known manner.

The welding device is also provided with a toggle lever device 60, by means of which the welding device can be moved from a rest position (FIG. 7) into a welding position (FIG. 9). The toggle lever device 60 is attached to the welding shoe arm 56 and provided with a longer toggle lever 61 pivotably articulated on the welding shoe arm 56. The toggle lever device 60 is also provided with a pivoting element 63, pivotably articulated about a pivoting axis 62, which in the toggle lever device 60 acts as the shorter toggle lever. The pivoting axis 62 of the pivoting element 63 runs parallel to the axes of the motor shaft 27 and the eccentric shaft 54.

The pivoting movement is initiated by the cam 32 on the cam wheel 33 which during rotational movement in the anticlockwise direction—in relation to the depictions in FIGS. 7 to 9—of the cam wheel 33 ends up under the pivoting element 63 (FIG. 8). A ramp-like ascending surface 32a of the cam 32 comes into contact with a contact element 64 set into the pivoting element 63. The pivoting element 63 is thus rotated clockwise about its pivoting axis 62. In the

20

area of a concave recess of the pivoting element 63 a two-part longitudinally-adjustable toggle lever rod of the toggle lever 61 is pivotably arranged about a pivoting axis 69 in accordance with the 'piston cylinder' principle. The latter is also rotatably articulated on an articulation point 65, designed as a further pivoting axis 65, of the welding shoe arm 56 in the vicinity of the welding shoe 53 and at a distance from the rotational axis 57 of the welding shoe arm 56. Between both ends of the longitudinally adjustable toggle lever rod a pressure spring 67 is arranged thereon, by means of which the toggle lever 61 is pressed against both the welding shoe arm 56 as well as against the pivoting element 63. In terms of its pivoting movements the pivoting element 63 is thus functionally connected to the toggle lever 61 and the welding shoe arm 56.

As can be seen in the depictions in FIG. 7, in the rest position there is an (imaginary) connecting line 68 for both articulation points of the toggle lever 61 running through the toggle lever 61 between the pivoting axis 62 of the pivoting element 63 and the cam wheel 33, i.e. on one side of the pivoting axis 62. By operating the cam wheel 33 the pivoting element 63 is rotated clockwise—in relation to the depictions in FIGS. 7 to 9. In this way the toggle lever 61 of the pivoting 63 is also operated. In FIG. 8 an intermediate position of the toggle lever 61 is shown in which the connecting line 68 of the articulation points 65, 69 intersects the pivoting axis 62 of the pivoting element 63. In the end position of the movement (welding position) shown in FIG. 9 the toggle lever 61 with its connecting line 68 is then on the other side of the pivoting axis 62 of the pivoting element 63 in relation to the cam wheel 33 and the rest position. During this movement the welding arm shoe 56 is transferred by the toggle lever 61 from its rest position into the welding position by rotation about the rotational axis 57. In the latter position the pressure spring 67 presses the pivoting element 63 against a stop, not shown in further detail, and the welding shoe 53 onto the two strap layers to be welded together. The toggle lever 61, and therefore also the welding shoe arm 56, is thus in a stable welding position.

The anticlockwise drive movement of the electric motor shown in FIGS. 6 and 9 is transmitted by the toothed belt 50 to the welding shoe 53, brought into the welding position by the toggle lever device 60, which is pressed onto both strap layer and moved to and fro in an oscillating movement. The welding time for producing a friction weld connection is determined by way of the adjustable number of revolutions of the cam wheel 33 being counted as of the time at which the cam 32 operates the contact element 64. For this the number of revolutions of the shaft 27 of the brushless direct current motor 14 is counted in order to determine the position of the cam wheel 33 as of which the motor 14 should switch off and thereby end the welding procedure. It should be avoided that on switching off the motor 14 the cam 32 comes to a rest under the contact element 64. Therefore, for switching off the motor 14 only relative positions of the cam 32 with regard to the pivoting element 63 are envisaged, at which the cam 32 is not under the pivoting element. This ensures that the welding shoe arm 56 can pivot back from the welding position into the rest position (FIG. 7). More particularly, this avoids a position of the cam 32 at which the cam 32 would position the toggle lever 61 at a dead point, i.e. a position in which the connecting line 68 of the two articulation points intersects the pivoting axis 62 of the pivoting element 63—as shown in FIG. 8. As such a position is avoided, by means of operating the rocker lever the rocker (FIG. 2) can be released from the tensioning wheel 7 and the toggle lever 61 pivoted in the direction of the cam wheel 33

21

into the position shown in FIG. 7. After the strap loop has been taken out of the strapping device, the latter is ready for a further strapping procedure.

The described consecutive procedures “tensioning” and “welding” can be jointly initiated in one switching status of the operating element 16. For this the operating element 16 is operated once, whereby the electric motor 14 first turns on the first rotational direction and thereby (only) the tensioner 6 is driven. The strap tension to be applied to the strap can be set on the strapping device, preferably by means of a push button in nine stages, which correspond to nine different strap tensions. Alternatively continuous adjustment of the strap tension can be envisaged. As the motor current is dependent on the torque of the tensioning wheel 7, and this in turn on the current strap tension, the strap tension to be applied can be set via push buttons in nine stages in the form of a motor current limit value on the control electronics of the strapping device.

After reaching a settable and thus predeterminable limit value for the motor current/strap tension, the motor 14 is switched off by its control device 22. Immediately afterwards the control device 22 operates the motor in the opposite rotational direction. As a result, in the manner described above, the welding shoe 52 is lowered onto the two layers of strap displaced one on top of the other and the oscillating movement of the welding shoe is carried out to produce the friction weld connection.

By operating switch 17 the operating element 16 can only activate the tensioner. If this is set, by operating the operating element only the tensioner is brought into operation and on reaching the preset strap tension is switched off again. To start the friction welding procedure the second operating element 18 must be operated. However, apart from separate activation, the function of the friction welding device is identical to the other mode of the first operating element.

As has already been explained, the rocker 8 can through operating the rocker lever 9 shown in FIGS. 2, 10, 11 carry out pivoting movements about the rocker axis 8a. For this, the rocker is moved by a rotating cam disc which is behind the tensioning wheel 7 and cannot therefore be seen in FIG. 2. Via the rocker lever 9 the cam disc can carry out a rotational movement of approximately 30° and move the rocker 8 and/or the tensioning plate 12 relative to the tensioning wheel 7 which allow the strap to be inserted into the strapping device/between the tensioning wheel 7 and tensioning plate 12.

In this way, the toothed tensioning plate arranged on the free end of the rocker can be pivoted from a rest position shown in FIG. 10 into a tensioning position shown in FIG. 11 and back again. In the rest position the tensioning plate 12 is at sufficiently great distance from the tensioning wheel 7 that a wrapping strap can be placed in two layers between the tensioning wheel and the tensioning plate as required for producing connection on a strap loop. In the tensioning position the tensioning plate 12 is pressed in a known way, for example by means of a spring force acting on the rocker, against the tensioning wheel 7, whereby, contrary to what is shown in FIG. 11, in a strapping procedure the two-layer strap is located between the tensioning plate and the tensioning wheel and thus there should be no contact between the two latter elements. The toothed surface 12a (tensioning surface) facing the tensioning wheel 7 is concavely curved whereby the curvature radius corresponds with the radius of the tensioning wheel 7 or is slightly larger.

As can be seen in particular in FIGS. 10 and 11 as well as the detailed drawings of FIG. 12-14, the toothed tensioning

22

plate 12 is arranged in a grooved recess 71 of the rocker. The length—in relation to the direction of the strap—of the recess 71 is greater than the length of the tensioning plate 12. In addition, the tensioning plate 12 is provided with a convex contact surface 12b with which it is arranged on a flat contact surface 71 in the recess 71 of the rocker 8. As shown in particular in FIGS. 11 and 12 the convex curvature runs in a direction parallel to the strap direction 70, while the contact surface 12b is designed flat and perpendicular to this direction (FIG. 13). As a result of this design the tensioning plate 12 is able to carry out pivoting movements in the strap direction 70 relative to the rocker 8 and to the tensioning wheel 7. The tensioning plate 12 is also attached to the rocker 8 by means of a screw 72 passing through the rocker from below. This screw is in an elongated hole 74 of the rocker, the longitudinal extent of which runs parallel to the course of the strap 70 in the strapping device. As a result in addition to be pivotable, the tensioning plate 12 is also arranged on the rocker 8 in a longitudinally adjustable manner.

In a tensioner the tensioning rocker 8 is initially moved from the rest position (FIG. 10) into the tensioning position (FIG. 11). In the tensioning position the sprung rocker 8 presses the tensioning plate in the direction of the tensioning wheel and thereby clamps the two strap layers between the tensioning wheel 7 and the tensioning plate 12. Due to different strap thicknesses this can result in differing spacings between the tensioning plate 12 and circumferential surface 7a of the tensioning wheel 7. This not only results in different pivoting positions of the rocker 8, but also different positions of the tensioning plate 12 in relation to the circumferential direction of the tensioning wheel 7. In order to still achieve uniform pressing conditions, during the pressing procedure the tensioning plate 12 adjusts itself to the strap through a longitudinal movement in the recess 71 as well as a pivoting movement via the contact surface 12b on contact surface 72 so that the tensioning plate 12 exerts as even a pressures as possible over its entire length on the wrapping strap. If the tensioning wheel 7 is then switched on the toothing of tensioning plate 12 holds the lower strap layer fast, while the tensioning wheel 7 grasps the upper strap layer with its toothed circumferential surface 7a. The rotational movement of the tensioning wheel 7 as well as the lower coefficient of friction between the two strap layers then results in the tensioning wheel pulling back the upper band layer, thereby increasing the tension in the strap loop up to the required tensile force value.

LIST OF REFERENCES

1.	Strapping device
2.	Casing
3.	Grip
4.	Base plate
6.	Tensioner
7.	Tensioning wheel
7a.	Circumferential surface
8.	Rocker
8.	Rocker pivoting axis
9.	Rocker lever
10.	Friction welder
11.	Welding shoe
12.	Tensioning plate
12a.	Tensioning surface
12b.	Contact surface
13.	Gear system device
14.	Electric direct current motor

23

-continued

15.	Storage battery
16.	Operating element
17.	Switch
18.	Operating element
19.	Transitioning device
20.	Rotor
24.	Stator
25.	Bridging circuit
27.	Motor side output shaft
28.	Sun gear
30.	Shaft
31.	Cog wheel
32.	Cam
32a.	Surface
33.	Cam wheel
35.	Sun gear
36.	Free wheel
HS1	Hall sensor
37.	Planetary gear
38.	Socket
39.	Shaft
40.	Output gear
42.	Free wheel
43.	Bevel gear
46.	Planetary gear system
47.	Sun gear
48.	Planetary gear
49.	Tensioning wheel
50.	Toothed belt
51.	Pinion
52.	Eccentric drive
53.	Welding shoe
54.	Eccentric shaft
55.	Eccentric tappet
56.	Welding shoe arm
57.	Rotational axis eccentric shaft
60.	Toggle lever device
61.	Longer toggle lever
62.	Pivoting axis
63.	Pivoting element
64.	Contact element
65.	Pivoting axis
66.	Pivoting axis
67.	Pressure spring
68.	Connecting line
69.	Pivoting axis
70.	Strap direction
71.	Recess
72.	Contact surface
73.	Screw
74.	Elongated hole
HS2	Hall sensor
HS3	Hall sensor

The invention claimed is:

1. A strapping device comprising:

a tensioner operable to tension a strap;

a strap connector operable to connect two areas of the strap to one another;

one or more motors configured to operate the tensioner and the strap connector;

a first input device;

a control device configured to, when in a first operating mode, responsive to an actuation of the first input device, control the one or more motors to: (1) operate the tensioner to tension the strap around an object until a predetermined tension is reached in the strap; and (2) after the predetermined tension is reached in the strap, without additional operator input automatically operate the strap connector to connect the two areas of the strap to form a tensioned strap loop around the object; and

a tension-setting input device configured to enable an operator to select the predetermined tension.

24

2. The strapping device of claim 1, further comprising a second input device, wherein the control device is further configured to, when in a third operating mode:

responsive to an actuation of the first input device, control

the one or more motors to operate the tensioner to tension the strap around the object until the predetermined tension is reached in the strap; and

responsive to an actuation of the second input device,

control the one or more motors to operate the strap connector to connect the two areas of the strap to form the tensioned strap loop around the object.

3. The strapping device of claim 2, wherein the control device is further configured to, when in a second operating mode:

responsive to an actuation of the first input device and the first input device being maintained in an actuated state, control the one or more motors to operate the tensioner to tension the strap around the object;

responsive to the first input device returning to a non-actuated state, control the one or more motors to stop tensioning the strap; and

responsive to an actuation of the second input device, control the one or more motors to operate the strap connector to connect the two areas of the strap to form the tensioned strap loop around the object.

4. The strapping device of claim 2, further comprising an operating-mode-selection input device configured to enable operator selection of any one of the first and third operating modes.

5. The strapping device of claim 1, wherein the one or more motors comprise a single motor configured to operate the tensioner and the strap connector.

6. The strapping device of claim 5, further comprising a transfer device operably connected to the strap connector and configured to move the strap connector from a rest position to a connecting position, wherein the single motor comprises a motor shaft, wherein rotation of the motor shaft of the single motor in a first direction causes operation of the tensioner and rotation of the motor shaft of the single motor in a second direction different from the first direction causes operation of the strap connector and causes the transfer device to move the strap connector from the rest position to the connecting position.

7. The strapping device of claim 1, further comprising a battery configured to power the one or more motors.

8. The strapping device of claim 1, further comprising a first drive train operably connecting at least one of the one or more motors to the tensioner and a second drive train operably connecting at least one of the one or more motors to the strap connector.

9. The strapping device of claim 8, wherein the second drive train comprises planetary gearing.

10. The strapping device of claim 1, further comprising a rechargeable battery configured to power the one or more motors, wherein the one or more motors comprise one or more brushless direct-current motors.

11. The strapping device of claim 1, wherein the control device is further configured to, when in a semi-automatic operating mode:

responsive to an actuation of the first input device and the first input device being maintained in an actuated state, control the one or more motors to operate the tensioner to tension the strap around the object until the predetermined tension is reached in the strap; and

after the predetermined tension is reached in the strap, without additional operator input automatically control the one or more motors to operate the strap connector

25

to connect the two areas of the strap to form the tensioned strap loop around the object.

12. The strapping device of claim 11, wherein the control device is further configured to, when in the semi-automatic operating mode, responsive to the first input device returning to a non-actuated state before the predetermined tension is reached in the strap, control the one or more motors to stop tensioning the strap.

13. The strapping device of claim 11, wherein the control device is further configured to, when in a second operating mode:

responsive to an actuation of the first input device and the first input device being maintained in the actuated state, control the one or more motors to operate the tensioner to tension the strap around the object; and

responsive to an actuation of a second input device, control the one or more motors to operate the strap connector to connect the two areas of the strap to form the tensioned strap loop around the object.

14. The strapping device of claim 13, wherein the control device is further configured to, when in the second operating mode, responsive to the first input device returning to a non-actuated state, control the one or more motors to stop tensioning the strap.

15. The strapping device of claim 13, wherein the first and second input devices comprise physical buttons.

16. The strapping device of claim 13, further comprising a battery configured to power the one or more motors.

17. The strapping device of claim 16, further comprising a tension-setting input device configured to enable operator selection of the predetermined tension.

18. The strapping device of claim 17, further comprising an operating-mode-selection input device configured to enable operator selection of any one of the first, semi-automatic, and second operating modes.

19. The strapping device of claim 18, wherein the operating-mode-selection input device comprises a physical button.

20. A strapping device comprising:

a battery;

a tensioner operable to tension a strap;

a strap connector operable to connect two areas of the strap to one another;

a tension-setting input device configured to enable an operator to set a predetermined tension; and

a control device powered by the battery and operable in at least one operating mode,

wherein when the control device is in a first operating mode, the control device is configured to, responsive to a first operator input, operate the tensioner to tension the strap around an object until the predetermined tension is reached in the strap and, after the predetermined tension is reached in the strap, without additional operator input automatically operate the strap connector to connect the two areas of the strap to form a tensioned strap loop around the object.

21. The strapping device of claim 20, further comprising one or more motors configured to operate the tensioner and the strap connector.

22. The strapping device of claim 21, wherein the one or more motors comprise a single motor.

23. The strapping device of claim 20, wherein the control device is further configured to, when in a semi-automatic operating mode:

responsive to a second operator input different from the first operator input, operate the tensioner to tension the

26

strap around the object until the predetermined tension is reached in the strap; and

after the predetermined tension is reached in the strap, without additional operator input automatically operate the strap connector to connect the two areas of the strap to form the tensioned strap loop around the object.

24. The strapping device of claim 23, further comprising a first input device configured to receive the first operator input and the second operator input.

25. The strapping device of claim 24, wherein the first operator input comprises an actuation of the first input device.

26. The strapping device of claim 25, wherein the second operator input comprises an actuation of the first input device and the first input device being maintained in an actuated state.

27. The strapping device of claim 26, wherein the control device is further configured to, when in the semi-automatic operating mode, responsive to the first input device returning to a non-actuated state before the predetermined tension is reached in the strap, operate the tensioner to stop tensioning the strap.

28. The strapping device of claim 27, wherein the control device is further configured to, when in a second operating mode:

responsive to an actuation of the first input device and the first input device being maintained in the actuated state, operate the tensioner to tension the strap around the object; and

responsive to an actuation of a second input device, operate the strap connector to connect the two areas of the strap to form the tensioned strap loop around the object.

29. The strapping device of claim 28, wherein the control device is further configured to, when in the second operating mode, responsive to the first input device returning to a non-actuated state, operate the tensioner to stop tensioning the strap.

30. The strapping device of claim 29, wherein the first and second input devices comprise physical buttons.

31. A strapping device comprising:

a battery;

a tensioner operable to tension a strap;

a friction welder operable to connect two areas of the strap to one another;

a tension-setting input device configured to enable an operator to set a predetermined tension;

a tensioning button;

a sealing button;

a control device powered by the battery and operable in an automatic operating mode, a semi-automatic operating mode, and a manual operating mode; and

an operating-mode-selection input device configured to enable the operator to select of any one of the automatic, semi-automatic, and manual operating modes, wherein when the control device is in the automatic operating mode, the control device is configured to, responsive to an actuation of the tensioning button: (1) operate the tensioner to tension the strap around an object until the predetermined tension is reached in the strap; and (2) after the predetermined tension is reached in the strap, without additional operator input automatically operate the friction welder to connect the two areas of the strap to form a tensioned strap loop around the object,

wherein when the control device is in the semi-automatic operating mode, the control device is configured to: (1)

responsive to an actuation of the tensioning button and the tensioning button being maintained in an actuated state, operate the tensioner to tension the strap around the object until the predetermined tension is reached in the strap; and (2) after the predetermined tension is 5 reached in the strap, without additional operator input automatically operate the strap connector to connect the two areas of the strap to form the tensioned strap loop around the object,

wherein when the control device is in the manual operating mode, the control device is configured to: (1) responsive to an actuation of the tensioning button and the tensioning button being maintained in the actuated state, operate the tensioner to tension the strap around the object; (2) responsive to the tensioning button 15 returning to a non-actuated state, stop operating the tensioner; and (3) responsive to an actuation of the sealing button, to operate the friction welder to connect the two areas of the strap to form the tensioned strap loop around the object. 20

32. The strapping device of claim **31**, wherein the control device is further configured to, when in the semi-automatic operating mode or the manual operating mode, responsive to the first input device returning to a non-actuated state, operate the tensioner to stop tensioning the strap. 25

33. The strapping device of claim **31**, wherein the tensioning button and the sealing button are physical buttons.

34. The strapping device of claim **31**, further comprising one or motors controlled by the control device and configured to operate the tensioner and the friction welder. 30

* * * * *