



US010523850B2

(12) **United States Patent**
Chen et al.

(10) **Patent No.:** **US 10,523,850 B2**
(45) **Date of Patent:** **Dec. 31, 2019**

(54) **CAMERA DEVICE WITH ADJUSTABLE APERTURE**

(71) Applicants: **SINTAI OPTICAL (SHENZHEN) CO., LTD.**, Shenzhen, Guangdong Province (CN); **ASIA OPTICAL CO., INC.**, Taichung (TW)

(72) Inventors: **Chien-hung Chen**, Taichung (TW); **Hsi-ling Chang**, Taichung (TW); **Chun-hung Huang**, Taichung (TW)

(73) Assignees: **SINTAI OPTICAL (SHENZHEN) CO., LTD.**, Shenzhen, Guangdong Province (CN); **ASIA OPTICAL CO., INC.**, Taichung (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/396,198**

(22) Filed: **Dec. 30, 2016**

(65) **Prior Publication Data**
US 2017/0195530 A1 Jul. 6, 2017

(30) **Foreign Application Priority Data**
Dec. 30, 2015 (CN) 2015 1 1020384
Dec. 30, 2015 (CN) 2015 1 1027143

(51) **Int. Cl.**
H04N 5/225 (2006.01)
G02B 27/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04N 5/2252** (2013.01); **G02B 5/005** (2013.01); **G02B 9/60** (2013.01); **G02B 13/0045** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G02B 5/005; G02B 27/0006; G02B 9/60; G02B 13/0045; H04N 5/2252; H04N 5/2254

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,609,273 A 9/1986 Kaise
5,659,821 A * 8/1997 Kawakita G03B 9/18 310/328

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1481065 A 3/2004
CN 101167346 A 4/2008

(Continued)

Primary Examiner — Clayton E. LaBalle


Assistant Examiner — Linda B Smith

(74) *Attorney, Agent, or Firm* — Muncy, Geissler, Olds & Lowe, P.C.

(57) **ABSTRACT**

A camera device is packaged inside an external shell of an electronic apparatus. The external shell has an opening. The camera device has a transparent plate, a part of which is adjacent to the opening of the external shell. The transparent plate forms an accommodating space for accommodating other components of the camera device. Thus, the dust can be prevented from falling into a shutter blade room of the camera device. The camera device also includes a shutter blade, a driver, and a plate. The plate has an aperture, and the aperture of the camera device is defined thereby. The aperture of the plate is completely pervious to light when the shutter blade is at a first position, and the aperture of the plate is partially pervious to light when the shutter blade is at a second position, thereby changing the aperture of the camera device.

28 Claims, 36 Drawing Sheets



US 10,523,850 B2

Page 2

- (51) **Int. Cl.**
G02B 13/00 (2006.01)
G02B 9/60 (2006.01)
G02B 5/00 (2006.01)
- 2010/0220993 A1 9/2010 Sawanobori et al.
2012/0024126 A1 2/2012 Numnual et al.
2013/0142503 A1 6/2013 Kim et al.
2015/0086190 A1* 3/2015 Koza G03B 9/06
396/462

- (52) **U.S. Cl.**
CPC **G02B 27/0006** (2013.01); **H04N 5/2254**
(2013.01)

FOREIGN PATENT DOCUMENTS

- (58) **Field of Classification Search**
USPC 396/452
See application file for complete search history.

CN	101750841 A	6/2010
CN	101819371 A	9/2010
JP	H02287446 A	11/1990
JP	2001075145 A	3/2001
JP	2005292355 A	10/2005
JP	2006072161 A	3/2006
JP	2007033602 A	2/2007
JP	2007183490 A	7/2007
JP	2010210955 A	9/2010
JP	2015129869	7/2015
KR	20110014380 A	2/2011
KR	101259026 B1	4/2013
KR	101272790 B1	6/2013

- (56) **References Cited**

U.S. PATENT DOCUMENTS

7,699,542 B2* 4/2010 Watanabe H04M 1/0264
396/448
2004/0126106 A1 7/2004 Horiike
2006/0029385 A1* 2/2006 Huang G03B 9/08
396/452
2009/0052886 A1 2/2009 Watanabe et al.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C

Polychromatic Diffraction MTF





FIG. 10D

Polychromatic Diffraction MTF



Spatial Frequency in cycles per mm

FIG. 10E




FIG. 11A




FIG. 11B




FIG. 11C

Polychromatic Diffraction MTF




FIG. 11D




FIG. 11E




FIG. 12A




FIG. 12B




FIG. 12C

Polychromatic Diffraction MTF




FIG. 12D

Polychromatic Diffraction MTF




FIG. 12E




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D

Polychromatic Diffraction MTF




FIG. 13E




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 14E




FIG. 15




FIG. 16

1**CAMERA DEVICE WITH ADJUSTABLE APERTURE**

TECHNICAL FIELD OF THE DISCLOSURE

The present invention relates to a camera device, and more particularly, to a camera device with an adjustable aperture

BACKGROUND OF THE DISCLOSURE

In conventional skills, an electronic apparatus equipped with a camera usually has an opening disposed on an external shell thereof. Thus, light rays can be transmitted to the lenses of the camera via the opening for facilitating image formation. Generally, such an opening will be covered by a transparent plate for preventing the dust from falling into the inner part of the electronic apparatus. However, in order to be convenient for manufacture, the transparent plate is just adhered to an external surface of the external shell in the conventional skills. Using such an approach, it is difficult to prevent the dust from falling into a blade room of an aperture adjusting device if the camera is of an aperture-adjustable type. In addition, if the size and volume of the camera can be further reduced, the thickness of the electronic apparatus equipped with the camera can be reduced as well. The thickness of conventional electronic apparatus equipped with the camera is still far from perfect.

Further, an aperture-adjustable camera is only carried out by a digital still camera or a digital camcorder, for example. Although photographic ability can be increased for a smartphone or a tablet by equipping with an external camera lens and the aperture adjustment can be carried out by the external camera lens, the aperture of a camera on a mobile terminal usually is fixed. Based on the requirement of thickness of the mobile terminal, it is a tough problem in this technical field to deploy an aperture adjusting device into the mobile terminal. However, it is quite useful if the aperture adjusting function is brought out to the mobile terminal since it can change the depth of field and improve the quality of a captured picture. Therefore, how to bring out the aperture adjusting function to the mobile terminal is an important development direction in this technical field.

SUMMARY OF THE DISCLOSURE

An objective of the present invention is to provide a camera device for solving the technical problem caused by the dust falling into a blade room of an aperture adjusting device in the conventional skills.

Another object of the present invention is to provide a camera device for reducing the thickness of an electronic apparatus equipped with the camera device.

Another object of the present invention is to provide a camera device for carrying out an adjustment of aperture of a camera lens.

In an aspect, the present invention provides a camera device, which is disposed in an electronic apparatus, the electronic apparatus having an external shell with an opening exposed, the camera device having an optical system frame and a lens system deployed in the external shell of the electronic apparatus, the lens system being mounted on the optical system frame, the camera device comprising a bottom plate fastened to the optical system frame or formed by extending from the optical system frame, a cover plate fastened to the bottom plate and distanced away from the bottom plate, at least one shutter blade disposed between the

2

cover plate and the bottom plate, configured to adjust an aperture of the camera device, and a transparent plate forming an accommodating space for accommodating the optical system frame, the bottom plate, and the cover plate, the transparent plate being located in the external shell and a part of the transparent plate being located between the bottom plate and the opening of the external shell, or between the cover plate and the opening of the external shell.

In another aspect, the present invention provides a camera device, which is disposed in an electronic apparatus, the electronic apparatus having an external shell with an opening exposed, the camera device having an optical system frame and a lens system deployed in the external shell of the electronic apparatus, the lens system being mounted on the optical system frame, the camera device comprising a bottom plate having a first opening, the bottom plate being fastened to the optical system frame or formed by extending from the optical system frame, the bottom plate further having a concave part formed thereon, a cover plate having a second opening, the cover plate being distanced away from the bottom plate, a fastening member having a base and an elongated part extending from the base, the base of the fastening member being accommodated in the concave part of the bottom plate, and the elongated part of the fastening member penetrating the concave part of the bottom plate and being fastened to the cover plate, and at least one shutter blade disposed between the cover plate and the bottom plate, configured to adjust an aperture of the camera device, wherein light rays are transmitted to the lens system sequentially via the opening of the external shell, the first opening of the bottom plate, and an aperture established by the shutter blade, and the second opening of the cover plate, or emitted out from the opening of the external shell in a reverse order.

In still another aspect, the present invention provides a camera device with adjustable aperture, comprising an optical system frame, a lens system mounted on the optical system frame, a plate configured to be fastened to the optical system frame or be formed by extending the optical system frame, the plate having an aperture; a shutter blade coupled to the plate, the aperture of the plate being completely pervious to light when the shutter blade is at a first position, the aperture of the plate being partially pervious to light when the shutter blade is at a second position, and a driver connecting to the shutter blade for causing a displacement of the shutter blade.

In another aspect, the present invention provides a camera device, which is disposed in an electronic apparatus, the electronic apparatus having an external shell with an opening exposed, the camera device having an optical system frame and an optical system deployed in the external shell of the electronic apparatus, the lens system being mounted on the optical system frame, the optical system comprising the present invention provides an optical lens, which makes object light rays transmit from an object side to an image side on an optical axis and form an image on an image plane, said optical lens comprising a lens group establishing the optical axis, comprising a first lens and a second lens arranged in order from the image side to the object side, wherein the first lens has an image-side surface which is a concave face and has a point of inflection arranged thereon, a first aperture stop and a second aperture stop separately located on the optical axis.

In still another aspect, the present invention provides a camera device, which is disposed in an electronic apparatus, the electronic apparatus having an external shell with an

opening exposed, the camera device having an optical system frame and an optical system deployed in the external shell of the electronic apparatus, the lens system being mounted on the optical system frame, the optical system comprising a lens group establishing the optical axis, a first aperture stop disposed within the lens group and a second aperture stop disposed at the object side outside the lens group.

In another aspect, the present invention provides a camera device, which is disposed in an electronic apparatus, the electronic apparatus having an external shell with an opening exposed, the camera device having an optical system frame and a lens system deployed in the external shell of the electronic apparatus, the lens system being mounted on the optical system frame, the camera device comprising a bottom plate fastened to the optical system frame or formed by extending from the optical system frame, a cover plate fastened to the bottom plate and distanced away from the bottom plate, at least one shutter blade disposed between the cover plate and the bottom plate, configured to adjust an aperture of the camera device, and a transparent plate forming an accommodating space for accommodating the optical system frame, the bottom plate, and the cover plate, the transparent plate being located in the external shell and a part of the transparent plate being located between the bottom plate and the opening of the external shell, or between the cover plate and the opening of the external shell, wherein a lens system comprises a first lens, a first aperture stop, a second lens and a second aperture stop arranged in order from the image side to the object side.

In the embodiments of the present invention, the shutter blade of the aperture-adjustable device is deployed between the exposed opening of the external shell and the outermost lens of the lens system. Therefore, there has more room at the lateral side for accommodating the driver or other components of the aperture-adjustable device. Further, a part of the transparent plate is arranged corresponding to the opening and abuts on the external shell. The transparent plate is fastened to or adhered on the optical system frame. Every component of the camera devices is disposed in the accommodating space formed by the transparent plate. Therefore, this can further prevent the dust from falling into a blade room of the aperture-adjustable device accommodating the shutter blade and prevent a user finger from touch. In addition, the cover plate can be disposed within coverage of the bottom plate. It is easy to process the optical system frame made of a plastic material to remove or cut out some parts thereof for deploying a room accommodating the fastening member, thereby reducing the total thickness of the camera device.

In the embodiments of the present invention, the shutter blade has a hole having an aperture. The aperture of a camera lens can be adjusted by driving the shutter blade using a driver and thus making the hole move toward the optical axis and shift to a position overlapping the original aperture. There can have multiple sets of the shutter blade and the driver so as to carry out a multi-stage aperture adjustment of the camera lens. An adjustment of depth of field can thus be carried out by a selection of aperture. In addition, in the embodiments of the present invention, one shutter blade is cooperated with one driver. It is convenient in replacement when these components are malfunctioned.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram showing a camera device in accordance with a first embodiment of the present invention.

FIG. 2 is a schematic diagram showing a camera device in accordance with a second embodiment of the present invention.

FIG. 3 is an exploded view of a camera device with adjustable aperture in accordance with a third embodiment of the present invention.

FIG. 4 is a schematic diagram showing that a first shutter blade and a second shutter blade are at turn-on positions in accordance with the first embodiment of the present invention.

FIG. 5 is a schematic diagram showing that the first shutter blade is at a turn-on position and the second shutter blade are at a turn-off position in accordance with the first embodiment of the present invention.

FIG. 6 is a schematic diagram showing that the first shutter blade is at a turn-off position and the second shutter blade are at a turn-on position in accordance with the first embodiment of the present invention.

FIG. 7 is an exploded view of a camera device with adjustable aperture in accordance with a fourth embodiment of the present invention.

FIG. 8 is a schematic diagram showing that a first shutter blade is at a turn-on position in accordance with the second embodiment of the present invention.

FIG. 9 is a schematic diagram showing that the first shutter blade is at a turn-off position in accordance with the second embodiment of the present invention.

FIG. 10A is a schematic diagram showing an optical structure in accordance with a fifth embodiment of an optical lens of the present invention.

FIG. 10B is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the fifth embodiment of the present invention in the condition that a first aperture stop is in an active state and a second aperture stop is in an inactive state.

FIG. 10C is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the fifth embodiment of the present invention in the condition that the first aperture stop is in the inactive state and the second aperture stop is in the active state.

FIG. 10D is a diagram showing polychromatic diffraction modulation transfer function (MTF) of the optical lens according to the fifth embodiment of the present invention in the condition that the first aperture stop is in the active state and the second aperture stop is in the inactive state.

FIG. 10E is a diagram showing polychromatic diffraction modulation transfer function of the optical lens according to the fifth embodiment of the present invention in the condition that the first aperture stop is in the inactive state and the second aperture stop is in the active state.

FIG. 11A is a schematic diagram showing an optical structure in accordance with a sixth embodiment of an optical lens of the present invention.

FIG. 11B is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the sixth embodiment of the present invention in the condition that a first aperture stop is in an active state and a second aperture stop is in an inactive state.

FIG. 11C is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the sixth embodiment of the present invention in the condition that the first aperture stop is in the inactive state and the second aperture stop is in the active state.

FIG. 11D is a diagram showing polychromatic diffraction modulation transfer function (MTF) of the optical lens according to the sixth embodiment of the present invention

in the condition that the first aperture stop is in the active state and the second aperture stop is in the inactive state.

FIG. 11E is a diagram showing polychromatic diffraction modulation transfer function of the optical lens according to the sixth embodiment of the present invention in the condition that the first aperture stop is in the inactive state and the second aperture stop is in the active state.

FIG. 12A is a schematic diagram showing an optical structure in accordance with a seventh embodiment of an optical lens of the present invention.

FIG. 12B is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the seventh embodiment of the present invention in the condition that a first aperture stop is in an active state and a second aperture stop is in an inactive state.

FIG. 12C is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the seventh embodiment of the present invention in the condition that the first aperture stop is in the inactive state and the second aperture stop is in the active state.

FIG. 12D is a diagram showing polychromatic diffraction modulation transfer function (MTF) of the optical lens according to the seventh embodiment of the present invention in the condition that the first aperture stop is in the active state and the second aperture stop is in the inactive state.

FIG. 12E is a diagram showing polychromatic diffraction modulation transfer function of the optical lens according to the seventh embodiment of the present invention in the condition that the first aperture stop is in the inactive state and the second aperture stop is in the active state.

FIG. 13A is a schematic diagram showing an optical structure in accordance with an eighth embodiment of an optical lens of the present invention.

FIG. 13B is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the eighth embodiment of the present invention in the condition that a first aperture stop is in an active state and a second aperture stop is in an inactive state.

FIG. 13C is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the eighth embodiment of the present invention in the condition that the first aperture stop is in the inactive state and the second aperture stop is in the active state.

FIG. 13D is a diagram showing polychromatic diffraction modulation transfer function (MTF) of the optical lens according to the eighth embodiment of the present invention in the condition that the first aperture stop is in the active state and the second aperture stop is in the inactive state.

FIG. 13E is a diagram showing polychromatic diffraction modulation transfer function of the optical lens according to the eighth embodiment of the present invention in the condition that the first aperture stop is in the inactive state and the second aperture stop is in the active state.

FIG. 14A is a schematic diagram showing an optical structure in accordance with a ninth embodiment of an optical lens of the present invention.

FIG. 14B is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the ninth embodiment of the present invention in the condition that a first aperture stop is in an active state and a second aperture stop is in an inactive state.

FIG. 14C is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the ninth embodiment of the present invention in the condition that the first aperture stop is in the inactive state and the second aperture stop is in the active state.

FIG. 14D is a diagram showing polychromatic diffraction modulation transfer function (MTF) of the optical lens according to the ninth embodiment of the present invention in the condition that the first aperture stop is in the active state and the second aperture stop is in the inactive state.

FIG. 14E is a diagram showing polychromatic diffraction modulation transfer function of the optical lens according to the ninth embodiment of the present invention in the condition that the first aperture stop is in the inactive state and the second aperture stop is in the active state.

FIG. 15 is a schematic diagram showing a package structure in accordance with a fifth embodiment of an optical lens of the present invention.

FIG. 16 is a schematic diagram showing a package structure in accordance with a sixth embodiment of an optical lens of the present invention.

DETAILED DESCRIPTION OF THE DISCLOSURE

To make the objectives, technical schemes, and technical effects of the present invention more clearly and definitely, the present invention will be described in details below by using embodiments in conjunction with the appending drawings. It should be understood that the specific embodiments described herein are merely for explaining the present invention, and as used herein, the term “embodiment” refers to an instance, an example, or an illustration but is not intended to limit the present invention. In addition, the articles “a” and “an” as used in the specification and the appended claims should generally be construed to mean “one or more” unless specified otherwise or clear from the context to be directed to a singular form. Also, in the appending drawings, the components having similar or the same structure or function are indicated by the same reference number.

Please refer to FIG. 1, which is a schematic diagram showing a camera device 10 in accordance with a first embodiment of the present invention. The camera device 10 is disposed in an electronic apparatus. For example, cell phones, smartphones, tablet computers, wearable devices, handheld game players, and other mobile terminals equipped with a camera lens are applicable to the electronic apparatuses. The electronic apparatuses can also be implemented by cameras or video recorders having a camera lens inherently, or by apparatuses having optical systems, such as projectors. The electronic apparatus has a shell or an external shell 11. Necessary electronic components or structural components supporting the electronic components are disposed inside the external shell 11. The external shell 11 is the outermost shell of the electronic apparatus. The external shell 11 has an opening 110 exposed. Light rays can go into the inner space of the camera device 10 (such as an image capture device) from the opening 110 or be emitted out from the inner space of the camera device 10 (such as a projector) via the opening 110. Taking a camera lens for example, the camera device 10 will be illustrated in the following.

As shown in FIG. 1, the camera device 10 has an optical system frame 15, a lens system 17, and an image recorder 18. The optical system frame 15 is made of a plastic material, and is a fastening component of the optical system. The components of the optical system can be mounted or fastened on the optical system frame 15. In addition, there is only one piece of lens shown in FIG. 1 but this is merely for illustration. It can be understood that the lens system 17 may include more than one lenses. The lenses of the lens system 17 are mounted on the optical system frame 15. The image

recorder **18** is disposed on a lower plate **185** and is configured to record images. Specifically, the image recorder **18** can receive the light rays passing the lens system **17** and form an image on an image plane.

Referring to FIG. 1, the camera device **10** having a camera lens also has a transparent plate **12**, a cover plate **13**, a bottom plate **16**, and at least one shutter blade **14**. The transparent plate **12** adopts a high-transparent material. The transparent plate **12** is disposed at an inner side of the external shell **11** and adjacent to the exposed opening **110** of the external shell **11**, and is fastened on the optical system frame **15**. The transparent plate **12** forms an accommodating space. The optical system frame **15**, the bottom plate **16**, and the cover plate **13** are placed into the accommodating space formed by the transparent plate **12**. The transparent plate **12** can be completely made of the high-transparent material. Alternatively, only a part of the transparent plate **12** corresponding to the exposed opening **110** of the external shell **11** is made of the high-transparent material, and the material of other parts is not limited. Further, a part of the transparent plate **12** is disposed between the exposed opening **110** of the external shell **11** and the cover plate **13**. The bottom plate **16** is fastened to the optical system frame **15** or extending from the optical system frame **15**. The bottom plate **16** also has an opening **160**. The cover plate **13** is a metal flat plate, and is perforated to form an opening **130** in the center such that light rays can transmit into the optical system. The cover plate **13** is distanced away from the bottom plate **16**, and is fastened to the bottom plate **16** or the optical system frame **15**. A screw **19** may be used to fasten the cover plate **13** to the bottom plate **16** or the optical system frame **15**. The shutter blade **14** is a part of components of an aperture adjusting device of the camera lens, and is driven by a driver of the aperture adjusting device. The size of aperture is adjusted by adjusting the position of the shutter blade **14**. The shutter blade **14** is disposed between the cover plate **13** and the bottom plate **16** fastened to the optical system frame **15** or extending from the optical system frame **15**, and is configured to adjust the aperture. It is known that as to the package framework of the camera device **10**, a part of the transparent plate **12**, the cover plate **13**, the shutter blade **14**, the bottom plate **16**, the lens system **17**, and the image recorder **18** are arranged in order from the exposed opening **110** of the external shell **11** to the lower plate **185**. In addition, the light rays transmit into the lens system **17** sequentially via the exposed opening **110** of the external shell **11**, a part of the transparent plate **12**, the opening **130** of the cover plate **13**, the aperture established by the shutter blade **14**, and the opening **160** of the bottom plate **16**. In other applications (e.g., projectors), the light rays may be emitted out from the exposed opening **110** of the external shell **11** in a reverse order.

In addition, the lens system **17** may include at least two pieces of lenses and an aperture stop disposed between the two lenses or between the set of the two lenses and the image plane. For instance, the aperture established by the shutter blade **14** is an adjustable aperture while the aperture of the aperture stop arranged in the lens system **17** is a fixed aperture. The aperture established by the shutter blade **14** is smaller than or equal to the aperture of the aperture stop arranged in the lens system **17**. The aperture of the optical system is defined by the aperture established by the shutter blade **14** when a small aperture is required by the optical system. The aperture of the optical system is defined by the aperture of the aperture stop arranged in the lens system **17** when a large aperture is required by the optical system. For instance, when a small aperture is required, the aperture

established by the shutter blade **14** is adjusted to decrease the size of aperture thereof. The aperture stop arranged in the lens system **17** ceases to be effective due to the evolution of light path and is thus in an inactive state. When a large aperture is required, the aperture established by the shutter blade **14** is adjusted to be equal to the aperture of the aperture stop arranged in the lens system **17**, and meanwhile the aperture of the optical system is defined by the aperture of the aperture stop arranged in the lens system **17**. In this way, an aperture-adjustable device having the shutter blades **14** can be deployed at the outer side of the lens at the most object side. Since there has more room for accommodating such an aperture-adjustable device in this configuration, the size of the camera device **10** can be reduced.

In the embodiments of the present invention, the shutter blade **14** of the aperture-adjustable device is deployed between the exposed opening **110** of the external shell **11** and the outermost lens of the lens system **17**. Therefore, there has more room at the lateral side for accommodating the driver or other components of the aperture-adjustable device. If the shutter blade **14** of the aperture-adjustable device is arranged between any two lenses, the deployment of the driver or other components of the aperture-adjustable device will be limited and such a deployment is more complicated and inconvenient. Further, in the embodiments of the present invention, a part of the transparent plate **12** is arranged corresponding to the opening **110** and abuts on the external shell **11**. The transparent plate **12** is fastened to or adhered on the optical system frame **15**. Every component of the camera devices is disposed in the accommodating space formed by the transparent plate **12**. Therefore, this can further prevent the dust from falling into a blade room of the aperture-adjustable device accommodating the shutter blade **14** and prevent a user finger from touch.

The differences between the camera device **20** of the second embodiment and the camera device **10** of the first embodiment are that in the second embodiment of the present invention, the cover plate **13** is disposed within coverage of the bottom plate **16**, and the bottom plate **16** is arranged at an upper side while the cover plate **13** is changed in its position to be at a lower side. A fastening member (e.g., a screw) **19** is utilized to fasten the cover plate **13** to the bottom plate **16** or the optical system frame **15**. The shutter blade **14** is accommodated between the cover plate **13** and the bottom plate **16**. Specifically, the bottom plate **16** has a concave part **161**. The fastening member **19** has a base **191** and an elongated part **192** extending from the base **191**. The base **191** of the fastening member **19** is accommodated into the concave part **161** of the bottom plate **161**. The elongated part **192** of the fastening member **19** penetrates the concave part **161** of the bottom plate **16** and is fastened on the cover plate **13**. In addition, as to the package framework of the camera device **20**, a part of the transparent plate **12**, the bottom plate **16**, the shutter blade **14**, the cover plate **13**, the lens system **17**, and the image recorder **18** are arranged in order from the exposed opening **110** of the external shell **11** to the lower plate **185**. In addition, the light rays transmit into the lens system **17** sequentially via the exposed opening **110** of the external shell **11**, a part of the transparent plate **12**, the opening **160** of the bottom plate **16**, the aperture established by the shutter blade **14**, and the opening **130** of the cover plate **13**. In other applications (e.g., projectors), the light rays may be emitted out from the exposed opening **110** of the external shell **11** in a reverse order. The advantages of such a technical scheme are that it is easy to process the optical system frame **15** made of a plastic material to remove or cut out some parts thereof for deploying a room accom-

modating the fastening member, thereby reducing the total thickness of the camera device.

The present invention can also have the camera device equipped with an aperture adjusting function such that an adjustment of depth of field can be carried out by a selection of aperture when a user takes pictures using the camera device on a mobile terminal, for example.

Please refer to FIG. 3, which is an exploded view of a camera device with adjustable aperture in accordance with a third embodiment of the present invention. As shown in FIG. 3, the camera device of the third embodiment of the present invention includes a supporting base 22, a driver supporting base 24, and a lens supporting base 26. The camera device further includes a first shutter blade 31, a second shutter blade 32, a cover plate 33, a bottom plate 34, a first driver 35, a second driver 36, a lens system 37, and an image recorder 38. As shown in the embodiment depicted in FIG. 3, the first shutter blade 31, the second shutter blade 32, the cover plate 33, and the bottom plate 41 can be mounted on the supporting base 22. The first driver 35 and the second driver 36 can be mounted on the driver supporting base 24. The lens system 37 and the image recorder 38 can be deployed on the lens supporting base 26.

It should be noted that the afore-described deployment is merely for illustration, and the supporting base 22, the driver supporting base 24, and the lens supporting base 26 may not be clearly distinguished. They can be deemed as an optical system frame, or any two of them can be combined into one entity, or at least two of the supporting base 22, the driver supporting base 24, and the lens supporting base 26 or all of them are integrally formed or made of a same material. In this way, the size of overall camera device can be reduced. For instance, the driver supporting base 24 and the lens supporting base 26 can be manufactured to be an integrally-formed supporting base.

Specifically, the bottom plate 34 is fastened on the supporting base 22. Alternatively, the bottom plate 34 can also be formed by extending from the supporting base 22, or is just a part of the supporting base 22. The cover plate 33 is distanced a part from the bottom plate 34. Preferably, the cover plate 33 is fastened to the supporting base 22. Various types of ways may be utilized to fasten the cover plate 33 to the supporting base 22. For instance, the cover plate 33 has some branches while supporting base 22 has slots corresponding to the branches. By engaging the branches and the slots, the cover plate 33 can thus be fastened on the supporting base 22.

The cover plate 33 and the bottom plate 34 are separated from each other. An accommodating space is formed between the cover plate 33 and the bottom plate 34, and is configured to accommodate the first shutter blade 31 and the second shutter blade 32, which are utilized to change or adjust the effective aperture of the camera device. In addition, as shown in FIG. 3, the driver supporting base 24 has a first accommodating room 241 and a second accommodating room 242 for accommodating the first driver 35 and the second driver 36, respectively. The first driver 35 is configured to drive the first shutter blade 31 and bring about a displacement of the first shutter blade 31, and the second driver 36 is configured to drive the second shutter blade 32 and bring about a displacement of the second shutter blade 32, thereby changing or adjusting the effective aperture of the camera device. Preferably, the first driver 35 and the second driver 36 are implemented by an electric motor such as a current-control-type electric motor. The first driver 35 and the second driver 36 can adopt a structure or configuration as the same as that of a conventional electric motor.

As shown in FIG. 3, the supporting base 22 has a first axle rod 221, and the first shutter blade 31 has a first axle hole 311 disposed corresponding to the position of the first axle rod 221. The bottom plate 34 and the cover plate 33 are perforated to form holes in corresponding positions. The first axle rod 221 penetrates the corresponding holes of the bottom plate 34 and the cover plate 33 and the first axle hole 311 of the first shutter blade 31. Alternatively, the bottom plate 34 and the cover plate 33 are manufactured with a configuration that is not prohibiting the first axle rod 221 from going through the first axle hole 311 of the first shutter blade 31. In this way, by using the deployment of the first axle rod 221 and the first axle hole 311, the first shutter blade 31 can pivot about an axial of the first axle rod 221.

Correspondingly, the supporting base 22 has a second axle rod 222, and the second shutter blade 32 has a second axle hole 321 disposed corresponding to the position of the second axle rod 222. The bottom plate 34 and the cover plate 33 are perforated to form holes in corresponding positions. The second axle rod 222 penetrates the corresponding holes of the bottom plate 34 and the cover plate 33 and the second axle hole 321 of the second shutter blade 32. Alternatively, the bottom plate 34 and the cover plate 33 are manufactured with a configuration that is not prohibiting the second axle rod 222 from going through the second axle hole 321 of the second shutter blade 32. In this way, by using the deployment of the second axle rod 222 and the second axle hole 321, the second shutter blade 32 can pivot about an axial of the second axle rod 222.

The first driver 35 has a first rotating rod 351 disposed thereon. The first rotating rod 351 is driven by the first driver 35 and thus moves in an arc orbit. The first driver 35 can make the first rotating rod 351 move circularly or in an arc fashion. An appropriate transmission mechanism or structure can be deployed between the first driver 35 and the first rotating rod 351. For instance, the first rotating rod 351 is protruded from the surface of a disc, and the disc transfers the force of a rotation generated by the first driver 35 by using a wheel gear. The supporting base 22 has a first orbital hole 223 disposed corresponding to the arc orbit of the first rotating rod 351 of the first driver 35, and the first shutter blade 31 has a first applying hole 312, correspondingly. The bottom plate 34 and the cover plate 33 has holes in corresponding positions. The first rotating rod 351 of the first driver 35 penetrates the first orbital hole 223 of the supporting base 22, the corresponding holes of the bottom plate 34 and the cover plate 33 and the first applying hole 312 of the first shutter blade 31. The first applying hole 312 can also be configured to be intersect with the first orbital hole 223. Of course, the bottom plate 34 and the cover plate 33 can also be configured not to affect the movement of the first rotating rod 351. When the first rotating rod 351 rotates under control of the first driver 35, the first rotating rod 351 moves from a first position to a second position within the first orbital hole 223 of the supporting base 22. Meanwhile, the first rotating rod 351 applies a force to the first shutter blade 31 through the first applying hole 312, thereby generating a torque for the first shutter blade 31 in a first direction. Thus, the first shutter blade 31 rotates around the first axle rod 221 from a turn-on position to a turn-off position, for example. When the first rotating rod 351 moves from the second position to the first position within the first orbital hole 223, the first rotating rod 351 gives to the first shutter blade 31 a torque of a second direction opposite to the first direction. Meanwhile, the first shutter blade 31 rotates from the turn-off position to the turn-on position, for example.

11

Similarly, the second driver **36** has a second rotating rod **361** disposed thereon. The second rotating rod **361** is driven by the second driver **36** and thus moves in an arc orbit. An appropriate transmission mechanism or structure can be deployed between the second driver **36** and the second rotating rod **361** such that the second driver **36** can make the second rotating rod **361** move circularly or in an arc fashion. The supporting base **22** has a second orbital hole **224** disposed corresponding to the arc orbit of the second rotating rod **361** of the second driver **36**, and the second shutter blade **32** has a second applying hole **322**, correspondingly. The bottom plate **34** and the cover plate **33** has holes in corresponding positions. The second rotating rod **361** of the second driver **36** penetrates the second orbital hole **224** of the supporting base **22**, the corresponding holes of the bottom plate **34** and the cover plate **33** and the second applying hole **322** of the second shutter blade **32**. The second applying hole **322** can also be configured to be intersect with the second orbital hole **224**. Of course, the bottom plate **34** and the cover plate **33** can also be configured not to affect the movement of the second rotating rod **361**. When the second rotating rod **361** rotates under control of the second driver **36**, the second rotating rod **361** moves from a first position to a second position within the second orbital hole **224** of the supporting base **22**. Meanwhile, the second rotating rod **361** applies a force to the second shutter blade **32** through the second applying hole **322**, thereby generating a torque for the second shutter blade **32** in a first direction. Thus, the second shutter blade **32** rotates around the second axel rod **222** from a turn-on position to a turn-off position, for example. When the second rotating rod **361** moves from the second position to the first position within the second orbital hole **224**, the second rotating rod **361** gives to the second shutter blade **32** a torque of a second direction opposite to the first direction. Meanwhile, the second shutter blade **32** rotates from the turn-off position to the turn-on position, for example.

The bottom plate **34**, the cover plate **33**, and the supporting base **22** respectively has openings **340**, **330**, and **220** arranged along an optical axis of the camera device, for the entrance of light rays. The aperture of the camera device can be defined by an opening of a plate, which can be implemented by any one of the bottom plate **34**, the cover plate **33**, and the supporting base **22**, or by other components having an opening on the optical axis. The overall aperture of the camera decreases when such an opening is blocked and thus decreases in size.

As shown in FIG. 3, the first shutter blade **31** further includes a first arc contour **310** and a first hole **O1** having a first aperture, and the second shutter blade **32** further includes a second arc contour **320** and a second hole **O2** having a second aperture. The size of the first hole **O1** of the first shutter blade **31** and the size of the second hole **O2** of the second shutter blade **32** are different from the aperture size defined by the plate, or are smaller than the aperture size of the plate. Also, the first aperture of the first hole **O1** of the first shutter blade **31** is different from the second aperture of second hole **O2** of the second shutter blade **32**. As shown in FIG. 3, in one example, the first aperture of the first shutter blade **31** is smaller than the second aperture of the second shutter blade **32**.

For instance, when the first shutter blade **31** is at the turn-on position, the aperture of the plate is completely pervious to light; when the first shutter blade **31** is at the turn-off position, the aperture of the plate is partially pervious to light. Similarly, when the second shutter blade **32** is at the turn-on position, the aperture of the plate is completely

12

pervious to light; when the second shutter blade **32** is at the turn-off position, the aperture of the plate is partially pervious to light.

Please refer to FIG. 4 with reference to FIG. 3. For instance, when the first driver **35** drives the first shutter blade **31** and makes it be located at the turn-on position and the second driver **36** drives the second shutter blade **32** and makes it be located at the turn-on position, the first arc contour **310** of the first shutter blade **31** will park at a position corresponding to a part of contours of the openings **340**, **330**, and **220** respectively of the bottom plate **34**, the cover plate **33**, and the supporting base **22** and the second arc contour **320** of the second shutter blade **32** will park at a position corresponding to the other part of contours of the openings **340**, **330**, and **220** respectively of the bottom plate **34**, the cover plate **33**, and the supporting base **22**. That is, the aperture of the overall camera device is unchanged at the time and is an initial value. The first shutter blade **31** and the second shutter blade **32** are modularized respectively with the first driver **35** and the second driver **36**. When the first shutter blade **31** and the second shutter blade **32** are disposed crossover from each other (e.g., in a top-to-down overlap configuration), it is convenient to replace the module of the first or the second shutter blade **31**, **32** without interfering by another module.

Please refer to FIG. 5 with reference to FIG. 3. When the first driver **35** drives the first shutter blade **31** and makes it be located at the turn-on position and the second driver **36** drives the second shutter blade **32** and makes it be located at the turn-off position, the first arc contour **310** of the first shutter blade **31** will park at a position corresponding to a part of contours of the openings **340**, **330**, and **220** respectively of the bottom plate **34**, the cover plate **33**, and the supporting base **22** and the second driver **36** makes the second hole **O2** of the second shutter blade **32** move toward the optical axis of the camera lens and shift to a position overlapping the aperture of the plate (e.g., the bottom plate **34**, the cover plate **33**, or the supporting base **22**). Meanwhile, the aperture of the camera device is defined by the second aperture of the second hole **O2** of the second shutter blade **32**.

Please refer to FIG. 6 with reference to FIG. 3. When the first driver **35** drives the first shutter blade **31** and makes it be located at the turn-off position and the second driver **36** drives the second shutter blade **32** and makes it be located at the turn-on position, the second arc contour **320** of the second shutter blade **32** will park at a position corresponding to a part of contours of the openings **340**, **330**, and **220** respectively of the bottom plate **34**, the cover plate **33**, and the supporting base **22** and the first driver **35** makes the first hole **O1** of the first shutter blade **31** move toward the optical axis of the camera lens and shift to a position overlapping the aperture of the plate (e.g., the bottom plate **34**, the cover plate **33**, or the supporting base **22**). Meanwhile, the aperture of the camera device is defined by the first aperture of the first hole **O1** of the first shutter blade **31**.

The afore-described framework can carry out a three-stage aperture adjustment. The aperture of the optical system can be adjusted to the aperture of the plate, the first aperture, and the second aperture. In addition, the first driver **35** and the second driver **36** can be deployed at the lateral side of the optical system frame, for example, be disposed at two opposite sides of the driver supporting base. The above-described embodiments are illustrated by two shutter blades **31** and **32** cooperating with two drivers **35** and **36**. It can be understood that assuming that one shutter blade and one driver are taken as a set of aperture adjusting device, there

13

can have only one set of aperture adjusting device. However, it can also deploy three, four, or more sets of aperture adjusting device at the lateral side of the optical system frame for carrying out a multi-stage aperture adjustment. Further, it can also deploy two or more than two blade rooms arranged front and back. The holes of the shutter blades in the blade rooms are arranged with different apertures. In this way, this increases the number of types of aperture for the user to choose.

The present invention further provides a fourth embodiment. As shown in FIG. 7, the fourth embodiment follows the reference numbers used in the third embodiment. The difference between the fourth embodiment and the third embodiment is that the camera device of the fourth embodiment includes the first shutter aperture **31** and the first driver **35** without including the second shutter aperture **32** and the second driver **36**.

Please refer to FIG. 8 with reference to FIG. 7. When the first driver **35** drives the first shutter blade **31** and makes it be located at the turn-on position, the first arc contour **310** of the first shutter blade **31** will park at a position corresponding to a part of contours of the openings **340**, **330**, and **220** respectively of the bottom plate **34**, the cover plate **33**, and the supporting base **22**. That is, the aperture of the overall camera device is unchanged at the time and is an initial value. The first shutter blade **31** is modularized with the first driver **35**.

Please refer to FIG. 9 with reference to FIG. 7. When the first driver **35** drives the first shutter blade **31** and makes it be located at the turn-off position, the first driver **35** makes the first hole **O1** of the first shutter blade **31** move toward the optical axis of the camera lens and shift to a position overlapping the aperture of the plate (e.g., the bottom plate **34**, the cover plate **33**, or the supporting base **22**). Meanwhile, the aperture of the camera device is defined by the first aperture of the first hole **O1** of the first shutter blade **31**.

The basic structure of the optical lens of the present inventions are illustrated by FIG. 10A, FIG. 11A, FIG. 12A, FIG. 13A and FIG. 14A (respectively corresponding to a fifth, a sixth, a seventh, an eighth and a ninth embodiments). The basic structure of the optical lens of the present inventions are described by Table 1, Table 2, Table 3, Table 4 and Table 5 (respectively corresponding to a fifth, a sixth, a seventh, an eighth and a ninth embodiments). The optical lens comprises a lens group, which establishes an optical axis **OA** and is arranged along the optical axis **OA**. Object light rays enter such an optical system from an object side **OBJ** of the optical axis **OA** and form an image on an image plane **IP** at an image side **IMA** thereof. The optical lens further comprises a first aperture stop **STO1** and a second aperture stop **STO2**. Preferably, the first aperture stop **STO1** is disposed inside the lens group, that is, between any two lenses of the lens group; and the second aperture stop **STO2** is disposed outside the lens group at the outside of the object side **OBJ** of the optical axis **OA**, that is, at the outside of a lens of the lens group at the most object side **OBJ**.

In the illustrated optical lens, the aperture of the optical lens is defined by the aperture of the second aperture stop **STO2** when a smaller aperture is required; the aperture of the optical lens is defined by the aperture of the first aperture stop **STO1** when a larger aperture is required. For instance, when a smaller aperture is required, decrease the aperture of the second aperture stop **STO2** to be at least less than the aperture of the first aperture stop **STO1**. Since the aperture of the first aperture stop **STO1** is greater than that of the second aperture stop **STO2**, the first aperture stop **STO1** ceases to be effective due to the evolution of light path and

14

is thus in an inactive state. Meanwhile, the second aperture stop **STO2** is in an active state, and therefore the smaller aperture of the optical lens is now defined by the aperture of the second aperture stop **STO2**. When a larger aperture is required, increase the aperture of the second aperture stop **STO2** to be at least greater than the aperture of the first aperture stop **STO1**. Meanwhile, the second aperture stop **STO2** ceases to be effective due to the evolution of light path and is thus in an inactive state. The first aperture stop **STO1** is in an active state, and therefore the aperture of the optical lens is now defined by the first aperture stop **STO1**. The afore-described example is illustrated by taking the second aperture stop **STO2** as an aperture stop with adjustable aperture for example. However, the following examples can also achieve above effects, that is, the first aperture stop **STO1** is an aperture stop with adjustable aperture or both of the first aperture stop **STO1** and the second aperture stop **STO2** are adjustable in aperture. However, the second aperture stop **STO2** that is adjustable in aperture has an advantage. That is, the aperture stop with adjustable aperture can be deployed at the outside of the lens at the most object side. Since there has more room for accommodating an aperture adjusting device in this configuration, the size of the optical lens can be reduced.

The afore-described optical framework improves the effective aperture range. In comparison to the optical lens having an aperture stop with adjustable aperture disposed within the lens group in the conventional skills, the optical lens of the present invention can deploy the aperture stop with adjustable aperture (that is, the second aperture stop **STO2**) at the outside of the lens group, and therefore the structural components or electric control components required to be used to mount the aperture-adjustable stop can be moved to the outside of the lens group, thereby carrying out further thinning of the optical lens.

The following is described with a package structure of the optical lens of the present invention.

Please refer to FIG. 15, which is a schematic diagram showing a package structure in accordance with a fifth embodiment of an optical lens of the present invention. The optical lens is packaged in an electronic device equipped with a photographing function and is disposed inside an external case **11** of the electronic device. The external case **11** has an opening **110** exposed therefrom, and light rays can thus enter the inner space of the optical lens through the opening **110**. The optical lens has an optical system frame **15**, a lens system **17**, and an image recorder **18**. The optical system frame **15** is made of plastic and is a fastening member of the optical system. The lens system **17** comprises one or more lenses mounted on the optical system frame **15**. The image recorder **18** can receive the light rays transmitted from the lens system **17** and thus form an image on the image plane. The optical lens also has a transparent plate **12**, a cover plate **13**, a base plate **16**, and one or more aperture adjusting blades **14**. The base plate **16** is fastened on the optical system frame **15** or formed by extending from the optical system frame **15**. The base plate **16** has an opening **160** disposed at a central part thereof. The cover plate **13** is spaced apart from the base plate **16** and is fastened to the base plate **16** or the optical system frame **15**. The cover plate **13** is a flat metal plate and is perforated to form an opening **130** at a central part thereof. The opening **130** of the cover plate **13** corresponds to the opening **160** of the base plate **16**. The aperture adjusting blade **14** is disposed in an accommodating space formed between the cover plate **13** and the base plate **16**. This optical lens is an aperture-adjustable optical lens. The aperture adjusting blade **14** is driven by a

15

driver (not shown) of an aperture adjusting device (not shown). The aperture of the optical lens is altered by adjusting the position of the aperture adjusting blade **14**. The transparent plate **12** is disposed at the inner side of the external case **11** and is disposed next to the exposed opening **110** of the external case **11**. Also, the transparent plate **12** is attached to the optical system frame **15**. As can be seen from FIG. **15**, the lens system **17**, the base plate **16**, the aperture adjusting blade **14**, the cover plate **13**, and the transparent plate **12** are sequentially arranged in order from the image side to the object side, that is, from the image recorder **18** to the exposed opening **110** of the external case **11**.

As described above, the aperture adjusting blade **14** is disposed between the lens at the most object side and the exposed opening **110** of the external case **11**. Therefore, in comparison to that disposed between any two lenses, this deployment leads to have more room at the lateral side for accommodating its driver and leads not to affect the deployment of other components. Further, the transparent plate **12** is fastened or attached to the optical system frame **15**. Such a technical scheme can further prevent the dust from falling into the blade room accommodating the aperture adjusting blade **14**.

Please refer to FIG. **16**, which is a schematic diagram showing a package structure in accordance with a sixth embodiment of an optical lens of the present invention. In comparison to the package structure described in the fifth embodiment, the present embodiment locates the base plate **16** at the upper side and locates the cover plate **13** at the lower side. Screws **19** are utilized to fasten the cover plate **13** to the base plate **16** or the optical system frame **15**. The cover plate **13** and the base plate **16** are spaced a part from each other. The aperture adjusting blade **14** is accommodated between the cover plate **13** and the base plate **16**. As can be seen from FIG. **16**, the lens system **17**, the cover plate **13**, the aperture adjusting blade **14**, the base plate **16**, and the transparent plate **12** are sequentially arranged in order from the image side to the object side, that is, from the image recorder **18** to the exposed opening **110** of the external case **11**. In such a technical scheme, the cover plate **13** is moved to the lower side and thus the plastic material of the optical system frame **15** can be partially removed for deploying a space for disposing the screws **19**, and therefore the fastening position of the screw can be moved down. In comparison to the embodiment shown in FIG. **15**, this embodiment can reduce the thickness of the optical lens, and thus reduce the thickness of the device equipped with the optical lens.

The optical lens provided in the present invention will be further described with reference to the following five embodiments taking a mobile phone camera lens for example and the data adopted in the respective embodiments are listed for reference. The fifth embodiment is illustrated in FIGS. **10A** to **10E**; the sixth embodiment is illustrated in FIGS. **11A** to **11E**; the seventh embodiment is illustrated in FIGS. **12A** to **12E**; the eighth embodiment is illustrated in FIGS. **13A** to **13E**; and the ninth embodiment is illustrated in FIGS. **14A** to **14E**.

Some lenses in the optical lens of the present invention are aspheric lenses. The shape of an aspheric lens may be expressed by the following formula:

$$z(r) = \frac{C \cdot r^2}{1 + \sqrt{1 - (1+k) \cdot C^2 \cdot r^2}} + \alpha_1 r^2 + \alpha_2 r^4 + \alpha_3 r^6 + \alpha_4 r^8 + \alpha_5 r^{10} + \alpha_6 r^{12} + \alpha_7 r^{14} + \alpha_8 r^{16} + \alpha_9 r^{18} + \alpha_{10} r^{20} \dots$$

16

where z represents the sag of a point on the aspheric surface at a height h distanced to a central axis of the lens; C is a reciprocal of a paraxial curvature radius; r represents a height of a point on the aspheric surface with respect to the central axis; k is the conic constant of the aspheric lens; and $\alpha_1, \alpha_2, \dots$, and α_{10} are aspheric surface coefficients for even (greater than or equal to two) order terms.

FIG. **10A** is a schematic diagram showing an optical structure in accordance with a fifth embodiment of an optical lens of the present invention. The optical lens according to the fifth embodiment of the present invention comprises five pieces of lenses, which are a first lens **L1**, a second lens **L2**, a third lens **L3**, a fifth lens **L5**, and a fourth lens **L4** arranged in order from the image side IMA to the object side OBJ. The optical lens utilizes two low-dispersion lenses **L2** and **L3** cooperating with three high-dispersion lenses **L1**, **L4**, and **L5**. The framework of its refractive power is negative, positive, negative, positive, and positive in order from the image side to the object side. Specifically, the first lens **L1** is a lens having negative refractive power, and the image-side surface thereof is a concave face and has at least a point of inflection arranged thereon. The second lens **L2** is a lens having positive refractive power and has a concave surface facing the object side and a convex surface facing the image side. The third lens **L3** is approximate to a plano-concave lens. The fifth lens **L5** is approximate to a meniscus convex lens. The fourth lens **L4** is also approximate to a meniscus convex lens.

The optical lens according to the fifth embodiment of the present invention also has at least two aperture stops, that is, a first aperture stop **STO1** and a second aperture stop **STO2**. The first aperture stop **STO1** is disposed between the fourth lens **L4** and the fifth lens **L5** and the second aperture stop **STO2** is disposed at the outside of the lens at the most object side (that is, the fourth lens **L4**). The distance on the optical axis from the first aperture stop **STO1** to the image plane IP is **SL1**, the distance on the optical axis from the second aperture stop **STO2** to the image plane IP is **SL2**, and the distance on the optical axis from the object-side surface of the lens at the most object side (that is, the fourth lens **L4**) to the image plane IP is **TTL**. The optical lens according to the fifth embodiment of the present invention satisfies the following equation: $1.2 < (SL1 + SL2) / TTL < 2.5$.

As shown in Table 1 below, related data of the respective lenses of the optical lens shown in FIG. **10A** are shown in the condition that the first aperture stop **STO1** is in an active state and the second aperture stop **STO2** is in an inactive state. Table 1 shows that the focal length of the optical lens according to the fifth embodiment of the present invention is 4.363, and the refractive power for the respective lenses sequentially is -6.54966, 20.2192, -4.7998, 4.1284, and 4.7496 in order from **L1**, **L2**, **L3**, **L5**, and **L4**. In the condition that the first aperture stop **STO1** is in the active state, the effective f-number of this optical system is 1.8, the viewing angle is 76 degrees, and the total length of the optical lens is 5.21 mm. Further, in the condition that the second aperture stop **STO2** is in the active state, the effective f-number of this optical system is 2.4.

TABLE 1

Focal length = 4.36 mm F-number = 1.8 Maximum half angle of view = 38						
Surface Index		Radius of Curvature R (mm)	Thickness/ Distance D (mm)	Refractive Index (Nd)	Abbe No. (Vd)	Conic Constant
R0	Image Side					
R1	IR	Plano	0.399847	1.5168	64.16734	0
R2		Plano	0.145			0
R3	L1	∞	0.517358	1.535037	55.71072	-7.31959
R4		3.224664	0.687077			-37.468
R5	L2	-6.84747	0.316889	1.651	21.5	12.32
R6		-13.594	0.626108			-3121.95
R7	L3	-202.472	0.655789	1.651	21.5	-7063.6
R8		-3.109	0.232827			0
R9	L5	-2.63506	0.038179	1.79679	45.35	0
R10		-11.8121	0.530297			0
R11	STO1	∞	0.301989			0
R12	L4	4.492898	0.090208	1.58913	61.18217	0
R13		1.824606	0.67288			-0.68912
R14	STO2	∞	0			0
R15	Object Side					

Table 2 shows related data of aspheric lenses shown in Table 1.

TABLE 2

IMA surface of L1	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.068326463	0.022631598	-0.005707664	0.00079391
OBJ surface of L1	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.16234125	0.063601191	-0.014359732	-0.000663867
IMA surface of L2	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.037355326	0.056839178	-0.047227199	0.017140171
OBJ surface of L2	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.046389552	0.054728295	-0.087083506	0.053893156
IMA surface of L3	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.064112847	0.017941495	0.038314249	-0.029126597
OBJ surface of L3	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.072558289	-0.015939819	0.077639598	-0.013915421
IMA surface of L4	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.013943442	0.020475405	-0.057163629	0.023398376
OBJ surface of L4	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	0.006641832	0.01166876	-0.001369296	-0.022192564
IMA surface of L5	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.013306555	-0.034459418	0.011549355	0.044164219
OBJ surface of L5	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.047675783	0.004435779	0.004355224	0.004355224
IMA surface of L5	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.02213491	-0.023906357	0.000935276	0.011708534
OBJ surface of L5	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
	0	-0.028121262	0.009003516	0.002926385	0.002926885

60

FIG. 10B is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the fifth embodiment of the present invention in the condition that the first aperture stop STO1 is in the active state and the second aperture stop STO2 is in the inactive state. FIG. 10C is a diagram showing the optical performance including field curvature and distortion of the optical

lens according to the fifth embodiment of the present invention in the condition that the first aperture stop STO1 is in the inactive state and the second aperture stop STO2 is in the active state. FIG. 10D is a diagram showing polychromatic diffraction modulation transfer function (MTF) of the optical lens according to the fifth embodiment of the present invention in the condition that the first aperture stop STO1 is in

65

the active state and the second aperture stop STO2 is in the inactive state. FIG. 10E is a diagram showing polychromatic diffraction modulation transfer function of the optical lens according to the fifth embodiment of the present invention in the condition that the first aperture stop STO1 is in the inactive state and the second aperture stop STO2 is in the active state.

TABLE 3

Focal length = 3.29 mm F-number = 2.0 Maximum half angle of view = 34.5						
Surface Index		Radius of Curvature R (mm)	Thickness/ Distance D (mm)	Refractive Index (Nd)	Abbe No. (Vd)	Conic Constant
R0	Image Side					
R1	IR	Plano	0.004258	1.5168	64.16734	0
R2		Plano	0.145			0
R3	L1	∞	0.88	1.5441	56.0936	-6.35903
R4		4.088057	0.378762			-133.327
R5	L2	-1.05192	0.238975	1.5441	56.0936	-0.77093
R6		-2.37771	0.450713			0.179669
R7	L3	-6.89504	0.464627	1.5441	56.0936	28.14493
R8		10.49814	0.390025			20.16273
R9	L5	1.193641	0.364742	1.635517	23.97184	-6.08747
R10		2.664022	0.215475			-35.7261
R11	STO1	∞	0.036573			0
R12	L4	-6.82072	-0.00473	1.5441	56.0936	7.335077
R13		1.644252	0.408306			0.125673
R14	STO2	∞	0			0
R15	Object Side					

Table 4 shows related data of aspheric lenses shown in Table 3.

TABLE 4

IMA surface of L1	Coefficient on r^2 0	Coefficient on r^4 -0.12261161	Coefficient on r^6 0.049977706	Coefficient on r^8 -0.017665442	Coefficient on r^{10} 0.003089853
OBJ surface of L1	Coefficient on r^2 0	Coefficient on r^4 -0.16359498	Coefficient on r^6 0.04211978	Coefficient on r^8 -0.001194497	Coefficient on r^{10} -0.000624809
IMA surface of L2	Coefficient on r^2 0	Coefficient on r^4 0.24409123	Coefficient on r^6 -0.17355054	Coefficient on r^8 0.070243881	Coefficient on r^{10} -0.004203009
OBJ surface of L2	Coefficient on r^2 0	Coefficient on r^4 0.038536069	Coefficient on r^6 -0.11142259	Coefficient on r^8 0.013661737	Coefficient on r^{10} -0.021625202
IMA surface of L3	Coefficient on r^2 0	Coefficient on r^4 -0.055902836	Coefficient on r^6 -0.038874183	Coefficient on r^8 0.017980386	Coefficient on r^{10} -0.028521372
OBJ surface of L3	Coefficient on r^2 0	Coefficient on r^4 -0.051388901	Coefficient on r^6 -0.03247322	Coefficient on r^8 0.15238218	Coefficient on r^{10} -0.077963205
IMA surface of L4	Coefficient on r^2 0	Coefficient on r^4 0.13622006	Coefficient on r^6 -0.16886925	Coefficient on r^8 0.34374751	Coefficient on r^{10} -0.58600811
OBJ surface of L4	Coefficient on r^2 0	Coefficient on r^4 0.009462623	Coefficient on r^6 -0.012480374	Coefficient on r^8 -0.01772093	Coefficient on r^{10} 0.044712063
IMA surface of L5	Coefficient on r^2 0	Coefficient on r^4 0.044795139	Coefficient on r^6 0.11055632	Coefficient on r^8 -0.15080884	Coefficient on r^{10} -0.070661935
OBJ surface of L5	Coefficient on r^2 0	Coefficient on r^4 0.040196019	Coefficient on r^6 -0.090194898	Coefficient on r^8 0.2241962	Coefficient on r^{10} -0.41489922

FIG. 12A is a schematic diagram showing an optical structure in accordance with a seventh embodiment of an optical lens of the present invention. The optical lens according to the seventh embodiment of the present invention comprises four pieces of lenses, which are a first lens L1, a second lens L2, a third lens L3, and a fourth lens L4 arranged in order from the image side IMA to the object side OBJ. The optical lens utilizes one low-dispersion lens L3 cooperating with three high-dispersion lenses L1, L2, and L4. The framework of its refractive power is negative, positive, negative, and positive in order from the image side to the object side. Specifically, the first lens L1 is a lens having negative refractive power, and the image-side surface thereof is a concave face and has at least a point of inflection arranged thereon. The second lens L2 is a lens having positive refractive power and has a concave surface facing the object side and a convex surface facing the image side. The third lens L3 is approximate to a meniscus concave lens. The fourth lens L4 is approximate to a bi-convex lens.

The optical lens according to the seventh embodiment of the present invention also has at least two aperture stops, that is, a first aperture stop STO1 and a second aperture stop STO2. The first aperture stop STO1 is disposed between the third lens L3 and the fourth lens L4 and the second aperture

stop STO2 is disposed at the outside of the lens at the most object side (that is, the fourth lens L4). The distance on the optical axis from the first aperture stop STO1 to the image plane IP is SL1, the distance on the optical axis from the second aperture stop STO2 to the image plane IP is SL2, and the distance on the optical axis from the object-side surface of the lens at the most object side (that is, the fourth lens L4) to the image plane IP is TTL. The optical lens according to the seventh embodiment of the present invention satisfies the following equation: $1.2 < (SL1 + SL2) / TTL < 2.5$.

As shown in Table 5 below, related data of the respective lenses of the optical lens shown in FIG. 12A are shown in the condition that the first aperture stop STO1 is in an active state and the second aperture stop STO2 is in an inactive state. Table 5 shows that the focal length of the optical lens according to the seventh embodiment of the present invention is 2.224, and the refractive power for the respective lenses sequentially is -1.27834, 1.15622, -2.82002, and 1.81389 in order from L1, L2, L3, and L4. In the condition that the first aperture stop STO1 is in the active state, the effective f-number of this optical system is 1.8, the viewing angle is 70 degrees, and the total length of the optical lens is 3.09 mm. Further, in the condition that the second aperture stop STO2 is in the active state, the effective f-number of this optical system is 2.4.

TABLE 5

Focal length = 2.22 mm F-number = 1.8 Maximum half angle of view = 35						
Surface Index		Radius of Curvature R (mm)	Thickness/ Distance D (mm)	Refractive Index (Nd)	Abbe No. (Vd)	Conic Constant
R0	Image Side					
R1	IR	Plano	0.377173	1.51633	64,14202	0
R2		Plano	0.3			0
R3	L1	0.634243	0.3	1.5441	56.0936	-7.33354
R4		8.27339	0.33814			-10914.700000
R5	L2	-0.65879	0.035445	1.69003	52.75	-3.17751
R6		-2.65838	0.459447			-8.45873
R7	L3	1.547733	0.397755	1.632755	23.29495	-5.06099
R8		11.75026	0.229978			0
R9	STO1	∞	0.075473			0
R10	L4	-3.3504	-0.04548	1.54	56.0936	0
R11		1.313104	0.623902			0.124189
R12	STO2	∞	0			0
R13	Object Side					

45

Table 6 shows related data of aspheric lenses shown in Table 5.

TABLE 6

	Coefficient on r^2	Coefficient on r^4	Coefficient on r^6	Coefficient on r^8	Coefficient on r^{10}
IMA surface of L1	0	-0.28029487	0.22709754	-0.15016616	0.034805119
	Coefficient on r^{12}	Coefficient on r^{14}	Coefficient on r^{16}	Coefficient on r^{18}	Coefficient on r^{20}
	-0.001965392	0.003020866	-0.001881296	-0.001881296	-0.001881296
OBJ surface of L1	0	-0.28339184	0.21241489	-0.093783116	-0.033079793
	Coefficient on r^{12}	Coefficient on r^{14}	Coefficient on r^{16}	Coefficient on r^{18}	Coefficient on r^{20}
	0.017751576	-0.023275011	0.028276075	0.028276075	0.028276075
IMA surface of L2	0	0.056170984	-0.75262164	1.8432287	-1.4175232
	Coefficient on r^{12}	Coefficient on r^{14}	Coefficient on r^{16}	Coefficient on r^{18}	Coefficient on r^{20}
	-0.81543338	1.2821335	0	0	0
OBJ surface of L2	0	0.004277422	0.014660242	-0.024193322	0.18893841
	Coefficient on r^{12}	Coefficient on r^{14}	Coefficient on r^{16}	Coefficient on r^{18}	Coefficient on r^{20}
	-1.7521547	2.2681374	0	0	0
IMA surface of L3	0	0.12014168	-0.039058636	-0.73253478	4.5037627
	Coefficient on r^{12}	Coefficient on r^{14}	Coefficient on r^{16}	Coefficient on r^{18}	Coefficient on r^{20}
	4.6527637	0	0	0	0

TABLE 6-continued

OBJ surface of L3	Coefficient on r^2 0	Coefficient on r^4 -0.13331015	Coefficient on r^6 -1.0335069	Coefficient on r^8 5.1431284	Coefficient on r^{10} 4.7487291
IMA surface of L4	Coefficient on r^{12} -1.1243573	Coefficient on r^{14} 0	Coefficient on r^{16} 0	Coefficient on r^{18} 0	Coefficient on r^{20} 0
OBJ surface of L4	Coefficient on r^2 0	Coefficient on r^4 -0.015180883	Coefficient on r^6 -1.1936464	Coefficient on r^8 4.9505495	Coefficient on r^{10} -5.7629299
	Coefficient on r^{12} 0	Coefficient on r^{14} 0	Coefficient on r^{16} 0	Coefficient on r^{18} 0	Coefficient on r^{20} 0
OBJ surface of L4	Coefficient on r^2 0	Coefficient on r^4 -0.047670449	Coefficient on r^6 -0.1274337	Coefficient on r^8 0.12082106	Coefficient on r^{10} -0.45177542
	Coefficient on r^{12} 0	Coefficient on r^{14} 0	Coefficient on r^{16} 0	Coefficient on r^{18} 0	Coefficient on r^{20} 0

FIG. 12B is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the seventh embodiment of the present invention in the condition that the first aperture stop STO1 is in the active state and the second aperture stop STO2 is in the inactive state. FIG. 12C is a diagram showing the optical performance including field curvature and distortion of the optical lens according to the seventh embodiment of the present invention in the condition that the first aperture stop STO1 is in the inactive state and the second aperture stop STO2 is in the active state. FIG. 12D is a diagram showing

polychromatic diffraction modulation transfer function (MTF) of the optical lens according to the seventh embodiment of the present invention in the condition that the first aperture stop STO1 is in the active state and the second aperture stop STO2 is in the inactive state. FIG. 12E is a diagram showing polychromatic diffraction modulation transfer function of the optical lens according to the seventh embodiment of the present invention in the condition that the first aperture stop STO1 is in the inactive state and the second aperture stop STO2 is in the active state.

TABLE 7

Focal length = 2.318 mm F-number = 1.8 Maximum half angle of view = 44.5						
Surface Index		Radius of Curvature R (mm)	Thickness/Distance D (mm)	Refractive Index (Nd)	Abbe No. (Vd)	Conic Constant
R0	Image Side					
R1	IR	Plano	0.105362	1.51633	64,14202	0
R2		Plano	0.21			0
R3	L1	0.898954	0.6844	1.5441	56.0936	-2.90282
R4		1.195782	0.452062			-0.44492
R5	L2	-1.26429	0.202173	1.650958	21.51361	0.051651
R6		-0.76452	0.455948			-0.24406
R7	L3	-1.19373	0.081371	1.755	51.2	0.037002
R8		4.0376	0.499949			5.994392
R9	STO1	∞	0.35304			0
R10	L4	8.735552	0.003026	1.755	51.2	0
R11		1.905175	0.362252			2.440844
R12	STO2	∞	0			0
R13	Object Side					

45

Table 8 shows related data of aspheric lenses shown in Table 7.

TABLE 8

IMA surface of L1	Coefficient on r^2 0	Coefficient on r^4 -0.23128355	Coefficient on r^6 0.14175378	Coefficient on r^8 -0.067994162	Coefficient on r^{10} 0.0213542
	Coefficient on r^{12} -0.004568351	Coefficient on r^{14} 0.000508655	Coefficient on r^{16} -1.12562E-05	Coefficient on r^{18} -1.12562E-05	Coefficient on r^{20} -1.12562E-05
OBJ surface of L1	Coefficient on r^2 0	Coefficient on r^4 -0.52650509	Coefficient on r^6 0.25194	Coefficient on r^8 -0.17353961	Coefficient on r^{10} 0.14660685
	Coefficient on r^{12} -0.10183205	Coefficient on r^{14} 0.039677909	Coefficient on r^{16} -0.006161127	Coefficient on r^{18} -0.006161127	Coefficient on r^{20} -0.006161127
IMA surface of L2	Coefficient on r^2 0	Coefficient on r^4 0.27010932	Coefficient on r^6 0.06650994	Coefficient on r^8 -0.32301541	Coefficient on r^{10} 0.77365395
	Coefficient on r^{12} -0.94713717	Coefficient on r^{14} 0.59387626	Coefficient on r^{16} -0.14295684	Coefficient on r^{18} -0.14295684	Coefficient on r^{20} -0.14295684
OBJ surface of L2	Coefficient on r^2 0	Coefficient on r^4 0.66898512	Coefficient on r^6 -0.61306349	Coefficient on r^8 1.4858343	Coefficient on r^{10} -1.342644
	Coefficient on r^{12} 2.9844358	Coefficient on r^{14} -6.412385	Coefficient on r^{16} 4.6891119	Coefficient on r^{18} 4.6891119	Coefficient on r^{20} 4.6891119
IMA surface of L3	Coefficient on r^2 0	Coefficient on r^4 -0.14982592	Coefficient on r^6 0.078819059	Coefficient on r^8 -0.63534856	Coefficient on r^{10} 2.5712369
	Coefficient on r^{12} -3.7370466	Coefficient on r^{14} 1.9102048	Coefficient on r^{16} -0.30854624	Coefficient on r^{18} -0.30854624	Coefficient on r^{20} -0.30854624

TABLE 8-continued

OBJ surface of L3	Coefficient on r^2 0	Coefficient on r^4 -0.28823379	Coefficient on r^6 -0.22965413	Coefficient on r^8 0.14621395	Coefficient on r^{10} -1.3892127
	Coefficient on r^{12} -0.77150298	Coefficient on r^{14} 17.474959	Coefficient on r^{16} -20.688299	Coefficient on r^{18} -20.688299	Coefficient on r^{20} -20.688299
IMA surface of L4	Coefficient on r^2 0	Coefficient on r^4 -0.178712	Coefficient on r^6 0.39455994	Coefficient on r^8 -2.7937285	Coefficient on r^{10} 1.5267098
	Coefficient on r^{12} 28.838141	Coefficient on r^{14} -82.831787	Coefficient on r^{16} 66.34717	Coefficient on r^{18} 66.34717	Coefficient on r^{20} 66.34717
OBJ surface of L4	Coefficient on r^2 0	Coefficient on r^4 -0.087825582	Coefficient on r^6 -0.23623031	Coefficient on r^8 0.25832584	Coefficient on r^{10} -0.042191405
	Coefficient on r^{12} 4.1396749	Coefficient on r^{14} 10.902824	Coefficient on r^{16} -9.0782311	Coefficient on r^{18} -9.0782311	Coefficient on r^{20} -9.0782311

TABLE 9

Focal length = 4.15 mm F-number = 1.6 Maximum half angle of view = 39.5						
Surface Index		Radius of Curvature R (mm)	Thickness/Distance D (mm)	Refractive Index (Nd)	Abbe No (Vd)	Conic Constant
R0	Image Side					
R1	IR	Plano	0.11413	1.5168	64.16734	0
R2		Plano	0.145			0
R3	L1	∞	0.8	1.535037	55.71072	-5.44208
R4		3.015938	0.745032			-17.1337
R5	L2	-6.7872	0.313655	1.651	21.5	12.06767
R6		-16.0254	0.554647			-2555.19
R7	L3	-100.075	0.591153	1.651	21.5	-11896
R8		-3.08129	0.232166			0
R9	L5	-2.76701	0.038179	1.79679	45.35	0
R10		-15.7774	0.641223			0
R11	STO1	∞	0.345203			0
R12	L4	4.659665	0.078218	1.59	61.18	0
R13		1.870937	0.598805			-0.69405
R14	STO2	∞	0			0
R15	Object Side					

Table 10 shows related data of aspheric lenses shown in Table 9.

TABLE 10

IMA surface of L1	Coefficient on r^2 0	Coefficient on r^4 -0.071190542	Coefficient on r^6 0.024244691	Coefficient on r^8 -0.00591398	Coefficient on r^{10} 0.000790785
	Coefficient on r^{12} 4.92E-05	Coefficient on r^{14} 3.19E-08	Coefficient on r^{16} 9.62427E-08	Coefficient on r^{18} 9.62427E-08	Coefficient on r^{20} 9.62427E-08
OBJ surface of L1	Coefficient on r^2 0	Coefficient on r^4 -0.16500606	Coefficient on r^6 0.062901685	Coefficient on r^8 -0.014461672	Coefficient on r^{10} -0.000675361
	Coefficient on r^{12} 0.000665084	Coefficient on r^{14} -5.40E-06	Coefficient on r^{16} -9.74299E-06	Coefficient on r^{18} -9.74299E-06	Coefficient on r^{20} -9.74299E-06
IMA surface of L2	Coefficient on r^2 0	Coefficient on r^4 -0.03644324	Coefficient on r^6 0.056433494	Coefficient on r^8 -0.048174107	Coefficient on r^{10} 0.01705914
	Coefficient on r^{12} -0.002686547	Coefficient on r^{14} -6.06425E-05	Coefficient on r^{16} 6.32451E-05	Coefficient on r^{18} 6.32451E-05	Coefficient on r^{20} 6.32451E-05
OBJ surface of L2	Coefficient on r^2 0	Coefficient on r^4 -0.035879366	Coefficient on r^6 0.049041986	Coefficient on r^8 -0.087187532	Coefficient on r^{10} 0.05414856
	Coefficient on r^{12} -0.016025378	Coefficient on r^{14} 0.000179043	Coefficient on r^{16} 0.000657297	Coefficient on r^{18} 0.000657297	Coefficient on r^{20} 0.000657297
IMA surface of L3	Coefficient on r^2 0	Coefficient on r^4 -0.061833968	Coefficient on r^6 0.014413759	Coefficient on r^8 0.036786997	Coefficient on r^{10} -0.029378927
	Coefficient on r^{12} 0.008084592	Coefficient on r^{14} 0.001797025	Coefficient on r^{16} 0.000727565	Coefficient on r^{18} -0.000727565	Coefficient on r^{20} -0.000727565
OBJ surface of L3	Coefficient on r^2 0	Coefficient on r^4 -0.07261039	Coefficient on r^6 -0.018200106	Coefficient on r^8 0.075646828	Coefficient on r^{10} -0.013022632
	Coefficient on r^{12} -0.024606296	Coefficient on r^{14} 0.007762861	Coefficient on r^{16} -0.000321085	Coefficient on r^{18} -0.000321085	Coefficient on r^{20} -0.000321085
IMA surface of L4	Coefficient on r^2 0	Coefficient on r^4 -0.015873347	Coefficient on r^6 0.023847742	Coefficient on r^8 -0.053177251	Coefficient on r^{10} 0.022204617
	Coefficient on r^{12} 0.007014824	Coefficient on r^{14} -0.015851821	Coefficient on r^{16} 0.005477248	Coefficient on r^{18} 0.005477248	Coefficient on r^{20} 0.005477248

TABLE 10-continued

OBJ surface of L4	Coefficient on r^2 0	Coefficient on r^4 0.006465554	Coefficient on r^6 0.01071186	Coefficient on r^8 -0.00123002	Coefficient on r^{10} -0.022193926
IMA surface of L5	Coefficient on r^{12} 0.025220379	Coefficient on r^{14} -0.011482542	Coefficient on r^{16} 0.000917697	Coefficient on r^{18} 0.000917697	Coefficient on r^{20} 0.000917697
OBJ surface of L5	Coefficient on r^2 0	Coefficient on r^4 -0.017238977	Coefficient on r^6 -0.037305922	Coefficient on r^8 0.010955635	Coefficient on r^{10} 0.046272346
	Coefficient on r^{12} -0.044312667	Coefficient on r^{14} 0.006289162	Coefficient on r^{16} 0.002419004	Coefficient on r^{18} 0.002419004	Coefficient on r^{20} 0.002419004
OBJ surface of L5	Coefficient on r^2 0	Coefficient on r^4 -0.019858833	Coefficient on r^6 -0.025689834	Coefficient on r^8 0.000320202	Coefficient on r^{10} 0.014439705
	Coefficient on r^{12} -0.025103433	Coefficient on r^{14} 0.009597725	Coefficient on r^{16} 0.000453701	Coefficient on r^{18} 0.000453701	Coefficient on r^{20} 0.000453701

In the embodiments of the present invention, the shutter blade has a hole having an aperture. The aperture of a camera lens can be adjusted by driving the shutter blade using a driver and thus making the hole move toward the optical axis and shift to a position overlapping the original aperture. There can have multiple sets of the shutter blade and the driver so as to carry out a multi-stage aperture adjustment of the camera lens. An adjustment of depth of field can thus be carried out by a selection of aperture. In addition, in the embodiments of the present invention, one shutter blade is cooperated with one driver. It is convenient in replacement when these components are malfunctioned.

While the preferred embodiments of the present invention have been illustrated and described in detail, various modifications and alterations can be made by persons skilled in this art. The embodiment of the present invention is therefore described in an illustrative but not restrictive sense. It is intended that the present invention should not be limited to the particular forms as illustrated, and that all modifications and alterations which maintain the spirit and realm of the present invention are within the scope as defined in the appended claims.

What is claimed is:

1. A camera device, which is disposed in an electronic apparatus, comprising:

an optical system frame;
the electronic apparatus having an external shell with an opening exposed;

a lens system deployed in the external shell of the electronic apparatus and mounted on the optical system frame;

a bottom plate fastened to the optical system frame or formed by extending from the optical system frame;

a cover plate fastened to the bottom plate and distanced away from the bottom plate;

a fastening member having a base and an elongated part extending from the base, the base of the fastening member accommodated in the bottom plate, and the elongated part of the fastening member penetrating the bottom plate and fastened to the cover plate;

at least one shutter blade disposed between the cover plate and the bottom plate, configured to adjust an aperture of the camera device; and

a transparent plate forming an accommodating space for accommodating the optical system frame, the bottom plate, and the cover plate, the transparent plate being located in the external shell and a part of the transparent plate being located between the bottom plate and the opening of the external shell, or between the cover plate and the opening of the external shell.

2. The camera device according to claim 1, wherein the part of the transparent plate, the cover plate, the at least one

shutter blade, and the bottom plate are arranged in order from the opening of the external shell to the lens system.

3. The camera device according to claim 2, wherein the cover plate has a first opening, the bottom plate has a second opening, and light rays are transmitted to the lens system sequentially via the opening of the external shell, the part of the transparent plate, the first opening, and the second opening or emitted out from the opening of the external shell in a reverse order.

4. The camera device according to claim 1, wherein the part of the transparent plate, the bottom plate, the at least one shutter blade, and the cover plate are arranged in order from the opening of the external shell to the lens system.

5. The camera device according to claim 4, wherein the cover plate has a first opening, the bottom plate has a second opening, and light rays are transmitted to the lens system sequentially via the opening of the external shell, the part of the transparent plate, the second opening, and the first opening or emitted out from the opening of the external shell in a reverse order.

6. The camera device according to claim 1, wherein the bottom plate has a concave part, the base of the fastening member is accommodated in the concave part of the bottom plate.

7. The camera device according to claim 1, wherein the optical system frame is made of a plastic material and the cover plate comprises a flat metal plate.

8. The camera device according to claim 1, wherein the lens system comprises at least two lenses and an aperture stop.

9. The camera device according to claim 8, wherein the aperture established by the at least one shutter blade is smaller than or equal to the aperture of the aperture stop of the lens system.

10. A camera device, which is disposed in an electronic apparatus, comprising:

an optical system frame;

the electronic apparatus having an external shell with an opening exposed;

a lens system deployed in the external shell of the electronic apparatus and mounted on the optical system frame;

a bottom plate having a first opening, the bottom plate being fastened to the optical system frame or formed by extending from the optical system frame, the bottom plate further having a concave part formed thereon;

a cover plate having a second opening, the cover plate being distanced away from the bottom plate;

a fastening member having a base and an elongated part extending from the base, the base of the fastening member being accommodated in the concave part of the bottom plate, and the elongated part of the fastening

member penetrating the concave part of the bottom plate and being fastened to the cover plate; and at least one shutter blade disposed between the cover plate and the bottom plate, configured to adjust an aperture of the camera device,

wherein light rays are transmitted to the lens system sequentially via the opening of the external shell, the first opening of the bottom plate, and an aperture established by the shutter blade, and the second opening of the cover plate, or emitted out from the opening of the external shell in a reverse order.

11. A camera device with adjustable aperture, comprising: an optical system frame;

a lens system mounted on the optical system frame;

a plate configured to be fastened to the optical system frame or be formed by extending the optical system frame, the plate having an aperture;

a shutter blade coupled to the plate, the aperture of the plate being completely pervious to light when the shutter blade is at a first position, the aperture of the plate being partially pervious to light when the shutter blade is at a second position; and

a driver connecting to the shutter blade for causing a displacement of the shutter blade,

wherein the optical system frame comprises:

a supporting base;

a driver supporting base; and

a lens supporting base,

wherein at least two of or all of the supporting base, the driver supporting base, and the lens supporting base are integrately formed.

12. The camera device according to claim **11**, wherein the shutter blade has a hole disposed thereon, a diameter of the hole of the shutter blade is less than that of the aperture of the plate.

13. The camera device according to claim **12**, wherein the driver makes the hole of the shutter blade move to a position overlapping the aperture of the plate.

14. The camera device according to claim **12**, further comprising an additional shutter blade coupled to the plate.

15. The camera device according to claim **14**, wherein the shutter blade and the additional shutter blade are disposed crossover from each other.

16. The camera device according to claim **15**, further comprising an additional driver connecting to the additional shutter blade, the additional driver causing a displacement of the additional shutter blade.

17. The camera device according to claim **16**, wherein the additional shutter blade has an additional hole disposed thereon, and wherein the additional driver makes the additional hole of the additional shutter blade move to a position overlapping the aperture of the plate.

18. The camera device according to claim **11**, further comprising a cover plate configured to be distanced away from the plate, the shutter blade being disposed between the cover plate and the plate.

19. The camera device according to claim **11**, wherein the shutter blade is pivotably connected to the plate.

20. The camera device according to claim **11**, wherein the driver is configured to drive the shutter blade to a turn-on position or a turn-off position; wherein when the driver drives the shutter blade to the turn-off position, the aperture of the camera device is defined by the size of the hole of the shutter blade.

21. The camera device according to claim **20**, wherein the shutter blade comprises an arc contour, and wherein when the driver drives the shutter blade to the turn-on position, the

arc contour of the shutter blade corresponds to a part of contour of the aperture of the plate.

22. The camera device according to claim **11**, wherein the shutter blade is pivotably disposed on the optical system frame, the driver has a rotating rod which is driven by the driver and thus moves in an arc orbit, the shutter blade has an applying hole disposed thereon, the rotating rod penetrates the applying hole, the rotating rod applies force to the applying hole when rotates under control of the driver, thereby bringing out the shutter blade to move toward the turn-on position or the turn-off position.

23. The camera device according to claim **17**, wherein the additional shutter blade is pivotably disposed on the optical system frame, the additional driver has a rotating rod which is driven by the additional driver and thus moves in an arc orbit, the optical system frame has an orbital hole corresponding to the arc orbit, the additional shutter blade has an applying hole disposed thereon, the rotating rod penetrates the orbital hole and the applying hole, the rotating rod applies force to the applying hole when rotates under control of the additional driver, thereby bringing out the additional shutter blade to move toward the turn-on position or the turn-off position.

24. The camera device according to claim **11**, wherein the supporting base is configured to mount the plate and the shutter blade thereon; the driver supporting base is configured to mount the driver; and the lens supporting base is configured to mount a lens in the lens system thereon.

25. The camera device according to claim **24**, wherein the driver supporting base is disposed between the supporting base and the lens supporting base, and the driver is disposed at a lateral side of the driver supporting base.

26. The camera device according to claim **11**, wherein the lens system comprises:

a lens group establishing an optical axis, the lens group comprising a first negative lens, a second positive lens, a third lens, a fifth lens and a fourth positive lens arranged in order from an image side to an object side, wherein the first negative lens has an image-side surface which is a concave face and has a point of inflection arranged thereon; the second positive lens comprises a concave surface facing the object side and a convex surface facing the image side; the third lens is a plano-concave lens; the fourth lens is a meniscus convex lens; the fifth lens is a meniscus convex lens and disposed between the third lens and the fourth lens; a first aperture stop disposed between the image side and the lens of the lens group at the most object side; and a second aperture disposed between the object side and a lens of the lens group at the most object side;

the camera device further comprising:

a cover plate spaced apart from the plate and fastened to the plate;

a transparent plate attached to the optical system frame; and

wherein the lens group, the plate, the shutter blade, the cover plate, and the transparent plate are arranged in order from the image side to the object side,

wherein the shutter blade is included in the second aperture, the second aperture is altered by adjusting the shutter blade, the shutter blade is disposed between the plate and the cover plate,

wherein the lens group satisfies the following equation:

$$1.2 < (SL1 + SL2) / TTL < 2.5,$$

where **SL1** is a distance on the optical axis from the first aperture stop to the image plane; **SL2** is a distance on

31

the optical axis from the second aperture stop to the image plane; and TTL is a distance on the optical axis from an object-side surface of a lens of the lens group at the most object side to the image plane.

27. The camera device according to claim 11, wherein the lens system comprises:

a lens group establishing an optical axis, the lens group comprising a first negative lens, a second positive lens, a third lens, a fifth lens and a fourth positive lens arranged in order from an image side to an object side, wherein the first negative lens has an image-side surface which is a concave face and has a point of inflection arranged thereon; the second positive lens comprises a concave surface facing the object side and a convex surface facing the image side; the third lens is a plano-concave lens; the fourth lens is a meniscus convex lens; the fifth lens is a meniscus convex lens and disposed between the third lens and the fourth lens; and

a first aperture stop and a second aperture stop separately located on the optical axis;

the camera device further comprising:

a cover plate spaced apart from the plate and fastened to the plate; and

a transparent plate attached to the optical system frame; wherein the lens group, the plate, the shutter blade, the cover plate, and the transparent plate are arranged in order from the image side to the object side;

wherein the shutter blade is included in the second aperture, the second aperture is altered by adjusting the shutter blade, the shutter blade is disposed between the plate and the cover plate.

28. The camera device according to claim 11, wherein the lens system comprises:

32

a lens group establishing an optical axis, the lens group comprising a first lens, a second lens, a third lens, and a fourth positive lens arranged in order from an image side to an object side;

a first aperture stop disposed within the lens group; and a second aperture disposed at the object side outside the lens group; wherein

the lens group further comprises a fifth lens disposed between the third lens and the fourth lens, and the refractive power of the lenses of the lens group sequentially are negative, positive, negative, positive, and positive, or negative, positive, positive, negative, and positive in order from the image side to the object side, and wherein the first aperture stop is disposed between the third lens and fourth lens or between the fourth lens and the fifth lens,

wherein the second aperture is an adjustable aperture, and the aperture of the first aperture stop is greater than that of the second aperture when the second aperture is adjusted to be in an active state;

the camera device further comprising:

a cover plate having an opening, the cover plate being spaced apart from the base plate and fastened to the base plate through a screw,

wherein the lens group, the cover plate, the shutter blade, and the plate are arranged in order from the image side to the object side,

wherein the shutter blade is included in the second aperture, the second aperture is altered by adjusting the shutter blade, the shutter blade is disposed between the plate and the cover plate.

* * * * *