



US010535642B2

(12) **United States Patent**
Bibl et al.

(10) **Patent No.: US 10,535,642 B2**
(45) **Date of Patent: Jan. 14, 2020**

(54) **DISPLAY MODULE AND SYSTEM APPLICATIONS**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventors: **Andreas Bibl**, Los Altos, CA (US);
Kapil V. Sakariya, Los Altos, CA (US); **Vikram Pavate**, Foster City, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/145,879**

(22) Filed: **Sep. 28, 2018**

(65) **Prior Publication Data**

US 2019/0043845 A1 Feb. 7, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/908,505, filed on Feb. 28, 2018, now Pat. No. 10,147,711, which is a (Continued)

(51) **Int. Cl.**
G06F 3/042 (2006.01)
H01L 25/16 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H01L 25/167** (2013.01); **G04G 9/10** (2013.01); **G06F 1/163** (2013.01); **G06F 1/1652** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G06F 3/0412; G06F 3/041; G06F 3/042; G06F 3/044; G09G 3/30; G09G 3/32
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,717,743 A 2/1973 Costello
3,935,986 A 2/1976 Lattari et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1747668 A 3/2006
CN 101640712 A 2/2010
(Continued)

OTHER PUBLICATIONS

Asano, Kazutoshi, et al., "Fundamental Study of an Electrostatic Chuck for Silicon Wafer Handling" IEEE Transactions on Industry Applications, vol. 38, No. 3, May/Jun. 2002, pp. 840-845.
(Continued)


Primary Examiner — Vijay Shankar

(74) *Attorney, Agent, or Firm* — Jaffery Watson
Mendonsa & Hamilton LLP

(57) **ABSTRACT**

A display module and system applications including a display module are described. The display module may include a display substrate including a front surface, a back surface, and a display area on the front surface. A plurality of interconnects extend through the display substrate from the front surface to the back surface. An array of light emitting diodes (LEDs) are in the display area and electrically connected with the plurality of interconnects, and one or more driver circuits are on the back surface of the display substrate. Exemplary system applications include wearable, rollable, and foldable displays.

15 Claims, 16 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/417,015, filed on Jan. 26, 2017, now Pat. No. 9,922,966, which is a continuation of application No. 15/157,235, filed on May 17, 2016, now Pat. No. 9,582,036, which is a continuation of application No. 14/109,864, filed on Dec. 17, 2013, now Pat. No. 9,367,094.

(51) Int. Cl.

G06F 3/041 (2006.01)
G06F 1/16 (2006.01)
G09G 3/32 (2016.01)
H01L 25/075 (2006.01)
G04G 9/10 (2006.01)
H01L 23/29 (2006.01)
H01L 23/31 (2006.01)
H01L 23/538 (2006.01)
H01L 31/0216 (2014.01)
H01L 31/16 (2006.01)
H01L 33/44 (2010.01)
H01L 33/62 (2010.01)
H05K 1/11 (2006.01)
H05K 1/18 (2006.01)
H05K 1/14 (2006.01)
G06F 3/14 (2006.01)

(52) U.S. Cl.

CPC **G06F 3/042** (2013.01); **G06F 3/0412** (2013.01); **G09G 3/32** (2013.01); **H01L 23/293** (2013.01); **H01L 23/3171** (2013.01); **H01L 23/5384** (2013.01); **H01L 23/5386** (2013.01); **H01L 23/5387** (2013.01); **H01L 25/0753** (2013.01); **H01L 31/0216** (2013.01); **H01L 31/16** (2013.01); **H01L 33/44** (2013.01); **H01L 33/62** (2013.01); **G06F 3/14** (2013.01); **G09G 2380/02** (2013.01); **H01L 2924/0002** (2013.01); **H05K 1/115** (2013.01); **H05K 1/147** (2013.01); **H05K 1/189** (2013.01); **H05K 2201/10106** (2013.01); **H05K 2201/10128** (2013.01)

(56)**References Cited****U.S. PATENT DOCUMENTS**

5,131,582 A 7/1992 Kaplan et al.
5,378,926 A 1/1995 Chi et al.
5,435,857 A 7/1995 Han et al.
5,592,358 A 1/1997 Shamouilian et al.
5,740,956 A 4/1998 Seo et al.
5,794,839 A 8/1998 Kimura et al.
5,839,187 A 11/1998 Sato et al.
5,851,664 A 12/1998 Bennett et al.
5,888,847 A 3/1999 Rostoker et al.
5,903,428 A 5/1999 Grimard et al.
5,996,218 A 12/1999 Shamouilian et al.
6,071,795 A 6/2000 Cheung et al.
6,080,650 A 6/2000 Edwards
6,081,414 A 6/2000 Flanigan et al.
6,335,263 B1 1/2002 Cheung et al.
6,403,985 B1 6/2002 Fan et al.
6,420,242 B1 7/2002 Cheung et al.
6,521,511 B1 2/2003 Inoue et al.
6,558,109 B2 5/2003 Gibbel
6,613,610 B2 9/2003 Iwafuchi et al.
6,629,553 B2 10/2003 Odashima et al.
6,670,038 B2 12/2003 Sun et al.
6,683,368 B1 1/2004 Mostafazadeh
6,786,390 B2 9/2004 Yang et al.
6,878,607 B2 4/2005 Inoue et al.
6,918,530 B2 7/2005 Shinkai et al.

7,033,842 B2 4/2006 Haji et al.
7,148,127 B2 12/2006 Oohata et al.
7,208,337 B2 4/2007 Eisert et al.
7,353,596 B2 4/2008 Shida et al.
7,358,158 B2 4/2008 Aihara et al.
7,439,549 B2 10/2008 Marchl et al.
7,585,703 B2 9/2009 Matsumura et al.
7,628,309 B1 12/2009 Erikssen et al.
7,667,962 B2 2/2010 Mullen
7,714,336 B2 5/2010 Imai
7,723,764 B2 5/2010 Oohata et al.
7,795,629 B2 9/2010 Watanabe et al.
7,797,820 B2 9/2010 Shida et al.
7,838,410 B2 11/2010 Hirao et al.
7,854,365 B2 12/2010 Li et al.
7,880,184 B2 2/2011 Iwafuchi et al.
7,884,543 B2 2/2011 Doi
7,888,690 B2 2/2011 Iwafuchi et al.
7,906,787 B2 3/2011 Kang
7,910,945 B2 3/2011 Donofrio et al.
7,927,976 B2 4/2011 Menard
7,928,465 B2 4/2011 Lee et al.
7,972,875 B2 7/2011 Rogers et al.
7,989,266 B2 8/2011 Borthakur et al.
7,999,454 B2 8/2011 Winters et al.
8,023,248 B2 9/2011 Yonekura et al.
8,076,670 B2 12/2011 Slater et al.
8,082,003 B2 12/2011 Jee
8,186,568 B2 5/2012 Coronel et al.
8,333,860 B1 12/2012 Bibl et al.
8,349,116 B1 1/2013 Bibl et al.
8,426,227 B1 4/2013 Bibl et al.
8,518,204 B2 8/2013 Hu et al.
8,814,754 B2 8/2014 Weast et al.
9,367,094 B2 6/2016 Bibl et al.
9,582,036 B2 2/2017 Bibl et al.
9,922,966 B2 3/2018 Bibl et al.
10,147,711 B2* 12/2018 Bibl G06F 3/0412
2001/0029088 A1 10/2001 Odajima et al.
2002/0076848 A1 6/2002 Spooner et al.
2003/0010975 A1 1/2003 Gibb et al.
2003/0177633 A1 9/2003 Haji et al.
2004/0100164 A1 5/2004 Murata et al.
2004/0232439 A1 11/2004 Gibb et al.
2004/0266048 A1 12/2004 Platt et al.
2005/0224822 A1 10/2005 Liu
2005/0232728 A1 10/2005 Rice et al.
2006/0038291 A1 2/2006 Chung et al.
2006/0055035 A1 3/2006 Lin et al.
2006/0061555 A1 3/2006 Mullen
2006/0065905 A1 3/2006 Eisert et al.
2006/0146514 A1 7/2006 Douglas
2006/0157721 A1 7/2006 Tran et al.
2006/0160276 A1 7/2006 Brown et al.
2006/0214299 A1 9/2006 Fairchild et al.
2007/0048902 A1 3/2007 Hiatt et al.
2007/0080438 A1 4/2007 Yamanaka et al.
2007/0166851 A1 7/2007 Tran et al.
2007/0194330 A1 8/2007 Ibbetson et al.
2008/0048206 A1 2/2008 Lee et al.
2008/0150134 A1 6/2008 Shinkai et al.
2008/0163481 A1 7/2008 Shida et al.
2008/0194054 A1 8/2008 Lin et al.
2008/0196237 A1 8/2008 Shinya et al.
2008/0205027 A1 8/2008 Coronel et al.
2008/0283190 A1 11/2008 Papworth et al.
2008/0283849 A1 11/2008 Imai
2008/0303038 A1 12/2008 Grottsch et al.
2009/0068774 A1 3/2009 Slater et al.
2009/0072382 A1 3/2009 Guzek
2009/0146303 A1 6/2009 Kwon
2009/0303713 A1 12/2009 Chang et al.
2009/0314991 A1 12/2009 Cho et al.
2010/0052004 A1 3/2010 Slater et al.
2010/0105172 A1 4/2010 Li et al.
2010/0123164 A1 5/2010 Suehiro et al.
2010/0176415 A1 7/2010 Lee et al.
2010/0188794 A1 7/2010 Park et al.
2010/0200884 A1 8/2010 Lee et al.

OTHER PUBLICATIONS

Bower, C.A., et al., "Active-Matrix OLED Display Backplanes

Bower, C.A., et al., "Active-Matrix OLED Backplanes Using Transfer-Printed Microscale Integrated Circuits", IEEE, 2010 Electronic Components and Technology Conference, pp. 1339-1343.

"Characteristics of electrostatic Chuck(ESC)" Advanced Materials Research Group, New Technology Research Laboratory, 2000, pp. 51-53 accessed at http://www.socnb.com/report/ptech_e/2000p51_e.pdf.

Guerre, Roland, et al, "Selective Transfer Technology for Microdevice Distribution" Journal of Microelectromechanical Systems, vol. 17, No. 1, Feb. 2008, pp. 157-165.

Han, Min-Koo, "AM backplane for AMOLED" Proc. of ASID '06 Oct. 8-12, New Delhi, pp. 53-58, Oct. 2006.

Harris, Jonathan H., "Sintered Aluminum Nitride Ceramics for High-Power Electronic Applications" Journal of the Minerals, Metals and Materials Society, vol. 50, No. 6, Jun. 1998, p. 56.

Horwitz, Chris M., "Electrostatic Chucks: Frequently Asked Questions" ElectroGrip, 2006, 10 pgs, accessed at www.electrogrip.com.

Hossick-Schott, Joachim, "Prospects for the ultimate energy density of oxide-based capacitor anodes" Proceedings of CARTS Europe, Barcelona, Spain, 2007, 10 pgs.

Lee, San Youl, et al., "Wafer-level fabrication of GAN-based vertical light-emitting diodes using a multi-functional bonding material system" Semicond. Sci. Technol. 24, 2009, 4 pgs.

"Major Research Thrust: Epitaxial Layer Transfer by Laser Lift-off" Purdue University, Heterogeneous Integration Research Group, accessed at https://engineering.purdue.edu/HetInt/project_epitaxial_layer_transfer_llo.htm, last updated Aug. 2003.

Mei, Zequn, et al., "Low-Temperature Solders" Hewlett-Packard Journal, Article 10, Aug. 1996, pp. 1-10.

Mercado, Lei, L., et al., "A Mechanical Approach to Overcome RF MEMS Switch Stiction Problem" 2003 Electronic Components and Technology Conference, pp. 377-384.

Miskys, Claudio R., et al., "Freestanding GaN-substrates and devices" phys. Stat. sol. © 0, No. 6, 2003, pp. 1627-1650.

"Principles of Electrostatic Chucks: 1—Techniques for High Performance Grip and Release" ElectroGrip, Principles1 rev3 May 2006, 2 pgs, accessed at www.electrogrip.com.

Steigerwald, Daniel, et al., "III-V Nitride Semiconductors for High-Performance Blue and Green Light-Emitting Devices" article appears in journal JOM 49 (9) 1997, pp. 18-23. Article accessed Nov. 2, 2011 at <http://www.tms.org/pubs/journals/jom/9709/setigerwald-9709.html>, 12 pgs.

Widas, Robert, "Electrostatic Substrate Clamping for Next Generation Semiconductor Devices" Apr. 21, 1999, 4 pgs.

"COF (Chip on Film)" Samsung Semiconductor Global Website. <http://www.samsung.com/global/business/semiconductor/support/package-info/package-datasheet/various-packages/cof>. Web. Nov. 14, 2013. 3 pages.

"COG (Chip on Glass)" Samsung Semiconductor Global Website. <http://www.samsung.com/global/business/semiconductor/support/package-info/package-datasheet/various-packages/cog>. Web. Nov. 14, 2013. 3 pages.

"Chip-On-Glass technology for a simpler, and less expensive LCD display solution" NXP Semiconductors N.V. Document No. 9397 750 17282. Date of release May 2012. 2 pages. <http://www.nxp.com/documents/leaflet/75017282.pdf>.

Johnson, Luke, "Apple job listing hunts for 'flexible display' engineer, iPhone 6 and iWatch mooted," Trusted Reviews. Apr. 11, 2013, 2 pgs. <http://www.trustedreviews.com/news/apple-job-listing-hunts-for-flexible-display-engineer-iphone-6-and-iwatch-mooted>. Web. Feb. 3, 2014.

"Samsung flexible display patents include pull-out and rollable concept units," posted Mar. 12, 2007 by Daniel P. 1 pg. http://www.phonearena.com/news/Samsung-flexible-display-patents-include-pull-out-and-rollable-concept-units_id27765. Web. Feb. 3, 2014.

"Samsung's Killer SmartPhone Continues to Advance," Patent Bolt, Jun. 18, 2012. 10 pages. <http://www.patentbolt.com/2012/06/samsungs-killer-smartphone-continues-to-advance.html>. Web. Nov. 12, 2013.

Smith, Chris, "Samsung tablet with flexible display spotted in new design patent," Android Authority. May 19, 2013. 3 pgs. <http://www.androidauthority.com/samsung-tablet-with-flexible-display-spotted-in-new-design-patent-101111/>.

Smith, Chris, "Samsung tablet with flexible display spotted in new design patent," Android Authority. May 19, 2013. 3 pgs. <http://www.androidauthority.com/samsung-flexible-display-tablet-patent-1011111/>

(56)

References Cited

OTHER PUBLICATIONS

www.androidauthority.com/samsung-tablet-flexible-display-spotted-new-design-patent-212624/. Web. Feb. 3, 2014.

Williams, Storm, “Here Comes Apple iWatch Patent—Bi-Stable Spring With Flexible Display (20130044215),” The Tech Storm, posted Feb. 21, 2013, 3 pgs. <http://www.thetechstorm.com/2013/02/here-comes-apple-iwatch-patent-bi-stable-spring-with-flexible-display-20130044215/>. Web. Feb. 3, 2014.

PCT International Search Report and Written Opinion for International Application No. PCT/US2014/067190, dated Jul. 29, 2015, 15 pages.

Takahashi, et al., “High density LED display panel on silicon microreflector and integrated circuit,” Electronic Manufacturing Technology Symposium, 1995, Proceedings of 1995 Japan International, 18th IEEE/CPMT International, pp. 271-275.

PCT International Preliminary Report of Patentability for International Application No. PCT/US2014/067190, dated Jun. 30, 2016, 9 pages.

* cited by examiner




FIG. 1A
Prior Art




FIG. 1B
Prior Art




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4





FIG. 5A







FIG. 5C






FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17

DISPLAY MODULE AND SYSTEM APPLICATIONS

RELATED APPLICATIONS

This application is a continuation of co-pending U.S. patent application Ser. No. 15/908,505, filed Feb. 28, 2018, which is a continuation of U.S. patent application Ser. No. 15/417,015, filed Jan. 26, 2017, now U.S. Pat. No. 9,922,966, which is a continuation of U.S. patent application Ser. No. 15/157,235, filed May 17, 2016, now U.S. Pat. No. 9,582,036, which is a continuation of U.S. patent application Ser. No. 14/109,864, filed on Dec. 17, 2013, now U.S. Pat. No. 9,367,094 which is incorporated herein by reference.

BACKGROUND

Field

The present invention relates to display modules. More particularly embodiments of the present invention relate to display module packages and system applications thereof.

Background Information

Light emitting diodes (LEDs) are increasingly being considered as a replacement technology for existing light sources. For example, LEDs are found in signage, traffic signals, automotive tail lights, mobile electronic displays, and televisions. Some specific mobile electronics are smart electronic devices, such as smartphones, smartwatches, etc. including more advanced computing capability than a feature phone or watch. Demand is increasing for thinner, lighter weight, and lower cost smart electronic devices, with higher resolution and larger touch screens. Organic light emitting diode (OLED) display and liquid crystal display (LCD) are the two most widely adopted display technologies in current smart electronic devices.

OLED technology generally includes a layer of an organic compound in a pixel area, and a thin film transistor (TFT) backplane to switch each individual pixel on or off. An OLED display works without a backlight and can display deep black levels. The organic compound layer is sensitive to air and moisture, which can lead to degradation of the display. OLED displays are typically encapsulated with a rigid glass cover to protect the organic compound from air and moisture.

LCD technology generally includes pixels filled with liquid crystals, and a thin film transistor (TFT) backplane to switch each individual pixel on or off. Since the liquid crystals do not produce light by themselves, they need backlight illumination from behind or side of the display panel.

Two widely adopted manners for packaging display modules based on OLED or LCD include chip-on-glass (COG) packaging and chip-on-film (COF) packaging. FIGS. 1A-1B are exemplary schematic cross-sectional side view and schematic front view illustrations of a COG packaged display module. As illustrated, the display module **100** includes a display panel **115** connected to a printed circuit board (PCB) **106** by a flexible printed circuit (FPC) **108**. The display panel **115** includes a display substrate **102** formed of either OLED or LCD display technologies, one or more driver ICs **110** mounted on the display substrate **102** and a cover **114** over the display substrate. A seal ring **113** may surround the display area **101** of the display substrate for attaching the cover **114** and sealing the display area **101** from air and

moisture. In smart electronic devices the display substrate **102** may additionally include a touch screen within the display area **101**. Alternatively a touch screen can be formed over the display substrate **102**. In the case of LCD display technology, a backlight **105** is located behind the display substrate.

Additional devices and IC chips **104** for operating the display module **100** are located off of the display substrate **102** on PCB **106**. For example, IC chips **104** can include a power management IC, processor, timing controller, touch sense IC, wireless controller, communications IC, etc. As illustrated, the PCB **106** is connected to the display substrate **102** with FPC **108**, with contact areas **107** of the FPC **108** bonded to surfaces of the display substrate **102** and PCB **106**. Referring to both FIGS. 1A-1B, the area reserved on the display substrate for the one or more driver ICs **110** and contact area **107** are referred to as a contact ledge **111**. The PCB **106** may extend laterally from the display substrate **102**, or alternatively can be wrapped behind the display substrate as illustrated. As shown in FIGS. 1A-1B, a lateral extension length **109** of the FPC **108** may be associated with the FPC **108** of the display module, even where the PCB **106** is wrapped behind the display substrate **102**. A battery **112** may also be located behind the display substrate with the PCB **106**.

COF packaging is similar to COG packaging, with one main difference being that the one or more driving ICs **110** are moved from the display substrate **102** onto the FPC **108**. In such applications, the contact ledge may require less space than COG packaging.

SUMMARY OF THE INVENTION

Display module packages and system applications thereof are described. In an embodiment, a display module includes a display substrate having a front surface, a back surface, and a display area on the front surface. A plurality of interconnects extend through the display substrate from the front surface to the back surface, and an array of LEDs are in the display area and electrically connected with the plurality of interconnects. One or more driver circuits are on the front surface or the back surface of the display substrate. In an embodiment, the plurality of interconnects extend through the display substrate from the front surface to the back surface directly behind the display area, and the one or more driver circuits are on the back surface of the display substrate. In an embodiment, a flexible printed circuit does not connect the one or more driver circuits to the display substrate.

The plurality of interconnects may be through vias that extend through the display substrate from the front surface to the back surface. The interconnects can be used for a variety of applications, for example, a ground via. A variety of devices can be located on the front or back surfaces of the display substrate. For example, a battery can be located on a back surface of the display substrate. In an embodiment, an array of micro chips are located on the front surface of the display substrate and within the display area. The array of micro chips may be electrically connected with the plurality of interconnects and the array of LEDs. In some embodiments, the array of micro chips overlaps the plurality of interconnects. In other embodiments, the array of micro chips do not overlap the plurality of interconnects. In an embodiment, the array of micro chips includes an array of ambient light sensors. A uniform distribution of ambient light sensors can be located in the array of micro chips.

In accordance with embodiments of the invention the display module can be incorporated into a wearable electronic device, for example, a smartwatch. In such an embodiment, the display area of the display substrate spans a watch face and a band of the smartwatch. In another embodiment, the display substrate is secured to a spool. In such an embodiment, the spool can include the one or more driver circuits in electrical contact with the plurality of interconnects. In one applications, the display module can be incorporated into a television.

In an embodiment, a non-transitory computer-readable medium stores instructions which, when executed by a processor, cause the processor to perform operations to adjust display data for a display area of a wearable electronic device. The operations include receiving input from a control device, with the input including data for the display area of the wearable electronic device. The input is parsed to derive the data for display, and the derived data is displayed on the display area, where the display area is on a flexible display substrate spanning a face and band of the wearable electronic device. For example, the wearable electronic device may be a smartwatch. In an embodiment, the non-transitory computer-readable medium stores additional instructions to perform additional operations including receiving a configuration of the display area of the watch face and band, receiving a design from the derived data, the design including a watch face and watch band, and updating the display area with the received design.

In an embodiment, a display module for a wearable electronic device includes a flexible display substrate spanning a face and a band of the wearable electronic device. An accessory manager is coupled to the display substrate, to receive input from a control device communicatively coupled to the display module. The display module additionally includes a graphical user interface (GUI) manager, to control information displayed on the display substrate, where the display substrate includes a first display area associated with a face of the wearable electronic device and a second display area associated with a band of the wearable electronic device. In an embodiment, the GUI manager is to further provide a watch face design to the first display area and a watch band design to the second display area. In an embodiment, the accessory manager is to further receive input data from a control device via a communication module, the input data including configuration data for the GUI manager.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a schematic cross-sectional side view illustration of a COG packaged display module.

FIG. 1B is a schematic front view illustration of a COG packaged display module.

FIG. 2A is a schematic cross-sectional side view illustration of a display substrate including a plurality of interconnects in accordance with an embodiment of the invention.

FIG. 2B is a schematic cross-sectional side view illustration of a display substrate including a plurality of through vias in accordance with an embodiment of the invention.

FIG. 3 is a schematic cross-sectional side view illustration of a display substrate including an array of LEDs and micro chips in a display area on a front surface of the display substrate in accordance with an embodiment of the invention.

FIG. 4 is a schematic cross-sectional side view illustration of a display module including one or more driver circuits on

the back surface of the display substrate directly behind the display area in accordance with an embodiment of the invention.

FIG. 5A is a schematic front view illustration of a display substrate including an array of LEDs and micro chips in a display area and a plurality of through vias directly beneath the display area, where the array of micro chips overlap the plurality of through vias in accordance with an embodiment of the invention.

FIG. 5B is a schematic back view illustration of a display substrate including one or more driver circuits on the back surface of the display substrate and a plurality of through vias directly behind the display area in accordance with an embodiment of the invention.

FIG. 5C is a schematic front view illustration of a display substrate including an array of LEDs and micro chips in a display area and a plurality of through vias directly beneath the display area, where the array of micro chips do not overlap the plurality of through vias in accordance with an embodiment of the invention.

FIG. 5D is a schematic front view illustration of a display substrate including an array of LEDs and micro chips in a display area and a plurality of through vias outside of the display area in accordance with an embodiment of the invention.

FIG. 6A is a schematic cross-sectional side view illustration of TFT display substrate including one or more through vias in accordance with an embodiment of the invention.

FIG. 6B is a schematic cross-sectional side view illustration of a TFT display substrate and display module including an array of LEDs in a display area and one or more through vias outside of the display area in accordance with an embodiment of the invention.

FIGS. 7A-7B are schematic front view illustration of a TFT substrate and display module including one or more driver circuits in contact with one or more through vias outside of the display area in accordance with embodiments of the invention.

FIG. 8 is a schematic front view illustration of a TFT display substrate and display module including an array of LEDs and a plurality of through vias in accordance with an embodiment of the invention.

FIG. 9 is a schematic front view illustration of a wearable electronic device including a display panel in accordance with an embodiment of the invention.

FIGS. 10-12 are perspective view illustrations of a wearable electronic device displaying various display images in accordance with embodiments of the invention.

FIG. 13 is a system diagram of a wearable electronic device having a display panel in accordance with an embodiment of the invention.

FIG. 14 is schematic cross-sectional side view illustration of a system including a flexible display panel secured to a spool in accordance with an embodiment of the invention.

FIG. 15 is a schematic cross-sectional side view illustration of a flexible display panel including an array of LEDs and micro chips in a display area on a front surface of the display substrate in accordance with an embodiment of the invention.

FIG. 16 is a schematic front view illustration of a flexible display panel including two areas of micro chips exposed to different levels of ambient light in accordance with an embodiment of the invention.

FIG. 17 is a system diagram of a display system including the flexible display panel in accordance with an embodiment of the invention.

5

DETAILED DESCRIPTION OF THE
INVENTION

Embodiments of the present invention describe display module packaging configurations and system applications thereof. In an embodiment, a display module includes a display panel which includes a display substrate with a front surface, a back surface, and a display area on the front surface. A plurality of interconnects extend through the display substrate from the front surface to the back surface, and are electrically connected with an array of LEDs are on the front surface of the display substrate. For example, each interconnect may be a single through via, or a series of interconnect lines and vias through multiple layers. One or more driver circuits are located on the front or back surfaces of display substrate and in electrical connection with the plurality of interconnects. In an embodiment the one or more driver circuits are located on the back surface of the display substrate. In an embodiment, the one or more driver circuits are located on the back surface of the display substrate directly behind the display area on the front surface of the display substrate.

In various embodiments, description is made with reference to figures. However, certain embodiments may be practiced without one or more of these specific details, or in combination with other known methods and configurations. In the following description, numerous specific details are set forth, such as specific configurations, dimensions and processes, etc., in order to provide a thorough understanding of the present invention. In other instances, well-known semiconductor processes and manufacturing techniques have not been described in particular detail in order to not unnecessarily obscure the present invention. Reference throughout this specification to “one embodiment” means that a particular feature, structure, configuration, or characteristic described in connection with the embodiment is included in at least one embodiment of the invention. Thus, the appearances of the phrase “in one embodiment” in various places throughout this specification are not necessarily referring to the same embodiment of the invention.

Furthermore, the particular features, structures, configurations, or characteristics may be combined in any suitable manner in one or more embodiments.

The terms “spanning”, “over”, “to”, “between” and “on” as used herein may refer to a relative position of one layer with respect to other layers. One layer “spanning”, “over” or “on” another layer or bonded “to” or in “contact” with another layer may be directly in contact with the other layer or may have one or more intervening layers. One layer “between” layers may be directly in contact with the layers or may have one or more intervening layers.

In one aspect, embodiments of the invention enable the fabrication of display panels and display modules with a reduced form factor in the x-y and z directions compared to COG and COF display module packaging configurations. In an embodiment, the x-y and z form factors are reduced compared to COG and COF display module packaging configurations by connecting the one or more driver circuits to interconnects, for example through vias, extending through the display substrate from the front surface to the back surface rather than with a FPC. Furthermore, the packaging approaches in accordance with embodiments of the invention may improve system performance due to shorter interconnects between components.

In an embodiment, the x-y form factor (e.g. length-width) is reduced compared to COG and COF display module packaging configurations by removing or reducing the con-

6

tact ledge area that would otherwise be reserved for one or more driver ICs **110** on the display area side of the display substrate, contact area of the FPC to the display substrate, and/or the lateral extension length associated with the FPC when positioned lateral to the display substrate **102** or wrapped around and below the display substrate. In accordance with embodiments of the invention, such a reduction of the x-y form factor may also allow for an increased allocation of display area on the display substrate. For example, COG packaging may require a contact ledge of at least 4-5 mm to allocate the driver ICs and FPC contact area. In accordance with embodiments of the invention, it is not required to allocate space for driver ICs and a FPC. In this manner a bevel width around the display area can be reduced below 1 mm, for example less than 0.5 mm.

In an embodiment, the z form factor (e.g. thickness) is reduced compared to COG and COF display module packaging configurations by removing the FPC and PCB. In accordance with embodiments of the invention, a plurality of interconnects, for example through vias, extend through the display substrate from the front surface to the back surface to connect the driver ICs and any additional IC chips including a power management IC, processor, timing controller, touch sense IC, wireless controller, communications IC, etc. In this manner, the chips and circuits for operating the display panel and module can be located on the back surface of the display substrate, eliminating the thickness of a PCB. In many embodiments, the driver ICs and additional IC chips are located directly behind the display area.

In some embodiments, the display panel includes a plurality of semiconductor-based LEDs in the display area. Such a configuration may enable the use of interconnects or through vias that otherwise may be problematic with the widely adopted LCD or OLED display technologies. For example, through vias and the placement of ICs on the back surface of the display substrate could be particularly problematic with conventional LCD technology which includes liquid crystals in the display area and requires the use of backlighting. Through vias could also be particularly problematic with existing OLED display technologies where through vias could potentially lead to air or moisture exposure. Though it is to be appreciated that some embodiments of the invention may be compatible with OLED display technology.

In another aspect, embodiments of the invention describe packaging configurations of flexible display panels into flexible display modules that can be incorporated into a variety of applications. In one application, embodiments of the invention describe a wearable electronic device, such as a smartwatch, including a flexible display panel and flexible display module. In this manner, the display area of the smartwatch is not limited to a rigid watch face area. In an embodiment, a smartwatch includes a flexible display panel that is integrated into a flexible watch band. Accordingly, curvature of the flexible display panel in both the watch face area and band may be adjusted to conform to the wrist size of the user. In addition, it is not required to include a FPC attached to the display area side of the display substrate. In this manner, the display area of the flexible display panel can cover more available space on the watch face area and band of the smartwatch.

The wearable electronic device may include a non-transitory computer readable medium including computer code for receiving a user input from a control device and adjusting display data for the display area of the wearable electronic device. For example, in one application, the user may select a specific watch design to be displayed on the display panel

of the smartwatch spanning a watch face and band of the smartwatch. Upon receiving the user input from a control device such as a computer, or portable electronic device such as a smartphone, the display data for the display area of the wearable electronic device is adjusted.

In another application, the flexible display panel is rollable. For example, the display panel may be incorporated into a television display that is rollable or foldable into and out of a housing. In an embodiment, the flexible television display panel is coupled to a spool onto which the display panel is rollable or foldable. In an embodiment, the driver ICs and/or any additional IC chips including a power management IC, processor, timing controller, touch sense IC, wireless controller, communications IC, etc. can be relocated to the spool and electrically connected with the flexible television display panel with a redistribution layer on the back surface of the flexible television display panel. The driver ICs and any additional IC chips can alternatively be located on the back surface of the display panel. In another application, the flexible display panel is foldable. For example, the display panel may be incorporated into a smartphone or tablet and folded into various configurations.

FIG. 2A is a schematic cross-sectional side view illustration of a display substrate including a plurality of interconnects in accordance with an embodiment of the invention. As illustrated, the display substrate **202** may include a front surface **203**, a back surface **205**, and a display area **201** on the front surface. A plurality of interconnects **204**, **206** extend through the display substrate from the front surface **203** to the back surface **205** directly behind the display area **201**. As illustrated, each interconnect **204**, **206** may be a series of interconnect lines **207A** and vias **207B** through multiple layers of a multi-layer display substrate **202**. Referring to FIG. 2B, each interconnect **204**, **206** may be a single through via formed through the display substrate **202**, which may be a single or multi-layer display substrate **202**. In interest of conciseness, the following description and figures refer to interconnect features **204**, **206** as through vias. It is to be appreciated however, that such a configuration references an embodiment, and that when referring to through vias **204**, **206**, these may be replaced by interconnects including a series of interconnect lines and vias through multiple layers of a multi-layer display substrate. Through vias **204**, **206** may be formed using a variety of techniques including, but not limited to, chemical etching or laser drilling.

Display substrate **202** can be formed from a variety of materials including glass, amorphous silicon, polysilicon, single crystal silicon, metal foil, metal foil covered with dielectric, or a polymer such as poly(methyl methacrylate) (PMMA), polyethylene terephthalate (PET), polyethylene naphthalate (PEN), polycarbonate (PC), polyethersulphone (PES), aromatic fluorine-containing polyarylates (PAR), polycyclic olefin (PCO), and polyimide (PI). In an embodiment, display substrate includes a polymer-silicon stack. In an embodiment, display substrate **202** is a flexible glass substrate. For example, display substrate **202** may be a flexible boro-silicate glass substrate. One exemplary flexible glass substrate is manufactured under the tradename WILLOW (™) glass by Corning Incorporated located in Corning, N.Y.

In the embodiments illustrated, a redistribution layer **208** is formed on the back surface **205** of the display substrate. Redistribution layer may include a single layer or a plurality of layers including wiring **210A**, **210B**. For example, wiring **210A** can be used to for electrical contact with an array of LEDs formed on the top surface **203** of the display substrate

202 with one or more through vias **204**, while wiring **210B** may be used for a Vss connection with one or more through vias **206**. In an embodiment, the one or more through vias **204**, **206** are directly behind the display area **201**. The one or more through vias **204**, **206** may also be located outside of the display area **201**, such as along a periphery of the display area **201** on the top surface **203** of display substrate **202**.

A wiring layer **212** may also be located on the top surface **203** of display substrate **202** in electrical contact with the plurality of through vias **204**. Wiring layers **212**, **210A**, **210B** and vias **204**, **206** may be formed of any suitable electrically conductive material used in packaging applications including metals films, conductive polymers, conductive oxides, etc. Referring now to FIG. 3, in accordance with an embodiment of the invention and array of LED devices **214** and optionally micro chips **216** may be transferred and bonded to the display substrate **202**. For example, the array of LED devices **214** and micro chips **216** may be in electrical connection with the plurality of through vias **204**.

In accordance with embodiments of the invention, the LED devices **214** are semiconductor-based LED devices including one or more active layers (e.g. quantum well layers) between two doped semiconductor cladding layers. In the particular embodiments illustrated, the LED devices **214** are vertical LED devices in which the layers are horizontal, and the layers are stacked vertically. Top and bottom conductive contacts are formed on the vertical LED devices in order to make electrical contact with the top contact layers **220** described in further detail with regard to FIG. 4 below and wiring layer **212**, respectively. In another embodiment, the LED devices **214** are horizontal LED devices in which the contacts to the doped cladding layers are both formed on the bottom surface of an LED device in order to make electrical contact with wiring layer **212**.

In accordance with embodiments of the invention, the micro chips **216** replace the TFT layer of a conventional active matrix display to switch and drive one or more LED devices **214**. In one embodiment, each micro chip **216** couples with one or more red, green, and blue led devices **214** that emit different colors of light. In such an exemplary red-green-blue (RGB) sub-pixel arrangement, each pixel includes three sub-pixels that emit red, green, and blue light. The RGB arrangement is exemplary and embodiments are not so limited. For example, alternative sub-pixel arrangements include red-green-blue-yellow (RGBY), red-green-blue-yellow-cyan (RBGYC), red-green-blue-white (RGBW), or other sub-pixel matrix schemes where the pixels have a different number of sub-pixels, such as displays manufactured under the trademark name PenTile (®). In the exemplary embodiments illustrated in the following description, a single micro chip **216** is illustrated as controlling two pixels. It is to be appreciated that this configuration is likewise exemplary and embodiments are not so limited. For example, each micro chip **216** can switch and drive one or more LED devices **214** arranged in series, in parallel, or a combination of the two, such that multiple LED devices are driven from the same control signal. A variety of alternative configurations are contemplated in accordance with embodiments of the invention. In other embodiments, sensors such as touch sensors or light sensors can also be located on the front surface of the display substrate within the display area similarly as the micro chips.

In one aspect, embodiments of the invention describe display panels and display module packaging configurations in which micro LED devices and/or micro chips are transferred and bonded to a wiring **212** using an electrostatic

transfer head assembly. In accordance with embodiments of the present invention, a pull-in voltage is applied to an electrostatic transfer head in order to generate a grip pressure on a micro LED device or micro chip. It has been observed that it can be difficult to impossible to generate sufficient grip pressure to pick up micro devices with vacuum chucking equipment when micro device sizes are reduced below a specific critical dimension of the vacuum chucking equipment, such as approximately 300 μm or less, or more specifically approximately 100 μm or less. Furthermore, electrostatic transfer heads in accordance with embodiments of the invention can be used to create grip pressures much larger than the 1 atm of pressure associated with vacuum chucking equipment. For example, grip pressures of 2 atm or greater, or even 20 atm or greater may be used in accordance with embodiments of the invention. Accordingly, in one aspect, embodiments of the invention provide the ability to transfer and integrate micro LED devices and micro chips into applications in which integration is not possible with current vacuum chucking equipment. In some embodiments, the term "micro" chip, "micro" LED device, or other "micro" structure may refer to the descriptive size, e.g. length or width, of certain devices or structures. In some embodiments, "micro" chips or "micro" LED devices may be on the scale of 1 μm to approximately 300 μm or less, or 100 μm or less in many applications. However, embodiments of the present invention are not necessarily so limited, and certain aspects of the embodiments may be applicable to larger micro devices or structures, and possibly smaller size scales.

Referring now to FIG. 4, following the transfer and bonding of the arrays of LEDs **216** and micro chips **216** a passivation layer **218** may be provided between the LEDs **216** and covering the wiring layer **212** followed by the deposition of a top contact layer **220**. In an embodiment, top contact layer **220** may be in electrical contact with a Vss line or Vss plane, for example that may be in electrical connection with the one or more through vias **206**. Alternatively the Vss line or Vss plane may be located on the top surface **203** of the display substrate **202**. Following the formation of top contact layer **220**, an encapsulation layer **222** may be formed over the display substrate. In some embodiments the encapsulation layer **222** may be a flexible encapsulation layer.

In accordance with embodiments of the invention, passivation layer **218** may be transparent or semi-transparent to the visible wavelength so as to not significantly degrade light extraction efficiency of the completed system. Passivation layer **218** may be formed of a variety of materials such as, but not limited to epoxy, poly(methyl methacrylate) (PMMA), benzocyclobutene (BCB), polyimide, and polyester. In an embodiment, passivation layer **218** is formed by ink jetting around the LEDs **214**.

Depending upon the particular application, top contact layer **220** may be opaque, reflective, transparent, or semi-transparent to the visible wavelength. For example, in top emission systems the top contact layer **220** may be transparent, and for bottom emission systems the top conductive contact may be reflective. Exemplary transparent conductive materials include amorphous silicon, transparent conductive oxides (TCO) such as indium-tin-oxide (ITO) and indium-zinc-oxide (IZO), carbon nanotube film, or a transparent conductive polymer such as poly(3,4-ethylenedioxythiophene) (PEDOT), polyaniline, polyacetylene, polypyrrole, and polythiophene. In an embodiment top conductive contact layer **220** is approximately 50 nm-1 μm thick ITO-silver-ITO stack. In an embodiment, the top conductive contact layer **220** includes nanoparticles such as silver, gold,

aluminum, molybdenum, titanium, tungsten, ITO, and IZO. In a particular embodiment, the top conductive contact **220** is formed by ink jetting. Other methods of formation may include chemical vapor deposition (CVD), physical vapor deposition (PVD), spin coating.

In embodiments where top conductive layer **220** is transparent, the top encapsulation layer **222** may also be transparent or semi-transparent so as to not degrade light extraction efficiency of the system. Top encapsulation layer **222** may be formed of a variety of materials such as, but not limited to, silicon oxide (SiO_2), silicon nitride (SiN_x), poly(methyl methacrylate) (PMMA), benzocyclobutene (BCB), polyimide, and polyester, and may be formed by a variety of methods including chemical vapor deposition (CVD), physical vapor deposition (PVD), spin coating.

Still referring to FIG. 4, in accordance with embodiments of the invention, driver ICs **230** and additional devices and IC chips **234** for operating the display module **200** are located on the back surface **205** of the display substrate **102** of the display panel **215**. For example, IC chips **234** can include a power management IC, processor, memory, timing controller, touch sense IC, wireless controller, communications IC, etc. As illustrated, the driver ICs **230** and additional IC chips **234** may be located on the back surface of the display substrate directly behind the display area **201**. In one embodiment, a battery **238** may also be formed on RDL **208** on the back surface **205**, or alternatively a thin film battery **238** can be formed on the array of IC chips **230**, **234**.

In an embodiment, the driver ICs **230** are in electrical connection with wiring **210A** in RDL **208**, which are in electrical connection with interconnects illustrated as through vias **204** extending between the front surface and back surface of the display substrate **202**, which are in electrical connection with wiring layer **212** on the top surface of display substrate **202**, which is in electrical connection with the LEDs **214** and optional micro chips **216**. In an embodiment wiring layer **212** includes scan lines, which are coupled to one or more scan driver ICs **230**, and data lines which are coupled to one or more data driver ICs **230** located on the back surface **204** of the display substrate **202** through vias **204**. The LEDs **214** may each be coupled to a common Vss through a through via **206**, or a plurality of through vias **216**.

FIG. 5A is a schematic front view illustration of a display substrate **202** including an array of LEDs **214** and micro chips **216** in a display area and a plurality of through vias **204**, **206** directly beneath the display area, where the array of micro chips overlap the plurality of through vias in accordance with an embodiment of the invention. As shown in FIG. 5A, the display area **201** may include the entire surface of display substrate **202**, or at least the maximum amount of surface possible for placing the LEDs and micro chips. Through vias **204** may be connected to any of the chips **230**, **234** on the back surface of the display substrate **202**. For example, through vias **204** may connect a micro chip **216** to a data line, scan line, Vdd, clock, etc. In the particular embodiment illustrated through vias **204** are directly beneath the array of micro chips **216**, and Vss through vias **206** are interspersed through the display area between the micro chips **216**. FIG. 5B is a schematic back view illustration of a display substrate **202** including one or more driver circuits **230** on the back surface of the display substrate and a plurality of through vias **204**, **206** directly behind the display area in accordance with an embodiment of the invention. As shown a number of additional IC chips **234** and battery **238** may also be located directly behind the display area.

11

FIG. 5C is schematic front view illustration of a display substrate including an alternative arrangement of an array of LEDs and micro chips in a display area 201 and a plurality of through vias directly beneath the display area 201, where the array of micro chips 216 do not overlap the plurality of through vias 204, 206 in accordance with an embodiment of the invention. For example, the plurality of through vias 204, 206 can be interspersed between the micro chips 216 as illustrated in FIG. 5C. In the exemplary embodiment illustrated in FIG. 5C, wiring 212 is illustrated connecting the plurality of through vias 204 and LEDs 214 to the array of micro chips 216.

FIG. 5D is a schematic front view illustration of a display substrate including an array of LEDs and micro chips in a display area 201 and a plurality of through vias outside of the display area 201 in accordance with an embodiment of the invention. As shown in FIG. 5D, the display area 201 may be smaller than the front surface of display substrate 202, and the plurality of through vias 204, 106 are located along a periphery of the display substrate 202 outside of the display area 201. In the exemplary embodiment illustrated in FIG. 5D, wiring 212 has not been illustrated for connecting the plurality of through vias 204 to the micro chips 216 in order to not obscure the illustration.

Referring now to FIGS. 6A-8, the packaging configurations in accordance with embodiments of the invention are applied to an existing OLED display panel 315 to form a display module 300. In the embodiment illustrated in FIG. 6A, a display substrate 302 is a TFT backplane including working circuitry 316 and organic LEDs 314. Exemplary TFT working circuitries 316 may include amorphous-silicon based, poly-silicon based, and indium-gallium-zinc-oxide based technologies. In an embodiment, through vias 304 can be formed through the display substrate in the contact ledge area 311 that is conventionally reserved for driver ICs and a FPC. Referring now to FIG. 6B, similar to the previous embodiments described and illustrated, additional devices and IC chips 334 for operating the display module 300 are located on the back surface 305 of the display substrate 302. For example, IC chips 334 can include a power management IC, processor, memory, timing controller, touch sense IC, wireless controller, communications IC, etc. As illustrated, the additional IC chips 334 may be located on the back surface of the display substrate directly behind the display area 301. In the embodiment illustrated in FIG. 7A, a driver IC 330 is located on the front surface 303 of the display substrate 302. The driver IC 330 may be in electrical connection with the through vias 304 which in turn are in electrical communication with the wiring 310 in RDL 308 on the back surface 305 of the display substrate 302. In the embodiment illustrated in FIG. 7B, a driver IC 330 is located on the back surface 305 of the display substrate 302, and in electrical communication with the through vias 304. In the embodiment illustrated in FIG. 7A, the driver ICs 330 are formed on the top surface of the display substrate 302 reserved for the contact ledge 311. In the embodiment illustrated in FIG. 7B, the drive IC 330 is at least partially located directly behind the display area 301. In either configuration, the driver IC 330 communicates with the working circuitry 316 similarly as with a conventional OLED display.

FIG. 8 is a schematic front view illustration of a TFT display substrate and display module including an array of LEDs and a plurality of through vias in accordance with an embodiment of the invention. The particular embodiment illustrated in FIG. 8 is similar to that previously illustrated in FIG. 4, with a TFT display substrate including working

12

circuitry 316 replacing micro chips 216. In an embodiment, through vias 304 can be formed through the display substrate directly behind the display area 301.

FIG. 9 is a schematic front view illustration of a wearable electronic device including a display panel in accordance with an embodiment of the invention. The wearable electronic device 400 may be any of a number of wearable accessory products that include a display panel 215, 315, and in particular a flexible display panel 215, 315. The flexible display panel 215, 315 may be formed in any of the display modules described above. In an embodiment, the flexible display panel 215, 315 does not include a contact ledge 111, which may allow for increased allocation space to the display area 201.

In one embodiment, the wearable electronic device is a smartwatch including a watch face 402, band 404, and clasp 406. A flexible display panel 215, 315 may be integrated into the smartwatch so that it spans both the watch face and band. In this manner, the flexible display panel 215, 315 can be adjusted to the contour of a user's arm. In accordance with embodiments of the invention, a bezel 410 width surrounding the display panel 215, 315 can be minimized, for example below 4-5 mm or even less than 1 mm, less than 0.5 mm, or eliminated. Thus, the bezel 210 design of the smartwatch can be designed for aesthetic concerns rather than as a requirement for allocating space for a contact ledge.

FIGS. 10-12 are perspective view illustrations of a wearable electronic device displaying various display images in accordance with embodiments of the invention. In the embodiment, illustrated in FIG. 10, the wearable electronic device 400 is illustrated with a blacked out display area of the display panel 215, 315. For example, this may indicate a state in which the display panel is turned off. FIGS. 11-12 illustrate states of where the display panel is displaying different images. For example, FIG. 11 may display a watch design A, including watch face and band and FIG. 12 may display a watch design B, including a watch face and band. Any number of displayed images are possible.

FIG. 13 illustrates a system diagram of an embodiment of wearable display module 1300. For example, the wearable display module 1300 may be incorporated into the wearable electronic devices of FIGS. 10-12, and include any of the flexible display panels described herein. The module 1300 includes a processor 1302 and memory 1303 for managing the wearable electronic devices and executing or interpreting instructions and commands for the wearable electronic devices. The processor 1302 can be a general-purpose processor or a microcontroller for controlling the wearable electronic devices. The memory 1303 can be integrated within the processor 1302, or coupled to the processor 1302 via a memory bus. The memory 1303 includes nonvolatile storage, such as flash memory, and can additionally include read only memory (ROM), and a form of volatile random access memory (RAM). In one embodiment, the processor 1302 includes media decode capability, to display encoded content via a flexible display panel 1304. In one embodiment, the module 1300 includes a graphical user interface (GUI) manager 1306, to control information that is provided to and displayed on the flexible display panel 1304.

The module 1300 also includes a communication module 1308 that facilitates communication between the module 1300 and other electronics. In one embodiment, the communication module 1308 includes a module to provide connectivity via universal serial bus (USB). The communication module 1308 can further include wireless transceivers for Bluetooth, or WLAN connectivity, and can additionally

13

include one or more WWAN transceivers to communicate with a wide area network including a cellular data network.

In one embodiment, the module **1300** includes an accessory manager **1310** that operates to authenticate and acquire data from an additional electronic device that can be coupled to the module **1300**. In one embodiment, the module **1300** is an accessory to a primary display device, and the accessory manager **1310** facilitates the connection of the additional electronic device to the module **1300**. In one embodiment, the module **1300** may have accessory devices that are managed by the accessory manager **1310**, which facilitates the transfer of data to and from accessory devices.

In an embodiment, memory **1303** includes non-transitory computer-readable medium stores instructions which, when executed by processor **1302**, cause the processor to perform operations to adjust display data for a flexible display panel **1304** of the module **1300**. In an embodiment, the operations including receiving input from a control device, the input including data for the flexible display panel, parsing the input to derive the data for display, and displaying the derived data on the flexible display panel. In an embodiment, the operations further include receiving a configuration of the flexible display panel of the watch face and band, receiving a design from the derived data, (e.g. type of watch design including a watch face and watch band), and updating the flexible display panel spanning the watch face and watch band of the smartwatch with the received design.

In an embodiment, an accessory manager is coupled to the flexible display substrate **1304** to receive input from a control device communicatively coupled to the module **1300**. A graphical user interface (GUI) manager is coupled to the display substrate, to control information displayed on the display substrate, where the display substrate includes a first display area associated with a face of the wearable electronic device and a second display area associated with a band of the wearable electronic device. In an embodiment, the GUI manager provides a watch face design to the first display area and a watch band design to the second display area. In an embodiment, the accessory manager receives input data from a control device via a communication module, the input data including configuration data for the GUI manager.

FIG. **14** is schematic cross-sectional side view illustration of a system **1400** including a flexible display panel **1500** secured to a spool **1410** in accordance with an embodiment of the invention. FIG. **15** is a schematic cross-sectional side view illustration of a flexible display panel **1500** including an array of LEDs **214** and micro chips **216** in a display area on a front surface **203** of the display substrate **202** in accordance with an embodiment of the invention. The display panel **1500** illustrated in FIGS. **14-15** may be similar to any of the display panels previously described above. In the embodiment illustrated in FIGS. **14-15**, the flexible display panel **1500** is rollable into and out of a housing **1420**. In such an embodiment, rather than locating the driver ICs **1430** additional IC chips **1434** and battery **1438** on the back surface **205** of the display substrate **202**, any combination of these components can be located within the housing **1420**, such as on the spool **1410**. In other embodiments, any of these components may also be located on the back surface **205** of the display substrate. For example, a thin film battery **1438** can be located on the back surface, or a plurality of batteries **1438** can be located on the back surface. Likewise one or more driver ICs **1430** may be located on the back surface to reduce transmission line distance to the micro chips **216**.

14

In an embodiment, the micro chips **216** may include ambient light sensors to measure the ambient light striking the display area of the flexible display panel **1500**. Referring to FIG. **16**, a schematic front view illustration is provided of a flexible display panel **1500** including two areas of micro chips **216A**, **216B** exposed to different levels of ambient light in accordance with an embodiment of the invention. In an embodiment, area **216B** of micro chips **216** is exposed to a greater amount of light than area **216A**, for example, glare from a window within a display room. In such an embodiment, a processor or ambient light controller in the system **1400** may increase the amount of light being emitted from the LEDs **214** operated by the micro chips **216** in area **216B** in order to compensate for the ambient light.

FIG. **17** illustrates a system diagram **1700** for an embodiment of a display system (e.g. a television) including a flexible display panel **1710** described herein, including the system and display panels described with regard to FIGS. **14-16**. The display system **1700** includes a processor **1720** and memory **1704** for managing the system and executing instructions. The memory includes non-volatile memory, such as flash memory, and can additionally include volatile memory, such as static or dynamic random access memory (RAM). The memory **1704** can additionally include a portion dedicated to read only memory (ROM) to store firmware and configuration utilities. In an embodiment, the processor **1720** manages ambient light correction of the flexible display panel **1710** by controlling each micro chip **216** output to LED devices **214** where light output is adjusted based on light sensor data from a sensor controller **1770**. Alternatively, such an ambient light correction module **1705** can be located on each of the micro chips **214** within the display panel **1710**.

The system also includes a power module **1780** (e.g., flexible batteries, wired or wireless charging circuits, etc.), a peripheral interface **1708**, and one or more external ports **1790** (e.g., Universal Serial Bus (USB), HDMI, Display Port, and/or others). In one embodiment, the display system **1700** includes a communication module **1712** configured to interface with the one or more external ports **1790**. For example, the communication module **1712** can include one or more transceivers functioning in accordance with IEEE standards, 3GPP standards, or other communication standards, and configured to receive and transmit data via the one or more external ports **1790**. The communication module **1712** can additionally include one or more WWAN transceivers configured to communicate with a wide area network including one or more cellular towers, or base stations to communicatively connect the display system **1700** to additional devices or components. Further, the communication module **1712** can include one or more WLAN and/or WPAN transceivers configured to connect the electronic device **1700** to local area networks and/or personal area networks, such as a Bluetooth network.

The display system **1700** can further include a sensor controller **1770** to manage input from one or more sensors such as, for example, proximity sensors, ambient light sensors, or infrared transceivers. In an embodiment, the array of micro chips **216** on the display panel includes an array of light sensors in communication with the sensor controller. Each micro chip **216** may include a light sensor, or only portion of the array of micro chips includes light sensors. For example, the array of light sensors can be uniformly distributed in the array of micro chips. In one embodiment the system includes an audio module **1731** including one or more speakers **1734** for audio output and one or more microphones **1732** for receiving audio. In

15

embodiments, the speaker 1734 and the microphone 1732 can be piezoelectric components. The electronic device 1700 further includes an input/output (I/O) controller 1722, a display screen 1710, and additional I/O components 1718 (e.g., keys, buttons, lights, LEDs, cursor control devices, haptic devices, and others). The display device/screen 1710 and the additional I/O components 1718 may be considered to form portions of a user interface (e.g., portions of the display system 1700 associated with presenting information to the user and/or receiving inputs from the user).

In utilizing the various aspects of this invention, it would become apparent to one skilled in the art that combinations or variations of the above embodiments are possible for forming flexible display panels and system applications including the flexible display panels. Although the present invention has been described in language specific to structural features and/or methodological acts, it is to be understood that the invention defined in the appended claims is not necessarily limited to the specific features or acts described. The specific features and acts disclosed are instead to be understood as particularly graceful implementations of the claimed invention useful for illustrating the present invention.

What is claimed is:

1. A portable electronic device comprising:
a display substrate including a display area and a bevel width around the display area, wherein the bevel width is less than 1 mm;
wherein the display substrate includes a first side and a second side;
a first wiring layer on the first side; and
an array of micro LEDs on and in electrical contact with the first wiring layer on the first side of the display substrate.
2. The portable electronic device of claim 1, wherein the display substrate is flexible.
3. The portable electronic device of claim 1, wherein the display substrate further comprises a contact ledge area, wherein the contact ledge area is wider than the bevel width.

16

4. The portable electronic device of claim 3, further comprising a driver IC bonded to the first wiring layer in the contact ledge area.

5. The portable electronic device of claim 4, further comprising a passivation layer laterally surrounding the array of micro LEDs.

6. The portable electronic device of claim 5, further comprising on or more top electrode layers over the passivation layer and in electrical contact with the array of micro LEDs.

7. The portable electronic device of claim 6, further comprising an array of openings in the passivation layer within the display area exposing an array of ground contacts, wherein the one or more top electrode layers are in electrical contact with the array of ground contacts.

8. The portable electronic device of claim 4, further comprising a plurality of interconnects extending through the display substrate from the first side to the second side.

9. The portable electronic device of claim 8, further comprising a second wiring layer on the second side of the substrate and in electrical communication with the plurality of interconnects.

10. The electronic device of claim 9, further comprising a plurality of integrated circuit (IC) chips in electrical connection with the second wiring layer.

11. The portable electronic device of claim 1, wherein the bevel width completely surrounds the display area.

12. The portable electronic device of claim 11, further comprising a plurality of interconnects extending through the display substrate from the first side to the second side.

13. The portable electronic device of claim 12, further comprising a second wiring layer on the second side of the substrate and in electrical communication with the plurality of interconnects.

14. The electronic device of claim 13, further comprising a plurality of integrated circuit (IC) chips in electrical connection with the second wiring layer.

15. The portable electronic device of claim 13, further comprising a driver IC bonded to the second wiring layer.

* * * * *