

US010547842B2

(12) **United States Patent**
Seregin et al.

(10) **Patent No.:** **US 10,547,842 B2**
(45) **Date of Patent:** ***Jan. 28, 2020**

(54) **METHOD AND APPARATUS FOR CODING VIDEO AND METHOD AND APPARATUS FOR DECODING VIDEO ACCOMPANIED WITH ARITHMETIC CODING**

(71) Applicant: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-si (KR)

(72) Inventors: **Vadim Seregin**, Suwon-si (KR); **Il-koo Kim**, Osan-si (KR)

(73) Assignee: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/119,706**

(22) Filed: **Aug. 31, 2018**

(65) **Prior Publication Data**

US 2018/0376144 A1 Dec. 27, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/584,523, filed on May 2, 2017, now Pat. No. 10,091,510, which is a (Continued)

(51) **Int. Cl.**
H04N 19/13 (2014.01)
H04N 19/593 (2014.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04N 19/13** (2014.11); **H04N 19/157** (2014.11); **H04N 19/176** (2014.11);
(Continued)

(58) **Field of Classification Search**
CPC H04N 19/91; H04N 19/13; H04N 19/176;
H04N 19/593

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,900,748 B2 5/2005 Marpe et al.

7,292,165 B2 11/2007 Cha et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1236461 A 11/1999

CN 1984336 A 6/2007

(Continued)

OTHER PUBLICATIONS

Communication dated Nov. 6, 2018, from the State Intellectual Property Office of People's Republic of China in counterpart Application No. 201510919253.3.

(Continued)


Primary Examiner — Tsion B Owens

(74) *Attorney, Agent, or Firm* — Sughrue Mion, PLLC

(57) **ABSTRACT**

A method of decoding a video through symbol decoding includes parsing symbols of image blocks from a received bitstream; classifying a current symbol into a prefix bit string and a suffix bit string based on a threshold value determined according to a size of a current block; performing arithmetic decoding of the prefix bit string and the suffix bit string by using respective arithmetic decoding methods determined for each of the prefix bit string and the suffix bit string; performing inverse binarization of the prefix bit string and the suffix bit string by using respective binarization methods determined for each of the prefix bit string and the suffix bit string; and restoring the image blocks by performing an inverse transformation operation and a prediction operation on the current block by using the current symbol restored through the arithmetic decoding and the inverse binarization.

1 Claim, 15 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/635,725, filed on Mar. 2, 2015, now Pat. No. 9,668,001, which is a continuation of application No. 14/130,052, filed as application No. PCT/KR2012/005087 on Jun. 27, 2012, now Pat. No. 9,565,455.

(60) Provisional application No. 61/502,038, filed on Jun. 28, 2011.

(51) **Int. Cl.**

H04N 19/169 (2014.01)
H04N 19/91 (2014.01)
H04N 19/157 (2014.01)
H04N 19/176 (2014.01)
H04N 19/44 (2014.01)
H04N 19/60 (2014.01)

(52) **U.S. Cl.**

CPC *H04N 19/1883* (2014.11); *H04N 19/44* (2014.11); *H04N 19/593* (2014.11); *H04N 19/60* (2014.11); *H04N 19/91* (2014.11)

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,564,384 B2	7/2009	He et al.
7,613,345 B2	11/2009	Kajiwarra et al.
7,898,445 B2	3/2011	Otsuka
7,929,614 B2	4/2011	Cho et al.
7,929,795 B2	4/2011	Kautzer et al.
8,705,622 B2	4/2014	Ye et al.
8,780,980 B2	7/2014	Yamaguchi
9,008,171 B2	4/2015	Karczewicz et al.
9,247,270 B2 *	1/2016	Seregin H04N 19/91
2004/0114683 A1	6/2004	Schwarz et al.
2005/0038837 A1	2/2005	Marpe et al.
2005/0071496 A1	3/2005	Singal et al.
2006/0098734 A1 *	5/2006	Cho H04N 19/423 375/240.03
2006/0153293 A1	7/2006	Hsu et al.
2007/0110153 A1	5/2007	Cho et al.
2007/0150497 A1 *	6/2007	De La Cruz H03M 7/3084
2007/0171985 A1	7/2007	Kim et al.
2007/0223825 A1	9/2007	Ye et al.
2007/0242894 A1	10/2007	Kautzer et al.
2008/0104154 A1	5/2008	Suzuki
2008/0212683 A1	9/2008	Nakata et al.
2009/0089549 A1	4/2009	Liu et al.
2009/0201986 A1	8/2009	Schwarz et al.
2010/0040140 A1	2/2010	Marpe et al.
2010/0040148 A1	2/2010	Marpe et al.
2010/0054326 A1	3/2010	Diamond et al.
2010/0232720 A1	9/2010	Tsai et al.
2011/0001643 A1 *	1/2011	Sze H03M 7/4006 341/87
2011/0032999 A1	2/2011	Chen et al.
2011/0090967 A1	4/2011	Chen et al.
2011/0110591 A1	5/2011	Sheu et al.
2012/0140814 A1	6/2012	Sole Rojals et al.
2012/0230405 A1	9/2012	An et al.
2013/0027230 A1 *	1/2013	Marpe H03M 7/4006 341/107
2013/0114738 A1 *	5/2013	Chien H03M 7/4018 375/240.24
2013/0202026 A1 *	8/2013	Fang H04N 19/91 375/240.02
2014/0198841 A1	7/2014	George et al.

FOREIGN PATENT DOCUMENTS

CN	101061515 A	10/2007
CN	101175210 A	5/2008

CN	101189874 A	5/2008
CN	101771879 A	7/2010
CN	101911702 A	12/2010
CN	102014283 A	4/2011
CN	102017629 A	4/2011
EP	1 797 536	4/2006
EP	1797536 B1	6/2007
EP	2 164 176 A1	3/2010
JP	2008-113374 A	5/2008
JP	2008-124926 A	5/2008
JP	2010-200281 A	9/2010
JP	2011-061877 A	3/2011
JP	2011-120047 A	6/2011
JP	2014-504077 A	2/2014
JP	2014-520451 A	8/2014
KR	10-2007-0051681 A	5/2007
KR	10-0718134 B1	5/2007
KR	10-2009-0129939 A	12/2009
RU	2 406 256 C2	12/2010
TW	201112769 A1	4/2011
TW	201116066 A1	5/2011
WO	03/094529 A2	11/2003
WO	2009/114233 A1	9/2009
WO	2011/128268 A1	10/2011
WO	2011142817 A1	11/2011
WO	WO-2011142817 A1 *	11/2011 H03M 7/4006
WO	2012/005551 A2	1/2012
WO	2010/021699 A1	2/2012
WO	2012/075181 A1	6/2012
WO	2012/172114 A1	12/2012

OTHER PUBLICATIONS

Communication dated Oct. 12, 2018, from the State Intellectual Property Office of People's Republic of China in counterpart Application No. 201510919014.8.

Communication dated Dec. 19, 2018, from the Russian Patent Office in counterpart application No. 2018113469/07.

Sole et al., "CE11: Parallel Context Processing for the significance map in high coding efficiency", Joint Collaborative Team on Video Coding (JCT-VC) of ITU-T SG16 WP# and ISO/IEC JTC1/SC29/WG11, Mar. 17, 2011, 6 pages.

Sole et al., "Parallel Context Processing for the significance map in high coding efficiency", Joint Collaborative Team on Video Coding (JCT-VC) of ITU-T SG16 WP3 and ISO/IEC JTC1/SC29/WG11, Jan. 2011, 4 pages.

Budagavi, "TE8: TI Parallel Context Processing (PCP) Proposal", Joint Collaborative Team on Video Coding (JCT-VC) of ITU-T SG16 WP3 and ISO/IEC JTC1/SC29/WG11, Oct. 2010, 7 pages total.

Communication dated Feb. 17, 2017 issued by European Patent Office in counterpart European Patent Application No. 12804190.2.

Communication, Issued by the Korean Intellectual Property Office, dated Aug. 19, 2014, In counterpart Korean application No. 10-2012-0069481.

Communication, Issued by the Japanese Patent Office, dated Oct. 9, 2014, in counterpart Japanese Application No. 2014-518796.

International Search Report (PCT/ISA/210), dated Jan. 10, 2013, issued by the International Searching Authority in counterpart International Patent Application No. PCT/KR2012/005087.

Communication dated May 12, 2014 issued by the Korean Intellectual Property Office in counterpart Korea Patent Application No. 10-2012-0069481.

Marpe, et al.; "Context-Based Adaptive Binary Arithmetic Coding in the H.264/AVC Video Compression Standard", IEEE Transaction on Circuits and Systems for Video Technology, Jul. 2003, vol. 13, No. 7, 17 pages total.

Communication dated Oct. 2, 2015, issued by the Russian Federal Service for Intellectual Property (Rospatent), in counterpart Russian Application No. 2014102581.

Sasai et al., "Parallel Context Processing for Significance map using block-based context updates", Joint Collaborative Team on Video Coding (JCT-VC) of ITU-T SG16 WP3 and ISO/IEC JTC1/SC29/WG11, 5th Meeting, Mar. 16-23, 2011, 4 total pages.

(56)

References Cited

OTHER PUBLICATIONS

Communication dated Nov. 20, 2015 by the Australian Intellectual Property Office in related Application No. 2012276453.

Communication dated Dec. 15, 2015 by the Japanese Patent Office in related Application No. 2015-084083.

Nguyen et al., "Reduced-complexity entropy coding of transform coefficient levels using a combination of VLC and Pipe", Joint Collaborative Team on Video Coding (JCT-VC) of ITU-T SG16 WP3 and ISO/IEC JTC1/SC29/WG11, 4th Meeting, Jan. 20-28, 2011, 8 total pages.

Seregin et al., "Binarisation modification for last position coding", Joint Collaborative Team on Video Coding (JCT-VC) of ITU-T SG16 WP3 and ISO/IEC JTC1/SC29/WG11, 6th Meeting, Jul. 14-22, 2011, 10 total pages.

Communication dated Feb. 9, 2016 issued by the European Patent Office in counterpart European Patent Application No. 14192917.4.

Communication dated Jan. 15, 2016 issued by the the Russian Patent Office in counterpart Russian Patent Application No. 2014102581.

Communication dated Mar. 18, 2016 issued by the Taiwanese Patent Office in counterpart Taiwanese Patent Application No. 101123244.

Communication dated Mar. 23, 2016 issued by the European Patent Office in counterpart European Patent Application No. 15194151.5.

Communication dated Mar. 23, 2016 issued by the European Patent Office in counterpart European Patent Application No. 15194152.3.

Rapporteur (Dr. Gary Sullican—Microsoft/USA) and Associate Rapporteur (Dr. Thomas Wiegand—H.Hertz Institute/Germany); "Editors Draft Text for Recommendation H.264 Advanced Video Coding for Generic Audiovisual Services"; 3GPP Draft; 3-037; 3rd Generation Partnership Project (3GPP); Mobile Competence Centre; 650; Route Des Lucioles; vol. SA WG4; No. Redmond, WA; XP050285552; Nov. 8, 2002; 203 total pages.

Communication dated Feb. 21, 2017 issued by the State Intellectual Property Office of P.R. China in counterpart Chinese Application No. 201510919014.8.

Communication dated Feb. 22, 2017 issued by the State Intellectual Property Office of P.R. China in counterpart Chinese Application No. 201510919040.0.

Communication dated Feb. 22, 2017 issued by the State Intellectual Property Office of P.R. China in counterpart Chinese Application No. 201510919313.1.

Communication dated Jan. 9, 2017 issued by Russian Intellectual Property Office in counterpart Russian Patent Application No. 201611706/07(027445).

Communication dated Jan. 17, 2017 issued by European Patent Office in counterpart European Patent Application No. 12804190.2.

Communication dated Dec. 15, 2016 issued by European Patent Office in counterpart European Patent Application No. 15153506.9.

Communication dated Mar. 10, 2015 issued by European Patent Office in counterpart European Patent Application No. 15153506.9. Panusopone et al., "Flexible Picture Partitioning", Joint Collaborative Team on Video Coding (JCT-VC) of ITU-T SG16 WP3 and ISO/IEC JTC1/SC29/WG11, Oct. 7-15, 2010, 13 pages total, p. 1-13, 3rd Meeting, Motorola Mobility, Guangzhou, CN, JCTVC-C260r1.

Communication dated Nov. 22, 2016 issued by European Patent Office in counterpart European Application No. 15 194 152.3.

Communication dated Dec. 30, 2016 issued by The State Intellectual Property Office of P.R. China in counterpart Chinese Application No. 201280042529.9.

Communication dated Nov. 24, 2016 issued by Ministry of Justice and Human Rights of The Republic of Indonesia Directorate General of Intellectual Property Rights in conterpart Indonesian Application No. HKI-3-HI.05.02.01.P00201400487-TA.

Communication dated Oct. 21, 2014 issued by the Japanese Patent Office in counterpart Japanese Patent Application No. 2014-518796.

Communication Notice of Allowance dated Jul. 8, 2015 issued by the Korean Intellectual Property Office in counterpart Korean Application No. 10-2015-0040056.

Communication Office Action dated Apr. 22, 2015 issued by the Korean Intellectual Property Office in counterpart Korean Application No. 10-2015-0040056.

Communication dated Jun. 29, 2016, from the European Patent Office in counterpart European Application No. 14192917.4.

Communication dated Feb. 17, 2015, from the European Patent Office in counterpart European Application No. 14192917.4.

Communication dated Mar. 2, 2015, from the European Patent Office in counterpart European Application No. 14192917.4.

Communication dated May 25, 2016, from the State Intellectual Property Office of People's Republic of China in counterpart Application No. 201280042529.9.

Communication dated May 10, 2016, from the European Patent Office in counterpart European Application No. 12804190.2.

Thomas Wiegand et al., "WD3: Working Draft 3 of High-Efficiency Video Coding", International Organisation for Standardisation Organisation Internationale De Normalisation ISO/IEC JTC1/SC29/WG11 Coding of Moving Pictures and Audio, ISO/IEC JTC1/SC29/WG11 N12001, Joint Collaborative Team on Video Coding (JCT-VC) of ITU-T SG16 WP3 and ISO/IEC JTC1/SC29/WG11 5th Meeting: Geneva, CH, Mar. 16-23, 2011, Document: JCTVC-E603 XP030018494 (216 Pages Total).

Communication dated Aug. 24, 2016, issued by the State Intellectual Property Office of P.R. China in counterpart Chinese application No. 201510919014.8.

Communication dated Feb. 24, 2015, issued by the Korean Intellectual Property Office in counterpart Korean Application No. 10-2014-0054356.

Communication dated Apr. 22, 2015, issued by the Korean Intellectual Property Office in counterpart Korean Application No. 10-2015-0040055.

Communication dated Apr. 22, 2015, issued by the Korean Intellectual Property Office in counterpart Korean Application No. 10-2014-0040056.

Non-Final Office Action dated Sep. 8, 2016 in U.S. Appl. No. 14/635,725.

Notice of Allowance dated Jan. 18, 2017 in U.S. Appl. No. 14/635,725.

Communication dated May 27, 2017, issued by the State Intellectual Property Office of P.R. China in counterpart Chinese Application No. 201280042529.9.

Communication dated Jun. 19, 2017, issued by the State Intellectual Property Office of P.R. China in counterpart Chinese Application No. 201510919014.8.

Communication dated Jun. 27, 2017, issued by the Taiwanese Intellectual Property Office in counterpart Taiwanese Application No. 105134471.

Communication dated Nov. 3, 2017 by the State Intellectual Property Office of P. R. China in counterpart Chinese Patent Application No. 201510919253.3.

Communication dated Jan. 5, 2018 by the European Patent Office in counterpart European Patent Application No. 17203278.1.

Han, et al., "Improved Video Compression Efficiency Through Flexible Unit Representation and Corresponding Extension of Coding Tools", Dec. 2010, IEEE Transactions on Circuits and Systems for Video Technology, vol. 20, No. 12, pp. 1709-1720.

Communication dated Jul. 10, 2018, issued by the Taiwanese Intellectual Property Office in counterpart Taiwan Patent Application No. 106146130.

Communication dated Aug. 6, 2018, issued by the European Patent Office in counterpart European Patent Application No. 18180918.7.

Communication dated May 6, 2019, issued by the Intellectual Property Office of the Philippines in counterpart Philippine Application No. 1/2017/500999.

Communication dated May 6, 2019, issued by the Intellectual Property Office of the Philippines in counterpart Philippine Application No. 1/2017/501000.

Communication dated May 9, 2019, issued by the Intellectual Property Office of the Philippines in counterpart Philippine Application No. 1/2017/501001.

Communication dated May 9, 2019, issued by the Intellectual Property Office of the Philippines in counterpart Philippine Application No. 1/2017/501002.

(56)

References Cited

OTHER PUBLICATIONS

Communication dated Jul. 2, 2019, issued by the Indonesian Patent Office in counterpart Indonesian Application No. P00201701487.
Communication dated Sep. 24, 2019, issued by the Chinese Patent Office in counterpart Chinese Application No. 201711346005.X.
Communication dated Nov. 6, 2019, issued by the Chinese Patent Office in counterpart Chinese Application No. 201711346630.4.
Communication dated Oct. 2, 2019, issued by the Indonesian Patent Office in counterpart Indonesian Application No. P00201701489.
Communication dated Oct. 2, 2019, issued by the Indonesian Patent Office in counterpart Indonesian Application No. P00201701490.
Communication dated Sep. 29, 2019, issued by the Chinese Patent Office in counterpart Chinese Application No. 201711346186.6.
Communication dated Oct. 8, 2019, issued by the Chinese Patent Office in counterpart Chinese Application No. 201711346980.0.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13





FIG. 14







FIG. 15

FIG. 16



CODING UNIT (1010)

FIG. 17




FIG. 18





FIG. 19



**METHOD AND APPARATUS FOR CODING
VIDEO AND METHOD AND APPARATUS
FOR DECODING VIDEO ACCOMPANIED
WITH ARITHMETIC CODING**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a Continuation of U.S. application Ser. No. 15/584,523 filed on May 2, 2017, in the U.S. Patent and Trademark Office, which is a Continuation of U.S. application Ser. No. 14/635,725 filed on Mar. 2, 2015, in the U.S. Patent and Trademark Office, now U.S. Pat. No. 9,668,001, issued on May 30, 2017, which is a Continuation of U.S. application Ser. No. 14/130,052 filed on Apr. 7, 2014, in the U.S. Patent and Trademark Office, now U.S. Pat. No. 9,565,455, issued on Feb. 7, 2017, which is a National Stage Entry of PCT/KR2012/005087 filed on Jun. 27, 2012, which claims the benefit of U.S. provisional patent application No. 61/502,038 filed on Jun. 28, 2011, in the U.S. Patent and Trademark Office, the entire disclosures of which are herein incorporated by reference in their entireties.

TECHNICAL FIELD

Exemplary embodiments relate to video encoding and video decoding involving arithmetic encoding and arithmetic decoding, respectively.

BACKGROUND OF THE RELATED ART

As hardware for reproducing and storing high resolution or high quality video content is being developed and supplied, a need for a video codec for effectively encoding or decoding the high resolution or high quality video content is increasing. In a conventional video codec, a video is encoded according to a limited encoding method based on a macroblock having a predetermined size.

Image data of a spatial domain is converted to coefficients of a frequency region by using a frequency conversion method. A video codec encodes frequency coefficients in units of blocks by dividing an image into a plurality of blocks having a predetermined size and performing discrete cosine transformation (DCT) conversion for rapid operation of frequency conversion. The coefficients of the frequency region are easily compressed compared to the image data of the spatial domain. In particular, a pixel value of an image in the spatial domain is represented as a prediction error, and thus, if frequency conversion is performed on the prediction error, a large amount of data may be converted to 0. A video codec converts data that is continuously and repeatedly generated into smaller data to reduce an amount of data.

SUMMARY

Exemplary embodiments provide a method and apparatus for performing arithmetic encoding and arithmetic decoding of a video by classifying a symbol into prefix and suffix bit strings.

According to an aspect of an exemplary embodiment, there is provided a method of decoding a video through symbol decoding, the method including: parsing symbols of image blocks from a received bitstream; classifying a current symbol into a prefix bit string and a suffix bit string based on a threshold value determined according to a size of a current block; performing arithmetic decoding of the prefix bit string and the suffix bit string by using respective

arithmetic decoding methods determined for each of the prefix bit string and the suffix bit string; performing inverse binarization of the prefix bit string and the suffix bit string by using respective binarization methods determined for each of the prefix bit string and the suffix bit string; and restoring the image blocks by performing an inverse transformation operation and a prediction operation on the current block by using the current symbol restored through the arithmetic decoding and the inverse binarization.

Efficiency of a symbol encoding/decoding process is improved by performing a binarization method having a relatively small amount of operation burden on the suffix region or the suffix bit string or by omitting the context modeling during the context-based arithmetic encoding/decoding for symbol encoding/decoding.

The performing of the inverse binarization may include restoring a prefix region and a suffix region of the current symbol by performing the inverse binarization according to the respective binarization methods determined for each of the prefix bit string and the suffix bit string.

The performing of the arithmetic decoding may include: performing arithmetic decoding for determining context modeling on the prefix bit string according to locations of bits; and performing arithmetic decoding for omitting the context modeling on the suffix bit string in a bypass mode.

The performing of the arithmetic decoding may include performing the arithmetic decoding by using a context of a predetermined index that is previously allocated to locations of bits of the prefix bit string, when the symbol is final coefficient position information of a transformation coefficient.

The current symbol may include at least one of an intra prediction mode and final coefficient position information of the current block.

The binarization method further may include at least one selected from the group consisting of unary binarization, truncated unary binarization, exponential golomb binarization, and fixed length binarization.

According to another aspect of an exemplary embodiment, there is provided a method of encoding a video through symbol encoding, the method including: generating symbols by performing a prediction operation and a transformation operation on image blocks; classifying a current symbol into a prefix region and a suffix region based on a threshold value determined according to a size of a current block; generating a prefix bit string and a suffix bit string by using respective binarization methods determined for each of the prefix region and the suffix region; performing symbol encoding of the prefix bit string and the suffix bit string by using respective arithmetic encoding methods determined for each of the prefix bit string and the suffix bit string; and outputting bit strings generated through the symbol encoding in the form of bitstreams.

The performing of the symbol encoding may include: performing the symbol encoding on the prefix bit string by using an arithmetic encoding method for performing context modeling according to locations of bits; and performing the symbol encoding on the suffix bit string by using an arithmetic encoding method for omitting the context modeling in a bypass mode.

The performing of the symbol encoding may include performing the arithmetic encoding by using a context of a predetermined index that is previously allocated to locations of bits of the prefix bit string, when the symbol is final coefficient position information of a transformation coefficient.

3

The current symbol may include at least one of an intra prediction mode and final coefficient position information of the current block.

The binarization method may further include at least one selected from the group consisting of unary binarization, truncated unary binarization, exponential golomb binarization, and fixed length binarization.

According to another aspect of an exemplary embodiment, there is provided an apparatus configured to decode a video through symbol decoding, the apparatus including: a parser configured to parse symbols of image blocks from a received bitstream; a symbol decoder configured to classify a current symbol into a prefix bit string and a suffix bit string based on a threshold value determined according to a size of a current block, and to perform arithmetic decoding of the prefix bit string and the suffix bit string by using respective arithmetic decoding methods determined for each of the prefix bit string and the suffix bit string, and to perform inverse binarization of the prefix bit string and the suffix bit string by using respective binarization methods determined for each of the prefix bit string and the suffix bit string; and an image restorer configured to restore the image blocks by performing an inverse transformation operation and a prediction operation on the current block by using the current symbol restored through the arithmetic decoding and the inverse binarization.

According to another aspect of an exemplary embodiment, there is provided an apparatus configured to encode a video through symbol encoding, the apparatus including: an image encoder configured to generate symbols by performing prediction and transformation on image blocks; a symbol encoder configured to classify a current symbol into a prefix region and a suffix region based on a threshold value determined according to a size of a current block, and to generate a prefix bit string and a suffix bit string by using respective binarization methods determined for each of the prefix region and the suffix region, and to perform symbol encoding of the prefix bit string and the suffix bit string by using arithmetic encoding methods determined for each of the prefix bit string and the suffix bit string; and a bitstream outputter configured to output bit strings generated through the symbol encoding in the form of bitstreams.

According to another aspect of an exemplary embodiment, there is provided a non-transitory computer readable recording medium having embodied thereon a computer program for executing the method of decoding a video through symbol decoding.

According to another aspect of an exemplary embodiment, there is provided a non-transitory computer readable recording medium having embodied thereon a computer program for executing the method of encoding a video through symbol encoding.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a block diagram of a video encoding apparatus, according to an exemplary embodiment;

FIG. 2 is a block diagram of a video decoding apparatus, according to an exemplary embodiment of the present invention;

FIGS. 3 and 4 are diagrams for describing arithmetic encoding by classifying a symbol into a prefix bit string and a suffix bit string according to a predetermined threshold value, according to an exemplary embodiment;

FIG. 5 is a flowchart for describing a video encoding method, according to an exemplary embodiment;

4

FIG. 6 is a flowchart for describing a video decoding method, according to an exemplary embodiment;

FIG. 7 is a block diagram of a video encoding apparatus based on coding units having a tree structure, according to an exemplary embodiment;

FIG. 8 is a block diagram of a video decoding apparatus based on a coding unit having a tree structure, according to an exemplary embodiment;

FIG. 9 is a conceptual diagram of coding units, according to an exemplary embodiment;

FIG. 10 is a block diagram of an image encoder based on coding units, according to an exemplary embodiment;

FIG. 11 is a block diagram of an image decoder based on coding units, according to an exemplary embodiment;

FIG. 12 is a diagram showing coding units according to depths and partitions, according to an exemplary embodiment;

FIG. 13 is a diagram for describing a relationship between a coding unit and transformation units, according to an exemplary embodiment;

FIG. 14 is a diagram for describing encoding information of coding units according to depths, according to an exemplary embodiment;

FIG. 15 is a diagram showing coding units according to depths, according to an exemplary embodiment;

FIGS. 16 to 18 are diagrams for describing a relationship between coding units, prediction units, and transformation units, according to an exemplary embodiment; and

FIG. 19 is a diagram for describing a relationship between a coding unit, a prediction unit, and a transformation unit according to encoding mode information of Table 1.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

Hereinafter, the exemplary embodiments will be described more fully with reference to the accompanying drawings, in which exemplary embodiments are shown. Expressions such as "at least one of," when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list.

A video encoding method involving arithmetic encoding and a video decoding method involving arithmetic decoding according to an exemplary embodiment will be described with reference to FIGS. 1 to 6. Also, a video encoding method involving arithmetic encoding and a video decoding method involving arithmetic decoding based on coding units having a tree structure according to an exemplary embodiment will be described with reference to FIGS. 7 to 19.

Hereinafter, an 'image' may refer to a still image of a video or a movie, that is, a video itself.

Hereinafter, a video encoding method and a video decoding method based on a prediction method in an intra prediction mode, according to an exemplary embodiment, will be described with reference to FIGS. 1 to 6.

FIG. 1 is a block diagram of a video encoding apparatus 10, according to an exemplary embodiment.

The video encoding apparatus 10 may encode video data of a spatial domain through intra prediction/inter prediction, transformation, quantization, and symbol encoding. Hereinafter, operations occurring when the video encoding apparatus 10 encodes symbols generated by the intra prediction/inter prediction, the transformation, and the quantization through arithmetic encoding will be described in detail.

The video encoding apparatus 10 includes an image encoder 12, a symbol encoder 14, and a bitstream output unit 16 (e.g., bitstream outputter).

The video encoding apparatus **10** may split image data of a video into a plurality of data units and encode the image data according to the data units. The data unit may have a square shape or a rectangular shape, or may be an arbitrary geometric shape, but the data unit is not limited to a data unit having a predetermined size. According to the video encoding method based on the coding units having a tree structure, a data unit may be a maximum coding unit, a coding unit, a prediction unit, a transformation unit, or the like. An example where an arithmetic encoding/decoding method according to an exemplary embodiment is used in the video encoding/decoding method based on the coding units having a tree structure will be described with reference to FIGS. **7** to **19**.

For convenience of description, a video encoding method for a 'block' which is a kind of data unit will be described in detail. However, the video encoding method according to various exemplary embodiments is not limited to the video encoding method for the 'block', and may be used for various data units.

The image encoder **12** performs operations, such as intra prediction and inter prediction, transformation, or quantization, on image blocks to generate symbols.

The symbol encoder **14** classifies a current symbol into a prefix region and a suffix region based on a threshold value determined according to a size of a current block to encode the current symbol from among the symbols generated according to the blocks. The symbol encoder **14** may determine the threshold value for classifying the current symbol into the prefix region and the suffix region based on at least one of a width and a height of the current block.

The symbol encoder **14** may determine a symbol encoding method for each of the prefix region and the suffix region and encode each of the prefix region and the suffix region according to the symbol encoding method.

Symbol encoding may be divided into a binarization process for transforming a symbol into bit strings and an arithmetic encoding process for performing context-based arithmetic encoding on the bit strings. The symbol encoder **14** may determine a binarization method for each of the prefix region and the suffix region of the symbol and perform binarization on each of the prefix region and the suffix region according to the binarization method. A prefix bit string and a suffix bit string may be generated from the prefix region and the suffix region, respectively.

Alternatively, the symbol encoder **14** may determine an arithmetic encoding method for each of the prefix bit string and the suffix bit string of the symbol and perform arithmetic encoding on each of the prefix bit string and the suffix bit string according to the arithmetic encoding method.

Also, the symbol encoder **14** may determine a binarization method for each of the prefix region and the suffix region of the symbol and perform binarization on each of the prefix region and the suffix region according to the binarization method, and may determine an arithmetic encoding method for each of the prefix bit string and the suffix bit string of the symbol and perform arithmetic encoding on the prefix bit string and the suffix bit string according to the arithmetic encoding method.

The symbol encoder **14** according to an exemplary embodiment may determine a binarization method for each of the prefix region and the suffix region. The binarization methods determined for the prefix region and the suffix region may be different from each other.

The symbol encoder **14** may determine an arithmetic encoding method for each of the prefix bit string and the

suffix bit string. The arithmetic encoding methods determined for the prefix bit string and the suffix bit string may be different from each other.

Accordingly, the symbol encoder **14** may binarize the prefix region and the suffix region by using different methods only in a binarization process of a symbol decoding process, or may encode the prefix bit string and the suffix bit string by using different methods only in an arithmetic encoding process. Also, the symbol encoder **14** may encode the prefix region (prefix bit string) and the suffix region (suffix bit string) by using different methods in both the binarization and arithmetic encoding processes.

The selected binarization method may be at least one of general binarization, unary binarization, truncated unary binarization, exponential golomb binarization, and fixed length binarization methods.

The symbol encoder **14** may perform symbol encoding by performing arithmetic encoding for performing context modeling on the prefix bit string according to locations of bits and by performing arithmetic encoding for omitting context modeling on the suffix bit string in a bypass mode.

The symbol encoder **14** may individually perform the symbol encoding on the prefix region and the suffix region with respect to symbols including at least one of an intra prediction mode and final coefficient position information of a transformation coefficient.

The symbol encoder **14** may also perform the arithmetic encoding by using a context of a predetermined index that is previously allocated to the prefix bit string. For example, the symbol encoder **14** may perform arithmetic encoding by using a context of a predetermined index that is previously allocated to each location of the bits of the prefix bit string when the symbol is final coefficient position information of the transformation coefficient.

The bitstream output unit **16** outputs bit strings generated through the symbol encoding in the form of bitstreams.

The video encoding apparatus **10** may perform arithmetic encoding on symbols of blocks of a video and output the symbols.

The video encoding apparatus **10** may include a central processor (not shown) for controlling each of the image encoder **12**, the symbol encoder **14**, and the bitstream output unit **16**. Alternatively, the image encoder **12**, the symbol encoder **14**, and the bitstream output unit **16** may be operated by processors (not shown) respectively installed therein, and the entire video encoding apparatus **10** may be operated by systematically operating the processors (not shown). Alternatively, the image encoder **12**, the symbol encoder **14**, and the bitstream output unit **16** may be controlled by an external processor (not shown) of the video encoding apparatus **10**.

The video encoding apparatus **10** may include at least one data storage unit (not shown) for storing data that is input/output to/from the image encoder **12**, the symbol encoder **14**, and the bitstream output unit **16**. The video encoding apparatus **10** may include a memory controller (not shown) for controlling input/output of data stored in the data storage unit (not shown).

The video encoding apparatus **10** is operated by being linked with an internal video encoding processor or an external video encoding processor to perform video encoding including prediction and transformation, thereby outputting a result of the video encoding. The internal video encoding processor of the video encoding apparatus **10** may perform a basic video encoding operation not only by using a separate processor, but also by including a video encoding

processing module in the video encoding apparatus 10, a central operating apparatus, or a graphic operating apparatus.

FIG. 2 is a block diagram of a video decoding apparatus 20, according to an exemplary embodiment.

The video decoding apparatus 20 may decode the video data encoded by the video encoding apparatus 10 through parsing, symbol decoding, inverse quantization, inverse transformation, intra prediction/motion compensation, etc. and restore the video data close to the original video data of the spatial domain. Hereinafter, a process in which the video decoding apparatus 20 performs arithmetic decoding on the parsed symbols from a bitstream to restore the symbols will be described.

The video decoding apparatus 20 includes a parser 22, a symbol decoder 24, and an image restoring unit 26 (e.g., image restorer).

The video decoding apparatus 20 may receive a bitstream including encoded data of a video. The parser 22 may parse symbols of image blocks from the bitstream.

The parser 22 may parse the symbols encoded through arithmetic encoding with respect to the blocks of the video from the bitstream.

The parser 22 may parse symbols including an intra prediction mode of the block of the video, final coefficient position information of a transformation coefficient, etc. from the received bitstream.

The symbol decoder 24 determines a threshold value for classifying a current symbol into a prefix bit string and a suffix bit string. The symbol decoder 24 may determine the threshold value for classifying the current symbol into the prefix bit string and the suffix bit string based on a size of a current block, that is, at least one of a width and a height of the current block. The symbol decoder 24 determines an arithmetic decoding method for each of the prefix bit string and the suffix bit string. The symbol decoder 24 performs symbol decoding by using the arithmetic decoding method determined for each of the prefix bit string and the suffix bit string.

The arithmetic decoding methods determined for the prefix bit string and the suffix bit string may be different from each other.

The symbol decoder 24 may determine a binarization method for each of the prefix bit string and the suffix bit string of the symbol. Accordingly, the symbol decoder 24 may perform inverse binarization on the prefix bit string of the symbol by using the binarization method. The binarization methods determined for the prefix bit string and the suffix bit string may be different from each other.

Also, the symbol decoder 24 may perform arithmetic decoding by using the arithmetic decoding method determined for each of the prefix bit string and the suffix bit string of the symbol, and may perform inverse binarization by using the binarization method determined for each of the prefix bit string and the suffix bit string generated through the arithmetic decoding.

Accordingly, the symbol decoder 24 may decode the prefix bit string and the suffix bit string by using different methods only in an arithmetic decoding process of a symbol decoding process, or may perform inverse binarization by using different methods only in an inverse binarization process. Also, the symbol decoder 24 may decode the prefix bit string and the suffix bit string by using different methods in both the arithmetic decoding and inverse binarization processes.

The binarization method determined for each of the prefix bit string and the suffix bit string of the symbol may not only

be a general binarization method, but may also be at least one of unary binarization, truncated unary binarization, exponential golomb binarization, and fixed length binarization methods.

The symbol decoder 24 may perform arithmetic decoding for performing context modeling on the prefix bit string according to locations of bits. The symbol decoder 24 may use an arithmetic decoding method for omitting context modeling on the suffix bit string in a bypass mode. Accordingly, the symbol decoder 24 may perform symbol decoding through the arithmetic decoding performed on each of the prefix bit string and the suffix bit string of the symbol.

The symbol decoder 24 may perform the arithmetic decoding on the prefix bit string and the suffix bit string of symbols including at least one of an intra prediction mode and final coefficient position information of a transformation coefficient.

The symbol decoder 24 may perform arithmetic decoding by using a context of a predetermined index that is previously allocated according to locations of the bits of the prefix bit string when the symbol is information about the final coefficient position of the transformation coefficient.

The image restoring unit 26 may restore a prefix region and a suffix region of a symbol by performing the arithmetic decoding and the inverse binarization on each of the prefix bit string and the suffix bit string. The image restoring unit 26 may restore the symbol by synthesizing the prefix region and the suffix region of the symbol.

The image restoring unit 26 performs inverse transformation and prediction on the current block by using the current symbol restored through the arithmetic decoding and the inverse binarization. The image restoring unit 26 may restore image blocks by performing operations, such as inverse quantization, inverse transformation, or intra prediction/motion compensation, by using the corresponding symbols for each of the image blocks.

The video decoding apparatus 20 according to an exemplary embodiment may include a central processor (not shown) for controlling each of the parser 22, the symbol decoder 24, and the image restoring unit 26. Alternatively, the parser 22, the symbol decoder 24, and the image restoring unit 26 may be operated by processors (not shown) respectively installed therein, and the entire video decoding apparatus 20 may be operated by systematically operating the processors (not shown). Alternatively, the parser 22, the symbol decoder 24, and the image restoring unit 26 may be controlled by an external processor (not shown) of the video decoding apparatus 20.

The video decoding apparatus 20 may include at least one data storage unit (not shown) for storing data that is input and output to and from the parser 22, the symbol decoder 24, and the image restoring unit 26. The video decoding apparatus 20 may include a memory controller (not shown) for controlling input/output of data stored in the data storage unit (not shown).

The video decoding apparatus 20 is operated by being linked with an internal video decoding processor or an external video decoding processor to perform video decoding including inverse transformation. The internal video decoding processor of the video decoding apparatus 20 may perform a basic video decoding operation not only by using a separate processor, but also by including a video decoding processing module in the video decoding apparatus 20, a central operating apparatus, or a graphic operating apparatus.

Context-based adaptive binary arithmetic coding (CABAC) is widely used as an arithmetic encoding and decod-

ing method based on a context for symbol encoding and decoding. According to the context-based arithmetic encoding and decoding, each bit of a symbol bit string may be a bin of a context, and a location of each bit may be mapped to a bin index. A length of the bit string, that is, a length of the bin, may vary according to a size of a symbol value. Context modeling for determining a context of a symbol is required to perform the context-based arithmetic encoding and decoding. The context is renewed according to locations of bits of the symbol bit string, that is, in each bin index, to perform the context modeling, and thus a complicated operation process is required.

According to the video encoding apparatus **10** and the video decoding apparatus **20** described with reference to FIGS. **1** and **2**, the symbol is classified into the prefix region and the suffix region, and a relatively simple binarization method may be used for the suffix region compared to the prefix region. Also, the arithmetic encoding and decoding through the context modeling is performed on the prefix bit string, and the context modeling is not performed on the suffix bit string, and thus a burden of an operation amount for the context-based arithmetic encoding and decoding may be reduced. Accordingly, the video encoding apparatus **10** and the video decoding apparatus **20** may improve efficiency of a symbol encoding and decoding process by performing a binarization method having a relatively small amount of operation burden on the suffix region or the suffix bit string or by omitting the context modeling during the context-based arithmetic encoding and decoding for symbol encoding and decoding.

Hereinafter, various exemplary embodiments for arithmetic encoding that may be performed by the video encoding apparatus **10** and the video decoding apparatus **20** will be described.

FIGS. **3** and **4** are diagrams for describing arithmetic encoding by classifying a symbol into a prefix bit string and a suffix bit string according to a predetermined threshold value, according to an exemplary embodiment.

Referring to FIG. **3**, a process of performing symbol encoding, according to an exemplary embodiment, on final coefficient position information of a symbol will be described in detail. The final coefficient position information is a symbol representing a location of a final coefficient, not 0, from among transformation coefficients of a block. Since a size of the block is defined as a width and a height, the final coefficient position information may be represented by two-dimensional coordinates, that is, an x-coordinate in a width direction and a y-coordinate in a height direction. For convenience of description, FIG. **3** shows a case where symbol encoding is performed on the x-coordinate in the width direction from among the final coefficient position information when a width of a block is w .

A range of the x-coordinate of the final coefficient position information is within the width of the block, and thus the x-coordinate of the final coefficient position information is equal to or greater than 0 and equal to or less than $w-1$. For the arithmetic encoding of the symbol, the symbol may be classified into a prefix region and a suffix region based on a predetermined threshold value th . Thus, the arithmetic encoding may be performed on the prefix bit string in which the prefix region is binarized, based on the context determined through the context modeling. Also, the arithmetic encoding may be performed on the suffix bit string in which the suffix region is binarized, in a bypass mode in which the context modeling is omitted.

Here, the threshold value th for classifying the symbol into the prefix region and the suffix region may be deter-

mined based on the width w of the block. For example, the threshold value th may be determined to be $(w/2)-1$ to divide the bit string by two (threshold value determination formula 1, shown below). Alternatively, the width w of the block generally has a square of 2, and thus the threshold value th may be determined based on a log value of the width w (threshold value determination formula 2, shown below).

$$th=(w/2)-1; \quad \text{<threshold value determination formula 1>}$$

$$th=(\log 2w \llcorner 1)-1; \quad \text{<threshold value determination formula 2>}$$

In FIG. **3**, according to the threshold value determination formula 1, when the width w of the block is 8, the formula outputs threshold value $th=(8/2)-1=3$. Thus, in the x-coordinate of the final coefficient position information, 3 may be classified as the prefix region, and the rest of values other than 3 may be classified as the suffix region. The prefix region and the suffix region may be binarized according to the binarization method determined for each of the prefix region and the suffix region.

When an x-coordinate N of current final coefficient position information is 5, the x-coordinate of the final coefficient position information may be classified as $N=th+2=3+2$. In other words, in the x-coordinate of the final coefficient position information, 3 may be classified as the prefix region, and 2 may be classified as the suffix region.

According to an exemplary embodiment, the prefix region and the suffix region may be binarized according to different binarization methods determined for the prefix region and the suffix region, respectively. For example, the prefix region may be binarized according to a unary binarization method, and the suffix region may be binarized according to a general binarization method.

Accordingly, after 3 is binarized according to the unary binarization method, a prefix bit string **32** '0001' may be generated from the prefix region, and after 2 is binarized according to the general binarization method, a suffix bit string **34** '010' may be generated from the suffix region.

Also, context-based arithmetic encoding may be performed on the prefix bit string **32** '0001' through context modeling. Thus, a context index may be determined for each bin of the prefix bit string **32** '0001'.

Arithmetic encoding may be performed on the suffix bit string **34** '010' in a bypass mode without performing context modeling. The arithmetic encoding may be performed without performing the context modeling assuming that in the bypass mode each bin has a context of an equal probability state, that is, the context of 50%.

Accordingly, the context-based arithmetic encoding may be performed on each of the prefix bit string **32** '0001' and the suffix bit string **34** '010' to complete the symbol encoding with respect to the x-coordinate N of the current final coefficient position information.

Although the exemplary embodiment in which the symbol encoding is performed via the binarization and the arithmetic encoding has been described, symbol decoding may be performed in the same manner. In other words, a parsed symbol bit string may be classified into a prefix bit string and a suffix bit string based on the width w of the block, the arithmetic decoding may be performed on the prefix bit string **32** through the context modeling, and the arithmetic decoding may be performed on the suffix bit string **34** without performing the context modeling. Inverse binarization may be performed on the prefix bit string **32** after the arithmetic decoding by using the unary binarization method, and the prefix region may be restored. Also, the inverse binarization may be performed on the suffix bit

11

string **34** after the arithmetic encoding by using the general binarization method, and thus the suffix region may be restored. The symbol may be restored by synthesizing the restored prefix region and suffix region.

Although the exemplary embodiment in which the unary binarization method is used for the prefix region (prefix bit string) and the general binarization method is used for the suffix region (suffix bit string) has been described, the binarization method is not limited thereto. Alternatively, for example, a truncated unary binarization method may be used for the prefix region (prefix bit string), and a fixed length binarization method may be used for the suffix region (suffix bit string).

Although only the exemplary embodiment regarding the final coefficient position information in a width direction of the block has been described, an exemplary embodiment regarding a final coefficient position information in a height direction of the block may also be used.

Also, there is no need to perform context modeling on the suffix bit string for performing the arithmetic encoding by using a context having a fixed probability, but there may be a need to perform variable context modeling on the prefix bit string. The context modeling to be performed on the prefix bit string may be determined according to a size of the block.

<Context Mapping Table>

Block Size	Bin Index No. of Selected Context
4 × 4	0, 1, 2, 2
8 × 8	3, 4, 5, 5
16 × 16	6, 7, 8, 9, 10, 10, 11, 11
32 × 32	12, 13, 14, 15, 16, 16, 16, 16, 17, 17, 17, 17, 18, 18, 18, 18

In the context mapping table, a location of each number corresponds to the bin index of the prefix bit string, and the number denotes a context index to be used in a location of the corresponding bit. For convenience of description, for example, in a 4×4 block, the prefix bit string is comprised of a total of four bits, and when k is 0, 1, 2, and 3 according to the context mapping table, the context indexes 0, 1, 2, and 2 are determined for a k-th bin index, and thus arithmetic encoding based on the context modeling may be performed.

FIG. 4 shows an exemplary embodiment in which an intra prediction mode includes a luma intra mode and a chroma intra mode indicating an intra prediction direction of a luma block and a chroma block, respectively. When the intra prediction mode is 6, a symbol bit string **40** '0000001' is generated according to a unary binarization method. In this case, arithmetic encoding may be performed on a first bit **41** '0' of the symbol bit string **40** of the intra prediction mode, through context modeling, and arithmetic encoding may be performed on the rest of bits **45** '000001' of the symbol bit string **40**, in a bypass mode. In other words, the first bit **41** of the symbol bit string **40** corresponds to a prefix bit string, and the rest of bits **45** of the symbol bit string **40** correspond to a suffix bit string.

How many bits of the symbol bit string **40** are encoded in arithmetic encoding as the prefix bit string through the context modeling and how many bits of the symbol bit string **40** are encoded in arithmetic encoding as the suffix bit string in the bypass mode may be determined according to a size of a block or a size of a set of blocks. For example, regarding a 64×64 block, arithmetic encoding may be performed only on a first bit from among bit strings of an intra prediction mode, and arithmetic encoding may be performed on the rest of bits in a bypass mode. Regarding blocks having other

12

sizes, arithmetic encoding may be performed on all bits of the bit strings of the intra prediction mode in the bypass mode.

In general, information about bits close to a least significant bit (LSB) is relatively less important than information about bits close to a most significant bit (MSB) of a symbol bit string. Accordingly, the video encoding apparatus **10** and the video decoding apparatus **20** may select an arithmetic encoding method according to a binarization method having a relatively high accuracy with respect to the prefix bit string close to the MSB even though there is a burden of an operation amount, and may select an arithmetic encoding method according to a binarization method capable of performing a simple operation with respect to the suffix bit string close to the LSB. Also, the video encoding apparatus **10** and the video decoding apparatus **20** may select an arithmetic encoding method based on context modeling with respect to the prefix bit string and may select an arithmetic encoding method, not performing context modeling, with respect to the suffix bit string close to the LSB.

In the above description, the exemplary embodiment in which binarization is performed on the prefix bit string and the suffix bit string of the final coefficient position information of the transformation coefficient by using different methods has been described with reference to FIG. 3. Also, the exemplary embodiment in which arithmetic encoding is performed on the prefix bit string and the suffix bit string from among the bit strings of the intra prediction mode by using different methods has been described with reference to FIG. 4.

However, according to various exemplary embodiments, a symbol encoding method in which binarization and arithmetic encoding methods individually determined for the prefix bit string and the suffix bit string are used or different binarization and arithmetic encoding methods are used is not limited to the exemplary embodiments described with reference to FIGS. 3 and 4, and various binarization and arithmetic encoding methods may be used for various symbols.

FIG. 5 is a flowchart for describing a video encoding method, according to an exemplary embodiment.

In operation **51**, symbols are generated by performing prediction and transformation on image blocks.

In operation **53**, a current symbol is classified into a prefix region and a suffix region based on a threshold value determined according to a size of a current block.

In operation **55**, a prefix bit string and a suffix bit string are generated by using binarization methods individually determined for the prefix region and the suffix region of the symbol.

In operation **57**, symbol encoding is performed by using arithmetic encoding methods individually determined for the prefix bit string and the suffix bit string.

In operation **59**, bit strings generated through the symbol encoding are output in the form of bitstreams.

In operation **57**, the symbol encoding may be performed on the prefix bit string by using an arithmetic encoding method for performing context modeling according to locations of bits, and the symbol encoding may also be performed on the suffix bit string by using an arithmetic encoding method for omitting the context modeling in a bypass mode.

In operation **57**, when the symbol is final coefficient position information of a transformation coefficient, the arithmetic encoding may be performed by using a context of a predetermined index that is previously allocated to the locations of the bits of the prefix bit string.

13

FIG. 6 is a flowchart for describing a video decoding method, according to an exemplary embodiment.

In operation **61**, symbols of image blocks are parsed from a received bitstream.

In operation **63**, a current symbol is classified into a prefix bit string and a suffix bit string based on a threshold value determined according to a size of a current block.

In operation **65**, arithmetic decoding is performed by using an arithmetic decoding method determined for each of the prefix bit string and the suffix bit string of the current symbol.

In operation **67**, after the arithmetic decoding, inverse binarization is performed by using a binarization method determined for each of the prefix bit string and the suffix bit string.

The prefix region and the suffix region of the symbol may be restored by performing the inverse binarization by using the binarization method determined for each of the prefix bit string and the suffix bit string.

In operation **69**, the image blocks may be restored by performing inverse transformation and prediction on the current block by using the current symbol restored through the arithmetic decoding and the inverse binarization.

In operation **65**, the arithmetic decoding for determining the context modeling according to the locations of the bits may be performed on the prefix bit string, and the arithmetic decoding for omitting the context modeling may be performed on the suffix bit string in a bypass mode.

In operation **65**, when the symbol is the final coefficient position information of the transformation coefficient, the arithmetic decoding may be performed by using the context of the predetermined index that is previously allocated to the locations of the bits of the prefix bit string.

In the video encoding apparatus **10** according to an exemplary embodiment and the video decoding apparatus **20** according to another exemplary embodiment, blocks in which video data is split are split into coding units having a tree structure, prediction units are used to perform intra prediction on the coding units, and a transformation unit is used to transform the coding units.

Hereinafter, a method and apparatus for encoding a video and a method and apparatus for decoding a video based on a coding unit having a tree structure, a prediction unit, and a transformation unit will be described.

FIG. 7 is a block diagram of a video encoding apparatus **100** based on coding units having a tree structure, according to an exemplary embodiment.

The video encoding apparatus **100** involving video prediction based on the coding unit having a tree structure includes a maximum coding unit splitter **110**, a coding unit determiner **120**, and an output unit **130** (e.g., outputter). For convenience of description, the video encoding apparatus **100** involving video prediction based on the coding unit having a tree structure will be referred to as a video encoding apparatus **100**.

The maximum coding unit splitter **110** may split a current picture based on a maximum coding unit for the current picture of an image. If the current picture is larger than the maximum coding unit, image data of the current picture may be split into the at least one maximum coding unit. The maximum coding unit according to an exemplary embodiment may be a data unit having a size of 32×32, 64×64, 128×128, 256×256, etc., wherein a shape of the data unit is a square having a width and length in squares of 2. The image data may be output to the coding unit determiner **120** according to the at least one maximum coding unit.

14

A coding unit according to an exemplary embodiment may be characterized by a maximum size and a depth. The depth denotes a number of times the coding unit is spatially split from the maximum coding unit, and as the depth deepens, deeper coding units according to depths may be split from the maximum coding unit to a minimum coding unit. A depth of the maximum coding unit is an uppermost depth and a depth of the minimum coding unit is a lowermost depth. Since a size of a coding unit corresponding to each depth decreases as the depth of the maximum coding unit deepens, a coding unit corresponding to an upper depth may include a plurality of coding units corresponding to lower depths.

As described above, the image data of the current picture is split into the maximum coding units according to a maximum size of the coding unit, and each of the maximum coding units may include deeper coding units that are split according to depths. Since the maximum coding unit according to an exemplary embodiment is split according to depths, the image data of a spatial domain included in the maximum coding unit may be hierarchically classified according to depths.

A maximum depth and a maximum size of a coding unit, which limit the total number of times a height and a width of the maximum coding unit are hierarchically split, may be predetermined.

The coding unit determiner **120** encodes at least one split region obtained by splitting a region of the maximum coding unit according to depths, and determines a depth to output finally encoded image data according to the at least one split region. In other words, the coding unit determiner **120** determines a coded depth by encoding the image data in the deeper coding units according to depths, according to the maximum coding unit of the current picture, and selecting a depth having the least encoding error. The determined coded depth and the encoded image data according to the determined coded depth are output to the output unit **130**.

The image data in the maximum coding unit is encoded based on the deeper coding units corresponding to at least one depth equal to or below the maximum depth, and results of encoding the image data are compared based on each of the deeper coding units. A depth having the least encoding error may be selected after comparing encoding errors of the deeper coding units. At least one coded depth may be selected for each maximum coding unit.

The size of the maximum coding unit is split as a coding unit is hierarchically split according to depths, and as the number of coding units increases. Also, even if coding units correspond to a same depth in one maximum coding unit, it is determined whether to split each of the coding units corresponding to the same depth to a lower depth by measuring an encoding error of the image data of the each coding unit, separately. Accordingly, even when image data is included in one maximum coding unit, the image data is split into regions according to the depths and the encoding errors may differ according to regions in the one maximum coding unit, and thus the coded depths may differ according to the regions in the image data. Thus, one or more coded depths may be determined in one maximum coding unit, and the image data of the maximum coding unit may be divided according to coding units of at least one coded depth.

Accordingly, the coding unit determiner **120** may determine coding units having a tree structure included in the maximum coding unit. The 'coding units having a tree structure' according to an exemplary embodiment include coding units corresponding to a depth determined to be the coded depth, from among all deeper coding units included in

the maximum coding unit. A coding unit of a coded depth may be hierarchically determined according to depths in the same region of the maximum coding unit, and may be independently determined in different regions. Similarly, a coded depth in a current region may be independently determined from a coded depth in another region.

A maximum depth according to an exemplary embodiment is an index related to the number of times splitting is performed from a maximum coding unit to a minimum coding unit. A first maximum depth according to an exemplary embodiment may denote the total number of times splitting is performed from the maximum coding unit to the minimum coding unit. A second maximum depth according to an exemplary embodiment may denote the total number of depth levels from the maximum coding unit to the minimum coding unit. For example, when a depth of the maximum coding unit is 0, a depth of a coding unit, in which the maximum coding unit is split once, may be set to 1, and a depth of a coding unit, in which the maximum coding unit is split twice, may be set to 2. Here, if the minimum coding unit is a coding unit in which the maximum coding unit is split four times, 5 depth levels of depths 0, 1, 2, 3 and 4 exist, and thus the first maximum depth may be set to 4, and the second maximum depth may be set to 5.

Prediction encoding and transformation may be performed according to the maximum coding unit. The prediction encoding and the transformation are also performed based on the deeper coding units according to a depth equal to or depths less than the maximum depth, according to the maximum coding unit.

Since the number of deeper coding units increases whenever the maximum coding unit is split according to depths, encoding including the prediction encoding and the transformation is performed on all of the deeper coding units which are generated as the depth deepens. For convenience of description, the prediction encoding and the transformation will now be described based on a coding unit of a current depth, in a maximum coding unit.

The video encoding apparatus **100** may variously select a size or shape of a data unit for encoding the image data. In order to encode the image data, operations, such as prediction encoding, transformation, and entropy encoding, are performed, and at this time, the same data unit may be used for all operations or different data units may be used for each operation.

For example, the video encoding apparatus **100** may select not only a coding unit for encoding the image data, but also a data unit different from the coding unit so as to perform the prediction encoding on the image data in the coding unit.

In order to perform prediction encoding in the maximum coding unit, the prediction encoding may be performed based on a coding unit corresponding to a coded depth, e.g., based on a coding unit that is no longer split to coding units corresponding to a lower depth. Hereinafter, the coding unit that is no longer split and becomes a basis unit for prediction encoding will now be referred to as a 'prediction unit'. A partition obtained by splitting the prediction unit may include a prediction unit or a data unit obtained by splitting at least one of a height and a width of the prediction unit. A partition is a data unit having a shape in which the prediction unit of the coding unit is divided, and the prediction unit may be a partition having the same size as the coding unit.

For example, when a coding unit of $2N \times 2N$ (where N is a positive integer) is no longer split and becomes a prediction unit of $2N \times 2N$, a size of a partition may be $2N \times 2N$, $2N \times N$, $N \times 2N$, or $N \times N$. Examples of a partition type include

symmetrical partitions that are obtained by symmetrically splitting a height or width of the prediction unit, partitions obtained by asymmetrically splitting the height or width of the prediction unit, such as 1:n or n:1, partitions that are obtained by geometrically splitting the prediction unit, and partitions having arbitrary shapes.

A prediction mode of the prediction unit may be at least one of an intra mode, an inter mode, and a skip mode. For example, the intra mode or the inter mode may be performed on the partition of $2N \times 2N$, $2N \times N$, $N \times 2N$, or $N \times N$. Also, the skip mode may be performed only on the partition of $2N \times 2N$. The encoding is independently performed on one prediction unit in a coding unit, thereby selecting a prediction mode having a smallest encoding error.

The video encoding apparatus **100** may also perform the transformation on the image data in a coding unit based not only on the coding unit for encoding the image data, but also based on a data unit that is different from the coding unit. In order to perform the transformation in the coding unit, the transformation may be performed based on a transformation unit having a size smaller than or equal to the coding unit. For example, the transformation unit may include a transformation unit for an intra mode and a transformation unit for an inter mode.

Similarly to the coding unit, the transformation unit in the coding unit may be recursively split into smaller sized regions. Thus, residual data in the coding unit may be divided according to the transformation having a tree structure according to transformation depths.

A transformation depth indicating the number of times splitting is performed to reach the transformation unit by splitting the height and width of the coding unit may also be set in the transformation unit. For example, in a current coding unit of $2N \times 2N$, a transformation depth may be 0 when the size of a transformation unit is also $2N \times 2N$, may be 1 when the transformation unit size is $N \times N$, and may be 2 when the transformation unit size is $N/2 \times N/2$. In other words, the transformation unit having a tree structure may be set according to transformation depths.

Encoding information according to coding units corresponding to a coded depth requires not only information about the coded depth, but also information related to prediction encoding and transformation. Accordingly, the coding unit determiner **120** not only determines a coded depth having a smallest encoding error, but also determines a partition type in a prediction unit, a prediction mode according to prediction units, and a size of a transformation unit for transformation.

Coding units according to a tree structure in a maximum coding unit and a method of determining a prediction unit and partition and a transformation unit, according to exemplary embodiments, will be described in detail later with reference to FIGS. 7 through 19.

The coding unit determiner **120** may measure an encoding error of deeper coding units according to depths by using Rate-Distortion Optimization based on Lagrangian multipliers.

The output unit **130** outputs the image data of the maximum coding unit, which is encoded based on the at least one coded depth determined by the coding unit determiner **120**, and information about the encoding mode according to the coded depth, in bitstreams.

The encoded image data may be obtained by encoding residual data of an image.

The information about the encoding mode according to coded depth may include information about the coded depth,

the partition type in the prediction unit, the prediction mode, and the size of the transformation unit.

The information about the coded depth may be defined by using split information according to depths, which indicates whether encoding is performed on coding units of a lower depth instead of a current depth. If the current depth of the current coding unit is the coded depth, image data in the current coding unit is encoded and output, and thus the split information may be defined not to split the current coding unit to a lower depth. Alternatively, if the current depth of the current coding unit is not the coded depth, the encoding is performed on the coding unit of the lower depth, and thus the split information may be defined to split the current coding unit to obtain the coding units of the lower depth.

If the current depth is not the coded depth, encoding is performed on the coding unit that is split into the coding unit of the lower depth. Since at least one coding unit of the lower depth exists in one coding unit of the current depth, the encoding is repeatedly performed on each coding unit of the lower depth, and thus the encoding may be recursively performed for the coding units having the same depth.

Since the coding units having a tree structure are determined for one maximum coding unit, and information about at least one encoding mode is determined for a coding unit of a coded depth, information about at least one encoding mode may be determined for one maximum coding unit. Also, a coded depth of the image data of the maximum coding unit may be different according to locations since the image data is hierarchically split according to depths, and thus information about the coded depth and the encoding mode may be set for the image data.

Accordingly, the output unit **130** may assign encoding information about a corresponding coded depth and an encoding mode to at least one of the coding unit, the prediction unit, and a minimum unit included in the maximum coding unit.

The minimum unit according to an exemplary embodiment is a rectangular data unit obtained by splitting the minimum coding unit constituting the lowermost depth by 4. Alternatively, the minimum unit may be a maximum rectangular data unit that may be included in all of the coding units, prediction units, partition units, and transformation units included in the maximum coding unit.

For example, the encoding information output through the output unit **130** may be classified into encoding information according to coding units, and encoding information according to prediction units. The encoding information according to the coding units may include the information about the prediction mode and information about the size of the partitions. The encoding information according to the prediction units may include information about an estimated direction of an inter mode, information about a reference image index of the inter mode, information about a motion vector, information about a chroma component of an intra mode, and information about an interpolation method of the intra mode. Also, information about a maximum size of the coding unit defined according to pictures, slices, or groups of pictures (GOPs), and information about a maximum depth may be inserted into a sequence parameter set (SPS) or a picture parameter set (PPS).

Also, information about the maximum size of the transformation unit allowed for the current video and information about the minimum size of the transformation unit may be output via a header of a bitstream, an SPS, or a PPS. The output unit **130** may encode and output reference information, single-direction prediction information, slice type

information including a fourth slice type, etc. related to the prediction described above with reference to FIGS. **1** to **6**.

In the video encoding apparatus **100**, the deeper coding unit may be a coding unit obtained by dividing a height or width of a coding unit of an upper depth, which is one layer above, by two. In other words, when the size of the coding unit of the current depth is $2N \times 2N$, the size of the coding unit of the lower depth is $N \times N$. Also, the coding unit of the current depth having the size of $2N \times 2N$ may include at most 4 coding units of the lower depth.

Accordingly, the video encoding apparatus **100** may form the coding units having the tree structure by determining coding units having an optimum shape and an optimum size for each maximum coding unit, based on the size of the maximum coding unit and the maximum depth determined considering characteristics of the current picture. Also, since encoding may be performed on each maximum coding unit by using any one of various prediction modes and transformations, an optimum encoding mode may be determined considering characteristics of the coding unit of various image sizes.

Thus, if an image having high resolution or a large data amount is encoded in a conventional macroblock, a number of macroblocks per picture excessively increases. Accordingly, a number of pieces of compressed information generated for each macroblock increases, and thus it is difficult to transmit the compressed information and data compression efficiency decreases. However, by using the video encoding apparatus **100**, image compression efficiency may be increased since a coding unit is adjusted while considering characteristics of an image while increasing a maximum size of a coding unit considering a size of the image.

The video encoding apparatus **100** of FIG. **7** may perform operations of the video encoding apparatus **10** described with reference to FIG. **1**.

The coding unit determiner **120** may perform operations of the image encoder **12** of the video encoding apparatus **10**. The coding unit determiner **120** may determine a prediction unit for intra prediction according to coding units having a tree structure for each maximum coding unit, perform the intra prediction in each prediction unit, determine a transformation unit for transformation, and perform transformation in each transformation unit.

The output unit **130** may perform operations of a symbol encoding unit **14** and a bitstream output unit **16** of the video encoding apparatus **10**. Symbols for various data units, such as a picture, a slice, a maximum coding unit, a coding unit, a prediction unit, and a transformation unit, are generated, and each of the symbols is classified into a prefix region and a suffix region according to a threshold value determined based on a size of the corresponding data unit. The output unit **130** may generate a prefix bit string and a suffix bit string by using a binarization method determined for each of the prefix region and the suffix region of the symbol. Any one of a general binarization, a unary binarization, a truncated unary binarization, an exponential golomb binarization, and a fixed length binarization is selected to binarize the prefix region and the suffix region, thereby generating the prefix bit string and the suffix bit string.

The output unit **130** may perform symbol encoding by performing arithmetic encoding determined for each of the prefix bit string and the suffix bit string. The output unit **130** may perform symbol encoding by performing arithmetic encoding for performing context modeling according to locations of bits on the prefix bit string and by performing arithmetic encoding for omitting context modeling on the suffix bit string in a bypass mode.

For example, when final coefficient position information of a transformation coefficient of the transformation unit is encoded, the threshold value for classifying the prefix bit string and the suffix bit string may be determined according to a size (width or height) of the transformation unit. Alternatively, the threshold value may be determined according to sizes of a slice including the current transformation unit, a maximum coding unit, a coding unit, a prediction unit, etc.

Alternatively, it may be determined by a maximum index of an intra prediction mode how many bits of a symbol bit string are encoded in arithmetic encoding as the prefix bit string through context modeling in the intra prediction mode and how many bits of the symbol bit string are encoded in arithmetic encoding as the suffix bit string in a bypass mode. For example, a total of 34 intra prediction modes may be used for prediction units having sizes of 8×8, 16×16, and 32×32, a total of 17 intra prediction modes may be used for a prediction unit having a size of 4×4, and a total of another number of intra prediction modes may be used for a prediction unit having a size of 64×64. In this case, since the prediction units capable of using the same number of intra prediction modes are regarded as having similar statistical characteristics, a first bit from among bit strings in the intra prediction mode may be encoded through the context modeling for arithmetic encoding with respect to the prediction units having sizes of 8×8, 16×16, and 32×32. Also, all bits from among the bit strings in the intra prediction mode may be encoded in the bypass mode for arithmetic encoding with respect to the rest of the prediction units, that is, the prediction units having sizes of 4×4 and 64×64.

The output unit **130** may output the bit strings generated through the symbol encoding in the form of bitstreams.

FIG. **8** is a block diagram of a video decoding apparatus **200** based on a coding unit having a tree structure, according to an exemplary embodiment.

The video decoding apparatus **200** performing video prediction based on the coding unit having a tree structure includes a receiver **210**, an image data and encoding information extractor **220**, and an image data decoder **230**.

Definitions of various terms, such as a coding unit, a depth, a prediction unit, a transformation unit, and information about various encoding modes, for various operations of the video decoding apparatus **200**, may be identical to those described with reference to FIG. **7** and the video encoding apparatus **100**.

The receiver **210** receives and parses a bitstream of an encoded video. The image data and encoding information extractor **220** extracts encoded image data for each coding unit from the parsed bitstream, wherein the coding units have a tree structure according to each maximum coding unit, and outputs the extracted image data to the image data decoder **230**. The image data and encoding information extractor **220** may extract information about a maximum size of a coding unit of a current picture from various sources, for example, a header of the current picture, an SPS, or a PPS.

Also, the image data and encoding information extractor **220** extracts information about a coded depth and an encoding mode for the coding units having a tree structure according to each maximum coding unit, from the parsed bitstream. The extracted information about the coded depth and the encoding mode is output to the image data decoder **230**. In other words, the image data in a bit string is split into the maximum coding unit so that the image data decoder **230** decodes the image data for each maximum coding unit.

The information about the coded depth and the encoding mode according to the maximum coding unit may be set for information about at least one coding unit corresponding to the coded depth, and information about an encoding mode may include information about a partition type of a corresponding coding unit corresponding to the coded depth, a prediction mode, and a size of a transformation unit. Also, splitting information according to depths may be extracted as the information about the coded depth.

The information about the coded depth and the encoding mode according to each maximum coding unit extracted by the image data and encoding information extractor **220** is information about a coded depth and an encoding mode determined to generate a minimum encoding error when an encoder, such as the video encoding apparatus **100**, repeatedly performs encoding for each deeper coding unit according to depths according to each maximum coding unit. Accordingly, the video decoding apparatus **200** may restore an image by decoding the image data according to a coded depth and an encoding mode that generates the minimum encoding error.

Since encoding information about the coded depth and the encoding mode may be assigned to a predetermined data unit from among a corresponding coding unit, a prediction unit, and a minimum unit, the image data and encoding information extractor **220** may extract the information about the coded depth and the encoding mode according to the predetermined data units. The predetermined data units to which the same information about the coded depth and the encoding mode is assigned may be inferred to be the data units included in the same maximum coding unit.

The image data decoder **230** restores the current picture by decoding the image data in each maximum coding unit based on the information about the coded depth and the encoding mode according to the maximum coding units. In other words, the image data decoder **230** may decode the encoded image data based on the extracted information about the partition type, the prediction mode, and the transformation unit for each coding unit from among the coding units having the tree structure included in each maximum coding unit. A decoding process may include prediction including intra prediction and motion compensation, and inverse transformation.

The image data decoder **230** may perform intra prediction or motion compensation according to a partition and a prediction mode of each coding unit, based on the information about the partition type and the prediction mode of the prediction unit of the coding unit according to coded depths.

Also, the image data decoder **230** may perform inverse transformation according to each transformation unit in the coding unit, based on the information about the transformation unit according to the coding units having a tree structure, so as to perform the inverse transformation according to maximum coding units. A pixel value of a spatial domain in the coding unit may be restored through the inverse transformation.

The image data decoder **230** may determine at least one coded depth of a current maximum coding unit by using split information according to depths. If the split information indicates that image data is no longer split in the current depth, the current depth is a coded depth. Accordingly, the image data decoder **230** may decode encoded data of at least one coding unit corresponding to each coded depth in the current maximum coding unit by using the information about the partition type of the prediction unit, the prediction mode, and the transformation unit size for each coding unit

21

corresponding to the coded depth, and output the image data of the current maximum coding unit.

In other words, data units containing the encoding information including the same split information may be gathered by observing the encoding information set assigned for the predetermined data unit from among the coding unit, the prediction unit, and the minimum unit, and the gathered data units may be considered to be one data unit to be decoded by the image data decoder **230** in the same encoding mode. Decoding of the current coding unit may be performed by obtaining information about the encoding mode for each coding unit determined in such a manner.

Also, the video decoding apparatus **200** of FIG. **8** may perform operations of the video decoding apparatus **20** described above with reference to FIG. **2**.

The receiver **210** and the image data and encoding information extractor **220** may perform operations of the parser **22** and the symbol decoder **24** of the video decoding apparatus **20**. The image data decoder **230** may perform operations of the symbol decoder **24** of the video decoding apparatus **20**.

The receiver **210** receives a bitstream of an image, and the image data and encoding information extractor **220** parses symbols of image blocks from the received bitstream.

The image data and encoding information extractor **220** may classify a current symbol into a prefix bit string and a suffix bit string based on a threshold value determined according to a size of a current block. For example, when the final coefficient position information of the transformation coefficient of the transformation unit is decoded, the threshold value for classifying the prefix bit string and the suffix bit string may be determined according to a size (width or height) of the transformation unit. Alternatively, the threshold value may be determined according to sizes of the slice including the current transformation unit, the maximum coding unit, the coding unit, the prediction unit, etc. Alternatively, it may be determined by the maximum index of the intra prediction mode how many bits of the symbol bit string are encoded in arithmetic encoding as the prefix bit string through context modeling in the intra prediction mode and how many bits of the symbol bit string are encoded in arithmetic encoding as the suffix bit string in the bypass mode.

Arithmetic decoding is performed by using an arithmetic decoding method determined for each of the prefix bit string and the suffix bit string of the current symbol. Arithmetic decoding for determining the context modeling according to bit positions may be performed on the prefix bit string, and arithmetic decoding for omitting the context modeling may be performed on the suffix bit string by using the bypass mode.

After the arithmetic decoding, inverse binarization is performed according to a binarization method determined for each of the prefix bit string and the suffix bit string. The prefix region and the suffix region of the symbol may be restored by performing the inverse binarization according to the binarization method determined for each of the prefix bit string and the suffix bit string.

The image data decoder **230** may restore image blocks by performing inverse transformation and prediction on the current block by using the current symbol restored through the arithmetic decoding and the inverse binarization.

Consequently, the video decoding apparatus **200** may obtain information about at least one coding unit that generates the minimum encoding error when encoding is recursively performed for each maximum coding unit, and may use the information to decode the current picture. In

22

other words, the coding units having the tree structure determined to be the optimum coding units in each maximum coding unit may be decoded.

Accordingly, even if image data has high resolution and a large amount of data, the image data may be efficiently decoded and restored by using a size of a coding unit and an encoding mode, which are adaptively determined according to characteristics of the image data, by using information about an optimum encoding mode received from an encoder.

FIG. **9** is a conceptual diagram of coding units, according to an exemplary embodiment.

A size of a coding unit may be expressed in width×height, and may be 64×64, 32×32, 16×16, and 8×8. A coding unit of 64×64 may be split into partitions of 64×64, 64×32, 32×64, or 32×32, a coding unit of 32×32 may be split into partitions of 32×32, 32×16, 16×32, or 16×16, a coding unit of 16×16 may be split into partitions of 16×16, 16×8, 8×16, or 8×8, and a coding unit of 8×8 may be split into partitions of 8×8, 8×4, 4×8, or 4×4.

In video data **310**, a resolution is 1920×1080, a maximum size of a coding unit is 64, and a maximum depth is 2. In video data **320**, a resolution is 1920×1080, a maximum size of a coding unit is 64, and a maximum depth is 3. In video data **330**, a resolution is 352×288, a maximum size of a coding unit is 16, and a maximum depth is 1. The maximum depth shown in FIG. **9** denotes a total number of splits from a maximum coding unit to a minimum decoding unit.

If a resolution is high or a data amount is large, a maximum size of a coding unit may be large so as to not only increase encoding efficiency but also to accurately reflect characteristics of an image. Accordingly, the maximum size of the coding unit of the video data **310** and **320** having a higher resolution than the video data **330** may be 64.

Since the maximum depth of the video data **310** is 2, coding units **315** of the video data **310** may include a maximum coding unit having a long axis size of 64, and coding units having long axis sizes of 32 and 16 since depths are deepened to two layers by splitting the maximum coding unit twice. Meanwhile, since the maximum depth of the video data **330** is 1, coding units **335** of the video data **330** may include a maximum coding unit having a long axis size of 16, and coding units having a long axis size of 8 since depths are deepened to one layer by splitting the maximum coding unit once.

Since the maximum depth of the video data **320** is 3, coding units **325** of the video data **320** may include a maximum coding unit having a long axis size of 64, and coding units having long axis sizes of 32, 16, and 8 since the depths are deepened to 3 layers by splitting the maximum coding unit three times. As a depth deepens, detailed information may be more precisely expressed.

FIG. **10** is a block diagram of an image encoder **400** based on coding units, according to an exemplary embodiment.

The image encoder **400** performs operations of the coding unit determiner **120** of the video encoding apparatus **100** to encode image data. In other words, an intra predictor **410** performs intra prediction on coding units in an intra mode, from among a current frame **405**, and a motion estimator **420** and a motion compensator **425** perform inter estimation and motion compensation on coding units in an inter mode from among the current frame **405** by using the current frame **405**, and a reference frame **495**.

Data output from the intra predictor **410**, the motion estimator **420**, and the motion compensator **425** is output as a quantized transformation coefficient through a transformer **430** and a quantizer **440**. The quantized transformation coefficient is restored as data in a spatial domain through an

inverse quantizer **460** and an inverse transformer **470**, and the restored data in the spatial domain is output as the reference frame **495** after being post-processed through a deblocking unit **480** (e.g., deblocker) and a loop filtering unit **490** (e.g., loop filter). The quantized transformation coefficient may be output as a bitstream **455** through an entropy encoder **450**.

In order for the image encoder **400** to be implemented in the video encoding apparatus **100**, each of the elements of the image encoder **400**, e.g., the intra predictor **410**, the motion estimator **420**, the motion compensator **425**, the transformer **430**, the quantizer **440**, the entropy encoder **450**, the inverse quantizer **460**, the inverse transformer **470**, the deblocking unit **480**, and the loop filtering unit **490** perform operations based on each coding unit from among coding units having a tree structure while considering the maximum depth of each maximum coding unit.

Specifically, the intra predictor **410**, the motion estimator **420**, and the motion compensator **425** determine partitions and a prediction mode of each coding unit from among the coding units having a tree structure while considering the maximum size and the maximum depth of a current maximum coding unit, and the transformer **430** determines the transformation unit size in each coding unit from among the coding units having a tree structure.

In particular, the entropy encoder **450** may perform symbol encoding on the prefix region and the suffix region by classifying a symbol into the prefix region and the suffix region according to a predetermined threshold value and using different binarization and arithmetic encoding methods with respect to the prefix region and the suffix region.

The threshold value for classifying the symbol into the prefix region and the suffix region may be determined based on sizes of data units of the symbol, for example, a slice, a maximum coding unit, a coding unit, a prediction unit, a transformation unit, etc.

FIG. **11** is a block diagram of an image decoder **500** based on coding units, according to an exemplary embodiment.

A parser **510** parses encoded image data to be decoded and information about encoding required for decoding from a bitstream **505**. The encoded image data is output as inverse quantized data through an entropy decoder **520** and an inverse quantizer **530**, and the inverse quantized data is restored to image data in a spatial domain through an inverse transformer **540**.

An intra predictor **550** performs intra prediction on coding units in an intra mode with respect to the image data in the spatial domain, and a motion compensator **560** performs motion compensation on coding units in an inter mode by using a reference frame **585**.

The image data in the spatial domain, which passed through the intra predictor **550** and the motion compensator **560**, may be output as a restored frame **595** after being post-processed through a deblocking unit **570** (e.g., deblocker) and a loop filtering unit **580** (e.g., loop filter). Also, the image data that is post-processed through the deblocking unit **570** and the loop filtering unit **580** may be output as the reference frame **585**.

In order to decode the image data in the image data decoder **230** of the video decoding apparatus **200**, the image decoder **500** may perform operations that are performed after the parsing performed by the parser **510**.

In order for the image decoder **500** to be implemented in the video decoding apparatus **200**, each of the elements of the image decoder **500**, e.g., the parser **510**, the entropy decoder **520**, the inverse quantizer **530**, the inverse transformer **540**, the intra predictor **550**, the motion compensator

560, the deblocking unit **570**, and the loop filtering unit **580** perform operations based on coding units having a tree structure for each maximum coding unit.

Specifically, the intra predictor **550** and the motion compensator **560** perform operations based on partitions and a prediction mode for each of the coding units having a tree structure, and the inverse transformer **540** perform operations based on a size of a transformation unit for each coding unit.

In particular, the entropy decoder **520** may perform symbol decoding for each of a prefix bit string and a suffix bit string by classifying the parsed symbol bit string into the prefix bit string and the suffix bit string according to a predetermined threshold value and using different binarization and arithmetic decoding methods with respect to the prefix bit string and the suffix bit string.

The threshold value for classifying the symbol bit string into the prefix bit string and the suffix bit string may be determined based on sizes of data units of the symbol, for example, a slice, a maximum coding unit, a coding unit, a prediction unit, a transformation unit, etc.

FIG. **12** is a diagram showing deeper coding units according to depths and partitions, according to an exemplary embodiment.

The video encoding apparatus **100** and the video decoding apparatus **200** use hierarchical coding units so as to consider characteristics of an image. A maximum height, a maximum width, and a maximum depth of coding units may be adaptively determined according to the characteristics of the image, or may be differently set by a user. Sizes of deeper coding units according to depths may be determined according to the predetermined maximum size of the coding unit.

In a hierarchical structure **600** of coding units, according to an exemplary embodiment, the maximum height and the maximum width of the coding units are each 64, and the maximum depth is 3. Here, the maximum depth denotes a total number of times splitting is performed from the maximum coding unit to the minimum coding unit. Since a depth deepens along a vertical axis of the hierarchical structure **600**, a height and a width of the deeper coding units are each split. Also, a prediction unit and partitions, which are bases for prediction encoding of each deeper coding unit, are shown along a horizontal axis of the hierarchical structure **600**.

In other words, a coding unit **610** is a maximum coding unit in the hierarchical structure **600**, wherein a depth is 0 and a size, e.g., a height by width, is 64×64. The depth deepens along the vertical axis, and a coding unit **620** having a size of 32×32 and a depth of 1, a coding unit **630** having a size of 16×16 and a depth of 2, and a coding unit **640** having a size of 8×8 and a depth of 3 are provided. A coding unit **640** having the size of 8×8 and the depth of 3 is a minimum coding unit.

The prediction unit and the partitions of a coding unit are arranged along the horizontal axis according to each depth. In other words, if the coding unit **610** having the size of 64×64 and the depth of 0 is a prediction unit, the prediction unit may be split into partitions included in the encoding unit **610**, e.g., a partition **610** having a size of 64×64, partitions **612** having the size of 64×32, partitions **614** having the size of 32×64, or partitions **616** having the size of 32×32.

Similarly, a prediction unit of the coding unit **620** having the size of 32×32 and the depth of 1 may be split into partitions included in the coding unit **620**, e.g., a partition **620** having a size of 32×32, partitions **622** having a size of 32×16, partitions **624** having a size of 16×32, and partitions **626** having a size of 16×16.

Similarly, a prediction unit of the coding unit **630** having the size of 16×16 and the depth of 2 may be split into partitions included in the coding unit **630**, e.g., a partition having a size of 16×16 included in the coding unit **630**, partitions **632** having a size of 16×8 , partitions **634** having a size of 8×16 , and partitions **636** having a size of 8×8 .

Similarly, a prediction unit of the coding unit **640** having the size of 8×8 and the depth of 3 may be split into partitions included in the coding unit **640**, e.g., a partition having a size of 8×8 included in the coding unit **640**, partitions **642** having a size of 8×4 , partitions **644** having a size of 4×8 , and partitions **646** having a size of 4×4 .

In order to determine the at least one coded depth of the coding units constituting the maximum coding unit **610**, the coding unit determiner **120** of the video encoding apparatus **100** performs encoding for coding units corresponding to each depth included in the maximum coding unit **610**.

A number of deeper coding units classified according to depths including data in the same range and the same size increases as the depth deepens. For example, four coding units corresponding to a depth of 2 are required to cover data that is included in one coding unit corresponding to a depth of 1. Accordingly, in order to compare encoding results of the same data according to depths, the coding unit corresponding to the depth of 1 and four coding units corresponding to the depth of 2 are each encoded.

In order to perform encoding for a current depth from among the depths, a minimum encoding error may be selected for the current depth by performing encoding for each prediction unit in the coding units corresponding to the current depth, along the horizontal axis of the hierarchical structure **600**. Alternatively, the minimum encoding error may be searched for by comparing the smallest encoding errors according to depths, by performing encoding for each depth as the depth deepens along the vertical axis of the hierarchical structure **600**. A depth and a partition having the minimum encoding error in the coding unit **610** may be selected as the coded depth and a partition type of the coding unit **610**.

FIG. **13** is a diagram for describing a relationship between a coding unit and transformation units, according to an exemplary embodiment.

The video encoding or decoding apparatus (e.g., **100** or **200**) encodes or decodes an image according to coding units having sizes smaller than or equal to a maximum coding unit for each maximum coding unit. Sizes of transformation units for transformation during encoding may be selected based on data units that are not larger than a corresponding coding unit.

For example, in the video encoding or decoding apparatus (e.g., **100** or **200**), if a size of the coding unit **710** is 64×64 , transformation may be performed by using the transformation units **720** having a size of 32×32 .

Also, data of the coding unit **710** having the size of 64×64 may be encoded by performing the transformation on each of the transformation units having the size of 32×32 , 16×16 , 8×8 , and 4×4 , which are smaller than 64×64 , and then a transformation unit having the least coding error may be selected.

FIG. **14** is a diagram for describing encoding information of coding units according to depths, according to an exemplary embodiment.

The output unit **130** of the video encoding apparatus **100** may encode and transmit information **800** about a partition type, information **810** about a prediction mode, and infor-

mation **820** about a size of a transformation unit for each coding unit corresponding to a coded depth, as information about an encoding mode.

The information **800** indicates information about a shape of a partition obtained by splitting a prediction unit of a current coding unit, wherein the partition is a data unit for prediction encoding the current coding unit. For example, a current coding unit **CU_0** having a size of $2N \times 2N$ may be split into any one of a partition **802** having a size of $2N \times 2N$, a partition **804** having a size of $2N \times N$, a partition **806** having a size of $N \times 2N$, and a partition **808** having a size of $N \times N$. Here, the information **800** about a partition type is set to indicate one of the partition **804** having a size of $2N \times N$, the partition **806** having a size of $N \times 2N$, and the partition **808** having a size of $N \times N$.

The information **810** indicates a prediction mode of each partition. For example, the information **810** may indicate a mode of prediction encoding performed on a partition indicated by the information **800**, e.g., an intra mode **812**, an inter mode **814**, or a skip mode **816**.

The information **820** indicates a transformation unit to be based on when transformation is performed on a current coding unit. For example, the transformation unit may be a first intra transformation unit **822**, a second intra transformation unit **824**, a first inter transformation unit **826**, or a second inter transformation unit **828**.

The image data and encoding information extractor **220** of the video decoding apparatus **200** may extract and use the information **800**, **810**, and **820** for decoding, according to each deeper coding unit.

FIG. **15** is a diagram showing deeper coding units according to depths, according to an exemplary embodiment.

Split information may be used to indicate a change of a depth. The split information indicates whether a coding unit of a current depth is split into coding units of a lower depth.

A prediction unit **910** for prediction encoding a coding unit **900** having a depth of 0 and a size of $2N_0 \times 2N_0$ may include partitions of a partition type **912** having a size of $2N_0 \times 2N_0$, a partition type **914** having a size of $2N_0 \times N_0$, a partition type **916** having a size of $N_0 \times 2N_0$, and a partition type **918** having a size of $N_0 \times N_0$. FIG. **15** only illustrates the partition types **912** through **918** which are obtained by symmetrically splitting the prediction unit **910**, but a partition type is not limited thereto, and the partitions of the prediction unit **910** may include asymmetrical partitions, partitions having a predetermined shape, and partitions having a geometrical shape.

Prediction encoding is repeatedly performed on one partition having a size of $2N_0 \times 2N_0$, two partitions having a size of $2N_0 \times N_0$, two partitions having a size of $N_0 \times 2N_0$, and four partitions having a size of $N_0 \times N_0$, according to each partition type. The prediction encoding in an intra mode and an inter mode may be performed on the partitions having the sizes of $2N_0 \times 2N_0$, $N_0 \times 2N_0$, $2N_0 \times N_0$, and $N_0 \times N_0$. The prediction encoding in a skip mode is performed only on the partition having the size of $2N_0 \times 2N_0$.

Errors of encoding including the prediction encoding in the partition types **912** through **918** are compared, and the minimal encoding error is determined among the partition types. If an encoding error is smallest in one of the partition types **912** through **916**, the prediction unit **910** may not be split into a lower depth.

If the encoding error is the smallest in the partition type **918**, a depth is changed from 0 to 1 to split the partition type **918** in operation **920**, and encoding is repeatedly performed

on coding units **930** having a depth of 2 and a size of $N_0 \times N_0$ to search for a minimum encoding error.

A prediction unit **940** for prediction encoding the coding unit **930** having a depth of 1 and a size of $2N_1 \times 2N_1$ ($=N_0 \times N_0$) may include partitions of a partition type **942** having a size of $2N_1 \times 2N_1$, a partition type **944** having a size of $2N_1 \times N_1$, a partition type **946** having a size of $N_1 \times 2N_1$, and a partition type **948** having a size of $N_1 \times N_1$.

If an encoding error is the smallest in the partition type **948**, a depth is changed from 1 to 2 to split the partition type **948** in operation **950**, and encoding is repeatedly performed on coding units **960**, which have a depth of 2 and a size of $N_2 \times N_2$ to search for a minimum encoding error.

When a maximum depth is d , the coding unit according to each depth may be performed up to when a depth becomes $d-1$, and split information may be encoded up to when a depth is one of 0 to $d-2$. In other words, when encoding is performed up to when the depth is $d-1$ after a coding unit corresponding to a depth of $d-2$ is split in operation **970**, a prediction unit **990** for prediction encoding a coding unit **980** having a depth of $d-1$ and a size of $2N_{(d-1)} \times 2N_{(d-1)}$ may include partitions of a partition type **992** having a size of $2N_{(d-1)} \times 2N_{(d-1)}$, a partition type **994** having a size of $2N_{(d-1)} \times N_{(d-1)}$, a partition type **996** having a size of $N_{(d-1)} \times 2N_{(d-1)}$, and a partition type **998** having a size of $N_{(d-1)} \times N_{(d-1)}$.

Prediction encoding may be repeatedly performed on one partition having a size of $2N_{(d-1)} \times 2N_{(d-1)}$, two partitions having a size of $2N_{(d-1)} \times N_{(d-1)}$, two partitions having a size of $N_{(d-1)} \times 2N_{(d-1)}$, and four partitions having a size of $N_{(d-1)} \times N_{(d-1)}$ from among the partition types **992** through **998** to search for a partition type having a minimum encoding error.

Even when the partition type **998** has the minimum encoding error, since a maximum depth is d , a coding unit $CU_{(d-1)}$ having a depth of $d-1$ is no longer split to a lower depth, and a coded depth for the coding units constituting a current maximum coding unit **900** is determined to be $d-1$ and a partition type of the current maximum coding unit **900** may be determined to be $N_{(d-1)} \times N_{(d-1)}$. Also, since the maximum depth is d and a minimum coding unit **980** having a lowermost depth of $d-1$ is no longer split to a lower depth, split information for the minimum coding unit **980** is not set.

A data unit **999** may be a 'minimum unit' for the current maximum coding unit. A minimum unit according to an exemplary embodiment may be a rectangular data unit obtained by splitting a minimum coding unit **980** by 4. By performing the encoding repeatedly, the video encoding apparatus **100** may select a depth having the least encoding error by comparing encoding errors according to depths of the coding unit **900** to determine a coded depth, and set a corresponding partition type and a prediction mode as an encoding mode of the coded depth.

As such, the minimum encoding errors according to depths are compared in all of the depths of 1 through d , and a depth having the least encoding error may be determined as a coded depth. The coded depth, the partition type of the prediction unit, and the prediction mode may be encoded and transmitted as information about an encoding mode. Also, since a coding unit is split from a depth of 0 to a coded

depth, only split information of the coded depth is set to 0, and split information of depths excluding the coded depth is set to 1.

The image data and encoding information extractor **220** of the video decoding apparatus **200** may extract and use the information about the coded depth and the prediction unit of the coding unit **900** to decode the partition **912**. The video decoding apparatus **200** may determine a depth, in which split information is 0, as a coded depth by using split information according to depths, and use information about an encoding mode of the corresponding depth for decoding.

FIGS. **16** to **18** are diagrams for describing a relationship between coding units, prediction units, and transformation units, according to an exemplary embodiment.

The coding units **1010** are coding units having a tree structure, corresponding to coded depths determined by the video encoding apparatus **100**, in a maximum coding unit. The prediction units **1060** are partitions of prediction units of each of the coding units **1010**, and the transformation units **1070** are transformation units of each of the coding units **1010**.

When a depth of a maximum coding unit is 0 in the coding units **1010**, depths of coding units **1012** and **1054** are 1, depths of coding units **1014**, **1016**, **1018**, **1028**, **1050**, and **1052** are 2, depths of coding units **1020**, **1022**, **1024**, **1026**, **1030**, **1032**, and **1048** are 3, and depths of coding units **1040**, **1042**, **1044**, and **1046** are 4.

In the prediction units **1060**, some encoding units **1014**, **1016**, **1022**, **1032**, **1048**, **1050**, **1052**, and **1054** are obtained by splitting the coding units in the encoding units **1010**. In other words, partition types in the coding units **1014**, **1022**, **1050**, and **1054** have a size of $2N \times N$, partition types in the coding units **1016**, **1048**, and **1052** have a size of $N \times 2N$, and a partition type of the coding unit **1032** has a size of $N \times N$. Prediction units and partitions of the coding units **1010** are smaller than or equal to each coding unit.

Transformation or inverse transformation is performed on image data of the coding unit **1052** in the transformation units **1070** in a data unit that is smaller than the coding unit **1052**. Also, the coding units **1014**, **1016**, **1022**, **1032**, **1048**, **1050**, and **1052** in the transformation units **1070** are different from those in the prediction units **1060** in terms of sizes and shapes. In other words, the video encoding and decoding apparatuses **100** and **200** may perform intra prediction, motion estimation, motion compensation, transformation, and inverse transformation individually on a data unit in the same coding unit.

Accordingly, encoding is recursively performed on each of coding units having a hierarchical structure in each region of a maximum coding unit to determine an optimum coding unit, and thus coding units having a recursive tree structure may be obtained. Encoding information may include split information about a coding unit, information about a partition type, information about a prediction mode, and information about a size of a transformation unit. Table 1 shows the encoding information that may be set by the video encoding and decoding apparatuses **100** and **200**.

TABLE 1

Prediction Mode	Split Information 0 (Encoding on Coding Unit having Size of $2N \times 2N$ and Current Depth of d)		Split Information 1	
	Partition Type	Size of Transformation Unit	Split Information 0 of Transformation Unit	Split Information 1 of Transformation Unit
Intra	Symmetrical	Asymmetrical	Split Information 0 of Transformation Unit	Split Information 1 of Transformation Unit
Inter	Partition Type	Partition Type	Split Information 0 of Transformation Unit	Split Information 1 of Transformation Unit
Skip (Only $2N \times 2N$)	$2N \times 2N$ $2N \times N$ $N \times 2N$ $N \times N$	$2N \times nU$ $2N \times nD$ $nL \times 2N$ $nR \times 2N$	$2N \times 2N$	$N \times N$ (Symmetrical Type) $N/2 \times N/2$ (Asymmetrical Type)

The output unit **130** of the video encoding apparatus **100** may output the encoding information about the coding units having a tree structure, and the image data and encoding information extractor **220** of the video decoding apparatus **200** may extract the encoding information about the coding units having a tree structure from a received bitstream.

Split information indicates whether a current coding unit is split into coding units of a lower depth. If split information of a current depth d is 0, a depth, in which a current coding unit is no longer split into a lower depth, is a coded depth, and thus information about a partition type, prediction mode, and a size of a transformation unit may be defined for the coded depth. If the current coding unit is further split according to the split information, encoding is independently performed on four split coding units of a lower depth.

A prediction mode may be one of an intra mode, an inter mode, and a skip mode. The intra mode and the inter mode may be defined in all partition types, and the skip mode is defined only in a partition type having a size of $2N \times 2N$.

The information about the partition type may indicate symmetrical partition types having sizes of $2N \times 2N$, $2N \times N$, $N \times 2N$, and $N \times N$, which are obtained by symmetrically splitting a height or a width of a prediction unit, and asymmetrical partition types having sizes of $2N \times nU$, $2N \times nD$, $nL \times 2N$, and $nR \times 2N$, which are obtained by asymmetrically splitting the height or width of the prediction unit. The asymmetrical partition types having the sizes of $2N \times nU$ and $2N \times nD$ may be respectively obtained by splitting the height of the prediction unit in 1:3 and 3:1, and the asymmetrical partition types having the sizes of $nL \times 2N$ and $nR \times 2N$ may be respectively obtained by splitting the width of the prediction unit in 1:3 and 3:1.

The transformation unit size may be set to be two types in the intra mode and two types in the inter mode. In other words, if split information of the transformation unit is 0, the transformation unit size may be $2N \times 2N$, which is the size of the current coding unit. If split information of the transformation unit is 1, the transformation units may be obtained by splitting the current coding unit. Also, if a partition type of the current coding unit having the size of $2N \times 2N$ is a symmetrical partition type, a size of a transformation unit may be $N \times N$, and if the partition type of the current coding unit is an asymmetrical partition type, the transformation unit size may be $N/2 \times N/2$.

The encoding information about coding units having a tree structure may include at least one of a coding unit corresponding to a coded depth, a prediction unit, and a minimum unit. The coding unit corresponding to the coded depth may include at least one of a prediction unit and a minimum unit containing the same encoding information.

Accordingly, it is determined whether adjacent data units are included in the same coding unit corresponding to the coded depth by comparing encoding information of the adjacent data units. Also, a corresponding coding unit corresponding to a coded depth is determined by using encoding information of a data unit, and thus a distribution of coded depths in a maximum coding unit may be determined.

Accordingly, if a current coding unit is predicted based on encoding information of adjacent data units, encoding information of data units in deeper coding units adjacent to the current coding unit may be directly referred to and used.

Alternatively, if a current coding unit is predicted based on encoding information of adjacent data units, data units adjacent to the current coding unit are searched using encoded information of the data units, and the searched adjacent coding units may be referred to for predicting the current coding unit.

FIG. 19 is a diagram for describing a relationship between a coding unit, a prediction unit, and a transformation unit according to encoding mode information of Table 1.

A maximum coding unit **1300** includes coding units **1302**, **1304**, **1306**, **1312**, **1314**, **1316**, and **1318** of coded depths. Here, since the coding unit **1318** is a coding unit of a coded depth, split information may be set to 0. Information about a partition type of the coding unit **1318** having a size of $2N \times 2N$ may be set to be one of a partition type **1322** having a size of $2N \times 2N$, a partition type **1324** having a size of $2N \times N$, a partition type **1326** having a size of $N \times 2N$, a partition type **1328** having a size of $N \times N$, a partition type **1332** having a size of $2N \times nU$, a partition type **1334** having a size of $2N \times nD$, a partition type **1336** having a size of $nL \times 2N$, and a partition type **1338** having a size of $nR \times 2N$.

Split information (TU size flag) of a transformation unit is a kind of a transformation index, and a transformation unit size corresponding to the transformation index may vary according to a type of the prediction unit or the partition of the coding unit.

For example, when the partition type is set to be symmetrical, e.g., the partition type **1322**, **1324**, **1326**, or **1328**, a transformation unit **1342** having a size of $2N \times 2N$ is set if the split information of the transformation unit is 0, and a transformation unit **1344** having a size of $N \times N$ is set if a TU size flag is 1.

When the partition type is set to be asymmetrical, e.g., the partition type **1332**, **1334**, **1336**, or **1338**, a transformation unit **1352** having a size of $2N \times 2N$ is set if a TU size flag is 0, and a transformation unit **1354** having a size of $N/2 \times N/2$ is set if a TU size flag is 1.

Referring to FIG. 19, the TU size flag is a flag having a value of 0 or 1, but the TU size flag is not limited to 1 bit,

and a transformation unit may be hierarchically split having a tree structure while the TU size flag increases from 0. The TU size flag may be used as an exemplary embodiment of the transformation index.

In this case, if split information of the transformation unit is used together with the maximum transformation unit size and the minimum transformation unit size, the transformation unit size that is actually used may be expressed. The video encoding apparatus **100** may encode maximum transformation unit size information, minimum transformation unit size information, and maximum transformation unit split information. The encoded maximum transformation unit size information, minimum transformation unit size information, and maximum transformation unit split information may be inserted into an SPS. The video decoding apparatus **200** may perform video decoding by using the maximum transformation unit size information, the minimum transformation unit size information, and the maximum transformation unit split information.

For example, if a current coding unit has a size of 64×64 and the maximum transformation unit size is 32×32, when the transformation unit split information is 0, a transformation unit size may be set to 32×32, when the transformation unit split information is 1, the transformation unit size may be set to 16×16, and when the transformation unit split information is 2, the transformation unit size may be set to 8×8.

Alternatively, if the current coding unit has a size of 32×32 and the minimum transformation unit size is 32×32, when the transformation unit split information is 1, the transformation unit size may be set to 32×32, and since the transformation unit size is equal to or larger than 32×32, no more transformation unit split information may be set.

Alternatively, if the current coding unit has a size of 64×64 and the maximum transformation unit split information is 1, the transformation unit split information may be set to 0 or 1, and other transformation unit split information may not be set.

Accordingly, if maximum transformation unit split information is defined as 'MaxTransformSizeIndex', if a minimum transformation unit size is defined as 'MinTransformSize', and if a transformation unit size is defined as 'RootTuSize' when the transformation unit split information is 0, 'CurrMinTuSize' which is a minimum transformation unit size available in the current coding unit may be defined by formula (1) below:

$$\text{CurrMinTuSize} = \max(\text{MinTransformSize}, \text{RootTuSize}/(2^{\text{MaxTransformSizeIndex}})) \quad \text{FORMULA 1}$$

Compared to 'CurrMinTuSize' which is the minimum transformation unit size available in the current coding unit, 'RootTuSize' which is a transformation unit size when the transformation unit split information is 0 may represent a maximum transformation unit size that may be adopted in a system. In other words, according to formula (1), 'RootTuSize/(2^{MaxTransformSizeIndex})' is a transformation unit size in which 'RootTuSize' is split a number of times corresponding to the maximum transformation unit split information and 'MinTransformSize' is a minimum transformation unit size, and thus a smaller value from among 'RootTuSize/(2^{MaxTransformSizeIndex})' and 'MinTransformSize' may be 'CurrMinTuSize' which is the minimum transformation unit size available in the current coding unit.

The 'RootTuSize' which is the maximum transformation unit size may vary according to a prediction mode.

For example, if a current prediction mode is an inter mode, the 'RootTuSize' may be determined according to formula (2) below. In formula (2), 'MaxTransformSize' denotes a maximum transformation unit size, and 'PUSize' denotes a current prediction unit size.

$$\text{RootTuSize} = \min(\text{MaxTransformSize}, \text{PUSize}) \quad \text{FORMULA 2}$$

In other words, if the current prediction mode is an inter mode, the 'RootTuSize' which is a transformation unit size when the transformation unit split information is 0 may be set to a smaller value from among the maximum transformation unit size and the current prediction unit size.

If a prediction mode of a current partition unit is an intra mode, the 'RootTuSize' may be determined according to formula (3) below. 'PartitionSize' denotes a current partition unit size.

$$\text{RootTuSize} = \min(\text{MaxTransformSize}, \text{PartitionSize}) \quad \text{FORMULA 3}$$

In other words, if the current prediction mode is an intra mode, the 'RootTuSize' may be set to a smaller value from among the maximum transformation unit size and the current partition unit size.

However, the current maximum transformation unit size 'RootTuSize' varying according to a prediction mode of the partition unit is just an example, and a factor for determining the current maximum transformation unit size is not limited thereto.

Image data of a spatial domain is encoded for each coding unit having a tree structure by using a video encoding method based on the coding units having a tree structure described above with reference to FIGS. 7 to 19, and decoding is performed on each maximum coding unit by using a video decoding method based on the coding units having a tree structure, and thus the image data of the spatial domain is restored, thereby restoring a video which is a picture and a picture sequence. The restored video may be reproduced by a reproducing apparatus, may be stored in a storage medium, or may be transmitted via a network.

The exemplary embodiments may be written as computer programs and may be implemented in general-use digital computers that execute the programs using a computer readable recording medium. Examples of the computer readable recording medium include magnetic storage media (e.g., ROM, floppy disks, hard disks, etc.) and optical recording media (e.g., CD-ROMs, or DVDs).

While the disclosure has been particularly shown and described with reference to exemplary embodiments thereof, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope of the exemplary embodiments as defined by the appended claims. The exemplary embodiments should be considered in a descriptive sense only and not for purposes of limitation. Therefore, the scope of the exemplary embodiments is defined not by the detailed description of the exemplary embodiments but by the appended claims, and all differences within the scope will be construed as being included in the exemplary embodiments.

What is claimed is:

1. An apparatus for decoding a video, the apparatus comprising at least one processor configured to:
 - obtain a prefix bitstring of a last coefficient location of a transformation block by performing context-based arithmetic decoding on a received bitstream;

when the prefix bitstring is greater than a predetermined
 value, obtain, from the bitstream, a suffix bitstring
 according to a bypass mode;
 perform inverse binarization on the prefix bitstring
 according to a truncated binarization scheme to obtain 5
 an inverse-binarized prefix;
 perform inverse binarization on the suffix bitstring
 according to a fixed-length binarization scheme to
 obtain an inverse-binarized suffix; and
 reconstruct a symbol indicating the last coefficient loca- 10
 tion of the transformation block by using the inverse-
 binarized prefix and the inverse-binarized suffix,
 wherein a range of a value of the inverse-binarized prefix
 is determined based on a size of the transformation
 block and a range of a value of the inverse-binarized 15
 suffix is determined based on the value of the inverse-
 binarized prefix,
 wherein a value of the symbol indicating the last coeffi-
 cient location of the transformation block is recon-
 structed by using the value of the inverse-binarized 20
 prefix and the value of the inverse-binarized suffix, and
 wherein the context-based arithmetic decoding is per-
 formed by using a context index determined based on
 the size of the transformation block and a bin index of
 the prefix bitstring. 25

* * * * *