

US010555043B2

(12) United States Patent

Chen et al.

(54) METHOD FOR CONTENT-BASED NON-LINEAR CONTROL OF MULTIMEDIA PLAYBACK

(71) Applicant: AT&T Intellectual Property II, L.P.,

Atlanta, GA (US)

(72) Inventors: Edward Y. Chen, Holmdel, NJ (US);

David Crawford Gibbon, Lincroft, NJ (US); Laurence W. Ruedisueli, Berkeley Heights, NJ (US); Behzad Shahraray, Freehold, NJ (US)

(73) Assignee: AT&T INTELLECTUAL PROPERTY II, L.P., Atlanta, GA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 16/420,315

(22) Filed: May 23, 2019

(65) Prior Publication Data

US 2019/0281358 A1 Sep. 12, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/819,156, filed on Nov. 21, 2017, now Pat. No. 10,306,322, which is a (Continued)

(51) Int. Cl.

H04N 21/472 (2011.01)

G06F 16/74 (2019.01)

(Continued)

(10) Patent No.: US 10,555,043 B2

(45) **Date of Patent:** *Feb. 4, 2020

(52) U.S. Cl.

CPC *H04N 21/47217* (2013.01); *G06F 16/40* (2019.01); *G06F 16/44* (2019.01);

(Continued)

(58) Field of Classification Search

None

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS


5,132,992 A 7/1992 Yurt et al. 5,410,326 A 4/1995 Goldstein (Continued)

Primary Examiner — An Son P Huynh

(57) ABSTRACT

A system and method are provided for content-based non-linear control of video data playback. A multimedia database having multimedia data including multimedia content data is searched based on a user query to determine a first set of multimedia data. The multimedia data includes indexes to and condensed representations of corresponding video data stored in a video database. A portion of the first set of multimedia data is displayed at a control device in response to the user query. A user of the control device selects an element of the first set of multimedia data for video playback and video data corresponding to the element delivered to a video device for playback. A user of the control device selects an element of the first set of multimedia data for additional information and a second set of multimedia data corresponding to the element delivered to the control device.

20 Claims, 5 Drawing Sheets



5,987,154 A

7,313,808 B1

7,325,199 B1

7,401,351 B2

12/2007 Gupta et al.

7/2008 Boreczky et al.

1/2008 Reid

11/1999 Gibbon

Related U.S. Application Data 11/1999 Schindler 5,995,155 A continuation of application No. 15/296,182, filed on 5/2000 Menard et al. 6,061,056 A 8/2000 Gibbon 6,098,082 A Oct. 18, 2016, now Pat. No. 9,832,529, which is a 6,104,334 A 8/2000 Allport continuation of application No. 13/687,497, filed on 9/2000 Proehl et al. 6,118,450 A Nov. 28, 2012, now Pat. No. 9,485,544, which is a 9/2000 Weaver et al. 6,119,154 A continuation of application No. 10/146,300, filed on 6,130,726 A 10/2000 Darbee May 14, 2002, now Pat. No. 8,479,238. 10/2000 Banks 6,139,197 A 11/2000 Jain et al. 6,144,375 A 6,154,600 A 11/2000 Newman et al. Provisional application No. 60/290,788, filed on May 11/2000 Rangan et al. 6,154,771 A 14, 2001. 6,173,317 B1 1/2001 Chaddha et al. 6,185,573 B1 2/2001 Angelucci et al. 6,188,398 B1 2/2001 Collins-Rector et al. (51) **Int. Cl.** 6,236,395 B1 5/2001 Sezan et al. G06F 16/73 (2019.01)6,266,094 B1 7/2001 Taylor, Jr. G06F 16/44 (2019.01)6,271,892 B1 8/2001 Gibbon et al. G06F 16/40 (2019.01)6,278,499 B1 8/2001 Darbee (2011.01)11/2001 Junqua et al. H04N 21/44 6,314,398 B1 11/2001 Huang 6,317,710 B1 (2011.01)H04N 21/482 12/2001 Seki 6,330,603 B1 H04N 21/432 (2011.01)12/2001 Koyama 6,333,739 B1 H04N 21/434 (2011.01)1/2002 Vasudevan et al. 6,342,904 B1 H04N 21/858 (2011.01)2/2002 Lortz 6,349,410 B1 6,405,371 B1 6/2002 Oosterhout et al. H04N 21/84 (2011.01)7/2002 Ciairin et al. 6,414,725 B1 H04N 21/6587 (2011.01)7/2002 Gupta et al. 6,415,326 B1 (2011.01)H04N 21/4782 7/2002 McNeill et al. 6,421,706 B1 H04N 21/462 (2011.01)9/2002 Morita et al. 6,449,608 B1 H04N 21/414 (2011.01)6,470,378 B1 10/2002 Tracton et al. 6,473,778 B1 10/2002 Gibbon H04N 21/278 (2011.01)11/2002 Croy 6,476,825 B1 H04N 21/266 (2011.01)1/2003 Croy et al. 6,509,908 B1 H04N 21/2343 (2011.01)3/2003 Uchihachi et al. 6,535,639 B1 H04N 7/173 (2011.01)6,567,980 B1 5/2003 Jain et al. (2019.01)G06F 16/738 6/2003 Liou et al. 6,580,437 B1 6,584,463 B2 6/2003 Morita et al. H04N 5/44 (2011.01)7/2003 Goldschmidt et al. 6,601,103 B1 U.S. Cl. (52)6,615,252 B1 9/2003 Oka et al. CPC *G06F 16/73* (2019.01); *G06F 16/738* 10/2003 Matthews et al. 6,631,523 B1 (2019.01); *G06F 16/74* (2019.01); *H04N* 10/2003 Feinleib 6,637,032 B1 12/2003 Dunn 6,668,377 B1 7/17336 (2013.01); **H04N 21/23439** (2013.01); 6,710,822 B1 3/2004 Walker et al. H04N 21/26603 (2013.01); H04N 21/278 6,711,741 B2 3/2004 Yeo (2013.01); *H04N 21/41407* (2013.01); *H04N* 6/2004 Yanagawa 6,745,252 B1 *21/432* (2013.01); *H04N 21/4345* (2013.01); 6/2004 Schumacher et al. 6,757,907 B1 H04N 21/44008 (2013.01); H04N 21/4622 6,760,916 B2 7/2004 Holtz et al. 6,788,882 B1 9/2004 Geer et al. (2013.01); **H04N 21/4782** (2013.01); **H04N** 9/2004 Eyer et al. 6,789,106 B2 21/47202 (2013.01); H04N 21/4821 (2013.01); 12/2004 Bhagavath et al. 6,829,781 B1 H04N 21/4828 (2013.01); H04N 21/6587 6,844,886 B1 1/2005 Yanagawa (2013.01); **H04N 21/84** (2013.01); **H04N** 1/2005 Shastri 6,845,485 B1 3/2005 Yeo et al. 6,870,573 B2 **21/8586** (2013.01); H04N 5/4401 (2013.01) 6,877,134 B1 4/2005 Fuller et al. 4/2005 Ahmad et al. 6,880,171 B1 **References Cited** (56)4/2005 Fu et al. 6,882,793 B1 6,918,132 B2 7/2005 Gargi U.S. PATENT DOCUMENTS 6,938,208 B2 8/2005 Reichardt 10/2005 Bergen et al. 6,956,573 B1 5,459,530 A 10/1995 Andersson 11/2005 Maybury et al. 6,961,954 B1 5,539,479 A 7/1996 Bertram 11/2005 Boccon-Gibod et al. 6,965,724 B1 9/1996 Reimer 5,553,221 A 11/2005 Zhang 6,968,366 B1 5,572,260 A 11/1996 Onishi et al. 12/2005 Takano 6,976,267 B1 2/1997 Youden et al. 5,606,359 A 7,065,250 B1 6/2006 Lennon 5,610,653 A 3/1997 Abecassis 7,073,127 B2 7/2006 Zhao et al. 4/1997 Billock et al. 5,619,249 A 7,107,532 B1 9/2006 Billmaier et al. 8/1998 Mano 5,793,366 A 7,116,357 B1 10/2006 Oya 10/1998 Nagasaka et al. 5,818,439 A 7,174,512 B2 2/2007 Martin et al. 11/1998 Wactlar et al. 5,835,667 A 7,178,107 B2 2/2007 Sezan et al. 12/1998 Coleman 5,844,620 A 7,200,857 B1 4/2007 Rodriguez et al. 5,854,894 A 12/1998 Lancaster et al. 7,231,603 B2 6/2007 Matsumoto 5,864,682 A 1/1999 Porter et al. 7,237,254 B1 6/2007 Omoigui 5,877,755 A 3/1999 Helhake 7,281,220 B1 10/2007 Rashkovskiy 3/1999 Iwamura 5,883,621 A 11/2007 Gupta et al. 7,293,280 B1 5,884,056 A 3/1999 Steele 11/2007 Redmond 7,301,944 B1 5,900,867 A 5/1999 Schindler

5/1999 Duhault et al.

10/1999 Itoh

6/1999 Anderson et al.

5,900,868 A

5,917,488 A

5,966,122 A

US 10,555,043 B2 Page 3

(56)	Referen	ces Cited	2003/0066085 A1		Boyer et al.
U.S	. PATENT	DOCUMENTS	2003/0103088 A1 2003/0113100 A1 2003/0123850 A1	6/2003 6/2003 7/2003	Hecht
		Maybury et al.	2004/0250272 A1 2005/0028194 A1	12/2004 2/2005	Ellis et al. Durden et al. Elenbaas et al.
8,108,892 B1	1/2012	Elliott et al. Durkee	2005/0028208 A1 2005/0088333 A1 2005/0210145 A1 2005/0229213 A1	4/2005 9/2005	Allport Kim et al.
8,214,422 B1 8,732,758 B2 2001/0043744 A1 2001/0049826 A1		Hieda	2005/0235319 A1 2005/0240961 A1 2005/0251827 A1	10/2005 10/2005 11/2005	Carpenter et al. Jerding et al. Ellis
2002/0039481 A1 2002/0051077 A1 2002/0056098 A1	5/2002 5/2002	White	2005/0262542 A1 2006/0059275 A1 2006/0095937 A1 2006/0110136 A1	3/2006 5/2006	DeWeese et al. Lefevre Knudson Abecassis
2002/0059621 A1 2002/0069218 A1 2002/0078176 A1 2002/0093591 A1	6/2002 6/2002	Thomas Sull et al. Nomura et al. Gong	2006/0110130 A1 2006/0129938 A1 2006/0140584 A1 2006/0242665 A1	6/2006 6/2006	Humpleman Ellis et al. Knee et al.
2002/0097984 A1 2002/0111968 A1 2002/0150387 A1	7/2002 8/2002 10/2002	Abecassis Ching Kunii	2007/0061853 A1 2008/0086754 A1*		Kondo Chen H04L 29/06027 725/105
2002/0163532 A1 2002/0170068 A1 2002/0194151 A1		Rafey et al.	2009/0060450 A1 * cited by examine		Daniels




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

METHOD FOR CONTENT-BASED NON-LINEAR CONTROL OF MULTIMEDIA PLAYBACK

PRIORITY INFORMATION

The present invention is a continuation of U.S. patent application Ser. No. 15/819,156, filed Nov. 21, 2017, which is a continuation of U.S. patent application Ser. No. 15/296, 182, filed Oct. 18, 2016, which is a continuation of U.S. patent application Ser. No. 13/687,497, filed Nov. 28, 2012, now U.S. Pat. No. 9,485,544, issued Nov. 1, 2016, which is a continuation of U.S. patent application Ser. No. 10/146, 300, filed May 14, 2002, now U.S. Pat. No. 8,479,238, issued Jul. 2, 2013, which is a non-provisional of U.S. Patent Provisional Application No. 60/290,788, filed May 14, 2001, the content of which are incorporated herein in their entireties by reference.

FIELD OF THE INVENTION

The present invention generally relates to the control and playback of user selected video material based on the content of the video material.

BACKGROUND OF THE INVENTION

Audio and video signal streams, whether carrying analog or digitally encoded information, have come to represent a significant source of consumer information and entertain- 30 ment. Traditionally such signal streams were provided to consumers over radio frequency bands through use of a transmitter and a receiver. Changes in distribution methods have led to the use of various alternative devices such as cable set top boxes, video recorder/player devices such as 35 cassette recorders and video disc players, or direct live video sources such as home cameras, game systems, and computers, and other alternative devices. As such devices have proliferated, so too have their associated control devices such that consumers are frequently faced with a proliferation 40 of control devices. For example, in "home theater systems" having numerous interconnected devices, several or even all the devices may have its own control device which enables the consumer to control the functionality of the respective device remotely without directly manipulating controls on 45 the device.

In addition, increased availability of networks for the transmission of signal streams has vastly increased the number and variety of information and entertainment services available to consumers. As a result, consumers have 50 trouble keeping informed as to the scheduling of available services. Accordingly, some cable television systems provide a dedicated channel that displays a current programming guide for scheduled services. However, such a channel typically slowly scrolls a limited and fixed amount of 55 information, usually only one to three hours of program scheduling. Moreover, these systems lack any user interface capability and cannot be customized to suit individual consumer's needs so that a consumer must inconveniently wait to potentially view information of interest and then, 60 may not even be provided with information suited to their particular interests.

Some systems enable searching of displayed data, such as the title of a movie or the name of a song, associated with stored video data. However, such systems do not facilitate 65 navigation of large aggregates of video material, or navigation within a particular video material entry, such as a single 2

video program, to enable the consumer to find information of particular interest. A consumer will thus often times have to navigate linearly through a large amount of irrelevant video material in order to find desired video programming, wasting time and effort. Moreover, such excessive navigation likewise requires excessive bandwidth when in communication with a video server, failing to minimize the time necessary for video material retrieval, and thereby slowing the network over which such communication occurs.

SUMMARY OF THE INVENTION

A system and method are provided for content-based non-linear control of video data playback. A multimedia database having multimedia data including multimedia content data is searched based on a user-selected parameter to determine a first set of multimedia data. The multimedia data includes indices to information pertaining to the information content of corresponding video data stored in a video database. The multimedia data also includes condensed 20 representations of corresponding video data, such as image scenes or closed captioned information concerning what was spoken in a image scene. A portion of the first set of multimedia data is displayed at a control device. A user of the control device selects an element of the first set of ₂₅ multimedia data for video playback and video data corresponding to the element delivered to a video device for playback. A user of the control device selects an element of the first set of multimedia data for additional information and a second set of multimedia data corresponding to the element delivered to the control device.

BRIEF DESCRIPTION OF THE DRAWINGS

Further aspects of the instant invention will be more readily appreciated upon review of the detailed description of the embodiments included below when taken in conjunction with the accompanying drawings, of which:

FIG. 1 illustrates an exemplary architecture for populating a multimedia system with detailed content specific information;

FIG. 2 is an exemplary network topology for implementing the invention;

FIG. 3 illustrates additional detail of the exemplary network topology shown in FIG. 2;

FIG. 4 illustrates an exemplary control device screen for specifying the video device that is to be controlled;

FIG. 5 illustrates an exemplary control device screen for the main search term selection screen (i.e., "home" screen);

FIG. 6 illustrates an exemplary control device screen for an topics list of exemplary common search terms;

FIG. 7 illustrates an exemplary control device screen of multimedia data indicating video data relevant to a particular search term;

FIG. 8 illustrates an exemplary control device screen of multimedia data indicating portions of individual video data relevant to a particular search term;

FIG. 9 illustrates an exemplary control device screen of an interface for browsing video material that has been closecaptioned; and

FIG. 10 illustrates an exemplary control device screen of an interface for browsing video material that has not been close-captioned.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to FIGS. 1-10, wherein similar components of the invention are numerically referenced in like

manner, disclosed are embodiments of an architecture and method for accessing, over a network, user selected video data based on selected multimedia data.

FIG. 1 illustrates an exemplary architecture for populating a multimedia system with detailed content specific informa- 5 tion. Video source material 110 is provided to a media analysis/metadata extraction device 120. The media analysis/metadata extraction device extracts content specific index data from the provided video material using automatic media processing techniques such video indexing and/or 10 audio indexing. The media analysis/metadata extraction device converts the video source material into video data and multimedia data for storage in a multimedia database and video database 140. Content specific index data determined by the media analysis/metadata extraction device is 15 included in the multimedia data. Each logical unit of video source material (e.g., a television program, a video-tape, a corporate speech) is broken down by the media analysis/ metadata extraction device into a distinct entry for the multimedia database and video database.

In addition, the media analysis/metadata extraction device may also break video source material into smaller entries based on topic or story boundaries of the video source material. The video source material may also be analyzed automatically to detect video shot boundaries and to record 25 any associated closed caption information. Further, automated speech recognition, such as Large Vocabulary Automated Speech Recognition (LVASR) can be used to obtain a transcription for inclusion in the multimedia data. In another alternative, the content specific index data is 30 extracted from the video data manually, a human functioning as that portion the media analysis/metadata extraction device that determines content specific index data.

Video data includes that data used to display the video source material **100** on a video device (i.e., the video itself). 35 Multimedia data includes multimedia content data, which is data based on the content of the video data, such as content specific index data, for example, an index of select keywords referenced in the video data. Examples of multimedia content data include still images (e.g., images of a scene from 40 a movie), preview videos (e.g., a theatrical trailer), detailed information about the video data (e.g., names of actors in a video program, the cinematography of the director of a video program), and the like. Multimedia data may also include metadata, which is other data used to index both the video 45 data and multimedia data, such as the title of a movie, the name of a song, or the like. In addition to creating multimedia data, the media analysis/metadata extraction device also may digitize and compress the video source material for storage on the multimedia database and video database **140**. 50 For example, video data may be stored in a format such as MPEG-1, MPEG-2, MPEG-4, or other formats and delivered across the network at various bitrates. Preferably, multiple versions of the video data in various formats are stored so that the highest possible quality version may be 55 later delivered to a consumer based on available bandwidth and the consumer's video device capabilities.

Ancillary source material 120 may also be provided to the media analysis/metadata extraction device 130 to improve the accuracy of indexing or to utilize other information 60 suitable for indexing and retrieving video data. Examples of ancillary data include offline transcriptions, manual annotations, topic classifications, post-production scripts, metadata, genre classifications, and the like. With ancillary source material, the media analysis/metadata extraction 65 device 130 would utilize both the video source material 110 and the ancillary source material 120 during the conversion

4

into video data and multimedia data, including content specific index data, for storage in the multimedia database and video database 140.

For each video data (e.g., television program) in the video database corresponding multimedia data is stored in the multimedia database. Multimedia data that may be stored includes a program stream, image frames and associated metadata (e.g., time within broadcast that the frame was sample, type of video transition) representing each scene, program metadata including title, broadcaster, time and date of airing, closed caption text, automatic speech transcriptions, and various data structures. For example, to indicating pagination each multimedia data representation of video data can be divided into sets of HTML pages and data structures established that indicate the number of HTML pages, and the captions and images that appear on given page. Optionally, the multimedia data that is stored can include an offline transcription that has been synchronized with the video data.

A number of such sets of video data and corresponding multimedia data are stored in the multimedia database and video database. Index services, (e.g., MS Indexing Service) are used to provide full text search capability on either the closed caption text and/or the offline transcription. HTML metatags are included with the text so that relational queries can be supported (e.g., "find all video data containing the term "NASA" from the broadcaster "NBC" that are less than one year old.") The system combines the basic closed caption text and or speech transcription with the metadata to generate files that a server can use as content for searching. Once video data matching a consumer's query has been identified, application software generates a content rich interface for browsing the corresponding multimedia data and initiating video data playback.

In this manner, the invention provides a database of information relating to video material, facilitates navigation of such information (e.g., a plurality of television programs) and further, facilitates navigation with a particular item of such information, such as, a particular television program. An illustrative example of such a database of information is an archive of all television programs in a particular geographic regions for a seven-day period.

The multimedia database and video database may be individually stored on a multimedia server and video server, respectively. Alternatively, the multimedia server and video server can be one in the same server. In either event, the video server and the multimedia server are in communication with the media analysis/metadata extraction device 130, to receive video data and multimedia data, respectively. While centralizing the video database offers economies of scale and eases maintenance, the video data can be stored locally (i.e., proximite a consumer's video device). Additionally, hybrid embodiments are possible in which some of the video data is stored locally and other video data is stored remotely, perhaps in several different geographic locations. Such embodiments may be organized such that popular or frequently viewed video data is stored proximately locally to minimize network communication and congestion. Further, intelligent content distribution networks can be utilized to efficiently distribute the video data from the video database to consumers.

FIG. 2 illustrates an exemplary network topology for implementing the invention. At a consumer premises 210, a control device 212 communicates via a network access point 214 over a network 216. The control device acts as a dynamic control pad for initiating video playback of content specific information and may be a suitably programmed

Personal Digital Assistant (PDA) device. The control device is capable of inputting control command, communicating data, and playing multimedia data such as, preferably, still images, text, preview videos, or the like. Alternatively, the control device may have capabilities limited to textual 5 display and not be able to play video material. The control device utilizes wireless data communications and may employ Bluetooth, IEEE 802.11b, infrared protocols, or other wireless protocols, to establish communication with the network access point. Alternatively, the control device 10 can be a palm-top computer, a tablet computer, a lap-top computer, a desk top computer, or any device capable of display of the multimedia data and solicitation of consumer input and generating control queries and commands.

The network access point negotiates data communications 15 between the control device and the network. The network preferably is an Internet Protocol (IP) network and may have bandwidth of 10 Mbps or greater. The control device communicates with the network and may establish communications at a bandwidth lower than that of the network proper, 20 for example at a bandwidth under 100 Kbps.

Additionally, a video device 218 is located at the consumer premises 210. The video device can decode compressed digital video data and may be a television monitor, computer monitor, or the similar device for display video 25 data. The video device communicates with the network using compatible protocols, as is known in the art. The video device may communicate with the network through a wireless connection that has sufficient bandwidth to support the playback of compressed digital video data. There may be 30 more than one video device that may be controlled by the control device.

Video server 220 stores video database 140 and is interconnected with the network 216. The video server is capable of indexing and accessing the video database via methods 35 known in the art. Multimedia server 222 stores the multimedia database 140 and is interconnected with the network 216. The multimedia server is capable of capable of indexing and accessing the multimedia database via methods known in the art. The multimedia server is also capable of 40 generating content for remote devices. Together, the video data and the multimedia data comprise the content information for utilization by the consumer. During operation of the method of the invention, the consumer interacts with the control device and multimedia data displayed thereon and 45 observes video data displayed on the display device.

From the consumer premises 210, the control device 212 communicates over the network 216 with the multimedia server 222. The multimedia server may be located remotely with respect to the consumer premises. In such an instance, 50 the network may use Wide Area Network (WAN) or other network protocols to route packets between the control device and the multimedia server, as is known in the art. Using the control device, a consumer is able to selectively retrieve multimedia data located on the multimedia server. 55 More than one multimedia server may be located on the network and communicated with in the same manner.

As described above in regard to FIG. 1, the multimedia data includes multimedia content data that is content specific data that is based on and corresponds to video data stored on a video server. Each video program having video data stored on a video server will have corresponding multimedia data pertaining to the content of its corresponding video data stored on at least one multimedia server. By viewing the multimedia content data for a particular multimedia data, the 65 multimedia data is not limited to conventional metadata, such as a title, but also includes information pertaining to the

6

content of the video data. A consumer may choose to retrieve a particular video program having particular video data to the video device located at the consumer premises. The multimedia data may be indexed and searched in a variety of ways, both consumer-defined and/or predefined by indexing software on the multimedia server. For example, the consumer may search for video programs having a particular actor or for video programs located on a particular video server.

After the user has selected multimedia data in order to view the corresponding video data for at least one video program, the control device 212 communicates with video server 220 over the network 216 to instruct the video server to retrieve and provide the desired video data to the video device 218. The video server 220 may be located remotely with respect to the consumer premises 210. In such an instance, the network 216 may use WAN or other network protocols to route packets between the control device and the video server, as is known in the art.

In other embodiments, the video device may be able to download video data or multimedia data and store such data locally within the video device, or utilize some other storage means at the consumer premises for the same purpose. Further, there may be more than one video server 220 located on the network 216, and video data for a particular video program may be located on more than one video server. The video data may be indexed in a variety of ways, as known in the art. It is also possible that the multimedia server and the video server are one in the same.

FIG. 3 illustrates additional detail of the exemplary network topology shown in FIG. 2. The control device 212 includes a graphic display 310 which displays multimedia data, a display controller 312 which controls the consumer interface (display of multimedia data and input of consumer selections in response thereto), and a control device network interface 314 which interfaces the control device to the network. The video device includes a video display 316 which displays video data, a video decoder 318 which decodes compressed video data, and a video device network interface 320 which interfaces the video display to the network. The video server 220 includes a video database 322 which stores the video data, a request processing controller 324 which handles queries and instructions to the video server, and a video server network interface 326 which interfaces the video server to the network. The multimedia server 222 includes a multimedia database 328 which stores the multimedia data, a query processing controller 330 which handles queries and instructions to the multimedia server, and a multimedia server network interface 332 which interfaces the multimedia server to the network. The video server network interface 326, the multimedia server network interface 332, the control device network interface 314 and the video device network interface 320 are connected via the network **216**. Communication between each of the network interfaces is accomplished as described above and via other methods known in the art.

FIGS. **4-10** are screen views for an exemplary control device and disclose one possible implementation of the invention. The control device provides an interface, such as a Graphical User Interface (GUI), for display of information and solicitation of consumer input/instruction as explained below in conjunction with FIG. **4-10**. For initiation and control of video data playback, application software on the control device generates URLs, which pass parameters to a CGI application running under the HTTP server on the video device. A CGI syntax of name/value pairs is used for passing parameters from the control device to the video device.

Parameters include MediaURL, VideoDevice, StartTime, Volume, Reply, and Command.

MediaURL is a URL, URN, or URI indicating the video data stream. VideoDevice is an IP address name or number indicating the video device that is being directed to display 5 the video data. StartTime indicates the video data play position in units since the start of the video data. Volume indicates volume amplitude on a liner scale. Replay indicates whether to send a status message response or issue a no response message. The Command parameter may take on 10 one of several values. Those values include play (play the video data at the given StartTime), stop (stop the video data playback and blank the video display), mute (set volume to zero), volup (increase the volume by a predetermined number of units), voldown (decrease the volume by a predeter- 15 mined number of units), volume (set the volume using the given Volume parameter) and pause (stop the video data playback, freezing the display on the current video frame), and other values within the skill of one in the art. The control device also queries the multimedia server and requests 20 action of the video server to commend the search for and delivery of information of interest to the consumer.

FIG. 4 illustrates an exemplary control device screen for specifying the video device that is to be controlled. The control device provides an input field 410 for the consumer 25 to specify the video device that is to be controlled. In this example, the user has entered the video device name "NTV1". Also provided is a connection button **412**, which, upon selection, instructs the control device that the video device indicated in the input field is to be provided video 30 data. There may be more than one video device that may be controlled by the control device. Preferably, the control device provides a list of all available video devices to which the consumer has access. The list of available video device a server. The list may be prepared at the time that each video device is installed. In addition, names entered by the consumer or selected previously can be presented to the consumer in a selectable list. Preferably each video device has a friendly name and a corresponding Domain Name Server 40 (DNS) entry that maps the friendly name to an Internet Protocol (IP) address. Alternatively, a protocol similar to Address Resolution Protocol (ARP) can be used to determine a list of active video devices.

FIG. 5 illustrates an exemplary control device screen for 45 the main or "home" screen after the video device selection. Command icons for control of the control device are located at the top of the display screen. These icons are linked via CGI URLs to control commands for stop 510, pause 512, volume up **514**, volume down **516**. The command icons can 50 be implemented as an HTML frame. Preferably, these icons remain at the top of the screen after a video device has been selected for control so that the consumer may assert control commands regardless of where the consumer is in a navigation session. Input fields are provide so that the consumer 55 may enter a search term 518, and may restrict the search to a particular broadcaster 520, program 522 or date range 524. A search button 526 is also provided, and which, upon selection, initiates a search of multimedia data based on the input search term. An input field **528** for control the sorting 60 of the result of a search of the multimedia data is preferably provided. Links for searches of the "latest news" 530 and hot "topics" 532 are also provided. Additionally, command icons for mute and other functions can be included with the icons illustrated. Further, a button for linking to a conven- 65 tional numeric keypad display can be added to permit the consumer to easily select a live broadcast channel. A display

of a status message indicating the currently playing content (perhaps by title and some indication of the playing time) can also be provided. Such a message can be displayed in a persistent manner similarly to the command icons.

FIG. 6 illustrates an exemplary control device screen for a hot "topics" list of exemplary common search terms. When the consumer selects the "topics" link (532), the consumer is provided with links 610 listing common search terms. If one of these hot topic links 610 is selected, the control device undertakes a search as if the term was entered into the search term input field (518).

FIG. 7 illustrates an exemplary control device screen of multimedia data indicating video data relevant to a particular search term. After a search term has been instructed (e.g., either by entering a search term on the main screen and clicking search button (518, 526) or by selecting a link on the topic list (610), a search of the multimedia data, specifically content specific index data, is undertaken and a listing of multimedia data describing, in some manner, video data relevant to the search term is displayed. Multimedia data displayed may include a program name, date and time of airing, network aired on, and the like. The display of this multimedia data conveys a summary or condensed representation pertaining to the content of the video data for browsing and serves as a dynamic control pad for initiating of video data playback. The consumer then selects a particular video data (e.g., a television program) of interest from this displayed list of condensed representations pertaining to the content of the video data.

FIG. 8 illustrates an exemplary control device screen of multimedia data indicating information pertaining to the content individual video data entries in the video data database that are relevant to a particular search term. After selecting a particular video data (e.g., a program) from a first may be a predetermined list of device names maintained on 35 list of multimedia data, such as condensed representations of programs (FIG. 7), a second list of relevant multimedia data extracted from selected video data is displayed. In the illustrated example, "NASA" was the search term and the system has selected multimedia data, for example, excerpts of pictorial transcriptions 810, that contains the term "NASA". If the consumer selects one of the displayed excerpts, the video data corresponding to the excerpt will be provided to the video device for playback at that point in the video data corresponding to the selected excerpt. If the consumer selects an arrow icon 812, additional multimedia data, for example the full pictorial transcription, of the selected excerpt is displayed as shown in FIG. 9. Using the full pictorial transcription displayed in FIG. 9, the consumer may scroll the display and select a other non-linear points in the video data (e.g., program) at which to initiate video data playback on the display device.

> If the consumer selects the "Latest News" link (528), a list of multimedia data pertaining to the content of the most recent video data (e.g., most recently aired video programs) in the video database will be displayed in reverse chronological order. Such a list would appear similar to the list illustrated in FIG. 7. Upon selecting from this list of multimedia data, a particular video data of particular interest, the consumer may be directly provided with the full pictorial transcription of the selected excerpt as shown in FIG. 9.

> FIG. 9 illustrates an exemplary control device screen of an interface for browsing video material that has been closecaptioned. The browsing capability includes a display of multimedia data, such as text extracts and corresponding key frame images, with hyperlinks for navigation to other points of interest within the video data corresponding to the displayed multimedia data, or other multimedia data addition-

ally relevant video data of interest. Templates through which the application software of the control device maps the multimedia data govern the form as well as the appearance of the multimedia data.

FIG. 10 illustrates an exemplary control device screen of an interface for browsing video material that has not been close-captioned or otherwise transcribed. In the illustrated example, the displayed multimedia data is arranged into a series of thumbnail images 1010 or "contact sheets." The consumer may scroll the displayed thumbnail images, which are representations of non-linear points within the video data, and select a particular point in the video data (e.g., video program), corresponding to the displayed multimedia data, at which to initiate video data playback. Video data playback is initiated at the point in the video data corresponding to the selected thumbnail image.

It is the intent of the invention to provide a system and method that facilitates searching and browsing of video material. FIGS. 1-10 describe a system and method for accessing multimedia data and video data that facilitates 20 navigation of a large aggregate of video material, and further, navigation within a particular selection of video material on a server or a database. By allowing a consumer to see a condensed representation of video data conveyed by multimedia data, including multimedia content specific data, 25 the consumer is able to make informed decisions as to the relevance or desirability of retrieving and viewing an entire video data entry. Such a system minimizes requests for irrelevant video material, thus minimizing the load on the network, maximizing available bandwidth, and saving consumer time and expense.

The invention enables the creation of user-friendly, network-based, video-on-demand entertainment and information services. It finds application in self-contained home entertainment system and pay-per-view video services on-the-go (e.g., airport) where a consumer uses a control device to find/select video or multimedia content to be delivered to a separate device.

It should be understood that, for convenience, the above description is representative of embodiments according to 40 the principles of the invention without exhaustively enumerating all possible embodiments. Other embodiments may result from combination of various alternative embodiments described herein and, as will be appreciated, are within the scope of the following claims. The figures described herein 45 are for illustrative purposes only, it being possible to implement the invention with user interfaces that differ considerably in appearance from the one depicted here. In fact, it would be desirable to have a plurality of interfaces that are customizable based upon the preferences of user or those of 50 content providers or broadcasters.

What is claimed is:

1. A method comprising:

searching by a server, in response to receiving a search 55 term from a user via a user interface of a mobile control device, a plurality of multimedia data stored in a database at a multimedia server to generate matched multimedia data associated with the search term, the matched multimedia data comprising video content and 60 one or more of a condensed representation pertaining to the video content, offline transcriptions, and closed captions associated with the video content, wherein the condensed representation, the offline transcriptions, and the closed captions associated with the video 65 content are stored in the database, wherein the matched multimedia data is generated by:

10

analyzing, by a media metadata extraction device, the video content and identifying video shot boundaries in the video content;

extracting, by the media metadata extraction device, from the video content, (1) text from the closed captions and (2) a frame corresponding to the text; and

extracting, by the media metadata extraction device, small segments of organized multimedia data based on topic boundaries and the video shot boundaries, each small segment of the small segments being smaller than a respective program containing the small segments, to yield the matched multimedia data;

displaying, with the matched multimedia data and via the user interface, a plurality of command icons for controlling which display device of a plurality of external devices to display a selected video content;

receiving, via the user interface of the mobile control device and from the user, a choice from the matched multimedia data to yield the selected video content; and

receiving, via the user interface of the mobile control device, a user input to display the selected video content on one of a first display device and a second display device of the plurality of external devices, wherein the plurality of command icons remains on the user interface of the mobile control device after one of the first display device and the second display device has been selected for control so that the user can assert control commands regardless of wherein the user is in a navigation session.

- 2. The method of claim 1, wherein the user interface comprises a graphical user interface.
- tion services. It finds application in self-contained home entertainment system and pay-per-view video services on- devices comprises the multimedia server, a video server, and the-go (e.g., airport) where a consumer uses a control device a plurality of video devices.
 - 4. The method of claim 1, wherein the selected video content is indexed by one of a title, a length, a rating, and a scene.
 - 5. The method of claim 1, wherein the search term is received as an utterance.
 - 6. The method of claim 1, wherein the matched multimedia data comprises a second condensed representation pertaining to the selected video content, an offline transcription, and closed captions associated with the selected video content.
 - 7. The method of claim 1, wherein the database comprises ancillary data used to index the selected video content.
 - 8. The method of claim 7, wherein the ancillary data comprises one of offline transcriptions, manual annotations, topic classifications, post-production scripts, metadata, and genre classifications.
 - 9. A system comprising:
 - a processor; and
 - a computer-readable storage medium having instructions stored which, when executed by the processor, cause the processor to perform operations comprising:
 - searching, in response to receiving a search term from a user via a user interface of the system, a plurality of multimedia data stored in a database at a multimedia server to generate matched multimedia data associated with the search term, the matched multimedia data comprising video content and one or more of a condensed representation pertaining to the video content, offline transcriptions, and closed captions associated with the video content, wherein the condensed representation, the offline transcriptions,

and the closed captions associated with the video content are stored in the database, wherein the matched multimedia data is generated by:

analyzing, by a media metadata extraction device, the video content and identifying video shot boundaries ⁵ in the video content;

extracting, by the media metadata extraction device, from the video content, (1) text from the closed captions and (2) a frame corresponding to the text; and

extracting, by the media metadata extraction device, small segments of organized multimedia data based on topic boundaries and the video shot boundaries, each small segment of the small segments being smaller than a respective program containing the small segments, to yield the matched multimedia data;

displaying, with the matched multimedia data and via the user interface, a plurality of command icons for controlling which display device of a plurality of external devices to display a selected video content;

receiving, via the user interface of the system and from the user, a choice from the matched multimedia data to yield the selected video content; and

receiving, via the user interface of the system, a user input to display the selected video content on one of a first display device and a second display device of the plurality of external devices, wherein the plurality of command icons remains on the user interface of the system after one of the first display device and the second display device has been selected for control so that the user can assert control commands regardless of wherein the user is in a navigation session.

10. The system of claim 9, wherein the user interface comprises a graphical user interface.

11. The system of claim 9, wherein the plurality of external devices comprises the multimedia server, a video server, and a plurality of video devices.

12. The system of claim 9, wherein the selected video content is indexed by one of a title, a length, a rating, and a scene.

13. The system of claim 9, wherein the search term is received as an utterance.

14. The system of claim 9, wherein the matched multimedia data comprises a second condensed representation pertaining to the selected video content, an offline transcription, and closed captions associated with the selected video content.

15. The system of claim 9, wherein the database comprises ancillary data used to index the selected video content.

16. The system of claim 15, wherein the ancillary data comprises one of offline transcriptions, manual annotations, topic classifications, post-production scripts, metadata, and genre classifications.

12

17. A computer-readable storage device having instructions stored which, when executed by a system, cause the system to perform operations comprising:

searching, in response to receiving a search term from a user via a user interface of the system, a plurality of multimedia data stored in a database at a multimedia server to generate matched multimedia data associated with the search term, the matched multimedia data comprising video content and one or more of a condensed representation pertaining to the video content, offline transcriptions, and closed captions associated with the video content, wherein the condensed representation, the offline transcriptions, and the closed captions associated with the video content are stored in the database, wherein the matched multimedia data is generated by:

analyzing, by a media metadata extraction device, the video content and identifying video shot boundaries in the video content;

extracting, by the media metadata extraction device, from the video content, (1) text from the closed captions and (2) a frame corresponding to the text; and

extracting, by the media metadata extraction device, small segments of organized multimedia data based on topic boundaries and the video shot boundaries, each small segment of the small segments being smaller than a respective program containing the small segments, to yield the matched multimedia data;

displaying, with the matched multimedia data and via the user interface, a plurality of command icons for controlling which display device of a plurality of external devices to display a selected video content;

receiving, via the user interface of the system and from the user, a choice from the matched multimedia data to yield the selected video content; and

receiving, via the user interface of the system, a user input to display the selected video content on one of a first display device and a second display device of the plurality of external devices, wherein the plurality of command icons remains on the user interface of the system after one of the first display device and the second display device has been selected for control so that the user can assert control commands regardless of wherein the user is in a navigation session.

18. The computer-readable storage device of claim 17, wherein the plurality of external devices comprises the multimedia server, a video server, and a plurality of video devices.

19. The computer-readable storage device of claim 17, wherein the selected video content is indexed by one of a title, a length, a rating, and a scene.

20. The computer-readable storage device of claim 17, wherein the search term is received as an utterance.

* * * *