



US010556202B2

(12) **United States Patent**
Nepsund et al.

(10) **Patent No.:** **US 10,556,202 B2**
(45) **Date of Patent:** ***Feb. 11, 2020**

(54) **AIR FILTER HAVING FLUTED FILTER MEDIA**

(71) Applicant: **Donaldson Company, Inc.**,
Minneapolis, MN (US)

(72) Inventors: **Larry R. Nepsund**, Savage, MN (US);
Bradley A. Kuempel, Eden Prairie,
MN (US); **Donald F. Engel**, Prior Lake,
MN (US); **Bruce Allen Boehrs**, Blaine,
MN (US); **Sheldon Anderson**,
Bloomington, MN (US); **Richard L.**
Bucholtz, Andover, MN (US); **Thomas**
John Lundgren, Bloomington, MN
(US)

(73) Assignee: **Donaldson Company, Inc.**,
Minneapolis, MN (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 154 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **15/704,057**

(22) Filed: **Sep. 14, 2017**

(65) **Prior Publication Data**

US 2018/0126317 A1 May 10, 2018

Related U.S. Application Data

(63) Continuation of application No. 14/854,094, filed on
Sep. 15, 2015, now Pat. No. 9,782,713, which is a
(Continued)

(51) **Int. Cl.**
B01D 46/52 (2006.01)
B01D 46/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B01D 46/527** (2013.01); **B01D 46/0002**
(2013.01); **B01D 46/0004** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B01D 46/525; B01D 46/527
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

991,572 A 5/1911 Weisenstein
3,019,854 A 2/1962 O'Bryant
(Continued)

FOREIGN PATENT DOCUMENTS

CA 997684 9/1976
DE 40 31 014 C2 10/1990
(Continued)

OTHER PUBLICATIONS

Opposition by Baldwin Filters, Inc. against European Patent 1 159
052 B1 owned by Donaldson Company, Inc. dated Aug. 24, 2004.
(Continued)


Primary Examiner — Robert Clemente

(74) *Attorney, Agent, or Firm* — Merchant & Gould P.C.

(57) **ABSTRACT**

An air cleaner includes a housing and an access cover. The
internal volume of the housing can be reached through an
opening in a side wall of the housing. A filter element having
fluted filter media is removable and replaceable from the air
cleaner. The housing is constructed and arranged to cam the
element into sealing engagement with the housing. The
access cover includes structure to help support and ensure
proper seating of the filter element within the housing. A
method of installing the filter element in the air cleaner
includes sliding a portion of the filter element against a slide
surface in the housing. A method of servicing an air cleaner
includes tilting the filter element against a tilt surface in the
housing to release a seal between the filter element and the
housing. The filter element can have a handle to assist in
servicing of the air cleaner. The housing can have a window
to allow visual inspection of the internal component of the
housing and to determine visually whether a filter element is
installed therein.

33 Claims, 16 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/022,399, filed on Sep. 10, 2013, now Pat. No. 9,162,172, which is a continuation of application No. 13/532,129, filed on Jun. 25, 2012, now Pat. No. 8,562,707, which is a continuation of application No. 13/214,913, filed on Aug. 22, 2011, now Pat. No. 8,206,479, which is a continuation of application No. 12/643,747, filed on Dec. 21, 2009, now Pat. No. 8,002,869, which is a continuation of application No. 12/135,742, filed on Jun. 9, 2008, now Pat. No. 7,635,403, which is a continuation of application No. 10/513,618, filed as application No. PCT/US03/14350 on May 8, 2003, now Pat. No. 7,396,375.

(60) Provisional application No. 60/379,824, filed on May 9, 2002.

(51) **Int. Cl.**
B01D 46/24 (2006.01)
B01D 46/42 (2006.01)

(52) **U.S. Cl.**
 CPC *B01D 46/0005* (2013.01); *B01D 46/0006* (2013.01); *B01D 46/2411* (2013.01); *B01D 46/42* (2013.01); *B01D 46/4227* (2013.01); *B01D 46/525* (2013.01); *B01D 2265/025* (2013.01); *B01D 2271/027* (2013.01); *Y10T 29/49826* (2015.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,025,963 A 3/1962 Bauer
 3,209,917 A 10/1965 Yelinek
 3,216,578 A 11/1965 Wright et al.
 3,442,067 A 5/1969 Swenson
 3,494,113 A 2/1970 Kinney
 3,676,242 A 7/1972 Prentice
 3,695,012 A 10/1972 Rolland
 3,695,437 A 10/1972 Shaltis
 3,712,033 A 1/1973 Gronholz
 3,740,933 A 6/1973 Hollowell
 3,807,150 A 4/1974 Maracle
 3,841,953 A 10/1974 Kohkamp et al.
 3,849,241 A 11/1974 Butin et al.
 3,878,014 A 4/1975 Melead
 3,912,631 A 10/1975 Turman
 4,065,341 A 12/1977 Cub
 4,159,899 A 7/1979 Deschenes
 4,187,091 A 2/1980 Durre et al.
 4,236,902 A 12/1980 Fricke
 4,282,186 A 8/1981 Nonnenmann et al.
 4,285,909 A 8/1981 Mizusawa et al.
 4,310,419 A 1/1982 Nara et al.
 4,322,231 A 3/1982 Hilzendeger et al.
 4,359,330 A 11/1982 Copley
 4,402,830 A 9/1983 Pall
 4,410,427 A 10/1983 Wydeven
 4,449,993 A 5/1984 Bergeron
 4,498,989 A 2/1985 Miyakawa et al.
 4,578,091 A 3/1986 Borja
 4,589,983 A 5/1986 Wydeven
 RE32,185 E 6/1986 Copley
 4,617,122 A 10/1986 Kruse et al.
 4,617,176 A 10/1986 Merry
 4,673,503 A 6/1987 Fujimoto
 4,704,143 A 11/1987 Percy
 4,720,292 A 1/1988 Engel et al.
 4,759,783 A 7/1988 Machado
 4,824,564 A 4/1989 Edwards et al.
 4,925,469 A 5/1990 Clement et al.
 4,925,561 A 5/1990 Ishii e al.

4,963,171 A 10/1990 Osendorf
 4,999,038 A 3/1991 Lundberg
 5,030,264 A 7/1991 Klotz et al.
 5,049,326 A 9/1991 Matsumoto et al.
 5,082,476 A 1/1992 Kahlbaugh et al.
 5,125,941 A 6/1992 Ernst et al.
 5,174,895 A 12/1992 Drori
 5,213,596 A 5/1993 Kume et al.
 5,238,474 A 8/1993 Kahlbaugh et al.
 5,240,479 A 8/1993 Bachinski
 5,304,312 A 4/1994 Forster et al.
 5,350,515 A 9/1994 Stark et al.
 5,415,677 A 5/1995 Ager et al.
 5,435,870 A 7/1995 Takagaki et al.
 5,472,463 A 12/1995 Herman et al.
 5,484,466 A 1/1996 Brown et al.
 5,487,767 A 1/1996 Brown
 5,494,497 A 2/1996 Lee
 5,543,007 A 8/1996 Takagaki et al.
 5,547,480 A 8/1996 Coulonvaux
 5,582,146 A 12/1996 Linsbauer et al.
 5,611,922 A 3/1997 SteNe
 5,613,992 A 3/1997 Engel
 5,645,718 A 7/1997 Hardison et al.
 5,672,399 A 9/1997 Kahlbaugh et al.
 5,683,660 A 11/1997 Wirth et al.
 5,685,985 A 11/1997 Brown et al.
 5,690,712 A 11/1997 Engel
 5,714,126 A 2/1998 Frund
 5,730,766 A 3/1998 Clements
 5,755,843 A 5/1998 Sundquist
 5,772,883 A 6/1998 Rothman et al.
 D396,098 S 7/1998 Gillingham et al.
 5,792,247 A 8/1998 Gillingham et al.
 D398,046 S 9/1998 Gillingham et al.
 5,800,587 A 9/1998 Kahlbaugh et al.
 5,820,646 A 10/1998 Gillingham et al.
 5,863,313 A 1/1999 Coulonvaux
 5,871,557 A 2/1999 Tokar et al.
 5,895,574 A 4/1999 Friedmann et al.
 5,897,676 A 4/1999 Engel
 5,902,364 A 5/1999 Tokar et al.
 5,908,480 A 6/1999 Ban et al.
 D416,308 S 11/1999 Ward et al.
 D417,268 S 11/1999 Gillingham
 6,048,386 A 4/2000 Gillingham et al.
 D425,189 S 5/2000 Gillingham et al.
 6,149,700 A 11/2000 Morgan et al.
 6,162,271 A 12/2000 Bullinger et al.
 6,164,457 A 12/2000 Schlör
 6,179,890 B1 1/2001 Ramos et al.
 6,190,432 B1 2/2001 Gieseke et al.
 D439,963 S 4/2001 Gieseke et al.
 6,217,627 B1 4/2001 Vyskocil et al.
 6,231,630 B1 5/2001 Ernst et al.
 6,235,195 B1 5/2001 Tokar
 6,264,713 B1 7/2001 Lewis
 6,299,661 B1 10/2001 Bloomer
 6,306,192 B1 10/2001 Greif et al.
 6,322,602 B2 11/2001 Engel et al.
 6,348,084 B1 2/2002 Gieseke et al.
 6,348,085 B1 2/2002 Tokar et al.
 6,350,291 B1 2/2002 Gieseke et al.
 6,375,700 B1 4/2002 Jaroszyzyk et al.
 6,391,076 B1 5/2002 Jaroszyzyk et al.
 D461,003 S 7/2002 Gieseke et al.
 6,416,561 B1 7/2002 Kallsen et al.
 6,482,247 B2 11/2002 Jaroszyzyk et al.
 6,511,599 B2 1/2003 Jaroszyzyk et al.
 6,547,857 B2 4/2003 Gieseke et al.
 6,572,667 B1 6/2003 Greif et al.
 6,585,792 B2 7/2003 Schneider et al.
 6,598,580 B2 7/2003 Baumann et al.
 6,610,117 B2 8/2003 Gieseke et al.
 6,610,126 B2 8/2003 Xu et al.
 6,641,637 B2 11/2003 Kallsen et al.
 D483,459 S 12/2003 DeWit et al.
 6,743,317 B2 6/2004 Wydeven
 6,746,518 B2 6/2004 Gieseke et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,780,217	B1	8/2004	Palmer	
6,783,565	B2	8/2004	Gieseke et al.	
6,875,256	B2	4/2005	Gillingham et al.	
6,878,190	B1	4/2005	Xu et al.	
6,908,494	B2	6/2005	Gillingham et al.	
6,916,360	B2	7/2005	Seguin et al.	
6,953,124	B2	10/2005	Winter et al.	
6,966,940	B2	11/2005	Krisko et al.	
7,001,450	B2	2/2006	Gieseke et al.	
7,004,986	B2	2/2006	Kopec et al.	
7,090,711	B2	8/2006	Gillingham et al.	
7,147,685	B2	12/2006	Lee	
7,211,124	B2	5/2007	Gieseke et al.	
7,303,604	B2	12/2007	Gieseke et al.	
7,323,029	B2	1/2008	Engelland et al.	
7,351,270	B2	4/2008	Engelland et al.	
7,396,375	B2	7/2008	Nepsund et al.	
7,520,913	B2	4/2009	Mills et al.	
7,615,091	B2	11/2009	Gieseke et al.	
7,635,403	B2	12/2009	Nepsund et al.	
7,674,308	B2	3/2010	Krisko et al.	
8,002,869	B2	8/2011	Nepsund et al.	
8,007,572	B2	8/2011	Gieseke et al.	
8,034,144	B2	10/2011	Gieseke et al.	
8,147,582	B2	4/2012	Engelland et al.	
8,206,479	B2	6/2012	Nepsund et al.	
8,246,708	B2	8/2012	Gieseke et al.	
8,382,875	B2	2/2013	Engelland et al.	
8,486,174	B2	7/2013	Gieseke et al.	
8,562,707	B2	10/2013	Nepsund et al.	
9,782,713	B2*	10/2017	Nepsund	B01D 46/0004
2001/0003893	A1	6/2001	Ramos et al.	
2001/0037631	A1	11/2001	Morgan et al.	
2002/0116909	A1	8/2002	Onoda	
2002/0185007	A1	12/2002	Xu et al.	
2002/0189457	A1	12/2002	Dallas et al.	
2003/0154863	A1	8/2003	Tokar et al.	
2004/0040271	A1	3/2004	Kopec et al.	
2004/0173097	A1	9/2004	Engelland et al.	
2004/0221555	A1	11/2004	Engelland et al.	
2004/0255781	A1	12/2004	Tokar et al.	
2005/0022669	A1	2/2005	Xu et al.	
2006/0123990	A1	6/2006	Tokar et al.	
2007/0186774	A1	8/2007	Gillingham et al.	
2007/0209343	A1	9/2007	Cuvelier	
2009/0199520	A1	8/2009	Mills et al.	
2010/0107577	A1	5/2010	Krisko et al.	
2010/0115897	A1	5/2010	Krisko et al.	
2010/0186353	A1	7/2010	Ackermann et al.	

FOREIGN PATENT DOCUMENTS

DE	39 36 837	A1	4/1991
DE	2155522		5/1993
DE	102 22 800	A1	12/2003
EP	0 376 443	A2	7/1990
EP	0 486 276	A1	5/1992
EP	0 492 250	A1	7/1992
EP	0 529 921	A1	3/1993
EP	0 581 695	A1	2/1994
EP	0 704 233	A1	4/1996
EP	0 726 389	A1	8/1996
EP	0 738 528	A2	10/1996
EP	1 159 052	B1	11/2003
EP	1 364 695	A1	11/2003
EP	1 509 311	B1	1/2007
EP	1 509 311	B2	12/2008
EP	1772 180	B1	11/2011
EP	2 275 188	B1	1/2012
EP	1 410 832	B2	4/2013
EP	1 795 246	B2	4/2013
GB	703823		2/1954
GB	1275651		5/1972
GB	2 106 634	A	4/1993
JP	S58-151417		3/1982

JP	59-26113		2/1984
JP	S60-155921		3/1984
JP	59-170669		11/1984
JP	H02-48118		9/1988
JP	1-11971		4/1989
JP	1-171615		7/1989
JP	9-234321		9/1997
JP	63-122617		6/1998
JP	H02-48117		9/1998
WO	WO 88/03431		5/1988
WO	WO 88/03432		5/1988
WO	WO 97/40908		11/1997
WO	WO 97/40910		11/1997
WO	WO 97/40917		11/1997
WO	WO 97/41939		11/1997
WO	WO 97/45200		12/1997
WO	WO 98/35144		8/1998
WO	WO 99/37381		7/1999
WO	WO 99/47237		9/1999
WO	WO 00/50149		8/2000
WO	WO 00/74818		12/2000
WO	WO 02/49741	A1	6/2002
WO	WO 03/095068	A1	11/2003
WO	WO 2005/037408	A1	4/2005
WO	WO 2005/107924	A2	11/2005
WO	WO 2008/067029	A1	6/2008
WO	WO 2009/106588	A1	9/2009
WO	WO 2009/106590	A1	9/2009

OTHER PUBLICATIONS

Response to the Notice of Opposition of European Patent 1 159 052 B1 (filed by Donaldson Company, Mar. 31, 2005).
 Decision Revoking the European Patent No. 1 159 052 dated Apr. 13, 2006.
 Grounds on Appeal for European Patent 1 159 052 B1 (filed by Donaldson Company, Aug. 13, 2006).
 Response to Grounds of Appeal for European Patent 1 159 052 B1 (filed by Baldwin Filters, Inc., Feb. 16, 2007).
 Decision of Appeal for European Patent 1 159 052 B1 dated Dec. 2, 2009.
 Declaration of Tom Miller dated Jun. 11, 2009.
 European Search Report cited in Application No. 10178236.5 dated Nov. 23, 2010.
 European Search Report cited in Application No. 10178875.0 dated Nov. 24, 2010.
 European Search Report cited in Application No. 07100191.1 dated Mar. 16, 2007.
 Jaroszczyk et al.; Recent Advances in Engine Air Cleaners Design and Evaluation; 2004; 17 pages.
 Thomas G. Miller, Statement Regarding Product; Dec. 23, 2010; 7 pages.
 Thomas G. Miller, Statement Regarding Product; Dec. 23, 2010; 10 pages.
 Notice of Opposition by Mann+Hummel against EP 1 509 311 B1 dated Nov. 14, 2007.
 Opposition Brief of Wittner & Muller against EP1509311 by Opposer Man + Hummel GmbH, dated Oct. 5, 2007, filed in European Patent Office (English Translation).
 Withdrawal by Mann+Hummel of Opposition against EP 1 509 311 B1 dated May 20, 2008.
 Response of Opposition against EP 1 509 311 B1 dated May 22, 2008.
 Decision of Opposition against EP 1 509 311 B1 dated Jun. 16, 2008.
 Notice of Opposition by Baldwin against EP 2 275 188 B1 dated Oct. 25, 2012.
 Grounds for Opposition by Baldwin against EP 2 275 188 B1 dated Oct. 17, 2012.
 Minutes of Oral Proceedings for EP 2 275 188 B1 dated Mar. 31, 2015.
 Decision for EP 2 275 188 B1 dated Mar. 31, 2015.
 Notice of Appeal by Baldwin against EP 2 275 188 B1 dated May 28, 2015.

(56)

References Cited

OTHER PUBLICATIONS

Grounds of Appeal by Baldwin against EP 2 275 188 B1 dated Jul. 29, 2015.

Appendix 1 to Grounds of Appeal dated Jul. 29, 2015.

Appendix 2 to Grounds of Appeal dated Jul. 29, 2015.

Appendix 3 to Grounds of Appeal dated Jul. 29, 2015.

Appendix 4 to Grounds of Appeal dated Jul. 29, 2015.

Appendix 5 to Grounds of Appeal dated Jul. 29, 2015.

Appendix 6 to Grounds of Appeal dated Jul. 29, 2015.

Response to Grounds of Appeal in EP 2 275 188 B1 dated Dec. 16, 2015.

Response Enclosure—O1=MA=EP 07 100 191.1.

Response Enclosure—EP 03 749 832.5.

Response Enclosure—Opponent's submission of Sep. 3, 2014.

Response Enclosure—Opponent's submission of Jan. 23, 2015.

Response Enclosure—Claims according to main request and auxiliary requests I-X (clean version).

Response Enclosure—Claims according to main request and auxiliary requests I-X (amended version).

Response Enclosure—Description version according to main request and auxiliary requests (clean version).

Response Enclosure—Description version according to main request and auxiliary requests (amended version).

* cited by examiner




FIG.1





FIG. 22







FIG. 3







FIG. 7

FIG. 8






FIG. 10





FIG. 11






FIG. 13











FIG. 14










FIG.26




FIG.27





FIG.28






FIG. 29

AIR FILTER HAVING FLUTED FILTER MEDIA

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of application Ser. No. 14/854,094, filed on Sep. 15, 2015, which is a continuation of application Ser. No. 14/022,399, filed on Sep. 10, 2013, now U.S. Pat. No. 9,162,172, which is a continuation of application Ser. No. 13/532,129, filed on Jun. 25, 2012, now U.S. Pat. No. 8,562,707, which is a continuation of application Ser. No. 13/214,913, filed on Aug. 22, 2011, now U.S. Pat. No. 8,206,479, which is a continuation of application Ser. No. 12/643,747, filed on Dec. 21, 2009, now U.S. Pat. No. 8,002,869, which is a continuation of application Ser. No. 12/135,742, filed on Jun. 9, 2008, now U.S. Pat. No. 7,635,403, which is a continuation of application Ser. No. 10/513,618, filed on Jun. 2, 2005, now U.S. Pat. No. 7,396,375, which application is a 371 of PCT/US03/14350, filed on May 8, 2003, which application claims the benefit of provisional application Ser. No. 60/379,824, filed on May 9, 2002, which applications are incorporated herein by reference in their entirety.

TECHNICAL FIELD

This disclosure concerns filter constructions for engines and methods of filtering and filter preparation. In particular, the disclosure describes Z-filter arrangements and side entry housings.

BACKGROUND

Gas streams often carry particulate material therein. In many instances, it is desirable to remove some or all of the particulate material from a gas flow stream. For example, air intake streams to engines for motorized vehicles or power generation equipment, gas streams directed to gas turbines, and air streams to various combustion furnaces, often include particulate material therein. The particulate material, should it reach the internal workings of the various mechanisms involved, can cause substantial damage thereto. It is therefore preferred, for such systems, to remove the particulate material from the gas flow upstream of the engine, turbine, furnace or other equipment involved. A variety of air filter or gas filter arrangements have been developed for particulate removal. In general, however, continued improvements are sought.

SUMMARY OF THE DISCLOSURE

An air cleaner includes a housing and an access cover. The internal volume of the housing can be reached through an opening in a wall of the housing. A filter element having fluted filter media is removable and replaceable from the air cleaner.

One example housing allows installation of the element by camming the element into sealing engagement with the housing. In one example of a camming system, there is a ramp to slide-mount the filter element therein.

One example housing includes a window to allow visual inspection of the internal components of the air cleaner.

One example access cover includes structure to help support and ensure proper seating of the filter element within the housing.

In one example embodiment, the filter element has a handle. Many different handles are useable. One particular handle includes a strap secured to the element. The strap is useful in aiding removal of the element from the housing.

A method of installing the filter element in the air cleaner includes sliding a portion of the filter element against a slide surface in the housing.

A method of servicing an air cleaner includes tilting the filter element against a tilt surface in the housing to release a seal between the filter element and the housing.

One example method of servicing includes applying a pull force to a strap secured to the element to release a seal between the filter element and the housing.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic view of one embodiment of a system in which air cleaners according to the present disclosure are used;

FIG. 2 is a perspective view of one embodiment of an air cleaner including a housing with a removable and replaceable filter element installed therein;

FIG. 3 is a side elevational view of the air cleaner depicted in FIG. 2, with a portion of the housing broken away to show the filter element operably installed therein;

FIG. 4 is a side elevational view of one embodiment of a filter element useable with the air cleaner depicted in FIGS. 2 and 3;

FIG. 5 is a top plan view of the filter element depicted in FIG. 4, the media being depicted schematically;

FIG. 6 is a fragmented, cross-sectional view showing a portion of the filter element, the cross-section being taken along the line 6-6 of FIG. 5;

FIG. 7 is a schematic, perspective view of a portion of filter media useable in the filter element depicted in FIGS. 4 and 5;

FIG. 8 is a perspective view of the air cleaner housing of FIGS. 2 and 3 with the service cover removed and with the filter element oriented for installation therein;

FIG. 9 is a side elevational view of the air cleaner depicted in FIGS. 2 and 3;

FIG. 10 is an end elevational view showing an inlet end of the air cleaner depicted in FIG. 9;

FIG. 11 is an end elevational view of the air cleaner depicted in FIG. 9 and showing an outlet end of the air cleaner;

FIG. 12 is a side elevational view of the housing cover used with the air cleaner of FIGS. 2, 3, and 9-11;

FIG. 13 is an end elevational view of the housing cover depicted in FIG. 12;

FIG. 14 is a cross-sectional view of the housing cover, the cross-section being taken along the line 14-14 of FIG. 13;

FIG. 15 is a perspective view of the housing body for the air cleaner depicted in FIGS. 2, 3, and 9-13;

FIG. 16 is a side elevational view of the interior portion of the housing body depicted in FIG. 15;

FIG. 17 is an end elevational view of the housing body depicted in FIGS. 15 and 16;

FIG. 18 is a top plan view of the housing body depicted in FIG. 15;

FIG. 19 is a side elevational view of the inlet construction used for the air cleaner housing depicted in FIGS. 2, 3, and 9-13;

FIG. 20 is a bottom plan view of the housing inlet construction depicted in FIG. 19;

FIG. 21 is a right end elevational view of the inlet construction depicted in FIG. 19;

FIG. 22 is an enlarged, perspective view showing a portion of the inlet construction interlocking with a portion of the air cleaner body;

FIG. 23 is a side elevational view of the outlet construction used with the air cleaner housing of FIGS. 2, 3, and 9-13;

FIG. 24 is a rear elevational view of the outlet construction depicted in FIG. 23;

FIG. 25 is a right end view of the outlet construction depicted in FIG. 23;

FIG. 26 is a schematic, fragmented, side elevational view showing the filter element interacting with the housing cover;

FIG. 27 is a side elevational view of an alternate embodiment of the air cleaner, the view being analogous to the view depicted in FIG. 3;

FIG. 28 is a view analogous to the view depicted in FIG. 26, but showing the alternate embodiment of FIG. 27; and

FIG. 29 is a perspective view of another embodiment of a filter element usable in the air cleaner of FIGS. 2, 3, and 8-28.

DETAILED DESCRIPTION

A. Example System and Overview of the Air Cleaner

Filter constructions and arrangements described herein are usable in a variety of systems. One particular type of system is depicted schematically in FIG. 1 generally at 30. In FIG. 1, equipment 32, such as a vehicle, having an engine 33 with some defined rated air flow demand, for example at least 50 cfm and up to 1800 cfm, is shown schematically. The equipment 32 may comprise a bus, an over-the-highway truck, an off-road vehicle, a tractor, a light-duty or medium duty truck, or a marine application such as a powerboat. The engine 33 powers the equipment 32, through use of an air and fuel mixture. In FIG. 1, air flow is shown drawn into the engine 33 at an intake region 35. An optional turbo 36 is shown in phantom, as optionally boosting the air intake into the engine 33. An air cleaner 40 having a filter construction 42 is upstream of the engine 33 and the turbo 36. In general, in operation, air is drawn in at arrow 44 into the air cleaner 40 and through the filter construction 42. There, particles and contaminants are removed from the air. The cleaned air flows downstream at arrow 46 into the intake 35. From there, the air flows into the engine 33 to power the equipment 32.

One embodiment of air cleaner 40 is shown now in FIGS. 2 and 3. In general, the air cleaner 40 includes a housing 48 with a removable and replaceable filter element 50. In preferred constructions, the housing 48 has a removable service cover 52. The service cover 52 allows access to an internal volume 54 of the housing 48 to permit servicing of the air cleaner 40. Servicing of the air cleaner 40 includes removal of the filter element 50 and installation and replacement of a new filter element 50 in the housing 48.

The housing 48 includes an inlet construction 56, an outlet construction 58, and a body member 60. In the preferred embodiment, the inlet construction 56, outlet construction 58, and body member 60 comprise a body construction 62. The cover 52 is removable and replaceable from the body construction 62. In the particular preferred embodiment illustrated, the cover 52 is removable from the body member 60.

In application, the inlet construction 56 forms an inlet end 64 to the housing 48, while the outlet construction 58 forms an outlet end 66 for the housing 48. The body member 60 comprises a side wall 68 extending between the inlet construction 56 and the outlet construction 58. The cover 52 is

removable from the body member 60 to provide an access opening 70 (FIG. 8) in the housing 48. The access opening 70 provides for a side entry 72 (FIG. 8) into the air cleaner 40.

In FIG. 3, the cover 52 is partially broken away to show the filter element 50 operably installed therein. By “operably installed” or variants thereof, it is meant that the filter element is oriented in the housing 48 such that there can be normal operation of the air cleaner 40 with air passing through the inlet construction 56, through the filter element 50, and out through the outlet construction 58. When operably assembled within the housing 48, the filter element 50 forms a seal 74 with the housing 48. In the particular embodiment shown, the seal 74 is formed with the outlet construction 58.

With that overview, we now turn to the various air cleaner components.

B. Filter Elements

1. Example Filter Element 50

A variety of filter elements may be used in accordance with this disclosure, including elements with depth media, tubular elements with pleated media, etc. One useable filter element 50 includes the types of filter elements described in U.S. Pat. No. 6,350,291 to Gieseke et al., incorporated by reference herein. With the exception of an additional band on the filter element 50 in this application, preferred elements are designated in accordance with the principles described in U.S. Pat. No. 6,350,291. In the embodiment shown, the filter element 50 is a filter element that allows for straight-through air flow. The particular illustrated embodiment utilizes fluted or Z-media 80.

In reference now to FIGS. 4 and 5, the filter element 50 shown includes a media pack 51 having first and second opposite ends 81, 82. At the first end, there is defined a first flow face 84, while the second 82 defines a second flow face 86. In the example shown, the first flow face 84 corresponds to an inlet end, while the second flow face 86 corresponds to an outlet end. The filter element 50 also includes a sealing system 88. In the preferred embodiment, the filter media 80 removes particulates from fluid, such as air, passing through the filter media 80, while the sealing system 88 seals the element 50 against the housing 48. By the term “seal”, it is meant that the sealing system 88, under normal conditions, prevents fluid from passing through a region between the media 80 and the housing 48; i.e., the sealing system 88 forces fluid to flow through the filter media 80 instead of bypass it.

The filter media 80 is configured for straight-through flow. That is, fluid to be filtered enters in one direction 90 through the first flow face 84 and exits in the same direction 91 from the second flow face 86. The filter media 80 is also referenced herein as “z-media.”

In the particular embodiment illustrated, the first flow face 84 and the second flow face 86 are depicted as planar and parallel. In other embodiments, the first flow face 84 and the second flow face 86 can be non-planar, for example, frusto-conical. Further, the first flow face 84 and the second flow face 86 can be slanted and not parallel to each other.

Generally, the filter element 50 will be a wound construction 87. That is, the construction 50 will typically include a layer of filter media that is turned completely or repeatedly about a center point. Typically, the wound construction 87 will be a coil, in that a layer of filter media will be rolled a series of turns around a center point. In arrangements where a wound, coiled construction is used, the filter element 50

5

will be a roll of filter media, typically permeable fluted filter media. In other implementations, the construction 50 is a stacked configuration.

Attention is now directed to FIG. 7. FIG. 7 is schematic, perspective view demonstrating the principles of operation of certain preferred media usable in the filter constructions herein. In FIG. 7, a fluted construction is generally designated at 94. Preferably, the fluted construction 94 includes: a layer 96 of corrugations having a plurality of flutes 98 and a face sheet 100. The FIG. 7 embodiment shows two sections of the face sheet 100, at 100A (depicted on top of the corrugated layer 96) and at 100B (depicted below the corrugated layer 96). Typically, the preferred media construction 102 used in arrangements described herein will include the corrugated layer 96 secured to the bottom face sheet 100B. When using this media construction 102 in a rolled construction, it typically will be wound around itself, such that the bottom face sheet 100B will cover the top of the corrugated layer 96. The face sheet 100 covering the top of the corrugated layer is depicted as 100A. It should be understood that the face sheet 100A and 100B are the same sheet 100.

When using this type of media construction 102, the flute chambers 98 preferably form alternating peaks 104 and troughs 106. The troughs 106 and peaks 104 divide the flutes into an upper row and lower row. In the particular configuration shown in FIG. 7, the upper flutes form flute chambers 108 closed at the downstream end, while flute chambers 110 having their upstream end closed form the lower row of flutes. The fluted chambers 110 are closed by a first end bead 112 that fills a portion of the upstream end of the flute between the fluting sheet 114 and the second facing sheet 100B. Similarly, a second end bead 113 closes the downstream end of alternating flutes 108.

When using media constructed in the form of media construction 102, during use, unfiltered fluid, such as air, enters the flute chambers 108 as indicated by the shaded arrows 116. The flute chambers 108 have their upstream ends 118 open. The unfiltered fluid flow is not permitted to pass through the downstream ends 120 of the flute chambers 108 because their downstream ends 128 are closed by the second end bead 113. Therefore, the fluid is forced to proceed through the fluting sheet 114 or face sheets 100. As the unfiltered fluid passes through the fluting sheet 114 or face sheets 100, the fluid is cleaned or filtered. The cleaned fluid is indicated by the unshaded arrow 124. The fluid then passes through the flute chambers 110 (which have their upstream ends 126 closed) to flow through the open downstream end 128 out the fluted construction 94. With the configuration shown, the unfiltered fluid can flow through the fluted sheet 114, the upper facing sheet 100A, or lower facing sheet 100B, and into a flute chamber 110.

A variety of ways can be used to coil or roll the media. In some preferred embodiments, the media construction 102 is wound about a center mandrel, which may be removed or left to plug to act as a core at the center of the filter element 50. It can be appreciated that non-round center winding members may be utilized for making filtering media shapes, such as filter media having an oblong, oval, rectangular, or racetrack-shaped profile. The media construction 102 can also be wound without a mandrel or center core. One process for making a coreless element 50 is described in U.S. Pat. No. 6,416,605, which is incorporated by reference herein.

While the flutes 98 depicted are shown as straight flutes, in other embodiments, it may be desired to have tapered flutes. Examples of tapered flutes are described in WO 97/40918, published 6 Nov. 1997, incorporated herein by

6

reference. Further, in some embodiments, the flutes can have deformed ends. Flutes with deformed ends are described in WO 97/40918, incorporated herein by reference.

In reference now to FIG. 5, a top plan view of the filter element 50 is shown. As can be seen in FIG. 5, the filter element 50 is a non-cylindrical construction. In particular, the filter element 50 has a race track configuration with a pair of parallel sides 130, 131 joined by a pair of arced or curved ends 132, 133. The flow face 86 is shown schematically; it should be understood that the entire flow face 86 will show the end of the media 102.

Still in reference to FIG. 4, the sealing system 88 includes a frame construction 134 and a seal member 136. The frame construction 134 provides a support structure or backing against which the seal member 136 can be compressed against to form seal 74 with the housing 48.

In the example shown in FIG. 6, the frame construction 134 includes a rigid projection 138 that projects or extends from at least a portion of the second flow face 86. In particular, the projection 138 extends axially from the second flow face 86. The projection 138 provides a support or backing to the seal member 136 such that seal 74 can be formed between and against the projection 138 and a sealing surface on the housing 48. When this type of construction is used, the projection 138 is a continuous member forming a closed ring 140. The seal member 136, in the one shown, engages an exterior portion of the ring 140. When this type of construction is used, the housing 48 circumscribes the projection 138 including the seal member 136 to form seal 74 between and against the projection 138 and the housing 48. In particular, the seal 74 is a radially directed seal 142 (FIG. 3).

Still in reference to FIGS. 4-6, the frame construction 134 includes a frame 144 that has a band, skirt, or depending lip 146. Preferably, an inside dimension of the depending lip 146 is approximately equal to the outside dimension of the wound filter construction 87. The depending lip 146 extends radially around the second flow face 86 of the filter construction 87. In particular, the lip 146 is secured to an outer periphery or outer annular portion 148 adjacent to the second flow face 86.

The filter element 50 defines an annular recess 150. In the preferred embodiment shown, the recess 150 is defined by a portion of the frame construction 134. In particular, the recess 150 is defined by an angled member 152 extending between the lip 146 and the projection 138. An end surface 154 of the seal member 136 also defines a portion of the recess 150. As explained below, the recess 150 receives a projection from the housing 48 to help stabilize the filter element 50 within the housing 48.

The frame 144 also preferably includes cross braces 156. Cross braces 156 support the frame 144 by helping to prevent the frame 144 from radially collapsing under the forces exerted around the circumference of the frame 144. The cross braces 156 depicted form a truss system 158 including a plurality of rigid struts 160, preferably molded as a single piece with remaining portions of the frame 144.

Attention is directed to FIG. 6. FIG. 6 is an enlarged, fragmented view of a particular preferred seal member 136 in an uncompressed state. In the embodiment shown, the seal member 136 is a stepped cross-sectional configuration of decreasing outermost dimensions from the first end 161 to a second end 162 to achieve desirable sealing. Preferred specifications for the seal member 136 include a polyurethane foam material having a plurality of (preferably, at least three) progressively larger steps configured to interface with the housing 48 to provide a fluid-tight seal. In the example

shown, the seal member 136 defines three steps 164, 165, 166. The cross-sectional dimension or width of the steps 164, 165, 166 increases the further the step is from the second end 162 of the seal member 136. The small dimension at the second end 162 allows for easy insertion into the housing 48. The larger dimension at the first end 161 insures a tight seal.

In reference again to FIG. 4, the filter element 50 further includes a frame or band 168 circumscribing the wound filter construction 87. Preferably, the band 168 is secured to the outer annular portion 148 of the element 50. In preferred embodiments, the band 168 is secured to the outer periphery 170 adjacent to the first flow face 84. The band 168 helps to provide a slide surface 172 for mounting the filter element 50 within the housing 48. Further, the band 168 helps to provide structure for stabilizing and supporting the filter element 50 when operably mounted in the housing 48. This can be seen in FIG. 26, for example. In FIG. 26, it can be seen how the band 168 engages the cover 52. This is explained further below.

2. Example Filter Element 500

In reference now to FIG. 29, another embodiment of a filter element 500 useable in the air cleaner 40 is shown at 500. The filter element 500 illustrated has the same features as the filter element 50, described above, including z-media 502, band 504, and seal member 506. The features of the z-media 502, band 504, and seal member 506 are analogous to the z-media 80, band 168, and seal member 136 described above, and are not repeated here. There is also a frame construction 508, which is similar to, but not identical to the frame construction 134 described above. The frame construction 508, in the illustrated embodiment, is modified from frame construction 134 in order to accommodate a handle.

The filter element 500 differs from the filter element 50 in that it has a handle 510 secured thereto to aid in servicing of the air cleaner 40. Many different embodiments of handle 510 are useable. One particular handle is illustrated as reference numeral 512. Handle 512 shown is a non-rigid, flexible strap 514. Strap 514 is secured to a part of the element 500. A number of different ways to secure the strap 514 can be used. In the illustrated embodiment, the strap 514 is secured to the frame construction 508. In preferred implementations, the strap 514 is secured to the lip 516 (analogous to lip 146). In the way shown in FIG. 29, the lip 516 defines a through-slot 518 and projecting tab 520. The strap 514 extends through the slot 518 and is held therein by engagement between a portion 522 of the strap 514 and the tab 520. In particular, the strap portion 522 includes a T-section 524 that is wider than the largest dimension of the slot 518, and thus, cannot pass through the slot 518. The T-section 524 engages the tab 520 to be secured in position.

The example, illustrated strap 514 also defines a plurality of apertures 526. The apertures 526 help to allow for a good grip by the user on the strap 514. In some embodiments, the strap 514 can be doubled over to form a closed loop. The term "strap" herein means single or multiple bands, belts, strips, as well as ones are folded or doubled-over to form closed loops. Materials useable for strap 514 include plastic, such as flexible nylon, and other flexible polymeric materials; of course, other materials can be used. The strap 514 can be many different sizes. One usable size includes: a length of at least 5 cm, for example 8-30 cm, including 10-20 cm; and a width of at least 0.5 cm, for example 0.75-10 cm, including 1-5 cm.

The handle 510 allows for exertion of a pull force on the element 500 in a direction about 70-110 degrees, usually

about 90 degrees, relative to the flow face 530. When the element 500 is installed in the housing 48, the handle 510 allows the pull force to be exerted on the element 500 to help release the seal 142 (FIG. 3) between the seal member 506 and sealing surface 176 (sealing surface 176 is described below). Once the seal 142 is released, the element 500 can be removed from the housing 48.

The element 500 is usable with the air cleaner 40, in the same way that the element 50 is, with the exception of removal of the element 50/500 from the air cleaner 40. The difference in the removal process relates to the use of the handle 510 that is present in element 500 and not in element 50. Otherwise, in all instances in this disclosure, when the element 50 is referenced, the element 500 is also useable and should be understood to be referenced by implication.

C. Example Housing 48

As mentioned above, preferred housings 48 will include body construction 62 and removable cover 52. Body construction 62 includes body member 60, inlet construction 56 and outlet construction 58.

It can be seen in FIG. 3 how the body construction 62 provides a sealing surface 176 against which the seal member 136 compresses to form radial seal 142. In the particular embodiment shown, the outlet construction 58 defines the sealing surface 176. In reference now to FIGS. 23-25, the outlet construction 58 is shown in detail. The particular embodiment of the outlet construction 58 shown includes an outlet construction housing 178. The housing 178 defines an interior volume 180 and an outlet port 182. The outlet port 182 is surrounded by a duct 184, which is typically connected to other ducting assembly. The housing 178 includes an outer rim 186 which connects to the body member 60. In preferred applications, the outlet construction housing 178 is secured in a permanent way to the body member 60, such as by hot plate welding. The rim 186 also provides for engagement with the service cover 52. The outlet construction housing 178 defines the sealing surface 176. The sealing surface 176 is an annular surface adjacent to the rim 186. Adjacent to the sealing surface 176 and angled thereto (preferably, orthogonally angled thereto), there is a stop surface 188. The stop surface 188 provides for an end surface for the seal member 136 to engage when the filter element 50 is properly seated within the housing 48.

Extending from an outer wall 190 of the sealing surface 176 is a mounting bracket 192. The mounting bracket 192 includes mounting apertures 193, 194 for accepting bolts or other mounting fasteners. The mounting bracket 192 is optionally usable to mount the air cleaner 40 onto equipment 32. As is described further, there is another mounting bracket on the inlet construction 56, which also may be used to mount the air cleaner 40. The provision of more than one mounting bracket on either the inlet construction 56 or outlet construction 58 provides for an ambidextrous air cleaner 40. That is, the air cleaner 40 can be mounted either at its inlet construction 56 or at its outlet construction 58.

In FIG. 11, an end view of the outlet construction 58 is viewable. The outlet construction 58, in preferred embodiments, includes provisions for a heat sensor 196; there is also a mount 198 available for a restriction indicator.

Attention is next directed to FIGS. 3, 10, and 19-21. One embodiment of an inlet construction 56 is illustrated. The inlet construction 56 shown includes an inlet construction housing 202 including an inlet duct 204 defining an inlet port 206. The inlet construction housing 202 further defines an internal volume 208. Circumscribing the internal volume 208 is an outer rim 210 which interacts with and engages with the body member 60 and the cover 52. In preferred

embodiments, the inlet construction housing 202 is secured in a permanent manner to the body member 60 by welding along the rim 210 to the body member 60.

Extending from the rim 210 is a mounting bracket 212. The mounting bracket 212, in the embodiment shown, is constructed identically to the bracket 192 on the outlet construction housing 178. The bracket 212 includes a flange 214 and first and second mounting apertures 215, 216. The apertures 215, 216 are for receiving suitable fasteners, such as bolts, for securing the bracket 212 and the housing 48 to the desired equipment 32. A mounting plate 219 extends from the rim 210 and is angled relative to the flange 214. Supporting the flange 214 is gusset structure 218 between the plate 219 and the flange 214.

Each of the mounting brackets 212 and 192 are constructed and arranged to slide and lock in place with the body member 60, which allows for adaptability in mounting locations and style. Attention is directed to FIG. 22. FIG. 22 is an enlarged view showing interaction between the inlet construction housing 202 and the body member 60. The bracket 212 defines a plurality of grooves 220. The grooves 220 receive tapered ribs 222 (FIG. 18) extending from a side wall 224 of the body member 60. As can be seen in FIG. 18, the ribs 222 taper or angle from a narrow section 226 to a wide section 228. The narrow section 226 is oriented closer to the inlet construction 56 than the wide section 228. The tapering of the ribs 222 allows for easier sliding in of the ribs 222 into the grooves 220, because the narrow section 226 is received first into the groove 220.

Attention is next directed to FIGS. 8 and 15-18. One embodiment of the body member 60 is illustrated. As mentioned above, the body member 60 includes side wall 224. In FIG. 17, it can be seen how the side wall 224 is curved in a shape that generally corresponds to the shape of the filter element 50. In this case, the side wall 224 is U-shaped. As such, the side wall 224 includes a bight section forming a closed end 234 and a mouth or open end 236. The open end 236 is sufficiently large enough to accommodate accepting the filter element 50 therethrough. The open end 236, in this embodiment, also corresponds to the side entry 72. The side wall 224 also defines an inlet end 238, which is mounted adjacent to the inlet construction 56 and an outlet end 240, which is mounted adjacent to the outlet construction 58. Edges 252, 254 extend between the inlet end 238 and the outlet end 240. A pair of mounting flanges 242, 243 extend from the side wall 224. The mounting flanges 242, 243 each include an aperture 244, 245 for receiving fasteners 246, 247 (FIG. 3) for removably securing the cover 52 to the body member 60.

The side wall 224 also includes a plurality of ribs 250 extending from edge 252 to edge 254, preferably continuously along the wall 224. The ribs 250 provide strength to the body member 60. Edge 252 and edge 254 define the mouth or open end 236. The edges 252, 254 also interact with and engage the cover 52.

The air cleaner 40 includes a system 259 for operably mounting the filter element 50 within the body construction 62. Generally, the air cleaner system 259 is constructed and arranged to cam the filter element 50 into sealing engagement with the housing. In one example, the system 259 includes a slide mount 260. The slide mount 260 enables the filter element 50 to be conveniently and smoothly inserted through the mouth or opening 236 and oriented with the seal member 136 compressed against the sealing surface 176 to form radial seal 142. A number of different implements are possible. In the particular implement illustrated in the drawings, the slide mount 260 includes a ramp 262. In the

preferred embodiment, the ramp 262 defines an angled slide surface 264, which angles downwardly from the open end 236 to the closed end 234. By the term “angled downwardly”, it is meant that the slide surface 264 is closer to the inlet end 238 at the open end 236 adjacent to the edges 252, 254 than the slide surface 264 is to the inlet end 238 at the bight section or closed end 234 of the side wall 224. This can be seen, for example, in FIG. 18. FIG. 18 is the exterior view of the ramp 262, but the shape of the ramp 262 can be seen as having the angled slide surface 264 angling from the closed end 234 to the open end 236. Another way of putting it is the ramp 262 is deepest at the closed end 234 forming deep ramp section 265, and narrowest at the open end 236 forming shallow ramp section 266. Between the open end 236 and the closed end 234, the ramp 262 forms a straight, and continuous slide surface 264.

The ramp 262 provides a camming surface for engaging the filter element 50 in order to urge or push the filter element 50 in place with the radial seal 142 formed with the housing 48. In particular, the ramp 262 translates the direction of the force applied to the filter element 50 from a force in a direction shown by arrow 268 (FIG. 8) (a lateral direction) directed toward the closed end 234 to a direction shown by arrow 270 (an axial direction) in a direction toward the outlet construction 58. In the preferred embodiment shown, the ramp 262 has a slope of less than 30 degrees, typically 5-25 degrees, and preferably 10-20 degrees.

In preferred embodiments, the band 168 on the filter element 50 is provided to engage and slide against the slide surface 264 in order to mount the filter element 50 into operable assembly in the housing 48.

Attention is next directed to FIGS. 3, 9, 12-14 and 26. The cover 52 is illustrated in various views. As mentioned above, the cover 52 is selectively removable from the body member 60 to selectively expose and cover the access opening 70. In this embodiment, the access opening 70 also corresponds to the mouth or the open end 236 of the body member 60. Although functionally the same, the cover 52 in FIGS. 9 and 26 differ somewhat from the cover shown in FIGS. 3 and 12-14 in that the cover 52 in FIGS. 9 and 26 have a portion for accommodating product labeling.

The cover 52 includes a curved side wall 276. In the embodiment shown in FIG. 13, the side wall 276 is generally C-shaped. The cover includes an inlet end 278, which is adjacent to the inlet construction 56; and opposite outlet end 280, which is adjacent to the outlet construction 58; and a pair of edges 282, 283 extending between the inlet end 278 and outlet end 280. The side wall 276 is preferably continuous and uninterrupted between the inlet end 278, outlet end 280, edge 282, and edge 283. Extending from each of the edges 282, 283 are mounting flanges 286, 288. The flanges 286, 288 are oriented to overlap with the flanges 242, 243 in the body member 60. The flanges 286, 288 accommodate fasteners 246, 247 for removably securing the cover 52 to the body member 60.

The side wall 276 includes a plurality of strengthening ribs 290, which extend from edge 282 continuously to edge 283. The ribs 290 are preferably evenly spaced apart from each other.

The cover 52 also includes a system for supporting and stabilizing the filter element 50. In one preferred embodiment, the side wall 276 of the cover 52 defines a shoulder or ledge 292. The ledge 292 comprises an annular surface 294 that extends from an element covering portion 296 of the side wall 276 to a neck 298. The neck 298 is adjacent to the inlet end 278 of the side wall 276, while the element

covering portion 296 is adjacent to the outlet end 280. The ledge 292 engages the filter element 50, in particular, the band 168 of the filter element 50. As such, the ledge 292 engages the band 168. FIG. 26 shows the band 168 engaged against the ledge 292.

It should be appreciated that the opposite end 302 (FIG. 8) of the element 50 is supported by engagement between the band 168 and the deep ramp section 265 at the closed end 234 of the body member 60.

The cover 52 also helps to support and keep the filter element 50 oriented in operable assembly seated with the seal 142 in place while in the housing 48. In particular, the cover 52 includes a projection 304 that extends or projects toward the interior volume 54 of the housing 48, when the cover 52 is operably mounted on the body member 60. In the orientation shown in FIG. 14, the projection 304 is hook-shaped or J-shaped. As can be seen in FIG. 26, the projection 304 extends into and out of the recess 150 in the filter element 50. By the term “into and out of”, it is meant that the projection 304 has a portion 306 that extends into the recess 150 as well as a portion 308 that leads from the portion 306 to the outside of the recess 150. As can be seen in FIG. 26, the portion 308 of the projection 304 is adjacent to and below the end surface 154 of the seal member 136.

In use, after the filter element 50 (or 500) is operably assembled into the body construction 62, the cover 52 is oriented over the exposed portion of the filter element 50 and mounted to the body member 60. If the filter element 50 is not properly seated within the housing 48 with the radial seal 142 formed, the cover 52 will be precluded or prevented from fitting or properly mounting to the body member 60. If the filter element 50 is properly mounted within the body construction 62, the cover 52 is guided to the proper mount by way of engagement between the band 168 and the ledge 292. Further, the projection 304 will be received by the recess 150 in the filter element 50. Also, the mounting flanges 286, 288 will match with the flanges 242, 243 so that the fasteners 246, 247 can be mounted therein.

FIGS. 27 and 28 show an alternate embodiment of the cover 52, depicted as 52'. A method for visually identifying the presence of the filter element 50 within the housing 48 without removal of the cover is provided by including a window 320 in the housing 48. The window 320 is oriented such that the filter element 50 is viewable through the window 320, when the filter element is installed within the housing 48. While the window 320 can be placed in many locations, in the particular illustrated embodiment, the window 320 is located in the cover 52'. In the illustrated embodiment, the window 320 includes a clear lens 322 snap-fit into an aperture 324 in the sidewall 276' of the cover 52'. The lens 322 can be made from durable, clear materials, such as polycarbonates. In preferred applications, the exterior of the filter element 50 is a bright color so that the element 50 is highly visible through the window 320. For Donaldson Company, the assignee of this disclosure, the color is also preferably source-indicative, so that the user knows the element 50 used is a Donaldson filter element. Donaldson blue would be preferred for Donaldson. The window 320 shown has a round shape (a circle), but in other embodiments, the window 320 can be other shapes such as irregular, polygon, rectangular, starburst, swirl, etc.

D. Methods of Use, Installing, and Servicing

To install the filter element 50 into the housing 48, the cover 52 is removed from the body construction 62 to expose the access opening 70. The filter element 50 is oriented such that the second end 82 of the element 50 is adjacent to the outlet construction 58, while the first end 81

is oriented adjacent to the inlet construction 56. The band 168 is oriented such that it engages the ramp 262. The filter element 50 is slid through the side entry 72 along the slide mount 260 in the direction of arrow 268. Engagement of the slide surface 264 against the band 168 moves the filter element in a direction toward the outlet construction 58 to urge the seal member 136 against the sealing surface 176 of the outlet construction 58. Eventually, the filter element 50 reaches the closed end 234 and the deep ramp section 265. At this point, the seal member 136 should be in place forming the radial seal 142 between and against the sealing surface 176 of the housing 48 and the rigid projection 138 on the frame construction 134 of the filter element 50. The cover 52 is then oriented over the exposed portion of the filter element 50. The ledge 292 engages the band 168 to support the filter element 50, while the projection 304 extends into and is received by the recess 150 in the filter element 50. The fasteners 246, 247 are inserted to connect the cover 52 to the body member 60. The air cleaner 40 is then ready for filtering operation.

To use the air cleaner 40, dirty air passes through the intake region 35 (FIG. 1), into ducting, and eventually through the inlet duct 204 of the inlet construction 56. The air then flows to the filter element 50 and passes through the first flow face 84. The dirty air is then forced to flow through the filter media 80, where the air is at least partially cleaned of particulate material. The clean air exits the filter element 50 by flowing from the second flow face 86. From there, the clean air flows through the outlet construction 58 and through the outlet duct 184. The clean air is then used by equipment 32, such as in an internal combustion engine 33.

After a period of operation, the filter element 50 will become clogged or occluded with an unacceptably high level of restriction. Servicing of the air cleaner 40 will become necessary. By “servicing”, it is meant removal of the filter element 50 and replacement with a new filter element 50.

To service the air cleaner 40, the cover 52 is removed from the housing 48 by removing the fasteners 246, 247. The cover 52 is removed to expose the access opening 70 defined by the mouth or open end 236 of the body member 60. The old filter element 50/500 is then removed from the housing 48 through the access opening 70. This is done by, first, releasing or breaking the seal 142 between the filter element 50/500 and the housing 48. For the element 50, the seal 142 is released by holding the exposed edge of the filter element 50 and applying a force in the direction of the inlet construction 56. For the element 500, the strap 514 is grasped by a user's hand, and a pull force is exerted about 90 degrees relative to the flow face 530 (e.g., in a direction toward the inlet construction 56). For element 50 or 500, when a force is applied in this direction, the band 168 engages against the deep section 265 of the ramp 262. This allows the filter element 50/500 to tilt about the pivot region created by the engagement between the band 168 and the deep section 265 of the ramp 262. This tilting action pulls the filter element 50/500 from the sealing surface 176 to release the radial seal 142. The filter element 50/500 can then be removed through the side entry 72 outside of the air cleaner 40.

The old filter element 50/500 is then disposed of. A second, new filter element 50/500 is provided. The new filter element 50/500 is installed in the air cleaner 40 by mounting it through the side entry 72 and sliding the element 50/500 in operable assembly within the housing 48. The cover 52 is then placed over the exposed portion of the filter element 50/500 and secured to the body member 60.

E. General Principles and Examples

In general, there is provide a method of servicing an air cleaner, the air cleaner including a filter element installed in a housing; the method comprising: tilting the filter element against a tilt surface in the housing to release a seal between the filter element and the housing; the filter element having first and second opposite flow faces; the filter element including media having a plurality of flutes; each of the flutes having an upstream portion adjacent to the first flow face and a downstream portion adjacent to the second flow face; selected ones of the flutes being open at the upstream portion and closed at the downstream portion; and selected ones of the flutes being closed at the upstream portion and open at the downstream portion.

The step of tilting the filter element against a tilt surface in the housing to release a seal includes releasing a radial seal between the filter element and housing.

After the step of tilting, there is a step of removing the filter element through an opening in a side of the housing.

After the step of removing, providing a second filter element and installing the second filter element in the housing; the second filter element having first and second opposite flow faces; the second filter element including media having a plurality of flutes; each of the flutes having an upstream portion adjacent to the first flow face and a downstream portion adjacent to the second flow face; selected ones of the flutes being open at the upstream portion and closed at the downstream portion; and selected ones of the flutes being closed at the upstream portion and open at the downstream portion.

The housing includes a ramp; the ramp forming a portion of the tilt surface; and the step of installing includes sliding a portion of the second filter element against the ramp in the housing to form a seal between a seal member on the second filter element and a sealing surface in the housing.

Before the step of tilting, there is a step of removing a cover from a side in the housing to expose an opening in the side of the housing.

After the step of installing, there is a step placing a cover over the opening in the housing.

After the step of placing a cover, viewing the filter element in the housing through a window in one of the cover and the housing.

The step of tilting the filter element against a tilt surface includes exerting a pull force to the element in a direction about 70-110 degrees relative to the second flow face. In one example, the element is pulled in a direction about 90 degrees relative to the second flow face.

The step of exerting a pull force includes pulling a handle secured to the filter element.

The step of pulling a handle includes pulling a flexible strap secured to the filter element.

The filter element includes a frame construction mounted thereon; and the step of pulling a flexible strap includes pulling a flexible strap secured to the frame construction.

A filter element is provided. One useable filter element includes a media pack having first and second opposite flow faces; the media pack including media having a plurality of flutes; each of the flutes having an upstream portion adjacent to the first flow face and a downstream portion adjacent to the second flow face; selected ones of the flutes being open at the upstream portion and closed at the downstream portion; and selected ones of the flutes being closed at the upstream portion and open at the downstream portion; a seal member secured to the media pack; and a flexible strap secured to a portion of the filter element.

A frame construction is mounted on the media pack; the frame construction supporting the seal member; the flexible strap being secured to the frame construction.

The frame construction has a lip mounted on an end thereof and an extension projecting axially from the second flow face; the seal member being supported by the extension of the frame construction; the flexible strap is secured to the lip of the frame construction.

The lip defines a through-slot; and the flexible strap extends through the through-slot.

An air cleaner is provided comprising: a housing having first and second opposite ends and a sidewall between the first and second ends; in some embodiments, the first end comprises an air inlet end and the second end comprising an air outlet end; the sidewall defining an access opening; an access cover removably positioned over the access opening; and a filter element operably installed in the housing; the filter element having first and second opposite flow faces; the filter element including media having a plurality of flutes; each of the flutes having an upstream portion adjacent to the first flow face and a downstream portion adjacent to the second flow face; selected ones of the flutes being open at the upstream portion and closed at the downstream portion; and selected ones of the flutes being closed at the upstream portion and open at the downstream portion; the housing being constructed and arranged to accept the filter element through the access opening in the sidewall and to cam the filter element into sealing engagement with the housing.

In one embodiment, the housing sidewall includes a slide mount to cam the filter element into sealing engagement with the housing. In some embodiments, the slide mount is in the form a ramp in the sidewall.

The access cover includes a projection extending within a recess defined by the filter element.

The filter element includes a seal member and a frame construction; the frame construction having an extension projecting axially from the second flow face; the seal member being supported by the extension of the frame construction; the seal member being compressed between and against the extension of the frame construction and the housing to form a radial seal.

The recess in the filter element is adjacent to the seal member.

The filter element includes a band around a periphery of the first flow face; and the access cover includes a ledge engaging the band to support the filter element.

The access cover includes a ledge extending toward an internal volume in the housing; and the filter element is supported at the first flow face by the ramp and by the ledge on the access cover.

The filter element includes a band around a periphery of the first flow face; the band engaging the ramp and the ledge.

The access cover includes a window to provide visual access to an internal volume of the housing.

An air cleaner is provided comprising a housing having first and second opposite ends and a sidewall between the first and second ends; and a filter element operably installed in the housing; the filter element having first and second opposite flow faces; the filter element including media having a plurality of flutes; each of the flutes having an upstream portion adjacent to the first flow face and a downstream portion adjacent to the second flow face; selected ones of the flutes being open at the upstream portion and closed at the downstream portion; and selected ones of the flutes being closed at the upstream portion and open at the downstream portion; the filter element including a seal-

15

ing gasket adjacent to the second flow face; the filter element defining a peripheral recess adjacent to the sealing gasket; the housing including a projection extending into and out of the peripheral recess.

The filter element includes a frame construction; the frame construction having a lip mounted on an end thereof and an extension projecting axially from the second flow face; the sealing gasket being supported by the extension of the frame construction; the sealing gasket being compressed between and against the extension of the frame construction and the housing to form a radial seal; the peripheral recess being defined by the frame construction and being between the lip and the extension.

The filter element includes a band around a periphery of the first flow face; and the housing includes a ledge engaging the band to support the filter element.

A method of installing a filter element into an air cleaner housing is provided; the method including: orienting a filter element in a housing body; the filter element having first and second opposite flow faces; the filter element including media having a plurality of flutes; each of the flutes having an upstream portion adjacent to the first flow face and a downstream portion adjacent to the second flow face; selected ones of the flutes being open at the upstream portion and closed at the downstream portion; and selected ones of the flutes being closed at the upstream portion and open at the downstream portion; the filter element defining a recess in an outer, annular portion of the filter element; forming a seal between the filter element and the housing body; and orienting a cover member over the housing body; the cover member including a projection; the step of orienting a cover member including placing the projection to extend into and out of the recess in the filter element.

A housing construction is provided comprising: a housing wall; the housing wall including a duct defining a fluid port; the housing wall having a rim; a mounting bracket extending from the rim of the wall; the bracket including: a flange defining a fastener-receiving aperture arrangement; a mounting plate extending between the flange and the rim; the flange being angled relative to the flange; the mounting plate defining a plurality of rib-receiving grooves; and a gusset arrangement between the mounting plate and the flange to support the flange.

The wall further defines an annular sealing surface adjacent to the rim, and an end stop surface angled adjacent thereto.

An engine having a rated air flow of at least 50 cfm and an air intake; and an air cleaner construction mounted in airflow communication with the air intakes provided; the air cleaner construction including a housing having first and second opposite ends and a sidewall between the first and second ends; the sidewall defining an access opening and a ramp extending from the opening toward a closed portion of the housing; an access cover removably positioned over the access opening; and a filter element operably installed in the housing; the filter element having first and second opposite flow faces; the filter element including media having a plurality of flutes; each of the flutes having an upstream portion adjacent to the first flow face and a downstream portion adjacent to the second flow face; selected ones of the flutes being open at the upstream portion and closed at the downstream portion; and selected ones of the flutes being closed at the upstream portion and open at the downstream portion.

A method for detecting the presence of a filter element within an air cleaner is provided; the method comprising:

16

visually inspecting an air cleaner housing with a cover mounted thereon; and viewing through a window in either the cover or the housing to determine whether a filter element is visible through the window in the housing.

What is claimed is:

1. A filter element comprising:

- (a) a filter media construction defining a first flow face and a second flow face, wherein the first flow face and the second flow face are on opposite ends of the filter media construction;
 - (i) the filter media construction having filter media including a plurality of flutes extending between the first and second opposite flow faces;
 - (ii) the filter media construction comprising a combination of a fluted media sheet adhered to a facing media sheet and arranged to form the plurality of flutes extending from the first flow face to the second flow face;
 - (iii) the filter media construction allowing air to pass through the first flow face and through the second flow face; the filter media construction being closed to passage of unfiltered air therethrough, without passage through the fluted media sheet or the facing media sheet;
- (b) the filter media construction having an outer periphery and a non-cylindrical configuration comprising two opposite curved ends and a pair of sides extending between the two opposite curved ends;
- (c) a first frame construction extending from one of the first flow face or the second flow face of the filter media construction, and forming two opposite curved ends and a pair of sides extending between the two opposite curved ends;
- (d) a seal member secured to the first frame construction and supported by the first frame construction to form a radially directed seal against a housing seal surface; and
- (e) a second frame construction extending around the outer periphery of the filter media construction at the other of the first flow face or the second flow face opposite the first frame construction, and forming two opposite curved ends and a pair of sides extending between the two opposite curved ends, wherein:
 - (i) the second frame construction has an L shaped outer surface formed by a first portion and a second portion, the first portion extending around the outer periphery of the filter media construction, and the second portion extending from the first portion over a portion of the other of the first flow face or the second flow face opposite the first frame construction.

2. A filter element according to claim 1 wherein:

- (a) one of the pair of sides extending between the opposite curved ends of the filter media construction is a straight side.

3. A filter element according to claim 1 wherein:

- (a) both of the pair of sides extending between the opposite curved ends of the filter media construction are straight sides.

4. A filter element according to claim 1 wherein:

- (a) the filter media construction is racetrack shaped.

5. A filter element according to claim 1 wherein:

- (a) the second frame construction includes a first part extending around the outer periphery of the filter media construction, and a second part extending over the first flow face or the second flow face.

17

6. A filter element according to claim 1, further comprising:
- (a) a structure extending along the outer periphery of the filter media construction.
7. A filter element according to claim 6 wherein:
- (a) the structure extending along the outer periphery of the filter media construction comprises a flexible strap.
8. A filter element according to claim 1 wherein:
- (a) one of the pair of sides of the first frame construction extending from one of the first flow face or the second flow face of the filter media construction is a straight side.
9. A filter element according to claim 1 wherein:
- (a) both of the pair of sides of the first frame construction extending from one of the first flow face or the second flow face of the filter media construction are straight sides.
10. A filter element according to claim 1 wherein:
- (a) one of the pair of sides of the second frame construction extending around the outer periphery of the filter media construction is a straight side.
11. A filter element according to claim 1 wherein:
- (a) both of the pair of sides of the second frame construction extending around the outer periphery of the filter media construction are straight sides.
12. A filter element according to claim 1 wherein:
- (a) the second frame construction extending around the outer periphery of the filter media construction is constructed to engage a slide surface on a housing.
13. A filter element according to claim 1 wherein:
- (a) the filter media construction comprises at least one wound construction of the fluted sheet and the facing sheet.
14. A filter element comprising:
- (a) a filter media construction defining a first flow face and a second flow face, wherein the first flow face and the second flow face are on opposite ends of the filter media construction;
- (i) the filter media construction having filter media including a plurality of flutes extending between the first and second opposite flow faces;
- (ii) the filter media construction comprising a combination of a fluted media sheet adhered to a facing media sheet and arranged to form the plurality of flutes extending from the first flow face to the second flow face;
- (iii) the filter media construction allowing air to pass through the first flow face and through the second flow face; the filter media construction being closed to passage of unfiltered air therethrough, without passage through the fluted media sheet or the facing media sheet;
- (b) the filter media construction having an outer periphery and a non-cylindrical configuration comprising two opposite curved ends and a pair of sides extending between the two opposite curved ends;
- (c) a first frame construction extending from one of the first flow face or the second flow face of the filter media construction, and forming two opposite curved ends and a pair of sides extending between the two opposite curved ends;
- (d) a seal member secured to the first frame construction and supported by the first frame construction; and
- (e) a second frame construction extending around the outer periphery of the filter media construction at the other of the first flow face or the second flow face opposite the first frame construction, and forming two

18

- opposite curved ends and a pair of sides extending between the two opposite curved ends, wherein:
- (i) the second frame construction has an L shaped outer surface formed by a first portion and a second portion, the first portion extending around the outer periphery of the filter media construction, and the second portion extending from the first portion over a portion of the other of the first flow face or the second flow face opposite the first frame construction.
15. An air cleaner comprising:
- (a) a housing having an inlet end, an opposite outlet end, and a sidewall extending between the inlet end and the outlet end;
- (i) the sidewall defining an access opening to provide for entry into an internal volume of the housing; the access opening being between the inlet end and the outlet end;
- (ii) the housing defining a housing seal surface; and
- (b) a filter element having a seal member; the filter element being operably installed in the housing and forming a seal therewith; the filter element comprising:
- (i) a filter media construction defining a first flow face and a second flow face, wherein the first flow face and the second flow face are on opposite ends of the filter media construction;
- (A) the filter media construction having filter media including a plurality of flutes extending between the first and second opposite flow faces;
- (B) the filter media construction comprising a combination of a fluted media sheet adhered to a facing media sheet and arranged to form the plurality of flutes extending from the first flow face to the second flow face;
- (C) the filter media construction allowing air to pass through the first flow face and through the second flow face; the filter media construction being closed to passage of unfiltered air therethrough, without passage through the fluted media sheet or the facing media sheet;
- (ii) the filter media construction having an outer periphery and a non-cylindrical configuration comprising two opposite curved ends and a pair of sides extending between the two opposite curved ends;
- (iii) a first frame construction extending from one of the first flow face or the second flow face of the filter media construction, and forming two opposite curved ends and a pair of sides extending between the two opposite curved ends;
- (iv) the seal member secured to the first frame construction and supported by the first frame construction to form a directed seal against the housing seal surface; and
- (v) a second frame construction extending around the outer periphery of the filter media construction at the other of the first flow face or the second flow face opposite the first frame construction, and forming two opposite curved ends and a pair of sides extending between the two opposite curved ends.
16. An air cleaner according to claim 15 wherein:
- (a) said housing sidewall is U-shaped forming a closed end of the housing.
17. An air cleaner according to claim 15 wherein:
- (a) said housing sidewall includes a ramp.

19

18. An air cleaner according to claim **17** wherein:
 (a) the ramp forms a shallow ramp section adjacent to the access opening and a deep ramp section adjacent to the closed end of the housing.

19. An air cleaner according to claim **15** wherein:
 (a) the frame construction includes an extension projecting axially from the second flow face; the seal member being supported by the extension of the frame construction; and the seal member forming a radial seal with the housing seal surface when the filter element is operably installed in the housing.

20. An air cleaner according to claim **15** wherein:
 (a) the access cover includes a system to support the filter element when the filter element is operably installed in the housing.

21. An air cleaner according to claim **17** wherein:
 (a) the second frame construction extending around the outer periphery of the media pack construction is constructed to engage the ramp when installing the filter element in the housing.

22. An air cleaner according to claim **15** wherein:
 (a) one of the pair of sides extending between the opposite curved ends of the filter media construction is a straight side.

23. An air cleaner according to claim **15** wherein:
 (a) both of the pair of sides extending between the opposite curved ends of the filter media construction are straight sides.

24. An air cleaner according to claim **15** wherein:
 (a) the filter media construction is racetrack shaped.

25. An air cleaner according to claim **15** wherein:
 (a) the second frame construction includes a first part extending around the outer periphery of the filter media construction, and a second part extending over the first flow face or the second flow face.

20

26. An air cleaner according to claim **15**, further comprising:

(a) a structure extending along the outer periphery of the filter media construction.

27. An air cleaner according to claim **26** wherein:

(a) the structure extending along the outer periphery of the filter media construction comprises a flexible strap.

28. An air cleaner according to claim **15** wherein:

(a) one of the pair of sides of the first frame construction extending from one of the first flow face or the second flow face of the filter media construction is a straight side.

29. An air cleaner according to claim **15** wherein:

(a) both of the pair of sides of the first frame construction extending from one of the first flow face or the second flow face of the filter media construction are straight sides.

30. An air cleaner according to claim **15** wherein:

(a) one of the pair of sides of the second frame construction extending around the outer periphery of the filter media construction is a straight side.

31. An air cleaner according to claim **15** wherein:

(a) both of the pair of sides of the second frame construction extending around the outer periphery of the filter media construction are straight sides.

32. An air cleaner according to claim **15** wherein:

(a) the second frame construction extending around the outer periphery of the filter media construction is constructed to engage a slide surface on a housing.

33. An air cleaner according to claim **15** wherein:

(a) the filter media construction comprises at least one wound construction of the fluted sheet and the facing sheet.

* * * * *