

(12) **United States Patent**
Baumann et al.

(10) **Patent No.:** **US 10,557,412 B2**
(45) **Date of Patent:** **Feb. 11, 2020**

(54) **SYSTEMS FOR REDUCING DEFLECTION OF A SHROUD THAT RETAINS FAN EXIT STATORS**

(58) **Field of Classification Search**
CPC .. F02C 7/055; F02C 7/045; F02C 7/05; F01D 5/24; F01D 11/122; F01D 21/045
See application file for complete search history.

(71) Applicant: **UNITED TECHNOLOGIES CORPORATION**, Farmington, CT (US)

(56) **References Cited**

(72) Inventors: **Paul W. Baumann**, Amesbury, MA (US); **Brian Barainca**, Kennebunk, MA (US); **Rolf Thorsen**, Deep River, CT (US); **Mark E. Simonds**, Cape Neddick, ME (US); **Gary F. Fowler**, Strafford, NH (US); **Hector M. Pinero**, Middletown, CT (US)

U.S. PATENT DOCUMENTS

3,326,523 A 6/1967 Bobo
4,720,236 A * 1/1988 Stevens F01D 9/042 415/116

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **UNITED TECHNOLOGIES CORPORATION**, Farmington, CT (US)

DE 102013017713 4/2015
EP 2204539 7/2010
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 303 days.

OTHER PUBLICATIONS

European Patent Office, European Search Report dated Oct. 11, 2018 in Application No. 18174032.5-1006.

(21) Appl. No.: **15/608,547**

(22) Filed: **May 30, 2017**

Primary Examiner — Joseph J Dallo
Assistant Examiner — Kurt Philip Liethen

(65) **Prior Publication Data**

US 2018/0347465 A1 Dec. 6, 2018


(57) **ABSTRACT**

(51) **Int. Cl.**
F02C 7/055 (2006.01)
F01D 21/04 (2006.01)
F01D 11/12 (2006.01)
F01D 5/24 (2006.01)
F02C 7/045 (2006.01)
F02C 7/05 (2006.01)

An outer diameter shroud for retaining a stator of a gas turbine engine having an axis includes an annular body positioned around the axis, extending in an axial direction, and defining a plurality of slots each configured to receive a portion of one of a plurality of stators. The outer diameter shroud further includes a shroud flange coupled to the annular body, extending in a direction perpendicular to the annular body, and configured to be fastened to a case of the gas turbine engine.

(52) **U.S. Cl.**
CPC **F02C 7/055** (2013.01); **F01D 5/24** (2013.01); **F01D 11/122** (2013.01); **F01D 21/045** (2013.01); **F02C 7/045** (2013.01); **F02C 7/05** (2013.01)

19 Claims, 5 Drawing Sheets



References Cited

6,409,472	B1 *	6/2002	McMahon	F01D 5/3023 415/119
6,655,912	B2	12/2003	Bos	
6,910,860	B2 *	6/2005	Glover	F01D 9/042 415/191
8,459,944	B2	6/2013	Hamana	
8,696,311	B2	4/2014	Eleftheriou et al.	
8,966,756	B2 *	3/2015	Feigleson	F01D 9/042 29/458
8,998,574	B2	4/2015	Menheere et al.	
9,506,361	B2	11/2016	Fielding et al.	
0/0034648	A1 *	2/2010	Robertson	F01D 25/28 415/199.4
11/0110783	A1 *	5/2011	Addis	B23P 6/005 416/219 R
4/0169972	A1 *	6/2014	Suciu	F01D 5/225 416/189
5/0118039	A1 *	4/2015	Aschenbruck	F01D 25/246 415/209.2
5/0377123	A1 *	12/2015	Adams	F02K 3/06 60/805
6/0290168	A1	10/2016	Karafilis et al.	

FR	2961850	12/2011
WO	0046489	8/2000
WO	2014105573	7/2014

* cited by examiner




FIG.1




FIG.2




FIG.3




FIG.4




FIG. 5




FIG. 6





FIG.7



1

SYSTEMS FOR REDUCING DEFLECTION OF A SHROUD THAT RETAINS FAN EXIT STATORS

FIELD

The present disclosure is directed to systems for reducing deflection of a shroud of a gas turbine engine and, more particularly, to systems for reducing deflection of an outer diameter shroud that retains fan exit stators of a gas turbine engine.

BACKGROUND

Gas turbine engines include a compressor section, a turbine section, and a combustor section. Many gas turbine engines also include a fan that is driven by the turbine section. The fan generates a core airflow that is received by the compressor section and a bypass airflow that bypasses the compressor, turbine, and combustor sections and generates thrust. A set of stators called fan exit stators may be located upstream from the compressor and may condition the core airflow. It is undesirable for the stators to become dislodged in response to ingestion of an object, such as a bird, in the core airflow.

SUMMARY

Disclosed herein is an outer diameter shroud for retaining a stator of a gas turbine engine having an axis. The outer diameter shroud includes an annular body positioned around the axis, extending in an axial direction, and defining a plurality of slots each configured to receive a portion of one of a plurality of stators. The outer diameter shroud further includes a shroud flange coupled to the annular body, extending in a direction perpendicular to the annular body, and configured to be fastened to a case of the gas turbine engine.

In any of the foregoing embodiments, the plurality of stators includes fan exit stators configured to condition a core airflow received from a fan section of the gas turbine engine.

Any of the foregoing embodiments may further include a flange transition that is curved, extends from the annular body to the shroud flange, and has a flange transition thickness that is greater than a body thickness of the annular body and is also greater than a flange thickness of the shroud flange.

In any of the foregoing embodiments, the case is a front center body of the gas turbine engine.

In any of the foregoing embodiments, the shroud flange is coupled to an aft end of the annular body and formed integrally with the annular body.

Any of the foregoing embodiments may further include a lip extending axially forward from the annular body away from the shroud flange, and a lip transition that is curved, extends from the annular body to the lip, and has a lip transition thickness that is greater than a body thickness of the annular body and is also greater than a lip thickness of the lip.

Any of the foregoing embodiments may further include a bracket extending from the shroud flange away from the annular body in the axial direction, the bracket formed integrally with the shroud flange and configured to be coupled to a splitter of the gas turbine engine.

2

In any of the foregoing embodiments, the annular body has a body axial length that is greater than an edge axial length of an outer diameter edge of each of the plurality of stators.

5 In any of the foregoing embodiments, the annular body has a forward end and an aft end that is positioned nearer the axis than the forward end.

10 In any of the foregoing embodiments, the shroud flange defines a plurality of fastener holes configured to receive fasteners for fastening the shroud flange to the case of the gas turbine engine.

15 Also described is a system for retaining a stator of a gas turbine engine having an axis. The system includes an outer diameter shroud having an annular body defining a plurality of slots each configured to receive a portion of one of a plurality of stators, and a bayonet extending aft from the annular body and defining a bayonet slot. The system further includes an annular case having a case body and a hook that 20 includes a first portion configured to be received by the bayonet slot and a second portion configured to extend over a portion of the outer diameter shroud to resist radially outward movement of the outer diameter shroud relative to the axis.

25 In any of the foregoing embodiments, the first portion is a radial portion extending radially outward from the case body and the second portion is an axial portion extending axially forward from the radial portion, the radial portion configured to be received by the bayonet slot and the axial portion configured to extend over the annular body.

30 In any of the foregoing embodiments, the first portion is a radial portion extending radially outward from the case body and the second portion is a circumferential portion extending in a circumferential direction from the radial portion, the radial portion configured to be received by the slot and the circumferential portion configured to extend over the bayonet.

35 In any of the foregoing embodiments, the annular case is a front center body of the gas turbine engine.

40 In any of the foregoing embodiments, the plurality of stators includes fan exit stators configured to condition a core airflow received from a fan section of the gas turbine engine.

45 In any of the foregoing embodiments, the outer diameter shroud includes a forward outer diameter shroud and an aft outer diameter shroud, and the bayonet is coupled to the aft outer diameter shroud.

50 Also described is a system for retaining a stator of a gas turbine engine having an axis. The system includes an outer diameter shroud having an annular shape and defining a plurality of slots each configured to receive a portion of one of a plurality of stators. The system further includes an annular case configured to be coupled to the outer diameter shroud. The system further includes a band configured to be positioned radially outward from the outer diameter shroud and to contact the outer diameter shroud to resist radially outward movement of the outer diameter shroud relative to the axis.

55 In any of the foregoing embodiments, wherein the outer diameter shroud includes either a single-piece outer diameter shroud such that the band is configured to contact the single-piece outer diameter shroud, or a combination of a forward outer diameter shroud and an aft outer diameter shroud such that the band is configured to contact the aft outer diameter shroud.

In any of the foregoing embodiments, the band is further configured to be positioned radially outward from the annular case and to contact the annular case and the outer diameter shroud.

In any of the foregoing embodiments, the plurality of stators includes fan exit stators configured to condition a core airflow received from a fan section of the gas turbine engine and the annular case is a front center body of the gas turbine engine.

The foregoing features and elements may be combined in various combinations without exclusivity, unless expressly indicated otherwise. These features and elements as well as the operation thereof will become more apparent in light of the following description and the accompanying drawings. It should be understood, however, the following description and drawings are intended to be exemplary in nature and non-limiting.

BRIEF DESCRIPTION OF THE DRAWINGS

Various features will become apparent to those skilled in the art from the following detailed description of the disclosed, non-limiting, embodiments. The drawings that accompany the detailed description can be briefly described as follows:

FIG. 1 is a cross-sectional view of an exemplary gas turbine engine, in accordance with various embodiments;

FIG. 2 is a cross-sectional view of a portion of the gas turbine engine of FIG. 1, in accordance with various embodiments;

FIG. 3 is a perspective view of an outer diameter shroud and a plurality of fan exit stators of a gas turbine engine, in accordance with various embodiments;

FIG. 4 is a cross-sectional view of the outer diameter shroud of FIG. 3, in accordance with various embodiments;

FIG. 5 is a perspective view of an aft outer diameter shroud and a front center body of a gas turbine engine having an axial hook for reducing deflection of the outer diameter shroud, in accordance with various embodiments;

FIG. 6 is a perspective view of an aft outer diameter shroud and a front center body of a gas turbine engine having a circumferential hook for reducing deflection of the outer diameter shroud, in accordance with various embodiments; and

FIG. 7 is a perspective view of a system for reducing deflection of an outer diameter shroud, the system including a band positioned radially outward from the outer diameter shroud, in accordance with various embodiments.

DETAILED DESCRIPTION

All ranges and ratio limits disclosed herein may be combined. It is to be understood that unless specifically stated otherwise, references to “a,” “an,” and/or “the” may include one or more than one and that reference to an item in the singular may also include the item in the plural.

The detailed description of various embodiments herein makes reference to the accompanying drawings, which show various embodiments by way of illustration. While these various embodiments are described in sufficient detail to enable those skilled in the art to practice the disclosure, it should be understood that other embodiments may be realized and that logical, chemical, and mechanical changes may be made without departing from the spirit and scope of the disclosure. Thus, the detailed description herein is presented for purposes of illustration only and not of limitation. For example, the steps recited in any of the method or process

descriptions may be executed in any order and are not necessarily limited to the order presented. Furthermore, any reference to singular includes plural embodiments, and any reference to more than one component or step may include a singular embodiment or step. Also, any reference to attached, fixed, connected, or the like may include permanent, removable, temporary, partial, full, and/or any other possible attachment option. Additionally, any reference to without contact (or similar phrases) may also include reduced contact or minimal contact. Cross hatching lines may be used throughout the figures to denote different parts but not necessarily to denote the same or different materials.

As used herein, “aft” refers to the direction associated with the exhaust (e.g., the back end) of a gas turbine engine.

As used herein, “forward” refers to the direction associated with the intake (e.g., the front end) of a gas turbine engine. An A-R-C axis is shown in various drawings to illustrate the axial, radial, and circumferential directions, respectively.

As used herein, “radially outward” refers to the direction generally away from the axis of rotation of a turbine engine.

As used herein, “radially inward” refers to the direction generally towards the axis of rotation of a turbine engine.

In various embodiments and with reference to FIG. 1, a gas turbine engine 20 is provided. The gas turbine engine 20 may be a two-spool turbofan that generally incorporates a fan section 22, a compressor section 24, a combustor section 26 and a turbine section 28. Alternative engines may include, for example, an augmentor section among other systems or features. In operation, the fan section 22 can drive coolant (e.g., air) along a bypass flow path B while the compressor section 24 can drive coolant along a core flow path C for compression and communication into the combustor section 26 then expansion through the turbine section 28. Although depicted as a two-spool turbofan gas turbine engine 20 herein, it should be understood that the concepts described herein are not limited to use with two-spool turbofans as the teachings may be applied to other types of turbine engines including turbojet, turboprop, turboshaft, or power generation turbines, with or without geared fan, geared compressor or three-spool architectures.

The gas turbine engine 20 may generally comprise a low speed spool 30 and a high speed spool 32 mounted for rotation about an engine central longitudinal axis X-X' relative to an engine static structure 36 or engine case via several bearing systems 38, 38-1, and 38-2. It should be understood that various bearing systems 38 at various locations may alternatively or additionally be provided, including for example, the bearing system 38, the bearing system 38-1, and the bearing system 38-2.

The low speed spool 30 may generally comprise an inner shaft 40 that interconnects a fan 42, a low pressure compressor 44 and a low pressure turbine 46. The inner shaft 40 may be connected to the fan 42 through a geared architecture 48 that can drive the fan 42 at a lower speed than the low speed spool 30. The geared architecture 48 may comprise a gear assembly 60 enclosed within a gear housing 62. The gear assembly 60 couples the inner shaft 40 to a rotating fan structure. The high speed spool 32 may comprise an outer shaft 50 that interconnects a high pressure compressor 52 and high pressure turbine 54. A combustor 26 may be located between high pressure compressor 52 and high pressure turbine 54. A mid-turbine frame 57 of the engine static structure 36 may be located generally between the high pressure turbine 54 and the low pressure turbine 46. Mid-turbine frame 57 may support one or more bearing systems 38 in the turbine section 28. The inner shaft 40 and the outer shaft 50 may be concentric and rotate via bearing

systems **38** about the engine central longitudinal axis X-X', which is collinear with their longitudinal axes. As used herein, a "high pressure" compressor or turbine experiences a higher pressure than a corresponding "low pressure" compressor or turbine.

The airflow of core flow path C may be received and conditioned by a fan exit stator **70**. After conditioning, the airflow of core flow path C may be compressed by the low pressure compressor **44** then the high pressure compressor **52**, mixed and burned with fuel in the combustor **26**, then expanded over the high pressure turbine **54** and the low pressure turbine **46**. The turbines **46**, **54** rotationally drive the respective low speed spool **30** and high speed spool **32** in response to the expansion.

The gas turbine engine **20** may be, for example, a high-bypass ratio geared engine. In various embodiments, the bypass ratio of the gas turbine engine **20** may be greater than about six (6). In various embodiments, the bypass ratio of the gas turbine engine **20** may be greater than ten (10). In various embodiments, the geared architecture **48** may be an epicyclic gear train, such as a star gear system (sun gear in meshing engagement with a plurality of star gears supported by a carrier and in meshing engagement with a ring gear) or other gear system. The geared architecture **48** may have a gear reduction ratio of greater than about 2.3 and the low pressure turbine **46** may have a pressure ratio that is greater than about five (5). In various embodiments, the bypass ratio of the gas turbine engine **20** is greater than about ten (10:1). In various embodiments, the diameter of the fan **42** may be significantly larger than that of the low pressure compressor **44**, and the low pressure turbine **46** may have a pressure ratio that is greater than about five (5:1). The low pressure turbine **46** pressure ratio may be measured prior to the inlet of the low pressure turbine **46** as related to the pressure at the outlet of the low pressure turbine **46** prior to an exhaust nozzle. It should be understood, however, that the above parameters are exemplary of various embodiments of a suitable geared architecture engine and that the present disclosure contemplates other gas turbine engines including direct drive turbofans. A gas turbine engine may comprise an industrial gas turbine (IGT) or a geared engine, such as a geared turbofan, or non-geared engine, such as a turbofan, a turboshaft, or may comprise any gas turbine engine as desired.

In various embodiments, the low pressure compressor **44**, the high pressure compressor **52**, the low pressure turbine **46**, and the high pressure turbine **54** may comprise one or more stages or sets of rotating blades and one or more stages or sets of stationary vanes axially interspersed with the associated blade stages but non-rotating about engine central longitudinal axis X-X'. The compressor and turbine sections **24**, **28** may be referred to as rotor systems. Within the rotor systems of the gas turbine engine **20** are multiple rotor disks, which may include one or more cover plates or minidisks. Minidisks may be configured to receive balancing weights or inserts for balancing the rotor systems.

Referring now to FIGS. 1 and 2, the static structure, or case, **36** may include a front center body (FCB) **100**. The FCB **100** may provide structural support for various components of the gas turbine engine **20**.

The gas turbine engine **20** may further include a splitter **102** designed to split the airflow from the fan section **22** into the core airflow C and the bypass airflow B. As shown, the core airflow is received by the plurality of fan exit stators **70** which are located at an inlet to the core of the gas turbine engine **20**.

An outer diameter shroud **104** may be located radially outward from the fan exit stators **70** and may retain the fan

exit stators **70** in place relative to the case **36**. In that regard, the outer diameter shroud **104** may be coupled to a portion of the case **36**, such as the FCB **100**. The outer diameter shroud **104** may further be coupled to the splitter **102**.

Because the outer diameter shroud **104** may retain the fan exit stators **70** in place, the fan exit stators **70** may undesirably become dislodged in response to sufficient radially outward deflection of the outer diameter shroud **104**. In that regard, it is desirable to reduce radially outward deflection of the outer diameter shroud **104**.

In various embodiments, the outer diameter shroud **104** may be a single piece or may include a forward outer diameter shroud **106** and an aft outer diameter shroud **108** coupled to the forward outer diameter shroud **106**. As described above, it is desirable for the outer diameter shroud **104** to resist movement in the radially outward direction which may occur, for example, during a bird strike (i.e., when a bird is ingested into the core airflow C).

Referring now to FIG. 3, an outer diameter shroud **202** may be coupled to a case of a gas turbine engine, such as a FCB **210**. The outer diameter shroud **202** may include features designed to resist radially outward movement.

The annular body **204** may extend in the axial direction and define a plurality of slots **206**. Each of the plurality of slots **206** may be designed to receive a portion of one of a plurality of stators **200**, such as fan exit stators. For example, each of the plurality of slots **206** may be designed to receive an outer diameter end of one of the plurality of stators **200**. In various embodiments, each of the plurality of stators **200** may be double potted, such as with a rubber potting or a polyurethane potting. In that regard, potting may cause the stators **200** to remain in place relative to an inner diameter shroud and the outer diameter shroud **202**.

The shroud flange **208** may extend in the radial direction and be designed to be coupled to the FCB **210**. For example, the shroud flange **208** may be designed to be fastened to the FCB **210** at case flanges **212** of the FCB **210**. As shown in FIG. 3, fasteners **218**, such as screws, bolts, rivets, or the like, may extend through fastener holes **216** of the shroud flange **208** and each of the case flanges **212** to fasten the shroud flange **208** to the FCB **210**.

The shroud flange **208** may extend around the entire circumference of the outer diameter shroud **202**. This design feature provides increased rigidity to the outer diameter shroud **202** at circumferential locations away from the locations of the fasteners **218**, thus reducing potential deflection of the outer diameter shroud **202** in response to contact with an object.

The single integral annular body **204** of the outer diameter shroud **202** provides additional rigidity over designs that include a forward outer diameter shroud and an aft outer diameter shroud. Outer diameter shrouds that include multiple pieces may have a forward outer diameter shroud that deflects at the junction with the aft outer diameter shroud due to the type of coupling. This type of deflection may tend to be prevented by use of a single outer diameter shroud.

The outer diameter shroud **202** may further include a plurality of brackets including a bracket **214**. The bracket **214** may extend aft from the radially outward end of the shroud flange **208** and may be foil led integral with the shroud flange **208** or may be a separate component from the shroud flange **208**. In that regard, the bracket **214** may extend from the shroud flange **208** in a direction away from the annular body **204**. The bracket **214** may be designed to be fastened to a splitter of a gas turbine engine.

Referring to FIG. 4, additional features of the outer diameter shroud **202** are shown. In particular, the annular

body **204** has a forward end **300** and an aft end **302**. The shroud flange **208** is coupled to the aft end **302** of the annular body **204** and a flange transition **304** is located at the junction of the shroud flange **208** and the annular body **204**.

The annular body **204** has a body thickness **308**, and the shroud flange **208** has a flange thickness **310**. The flange transition **304** includes a flange transition thickness **306** that is greater than the body thickness **308** and the flange thickness **310**. This feature increases rigidity of the annular body **204**, resulting in a tendency for reduced deflection of the annular body **204** in response to contact with an object.

The outer diameter shroud **202** further includes a lip **312** extending axially forward from the forward end **300** of the annular body **204**. The lip **312** may be formed integral with the other components of the outer diameter shroud **202**. The outer diameter shroud **202** may further include a lip transition **314** at the junction of the forward end **300** of the annular body **204** and the lip **312**. The lip **312** may have a lip thickness **318** and the lip transition **314** may have a lip transition thickness **316**. The lip transition thickness **316** may be greater than the lip thickness **318** and the body thickness **308**. The relatively large thickness of the lip transition **314** increases rigidity of the annular body **204**, resulting in reduced deflection of the annular body **204** in response to contact with an object.

The annular body **204** may have a body axial length **320**, and an outer diameter edge **322** of one of the plurality of stators **200** may have an edge axial length **324**. The body axial length **320** may be greater than the edge axial length **324** of the outer diameter edge **322** of the stators **200**. In that regard, the annular body **204** may comprise a single integral piece of material which, as described above, increases rigidity of the annular body **204** relative to an outer diameter shroud having multiple components coupled together.

Turning now to FIG. 5, a system **403** that includes an outer diameter shroud **400** and an annular case **410** (such as a FCB) may include various features for reducing radial deflection of the outer diameter shroud **400**. The outer diameter shroud **400** includes multiple pieces including an aft outer diameter shroud **401**. The aft outer diameter shroud **401** includes an annular body **402** that defines a plurality of slots **404** each designed to receive a portion of a stator, such as a fan exit stator. The aft outer diameter shroud **401** further includes a bayonet **406** extending axially aft from the annular body **402**. The bayonet **406** defines a bayonet slot **408** which may be a circumferential slot.

The annular case **410** includes a case body **412** and a hook **414**. The hook **414** includes a first portion **416** and a second portion **418**. The first portion **416** of the hook **414** may be referred to as a radial portion **417** as it extends away from the case body **412** in the radial direction. The radial portion **417** is designed to be received by the bayonet slot **408** to couple the aft outer diameter shroud **401** to the annular case **410**.

The second portion **418** of the hook **414** may be referred to as an axial portion **419** as it extends away from the case body **412** in the axially forward direction. The axial portion **419** is designed to extend over a portion of the aft outer diameter shroud **401** in the axial direction. Stated differently, the axial portion **419** is designed to be positioned radially outward from and contact a portion of the aft outer diameter shroud **401**. In various embodiments, the hook **414** may be used with a single-piece outer diameter shroud to resist deflection of the single-piece outer diameter shroud.

Contact between the axial portion **419** and the aft outer diameter shroud **401** resists radially outward movement of the aft outer diameter shroud **401**. In that regard, the axial

portion **419** may be said to resist outward radial deflection of the aft outer diameter shroud **401** in response to contact with an object.

Similar advantages may be achieved by using hooks having different shapes. For example and referring to FIG. 6, a system **503** that includes an outer diameter shroud **500** and an annular case **510** (such as a FCB) may include various features for reducing radial deflection of the outer diameter shroud **500**. The outer diameter shroud **500** includes multiple pieces including an aft outer diameter shroud **501**. The aft outer diameter shroud **501** includes an annular body **502** that defines a plurality of slots **504** each designed to receive a stator, such as a fan exit stator. The aft outer diameter shroud **501** further includes a bayonet **506** extending axially aft from the annular body **502**. The bayonet **506** defines a bayonet slot **508** which may be a circumferential slot.

The annular case **510** includes a case body **512** and a hook **514**. The hook **514** includes a first portion **516** and a second portion **518**. The first portion **516** of the hook **514** may be referred to as a radial portion **517** as it extends away from the case body **512** in the radial direction. The radial portion **517** is designed to be received by the bayonet slot **508** in order to couple the aft outer diameter shroud **501** to the annular case **510**. A hook may include any object having a first portion extending in a first direction and a second portion extending in a second direction that is different than the first direction.

The second portion **518** of the hook **514** may be referred to as a circumferential portion **519** as it extends away from the radial portion **517** in a circumferential direction. The circumferential portion **519** is designed to extend over a portion of the bayonet **506** in the circumferential direction. Stated differently, the circumferential portion **519** is designed to be positioned radially outward from and contact a portion of the bayonet **506**.

Contact between the circumferential portion **519** and the bayonet **506** resists radially outward movement of the bayonet **506**. Because the bayonet **506** is coupled to the annular body **502**, the contact between the circumferential portion **519** and the bayonet **506** resists radially outward movement of the aft outer diameter shroud **501**. In that regard, the circumferential portion **519** may be said to resist outward radial deflection of the aft outer diameter shroud **501** in response to contact with an object.

Referring to FIG. 7, a system **601** for reducing radial deflection of an outer diameter shroud **600** is shown. The system **601** includes the outer diameter shroud **600**, an annular case **608** (such as a FCB), and a band **610**. The outer diameter shroud **600** may include a forward outer diameter shroud **602** and an aft outer diameter shroud **604**. The outer diameter shroud **600** includes a plurality of slots **606** each designed to receive one of a plurality of stators **612**, such as fan exit stators.

The band **610** is positioned radially outward from a portion of the outer diameter shroud **600** and a portion of the case **608**. The band **610** may contact one or both of the forward outer diameter shroud **602** or the aft outer diameter shroud **604**. In various embodiments, the band **610** may be used with a single-piece outer diameter shroud to resist deflection of the single-piece outer diameter shroud. As shown in FIG. 7, the band **610** contacts the aft outer diameter shroud **604** and the case **608**. Contact between the band **610** and the outer diameter shroud **600** resists radially outward movement of the outer diameter shroud **600**. In that regard,

the band **610** may be said to resist radial deflection of the outer diameter shroud **600** in response to contact with an object.

The band **610** may include any of a plurality of materials such as a plastic, a rubber, silicone, a metal, or the like. The band **610** may extend around the entire circumference of the outer diameter shroud **600**. The band **610** may further define a plurality of openings **614** each designed to be aligned with the one of a plurality of tabs **616** of the outer diameter shroud **600**. The tabs **616** may, for example, be used to couple the outer diameter shroud **600** to a splitter of a gas turbine engine.

While the disclosure is described with reference to exemplary embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted without departing from the spirit and scope of the disclosure. In addition, different modifications may be made to adapt the teachings of the disclosure to particular situations or materials, without departing from the essential scope thereof. The disclosure is thus not limited to the particular examples disclosed herein, but includes all embodiments falling within the scope of the appended claims.

Benefits, other advantages, and solutions to problems have been described herein with regard to specific embodiments. Furthermore, the connecting lines shown in the various figures contained herein are intended to represent exemplary functional relationships and/or physical couplings between the various elements. It should be noted that many alternative or additional functional relationships or physical connections may be present in a practical system. However, the benefits, advantages, solutions to problems, and any elements that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as critical, required, or essential features or elements of the disclosure. The scope of the disclosure is accordingly to be limited by nothing other than the appended claims, in which reference to an element in the singular is not intended to mean “one and only one” unless explicitly so stated, but rather “one or more.” Moreover, where a phrase similar to “at least one of a, b, or c” is used in the claims, it is intended that the phrase be interpreted to mean that a alone may be present in an embodiment, b alone may be present in an embodiment, c alone may be present in an embodiment, or that any combination of the elements a, b and c may be present in a single embodiment; for example, a and b, a and c, b and c, or a and b and c. Different cross-hatching is used throughout the figures to denote different parts but not necessarily to denote the same or different materials.

Systems, methods and apparatus are provided herein. In the detailed description herein, references to “one embodiment”, “an embodiment”, “an example embodiment”, etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to affect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described. After reading the description, it will be apparent to one skilled in the relevant art(s) how to implement the disclosure in alternative embodiments.

Furthermore, no element, component, or method step in the present disclosure is intended to be dedicated to the public regardless of whether the element, component, or method step is explicitly recited in the claims. No claim element herein is to be construed under the provisions of 35 U.S.C. 112(f), unless the element is expressly recited using the phrase “means for.” As used herein, the terms “comprises”, “comprising”, or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus.

What is claimed is:

1. A system for retaining stators of a gas turbine engine having an axis, the outer diameter shroud comprising:
 - an annular body positioned around the axis, extending in an axial direction, and defining a plurality of slots each configured to receive a portion of one of a plurality of stators;
 - a shroud flange coupled to the annular body, extending in a direction perpendicular to a tangent of the annular body, and configured to be fastened to a case of the gas turbine engine; and
 - a stator being double potted and having an outer diameter end configured to be received by one of the plurality of slots defined by the annular body.
2. The system of claim 1, wherein the plurality of stators includes fan exit stators configured to condition a core airflow received from a fan section of the gas turbine engine.
3. The system of claim 1, further comprising a flange transition that is curved, extends from the annular body to the shroud flange, and has a flange transition thickness that is greater than a body thickness of the annular body and is also greater than a flange thickness of the shroud flange.
4. The system of claim 1, wherein the case is a front center body of the gas turbine engine.
5. The system of claim 1, wherein the shroud flange is coupled to an aft end of the annular body and formed integrally with the annular body.
6. The system of claim 5, further comprising:
 - a lip extending axially forward from the annular body away from the shroud flange; and
 - a lip transition that is curved, extends from the annular body to the lip, and has a lip transition thickness that is greater than a body thickness of the annular body and is also greater than a lip thickness of the lip.
7. The system of claim 1, further comprising a bracket extending from the shroud flange away from the annular body in the axial direction, the bracket formed integrally with the shroud flange and configured to be coupled to a splitter of the gas turbine engine.
8. The system of claim 1, wherein the annular body has a body axial length that is greater than an edge axial length of an outer diameter edge of each of the plurality of stators.
9. The system of claim 1, wherein the annular body has a forward end and an aft end that is positioned nearer the axis than the forward end.
10. The system of claim 1, wherein the shroud flange defines a plurality of fastener holes configured to receive fasteners for fastening the shroud flange to the case of the gas turbine engine.
11. A system for retaining a stator of a gas turbine engine having an axis, the system comprising:
 - an outer diameter shroud having:

11

- an annular body defining a plurality of slots each configured to receive a portion of one of a plurality of stators, and
- a bayonet extending aft from the annular body and defining a bayonet slot that extends circumferentially; and
- an annular case having a case body and a hook that includes a first portion configured to be received by the bayonet slot and a second portion configured to extend over a portion of the outer diameter shroud to resist radially outward movement of the outer diameter shroud relative to the axis axis,
- wherein the first portion is a radial portion extending radially outward from the case body and the second portion is an axial portion extending axially forward from the radial portion, the radial portion configured to be received by the bayonet slot and the axial portion configured to extend over the annular body.
- 12.** The system of claim **11**, wherein the first portion is a radial portion extending radially outward from the case body and the further comprising a stator being double potted and having an outer diameter end configured to be received by one of the plurality of slots defined by the annular body.
- 13.** The system of claim **11**, wherein the annular case is a front center body of the gas turbine engine.
- 14.** The system of claim **11**, wherein the plurality of stators includes fan exit stators configured to condition a core airflow received from a fan section of the gas turbine engine.
- 15.** The system of claim **11**, wherein the outer diameter shroud includes a forward outer diameter shroud and an aft outer diameter shroud, and the bayonet is coupled to the aft outer diameter shroud.

12

- 16.** A system for retaining stators of a gas turbine engine having an axis, the system comprising:
- an outer diameter shroud having an annular shape and defining a plurality of slots each configured to receive a portion of one of a plurality of stators;
- an annular case configured to be coupled to the outer diameter shroud;
- a stator being double potted and having an outer diameter end configured to be received by one of the plurality of slots defined by the annular body; and
- a band configured to be positioned radially outward from the outer diameter shroud and to contact the outer diameter shroud to resist radially outward movement of the outer diameter shroud relative to the axis.
- 17.** The system of claim **16**, wherein the outer diameter shroud includes either a single-piece outer diameter shroud such that the band is configured to contact the single-piece outer diameter shroud, or a combination of a forward outer diameter shroud and an aft outer diameter shroud such that the band is configured to contact the aft outer diameter shroud.
- 18.** The system of claim **16**, wherein the band is further configured to be positioned radially outward from the annular case and to contact the annular case and the outer diameter shroud.
- 19.** The system of claim **16**, wherein the plurality of stators includes fan exit stators configured to condition a core airflow received from a fan section of the gas turbine engine and the annular case is a front center body of the gas turbine engine.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION


PATENT NO. : 10,557,412 B2
APPLICATION NO. : 15/608547
DATED : February 11, 2020
INVENTOR(S) : Paul W. Baumann

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claim 11 - In Column 11, Line 12 please delete the first “axis”.

Signed and Sealed this
Sixth Day of October, 2020

A handwritten signature in black ink, appearing to read "Andrei Iancu", written in a cursive style.

Andrei Iancu
Director of the United States Patent and Trademark Office