

(12)

United States Patent

Moran et al.

(10) Patent No.:

US 10,580,014 B2

(45) Date of Patent:

Mar. 3, 2020

(54)

SYSTEM AND METHOD FOR PAYMENT CARD INDUSTRY COMPLIANCE

7,769,176 B2 \*

8/2010

Watson

.....

G06Q 20/3674

380/200

(71)

Applicant: Avaya Inc., Santa Clara, CA (US)

7,774,854 B1 \*

8/2010

Watson

.....

G06F 21/6209

726/26

(72)

Inventors: Thomas J. Moran, Co. Galway (IE); Gerard Carty, Co. Galway (IE)

8,401,155 B1 \*

3/2013

Barnes

.....

H04M 3/51

370/352

(73)

Assignee: Avaya Inc., Santa Clara, CA (US)

8,861,707 B2 \*

10/2014

Beckett, II

.....

H04M 3/5175

379/100.05

(\*)

Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 747 days.

9,185,219 B2 \*

11/2015

Kumar

.....

H04M 3/5166

2006/0126817 A1 \*

6/2006

Beckett, II

.....

H04M 3/5175

379/265.06

2007/0201675 A1 \*

8/2007

Nourbakhsh

.....

H04M 3/5175

379/265.01

2013/0110565 A1 \*

5/2013

Means, Jr.

.....

G06Q 10/06

705/7.11

(21) Appl. No.: 14/302,643

(22) Filed: Jun. 12, 2014

(65) Prior Publication Data

US 2015/0363789 A1 Dec. 17, 2015

(51) Int. Cl.

G06Q 30/00 (2012.01)

H04M 3/51 (2006.01)

(52) U.S. Cl.

CPC ..... G06Q 30/018 (2013.01); G06Q 30/016 (2013.01); H04M 3/5175 (2013.01)

(58) Field of Classification Search

CPC .... G06Q 30/018; G06Q 30/016; G06Q 10/10; G16H 10/40; G16H 10/60; H04L 63/0421; G06F 2201/84; G06F 11/3438

USPC ..... 705/314, 304; 345/545

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

6,646,655 B1 \* 11/2003 Brandt ..... H04N 5/06 348/E5.011

7,236,632 B2 \* 6/2007 Erol ..... G06F 17/30256 382/218

(Continued)

OTHER PUBLICATIONS

Kendrick, Scott, “10 Keys to PCI Compliance in the Call Center,” Engagement Optimization, Apr. 18, 2014, [online], available at: <<https://callminer.com/blog/5-keys-pci-compliance-call-center/>>. (Year: 2014).\*

(Continued)

Primary Examiner — Minnah L Seoh

Assistant Examiner — Richard W. Crandall

(57) ABSTRACT

A system for providing Payment Card Industry (PCI) compliance for a contact center is disclosed. The system includes a monitoring module configured to monitor a communication session between an agent and a customer. At least one image associated with the agent’s computer screen is captured during the communication session. An analysis module is configured to compare the at least one image with at least one predefined image. A control module is configured to control a recording of information associated with the communication session based on the comparison.

11 Claims, 6 Drawing Sheets

```

graph TD
    Start([Start]) --> 504[Monitor a communication session between an agent and a customer]
    504 --> 508{Communication session ended?}
    508 -- Yes --> End([End])
    508 -- No --> 512[Capture at least one image associated with the agent's computer]
    512 --> 516[Compare the at least one image with at least one predefined image]
    516 --> 520[Determine a confidence score based on the comparison]
    520 --> 524{The confidence score meets predetermined criteria?}
    524 -- Yes --> 532[Pause the recording of information associated with the communication session]
    524 -- No --> 528[Record information associated with the communication session]
    532 --> 504
    528 --> 504
  
```

(56)

**References Cited**

U.S. PATENT DOCUMENTS

2015/0281436 A1 \* 10/2015 Kumar ..... H04M 3/5166  
379/68

OTHER PUBLICATIONS

PCI and DSS Call Recording, “Why is PCI Compliance such a big issue for contact centres?” [online], archived on Mar. 31, 2014, available at: < <https://web.archive.org/web/20140331222918/https://www.callcentrehelper.com/pci-dss-and-call-recording-57184.htm> >, last accessed Oct. 31, 2019. (Year: 2014).\*

\* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B


400

FIG. 4






FIG. 5



## 1

**SYSTEM AND METHOD FOR PAYMENT  
CARD INDUSTRY COMPLIANCE**

## BACKGROUND

## Field

Embodiments of the present invention generally relate to a system and method for providing Payment Card Industry (PCI) compliance and particularly to a system and method for providing the PCI compliance using image recognition.

## Description of Related Art

Contact centers are employed by many enterprises to service inbound and outbound contacts from customers. A typical contact center includes a switch and/or server to receive and route incoming packet-switched and/or circuit-switched contacts and one or more resources, such as human agents and automated resources (e.g., Interactive Voice Response (IVR) units), to service the incoming contacts or work items. Contact centers distribute contacts, whether inbound or outbound, for servicing to any suitable resource according to predefined criteria.

Usually, a contact center has many agents who handle queries from customers. Each agent has an associated agent machine for use of the agent. Each agent machine has recording capability for monitoring service quality of the agent. The agent machine may be a personal computer, a laptop, a palmtop, a mobile device, and the like. The agent machine may include a client screen recording application that continuously records activity of the agent on the client machine. Further, the agent machine may include a client desktop analysis application that monitors in focus screens of applications being used at the agent machine. The agent machine may include a manual recording control application which can be used by the agent to manually pause and resume recording of a communication.

A contact center that handles information related to payment cards needs to comply with PCI regulations. The PCI regulations require sensitive information associated with payment cards to be protected from all internal or external agents. For example, information such as a credit card number must not be recorded or saved by the enterprise while still recording other information being exchanged between the customer and the agent for service quality purposes.

Existing solutions deploy a client application (for example, a manual recording control application) on each agent machine that monitors agent activity on the agent machine and on a call with a customer. The client application can be used to pause and resume recording of a call between the customer and the agent based on a manual trigger from the agent. To comply with the PCI regulations, the agent manually stops recording of the call when the call involves exchange of sensitive information such as a credit card number. The agent may forget to manually pause the recording when the sensitive information is being exchanged. The agent may also forget to resume the recording when exchange of sensitive information is over. Thus, the manual controlling of the information recording is cumbersome. Further, the manual recording is prone to inadequate monitoring of the agent activity and/or PCI regulations violation by the enterprise.

In other existing solutions, a client application (for example, a client desktop analysis application) automatically detects exchange of the sensitive information and

## 2

triggers a pause to recording of the information as long as information being exchanged remains sensitive. The recording of the information is resumed once the exchange of sensitive information is over. However, if a client application (for example, a client financial application) is modified or replaced; each agent machine also requires updating of the client desktop analysis application. Consequently, even a minor update to the client financial application would require manual updating of the client desktop analysis application at each agent machine. This is a time consuming, error prone and expensive exercise.

There is thus a need for a system and method for improved PCI compliance for a contact center.

## SUMMARY

Embodiments in accordance with the present invention provide a system for providing Payment Card Industry (PCI) compliance for a contact center. The system includes a monitoring module configured to monitor a communication session between an agent and a customer. At least one image associated with the agent's computer screen is captured during the communication session. The system further includes an analysis module configured to compare the at least one image with at least one predefined image. The system further includes a control module configured to control a recording of information associated with the communication session based on the comparison.

Embodiments in accordance with the present invention further provide a computer-implemented method for providing PCI compliance for a contact center. The method includes monitoring a communication session between an agent and a customer. At least one image associated with the agent's computer screen is captured during the communication session. The at least one image is compared with at least one predefined image. A recording of information associated with the communication session is controlled based on the comparison.

Embodiments in accordance with the present invention further provide a computer-implemented method for providing PCI compliance for a contact center. The method includes monitoring a communication session between an agent and a customer. At least one image associated with the agent's computer screen is captured during the communication session. The at least one image is compared with at least one predefined image. The at least one image is constructed based on real time data stream received from the agent's computer. A recording of information associated with the communication session is controlled based on the comparison.

Embodiments of the present invention may provide a number of advantages depending on its particular configuration. First, an embodiment of the present application provides a system and a method for providing improved PCI compliance for a contact center. Sensitive information such as credit card numbers is protected. Secondly, the system provides for a centralized monitoring of agent's actions. The centralized monitoring provides for easy deployment and updating of system. Thirdly, the system provides for real time image recognition for providing the PCI compliance for the contact center. Finally, the system is scalable and cost effective for the PCI compliance for the contact center. These and other advantages will be apparent from the present application of the embodiments described herein.

The preceding is a simplified summary to provide an understanding of some aspects of embodiments of the present invention. This summary is neither an extensive nor



exhaustive overview of the present invention and its various embodiments. The summary presents selected concepts of the embodiments of the present invention in a simplified form as an introduction to the more detailed description presented below. As will be appreciated, other embodiments of the present invention are possible utilizing, alone or in combination, one or more of the features set forth above or described in detail below.

### BRIEF DESCRIPTION OF THE DRAWINGS

The above and still further features and advantages of embodiments of the present invention will become apparent upon consideration of the following detailed description of embodiments thereof, especially when taken in conjunction with the accompanying drawings, and wherein:

FIG. 1A illustrates a block diagram of a contact center, according to an embodiment of the present invention;

FIG. 1B illustrates at a relatively high level of hardware abstraction a block diagram of a server associated with the contact center, according to an embodiment of the present invention;

FIG. 2 illustrates a block diagram of a compliance system included in the server of FIG. 1B, according to an embodiment of the present invention;

FIG. 3A illustrates an exemplary predefined image, according to an embodiment of the present invention;

FIG. 3B illustrates an exemplary real time screen shot of an agent's computer screen, according to an embodiment of the present invention;

FIG. 4 is a flowchart of a method for providing the PCI compliance, according to an embodiment of the present invention; and

FIG. 5 is a flowchart of a detailed method for providing the PCI compliance, according to an embodiment of the present invention.

The headings used herein are for organizational purposes only and are not meant to be used to limit the scope of the description or the claims. As used throughout this application, the word "may" is used in a permissive sense (i.e., meaning having the potential to), rather than the mandatory sense (i.e., meaning must). Similarly, the words "include", "including", and "includes" mean including but not limited to. To facilitate understanding, like reference numerals have been used, where possible, to designate like elements common to the figures.

### DETAILED DESCRIPTION

Embodiments of the present invention will be illustrated below in conjunction with an exemplary communication system, e.g., the Avaya Aura® system. Although well suited for use with, e.g., a system having an Automatic Call Distribution (ACD) or other similar contact processing switch, embodiments of the present invention are not limited to any particular type of communication system switch or configuration of system elements. Those skilled in the art will recognize the disclosed techniques may be used in any communication application in which it is desirable to provide improved contact processing.

The phrases "at least one", "one or more", and "and/or" are open-ended expressions that are both conjunctive and disjunctive in operation. For example, each of the expressions "at least one of A, B and C", "at least one of A, B, or C", "one or more of A, B, and C", "one or more of A, B, or

C" and "A, B, and/or C" means A alone, B alone, C alone, A and B together, A and C together, B and C together, or A, B and C together.

The term "a" or "an" entity refers to one or more of that entity. As such, the terms "a" (or "an"), "one or more" and "at least one" can be used interchangeably herein. It is also to be noted that the terms "comprising", "including", and "having" can be used interchangeably.

The term "automatic" and variations thereof, as used herein, refers to any process or operation done without material human input when the process or operation is performed. However, a process or operation can be automatic, even though performance of the process or operation uses material or immaterial human input, if the input is received before performance of the process or operation. Human input is deemed to be material if such input influences how the process or operation will be performed. Human input that consents to the performance of the process or operation is not deemed to be "material".

The term "computer-readable medium" as used herein refers to any tangible storage and/or transmission medium that participate in providing instructions to a processor for execution. Such a medium may take many forms, including but not limited to, non-volatile media, volatile media, and transmission media. Non-volatile media includes, for example, NVRAM, or magnetic or optical disks. Volatile media includes dynamic memory, such as main memory. Common forms of computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, magneto-optical medium, a CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, a RAM, a PROM, and EPROM, a FLASH-EPROM, a solid state medium like a memory card, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read.

A digital file attachment to e-mail or other self-contained information archive or set of archives is considered a distribution medium equivalent to a tangible storage medium. When the computer-readable media is configured as a database, it is to be understood that the database may be any type of database, such as relational, hierarchical, object-oriented, and/or the like. Accordingly, embodiments may include a tangible storage medium or distribution medium and prior art-recognized equivalents and successor media, in which the software embodiments of the present invention are stored.

The terms "determine", "calculate" and "compute," and variations thereof, as used herein, are used interchangeably and include any type of methodology, process, mathematical operation or technique.

The term "module" as used herein refers to any known or later developed hardware, software, firmware, artificial intelligence, fuzzy logic, or combination of hardware and software that is capable of performing the functionality associated with that element. Also, while the present invention is described in terms of exemplary embodiments, it should be appreciated those individual aspects of the present invention can be separately claimed.

The term "switch" or "server" as used herein should be understood to include a Private Branch Exchange (PBX), an ACD, an enterprise switch, or other type of communications system switch or server, as well as other types of processor-based communication control devices such as media servers, computers, adjuncts, etc.



## 5

FIG. 1A shows an illustrative embodiment of the present invention. A contact center **100** comprises a server **110**, a set of data stores or databases **114** containing contact (or call) or customer related information, data items, and other information that may enhance the value and efficiency of the contact processing, and a plurality of servers, namely a voice mail server **118**, an Interactive Voice Response unit (e.g., IVR) **122**, and other servers **126**, a switch **130**, a plurality of working agents operating packet-switched (first) communication devices **134-1-N** (such as computer work stations or personal computers), and/or circuit-switched (second) communication devices **138-1-M**, all interconnected by a Local Area Network (LAN) **142**, (or Wide Area Network (WAN)). In an embodiment of the present invention, the database **114** may store data items associated with the agents of the contact center **100**. The data items may include, but is not restricted to, emails, documents, reports, and so forth. The data items may be stored in more than one database of the contact center **114**, in another embodiment of the present invention. The database **114** may further store metrics associated with the agents, supervisors, and the data items, in another embodiment of the present invention. Further, the database **114** may also store a rating associated with the data items. Further, the database **114** may store a formula or a mathematical algorithm that may be used to enhance information workflow in the contact center **100**.

The servers may be connected via optional communication lines **146** to the switch **130**. As will be appreciated, the other servers **126** may also include a scanner (which is normally not connected to the switch **130** or Web Server), VoIP software, video call software, voice messaging software, an IP voice server, a fax server, a web server, an email server, and the like. The switch **130** is connected via a plurality of trunks to a circuit-switched network **152** (e.g., Public Switch Telephone Network (PSTN)) and via link(s) **154** to the second communication devices **138-1-M**. A security gateway **158** is positioned between the server **110** and a packet-switched network **162** to process communications passing between the server **110** and the packet-switched network **162**. In an embodiment of the present invention, the security gateway **158** (as shown in FIG. 1A) may be Avaya Inc.'s, G700 Media Gateway™ and may be implemented as hardware such as via an adjunct processor (as shown) or as a chip in the server **110**.

The switch **130** and/or server **110** may be any architecture for directing contacts to one or more communication devices. In some embodiments of the present invention, the switch **130** may perform load-balancing functions by allocating incoming or outgoing contacts among a plurality of logically and/or geographically distinct contact centers. Illustratively, the switch **130** and/or server **110** may be a modified form of the subscriber-premises equipment sold by Avaya Inc. under the names Definity™ Private-Branch Exchange (PBX) based ACD system, MultiVantage™ PBX, Communication Manager™, S8300™ media server and any other media servers, SIP Enabled Services™, Intelligent Presence Server™, and/or Avaya Interaction Center™, and any other products or solutions offered by Avaya or another company. Typically, the switch **130**/server **110** is a stored-program-controlled system that conventionally includes interfaces to external communication links, a communications switching fabric, service circuits (e.g., tone generators, announcement circuits, etc.), memory for storing control programs and data, and a processor (i.e., a computer) for executing the stored control programs to control the interfaces and the fabric and to provide ACD functionality. Other

## 6

types of known switches and servers are well known in the art and therefore not described in detail herein.

The first communication devices **134-1-N** are packet-switched and may include, for example, IP hardphones such as the Avaya Inc.'s, 4600 Series IP Phones™, IP softphones such as Avaya Inc.'s, IP Softphone™, Personal Digital Assistants (PDAs), Personal Computers (PCs), laptops, packet-based H.320 video phones and conferencing units, packet-based voice messaging and response units, packet-based traditional computer telephony adjuncts, peer-to-peer based communication devices, and any other communication device.

The second communication devices **138-1-M** are circuit-switched devices. Each of the second communication devices **138-1-M** corresponds to one of a set of internal extensions Ext1-M, respectively. The second communication devices **138-1-M** may include, for example, wired and wireless telephones, PDAs, H.320 video phones and conferencing units, voice messaging and response units, traditional computer telephony adjuncts, and any other communication devices.

It should be noted that the embodiments of present invention do not require any particular type of information transport medium between switch, or server and first and second communication devices, i.e., the embodiments may be implemented with any desired type of transport medium as well as combinations of different types of transport channels.

The packet-switched network **162** may be any data and/or distributed processing network, such as the Internet. The packet-switched network **162** typically includes proxies (not shown), registrars (not shown), and routers (not shown) for managing packet flows.

The packet-switched network **162** as shown in FIG. 1A is in communication with an external first communication device **166** via a security gateway **170** and the circuit-switched network **150** is in communication with an external second communication device **174**.

In one configuration, the server **110**, the packet-switched network **162**, and the first communication devices **134-1-N** are Session Initiation Protocol (SIP) compatible and may include interfaces for various other protocols such as the Lightweight Directory Access Protocol (LDAP), H.248, H.323, Simple Mail Transfer Protocol (SMTP), IMAP4, ISDN, E1/T1, and analog line or trunk.

It should be emphasized that the configuration of the switch **130**, the server **110**, user communication devices, and other elements as shown in FIG. 1A is for purposes of illustration only and should not be construed as limiting embodiments of the present invention to any particular arrangement of elements.

Further, the server **110** is notified via the LAN **142** of an incoming service request or work item by the communications component (e.g., switch **130**, a fax server, an email server, a web server, and/or other servers) receiving the incoming service request as shown in FIG. 1A. The incoming service request is held by the receiving telecommunications component until the server **110** forwards instructions to the component to forward or route the contact to a specific contact center resource, such as the IVR unit **122**, the voice mail server **118**, and/or first or second telecommunication device **134-1-N**, **138-1-M** associated with a selected agent.

FIG. 1B illustrates at a relatively high level of hardware abstraction a block diagram of a server such as the server **110**, in accordance with an embodiment of the present invention. The server **110** may include an internal communication interface **151** that interconnects a processor **157**, a



memory **155** and a communication interface circuit **159**. The communication interface circuit **159** may include a receiver and transmitter (not shown) to communicate with other elements of the contact center **100** such as the switch **130**, the security gateway **158**, the LAN **142**, and so forth. By use of programming code and data stored in the memory **155**, the processor **157** may be programmed to carry out the various functions of the server **110**.

Although embodiments are discussed with reference to client-server architecture, it is to be understood that the principles of embodiments of the present invention apply to other network architectures. For example, embodiments of the present invention apply to peer-to-peer networks, such as those envisioned by the Session Initiation Protocol (SIP). In the client-server model or paradigm, network services and the programs used by end users to access the services are described. The client side provides a user with an interface for requesting services from the network, and the server side is responsible for accepting user requests for services and providing the services transparent to the user. By contrast in the peer-to-peer model or paradigm, each networked host runs both the client and server parts of an application program. Additionally, embodiments do not require the presence of packet- or circuit-switched networks.

The term “switch” or “server” as used herein should be understood to include a Private Branch Exchange (PBX), an ACD, an enterprise switch, an enterprise server, or other type of telecommunications system switch or server, as well as other types of processor-based communication control devices such as media servers, computers, adjuncts, etc.

Referring to FIG. 2, one possible configuration of the server **110** is depicted. The server **110** is in communication with a plurality of customer communication lines **200a-y** (which can be one or more trunks, phone lines, etc.) and agent communication line **204** (which can be a voice-and-data transmission line such as LAN **142** and/or a circuit switched voice line). The server **110** can include Avaya Inc.’s Operational Analyst™ with On-Line Analytical processing, or OLAP technology or a Call Management System or CMS **228** that gathers call records and contact-center statistics for use in generating contact-center reports. OA and CMS will hereinafter be referred to jointly as CMS **228**.

As can be seen in FIG. 2, included among the data stored in the server **110** is a set of contact queues **208a-n** and a separate set of agent queues **212a-n**. Each contact queue **208a-n** corresponds to a different set of agent queues, as does each agent queue **212a-n**. Conventionally, contacts are prioritized and either is enqueued in individual ones of the contact queues **208a-n** in their order of priority or is enqueued in different ones of a plurality of contact queues that correspond to a different priority. Likewise, each agent’s queues are prioritized according to his or her level of expertise or skill in that queue, and either agents are enqueued in individual ones of agent queues **212a-n** in their order of expertise level or are enqueued in different ones of a plurality of agent queues **212a-n** that correspond to a queue and each one of which corresponds to a different expertise level.

Included among the control programs in the server **110** is a work item vector **216**. Contacts incoming to the contact center are assigned by work item vector **216** to different work item queues **208a-n** based upon a number of predetermined criteria, including customer identity, customer needs, contact center needs, current contact center queue lengths, customer value, and the agent skill that is required for the proper handling of the contact. Agents who are available for handling work items are assigned to agent

queues **212a-n** based upon the skills that they possess. An agent may have multiple skills, and hence may be assigned to multiple agent queues **212a-n** simultaneously. Furthermore, an agent may have different levels of skill expertise (e.g., skill levels 1-N in one configuration or merely primary skill levels and secondary skill levels in another configuration), and hence may be assigned to different agent queues **212a-n** at different expertise levels.

According to embodiments of the present invention, included among the programs executing on the server **110** are an agent and work item selector **220** and a compliance system **224**. The agent selector **220** and the compliance system **224** are stored either in the main memory or in a peripheral memory (e.g., disk, CD ROM, etc.) or some other computer-readable medium of the contact center **100**. The agent selector **220** effects an assignment between available work items (or contacts) and available agents in a way that tends to maximize contact center efficiency for the current contact center state. The agent selector **220** uses predefined criteria in selecting an appropriate agent to service the work item. The selector **220**, in particular, obtains, for each of a plurality of contact center goals or objectives, status information, or information respecting whether or not a corresponding goal (for example, the service level agreement) is being met or unmet and/or a level to which the corresponding goal is being met or unmet.

For example, exemplary goal levels can be expressed as actual, average or median wait times in each queue **208**, actual, average, or median agent staffing levels in each queue **212**, actual, average, or median revenue (whether gross or net) realized by a designated set of agents (such as the agents in an agent skill queue) per serviced contact, a customer satisfaction level for a set of designated agents determined during or after servicing of each customer’s contact, actual, average, or median time for the agents in a set of designated agents to service contacts, number of contacts to be serviced by a set of designated agents during a selected time period, and the service level agreement between the contractor and the client. This information, along with other statistics is typically gathered by the CMS **228**.

The compliance system **224** controls recording of information associated with a communication session between a customer and an agent of the contact center **100**. The compliance system **224** is shown inside the server **110** only as illustration. The compliance system may be located outside of the server **110**, on a same site as the server **110** or on a remote site. The compliance system **224** is communicably coupled to the server **110**. In an embodiment of the present invention, the compliance system **224** includes a monitoring module **232**, an analysis module **234**, and a control module **236**.

The monitoring module **232** is configured to monitor a communication session between a customer and an agent. In one embodiment of the present invention, monitoring includes monitoring keystrokes, mouse movement at the agent’s computer. In another embodiment, the monitoring includes video monitoring of the agent’s computer screen. In another embodiment, the monitoring includes monitoring of a telephone call, an instant messaging service, a short messaging service, a multimedia messaging service, a screen sharing service, and an interactive voice response service. In another embodiment, the monitoring includes parsing of data exchanged during the communication session. In another embodiment, the monitoring includes receiving data stream from the agent’s computer. The data stream may include a video, an audio, an image, or other electronic data.



The monitoring module **232** captures at least one image associated with the agent's computer screen during the communication session. The image may be captured based on a data stream received from the agent's computer. The data stream may include, but not limited to, a video and images. In one embodiment of the present invention, the image is extracted from the video. In one embodiment, every nth frame may be extracted from the video. In another embodiment, the image may be selected from among the received images based on predetermined criteria. The predetermined criteria may include, but not limited to a timing criteria, a numbering criteria. For example, in one embodiment, every nth image may be selected from the received images. In another embodiment, one image may be selected every nth second.

In one embodiment of the present invention, the at least one image is a real time screenshot of the agent's computer screen. In another embodiment, the at least one image is a combination of two or more real time screenshots of the agent's computer screen.

In another embodiment, the monitoring module **232** monitors a plurality of communication sessions associated with the agent. In another embodiment, the monitoring module **232** monitors a plurality of communication sessions each of which is associated with a different agent. In another embodiment, the monitoring module **232** monitors a plurality of communication sessions associated with a plurality of agents. The monitoring module **232** is communicatively coupled to the analysis module **234**. The monitoring module provides the at least one image to the analysis module via a communication channel. The communication channel may be any communication channel known in state of the art. The communication channel can be any proprietary or non-proprietary communication channel.

The analysis module **234** compares the captured image received from the monitoring module **232** with a predefined image. In an embodiment of the present invention, the predefined image comprises one or more screenshots of the agent's computer screen. In another embodiment, the predefined image may be a picture of a window or area of the client application that receives sensitive information. The predefined image may be fetched by the analysis module **234** from a data store where it has been stored. In one embodiment of the present invention, the data store comprises a database **114** that is communicatively coupled to the server **110**. In another embodiment, the at least one predefined image is stored in a memory location internal to the server **110**.

Further, the analysis module **234** may store the captured image and the predefined image in a buffer before performing the comparison. The analysis module **234** may modify either or both of the captured image and the predefined image before performing the comparison. The analysis module **234** may employ any state of the art, proprietary or non-proprietary technique, system, or algorithm to perform the comparison.

The analysis module **234** generates a confidence score based on the comparison. In one embodiment of the present invention, the confidence score may be in a range from 1 to 100. A confidence score of 1 may indicate that the captured image is distinct from the predefined image. On the other hand, a confidence score of 100 may indicate a perfect match between the captured image and the predefined image. However, a scale of 1 to 100 is described only for illustration purposes. Any suitable scale may be employed for determining the confidence score. The confidence score may be determined based on various parameters associated with the

captured image and the predefined image. The confidence score may be determined using various methods, algorithms, statistical analysis, image recognition and/or image processing techniques.

The analysis module **234** is communicatively coupled to the control module **236** via a communication channel. The communication channel may be any communication channel known in state of the art. The communication channel can be any proprietary or non-proprietary communication channel. The analysis module **234** provides the confidence score to the control module **236**.

The control module **236** controls a recording of information associated with the communication session based on the confidence score. The information associated with the communication session may include data associated with a telephone call, an instant messaging service, a multimedia messaging service, a screen sharing service and/or screen recording video of the agent machine. The control module **236** determined whether the confidence score meets predetermined criteria. In one embodiment of the present invention, the predetermined criterion is expressed as a threshold score. The predetermined criteria may be met when the threshold score is less than, equal to, less than or equal to or greater than, or greater than or equal to the threshold score. In one embodiment, the predetermined criteria are met when the confidence score is greater than or equal to the threshold score.

If the confidence score is less than the threshold score, the information associated with the communication session is recorded. The recording of the information enables maintaining quality of service at the contact center and measuring performance of the agent. The information associated with the communication session may include, but not limited to a telephone call, an instant messaging service, a short messaging service, a multimedia messaging service, a screen sharing service, an interactive voice response service, a video, an audio, an image or other electronic data. The information may be recorded in a data store such as database **114** for service quality purposes.

If the confidence score is greater than or equal to the threshold score, the recording of the information associated with the communication session is paused. In one embodiment of the present invention, the pausing may include receiving the data but masking it. In one embodiment of the present invention, the threshold score is a percentage/fraction of scale employed to measure the confidence score. In another embodiment, the threshold score is determined based on the scale of the confidence score using statistical methods. In one embodiment of the present invention, the threshold score is in a range from about 70 to about 90 on a scale from 1 to 100.

The predetermined threshold score may vary according to the type of client applications installed on the agent's computer. In one embodiment of the present invention, the predetermined threshold score may vary with the at least one predefined image. For example, the predetermined threshold score may vary based on number and configuration of objects in the at least one predefined image.

In another embodiment, the predetermined criteria may be based on statistical modeling, correlation analysis or other statistical criteria.

The embodiments of the present invention provide improved PCI compliance for a contact center. The embodiments of the present invention provide centralized and automatic controlling of recording of information for various communication sessions between customers and agents of the contact center. Thus, system and method according to



## 11

present invention provides for adherence to PCI regulations while being cost effective and easy to manage.

FIGS. 3A and 3B illustrate with a block diagram **300**, exemplary predefined image **304** and captured image **316** associated with the agent's computer. The image **304**, in an embodiment of the present invention, comprises a predefined image. The image **304** includes a plurality of named fields **308** including, but not limited to, a name, a credit card number, a security code, and an expiry date. In one embodiment of the present invention, the plurality of named fields **308** includes at least one sensitive named field. For the purposes of this specification, a sensitive named field includes any named field associated with sensitive information. The image **304** further includes a plurality of blank input fields **312**. The plurality of blank input fields **312** correspond to the plurality of named fields **308**, for example, the blank input field shown against the credit card number receives input corresponding to the credit card number. In an embodiment of the present invention, the image **304** comprises one or more screenshots of an agent's computer screen.

The image **316** comprises of a real time screenshot of an agent's computer screen. As is seen from the FIG. 3B, the image **316** comprises a plurality of named fields **320** and a plurality of filled or partially filled input areas **324**.

In an exemplary embodiment of the present invention, the predefined image **304** is compared with the captured image **316** to determine a confidence score. Based on the confidence score, recording of the information for the communication session between the customer and the agent is controlled. The detailed methods of controlling the recording and associated advantages are further explained in relation to FIG. 5 below.

FIG. 4 depicts a flowchart of a method **400** for controlling recording of information for a contact center, according to an embodiment of the present invention.

At step **404**, a communication session between a customer and an agent of the contact center is monitored. In one embodiment of the present invention, monitoring includes monitoring keystrokes, mouse movement at the agent's computer. In another embodiment, the monitoring includes video monitoring of the agent's computer screen. In another embodiment, the monitoring includes monitoring of a telephone call, an instant messaging service, a short messaging service, a multimedia messaging service, a screen sharing service, and an interactive voice response service. In another embodiment, the monitoring includes parsing of data exchanged during the communication session. In another embodiment, the monitoring includes receiving data stream from the agent's computer. The data stream may include a video, an audio, an image, or other electronic data.

At least one image associated with the agent's computer screen is captured during the communication session. The at least one image may be in any known proprietary or non-proprietary format.

At step **408**, the captured image is compared to a predefined image. The predefined image may include one or more screenshots of the agent's machine. The predefined image may be in any known proprietary or non-proprietary format. In one embodiment, the predefined image is in a format different from the format of the captured image. In another embodiment, the format of the predefined image is changed to the format of the captured image.

At step **412**, recording of the information associated with the communication session is controlled based on the comparison. In one embodiment of the present invention, the controlling includes, but not limited to recording, pausing

## 12

the recording, masking the recorded information, discarding the received information. The controlling of the recording may be based on predetermined criteria. The controlling of the recording of the information provides improved PCI compliance for a contact center. The embodiments of the present invention provide centralized and automatic controlling of recording of information for various communication sessions between customers and agents of the contact center. Thus, system and method according to present invention provides for adherence to PCI regulations while being cost effective and easy to manage.

FIG. 5 depicts a detailed flowchart of a method **500** for controlling recording of information for a contact center, according to an embodiment of the present invention.

At step **504**, a communication session between a customer and an agent of is monitored. In one embodiment of the present invention, monitoring includes monitoring keystrokes, mouse movement at the agent's computer. In another embodiment, the monitoring includes video monitoring of the agent's computer screen. In another embodiment, the monitoring includes monitoring of a telephone call, an instant messaging service, a short messaging service, a multimedia messaging service, a screen sharing service, and an interactive voice response service. In another embodiment, the monitoring includes parsing of data exchanged during the communication session. In another embodiment, the monitoring includes receiving data stream from the agent's computer. The data stream may include a video, an audio, an image, or other electronic data.

At step **508**, it is determined whether the communication session between the customer and the agent has ended. The communication session may be ended by the customer, the agent, or due to technical problem such as power shutdown or an application not working. If the communication session has ended at step **508**, the method **500** ends. If the communication session has not ended, then the method **500** proceeds to step **512**.

At step **512**, an image associated with an agent's computer screen is captured. The image may be captured by based on a data stream received from the agent's computer. The data stream may include, but not limited to, a video and one or more images. In one embodiment of the present invention, the image is extracted from the video. In one embodiment, every nth frame may be extracted from the video. In another embodiment, the image may be selected from among the received images based on predetermined criteria. The predetermined criteria may include, but not limited to a timing criteria, a numbering criteria. For example, in one embodiment, every nth image may be selected from the received images. In another embodiment, one image may be selected every nth second.

In one embodiment of the present invention, the at least one image is a real time screenshot of the agent's computer screen. In another embodiment, the at least one image is a combination of two or more real time screenshots of the agent's computer screen. In another embodiment, a plurality of communication sessions associated with the agent is monitored. In another embodiment, a plurality of communication sessions each of which is associated with a different agent is monitored. In another embodiment, a plurality of communication sessions associated with a plurality of agents is monitored.

At step **516**, the captured image is compared with a predefined image. In an embodiment of the present invention, the predefined image comprises one or more screenshots of the agent's computer screen. In another embodiment, the at least one predefined image may be a picture of



13

a window or area of the client application that receives sensitive information. The predefined image may be fetched from a data store where it has been stored. In one embodiment of the present invention, the data store may be database 114 that is communicatively coupled to the server 110. In another embodiment, the predefined image is stored in a memory location internal to the server 110.

Further, the captured image and the predefined image may be stored in a buffer before performing the comparison. In an embodiment of the present invention, either or both of the captured image and the predefined image may be modified before performing the comparison. Any state of the art, proprietary or non-proprietary technique, system, method or algorithm may be employed to perform the comparison.

At step 520, a confidence score is determined based on the comparison of the captured image with the predefined image. In one embodiment of the present invention, the confidence score may be in a range from 1 to 100. A confidence score of 1 may indicate that the captured image is distinct from the predefined image. On the other hand, a confidence score of 100 may indicate a perfect match between the captured image and the predefined image. However, a scale of 1 to 100 is described only for illustration purposes. Any suitable scale may be employed for determining the confidence score. The confidence score may be determined based on various parameters associated with the captured image and the predefined image. The confidence score may be determined using various methods, algorithms, statistical analysis, image recognition and/or image processing techniques.

At step 524, it is determined whether the confidence score meets predetermined criteria. In one embodiment of the present invention, the predetermined criteria a threshold score. The predetermined criteria may be met when the threshold score is less than, equal to, less than or equal to or greater than, or greater than or equal to threshold score. In one embodiment, the predetermined criteria are met when the confidence score is greater than or equal to the threshold score. In this embodiment, if the confidence score is less than the threshold score, the method 500 proceeds to step 528.

At step 528, the information associated with the communication session is recorded. The recording of the information enables maintaining quality of service at the contact center and measuring performance of the agent. The information associated with the communication session may include, but not limited to a telephone call, an instant messaging service, a short messaging service, a multimedia messaging service, a screen sharing service, an interactive voice response service, a video, an audio, an image or other electronic data. The information may be recorded in a data store such as database 114 for service quality purposes. At this stage, the method 500 loop back to step 504, at which the monitoring of the communication session is continued in real time.

If the confidence score is greater than or equal to the threshold score, the method proceeds to step 532.

At step 532, the recording of the information associated with the communication session is paused. In one embodiment of the present invention, the pausing may include receiving the data but masking it. At this stage, the method 500 loop back to step 504, at which the monitoring of the communication session is continued in real time.

In one embodiment of the present invention, the threshold score is a percentage/fraction of scale employed to measure the confidence score. In another embodiment, the threshold score is determined based on the scale of the confidence

14

score using statistical methods. In one embodiment of the present invention, the threshold score is in a range from about 70 to about 90 on a scale from 1 to 100.

The predetermined threshold score may vary according to the type of client applications installed on the agent's computer. In one embodiment of the present invention, the predetermined threshold score may vary with the at least one predefined image. For example, the predetermined threshold score may vary based on number and configuration of objects in the at least one predefined image.

In another embodiment, the predetermined criteria may be based on statistical modeling, correlation analysis or other statistical criteria.

The embodiments of the present invention provide improved PCI compliance for a contact center. The embodiments of the present invention provide centralized and automatic controlling of recording of information for various communication sessions between customers and agents of the contact center. Thus, system and method according to present invention provides for adherence to PCI regulations while being cost effective and easy to manage.

The exemplary embodiments of this present invention have been described in relation to a contact center. However, to avoid unnecessarily obscuring the present invention, the preceding description omits a number of known structures and devices. This omission is not to be construed as a limitation of the scope of the present invention. Specific details are set forth by use of the embodiments to provide an understanding of the present invention. It should however be appreciated that the present invention may be practiced in a variety of ways beyond the specific embodiments set forth herein.

Furthermore, while the exemplary embodiments of the present invention illustrated herein show the various components of the system collocated, certain components of the system can be located remotely, at distant portions of a distributed network, such as a LAN and/or the Internet, or within a dedicated system. Thus, it should be appreciated, that the components of the system can be combined in to one or more devices, such as a switch, server, and/or adjunct, or collocated on a particular node of a distributed network, such as an analog and/or digital telecommunications network, a packet-switch network, or a circuit-switched network.

It will be appreciated from the preceding description, and for reasons of computational efficiency, that the components of the system can be arranged at any location within a distributed network of components without affecting the operation of the system. For example, the various components can be located in a switch such as a PBX and media server, gateway, in one or more communications devices, at one or more users' premises, or some combination thereof. Similarly, one or more functional portions of the system could be distributed between a telecommunications device(s) and an associated computing device.

Furthermore, it should be appreciated the various links connecting the elements can be wired or wireless links, or any combination thereof, or any other known or later developed element(s) that is capable of supplying and/or communicating data to and from the connected elements. These wired or wireless links can also be secure links and may be capable of communicating encrypted information. Transmission media used as links, for example, can be any suitable carrier for electrical signals, including coaxial cables, copper wire and fiber optics, and may take the form of acoustic or light waves, such as those generated during radio-wave and infra-red data communications.



15

Also, while the flowcharts have been discussed and illustrated in relation to a particular sequence of events, it should be appreciated that changes, additions, and omissions to this sequence can occur without materially affecting the operation of embodiments of the present invention.

A number of variations and modifications of the present invention can be used. It would be possible to provide for some features of the present invention without providing others.

For example in one alternative embodiment of the present invention, the systems and methods of this present invention can be implemented in conjunction with a special purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit element(s), an ASIC or other integrated circuit, a digital signal processor, a hard-wired electronic or logic circuit such as discrete element circuit, a programmable logic device or gate array such as PLD, PLA, FPGA, PAL, special purpose computer, any comparable means, or the like.

In general, any device(s) or means capable of implementing the methodology illustrated herein can be used to implement the various aspects of this present invention. Exemplary hardware that can be used for the present invention includes computers, handheld devices, telephones (e.g., cellular, Internet enabled, digital, analog, hybrids, and others), and other hardware known in the art. Some of these devices include processors (e.g., a single or multiple microprocessors), memory, non-volatile storage, input devices, and output devices. Furthermore, alternative software implementations including, but not limited to, distributed processing or component/object distributed processing, parallel processing, or virtual machine processing can also be constructed to implement the methods described herein.

In yet another embodiment of the present invention, the disclosed methods may be readily implemented in conjunction with software using object or object-oriented software development environments that provide portable source code that can be used on a variety of computer or workstation platforms. Alternatively, the disclosed system may be implemented partially or fully in hardware using standard logic circuits or VLSI design. Whether software or hardware is used to implement the systems in accordance with embodiments of the present invention is dependent on the speed and/or efficiency requirements of the system, the particular function, and the particular software or hardware systems or microprocessor or microcomputer systems being utilized.

In yet another embodiment of the present invention, the disclosed methods may be partially implemented in software that can be stored on a storage medium, executed on programmed general-purpose computer with the cooperation of a controller and memory, a special purpose computer, a microprocessor, or the like. In these instances, the systems and methods of this present invention can be implemented as program embedded on personal computer such as an applet, JAVA® or CGI script, as a resource residing on a server or computer workstation, as a routine embedded in a dedicated measurement system, system component, or the like. The system can also be implemented by physically incorporating the system and/or method into a software and/or hardware system.

Although the present invention describes components and functions implemented in the embodiments with reference to particular standards and protocols, the present invention is not limited to such standards and protocols. Other similar standards and protocols not mentioned herein are in existence and are considered to be included in the present

16

invention. Moreover, the standards and protocols mentioned herein and other similar standards and protocols not mentioned herein are periodically superseded by faster or more effective equivalents having essentially the same functions.

Such replacement standards and protocols having the same functions are considered equivalents included in the present invention.

The present invention, in various embodiments, configurations, and aspects, includes components, methods, processes, systems and/or apparatus substantially as depicted and described herein, including various embodiments, sub-combinations, and subsets thereof. Those of skill in the art will understand how to make and use the present invention after understanding the present disclosure. The present invention, in various embodiments, configurations, and aspects, includes providing devices and processes in the absence of items not depicted and/or described herein or in various embodiments, configurations, or aspects hereof, including in the absence of such items as may have been used in previous devices or processes, e.g., for improving performance, achieving ease and/or reducing cost of implementation.

The foregoing discussion of the present invention has been presented for purposes of illustration and description. The foregoing is not intended to limit the present invention to the form or forms disclosed herein. In the foregoing Detailed Description for example, various features of the present invention are grouped together in one or more embodiments, configurations, or aspects for the purpose of streamlining the disclosure. The features of the embodiments, configurations, or aspects of the present invention may be combined in alternate embodiments, configurations, or aspects other than those discussed above. This method of disclosure is not to be interpreted as reflecting an intention that the present invention requires more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive aspects lie in less than all features of a single foregoing disclosed embodiment, configuration, or aspect. Thus, the following claims are hereby incorporated into this Detailed Description, with each claim standing on its own as a separate embodiment of the present invention.

Moreover, though the description of the present invention has included description of one or more embodiments, configurations, or aspects and certain variations and modifications, other variations, combinations, and modifications are within the scope of the present invention, e.g., as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It is intended to obtain rights which include alternative embodiments, configurations, or aspects to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures, functions, ranges or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

What is claimed is:

1. A server comprising a compliance system for a contact center, the server comprising a processor and a memory, wherein the processor executes programming code stored in the memory to:

monitor an ongoing communication session between an agent and a customer;  
receive, from a computer of the agent, a video data stream of a screen of the computer of the agent during the monitored ongoing communication session;



17

extract a first image from the received video data stream,  
 wherein the first image is extracted from a periodic  
 subset of frames of the received video data stream;  
 retrieve a stored predefined image, wherein the stored  
 predefined image comprises at least one field associated  
 with sensitive data to avoid recording; 5  
 compare the first image with the predefined image that  
 comprises at least one field associated with sensitive  
 data to avoid recording;  
 generate a first confidence score based on the comparison 10  
 of the first image with the predefined image; and  
 selectively perform:  
 a) recording of information associated with the ongoing  
 communication session when the first confidence  
 score is less than a threshold value; and 15  
 b) pause recording of information associated with the  
 ongoing communication session when the first con-  
 fidence score is greater than or equal to the threshold  
 value. 20  
 2. The system of claim 1, wherein the processor executes  
 programming code stored in the memory to:  
 subsequent to extracting the first image, determine the  
 ongoing communication session has not ended and  
 extract a second image from the received video data 25  
 stream, wherein the second image is extracted from the  
 periodic subset of frames of the received video data  
 stream;  
 compare the second image with the predefined image;  
 generate a second confidence score based on the com- 30  
 parison of the second image with the predefined image;  
 and  
 resume recording of information associated with the  
 ongoing communication session based on the second  
 confidence score being less than the threshold value. 35  
 3. The system of claim 1, wherein pausing recording of  
 information associated with the ongoing communication  
 comprises masking the sensitive data.  
 4. The system of claim 1, wherein the information asso- 40  
 ciated with the ongoing communication session comprises  
 data associated with at least one of a telephone call, a video  
 conference, an instant messaging service, a short messaging  
 service, a multimedia messaging service, a screen sharing  
 service, or an interactive voice response service.  
 5. The system of claim 1, wherein the predefined image 45  
 comprises a one or more screenshots of the agent's computer  
 screen.  
 6. A computer-implemented method in a contact center,  
 the method comprising:  
 monitoring, by a server, an ongoing communication ses-  
 sion between an agent and a customer;

18

receiving, by the server, from a computer of the agent, a  
 video data stream of a screen of the computer of the  
 agent during the monitored ongoing communication  
 session;  
 extracting, by the server, a first image from the received  
 video data stream, wherein the first image is extracted  
 from a periodic subset of frames of the received video  
 data stream;  
 retrieving, by the computer, a stored predefined image,  
 wherein the stored predefined image comprises at least  
 one field associated with sensitive data to avoid record-  
 ing;  
 comparing, by the server, the first image with the pre-  
 defined image that comprises at least one field associ-  
 ated with sensitive data to avoid recording;  
 generating, by the server, a first confidence score based on  
 the comparison of the first image with the predefined  
 image; and  
 based on the first confidence score being greater than or  
 equal to a threshold value, pausing, by the server,  
 recording of information associated with the ongoing  
 communication session.  
 7. The method of claim 6, comprising:  
 subsequent to extracting the first image, determining, by  
 the server, the ongoing communication session has not  
 ended and extracting, by the server, a second image  
 from the received video data stream, wherein the sec-  
 ond image is extracted from the periodic subset of  
 frames of the received video data stream;  
 comparing, by the server, the second image with the  
 predefined image;  
 generating, by the server, a second confidence score based  
 on the comparison of the second image with the pre-  
 defined image; and  
 resuming, by the server, recording of information associ-  
 ated with the ongoing communication session based on  
 the second confidence score being less than the thresh-  
 old value.  
 8. The method of claim 6, wherein the pausing comprises  
 one of a masking of the sensitive data or a shedding of the  
 sensitive data.  
 9. The method of claim 6, wherein the predefined image  
 comprises a screenshot of a client application that receives  
 the sensitive information.  
 10. The method of claim 9, wherein the screenshot  
 comprises a plurality of named fields and a plurality of  
 corresponding input areas.  
 11. The method of claim 6, wherein the at least one field  
 comprises at least one of a customer name, a credit card  
 number, a card security number or an expiry date.

\* \* \* \* \*