



US010589019B2

(12) **United States Patent**
Provost et al.

(10) **Patent No.:** **US 10,589,019 B2**
(45) **Date of Patent:** **Mar. 17, 2020**

(54) **INFUSION LINE SYSTEMS**

(71) Applicant: **MJ Stewart Investments, LLC**,
Washington, UT (US)

(72) Inventors: **Wayne A. Provost**, St. George, UT
(US); **Jeffrey D. Stewart**, Washington,
UT (US)

(73) Assignee: **MJ Stewart Investments**, Washington,
UT (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/053,495**

(22) Filed: **Aug. 2, 2018**

(65) **Prior Publication Data**

US 2018/0344923 A1 Dec. 6, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/902,682, filed on
Feb. 22, 2018, now Pat. No. 10,064,991, which is a
continuation-in-part of application No. 15/618,799,
filed on Jun. 9, 2017.

(60) Provisional application No. 62/354,617, filed on Jun.
24, 2016.

(51) **Int. Cl.**

F21V 8/00 (2006.01)
A61M 5/14 (2006.01)
A61M 39/10 (2006.01)
G06F 21/35 (2013.01)

(52) **U.S. Cl.**

CPC **A61M 5/14** (2013.01); **A61M 39/10**
(2013.01); **G02B 6/0006** (2013.01); **G06F**
21/35 (2013.01); **A61M 2205/587** (2013.01);
A61M 2205/6081 (2013.01); **G02B 6/001**
(2013.01)

(58) **Field of Classification Search**

CPC **A61B 17/3403**; **A61B 5/150748**; **A61B**
2017/00057; **F21V 33/0068**; **F21V**
33/0072; **F21V 21/088**

USPC **362/572**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,316,473	A	5/1994	Hare	
6,984,052	B1	1/2006	Castillo	
D518,261	S	3/2006	Varga	
9,308,051	B2	4/2016	Adams et al.	
2007/0100222	A1*	5/2007	Mastrototaro A61B 5/01 600/365
2007/0106263	A1	5/2007	Ward	
2008/0033519	A1	2/2008	Burwell et al.	

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 62/354,617, filed Jun. 24, 2016, Provost et al.
(Continued)


Primary Examiner — William J Carter

(74) *Attorney, Agent, or Firm* — Workman Nydegger

(57) **ABSTRACT**

An IV line identification system to enable ready identifica-
tion of an IV line and its associated fluid source and output
and to enable distinguishing the IV line from other IV lines
and their fluid sources and outputs. The IV line identification
system includes a first light source and a second light source
communicatively coupled to one another via a wireless
connection. The light sources are configured such that when
one is activated so as to generate a light signal, the other is
automatically activated to generate a corresponding light
signal. Each light source may be placed on opposite ends of
an IV line to enable ready identification of each end of the
same IV line.

19 Claims, 14 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0177145 A1 7/2008 Furnish
2013/0208497 A1* 8/2013 Provost A61M 5/14
362/555
2017/0258983 A1 9/2017 Utz
2017/0368255 A1 12/2017 Provost et al.
2018/0177938 A1 6/2018 Provost et al.

OTHER PUBLICATIONS

U.S. Appl. No. 15/902,682, Jul. 13, 2018, Notice of Allowance.
International Search Report and Written Opinions for PCT/US2019/
018826 dated May 22, 2019.
U.S. Appl. No. 16/548,067, Sep. 12, 2019, Office Action.
U.S. Appl. No. 15/618,799, Oct. 28, 2019, Office Action.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 3G




FIG. 3H




FIG. 3I




FIG. 3K




FIG. 3J




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15

1**INFUSION LINE SYSTEMS****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 15/902,682, filed Feb. 22, 2018 and titled "INFUSION LINE SYSTEMS," which is a continuation-in-part of U.S. application Ser. No. 15/618,799, filed Jun. 9, 2017 and titled "ILLUMINATED INFUSION LINE AND SYSTEMS," which claims priority to and the benefit of U.S. Provisional Patent Application Ser. No. 62/354,617, filed Jun. 24, 2016 and titled "ILLUMINATED INFUSION LINE AND SYSTEMS," the disclosures of each of which are incorporated herein by these references in their entireties.

BACKGROUND**1. The Field of the Invention**

The present disclosure generally relates to systems for the intravenous administration of medications, fluids, and/or nutrients. More particularly, the disclosure relates to systems and devices for distinctly identifying each of several intravenous lines used to intravenously administer medications, fluids, and/or nutrients.

2. The Relevant Technology

In a hospital setting, patients are often administered liquid medications, fluids, and nutrients (hereinafter collectively referred to as "therapeutic fluids") via intravenous lines (hereinafter referred to as "IV lines"). IV lines generally consist of flexible, plastic tubing connected at one end to a fluid source and at another end to a needle or port that provides access to a blood vessel/artery of a patient. It is not uncommon for multiple IV lines, each connected to a different source of fluid, to be used simultaneously to deliver several therapeutic fluids at once to a single patient. It is also not uncommon for the needles or ports to be located adjacent to one another, such as multiple adjacent needles providing access into the brachial vein running through the arm of the patient.

While the simultaneous use of multiple IV lines can provide numerous benefits, some challenges can also be encountered. For instance, when multiple IV lines are used to administer multiple therapeutic fluids to a single patient, it can become cumbersome and difficult to readily identify one IV line from another. Thus, it can be difficult to quickly and accurately identify a particular therapeutic fluid source and corresponding therapeutic fluid output compared to another medication source and its corresponding therapeutic fluid output. This problem is aggravated by the tendency of each of the intravenous lines to coil up to their packaged configuration and consequently tangle with other IV lines or tangle under bed sheets or clothing.

Quick identification of a particular therapeutic fluid source is often required in emergency situations. For example, when a patient hooked up to multiple IV lines is in need of emergency intravenous administration of a therapeutic fluid not currently being provided through one of the IV lines, it is necessary to immediately provide that therapeutic fluid. If a blood vessel cannot rapidly be located into which the therapeutic fluid can be injected, it is common practice to provide the drug through an IV line in which a therapeutic fluid is already being administered. This practice of using existing IV lines to administer new therapeutic

2

fluids is also common in non-emergency situations. The person administering the drug, however, must be sure that the IV line through which the new therapeutic fluid is administered is carrying a therapeutic fluid which is compatible with the new therapeutic fluid. Severe results may occur if a new therapeutic fluid is injected through an IV line in which the therapeutic fluid already flowing therethrough is not compatible with the new therapeutic fluid. For example, if heparin is injected into an IV line through which lidocaine is already flowing, a flakey precipitate will form in the mixture which can be dangerous to a patient. Similarly, mixing insulin with certain chemotherapy drugs in a common IV line can be extremely dangerous for a patient.

As a result of the difficulties in distinguishing between multiple IV lines and their associated fluid sources and outputs and the potentially life-threatening possibilities that can occur if incompatible therapeutic fluids are injected through the same IV line, there is a need for devices and systems that allow for ready and accurate identification of individual IV lines with their associated fluid sources and outputs.

BRIEF SUMMARY

In an embodiment, an intravenous infusion line assembly includes an elongated member and an optical member. The elongated member has a fluid conduit for administering therapeutic fluid to a patient by providing fluid communication between a first end of the elongated member and a second end of the elongated member. The optical member is at least partially affixed to the elongated member, and is at least partially optically transmissive to internally reflect light within the optical member.

In another embodiment, an intravenous infusion line identification system includes an intravenous therapy system for administering therapeutic fluid to a patient and a light source. The intravenous therapy system includes a therapeutic fluid input, and a therapeutic fluid output with an elongated member and optical member. The elongated member provides fluid communication from the therapeutic fluid input to the therapeutic fluid output. The optical member is at least partially coupled to the elongated member, and is at least partially optically transmissive to internally reflect light within the optical member. In some configurations, the optical member is at least partially coupled to the elongated member with a plurality of rigid fasteners/clamps. The light source is selectively couplable to the optical member and configured to provide light into the optical member. In some configurations, the light source is selectively attachable to the elongated member by with a plurality of clips.

In yet another embodiment, a method of identifying an infusion line being used to administer therapeutic fluids to a patient includes providing an infusion line having an optical member; positioning a light source adjacent to the optical member; and directing a light from the light source into the optical member. The optical member is configured to reflect at least a first portion of the light internally within the optical member.

In another embodiment, an intravenous infusion line identification system includes a first light source and a second light source communicatively coupled to one another via a wireless connection. The light sources are configured such that when one is activated so as to generate a light signal, the other is automatically activated to generate a corresponding light signal. Each light source may be placed on opposite ends of an infusion line to enable ready identification of each end of the same infusion line, thereby

3

preventing misidentification of an infusion line and/or mistaken association of one end of an infusion line with another end of a different infusion line.

These and other objects and features of the present invention will become more fully apparent from the following description and appended claims, or may be learned by the practice of the invention as set forth hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

To further clarify the above and other advantages and features of the present invention, a more particular description of the invention will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. It is appreciated that these drawings depict only illustrated embodiments of the invention and are therefore not to be considered limiting of its scope. The invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

FIG. 1 illustrates a schematic view of an embodiment of an intravenous (“IV”) infusion line assembly, according to the present disclosure, where a first light component is a light source and where a second light component is an optical member operatively coupled to the light source such that both the first and second light components provide synchronous visual identifiers;

FIG. 2 illustrates a transverse cross-sectional view of the embodiment of an IV infusion line assembly of FIG. 1, according to the present disclosure;

FIG. 3A illustrates a perspective view of an embodiment of the IV infusion line assembly, according to the present disclosure;

FIG. 3B illustrates a top view of an embodiment of the IV infusion line assembly, according to the present disclosure;

FIG. 3C illustrates a right side view of an embodiment of the IV infusion line assembly, according to the present disclosure;

FIG. 3D illustrates a cross-sectional front view of an embodiment of the IV infusion line assembly, according to the present disclosure;

FIG. 3E illustrates a perspective view of a line fastener, according to the present disclosure;

FIG. 3F illustrates a front view of a line fastener, according to the present disclosure;

FIG. 3G illustrates a rear view of a line fastener, according to the present disclosure;

FIG. 3H illustrates a bottom view of a line fastener, according to the present disclosure;

FIG. 3I illustrates a top view of a line fastener, according to the present disclosure;

FIG. 3J illustrates a right side view of a line fastener, according to the present disclosure;

FIG. 3K illustrates a left side view of a line fastener, according to the present disclosure;

FIG. 4 is a side view of an embodiment of an IV infusion line identification system, according to the present disclosure;

FIG. 5 illustrates an exploded perspective view of an embodiment of a light source, according to the present disclosure;

FIG. 6 is a partial cutaway side view of the embodiment of an IV infusion line identification system of FIG. 4, according to the present disclosure;

FIG. 7A illustrates an embodiment of a light source, according to the present disclosure;

4

FIG. 7B illustrates a side view of the embodiment of a light source of FIG. 7A, according to the present disclosure;

FIG. 8 is a side view of another embodiment of an IV infusion line identification system, according to the present disclosure;

FIG. 9A is a partial cutaway side view of the embodiment of an IV infusion line identification system of FIG. 8, according to the present disclosure;

FIG. 9B is a partial cutaway end view of the embodiment of an IV infusion line identification system of FIG. 8, according to the present disclosure;

FIG. 10A is a transverse cross-sectional view of another embodiment of an IV infusion line, according to the present disclosure;

FIG. 10B is a longitudinal cross-sectional view of the embodiment of an IV infusion line of FIG. 10A, according to the present disclosure;

FIG. 11 is a side view of an embodiment of an IV infusion line with an inline filter, according to the present disclosure;

FIG. 12 is a side view of an embodiment of an IV infusion line with an inline rotary pump, according to the present disclosure;

FIG. 13 illustrates another embodiment of an infusion line identification system where a first light component is a light source and where a second light component is also a light source, the light sources being operatively coupled to one another such that both the first and second light components provide synchronous visual identifiers;

FIG. 14 illustrates an embodiment of an infusion line system as in FIG. 13 with the addition of a pump assembly; and

FIG. 15 is a detailed view of a light source of the system of FIG. 13.

DETAILED DESCRIPTION

The embodiments described herein extend to methods, devices, systems, assemblies, and apparatus for identification of intravenous (“IV”) infusion lines. Such are configured to, for example, enable the reliable identification of one IV infusion line from another in a simple and efficient manner to prevent the inadvertent injection of incompatible therapeutic fluids through a single IV infusion line. An IV infusion line identification system, as described herein, may reduce the number of misidentified infusion lines without significant changes to the existing clinical methods and/or equipment.

Reference will now be made to the drawings to describe various aspects of exemplary embodiments of the invention. It is understood that the drawings are diagrammatic and schematic representations of such exemplary embodiments, and are not limiting of the present invention, nor are any particular elements to be considered essential for all embodiments or that elements be assembled or manufactured in any particular order or manner. No inference should therefore be drawn from the drawings as to the necessity of any element. In the following description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be obvious, however, to one of ordinary skill in the art that the present invention may be practiced without these specific details. In other cases, well known aspects of IV lines and related devices and methods, general manufacturing techniques, and the like are not described in detail herein in order to avoid unnecessarily obscuring the novel aspects of the present invention.

FIGS. 1 through 12 and the following discussion are intended to provide a brief general description of exemplary

devices in which embodiments of the invention may be implemented. While IV therapy apparatuses for administering therapeutic fluids are described below, this is but one single exemplary application for the present invention, and embodiments of the invention may be implemented in other applications, both within the medical field and in other technical fields. Accordingly, throughout the specification and claims, references to medical devices and systems, such as “IV lines,” “IV bags,” “pumps,” “needles,” “ports,” “IV therapy systems,” and the like, are intended to apply broadly to any type of items that may need to be individually identified and distinguished from other similar items, as described herein.

Furthermore, while embodiments of IV therapy systems are shown and described, it will be understood that these are merely exemplary embodiments. Various components of these exemplary embodiments may be excluded or replaced with other components known and used in the art. By way of non-limiting example, some of the exemplary embodiments include IV bags, pumps, and connectors. Each of these components could be eliminated or replaced with other components. For instance, various types of pumps, or no pump at all, can be used with the systems. Similarly, various types of fluid sources and connectors other than IV bags and Y-connectors could be employed.

With reference to FIG. 1, there is illustrated an IV infusion line assembly 100 for use in administering therapeutic fluid to a patient. The IV infusion line assembly 100 includes an elongated member 102 with a fluid conduit thereto. The fluid conduit may provide fluid communication for one or more therapeutic fluids, such as saline, medications, or nutrients. The IV infusion line assembly 100 includes an optical member 104 that is at least partially affixed to the elongated member 102. The optical member 104 is at least partially optically transmissive, such that light may pass through the optical member 104.

In some embodiments, the elongated member 102 may have a therapeutic fluid input 106 and a therapeutic fluid output 108. The therapeutic fluid input 106 may allow the elongated member to connect to a reservoir of therapeutic fluid, such as an IV bag, a glass bottle, a plastic bottle, a syringe, or other sterile reservoir. At an opposing end of the elongated member 102 is a therapeutic fluid output 108. The therapeutic fluid output is configured to connect the elongated member 102 to an access device (not shown), such as a needle or port, so that the elongated member 102 can provide fluid communication to a patient.

The optical member 104 has a first end 110 and a second end 112. In some embodiments, the first end 110 is located proximate the therapeutic fluid input 106 of the elongated member 102 and the second end 112 is located proximate the therapeutic fluid output 108 of the elongated member 102. At least a portion of the elongated member 102 and optical member 104 are fixed relative to one another. The elongated member 102 and optical member 104 are flexible, such that the optical member 104 and elongated member 102 may move as one or the other is moved. In some embodiments, the entire length of the optical member 104 is fixed to the elongated member 102. In other embodiments, a portion less than the entire length of the optical member 104 is fixed to the elongated member 102. In some embodiments, the first end 110 of the optical member 104 is fixed to the elongated member 102 and the second end 112 is fixed to the elongated member 102.

The optical member 104 may be optically transmissive to allow light to pass through and/or be transmitted by the optical member 104. In some embodiments, the optical

member 104 may have a transmission percentage in visible wavelengths in a range having an upper value, a lower value, or upper and lower values including any of 40%, 45%, 50%, 55%, 60%, 65%, 70%, 75%, 80%, 85%, 90%, 95%, or any values therebetween. For example, the optical member 104 may have a transmission percentage in visible wavelengths greater than 40%. In other examples, the optical member 104 may have a transmission percentage in visible wavelength less than 95%. In yet other examples, the optical member 104 may have a transmission percentage between 40% and 95%. In further examples, the optical member 104 may have a transmission percentage between 50% and 90%.

In some embodiments, the optical member 104 may be a fiber optic cable. For example, at least a portion of a light that is provided at the first end 110 of the optical member 104 may be conveyed to the second end 112 of the optical member 104. The light may be conveyed from the first end 110 to the second end 112 via internal refraction. For example, the optical member 104 may have a first index of refraction and the surrounding environment, such as air, may have a second index of refraction that is less than the first index of refraction. The light may propagate along the inside of the optical member 104 in a longitudinal direction refracting off of the surface of the optical member 104 at an angle less than a critical angle, at least partially dependent on the relationship of the first index of refraction and the second index of refraction. In some embodiments, the optical member 104 may have an index of refraction greater than 1.5. In other embodiments, the optical member 104 may have an index of refraction greater than 1.8. In yet other embodiments, the optical member 104 may have an index of refraction greater than 2.0.

In some embodiments, the optical member 104 may be configured to convey at least a portion of the light in a longitudinal direction (i.e., from the first end 110 to the second end 112 or vice versa). The optical member 104 is configured to emit at least some of the light in a transverse direction (i.e. in a direction transverse to the longitudinal direction) and between the first end 110 and the second end 112. For example, when a light is provided at the first end 110 of the optical member 104, at least 10% of the light is emitted transversely along the length of the optical member 104. In other examples, when a light is provided at the first end 110 of the optical member 104, at least 20% of the light is emitted transversely along the length of the optical member 104. In yet other examples, when a light is provided at the first end 110 of the optical member 104, at least 30% of the light is emitted transversely along the length of the optical member 104. In at least one example, when a light is provided at the first end 110 of the optical member 104, at least 50% of the light is emitted transversely along the length of the optical member 104.

FIG. 2 illustrates a transverse cross-sectional view of the IV infusion line assembly 100 of FIG. 1. The elongated member 102 has an outer surface 114 and an inner surface 116. The inner surface 116 defines a fluid conduit 118 that extends longitudinally through the elongated member to provide fluid communication therethrough. The fluid 120 may be a therapeutic fluid provided from a reservoir to a patient.

In some embodiments, the optical member 104 may be uniform along a length thereof. In other embodiments the optical member 104, as shown in FIG. 2, includes a plurality of scattering elements embedded in the optical member 104 to scatter light transmitted therethrough and emit the light through a sidewall of the optical member 104.

In some embodiments, the optical member **104** may be at least partially affixed to the outer surface **114** of the elongated member **102**. For example, the optical member **104** may be affixed to the outer surface **114** of the elongated member **102** with a plurality of fasteners or clamps. In other examples, the optical member **104** may be adhered to the outer surface **114** with an adhesive positioned therebetween. In yet other examples, the optical member **104** may be directly bonded to the elongated member **102**, such as by partially melting of the optical member **104** and/or elongated member **102** to bond the material of the optical member **104** and elongated member **102**. The optical member **104** and elongated member **102** may be bonded together by sonic welding, by frictional welding, by application of heat from an external source, or by other partial melting methods. Embodiments may include any combination of said or other means for at least partially affixing the optical member **104** to the outer surface **114** of the elongated member **102**.

FIGS. **3A** through **3D** illustrate various views of an embodiment of the IV infusion line assembly **100** of FIG. **1** in which the optical member **104** is at least partially coupled to the elongated member **102** with a plurality of line fasteners **130** (also referred to herein as “rigid clamps”). As used herein, the “rigid clamps” are “rigid” in that they do not necessarily require moving parts for adapting to and fastening the optical member **104** and elongated member **102**. The “rigid clamps” may therefore include an amount of flexibility inherent in the material in which they are made (e.g., a suitable polymer or metal material).

The rigid clamps **130** include a first opening **131** and a second opening **132**, each adapted to receiving the optical member **104** and the elongated member **102**. The rigid clamps **130** have a first groove **140** adapted to removably secure the optical member **104**. The rigid clamps **130** also have a second groove **141** and a third groove **142**, which are adapted to, in tandem, removably secure the elongated member **102**. For example, a user may loop the optical member **104** and elongated member **102** through the respective openings **131** and **132**, may position the optical member **104** within the first groove **140**, and may position the elongated member **102** within the second groove **141** and third groove **142**.

In one of arrangement, the rigid clamps **130** are spaced about six to eight inches apart along the length of the IV infusion line assembly **100**. Although six to eight inch spacing is the presently preferred configuration, other configurations may include tighter spacing (e.g., a half inch of space between the rigid clamps **130** along the length of the IV infusion line assembly **100**), looser spacing (e.g., fourteen inches of space between the rigid clamps **130** along the length of the IV infusion line assembly **100**), a non-uniform spacing arrangement (e.g., with variable spacing between the rigid clamps **130** along the length of the IV infusion line assembly **100**), etcetera.

FIGS. **3E** through **3K** show additional views of the exemplary rigid clamp **130**. In the illustrated embodiment, the first groove **140** has a smaller diameter than that of the second and third grooves **141** and **142**. Such a configuration beneficially allows the relatively smaller optical member **104** to engage with the first groove **140** while the relatively larger elongated member **102** engages with the second and third grooves **141** and **142**. In other embodiments, the groove sizes may be adjusted according to corresponding sizes of elongated members and/or optical members. In some implementations, the positions of the elongated member **102** and the optical member **104** may be reversed. Other embodiments may additionally or alternatively use other

types of fasteners or clamps (e.g., spring-loaded clamps, hinged clasps) to at least partially couple the optical member **104** to the elongated member **102**.

In some embodiments, the connection between the elongated member **102** and the optical member **104** may be breakable by a user. For example, at least a portion of the longitudinal length of the connection between the elongated member **102** and optical member **104** may be broken (e.g., the elongated member **102** and optical member **104** may be pulled apart from one another) to allow the use of inline filters, rotary pumps, or for connection of other devices, as needed by a user.

For example, FIG. **4** illustrates an embodiment of an IV infusion line identification system with an IV infusion line assembly **200** with at least a portion of the optical member **204** branched from the elongated member **202** to allow a light source **222** to connect to the optical member **204**. The light source **222** may be coupled to the IV infusion line assembly **200** prior to a sterilization procedure (e.g., gamma radiation, ethylene oxide gas). Alternatively, the light source **222** may be a portable light source reusable with a plurality of IV infusion line assemblies **200**. For example, a user, such as a doctor, a nurse practitioner, a physician’s assistant, etc., may carry a light source **222** as described herein, and use the light source with a plurality of IV infusion line assemblies **200** on a single patient or with multiple patients. Typically, however, the light source **222** will be coupled to the IV infusion line assembly **200** prior to sterilization so that the system may be provided to users in a sterile and ready-to-use state.

The light source **222** may be selectively coupled to the optical member **204** to provide a light to the optical member **204**. The light source **222** may include an outboard power supply, such as a rechargeable and/or replaceable battery, allowing the light source **222** to be carried with a user. In other embodiments, the light source **222** may have one or more connectors to allow the light source **222** to be connected to an external power source. The light source **222** may provide light to the first end **210** of the optical member **204** to illuminate the optical member **204** along a longitudinal length of the optical member **204**. In other embodiments, the light source **222** may provide light to the second end (e.g., the second end **112** as shown in FIG. **1**) of the optical member **204** and illuminate the optical member **204** along a longitudinal length of the optical member **204**.

FIG. **5** illustrates an exploded view of an embodiment of a light source **222** of FIG. **4**. The light source **222** includes an O-ring slot **250** for receiving an O-ring **251**. The O-ring **251** is adapted to removably secure the optical member **204** to provide selective coupling between the optical member **204** and the light source **222**. Other embodiments may additionally or alternatively use other means for effecting selective coupling between the optical member **204** and the light source **222** (e.g., friction fitting, adhesive, clamps).

In some embodiments, the light source **222** may be activated by a user-operated manual switch, such as the illustrated push button **240**. Although the user operable manual switch is a presently preferred embodiment, other embodiments may include systems for automatically activating the light source **222** upon coupling the optical member **204** to the light source **222**, as described below with respect to FIG. **6**. FIG. **6** illustrates a cross-sectional view of one optional configuration of the light source **222** of FIG. **4** which includes a sensor for automatic actuation of the light source **222** (e.g., as an alternative to a manual switch). The light source **222** may have a light emitting diode (“LED”) **224**, light bulb, laser diode, or other photon source posi-

tioned adjacent a cavity 226 in the light source 222. The cavity 226 may have a sensor 228 positioned in a side of the cavity 226. The sensor 228 may be configured to sense the presence of an optical member 204 positioned in the cavity 226. The sensor 228 is operably coupled to the LED 224 to allow electricity to the LED 224 upon sensing the presence of the first end 210 (or second end) of the optical member 204 in the cavity 226. In other words, the light source 222 provides a light to the optical member 204 when the user inserts a portion of the optical member 204 into the light source 222. In some embodiments, the LED 224 may be positioned at a rear end 230 of the cavity 226. In other embodiments, the LED 224 may be positioned at other orientations to the cavity 226.

The sensor 228 may be a physical sensor, such as a switch, toggle, or button that senses the optical member 204 via mechanical contact with the optical member 204. In other embodiments, the sensor 228 may be an optical sensor, such as an infrared sensor, UV sensor, laser sensor, or other sensor that senses the optical member 204 via interference between the optical member 204 and an emitted signal.

FIGS. 7A and 7B illustrate another embodiment of a light source 722. The light source 722 may be configured in a fashion similar to that of the light source 222 of FIG. 4 except as noted below. The light source 722 may be selectively attachable to the elongated member 702 by means of a first clip 761 with a first opening 771 facing a first direction, a second clip 762 with a second opening 772 facing a second direction opposite the first direction, and a third clip 763 with a third opening 773 facing the first direction. Other embodiments may use a single clip. In such embodiments, the single clip may extend across approximately a majority of the length of the light source 722. Other embodiments may include a plurality of clips (with at least one facing an opposite direction from one other), a plurality of clips with openings facing the same direction, a channel groove, a plurality of channel grooves, or other structural configurations for making the light source 722 selectively attachable to the elongated member 702.

In the illustrated embodiment, the clips 761, 762, and 763 are arranged so as to be spread across a sufficient length of the light source 722 to provide a connection when the light source 722 is coupled to the elongated member 702. For example, the distance between the first clip 761 and third clip 763 may be about 50% to about 80% of the overall length of the light source 722.

As with other embodiments described herein, the light source, as a first light component, may be positioned near a first end the elongated member 702 (e.g., near the fluid input) and an optical member (not shown in this view), as a second light component, may extend and be positioned near a second end of the elongated member 702 (e.g., near the fluid output). The first and second light components are operatively coupled to one another such that when the first light component is activated to generate a light signal at the first end of the elongated member 702, a corresponding light signal will be generated at the second end of the elongated member 702 by way of the second light component.

FIG. 8 illustrates another embodiment of an IV infusion line identification system with an IV infusion line assembly 300 with a first end 310 of the optical member 304 coupled to the elongated member 302. The light source 322 is configured to connect over the elongated member 302 and the optical member 304 from the transverse direction to provide light to the first end 310 (or second end) of the optical member 304 without having to decouple an end of the optical member 304 and the elongated member 302.

FIGS. 9A and 9B show detail views of the embodiment of a light source 322 of FIG. 8. FIG. 9A shows a cross-sectional side view of the IV infusion line assembly 300 positioned in the light source 322. The cavity 326 of the light source 322 shown in FIGS. 9A and 9B is configured to allow the elongated member 302 to extend through the light source 322 while the optical member 304 terminated in the light source 322 adjacent an LED 324 (or other photon source).

FIG. 9B shows an end view of the light source 322 showing a sensor 328 in a wall 332 of the cavity 326 shown in FIG. 9A. Referring again to FIG. 9B, the sensor 328 may be configured to sense the presence of the elongated member 302 positioned in the light source 322. Similar to the sensor 228 described in relation to FIG. 6, the sensor 328 may be a physical sensor, such as a switch, toggle, or button that senses the elongated member 302 via mechanical contact with the elongated member 302. In other embodiments, the sensor 328 may be an optical sensor, such as an infrared sensor, UV sensor, laser sensor, or other sensor that senses the elongated member 302 via interference between the elongated member 302 and an emitted signal.

In the depicted embodiment, the sensor 328 is depressed by the elongated member 302 when a force is applied to the elongated member 302 by a clip 334 of the light source 322. The clip 334 may be movably connected to the light source 322 about a hinged connection 336. The hinged connection 336 may be biased to close the clip 334 and/or hold the clip 334 closed against the light source 322. The bias of the hinged connection 336 may apply a sufficient force through the clip 334 to compress the elongated member 302 against the sensor 328. The bias of the hinged connection 336 may apply a sufficient force through the clip 334 to retain the light source 322 on the elongated member 302 when a user releases the light source 322. In other words, the user may clip the light source 322 onto the elongated member 302 and the light source 322 may hang in place on the elongated member 302 without the user continuing to support the light source 322.

FIG. 10A illustrates a transverse cross-section of another embodiment of an IV infusion line assembly 400. The elongated member 402 defines a conduit 418 through the center of the elongated member 402 and an optical member 404 is positioned in contact with an outer surface of the elongated member 402. In some embodiments, the optical member 404 may be fixed to the outer surface of the elongated member 402. In other embodiments, the optical member 404 may be slidable in a longitudinal direction relative to the elongated member 402. In other word, the optical member 404 may be positioned circumferentially about the elongated member 402 but not fixed thereto.

FIG. 10B illustrates a longitudinal cross-section of the embodiment of an IV infusion line assembly 400. In such embodiments, the optical member 404 may terminate before the end of the elongated member 402 or the terminal end of the IV infusion line assembly 400 may be obscured or covered by medical equipment or the patient. In such embodiment, a light may be provided to the optical member 404 in a transverse direction through one or more diffraction optical elements such as an in-coupling grating 438 shown in FIG. 10B. The in-coupling grating 438 includes a plurality of wedges or other lenses that refract light at an angle and allow the light to propagate within the optical member 404 in a longitudinal direction.

As described herein, the optical member and the elongated member may selectively separable to allow a user to detach at least a portion of the optical member from the elongated member. FIG. 11 illustrates an embodiment of an

11

IV infusion line assembly **500** in which the optical member **504** has been detached from the elongated member **502** and the elongated member **502** is directed through a filter **540**. The filter **540** is configured to filter the contents (i.e., therapeutic fluid) of the elongated member **502** while the optical member **504** continues around the filter **540** and rejoins the elongated member **502** on the opposing side of the filter **540**.

FIG. **12** illustrates an embodiment of an IV infusion line assembly **600** in which the optical member **604** has been detached from the elongated member **602** and the elongated member **602** is directed through a rotary pump **642**. The rotary pump **642** is configured to apply a force to the elongated member **602** to urge the contents (i.e., therapeutic fluid) of the elongated member **502** in the longitudinal direction. The optical member **604** continues around the rotary pump **642** and rejoins the elongated member **602** on the opposing side of the rotary pump **642**.

At least some of the embodiments of an IV infusion line described herein allow a user to illuminate the IV infusion line using a light source to identify a length of the IV infusion line in a clinical environment. The IV infusion line may be disposable, elongated member and optical member included, and used with conventional adapters and equipment.

FIG. **13** illustrates an alternative embodiment of an infusion line assembly **800**. As with other embodiments described herein, the infusion line assembly **800** includes an elongated member **802** and a first light source **822** disposed at a first end **806** of the elongated member **802** (e.g., near an IV bag **860** and associated fluid input). In this embodiment, the optical member is omitted, and instead, the infusion line assembly **800** includes a second light source **823** disposed at a second end **808** of the elongated member **802** (e.g., near a fluid output and patient port **862**). The second light source **823** is communicatively coupled to the first light source **822**. Thus, rather than using an optical member to transmit light generated by the first light source **822** at the first end **806** to the second end **808**, the illustrated embodiment utilizes the two operatively and communicatively coupled light sources **822** and **823** to ensure that the light signal generated at one end of the elongated member **802** has a corresponding light signal generated at the opposite end of the elongated member **802**.

The first and second light sources **822** and **823** may be operatively and communicatively coupled via a wireless connection/link. For example, the first and second light sources **822** and **823** may be paired using a Bluetooth wireless link, Wi-Fi, or other suitable wireless communication protocol.

In use, a first light component (in the form of the first light source **822**) is positioned near the first end **806** of the elongated member **802** and a second light component (in the form of the second light source **823**) is positioned near the second end **808** of the elongated member **802**. The first and second light components are operatively coupled to one another (e.g., via a wireless communication link) so that when either is activated, the other is likewise activated. In this manner, a user can activate the first light source **822** or the second light source **823**, and the other light source will also automatically be activated, providing a visual indication confirming that each of ends **806** and **808** belong to the same elongated member **802**. As stated above, this visual indication can prevent infusion line misidentification and associated accidents and patient risks. For example, a caretaker can quickly and easily use the system to identify which

12

infusion line and/or medicine is attached to which patient vein, and can thereby identify the correct setup quickly and safely.

As shown in FIG. **14**, the infusion line system can also optionally include a pump assembly **842** attachable or operatively coupled to the elongated member **802**. The pump assembly **842** may be provided as a peristaltic pump or other suitable means of moving fluid through the elongated member **802**. The pump assembly **842** may also be communicatively coupled (via the aforementioned wireless link) to the first light source **822** and the second light source **823** such that activation of any one of the first light source **822**, second light source **823**, or pump assembly **842** causes activation of the other components. For example, the pump assembly may be activated when a user actuates a controller **840a** (the term “controller” also being synonymously referred to herein as a “manual switch”). The controller **840a** may be provided as a pushbutton, toggle, switch, slider, knob, or other suitable means for selectively activating the device.

Upon activation, the pump assembly **842** may display a visual indicator indicating that the device has been activated. For example, a light **824a** can turn on to indicate activation of the device. In some embodiments, the light **824a** is separate from the controller **840a**. In other embodiments, the light **824a** may be included in the controller **840a** itself. For example, the controller **840a** may be a pushbutton that lights up when activated and turns off when pressed again.

Upon activation of the pump assembly **842**, corresponding visual indicators (e.g., light **824b** as shown in FIG. **15**) at the first and second light sources **822** and **823** are also automatically activated. The infusion line system **800** need not necessarily be activated by actuating the controller **840a** of the pump assembly **842**. For example, a user may activate any one of the first light source **822**, second light source **823**, or pump assembly **842** to trigger activation of the corresponding indicators (e.g., light signals) in the other components. In this manner, a user may activate whichever component is closest or is otherwise most convenient to activate, and by so doing can automatically activate all other communicatively linked components of the system.

As shown, the pump assembly **842** may also include one or more stations **850** configured to receive light sources **822** and/or **823**. The stations **850** may be configured as charging ports for charging the internal battery/batteries of the light sources **822** and/or **823** when they are plugged in or otherwise attached. The pump assembly **842** may itself be powered by wired connection to a wall outlet and/or may include its own internal battery.

In some embodiments, the pump assembly **842** includes a speaker **854** capable of providing an audible alarm. For example, when a low battery condition is detected in any of the linked light sources, the speaker **854** can be triggered to provide an audible alarm notifying nearby users of the need to replace or otherwise attend to the components. The alarm may additionally or alternatively include other indicators, such as flashing lights at one or more of the pump assembly **842** or the light sources **822**, **823**, the sending of an error message to other associated devices, etcetera. Either or both of the light sources **822**, **823** may include a speaker, either in addition to or as an alternative to the speaker **854** of the pump assembly **842**. However, a typical embodiment will omit speakers at the light sources **822**, **823**.

In some embodiments, two or more components of the infusion line system **800** are provided together as a kit. For example, the two light sources **822** and **823** may be packaged together as a pair. Preferably, the wireless pairing/linking of the two associated light sources will be estab-

lished prior to packaging, so that the components are ready to use immediately after opening. Pairing/linking prior to packaging can also reduce the risk of error during use, since it will not be necessary for the user to manually pair one or more pairs of lights during installation on corresponding infusion lines. In some embodiments, a kit includes a pair of light sources and the pump assembly **842**. Again, it is preferable that these components be wirelessly paired/linking prior to packaging so that the components are more readily used and risks associated with incorrect installation or pairing are reduced. Any of such kits are also preferably sterilized using a suitable sterilization process known in the art, such as a cold sterilization process typically used to sterilize pumps and infusion lines.

FIG. **15** illustrates a detailed view of one of the light sources **822**. Since each light source **822** and **823** will typically be similar in size, shape, and construction, only the first light source **822** is shown. However, it will be understood that the second light source **823** may include the same components and features as illustrated. The light source **822** may include any of the other light source embodiments described herein. For example, the light source **822** may include any of the clip features shown in FIGS. **7A** and **7B** to enable effective attachment to the elongated member **802**. In a typical embodiment, the light source **822** will include one or more internal batteries, though other power sources, such as a direct electrical connection to a wall outlet, may additionally or alternatively be utilized.

As with the optional pump assembly **824**, the light source **822** includes a visual indicator in the form of a light **824b** and a corresponding controller **840b** (also synonymously referred to herein as a “manual switch”). When the controller **840b** is actuated, the light **824b** is activated, and the corresponding visual indicators of the other communicatively linked light sources (and pump assembly **842** where applicable) are also automatically activated. As described in reference to the pump assembly **842**, the light **842b** and controller **840b** may be separate features, as shown, or may alternatively be combined into one manually activatable component such as a pushbutton that lights up upon actuation.

Presently preferred embodiments also include a battery protector **852** configured to prevent accidental activation of the device and/or draining of the battery prior to intended use. The battery protector **852** may be a thin paper, film, or other such structure that partially extends into the light source **822** to break the internal electrical circuit and prevent activation during shipping and storage of the device. For example, the battery protector **852** typically extends across a surface of a battery between the battery and the terminal connector.

A portion of the battery protector **852** (the portion visible in FIG. **15**) extends beyond the housing of the light source **822** so that a user can grip the battery protector **852** and pull it away from the light source **822**. This allows the internal circuit of the light source **822** to close and allows initiation of the device. Upon initiation, the wireless communication component (e.g., Bluetooth component) of the device will cause the device to search for and seek to establish a communicative link to its associated components (the other light source and optional pump assembly). Once all components have been initiated, the communicative link will be established and the components will be ready for use. The battery/batteries may be designed so that light source operation lasts the duration of a standard IV bag, which is usually about 96 hours.

Certain embodiments may be configured so that the visual indicators activate automatically upon initiation. Additionally, or alternatively, activation and deactivation may be selectively controlled through actuation of the controllers **840a**, **840b**, as described by the foregoing.

In some embodiments, the visual indicators of each set of communicatively linked components have corresponding features to distinguish from other sets of communicatively linked components. For example, one pair of linked light sources may have a first color of light when activated while another pair of linked light sources may have a second, different color of light when activated.

Although the foregoing embodiment has been described with reference to two light sources, it will be understood that other light sources may additionally be included as well. For example, some embodiments may include a series of communicatively linked light sources spanning the length of the elongated member **802**, such as one or more light sources positioned at intermediate positions between the ends of the elongated member **802**.

The articles “a,” “an,” and “the” are intended to mean that there are one or more of the elements in the preceding descriptions. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. Additionally, it should be understood that references to “one embodiment” or “an embodiment” of the present disclosure are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features. Numbers, percentages, ratios, or other values stated herein are intended to include that value, and also other values that are “about” or “approximately” the stated value, as would be appreciated by one of ordinary skill in the art encompassed by embodiments of the present disclosure. A stated value should therefore be interpreted broadly enough to encompass values that are at least close enough to the stated value to perform a desired function or achieve a desired result. The stated values include at least the variation to be expected in a suitable manufacturing or production process, and may include values that are within 5%, within 1%, within 0.1%, or within 0.01% of a stated value.

A person having ordinary skill in the art should realize in view of the present disclosure that equivalent constructions do not depart from the spirit and scope of the present disclosure, and that various changes, substitutions, and alterations may be made to embodiments disclosed herein without departing from the spirit and scope of the present disclosure. Equivalent constructions, including functional “means-plus-function” clauses are intended to cover the structures described herein as performing the recited function, including both structural equivalents that operate in the same manner, and equivalent structures that provide the same function. It is the express intention of the applicant not to invoke means-plus-function or other functional claiming for any claim except for those in which the words ‘means for’ appear together with an associated function. Each addition, deletion, and modification to the embodiments that falls within the meaning and scope of the claims is to be embraced by the claims.

The terms “approximately,” “about,” and “substantially” as used herein represent an amount close to the stated amount that still performs a desired function or achieves a desired result. For example, the terms “approximately,” “about,” and “substantially” may refer to an amount that is within 95% of, within 99% of, within 99.9% of, or within 99.99% of a stated amount. Further, it should be understood that any directions or reference frames in the preceding

15

description are merely relative directions or movements. For example, any references to “up” and “down” or “above” or “below” are merely descriptive of the relative position or movement of the related elements.

Elements described in relation to any embodiment depicted and/or described herein may be substituted for or combined with elements described in relation to any other embodiment depicted and/or described herein. For example, any of the components or features described in relation to the light source 722 of FIG. 7 may be substituted for or combined with any of the components or features described in relation to the IV infusion line assembly 200, and vice versa.

The present invention may be embodied in other specific forms without departing from its spirit or characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

What is claimed is:

1. An intravenous (IV) infusion line assembly, the assembly comprising:

an elongated member having a fluid conduit for administering therapeutic fluid to a patient, the fluid conduit configured to provide fluid communication between a first end of the elongated member and a second end of the elongated member;

a first light source selectively attachable to the elongated member at least near the first end of the elongated member; and

a second light source selectively attachable to the elongated member at least near the second end of the elongated member,

wherein the first and second light sources are operatively coupled to one another via a wireless connection,

wherein the first light source includes a manual switch configured to, upon actuation, activate the first light source to provide a light signal at the first light source, and to automatically activate at least one additional light source to provide a corresponding light signal at the at least one additional light source, and

wherein the second light source includes a manual switch configured to, upon actuation, activate the second light source to provide a light signal at the second light source, and to automatically activate the at least one additional light source to provide a corresponding light signal at the at least one additional light source.

2. The assembly of claim 1, wherein at least one of the first and second light sources includes one or more clips enabling the light source to be selectively attachable to the elongated member.

3. The assembly of claim 1, wherein at least one of the first and second light sources includes a battery protector configured to prevent activation of the at least one light source until the battery protector has been removed from the at least one light source.

4. The assembly of claim 3, wherein the at least one light source is configured such that upon removal of the battery protector, the at least one light source begins an initiation process to establish the wireless connection with the other light source.

5. The assembly of claim 1, wherein the first and second light sources are configured to provide light for a duration of about 72 to 120 hours.

16

6. The assembly of claim 1, further comprising a pump assembly communicatively linked to the first and second light sources via the wireless connection, the pump assembly including a manual switch, wherein the first and second light sources are configured to provide respective light signals upon activation of the manual switch of the pump assembly, and wherein the pump assembly is configured to generate a light signal corresponding to the light signals of the first and second light sources upon activation of the first light source, and is configured to generate a light signal corresponding to the light signals of the first and second light sources upon activation of the second light source.

7. The assembly of claim 6, wherein the pump assembly includes a peristaltic pump.

8. The assembly of claim 6, wherein the pump assembly is also configured to generate a light signal corresponding to the light signals of the first and second light sources upon activation of the pump assembly itself.

9. The assembly of claim 6, wherein the pump assembly includes a speaker capable of providing an audible alarm upon detection of a low battery condition in at least one of the first or second light sources.

10. The assembly of claim 6, wherein the pump assembly includes one or more charging ports for receiving the first and/or second light source to charge the first and/or second light source.

11. The assembly of claim 1, wherein the wireless connection is an ultrahigh frequency radio wave connection.

12. An intravenous (IV) infusion line assembly, the assembly comprising:

an elongated member having a fluid conduit for administering therapeutic fluid to a patient, the fluid conduit configured to provide fluid communication between a first end of the elongated member and a second end of the elongated member;

a first light source selectively attachable to the elongated member near the first end of the elongated member, the first light source having a manual switch and being configured to generate a light signal upon activation of the manual

switch, and to automatically activate at least one additional light source to provide a corresponding light signal at the at least one additional light source; a second light source selectively attachable to the elongated member near the second end of the elongated member, the second light source having a manual switch and being configured to generate a light signal upon activation of the manual switch, and to automatically activate at least one additional light source to provide a corresponding light signal at the at least one additional light source, wherein the first and second light sources are communicatively coupled to one another via a wireless connection; and a pump assembly communicatively linked to the first and second light sources via the wireless connection, the pump assembly including a manual switch configured to generate a light signal upon activation of the manual switch, and to automatically activate at least one additional light source to provide a corresponding light signal at the at least one additional light source.

13. The assembly of claim 12, wherein the pump assembly includes a peristaltic pump.

14. The assembly of claim 12, wherein the pump assembly includes a speaker capable of providing an audible alarm upon detection of a low battery condition in at least one of the first or second light sources.

17

15. The assembly of claim 12, wherein the pump assembly includes one or more charging ports for receiving the first and/or second light source to charge the first and/or second light source.

16. A kit for providing visual identification of opposite ends of an infusion line, the kit comprising:

a first light source adapted to be selectively attachable to an infusion line, the first light source having a manual switch and being configured to generate a light signal upon activation of the manual

switch, and to automatically activate at least one additional light source to provide a corresponding light signal at the at least one additional light source; a second light source adapted to be selectively attachable to an infusion line, the second light source having a manual switch and being configured to generate a light signal upon activation of the manual switch, and to automatically activate at least one additional light source to provide a corresponding light signal at the at least one additional light source; and a pump assembly, the pump assembly including a light and a manual switch, the pump assembly being configured to generate a light signal upon activation of the manual switch of the pump assembly, and to automatically activate at least one additional light source to provide a corresponding light signal at the at least one additional light source,

wherein each of the first light source, second light source, and pump assembly are communicatively coupled to one another via a wireless connection and are configured such that

when the first light source is activated to provide a light signal, the second light source and pump assembly are also automatically activated to provide a corresponding light signal,

when the second light source is activated to provide a light signal, the first light source and the pump assembly are also automatically activated to provide a corresponding light signal, and

when the pump assembly is activated to provide a light signal, the first and second light sources are also automatically activated to provide a corresponding light signal,

thereby enabling visual identification of different sections of an infusion line when each is respectively attached to different sections of the infusion line.

18

17. The kit of claim 16, wherein at least one of the first and second light sources includes a battery protector configured to prevent activation of the at least one light source until the battery protector has been removed from the at least one light source, and wherein the at least one light source is configured such that upon removal of the battery protector, the at least one light source begins an initiation process for establishing the wireless connection with the other light source.

18. The kit of claim 16, wherein at least one of the first and second light sources includes one or more clips enabling the light source to be selectively attachable to an infusion line.

19. A method of modifying an infusion line to make the infusion line identifiable, the method comprising:

providing an infusion line;

providing a first light source adapted to be selectively attachable to an infusion line, the first light source having a manual switch and being configured to generate a light signal upon activation of the manual

switch, and to automatically activate at least one additional light source to provide a corresponding light signal at the at least one additional light source; providing a second light source adapted to be selectively attachable to an infusion line, the second light source having a manual switch and being configured to generate a light signal upon activation of the manual switch, and to automatically activate at least one additional light source to provide a corresponding light signal at the at least one additional light source,

wherein the first and second light sources are operatively coupled to one another via a wireless connection and are configured such that

when the first light source is activated to provide a light signal, the second light source is also automatically activated to provide a corresponding light signal, and when the second light source is activated to provide a light signal, the first light source is also automatically activated to provide a corresponding light signal;

attaching the first light source to a first end of the infusion line and the second light source to a second end of the infusion line; and

activating the manual switch of the first light source or the manual switch of the second light source to cause both the first and second light sources to activate.

* * * * *