



US010589482B2

(12) **United States Patent**  
**Mancini et al.**

(10) **Patent No.:** **US 10,589,482 B2**  
(45) **Date of Patent:** **Mar. 17, 2020**

(54) **PROCESS FOR MANUFACTURING TYRES FOR VEHICLE WHEELS**

(56) **References Cited**

(71) Applicant: **PIRELLI TYRE S.p.A.**, Milan (IT)  
(72) Inventors: **Gianni Mancini**, Milan (IT); **Maurizio Marchini**, Milan (IT); **Gaetano Lo Presti**, Milan (IT)

U.S. PATENT DOCUMENTS  
2,664,937 A 1/1954 Hirsch  
3,016,321 A 1/1962 Beckadolph  
(Continued)

(73) Assignee: **PIRELLI TYPRE S.p.A.**, Milan (IT)  
(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 511 days.

FOREIGN PATENT DOCUMENTS

AT 317 014 8/1974  
CN 1564739 A 1/2005  
(Continued)

(21) Appl. No.: **15/437,764**

NII Shinnoi Promy, FR-1463469-A, machine translation. (Year: 1966).\*

(22) Filed: **Feb. 21, 2017**

(Continued)

(65) **Prior Publication Data**  
US 2017/0225421 A1 Aug. 10, 2017

*Primary Examiner* — Robert C Dye  
*Assistant Examiner* — Sedef E Paquette  
(74) *Attorney, Agent, or Firm* — Finnegan, Henderson, Farabow, Garrett & Dunner, L.L.P.

**Related U.S. Application Data**

(63) Continuation of application No. 13/055,114, filed as application No. PCT/IB2008/001933 on Jul. 23, 2008, now Pat. No. 9,616,628.

(51) **Int. Cl.**  
**B29D 30/32** (2006.01)  
**B29D 30/24** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **B29D 30/32** (2013.01); **B29D 30/244** (2013.01); **B29D 2030/3207** (2013.01); **B29D 2030/3264** (2013.01); **B29D 2030/3278** (2013.01)


(58) **Field of Classification Search**  
CPC ..... B29D 30/18; B29D 30/244; B29D 30/32; B29D 30/36; B29D 2030/3207;

(57) **ABSTRACT**

A process for manufacturing a lot of tires including: selecting a first operating radial position; setting a positioning device to the first operating radial position; setting a turning up device to the first operating radial position; positioning a first annular anchoring structure on an edge of a first carcass ply; turning up the edge of the first carcass ply around the first annular anchoring structure; pulling down the edge of the first carcass ply toward the longitudinal axis of a first forming support; replacing the first forming support with a second forming support; selecting a second operating radial position; setting the positioning device to the second operating radial position; setting the turning up device to the second operating radial position; positioning a second annular anchoring structure on an edge of the second carcass ply; and turning up the edge of the second carcass ply around the second annular anchoring structure.

(Continued)

**4 Claims, 6 Drawing Sheets**



(58) **Field of Classification Search**  
 CPC .... B29D 2030/3221; B29D 2030/3257; B29D  
 2030/3264; B29D 2030/3278  
 USPC ..... 156/131, 132, 135  
 See application file for complete search history.

GB	620660 A	*	3/1949	.....	B29D 30/248
GB	878837		10/1961		
GB	947182		1/1964		
GB	1153944		6/1969		
GB	1390399		4/1976		
JP	49-103967		10/1974		
JP	58-108125		6/1983		
JP	59-230736		12/1984		
JP	60-92837		5/1985		
JP	02-153728		6/1990		
JP	2622987		6/1997		
JP	11-268150		10/1999		
SU	295691		2/1971		
SU	1270020		11/1986		
SU	750902		1/1991		
SU	1195567		12/1991		
WO	WO 2008/001154	A1	1/2008		
WO	WO-2009/054185	A1	4/2009		
WO	WO-2009/063264	A1	5/2009		
WO	WO-2010/018420	A1	2/2010		

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,032,093	A	5/1962	Nebout		
3,078,204	A	2/1963	Appleby		
3,765,986	A	10/1973	Brey		
3,776,793	A	12/1973	Frazier		
3,948,591	A	4/1976	Kratochvil		
4,324,604	A	4/1982	Alexander		
4,353,771	A	10/1982	Yuhas		
4,362,592	A *	12/1982	Ruppel	.....	B29D 30/32 156/402
4,498,948	A	2/1985	Brown et al.		
4,508,586	A	4/1985	Brown et al.		
4,584,038	A	4/1986	Enders		
4,923,553	A	5/1990	Nishide		
5,087,316	A	2/1992	Sumiuchi		
5,858,165	A	1/1999	Takasuga		
7,361,243	B2	4/2008	Ogawa		
2003/0168144	A1	9/2003	Weaver		
2005/0000624	A1	1/2005	Tokunaga		
2005/0150587	A1	7/2005	Wiens		
2005/0211366	A1	9/2005	Ogawa		
2006/0102272	A1	5/2006	Iyanagi et al.		

FOREIGN PATENT DOCUMENTS

DE	853 346	C	10/1952		
DE	17 29 571	A1	6/1971		
DE	21 18 467	A1	10/1972		
DE	24 11 013	A1	9/1975		
EP	0 150 925	A1	8/1985		
EP	1 537 986	A1	6/2005		
FR	1463469	A *	12/1966	.....	B29D 30/18
FR	2006441		12/1969		

OTHER PUBLICATIONS

Decision on Grant Patent for Invention dated Apr. 26, 2012 by Russian Patent Office in corresponding Russian Patent Application No. 2011106774/05(009623) (11 pages).  
 English-language translation of Decision on Grant Patent for Invention dated Apr. 26, 2012 by Russian Patent Office in corresponding Russian Patent Application No. 2011106774/05(009623) (7 pages).  
 English-language translation of Notification of the First Office Action issued by State Intellectual Property Office of the People's Republic of China in corresponding Application No. 200880131138.8 dated Feb. 17, 2013 (6 pages).  
 International Search Report from the European Patent Office for International Application No. PCT/IB2008/001933 (dated Apr. 14, 2009).  
 International Search Report from the European Patent Office for International Application No. PCT/IB2008/001912 (WO-2010/018410 A1) (dated Apr. 20, 2009).

\* cited by examiner








Fig. 1








*Fig. 3*



*Fig. 4*







Fig. 6



*Fig. 7*



## PROCESS FOR MANUFACTURING TYRES FOR VEHICLE WHEELS

### CROSS REFERENCE TO RELATED APPLICATION

This is a continuation of U.S. patent application Ser. No. 13/055,114, filed Apr. 13, 2011, which is a national stage entry under 35 U.S.C. § 371 of international Application No. PCT/IB2008/001933, filed Jul. 23, 2008. All of the aforementioned applications are incorporated herein by reference in their entirety.

### BACKGROUND OF THE INVENTION

#### Field of the Invention

The present invention relates to an apparatus for manufacturing tyres for vehicle wheels.

The invention also relates to a process for manufacturing a lot of tyres for vehicle wheels comprising at least two tyres of different radial dimensions.

#### Description of the Related Art

A tyre for vehicle wheel generally comprises a carcass structure comprising at least one carcass ply formed by reinforcing cords embedded in an elastomeric matrix. The carcass ply has end edges respectively engaged with annular anchoring structures. The latter are arranged in the tyre zones usually identified with the name of “beads” and normally consist each of an annular substantially circumferential insert on which at least one filling insert is applied, in a radially outer position thereof. Such annular anchoring structures are commonly identified as “bead cores” and have the task of keeping the tyre well fixed to the anchoring seat specifically provided in the wheel rim, thus preventing, in operation, the radially inner edge (also referred to as an “end edge” herein) of the tyre coining out from such seat.

At the beads specific reinforcing structures may be provided having the function of improving the torque transmission to the tyre.

In a radially outer position with respect to the carcass ply, a belt structure comprising one or more belt layers is associated, said belt layers being arranged radially one of top of the other and having textile or metal reinforcing cords with crossed orientation and/or substantially parallel to the direction of circumferential extension of the tyre.

Between the carcass structure and the belt structure a layer of elastomeric material, known as “under-belt”, can be provided, said layer having the function of making the radially outer surface of the carcass structure as uniform as possible for the subsequent application of the belt structure.

In a radially outer position with respect to the belt structure a tread band is applied, made from elastomeric material as well.

Between the tread band and the belt structure a so-called “under-layer” of elastomeric material can be arranged, said layer having properties suitable to ensure a steady union of the tread band itself.

On the side surfaces of the carcass structure respective sidewalls of elastomeric material are also applied, each one extending from one of the side edges of the tread band up to the respective annular anchoring structure to the beads.

### SUMMARY OF THE INVENTION

An apparatus for manufacturing the aforementioned carcass structure typically comprises a forming support extending along a longitudinal axis, wherein the above carcass ply

is laid on a device for positioning the bead core on the end edge of the carcass ply and a device for turning up the end edge of the carcass ply about the bead core.

The device for positioning the bead core essentially comprises a ring structure axially movable towards the forming support for positioning the bead core on the end edge of the carcass ply and away from the forming support for allowing the execution of the subsequent steps of the tyre bead forming process.

WO 2008/001154 to the same Applicant shows an apparatus wherein the device for turning up the end edge of the carcass ply about the bead core essentially comprises an annularly continuous pressure element axially movable toward/away to/from the forming support. Such pressure element comprises a plurality of arms, each one carrying a respective turning up roller at a free end thereof. The turning up rollers are arranged one next to the other in a circumferential direction and coaxially with respect to the longitudinal axis of the forming support. The rollers are radially movable in a synchronous manner, thus obtaining the radial expansion/contraction of the above pressure element between a contracted position and an expanded position. The combination of the radial movement of the turning up rollers and of the movement of such rollers toward/away to/from the forming support, allows turning up the end edge of the carcass ply around the bead core for making the tyre bead. The turning up device is further provided with means for adjusting the contracted position of the pressure element based on the radial dimension of the tyre to be made.

The Applicant has noted that a turning up device of the type schematically described above may be used for carrying out the step of turning up the end edge of the carcass ply in the manufacturing of tyres having different radial dimensions.

However, the Applicant has noted that with a device of the type described above it is possible to carry out the aforementioned turning up step for tyres having at most two or three different and adjacent fittings; in other words, the device described above allows carrying out the turning up step for a number of tyres having radial dimensions that differ by two or three inches only.

The Applicant has further noted that even using an apparatus of the type described in WO 2008/001154, the manufacturing of tyres of different radial dimensions would nevertheless continue to require the use of a bead core positioning device specifically designed based on the specific radial dimension of the tyre to be manufactured. The Applicant has further found that, if a step of pulling down the end edge of the carcass ply prior to the positioning of the bead core is provided and/or if a step of pulling down the filling insert of the bead core prior to the turning up of the end edge of the carcass ply about the bead core is provided, the manufacturing of tyres of different radial dimensions would require the use of respective devices specifically designed based on the specific radial dimension of the tyre to be manufactured.

The Applicant has now found that it is possible to manufacture tyres of different radial dimensions using always the same apparatus, making all the devices that are involved in the execution of the various manufacturing steps of the carcass structure, and thus at least the device for positioning the bead cores and the device for turning up the end edge of the carcass ply, radially expandable/contractible with respect to the longitudinal axis of the forming support of the apparatus.

The Applicant has further found that, if a step of pulling down the end edge of the carcass ply prior to the positioning



of the bead core is provided and/or if a step of pulling down the filling insert of the bead core prior to the turning up of the end edge of the carcass ply about the bead core is provided, it is possible to make radially expandable/contractible with respect to the longitudinal axis of the forming support of the apparatus also the devices intended to carry out the above steps, thus also in these cases being able to manufacturing tyres of different radial dimensions with a same apparatus.

The Applicant has thus found that providing an apparatus for manufacturing tyres wherein the bead core positioning device and the device for turning up the end edge of the carcass ply and, if provided, also the device for pulling down the end edge of the carcass ply and the device for pulling down the filling insert of the bead core, are expandable/contractible in radial direction it is possible to set such devices, and thus the apparatus composed thereby, in a plurality of different operating radial positions, each operating radial position being selected based on the radial dimension of the tyre to be manufactured.

Throughout the present description and following claims, the terms “radial” and “axial” and the expressions “radially inner/outer” and “axially inner/outer” are used with reference to the radial direction and to the axial direction of the forming support. The terms “circumferential” and “circumferentially” instead, are used referring to the annular extension of the forming support.

In a first aspect thereof, the present invention therefore relates to an apparatus for manufacturing tyres for vehicle wheels, the tyres comprising a carcass structure formed starting from at least one carcass ply laid on a forming support extended along a longitudinal axis, the apparatus comprising:

- at least one device for positioning at least one annular anchoring structure on at least one end edge of said at least one carcass ply, the positioning device being circumferentially extended around the longitudinal axis of the forming support and axially movable with respect to the forming support between an operating position distal from the forming support and at least one operating position close to the forming support;
- at least one device for turning up the end edge of the carcass ply around the annular anchoring structure, the turning up device being circumferentially extended about the longitudinal axis of the forming support and axially movable for approaching/moving away to/from the forming support;

wherein the positioning device and the turning up device are radially expandable/contractible in a synchronous manner with respect to the longitudinal axis of the forming support and are settable in a plurality of different operating radial positions, each operating radial position being selected based on a respective radial dimension of the tyre to be manufactured.

Throughout the present description and in the following claims, the expression: radial dimension of the tyre, indicates the nominal fitting diameter of the rim whereon the tyre is intended to be fitted, such diameter generally being indicated in inches.

In the present description and following claims, the expression “annular anchoring structure” and the term “bead core” shall often be used without distinction to indicate the same component of the tyre.

Advantageously, an apparatus of the type described above may be used for manufacturing tyres having different radial dimensions; in fact, such apparatus is settable in a plurality of different operating configurations, each operating con-

figuration being defined by a respective radial position of the devices for positioning the bead core and for turning up the end edge of the carcass ply, such radial position being properly selected based on the specific radial dimension of the tyre to be manufactured.

Advantageously, the apparatus setup time and costs are thus drastically reduced when passing from the manufacturing of a tyre having a certain radial dimension to the manufacturing of a tyre having a different radial dimension.

Moreover, advantageously, the apparatus of the present invention allows manufacturing tyres with at least four different and adjacent fittings.

The apparatus of the present invention can comprise, individually or in a combination, at least one of the following preferred features.

Preferably, the device for positioning the annular anchoring structure comprises a plurality of positioning members arranged adjacent to one another along a circumferential direction and coaxially to the longitudinal axis of the forming support, said positioning members being radially movable in a synchronous manner with respect to the longitudinal axis of the forming support between a maximum contraction position and a maximum expansion position.

Advantageously, the synchronous movement in the radial direction of the aforementioned positioning members causes the radial expansion/contraction of the positioning device of the annular anchoring structure and allows setting up the aforementioned device to the radial position defined in the design stage based on the radial dimension of the tyre to be manufactured.

Preferably, the apparatus of the present invention comprises a device for controlling the radial movement of said positioning members, such control device comprising a sliding guide with a spiral shape whose rotation around the longitudinal axis of the forming support can be controlled and a plurality of sliding runners extending radially with respect to said longitudinal axis, each of said positioning members being slidably coupled to a respective sliding runner and to said sliding guide with a spiral shape so that a predetermined angular movement of the guide with a spiral shape causes a predetermined radial movement of each positioning member.

Advantageously, the setup of the device for positioning the annular anchoring structure to the desired radial position is achieved by simply rotating the aforementioned sliding guide with a spiral shape by a predetermined angle. Such rotation in fact causes a predetermined radial movement of the positioning members.

Preferably, the device for turning up the end edge of the carcass ply comprises a plurality of turning up members arranged adjacent to one another along a circumferential direction and coaxially to the longitudinal axis of the forming support, said turning up members being radially movable in a synchronous manner with respect to the longitudinal axis of the forming support between a maximum contraction position and a maximum expansion position.

Advantageously, the synchronous movement in the radial direction of the above positioning members carries out the radial expansion/contraction of the device for turning up the end edge of the carcass ply and allows setting up the above device to the radial position defined in the design stage based on the radial dimension of the tyre to be manufactured.

Preferably, the apparatus of the present invention comprises a device for controlling the radial movement of said turning up members, such control device comprising a sliding guide with a spiral shape whose rotation around the longitudinal axis of the forming support can be controlled



5

and a plurality of sliding runners extending radially with respect to said longitudinal axis, each of said turning up members being slidably coupled to a respective sliding runner and to said sliding guide with a spiral shape so that a predetermined angular movement of the guide with spiral

movement causes a predetermined radial movement of each turning up member.

Advantageously, the setup of the device for turning up the end edge of the carcass ply to the desired radial position is achieved by simply rotating the above sliding guide with a spiral shape by a predetermined angle. Such rotation in fact causes a predetermined radial movement of the turning up members.

Preferably, each turning up member comprises a roller associated to a free end of a respective arm, each roller being coupled to the circumferentially consecutive roller by a compression spring.

Advantageously, the above springs ensure the structural continuity in the circumferential direction of the device for turning up the end edge of the carcass ply. Such springs further ensure the desired concentricity of the assembly consisting of the above turning up members with respect to axis X-X of the forming support upon the variation of the radial position of the rollers during the turning up of the end edge of the carcass ply and the setup of the device for manufacturing tyres having different radial dimensions.

Preferably, the device for positioning the annular anchoring structure and the device for turning up the end edge of the carcass ply are slidably mounted on at least one sliding track extended along a direction parallel to the longitudinal axis of the forming support, the turning up device being associated to said at least one sliding track in an axially outer position to the positioning device with respect to the forming support and wherein the arms of the turning up members are axially sliding in radially inner position with respect to the positioning members.

Advantageously, a configuration of the type described above allows containing the radial and axial dimension of the apparatus, with evident advantages in terms of space economy.

In a preferred embodiment thereof, the apparatus of the present invention further comprises at least one device for pulling down the end edge of the carcass ply towards the longitudinal axis of the forming support, such pulling down device being circumferentially extended around the longitudinal axis of the forming support and axially movable between an operating position distal from the forming support and an operating position proximal to the forming support, the aforementioned pulling down device being radially expandable/contractible with respect to the longitudinal axis of the forming support synchronously to the positioning device and to the turning up device, the aforementioned pulling down device being further settable in a plurality of different operating radial positions, each operating radial position being selected based on a respective radial dimension of the tyre to be manufactured.

Advantageously, such device can be used for manufacturing tyres of different radial dimensions.

Preferably, the radial expansion/contraction of the device for pulling down the end edge of the carcass ply is actuated by the radial expansion/contraction of the positioning device.

In a preferred embodiment thereof, the above pulling down device comprises a plurality of ply pulling down members arranged adjacent to one another along a circumferential direction and coaxially to the longitudinal axis of the forming support, said ply pulling down members com-

6

prising respective arms radially movable with respect to the longitudinal axis of the forming support between a maximum contraction position and a maximum expansion position. Advantageously, the synchronous movement in the radial direction of the arms of the aforementioned ply pulling down members causes the radial expansion/contraction of the device for turning up the end edge of the carcass ply and allows setting up the above device to the radial position defined in the design stage based on the radial dimension of the tyre to be manufactured.

Preferably, each of the aforementioned ply pulling down members comprises at least two longitudinal finger plates arranged side by side and partially overlapped in a circumferential direction. More preferably, also the circumferentially adjacent finger plates of two circumferentially consecutive ply pulling down members are partially overlapped in the circumferential direction. Advantageously, the partial overlapping of the finger plates allows an even and effective turning up of the end edge of the carcass ply irrespective of the radial position of the pulling down members, and thus irrespective of the radial dimension of the tyre to be manufactured. Preferably, the device for positioning the annular anchoring structure is axially slidable in a radially outer position with respect to said finger plate and, for a predetermined radial position of the device for positioning the annular anchoring structure and the device for pulling down the end edge of the carcass ply, the finger plates are retained by the above positioning device in a radially contracted configuration when such positioning device is radially overlapped to the finger plates, the finger plates taking up a radially expanded configuration when such positioning device is axially moved with respect to the device for pulling down the end edge of the carcass ply so as not to be radially overlapped to the finger plates.

Advantageously, in the passage from the radially expanded configuration to the radially contracted configuration, the finger plates causes the pulling down of the end edge of the carcass ply. More advantageously, for a predetermined radial position of the device for positioning the annular anchoring structure and the device for pulling down the end edge of the carcass ply, the radial expansion of the finger plates is actuated by the axial movement of the above pulling down device with respect to the device for positioning the annular anchoring structure, while the radial contraction of the finger plates is actuated by the axial movement of the device for positioning the annular anchoring structure with respect to the device for pulling down the end edge of the carcass ply. An advantageous process economy is thus obtained.

The annular anchoring structure preferably comprises at least one substantially circumferential annular insert and at least one filling insert associated in a radially outer position with respect to the substantially circumferential annular insert, and in a preferred embodiment thereof, the apparatus of the present invention comprises at least one device for pulling down the filling insert end edge of the carcass ply. Preferably, the device for pulling down the filling insert comprises a plurality of filling insert pulling down members, each of such members being supported by a respective positioning member and being axially slidable with respect to said positioning member.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Further features and advantages of the present invention will appear more clearly from the following detailed description of some preferred embodiments of an apparatus



and process according to the present invention, made with reference to the annexed drawings. In such drawings:

FIG. 1 is a schematic side view of a portion of an apparatus for manufacturing tyres for vehicle wheels according to the present invention;

FIG. 2 is an enlarged schematic side view of a portion of a bead core positioning device and of a ply pulling down device of the apparatus of FIG. 1;

FIG. 3 is a schematic perspective view of a portion of the ply pulling down device of the apparatus of FIG. 1;

FIG. 4 is a schematic front view of an element of the portion of FIG. 3;

FIG. 5 is an enlarged schematic side view of a portion of a turning up device of the apparatus of FIG. 1;

FIG. 6 is a schematic front view of a portion of the device of FIG. 5;

FIG. 7 is a schematic front view of a portion of the bead core positioning device of FIG. 2 and of the turning up device of FIG. 5.

#### DETAILED DESCRIPTION OF THE INVENTION

In FIG. 1, reference numeral 100 globally indicates a portion of an exemplifying embodiment of an apparatus usable in a process for manufacturing a tyre for vehicle wheels, according to a preferred embodiment of the present invention.

In particular, apparatus 100 is used in a step of building a carcass structure of the tyre for providing one or more annular anchoring structures 10 (hereinafter also called bead cores and better shown in FIG. 2) at that region of the carcass structure that will make the tyre bead. Such annular anchoring structures 10 are intended for keeping the tyre well fixed to the anchoring seat specifically provided in the vehicle tyre rim.

The building of the carcass structure of the tyre comprises the initial step of arranging a carcass ply 2 on a substantially cylindrical forming support 50 so that the opposite end edges 2a of the carcass ply project cantilevered from the forming support 50. Subsequently, each annular anchoring structure 10 is associated to each of the opposite end edges 2a of the carcass ply 2.

In the embodiment illustrated in the annexed figures, each annular anchoring structure 10 is associated to each end edge 2a of the carcass ply 2 at a respective side shoulder 51 of the forming support 50.

For simplicity of description, the description of apparatus 100 and of the process carried out thereby shall be made hereinafter with reference to only one of the opposite end edges 2a of the carcass ply 2 and to a side shoulder 51 of the forming support 50 (thus, with reference to only one of the opposite tyre beads). In fact, apparatus 100 is symmetrical in axial direction and the description made with reference to one end edge 2a and to one side 51 of the forming support 50 also applies with reference to the axially opposite end edge and side of the forming support 50.

The forming support 50 is rotatably mounted about an axis of rotation X-X in a totally conventional manner. The structure of the forming support 50 is not described in detail herein since it can be made in any convenient manner by a man skilled in the art. Likewise, the members for supporting and moving the forming support 50 shall not be described as they are totally conventional.

As illustrated in FIG. 2, the annular reinforcing structure 10 comprises at least one substantially circumferential annular insert 11 and at least one filling insert 12 applied in

radially outer position thereof. Apparatus 100 comprises a support frame 101 provided with support feet 102. Opposite first pairs of axial sliding tracks 103a (only one track 103a being visible in FIG. 1) and opposite second pairs of tracks 103b (only one track 103b being visible in FIG. 1) parallel to tracks 103a are mounted on a base 101a of the support frame 101.

Apparatus 100 further comprises, at each of the axial ends thereof, a side upright 104 on which three longitudinal screws 105 are mounted arranged at 120° with respect to each other (only two of such screws being visible in FIG. 1).

Apparatus 100 comprises a device 110 slidable along a direction x parallel to the axis of rotation X-X of the forming support 50, and thus in the two opposite ways of the direction indicated in FIGS. 1 and 2 by arrow F, between a distal position with respect to the forming support 50 and a position close to the forming support 50, so as to approach, or move away from, the forming support 50.

Device 110 is intended for supporting the annular anchoring structure 10 and bringing it in contact with the end edge 2a of the carcass ply 2. In particular, device 110 acts on the substantially circumferential annular insert 11 of the annular anchoring structure 10 by supporting and pushing it against shoulder 51 of the forming support 50. The annular anchoring structure 10 is thus positioned at the desired position on the end edge 2a of the carcass ply 2. Hereinafter in the present description, device 110 shall also be defined as "bead core positioning device". Device 110 comprises an annular element 115 mounted, by respective runners 116, to the sliding tracks 103a.

In an alternative embodiment of apparatus 100 (not shown), instead of tracks 103a and of runners 116, longitudinal guides extending from the side upright 104 parallel to the longitudinal screws 105 may be provided for allowing the axial sliding of device 110. Preferably, three longitudinal guides are provided in this case, arranged at 120° with respect to each other, and thus one at each longitudinal screw 105. The annular element 115 in this case is slidingly coupled to the aforementioned longitudinal guides by respective sliding bushes.

A plurality of bead core positioning members 118 are mounted on the annular element 115 (one of these is shown in detail in FIG. 2), the positioning members 118 being arranged adjacent to each other in a circumferential direction and coaxially to axis X-X of the forming support 50. Each bead core positioning member 118 comprises a support portion 111 of the annular anchoring structure 10, a portion 112 for pushing the annular anchoring structure 10, arranged in a radially outer position to the support portion 111 and an arm 112a integral with respect to the thrust portion 112 and intended for allowing the coupling of the positioning member 118 to the annular element 115.

Preferably, the bead core positioning members are at least eight. More preferably, such members are sixteen or twenty-four.

Arms 112a are radially and synchronously movable with respect to axis X-X of the forming support 50, and thus in the two opposite ways of the direction indicated in FIGS. 1 and 2 by arrow R.

The radial synchronous movement of arms 112a allows the radial synchronous movement of the positioning members 118 and thus the radial expansion/contraction of the bead core positioning device 110 between a maximum contraction position and a maximum expansion position. Device 110 can thus take on a plurality of different operating setup configurations according to the radial dimension of the



tyre to be manufactured, each of such configurations being defined by a corresponding radial operating position of the positioning members **118**.

Details on the way the radial movement of arms **112a**, and thus the radial expansion/contraction of the bead core positioning device **110** is obtained, shall be given hereinafter in the present description.

Apparatus **100** further comprises a device **120** for pulling down the end edge **2a** of the carcass ply **2** towards the axis X-X of the forming support **50**. Such pulling down is required, in the embodiment shown in the annexed drawings, for allowing the bead core positioning device **110** to approach the forming support **50** for positioning the annular anchoring structure **10** at the desired position on the end edge **2a** of the carcass ply **2**. Hereinafter in the present description, device **120** shall also be defined as "ply pulling down device".

As shown in FIGS. 1 and 2, device **120** is slidable parallel to axis X-X with respect to the bead core positioning device **110** in the two opposite ways of the direction indicated by arrow G.

Device **120** comprises an annular element **125** slidably mounted, by respective runners **126** (FIG. 1), to the sliding tracks **103b** mounted on the base **101**. If longitudinal guides parallel to longitudinal screws **105** are provided for the axial sliding of the bead core positioning device **110**, also tracks **103b** and runners **126** (as well as tracks **103a** and runners **116**) may be omitted and the annular element **125** may be slidably coupled to the above longitudinal guides by respective sliding bushes.

The annular element **125** is further coupled, by respective lead nuts **127**, to the longitudinal screws **105**. Lead nuts **127**, once actuated in rotation, allow the sliding of the annular element **125** along a direction x parallel to the axis X-X of the forming support **50**.

The annular element **125** is arranged in an axially external position to the annular element **115** of the bead core positioning device **110** with respect to the forming support **50**. Between the annular element **125** and the annular element **115** a pair of pneumatic cylinders **117a**, **117b** intended for controlling the relative axial sliding of the annular element **115** with respect to the annular element **125** are provided.

A plurality of ply pulling down members **128** are mounted on the annular element **125** (one of these is shown in detail in FIG. 2), the pulling down members **128** being arranged adjacent to each other in a circumferential direction and coaxially to the axis X-X of the forming support **50**. Such ply pulling down members **128** comprise respective arms **128a** radially and synchronously movable with respect to the axis X-X of the forming support **50**, and thus in the two opposite ways of the direction indicated in FIGS. 1 and 2 by arrow R'.

The radial synchronous movement of arms **128a** allows the radial synchronous movement of the ply pulling down members **128** and thus the radial expansion/contraction of the ply pulling down device **120** between a maximum contraction position and a maximum expansion position. Device **120** can thus take on a plurality of different operating setup configurations according to the radial dimension of the tyre to be manufactured, each of such configurations being defined by a corresponding radial operating position of the ply pulling down members **128**.

As illustrated in FIGS. 2-4, each ply pulling down member **128** comprises, at a radially inner portion **128b** of arms **128a**, a pair of holes **129**. Holes **129** house respective sliding guides **119** extending parallel to the axis X-X of the forming

support **50** and integral to the thrust member **112** of a respective bead core positioning member **118** (FIG. 2).

Each ply pulling down member **128** therefore is slidable on the sliding guides **119** with respect to the bead core positioning member **118** and is radially supported by the respective bead core positioning member **118** to which it is associated, so that the radial movement of arm **128a** of each ply pulling down member **128** is actuated by the radial movement of arm **112a** of the respective bead core positioning member **118**.

A central hole **129a** is provided between holes **129**, the central hole **129a** being suitable for housing a sliding guide (not visible in FIG. 2) extending parallel to axis X-X of the forming support **50** between the sliding guides **119** and integral to the support member **111** of a respective bead core positioning member **118**, so as to allow, if desired, the relative axial sliding of the support portion **111** with respect to the thrust portion **112**. Preferably, a compression spring (not shown in FIG. 2) is active between the head **119a** of the sliding guide **119** and the radially inner portion **128b** of arm **128a** which in rest configuration, keeps the support portion **111** in the position shown in FIG. 2.

As illustrated in FIGS. 3 and 4, each ply pulling down member **128** comprises a plurality of finger plates **121** (three in the annexed figures, respectively indicated with **121a**, **121b** and **121c**), extending longitudinally at a radially inner surface of the radially inner portion **128b** of arms **128a** and partially overlapped in a circumferential direction. In particular, finger plate **121c** of a ply pulling down member **128** is partially overlapped to finger plate **121a** of the same member, whereas the central finger plate **121b** of such member is partially overlapped to the aforementioned finger plates **121a** and **121c**. In order to do so, finger plate **121a** has an inclination angle  $\alpha$  greater than the inclination angle  $\beta$  of finger plate **121c**, so as to facilitate the overlapping of finger plate **121c** on finger plate **121a** (FIG. 4).

FIG. 3 also shows how the circumferentially outer finger plates **121** of two circumferentially consecutive ply pulling down members **128** are arranged in such a way as to also be partially overlapped in the circumferential direction. In particular, finger plate **121c** of a ply pulling down member **128** is partially overlapped to finger plate **121a** of the circumferentially consecutive ply pulling down member **128**.

Finger plates **121** are preferably made of elastically bending material and are shaped so that, at rest, as a whole they take on an open corolla-like configuration, that is, a configuration expanded in a radial direction. When stressed in the radial direction, finger plates **121** on the other hand may take on, as a whole, a closed or radially contracted configuration.

During the relative sliding of the ply pulling down device **120** with respect to the bead core positioning device **110**, finger plates **121** axially slide in the direction x in a position radially internal with respect to the bead core positioning members **118** (FIG. 2).

In the embodiment shown in the annexed figures, finger plates **121** are kept in the radially contracted configuration thereof by the bead core positioning members **118** of the bead core positioning device **110** when such device is radially overlapped to finger plates **121** (FIG. 2). Finger plates **121** on the other hand, take on the radially expanded configuration when the finger plate pulling down device **120** is axially moved with respect to the bead core positioning device **110** in the direction x and so that the latter is not radially overlapped to finger plates **121**.



## 11

The shape and the position of finger plates **121** is such that they remain partially overlapped in the circumferential direction when they are in the radially expanded configuration thereof.

Apparatus **100** further comprises a device **130** for pulling down the filling insert **12**, mounted on the bead core positioning device **110** (FIG. 2).

In the specific embodiment illustrated in FIG. 2, device **130** comprises a plurality of filling insert pulling down members **138** each provided with a respective roller **131** (only one whereof is illustrated). Roller **131** is mounted on the top surface of the thrust member **112** of each bead core positioning member **118**.

In this way, the radial movement of the bead core positioning members **118** causes a corresponding radial movement of rollers **131**, and thus the radial expansion/contraction of device **130**. The aforementioned device **130** can thus be used for pulling down the filling insert **12** of the annular anchoring structure **10** for different radial dimensions of the tyre to be manufactured.

Rollers **131** are arranged one next to the other in a circumferential direction coaxially with respect to axis X-X of the forming support **50**.

Each roller is elastically associated to the respective bead core positioning member **118**, as described in patent application PCT/IB2007/003500 to the same Applicant. In particular, each roller **131** is kept pressed, by a special compression spring **132**, against the radially outer surface of the thrust member **112** of the respective bead core positioning member **118**.

The pulling down of the filling insert **12** on the end edge **2a** of the carcass ply **2** takes place as a consequence of the rolling of rollers **131** on the radially outer surface of the radially outer annular portion of the respective bead core positioning member **118** and on the side surface **12a** of the filling insert **12** of the annular anchoring structure **10**, starting from a radially inner annular portion of such side surface **12a** to continue on a portion of the side surface **12a** radially outermost with respect to the aforementioned radially inner annular portion.

Apparatus **100** further comprises a device **140** suitable for turning up the end edge **2a** of the carcass ply about the annular anchoring structure **10** in order to form a turned up end portion of the carcass ply **2** comprising the annular anchoring structure **10** therein. Hereinafter in the present description, device **140** shall also be defined as "turning up device".

Device **140** is slidable parallel to axis X-X with respect to the bead core positioning device **110** and to the ply pulling down device **120** in the two opposite ways of the direction indicated by arrow H in FIGS. 1 and 5.

As shown in FIG. 1, device **140** comprises an annular element **145** mounted, by respective runners **146**, to the sliding tracks **103a** and by respective lead nuts **147** to the longitudinal screws **105**. Lead nuts **147**, once actuated in rotation, allow the sliding of the annular element **145** along direction x parallel to the axis X-X of the forming support **50**.

If longitudinal guides parallel to longitudinal screws **105** are provided in place of tracks **103a**, **103b** and of runners **116**, **126** for the axial sliding of the bead core positioning device **110** and of the device **120** for pulling down the end edge **2a** of the carcass ply **2**, the annular element **145** is slidably coupled to the above longitudinal guides by respective sliding bushes.

## 12

The annular element **145** is arranged in an axially external position to the annular element **125** of device **120** for pulling down the end edge of the carcass ply with respect to the forming support **50**.

A plurality of turning up members **148** are mounted on the annular element **145** (one of these is shown in detail in FIG. 5), the turning up members **148** being arranged adjacent to each other in a circumferential direction and coaxially to axis X-X of the forming support **50**.

The number of turning up members **148** is equal to that of the positioning members **118**.

Each turning up member **148** comprises a respective roller **141** supported by a respective arm **142**. The rollers are arranged adjacent to one another along a circumferential direction and coaxially to axis X-X of the forming support **50**.

As shown in FIG. 6, each roller **141** is associated to the circumferentially consecutive roller **141** by the interposition of a respective compression spring **143**.

Arms **142** are axially and radially movable in a synchronous manner with respect to the forming support **50** along a path that reproduces the profile of the annular anchoring structure **10** when the filling insert **12** is pulled down on the carcass ply **2**. The synchronised radial movement of arms **142** causes the synchronised radial movement of the turning up members **148** and thus, the radial expansion/contraction of the turning up device **140**.

The radial expansion of device **140**, along with the axial movement of the aforementioned device along the direction x, allows turning up the end edge **2a** of the carcass ply **2** about the annular anchoring structure **10**, as is described for example in patent application WO2008/001154 to the same Applicant.

The synchronous radial movement of the arms **142** of the turning up device **140** with respect to the axis X-X of the forming support **50**, and thus in the two opposite ways of the direction indicated in FIGS. 1 and 2 by arrow "R", further allows setting up the turning up device **140** to a plurality of different operating configurations according to the radial dimension of the tyre to be manufactured, each of such configurations being defined by a corresponding operating radial position of the arms **142** of the turning up members **148**.

The radial movement of arms **112a** of the bead core positioning members **118** takes place synchronously to that of arms **142** of the turning up members **148**. Such movement is obtained by respective control devices **200**, **300** totally similar.

Below is a detailed description of the control device **200** of the radial movement of arms **112a** of the bead core positioning members **118**, referring to FIGS. 2 and 7. The control device **300** of the radial movement of arms **142** of the turning up members **148** is totally similar to device **200** and its components are identified in FIGS. 3 and 7 with reference numbers corresponding to those related to device **200** and increased by 100. The reference numbers of the components of device **300** are shown hereinafter, and in FIG. 7, in brackets next to the reference numbers of the components of device **200**.

Device **200** (**300**) comprises a bracket **201** (**301**) attached to the axially outer face of the annular element **115** (**145**) and intended for supporting a motor reduction unit **202** (**302**).

A pulley **203** (**303**) is further mounted on bracket **201** (**301**), in axis with the motor reduction unit **202** (**302**). Motor reduction unit **202** (**302**) controls the rotation of pulley **203** (**303**) which, through a belt **204** (**304**), imparts a rotation to an annular member **205** (**305**) mounted on the axially outer



## 13

face of the annular element **115 (145)**. A spiral guide **206 (306)** shaped according to an Archimedes spiral is formed on the axially inner face of the annular member **205 (305)** (FIG. 7).

Arm **112a (142)** of each member **118 (148)** is slidingly associated to guide **206 (306)** by a respective pin **207 (307)**. It should be noted that for clarity reasons, only one arm **112a (142)** is shown in FIG. 7. Arm **112a (142)** of each member **118 (148)** is further rigidly connected to a guide **208 (308)** which is slidingly associated to a respective runner **209 (309)** mounted on the annular element **115 (145)** and arranged according to a radial direction. The rotation of the annular member **205 (305)** by a predetermined angle along the circumferential direction indicated with T in FIG. 7 therefore causes a corresponding shifting of each arm **112a (142)** along the radial direction indicated with R (R") in FIG. 7. The synchronous and centred movement of the bead core positioning members **118** and of the turning up members **148**, and thus the radial expansion/contraction of the bead core positioning device **110** and of the turning up device **140**, are thus obtained.

In the light of the fact that, as said above, each ply pulling down member **128** and each member **138** for pulling down the filling insert **12** is constrained, in the radial direction, to a respective bead core positioning member **118**, the radial movement of the ply pulling down members **128** and of the members **138** for pulling down the filling insert **12** takes place integrally to the radial movement of the bead core positioning member **118**.

From the above description it is clear that the possibility of the bead core positioning device **110**, of the ply pulling down device **120**, of the filling insert pulling down device **130** and of the turning up device **140**, of radially expanding/contracting with respect to the forming support **50** allows the use of apparatus **100** of the present invention for manufacturing a plurality of tyres having different radial dimension, in particular tyres with at least four different and adjacent fittings.

The invention claimed is:

1. A process for manufacturing a lot of tyres for vehicle wheels, the lot having at least two tyres of different radial dimensions, each tyre comprising a respective carcass structure formed starting from a respective carcass ply laid on a respective forming support, comprising:

selecting a first operating radial position based on a radial dimension of a first tyre of the lot to be manufactured; setting a positioning device to the first operating radial position by radially expanding/contracting in a synchronous manner a plurality of components with respect to a longitudinal axis of a first forming support, the positioning device being circumferentially extended around the longitudinal axis of the first forming support and axially movable with respect to the first forming support between an operating position distal from the first forming support and an operating position close to the first forming support,

wherein the positioning device is capable of positioning a first annular anchoring structure on an edge at an axial end of a first carcass ply laid on said first forming support;

setting a turning up device to the first operating radial position by radially expanding/contracting a plurality of components in a synchronous manner with respect to the longitudinal axis of the first forming support, the turning device being circumferentially extended around

## 14

the longitudinal axis of the first forming support and axially movable for approaching/moving away to/from the first forming drum,

wherein the turning up device is capable of turning up the edge at the axial end of said first carcass ply around the first annular anchoring structure,

wherein the turning up device is configured to move axially with respect to the positioning device during turning up of the edge of the first carcass ply around the first annular anchoring structure,

wherein the turning up device comprises a plurality of turning up members arranged adjacent to one another along a circumferential direction of the first forming support and coaxially with the longitudinal axis of the first forming support, said turning up members being radially movable in a synchronous manner with respect to the longitudinal axis of the first forming support between a maximum contraction position and a maximum expansion position,

wherein each turning up member comprises a roller associated with a free end of a respective arm, each roller being coupled to a circumferentially consecutive roller by a compression spring;

positioning said first annular anchoring structure on the edge at the axial end of said first carcass ply by axially moving said positioning device toward said first forming support;

turning up the edge at the axial end of said first carcass ply around said first annular anchoring structure by axially and radially moving said turning up device with respect to said first forming support,

wherein the radial movement of said plurality of turning up members is controlled by a control device comprising a sliding guide with a spiral shape and having a rotation around the longitudinal axis of the first forming support which can be controlled, and a plurality of sliding runners extending radially with respect to said longitudinal axis, each of said turning up members being slidingly coupled to a respective one of the sliding runners and to said sliding guide with the spiral shape so that a predetermined angular movement of the sliding guide with the spiral shape causes a predetermined radial movement of each turning up member;

pulling down the edge at the axial end of the first carcass ply toward the longitudinal axis of the first forming support,

wherein said pulling down is carried out by a pulling down device, which is distinct from said turning up device, wherein a portion of the positioning device extends through an arm of the pulling down device, and wherein said pulling down device is positioned radially outward of said turning up device,

wherein the pulling down device comprises a pulling down member slidably associated with a sliding guide extending parallel to the axis of the first forming support, the pulling down member being slidable along the axis of the first forming support with respect to the positioning device,

wherein the pulling down member is mounted on an annular element and radially movable with respect to the longitudinal axis of the first forming support,

replacing the first forming support with a second forming support whereon a second carcass ply is laid thereon; selecting a second operating radial position based on a radial dimension of a second tyre of the lot to be manufactured;



**15**

setting the positioning device to the second operating radial position, the positioning device being circumferentially extended around a longitudinal axis of the second forming support;

setting the turning up device to the second operating radial position, the turning device being circumferentially extended around the longitudinal axis of the second forming support;

positioning a second annular anchoring structure on an edge at an axial end of said second carcass ply by axially moving said positioning device toward said second forming support; and

turning up the edge at the axial end of the second carcass ply around the second annular anchoring structure by axially and radially moving said turning up device with respect to said second forming support.

**2.** The process according to claim **1**, wherein setting the positioning device to the second operating radial position comprises radially expanding/contracting said plurality of

**16**

components of the positioning device in a synchronous manner with respect to the longitudinal axis of the second forming support.

**3.** The process according to claim **2**, wherein the positioning device comprises a plurality of sliding guides with a spiral shape and having a rotation around the longitudinal axis of the first forming support which can be controlled, and a plurality of positioning members, each of said positioning members being slidably coupled to a respective one of the sliding guides with the spiral shape of the positioning device, so that a predetermined angular movement of each sliding guide with the spiral shape of the positioning device causes a predetermined radial movement of each positioning member.

**4.** The process according to claim **1**, wherein setting the turning up device to said respective operating radial position comprises radially expanding/contracting said plurality of components of the turning up device in a synchronous manner with respect to the longitudinal axis of the second forming support.

\* \* \* \* \*