

US010596029B2

(12) **United States Patent**  
**Lim et al.**

(10) **Patent No.:** **US 10,596,029 B2**  
(45) **Date of Patent:** **\*Mar. 24, 2020**

(54) **INTRAVASCULAR HEAT EXCHANGE  
CATHETER WITH RIB CAGE-LIKE  
COOLANT PATH**

(58) **Field of Classification Search**  
CPC ..... A61F 7/12; A61F 2007/126  
See application file for complete search history.

(71) Applicant: **Zoll Circulation, Inc.**, San Jose, CA  
(US)

(56) **References Cited**

(72) Inventors: **Alex L. Lim**, Santa Clara, CA (US);  
**Masouneh Mafi**, Mountain View, CA  
(US); **Venkata Vishnu Gurukula**,  
Mountain View, CA (US); **Richard A.**  
**Helkowski**, Redwood City, CA (US)

U.S. PATENT DOCUMENTS

1,459,112 A	6/1923	Mehl
1,857,031 A	5/1932	Schaffer
2,663,030 A	12/1953	Dahlberg
2,673,987 A	4/1954	Upshaw et al.
3,225,191 A	12/1965	Calhoun
3,369,549 A	2/1968	Armao
3,425,419 A	2/1969	Dato
3,504,674 A	4/1970	Swenson
3,726,269 A	4/1973	Webster, Jr.
3,744,555 A	7/1973	Fletcher et al.

(Continued)

(73) Assignee: **Zoll Circulation, Inc.**, San Jose, CA  
(US)

FOREIGN PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 835 days.

This patent is subject to a terminal dis-  
claimer.

DE	19531935	2/1997
GB	2040169	8/1980

(Continued)

(21) Appl. No.: **15/248,203**

OTHER PUBLICATIONS

(22) Filed: **Aug. 26, 2016**

(65) **Prior Publication Data**

US 2016/0361197 A1 Dec. 15, 2016

**Related U.S. Application Data**

(63) Continuation of application No. 13/675,241, filed on  
Nov. 13, 2012, now Pat. No. 9,433,528.

(60) Provisional application No. 61/707,146, filed on Sep.  
28, 2012.

Behmann et al., "Die Regelung der Warmebildung bei kunstlicher  
Hypothermie", Pflugers Archie, Bd. 266, S. 408-421 (1958).

(Continued)

(51) **Int. Cl.**  
**A61F 7/12** (2006.01)

*Primary Examiner* — Kaitlyn E Smith

*Assistant Examiner* — Yasamin Ekrami


(52) **U.S. Cl.**  
CPC ..... **A61F 7/12** (2013.01); **A61F 2007/126**  
(2013.01)

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

An intravascular heat exchange catheter has serpentine-like  
supply and return conduits circulating working fluid with a  
heat exchange system to warm or cool a patient in which the  
catheter is intubated.

**17 Claims, 2 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

3,751,077 A	8/1973	Hiszpanski	6,117,065 A	9/2000	Hastings et al.
3,937,224 A	2/1976	Uecker	6,117,105 A	9/2000	Bresnaham et al.
3,945,063 A	3/1976	Matsuura	6,124,452 A	9/2000	Di Magno
4,038,519 A	7/1977	Foucras	6,126,684 A	10/2000	Gobin et al.
4,065,264 A	12/1977	Lewin	6,146,141 A	11/2000	Schumann
4,103,511 A	8/1978	Kress et al.	6,146,411 A	11/2000	Noda et al.
4,126,132 A	11/1978	Portner et al.	6,148,634 A	11/2000	Sherwood
4,153,048 A	5/1979	Magrini	6,149,670 A	11/2000	Worthen et al.
4,173,228 A	11/1979	Van Steenwyk et al.	6,149,677 A	11/2000	Dobak, III
4,181,132 A	1/1980	Parks	6,231,594 B1	5/2001	Dae
4,298,006 A	11/1981	Parks	6,261,312 B1	7/2001	Dobak, III et al.
4,459,468 A	7/1984	Bailey	6,280,441 B1	8/2001	Ryan
4,532,414 A	7/1985	Shah et al.	6,283,940 B1	9/2001	Mulholland
4,554,793 A	11/1985	Harding, Jr.	6,299,599 B1	10/2001	Pham et al.
4,581,017 A	4/1986	Sahota	6,308,090 B1	10/2001	Tu et al.
4,638,436 A	1/1987	Badger et al.	6,322,559 B1	11/2001	Daulton et al.
4,653,987 A	3/1987	Tsuji et al.	6,338,727 B1	1/2002	Noda et al.
4,661,094 A	4/1987	Simpson	6,368,304 B1	4/2002	Aliberto
4,665,391 A	5/1987	Spani	6,383,144 B1	5/2002	Mooney et al.
4,672,962 A	6/1987	Hershenson	6,409,747 B1	6/2002	Gobin et al.
4,754,752 A	7/1988	Ginsburg et al.	6,416,533 B1	7/2002	Gobin et al.
4,787,388 A	11/1988	Hofmann	6,428,563 B1	8/2002	Keller
4,813,855 A	3/1989	Leveen et al.	6,450,990 B1	9/2002	Walker et al.
4,849,196 A	7/1989	Yamada et al.	6,451,045 B1	9/2002	Walker et al.
4,852,567 A	8/1989	Sinofsky	6,464,716 B1	10/2002	Dobak, III et al.
4,860,744 A	8/1989	Johnson et al.	6,527,798 B2	3/2003	Ginsburg et al.
4,906,237 A	3/1990	Johansson et al.	6,530,946 B1	3/2003	Noda et al.
4,941,475 A	7/1990	Williams et al.	6,544,282 B1	4/2003	Dae et al.
5,092,841 A	3/1992	Spears	6,551,309 B1	4/2003	Le Pivert
5,103,360 A	4/1992	Maeda	6,551,349 B2	4/2003	Lasheras
5,106,360 A	4/1992	Ishiwara et al.	6,554,791 B1	4/2003	Cartledge et al.
5,192,274 A	3/1993	Bierman	6,554,797 B1	4/2003	Worthen et al.
5,195,965 A	3/1993	Shantha	6,581,403 B2	6/2003	Whitebook
5,211,631 A	5/1993	Sheaff	6,585,692 B1	7/2003	Worthen et al.
5,269,758 A	12/1993	Taheri	6,589,271 B1	7/2003	Tzeng et al.
5,281,215 A	1/1994	Milder	6,605,106 B2	8/2003	Schwartz
5,304,214 A	4/1994	DeFord et al.	6,610,083 B2	8/2003	Keller et al.
5,342,301 A	8/1994	Saab	6,620,187 B2	9/2003	Carson et al.
5,344,436 A	9/1994	Fontenot et al.	6,620,188 B1	9/2003	Ginsburg et al.
5,370,675 A	12/1994	Edwards et al.	6,624,679 B2	9/2003	Tomaiuolo et al.
5,383,856 A	1/1995	Bersin	6,635,079 B2	10/2003	Unsworth et al.
5,403,281 A	4/1995	O'Neill et al.	6,673,042 B1	1/2004	Samson et al.
5,433,740 A	7/1995	Yamaguchi	6,679,906 B2	1/2004	Hammack et al.
5,437,673 A	8/1995	Baust et al.	6,685,733 B1	2/2004	Dae et al.
5,458,639 A	10/1995	Tsukashima et al.	6,706,060 B2	3/2004	Tzeng et al.
5,486,207 A	1/1996	Mahawili	6,716,188 B2	4/2004	Noda et al.
5,486,208 A	1/1996	Ginsburg	6,719,723 B2	4/2004	Wemeth
5,507,792 A	4/1996	Mason et al.	6,719,779 B2	4/2004	Daoud
5,531,714 A	7/1996	Dahn et al.	6,726,653 B2	4/2004	Noda et al.
5,531,776 A	7/1996	Ward et al.	6,740,109 B2	5/2004	Dobak, III
5,624,392 A	4/1997	Saab	6,746,474 B2	6/2004	Saadat
5,634,907 A	6/1997	Rani et al.	6,749,625 B2	6/2004	Pompa et al.
5,676,670 A	10/1997	Kim	6,796,995 B2	9/2004	Pham et al.
5,701,905 A	12/1997	Esch	6,799,342 B1	10/2004	Jarmon
5,709,564 A	1/1998	Yamada et al.	6,843,800 B1	1/2005	Dobak, III
5,709,654 A	1/1998	Klatz et al.	6,881,551 B2	4/2005	Heller
5,716,386 A	2/1998	Ward et al.	6,887,263 B2	5/2005	Bleam et al.
5,730,720 A	3/1998	Sites et al.	6,893,419 B2	5/2005	Noda et al.
5,733,319 A	3/1998	Neilson et al.	6,969,399 B2	11/2005	Schock et al.
5,737,782 A	4/1998	Matsuura et al.	7,156,843 B2	1/2007	Skarda
5,776,079 A	7/1998	Cope et al.	7,287,398 B2	10/2007	Noda et al.
5,788,647 A	8/1998	Eggers	7,510,569 B2	3/2009	Dae et al.
5,837,003 A	11/1998	Ginsburg	7,666,215 B2	2/2010	Callister et al.
5,862,675 A	1/1999	Scaringe et al.	7,686,070 B2	3/2010	Chu et al.
5,895,418 A	4/1999	Saringer	7,822,485 B2	10/2010	Collins
5,908,407 A	6/1999	Frazee et al.	7,846,193 B2	12/2010	Dae et al.
5,957,963 A	9/1999	Dobak, III	7,857,781 B2	12/2010	Noda et al.
5,980,561 A	11/1999	Kolen et al.	8,105,262 B2	1/2012	Noda et al.
6,019,783 A	2/2000	Philips et al.	8,105,263 B2	1/2012	Noda et al.
6,042,559 A	3/2000	Dobak, III	8,105,264 B2	1/2012	Noda et al.
6,051,019 A	4/2000	Dobak, III	8,109,894 B2	2/2012	Noda et al.
6,059,825 A	5/2000	Hobbs et al.	2001/0031946 A1	10/2001	Walker et al.
6,096,068 A	8/2000	Dobak, III et al.	2001/0047196 A1	11/2001	Ginsburg et al.
6,106,522 A	8/2000	Fleischman et al.	2002/0013569 A1	1/2002	Sterman et al.
6,110,139 A	8/2000	Loubser	2002/0022823 A1	2/2002	Luo et al.
			2002/0145525 A1	10/2002	Friedman et al.
			2002/0147445 A1	10/2002	Farley et al.
			2002/0183692 A1	12/2002	Callister
			2002/0198579 A1	12/2002	Khanna



(56)

References Cited

U.S. PATENT DOCUMENTS

2003/0023288 A1 1/2003 Magers  
 2003/0139750 A1 7/2003 Shinozuka et al.  
 2003/0176902 A1 9/2003 Gunn et al.  
 2003/0236496 A1 12/2003 Samson et al.  
 2004/0015221 A1 1/2004 Kuzma  
 2004/0044387 A1\* 3/2004 Pompa ..... A61F 7/12  
 607/105  
 2004/0089058 A1 5/2004 De Haan et al.  
 2004/0102825 A1 5/2004 Daoud  
 2004/0210231 A1 10/2004 Boucher et al.  
 2005/0010273 A1 1/2005 Walker et al.  
 2005/0156744 A1 7/2005 Pires  
 2006/0095104 A1 5/2006 Magers et al.  
 2006/0185828 A1 8/2006 Takehara et al.  
 2007/0007640 A1 1/2007 Hamden et al.  
 2007/0076401 A1 4/2007 Carrez et al.  
 2008/0154297 A1 6/2008 Lee et al.  
 2008/0262584 A1 10/2008 Bottomley et al.  
 2009/0018534 A1 1/2009 Taimisto et al.  
 2009/0056927 A1 3/2009 Zobel et al.  
 2009/0062837 A1 3/2009 Gasche et al.  
 2009/0247963 A1 10/2009 Bleam et al.  
 2011/0270368 A1 11/2011 Ginsburg et al.  
 2014/0094883 A1 4/2014 Lim

FOREIGN PATENT DOCUMENTS

GB 1183185 2/1985  
 GB 2212262 7/1989

GB 2383828 7/2003  
 JP 09-215754 8/1997  
 JP 10-0127777 5/1998  
 JP 10-305103 11/1998  
 WO WO 1990001682 2/1990  
 WO WO 1993004727 3/1993  
 WO WO 1994000177 1/1994  
 WO WO 1994001177 1/1994  
 WO WO 1997025011 7/1997  
 WO WO 1998024491 6/1998  
 WO WO 1998040017 9/1998  
 WO WO 2000010494 3/2000  
 WO WO 2001013809 3/2001  
 WO WO 2001064146 9/2001  
 WO WO 2001076517 10/2001  
 WO WO 2001083001 11/2001

OTHER PUBLICATIONS

Behmann et al., "Intravasale Kuehlung", Pffugers Archie, Bd. 263, S. 145-165 (1956).  
 Behringer et al., "Rapid Hypothermic Aortic Flush Can Achieve Survival without Brain Damage after 30 Minutes Cardiac Arrest in Dogs", anesthesiology, V. 93, No. 6, Dec. 2000.  
 Watts et al., "Hypothermic Coagulopathy in trauma: Effect of Varying levels of Hypothermia on Enzyme Speed, Platelet Function, and Fibrinolytic Activity". The Journal of Trauma: Injury, Infection, and Critical Care, vol. 44, No. 5 (1998).

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3



1

## INTRAVASCULAR HEAT EXCHANGE CATHETER WITH RIB CAGE-LIKE COOLANT PATH

This application is a continuation of application Ser. No. 13/675,241, filed Nov. 13, 2012, now U.S. Pat. No. 9,433,528, entitled "Intravascular heat exchange catheter with rib cage-like coolant path,"

### FIELD

The present application relates generally to patient temperature control systems.

### BACKGROUND

It has been discovered that the medical outcome for a patient suffering from severe brain trauma or from ischemia caused by stroke or heart attack or cardiac arrest is improved if the patient is cooled below normal body temperature (37° C.). Furthermore, it is also accepted that for such patients, it is important to prevent hyperthermia (fever) even if it is decided not to induce hypothermia. Moreover, in certain applications such as post-CABG surgery, skin graft surgery, and the like, it might be desirable to rewarm a hypothermic patient.

As recognized by the present application, the above-mentioned advantages in regulating temperature can be realized by cooling or heating the patient's entire body using a closed loop heat exchange catheter placed in the patient's venous system and circulating a working fluid such as saline through the catheter, heating or cooling the working fluid as appropriate in an external heat exchanger that is connected to the catheter. The following U.S. patents, all of which are incorporated herein by reference, disclose various intravascular catheters/systems/methods for such purposes: U.S. Pat. Nos. 6,881,551 and 6,585,692 (tri-lobe catheter), U.S. Pat. Nos. 6,551,349 and 6,554,797 (metal catheter with bellows), U.S. Pat. Nos. 6,749,625 and 6,796,995 (catheters with non-straight, non-helical heat exchange elements), U.S. Pat. Nos. 6,126,684, 6,299,599, 6,368,304, and 6,338,727 (catheters with multiple heat exchange balloons), U.S. Pat. Nos. 6,146,411, 6,019,783, 6,581,403, 7,287,398, and 5,837,003 (heat exchange systems for catheter), U.S. Pat. No. 7,857,781 (various heat exchange catheters).

### SUMMARY

A catheter includes a heat exchange supply conduit configured to supply working fluid received from a source of working fluid to a distal location, and a heat exchange return conduit communicating with the supply conduit at the distal location and configured to return working fluid to the source. At least a portion of the supply conduit and/or at least a portion of the return conduit is configured in a serpentine configuration when working fluid flows therethrough.

In example embodiments, at least a portion of the supply conduit and at least a portion of the return conduit are configured in a serpentine configuration when working fluid flow therethrough. Furthermore, serpentine portions of the supply conduit establish axially longer segments and axially shorter segments and serpentine portions of the return conduit establish axially longer segments and axially shorter segments. At least one axially shorter segment of the return conduit is bordered by and axially between transverse legs of axially longer segment of the supply conduit and at least one axially shorter segment of the supply conduit is bor-

2

dered by and axially between transverse legs of an axially longer segment of the return conduit.

As discussed in one example below, when the conduits are inflated with working fluid, a proximal-most transverse segment of the supply conduit ends at a first distally-extending axially-oriented segment, which merges at a distal end with a second transverse segment, which in turn merges at an opposite end of the second transverse segment with another distally-extending axially-oriented segment. Likewise, when the conduits are inflated with working fluid, a distal-most transverse segment of the return conduit ends at a first proximally-extending axially-oriented segment, which merges at a proximal end with a second transverse segment, which in turn merges at an opposite end of the second transverse segment with another proximally-extending axially-oriented segment.

In non-limiting examples, in each conduit, lengths of the axially-oriented segments sequentially alternate between a short length and a long length, while in contrast each transverse segment has substantially the same length as the other transverse segments. Additionally, a long axially-oriented segment of the supply conduit axially spans a short axially-oriented segment of the return conduit, and likewise a long axially-oriented segment of the return conduit axially spans a short axially-oriented segment of the supply conduit. Short axially-oriented segments of the conduits may be substantially straight and parallel to a long axis of the catheter, while long axially-oriented segments the conduits can be concave.

In another aspect, a catheter includes a heat exchange supply conduit configured to supply working fluid received from a source of working fluid to a distal location. A heat exchange return conduit communicates with the supply conduit at the distal location and is configured to return working fluid to the source. At least a portion of the supply conduit and at least a portion of the return conduit are configured in a serpentine configuration when working fluid flow therethrough. Serpentine portions of the supply conduit establish axially longer segments and axially shorter segments and serpentine portions of the return conduit establish axially longer segments and axially shorter segments. At least one axially shorter segment of the return conduit is bordered by and spaced axially between transverse legs of an axially longer segment of the supply conduit and at least one axially shorter segment of the supply conduit is bordered by and axially between transverse legs of an axially longer segment of the return conduit.

In another aspect, an intravascular heat exchange catheter has serpentine-like supply and return conduits circulating working fluid with a heat exchange system to warm or cool a patient in which the catheter is intubated.

The details of the present invention, both as to its structure and operation, can best be understood in reference to the accompanying drawings, in which like reference numerals refer to like parts, and in which:

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram showing an example catheter engaged with an example heat exchange system;

FIG. 2 is a perspective view of the heat exchange region showing only the coolant supply and return lumens and omitting infusion lumens for clarity; and

FIG. 3 is a close up view of the heat exchange region.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring initially to FIG. 1, an intravascular temperature management catheter 10 is in fluid communication with a



catheter temperature control system **12** that includes a processor executing logic that in some non-limiting examples is in accordance with disclosure in the above-referenced system patents to control the temperature of working fluid circulating through the catheter **10** in accordance with a treatment paradigm responsive to patient core temperature feedback signals. In accordance with present principles, the catheter **10** can be used to induce therapeutic hypothermia in a patient **14** using the catheter, in which coolant such as but not limited to saline circulates in a closed loop, such that no coolant enters the body. Such treatment may be indicated for stroke, cardiac arrest (post-resuscitation), acute myocardial infarction, spinal injury, and traumatic brain injury. The catheter **10** can also be used to warm a patient, e.g., after bypass surgery or burn treatment, and to combat hyperthermia in, e.g., patient suffering from subarachnoid hemorrhage or intracerebral hemorrhage.

As shown, working fluid such a refrigerant may be circulated between the heat exchange system **12** and catheter **10** through supply and return lines **16**, **18** that connect to the proximal end of the catheter **10** as shown. Note that as used herein, “proximal” and “distal” in reference to the catheter are relative to the system **12**. A patient temperature signal from a catheter-borne temperature sensor may be provided to the system **12** through an electrical line **20** or wirelessly if desired. Alternatively, a patient temperature signal may be provided to the system **12** from a separate esophageal probe or rectal probe or tympanic sensor or bladder probe or other temperature probe that measures the temperature of the patient **14**.

The catheter **10**, in addition to interior supply and return lumens through which the working fluid is circulated, may also have one or more infusion lumens connectable to an IV component **22** such as a syringe or IV bag for infusing medicaments into the patient, or an instrument such as an oxygen or pressure monitor for monitoring patient parameters, etc.

The catheter **10** can be positioned typically in the vasculature of the patient **14** and more preferably in the venous system of the patient **14** such as in the inferior vena cava through a groin insertion point or the superior vena cava through a neck (jugular or subclavian) insertion point.

Now referring to FIGS. **2** and **3**, the catheter **10** includes a distal portion **100** which has a supply port **102** configured to communicate with the supply line **16** in FIG. **1** and a return port **104** configured to communicate with the return line **18** in FIG. **1**. A heat exchange supply conduit **106** receives working fluid from the supply line **16** and, hence, from a source of working fluid such as the heat exchange system **12**. The supply conduit **106** conveys the working fluid to a distal location **108**, where it joins a heat exchange return conduit **110** to return working fluid through the return port **104** and thence to the source.

As shown, at least a portion of the supply conduit **106** and/or at least a portion of the return conduit **110** is configured in a serpentine configuration when working fluid flows therethrough. In the example, substantially all of the conduits **106** and **110** are so formed.

Referring particularly to FIG. **3**, in the example shown portions **112**, **114** of the supply conduit **106** establish axially longer segments and axially shorter segments, respectively. Likewise, portions **116**, **118** of the return conduit establish axially longer segments and axially shorter segments, respectively. FIG. **3** shows that axially shorter segments **118** of the return conduit **100** are bordered by and spaced axially between transverse legs of respective axially longer segments **112** of the supply conduit **106**. Similarly, axially

shorter segments **114** of the supply conduit are bordered by and spaced axially between transverse legs of a respective axially longer segment **116** of the return conduit **110**.

As discussed in one example below, when the conduits are inflated with working fluid, a proximal-most transverse segment **120** of the supply conduit ends at a first distally-extending axially-oriented segment **122**, which merges at a distal end **124** with a second transverse segment **126**, which in turn merges at an opposite end of the second transverse segment **126** with another distally-extending axially-oriented segment **128**, and so on. Likewise, when the conduits are inflated with working fluid, a distal-most transverse segment **130** of the return conduit **110** ends at a first proximally-extending axially-oriented segment **132**, which merges at a proximal end with a second transverse segment **134**, which in turn merges at an opposite end of the second transverse segment with another proximally-extending axially-oriented segment **136**, and so on.

In non-limiting examples and as shown in FIG. **3**, in each conduit **106**, **110**, lengths of the axially-oriented segments sequentially alternate between a short length and a long length, while in contrast each transverse segment has substantially the same length as the other transverse segments. Additionally, a long axially-oriented segment of the supply conduit axially spans a short axially-oriented segment of the return conduit, and likewise a long axially-oriented segment of the return conduit axially spans a short axially-oriented segment of the supply conduit. Short axially-oriented segments of the conduits may be substantially straight and parallel to a long axis of the catheter as shown, while long axially-oriented segments (e.g., as shown **112** and **116**) of the conduits can be concave.

While the particular INTRAVASCULAR HEAT EXCHANGE CATHETER WITH RIB CAGE-LIKE COOLANT PATH is herein shown and described in detail, it is to be understood that the subject matter which is encompassed by the present invention is limited only by the claims.

What is claimed is:

**1.** A catheter, comprising:

a first conduit;

a second conduit communicating with the first conduit; wherein the catheter defines a longitudinal axis, and portions of the first conduit establish axially longer segments and axially shorter segments and wherein portions of the second conduit establish axially longer segments and axially shorter segments, the axially shorter segments being axially shorter segments and the axially longer segments being axially longer segments in that the axially shorter segments are shorter in a dimension defined by the longitudinal axis than the axially longer segments, and further wherein at least one of the axially shorter segments of the second conduit extends axially between first and second transverse segments associated with at least one of the axially longer segments of the first conduit, at least one axially shorter segment of the first conduit being oriented parallel to the longitudinal axis.

**2.** The catheter of claim **1**, wherein at least when the first and second conduits are inflated, a proximal-most transverse segment of the first conduit from among all transverse segments of the first conduit ends at a first distally-extending axially-oriented segment from among all axially-oriented segments of the catheter, which merges with a second transverse segment from among all the transverse segments, which in turn merges at an opposite end of the second



## 5

transverse segment with another distally-extending axially-oriented segment from among all axially-oriented segments of the catheter.

3. The catheter of claim 2, wherein at least when the first and second conduits are inflated, a distal-most transverse segment of the second conduit from among all the transverse segments of the second conduit ends at a first proximally-extending axially-oriented segment from among all axially-oriented segments of second conduit, which merges via at least one segment of all the segments of the catheter with another proximally-extending axially-oriented segment of all of the axially oriented segments of at least one of a supply conduit or the second conduit.

4. The catheter of claim 3, wherein in each of the first and second conduit, the axially shorter segments alternate with the axially longer segments while in contrast each transverse segment does not have a shorter length or long length relative to the other transverse segments.

5. The catheter of claim 4, wherein a first one of the axially longer segments of the first conduit axially spans a first one of the axially shorter segments of the second conduit, and likewise a first one of the axially longer segments of the second conduit axially spans a first one of the axially shorter segments of the first conduit.

6. A catheter, comprising:  
a first conduit;

a second conduit communicating with the first conduit;  
wherein

at least a portion of the first conduit and at least a portion of the second conduit are configured in a configuration when a working fluid flows therethrough, the catheter defining a longitudinal axis, the configuration comprising:

axially longer segments and axially shorter segments, the axially shorter segments being axially shorter segments and the axially longer segments being axially longer segments in that the axially shorter segments are shorter in a dimension defined by the longitudinal axis than the axially longer segments, at least one of the axially shorter segments of the second conduit extending between first and second transverse segments of at least one of the axially longer segments of the first conduit, at least one of the axially shorter segments being oriented parallel to the longitudinal axis.

7. The catheter of claim 6, wherein at least when the first and second conduits are inflated, a proximal-most transverse segment of the first conduit from among all transverse segments of the first conduit ends at a first distally-extending axially-oriented segment from among all axially-oriented segments of the catheter, which merges with a second transverse segment from among all the transverse segments, which in turn merges at an opposite end of the second transverse segment with another distally-extending axially-oriented segment from among all axially-oriented segments of the catheter.

8. The catheter of claim 7, wherein at least when the first and second conduits are inflated, a distal-most transverse segment of the second conduit from among all the transverse segments of the second conduit ends at a first proximally-extending axially-oriented segment from among all the axially-oriented segments of the second conduit, which merges via at least one segment of all the segments of the catheter with another proximally-extending axially-oriented segment of all of axially oriented segments of at least one of a supply conduit or the second conduit.

9. The catheter of claim 8, wherein in each of the first and second conduit, the axially shorter segments alternate with

## 6

the axially longer segments while in contrast each transverse segment does not have a shorter length or long length relative to the other transverse segments.

10. The catheter of claim 9, wherein a long axially-oriented segment of the first conduit axially spans a short axially-oriented segment of the second conduit, and likewise a long axially-oriented segment of the second conduit axially spans a short axially-oriented segment of the first conduit.

11. The catheter of claim 10, wherein short axially-oriented segments of at least one of the supply conduit or the second conduit is parallel to a long axis of the catheter, while long axially-oriented segments of at least one of the supply or second conduits are concave.

12. The catheter of claim 6, wherein at least one of the axially shorter segments of the first conduit is bordered by and axially between first and second transverse segments of at least one of the axially longer segments of the second conduit, the at least one of the axially shorter segments of the first conduit extending from the first transverse segment of the at least one of the axially longer segments of the second conduit to the second transverse segment of the at least one of the axially longer segments of the second conduit.

13. An intravascular heat exchange catheter defining a longitudinal axis and comprising:

first and second conduits in a configuration comprising:  
axially longer segments and axially shorter segments, the

axially shorter segments being axially shorter segments and the axially longer segments being axially longer segments in that the axially shorter segments are shorter in a dimension defined by the longitudinal axis than the axially longer segments, at least one of the axially shorter segments of the first conduit extends from a first transverse segment of at least one of the axially longer segments of the second conduit to a second transverse segment of the axially longer segment of the second conduit, at least one of the axially shorter segments being oriented parallel to the longitudinal axis.

14. The catheter of claim 13, wherein at least when the first and second conduits are

inflated, a proximal-most transverse segment of the first conduit from among all transverse segments of the first conduit ends at a first distally-extending axially-oriented segment from among all axially-oriented segments of the catheter, which merges with a second transverse segment from among all the transverse segments, which in turn merges at an opposite end of the second transverse segment with another distally-extending axially-oriented segment from among all axially-oriented segments of the catheter.

15. The catheter of claim 14, wherein at least when the first and second conduits are inflated, a distal-most transverse segment of the second conduit from among all the transverse segments of the second conduit ends at a first proximally-extending axially-oriented segment from among all the axially-oriented segments of the second conduit, which merges via at least one segment of all the segments of the catheter with another proximally-extending axially-oriented segment of all of axially oriented segments of at least one of the supply conduit or the second conduit.

16. The catheter of claim 14, wherein in each of the first and second conduit, the axially shorter segments alternate with the axially longer segments while in contrast each transverse segment does not have a shorter length or long length relative to the other transverse segments.



17. The catheter of claim 13, wherein at least one of the axially shorter segments of the second conduit extends axially from a first transverse segment of at least one of the axially longer segments of the first conduit to a second transverse segment of the axially longer segment of the first conduit. 5

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 10,596,029 B2  
APPLICATION NO. : 15/248203  
DATED : March 24, 2020  
INVENTOR(S) : Lim et al.


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specification

Column 1, Line 8, delete "path,"" and insert -- path". --

Signed and Sealed this  
Twenty-sixth Day of May, 2020



Andrei Iancu  
*Director of the United States Patent and Trademark Office*