

US010603995B2

(12) **United States Patent**
Biancalana et al.

(10) **Patent No.:** **US 10,603,995 B2**
(45) **Date of Patent:** **Mar. 31, 2020**

(54) **CAR WITH TARGA TOP BODY PROVIDED WITH SUNROOF OR OPEN ROOF**

(71) Applicant: **FERRARI S.P.A.**, Modena (IT)

(72) Inventors: **Matteo Biancalana**, Modena (IT);
Giuseppe Cuzzillo, Modena (IT)

(73) Assignee: **FERRARI S.P.A.**, Modena (IT)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 144 days.

(21) Appl. No.: **15/883,145**

(22) Filed: **Jan. 30, 2018**

(65) **Prior Publication Data**

US 2018/0222297 A1 Aug. 9, 2018

(30) **Foreign Application Priority Data**

Jan. 30, 2017 (IT) 102017000009662

(51) **Int. Cl.**
B60J 7/22 (2006.01)
B60J 7/10 (2006.01)

(52) **U.S. Cl.**
CPC **B60J 7/223** (2013.01); **B60J 7/106** (2013.01)

(58) **Field of Classification Search**
CPC B60J 7/106; B60J 7/22; B60J 7/223
USPC 296/180.1, 181.4, 217
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,253,916 A * 10/1993 Moore B60J 7/223
296/180.5
7,963,559 B2 * 6/2011 Ballard B60Q 1/2661
280/756

2005/0140172 A1 * 6/2005 Sogame B60J 7/223
296/180.1
2008/0001428 A1 * 1/2008 Pehrson B60J 7/223
296/180.1
2008/0067834 A1 * 3/2008 Erb B60J 7/19
296/180.1
2011/0000727 A1 * 1/2011 Froeschle B60J 1/2008
180/68.1
2011/0001329 A1 * 1/2011 Froeschle B60J 1/2008
296/76
2013/0257088 A1 * 10/2013 Noble B60J 1/20
296/96.11
2015/0298530 A1 * 10/2015 Pennington B60Q 1/50
296/180.1

(Continued)

FOREIGN PATENT DOCUMENTS

DE 199908502 C1 5/2000
EP 0895889 A2 10/1999
EP 2062769 A1 5/2009

(Continued)

OTHER PUBLICATIONS

Search Report issued in Italian Patent Application No. 201700009662, dated Nov. 2, 2017; 8 pages.


Primary Examiner — Jason S Morrow

(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(57) **ABSTRACT**

A car having: a passenger compartment; a windshield, which defines the passenger compartment at the front; a roll bar, which defines the passenger compartment at the rear; a pair of seats, which are arranged inside the passenger compartment between the windshield and the roll bar; a rear parcel shelf, which is arranged inside the passenger compartment behind the seats; and a protection panel, which is arranged inside the passenger compartment and projects for the rear parcel shelf.

14 Claims, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2019/0160927 A1* 5/2019 Saka B60J 7/223

FOREIGN PATENT DOCUMENTS

WO 9403342 A1 2/1994
WO 2006058703 A1 6/2006

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig.4

CAR WITH TARGA TOP BODY PROVIDED WITH SUNROOF OR OPEN ROOF

PRIORITY CLAIM

This application claims priority from Italian Patent Application No. 102017000009662 filed on Jan. 30, 2017, the disclosure of which is incorporated by reference.

TECHNICAL FIELD

The present invention relates to a car with a “Targa Top” body, provided with a sunroof or open roof.

The present invention finds advantageous application to a car with a “Targa Top” body (or, for short, “Targa”) with a sunroof, to which the following description will make explicit reference without losing its generality.

PRIOR ART

The “Targa” car body is a type of car body halfway between the “coupe” body and the “spider” body. It actually is a “coupe” body with a rigid roof (often made of a plastic material to have a reduced weight and therefore be easily handled by one person) that is removable and is supported at the front by the upright of the windshield and at the rear by a robust full-width roll bar, which is integrated into the body and is (generally) provided with a centrally arranged transparent rear window. The “Targa” body began to spread in the second half of the Sixties and enjoyed a good success throughout the Seventies; currently the “Targa” body is essentially used for high-performance sports cars. For example, a car with the “Targa” body is described in the patent application DE102008028668A1.

A significant aerodynamic turbulence, annoying for the occupants of the passenger compartment, has been observed by traveling at a high speed in the passenger compartment in a car with the “Targa” body when the roof is removed. Such aerodynamic turbulence is essentially due to air flows which, after having passed the upright of the windshield, sink below the roll bar (i.e. enter the passenger compartment from above) until they hit the rear window and, after impacting against the rear window, “bounce” towards the two passengers, thus hitting them from behind (very annoying).

In order to get rid of such aerodynamic turbulence it has been proposed to increase the height of the upright of the windshield (possibly also with a false insert to be installed only when the roof is removed) so that the upright of the windshield is adequately higher than the rear roll bar (approximately 3-5 cm higher than the rear roll bar). However, this solution involves a significant increase in the car’s front section and therefore an increase in the aerodynamic resistance of the car (i.e. a deterioration in both speed performance and fuel consumption).

DESCRIPTION OF THE INVENTION

The object of the present invention is to provide a car with a “Targa Top” body provided with a sunroof or open roof, said car being free from the aforementioned drawbacks and, at the same time, being also easy and inexpensive to manufacture.

According to the present invention, it is provided a car with a “Targa Top” body provided with a sunroof or open roof, as claimed in the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will now be described with reference to the accompanying drawings showing an example of non-limiting embodiment, in which:

FIG. 1 is a front perspective view of a car manufactured in accordance with the present invention;

FIG. 2 is a front perspective view of the car of FIG. 1 with the roof removed;

FIG. 3 is a perspective and schematic view of part of a passenger compartment of the car of FIG. 1 when the roof is removed; and

FIGS. 4 and 5 are two perspective and schematic views of the passenger compartment of FIG. 3 showing the air flows when the roof is removed.

PREFERRED EMBODIMENTS OF THE INVENTION

In FIGS. 1 and 2, the reference number 1 indicates as a whole a car driven by a centrally arranged internal combustion engine. The car 1 comprises a chassis, which supports the internal combustion engine, a pair of front wheels 2 and a pair of rear wheels 3.

Between the front wheels 2 and the rear wheels 3 there is a passenger compartment 4, which can be accessed through a pair of doors 5. Behind the passenger compartment 4 and in a central position there is a motor compartment housing the internal combustion engine. The chassis is covered by a body that includes, among other things, the doors 5, a transparent windshield 6, which is enclosed by an upright rigidly connected to the chassis and defining the passenger compartment 4, and a roof 7, which defines from above the passenger compartment 4. The roof 7 is supported at the front by the upright of the windshield 6 and at the rear by a full-width roll bar 8, which is integrated into the body (i.e. is rigidly connected to the chassis), has an inverted “U” shape and is provided with a centrally arranged (as shown in FIGS. 3, 4 and 5) and fixed (i.e. with no moving components) transparent rear window 9.

In the car 1 shown in the attached figures, the upright of the windshield 6 has the same height as the roll bar 8 and therefore the roof 7 is substantially horizontal when it rests at the front on the upright of the windshield 6 and at the rear on the roll bar 8.

The car body 1 is of the “Targa” type and therefore the roof 7 covering the passenger compartment 4 from above can be removed. FIG. 1 shows the car 1 with the roof 7, whereas FIG. 2 shows the car 1 without the roof 7 (i.e. with the passenger compartment 4 open at the top).

As better shown in FIG. 3, in the passenger compartment 4 two seats 10 are arranged side by side (generally a seat 10 on the left for the driver and a seat 10 on the right for a possible passenger or vice versa in the case of right-hand drive). The two seats 10 are positioned between the windshield 6 (which is arranged before the seats 10) and the roll bar 8 (which is arranged behind the seats 10). Each seat 10 comprises a sitting element (substantially horizontal) and a backrest (substantially vertical) ending at the top with a headrest.

The passenger compartment 4 contains a rear parcel shelf 11 (i.e. a hatbox), which is arranged inside the passenger compartment 4 behind the seats 10 and is substantially horizontal; furthermore, the rear parcel shelf 11 is arranged below the roll bar 8 and in front of the transparent rear window 9. In particular, the rear parcel shelf 11 has a greater length (i.e. a greater longitudinal dimension) between the

two seats **10** and has a shorter length (i.e. a smaller longitudinal dimension) at the two seats **10**. In other words, the rear parcel shelf **11** projects with a swelling between the two seats **10**.

Two vent channels **12** are provided, each of which starts at an inlet opening **13** formed through the rear parcel shelf **11** and ends in two adjacent and separate outlet openings **14**; the two vent channels **12** are alike and symmetrical and are arranged one on the right and one on the left. Preferably, the inlet openings **13** of the vent channels **12** are limited to a region of the rear parcel shelf **11** arranged between the headrests of the two seats **10**.

The embodiment shown in the accompanying figures provides two vent channels **12**, each comprising a single inlet opening **13** and two different outlet openings **14**. Other embodiments that are perfectly equivalent and not shown provide a different number of vent channels **12** (e.g. a single vent channel **12** or three or four vent channels **12**) and/or each vent channel **12** has a different number of inlet openings **13** (e.g. two or three separate inlet openings **13**) and/or each vent channel **12** has a different number of outlet openings **14** (e.g. a single outlet opening **14** or three or four outlet openings **14**).

In the embodiment shown in the attached figures, the outlet openings **14** of the vent channels **12** are arranged inside the passenger compartment **4**. In an alternative embodiment that is perfectly equivalent and not shown, the outlet openings of the vent channels **12** are arranged out of the passenger compartment **4**, e.g. the outlet openings **14** of the vent channels **12** may lead to the engine compartment or outside through the car body or through the vehicle floor.

In the embodiment shown in the accompanying figures, the outlet openings **14** of the vent channels **12** are arranged behind the seats **10** near the doors **5** giving access to the passenger compartment **4**. Preferably, the outlet openings **14** of the vent channels **12** are oriented towards the outside of the passenger compartment **4**. Preferably, the outlet openings **14** of the vent channels **12** are arranged above the beltline of the doors **5** (i.e. at the movable glass windows of the doors **5**). Preferably, the outlet openings **14** of the vent channels **12** are arranged behind the headrests of the seats **10**.

A protection panel **15**, arranged inside the passenger compartment **4** in front of the transparent rear window **9**, projects from the rear parcel shelf **11** towards the roll bar **8** and is arranged in front of the inlet openings **13** of the vent channels **12**. The protection panel **15** is fixed, namely is rigidly connected to the rear parcel shelf **11** and cannot move with respect to the rear parcel shelf **11**, thus maintaining the same position (i.e. it can never modify its position with respect to the rear parcel shelf).

Furthermore, the protection panel **15** is completely airtight, i.e. it does not allow any air passage. Consequently, the air can pass over or alongside the protection panel **15**, but it can never go through the protection panel **15**; this result is obtained by manufacturing the protection panel **15** in a solid and full (i.e. without holes) material. Generally, the protection panel **15** is transparent (i.e. made of glass or transparent plastic material) not to block the view through the rear window **9**. Preferably, the protection panel **15** forms an acute angle (and obviously a complementary obtuse angle) with the rear parcel shelf **11** and slopes down towards the windshield **6**. Preferably, the protection panel **15** has an upper edge, which is spaced from the roll bar **8** to leave a free passage between the upper edge of the protection panel **15** and the roll bar **8**. Preferably, the upper edge of the

protection panel **15** is lower than the roll bar **8**. Preferably, the protection panel **15** has a curved “eyelid” shape.

With reference to FIGS. **4** and **5**, it is described the operation of the vent channels **12** when the car **1** travels without the roof **7** (namely with the open roof **7**).

After having passed the upright of the windshield **6**, some air flows due to the advancement of the car **1** sink below the roll bar **8** (i.e. enter the passenger compartment **4** from above). In particular, such air flows tend to slip between the upper edge of the protection panel **15** (which is lower than the roll bar **8**) and the roll bar **8**, and therefore tend to concentrate in the space between the rear window **9** and the protection panel **15**. In other words, the air flows which, after having passed the upright of the windshield **6**, sink below the roll bar **8** (i.e. enter the passenger compartment **4** from above), “slide” into the space between the rear window **9** and the protection panel **15**, going through the passage between the roll bar **8** and the protection panel **15**. Such air flows are only slightly lower than the windshield **6** (and therefore the roll bar **8**), particularly when traveling at high speeds, and as a result even a small free passage area between the rear window **9** and the protection panel **15** is enough to “catch” almost all of these air flows. The air flows entering the defined space between the rear window **9** and the protection panel **15** tend to increase the local pressure and then vent, i.e. exit, through the two vent channels **12**, entering the inlet openings **13** and exiting the outlet openings **14**.

When the outlet openings **14** of the vent channels **12** are oriented towards the windows of the doors **5**, the air leakage through the outlet openings **14** creates a kind of “air cushion” at the windows of the doors **5**, which prevents the entry of air flows from the outside (obviously when the windows are open), thus improving the aerodynamic penetration of the car **1**. In other words, when the car **1** advances, some air flows, after having surpassed the side uprights of the windshield **6**, enter the passenger compartment **4** from the side (obviously when the windows are open) and the air blown through the outlet openings **14** of the vent channels **12** at the windows of the doors **5** and outwards prevents/contrasts (at least in part) the air inlet from the outside.

A different embodiment, not shown, provides only the protection panel **15**, but not the vent channels **12**. In this embodiment, the air flows which are concentrated in the space defined between the rear window **9** and the protection panel **15** (going through the passage area between the roll bar **8** and the protection panel **15**) locally increase the pressure, and not being able to vent through the vent channels **12** (no longer present) create side air flows (i.e. parallel to the protection panel **15**). In this embodiment, the protection panel **15** preferably has a greater transverse extension so as to end extensively beyond the headrests of the seats **10**.

The car **1** described above has numerous advantages.

First, in the car **1** described above, the formation of aerodynamic turbulence inside the passenger compartment **4** is prevented due to the air flows which, after having passed the upright of the windshield **6**, sink below the roll bar **8**. This result is due to the presence of the protection panel **15** and to the presence of vent channels **12** without any need to (more or less falsely) increase the height of the upright of the windshield **6** beyond the roll bar **8**.

Moreover, the car **1** described above is easy and inexpensive to manufacture, as it only requires the addition of a small fixed element (the protection panel **15**) and the creation of some “holes” (the openings **13** and **14** of the vent channels **12**).

5

The invention claimed is:

1. A car (1) with "Targa top" body, comprising:
a chassis;
a passenger compartment (4);
a windshield (6), which defines the passenger compartment (4) at the front and is enclosed by an upright rigidly connected to the chassis;
a full-width roll bar (8), which defines the passenger compartment (4) at the rear, is rigidly connected to the chassis, has an inverted "U" shape and is provided with a fixed transparent rear window (9);
a pair of seats (10), which are arranged inside the passenger compartment (4), between the windshield (6) and the roll bar (8);
a rear parcel shelf (11), which is arranged inside the passenger compartment (4) behind the seats (10); and
a protection panel (15), which is arranged inside the passenger compartment (4) in front of the transparent rear window (9), projects from the rear parcel shelf (11) towards the roll bar (8), is completely air-tight and is fixed, namely is rigidly connected to the rear parcel shelf (11) and cannot move with respect to the rear parcel shelf (11);
wherein the protection panel (15) has an upper edge, which is spaced from the roll bar (8) so as to leave a free passage between the upper edge of the protection panel (15) and the roll bar (8).
2. A car (1) according to claim 1, wherein the protection panel (15) forms an acute angle with the rear parcel shelf (11) and slopes down towards the windshield (6).
3. A car (1) according to claim 1, wherein: the upright of the windshield (6) has the same height as the roll bar (8); and it is provided a roof (7), which is supported at the front by the upright of the windshield (6) and at the rear by the roll bar (8).

6

4. A car (1) according to claim 1, wherein the protection panel (15) has an upper edge that is lower than the roll bar (8).
5. A car (1) according to claim 1, wherein the protection panel (15) has a curved "eyelid" shape.
6. A car (1) according to claim 1, wherein the protection panel (15) is transparent.
7. A car (1) according to claim 1 and comprising a vent channel (12) starting at an inlet opening (13), which is formed through the rear parcel shelf (11) and is arranged behind the protection panel (15), ending in an outlet opening (14).
8. A car (1) according to claim 7, wherein the outlet opening (14) of the vent channel (12) is arranged inside the passenger compartment (4).
9. A car (1) according to claim 8, wherein the outlet opening (14) of the vent channel (12) is arranged behind one of said pair of seats (10) close to a door (5) that allows entering the passenger compartment (4).
10. A car (1) according to claim 9, wherein the outlet opening (14) of the vent channel (12) is oriented towards the outside of the passenger compartment (4).
11. A car (1) according to claim 9, wherein the outlet opening (14) of the vent channel (12) is arranged above the belt line of the door (5).
12. A car (1) according to claim 9, wherein the outlet opening (14) of the vent channel (12) is arranged behind a headrest of one of said pair of seats (10).
13. A car (1) according to claim 7, wherein the inlet opening (13) of the vent channel (12) is limited to an area of the rear parcel shelf (11) arranged between the headrests of the two seats (10).
14. A car (1) according to claim 1, wherein the protection panel (15) ends above the headrests of the seats (10).

* * * * *