

US010606542B2

(12) **United States Patent**  
**Manchinasetti et al.**

(10) **Patent No.:** **US 10,606,542 B2**  
(45) **Date of Patent:** **Mar. 31, 2020**

(54) **IMAGE DISPLAY APPARATUS**

(71) Applicant: **LG ELECTRONICS INC.**, Seoul (KR)

(72) Inventors: **Sai Manchinasetti**, Bengaluru (IN); **Samavarthy Challagali**, Bengaluru (IN); **Reddy Pratap Ratakonda**, Bengaluru (IN); **Chanabasappa Chitrali**, Bengaluru (IN)

(73) Assignee: **LG ELECTRONICS INC.**, Seoul (KR)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 315 days.

(21) Appl. No.: **15/403,778**

(22) Filed: **Jan. 11, 2017**

(65) **Prior Publication Data**

US 2017/0199715 A1 Jul. 13, 2017

(30) **Foreign Application Priority Data**

Jan. 11, 2016 (KR) ..... 10-2016-0003106

(51) **Int. Cl.**

**G06F 3/14** (2006.01)  
**G06F 3/048** (2013.01)  
**H04N 5/445** (2011.01)  
**H04N 5/44** (2011.01)  
**H04N 21/414** (2011.01)  
**H04N 21/41** (2011.01)  
**H04N 21/431** (2011.01)  
**G06F 3/0484** (2013.01)  
**G06F 3/0482** (2013.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **G06F 3/1454** (2013.01); **G06F 3/0346** (2013.01); **G06F 3/048** (2013.01); **G06F 3/0482** (2013.01); **G06F 3/04847** (2013.01);

**G06F 3/1462** (2013.01); **H04L 65/4015** (2013.01); **H04N 5/4403** (2013.01); **H04N 5/44582** (2013.01); **H04N 5/44591** (2013.01); **H04N 21/4122** (2013.01); **H04N 21/41407** (2013.01); **H04N 21/4314** (2013.01); **H04N 21/4316** (2013.01); **G06F 3/1423** (2013.01); **G09G 2354/00** (2013.01); **H04N 21/4854** (2013.01)

(58) **Field of Classification Search**

CPC ..... **G06F 3/0346**; **G06F 3/048**; **G06F 3/1423**; **G06F 3/1454**; **G06F 3/1462**; **G09G 2354/00**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2009/0174818 A1 7/2009 Morita et al.  
2010/0247061 A1 9/2010 Bennett et al.  
(Continued)

FOREIGN PATENT DOCUMENTS

EP 2682859 A2 1/2014  
EP 2741205 A2 6/2014  
EP 2797329 A1 10/2014


Primary Examiner — Antonio Xavier

(74) Attorney, Agent, or Firm — Birch, Stewart, Kolasch & Birch, LLP

(57) **ABSTRACT**

An image display apparatus is disclosed. The image display apparatus includes a display, an interface unit to exchange data with a mobile terminal, and a controller configured to display an mirroring image received from the mobile terminal and to display additional information related to the mirroring image in a blank area other than a display area for display of the mirroring image.

**15 Claims, 87 Drawing Sheets**



- (51) **Int. Cl.**  
*G06F 3/0346* (2013.01)  
*H04L 29/06* (2006.01)  
*H04N 21/485* (2011.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2012/0088548 A1\* 4/2012 Yun ..... G08C 17/02  
455/557  
2013/0040623 A1\* 2/2013 Chun ..... H04N 21/4126  
455/414.2  
2013/0094423 A1\* 4/2013 Wengrovitz ..... H04L 12/1836  
370/312  
2013/0138728 A1\* 5/2013 Kim ..... G06F 15/16  
709/203  
2013/0326397 A1\* 12/2013 Kim ..... G06F 3/0484  
715/781  
2014/0002389 A1\* 1/2014 Kim ..... G06F 3/1446  
345/173  
2014/0026068 A1\* 1/2014 Park ..... G06F 3/0482  
715/748  
2014/0032635 A1\* 1/2014 Pimmel ..... H04N 21/4126  
709/203  
2016/0007077 A1\* 1/2016 Hoffert ..... H04N 5/44591  
348/564  
2016/0139868 A1\* 5/2016 Vedula ..... H04W 76/10  
715/738  
2016/0350063 A1\* 12/2016 Chen ..... G06F 3/1454

\* cited by examiner

FIG. 1




FIG. 2





FIG. 3



170

FIG. 4A




FIG. 4B




FIG. 5






FIG. 6




FIG. 7A




FIG. 7B



FIG. 7C




FIG. 7D




FIG. 7E




FIG. 7F




FIG. 8A






FIG. 8B




FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 9A




FIG. 9B




FIG. 9C






FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 10E




FIG. 11A




FIG. 11B




FIG. 11C






FIG. 11D




FIG. 11E




FIG. 11F




FIG. 11G




FIG. 11H




FIG. 11I




FIG. 11J




FIG. 11K






FIG. 12




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13E




FIG. 13F




FIG. 13G







FIG. 13H




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 14E




FIG. 14F




FIG. 14G






FIG. 14H




FIG. 14I




FIG. 14J




FIG. 14K




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D






FIG. 15E




FIG. 15F




FIG. 15G




FIG. 15H




FIG. 15I




FIG. 15J



FIG. 15K



FIG. 15L






FIG. 15M




FIG. 15N




FIG. 150




FIG. 15P




FIG. 15Q




FIG. 15R




FIG. 15S




FIG. 15T






FIG. 16




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 17D






FIG. 17F




FIG. 17G







FIG. 17H



**1****IMAGE DISPLAY APPARATUS****CROSS-REFERENCE TO RELATED APPLICATION**

This application claims the priority benefit of Korean Patent Application No. 10-2016-0003106, filed Republic of Korea on Jan. 11, 2016, which is hereby expressly incorporated by reference into the present application.

**BACKGROUND OF THE INVENTION****1. Field of the Invention**

The present invention relates to an image display apparatus and, more particularly, to an image display apparatus enabling simultaneous viewing of a mirroring image and various kinds of information in performing mirroring between a mobile terminal and the image display apparatus.

**2. Description of the Related Art**

An image display apparatus is an apparatus having a function to provide images viewable by a user. The user may watch a broadcast program through the image display apparatus. The image display apparatus provides a broadcast program selected by the user among broadcast signals transmitted from broadcast stations, and displays broadcast images on the display. Currently, the broadcasting technology is transitioning from analog broadcasting to digital broadcasting around the world.

Digital broadcasting refers to broadcasting for transmitting digital images and voice signals. Compared to analog broadcasting, digital broadcasting is robust to external noises and thus suffers lower data loss. Further digital broadcasting is advantageous in terms of error correction, and provides high definition and clear images. Further, in contrast with analog broadcasting, digital broadcasting enables bidirectional services.

**SUMMARY OF THE INVENTION**

Therefore, the present invention has been made in view of the above problems, and it is an object of the present invention to provide an image display apparatus enabling simultaneous viewing of a mirroring image and various kinds of information in performing mirroring between a mobile terminal and the image display apparatus.

Another object of the present invention is to provide an image display apparatus capable of facilitating mirroring between the mobile terminal and the image display apparatus.

In accordance with an aspect of the present invention, the above and other objects can be accomplished by the provision of an image display apparatus including a display, an interface unit to exchange data with a mobile terminal, and a controller configured to display a mirroring image received from the mobile terminal and to display additional information related to the mirroring image in a blank area other than a display area for display of the mirroring image.

In accordance with another aspect of the present invention, there is provided an image display apparatus including a display, an interface unit to exchange data with a mobile terminal, and a controller configured to display a mirroring image received from the mobile terminal and to display additional information related to the mirroring image in a display area for display of the mirroring image.

**BRIEF DESCRIPTION OF THE DRAWINGS**

The above and other objects, features and other advantages of the present invention will be more clearly under-

**2**

stood from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1 illustrates an image display system for mirroring according to an embodiment of the present invention;

FIG. 2 is an internal block diagram illustrating the image display apparatus of FIG. 1;

FIG. 3 is an internal block diagram illustrating the controller of FIG. 2;

FIG. 4A illustrates a method for controlling the remote control device of FIG. 2.

FIG. 4B is an internal block diagram illustrating the remote control device of FIG. 2;

FIG. 5 is an internal block diagram illustrating the mobile terminal of FIG. 1;

FIG. 6 is a flowchart illustrating operation of an image display apparatus and mobile terminal according to an embodiment of the present invention;

FIGS. 7A to 7F, 8A to 8F, 9A to 9C, 10A to 10E and 11A to 11K illustrate the operation method of FIG. 6;

FIG. 12 is a flowchart illustrating operation of an image display apparatus and mobile terminal according to another embodiment of the present invention;

FIGS. 13A to 13H, 14A to 14K and 15A to 15T illustrate the operation method of FIG. 12;

FIG. 16 is a flowchart illustrating operation of an image display apparatus and mobile terminal according to another embodiment of the present invention; and

FIGS. 17A to 17H illustrate the operation method of FIG. 16.

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

As used herein, the suffixes “module” and “unit” are added to simply facilitate preparation of this specification and are not intended to suggest special meanings or functions. Therefore, the suffixes “module” and “unit” may be used interchangeably.

FIG. 1 illustrates an image display system for mirroring according to an embodiment of the present invention.

Referring to FIG. 1, an image display system 10 for mirroring may include an image display apparatus 100, a mobile terminal 600 and a server 500.

The image display apparatus 100 may perform mirroring with the mobile terminal 600.

In particular, the image display apparatus 100 may receive a mirroring image from the mobile terminal 600 and display the mirroring image on a display 180.

If there is a blank area in addition to a display area for display of a mirroring image when mirroring is performed between the image display apparatus 100 and the mobile terminal 600 and thus the mirroring image is displayed by the image display apparatus 100, additional information related to the mirroring image is displayed. In particular, the additional information is displayed in the blank area other than the display area for display of the mirroring image. Thereby, the mirroring image and various kinds of information may be viewed simultaneously when mirroring is performed between the image display apparatus 100 and the mobile terminal 600.

A controller 170 of the image display apparatus 100 may perform a control operation to display a pointer on the

display **180**, based on a pointing signal from the remote control device **200**. In addition, if the pointer is located in the blank area when the mirroring image is displayed, the controller **170** may perform a control operation to display additional information related to the mirroring image in the blank area. By displaying the additional information according to location of the pointer, information serving the user's intention may be displayed.

In displaying the additional information related to the mirroring image in the display area, the controller **170** of the image display apparatus **100** may perform a control operation to move and display the mirroring image. If the amount of data of the additional information is large, the controller **170** of the image display apparatus **100** may control the displayed mirroring image to move or to be scaled down. Thereby, additional information having a large amount of data may be viewed at once.

In addition, the controller **170** of the image display apparatus **100** may perform a control operation to display the pointer on the display based on a pointing signal of the remote control device **200**. If the pointer is located in a second area corresponding to the blank area, the back key of the remote control device operates, or the pointer flicks to the left when a mirroring image is displayed, the controller **170** may perform a control operation to display additional information related to the mirroring image in the second area. If the pointer is located in a third area corresponding to the blank area, or the pointer flicks to the right when a mirroring image is displayed, the controller **170** may control the additional information related to the mirroring image display in the third area. By displaying relevant additional information according to movement of the pointer, user convenience may be enhanced.

If the pointer moves from the second area to the third area when a mirroring image is displayed, the controller **170** of the image display apparatus **100** may perform a control operation to display second additional information in the third area with first additional information displayed in the second area.

If the pointer moves from the second area to the third area when a mirroring image is displayed, the controller **170** of the image display apparatus **100** may control the additional information displayed in the second area to disappear and control the additional information to be displayed in the third area.

The additional information may include at least one of an image adjustment item for the mirroring image, a Share item for sharing an image, a previous image for the mirroring image, a next image for the mirroring image, an image list related to the mirroring image, an application item related to the mirroring image and detailed information about the mirroring image.

If the mirroring image is a home screen window or idle screen window of the mobile terminal **600**, the controller **170** of the image display apparatus **100** may perform a control operation to display, in the blank area, at least one of an object corresponding to a camera manipulation button attached to the mobile terminal **600**, an object corresponding to a power button, an object corresponding to a volume adjustment button and a zooming adjustment button.

If the mirroring image is the home screen window or idle screen window of the mobile terminal **600**, the controller **170** of the image display apparatus **100** may perform a control operation to display, in the blank area, at least one of an object indicating a first connector for connection with an external device and an object indicating a second connector for connection with a detachable additional memory.

The controller **170** of the image display apparatus **100** may control additional information related to the mirroring image to vary according to the attribute of the mirroring image.

For example, if the mirroring image is a gallery application, the controller **170** of the image display apparatus **100** may control the additional information to include an image quality adjustment item.

As another example, if the mirroring image is the gallery application, the controller **170** of the image display apparatus **100** may control the additional information to include a Share item for sharing an image or an application item for sharing.

As another example, if the mirroring image is a moving image which is being reproduced, the controller **170** of the image display apparatus **100** may control the additional information to include title information about the moving image, resolution information about the moving image, caption information, actor/actress information, or frequency information.

As another example, if the mirroring image is an image related to a music file which is being reproduced, the controller **170** of the image display apparatus **100** may control the additional information to include title information about the music file, lyrics information, singer information, composer information, or scale information.

As another example, if the mirroring image is a web image, the controller **170** of the image display apparatus **100** may control the additional information to include previous web image or a bookmark item.

As another example, if the mirroring image is a map image, the controller **170** of the image display apparatus **100** may control the additional information to include a map image of an area is not displayed, information about locations in the map image or shop name information.

As another example, if the mirroring image is the home screen window or idle screen window of the mobile terminal **600**, the controller **170** of the image display apparatus **100** may control the additional information to include at least one of an object corresponding to a camera manipulation button attached to the mobile terminal **600**, an object corresponding to a power button, an object corresponding to a volume adjustment button and an object corresponding to a zooming adjustment button.

As another example, if the mirroring image is the home screen window or idle screen window of the mobile terminal **600**, the controller **170** of the image display apparatus **100** may control the additional information to include at least one of an object indicating a first connector for connection with an external device and an object indicating a second connector for connection with a detachable additional memory.

The controller **170** of the image display apparatus **100** may control a mirroring image received from the mobile terminal to be scaled and displayed in a first area of the display and perform a control operation to display additional information related to the mirroring image in a second area corresponding to a blank area.

To perform mirroring between the image display apparatus **100** and the mobile terminal **600**, pairing needs to be performed between the image display apparatus **100** and the mobile terminal **600**.

In this embodiment, a method for easily performing pairing between the image display apparatus **100** and the mobile terminal **600** is proposed.

The controller **170** of the image display apparatus **100** may perform a control operation to display a device con-

nection application item according to a predetermined input, and display an image including server information such that the image is captured based on selection of the device connection application item using the mobile terminal **600**. Thereafter, the controller **170** may perform pairing with the mobile terminal **600**. Once pairing is completed, the controller **170** may perform a control operation to display an object indicating the paired mobile terminal **600**.

In particular, after displaying the image including the image the server information such that the image is captured using the mobile terminal **600**, the controller **170** of the image display apparatus **100** may perform a control operation to display randomly produced code information. Then, reliable and convenient pairing may be performed through pairing with the mobile terminal **600** after display of the code information. Further, completion of the pairing may be easily recognized.

If pairing with the mobile terminal **600** is performed while an image is being displayed on the display **180**, the controller **170** of the image display apparatus **100** may perform a control operation to display an object indicating the paired mobile terminal **600** in the image. Thereby, completion of the pairing may be easily recognized while the displayed image is viewed.

If pairing with the mobile terminal **600** is performed while a broadcast image based on a broadcast signal received from a broadcast receiver **105** is being displayed, the controller **170** of the image display apparatus **100** may perform a control operation to display an object indicating the paired mobile terminal **600**.

To perform pairing, the image display apparatus **100** may wirelessly transmit a pairing signal, and the mobile terminal **600** may transmit a pairing response signal in response to the pairing signal. Thereby, pairing may be performed and the mobile terminal **600** and the image display apparatus **100** may be connected to each other.

Herein, the pairing signal and the pairing response signal may be Bluetooth low energy (BLE) signals. In particular, the image display apparatus **100** may periodically transmit a BLE pairing signal.

In addition to the pairing signal, the image display apparatus **100** may further transmit device information including the device ID of the image display apparatus.

If the object indicating the paired mobile terminal **600** is selected, the controller **170** of the image display apparatus **100** may perform a control operation to display an application list related to the paired mobile terminal **600**.

When a first application item is selected in the application list related to the paired mobile terminal **600**, the controller **170** may send a request for a screen window related to the first application to the mobile terminal **600**, and perform a control operation to display an image for execution of the first application on the display based on information received from the mobile terminal **600**.

That is, when the first application item is selected in the application list related to the paired mobile terminal **600**, the controller **170** may perform a control operation to implement mirroring.

The communication scheme for pairing may be different from the communication scheme for mirroring.

To improve data transfer rate in performing mirroring, if the source of moving images reproduced in the mobile terminal **600** is a coded video signal, the mobile terminal **600** may transmit the coded video signal to the image display apparatus **100** without decoding and reproducing the coded video signal, and the image display apparatus **100**

may decode the coded video signal and reproduce and display the decoded video signal.

If the mobile terminal **600** approaches the image display apparatus **100** within a predetermined distance allowing pairing, the controller **170** of the image display apparatus **100** may perform pairing.

The controller **170** may perform a control operation to transmit a pairing signal. If the mobile terminal **600** approaches within a predetermined distance enabling pairing, the controller **170** may receive a pairing response signal from the mobile terminal **600**, and perform pairing based on the pairing response signal.

As described above, the image display apparatus **100** may transmit a pairing signal, and the mobile terminal **600** may transmit a pairing response signal. Alternatively, the mobile terminal **600** may transmit a pairing signal, and the image display apparatus **100** may transmit a pairing response signal.

If the image display apparatus **100** is additionally paired with a second mobile terminal **600** while an object indicating the paired mobile terminal is displayed, the controller **170** of the image display apparatus **100** may perform a control operation to display the second object indicating the paired second mobile terminal **600** in addition to the first object.

When the second object indicating the paired second mobile terminal is selected, the controller **170** of the image display apparatus **100** may perform a control operation to display a second application list related to the paired second mobile terminal.

If the second object indicating the second paired mobile terminal **600** is selected after the object indicating the mobile terminal **600** is selected and the application list related to the paired mobile terminal **600** is displayed, the controller **170** of the image display apparatus **100** may perform a control operation to display a second application list related to the second paired mobile terminal **600**.

In addition, if the second object indicating the second paired mobile terminal **600** is selected after the object indicating the mobile terminal **600** is selected and the application list related to the paired mobile terminal **600** is displayed, the controller **170** of the image display apparatus **100** may perform a control operation to display a user change object and a user addition object. When the user change object is selected, the controller **170** may perform a control operation to display the second application list related to the second paired mobile terminal **600**.

A more detailed description of various methods for operating the image display apparatus **100** and the mobile terminal **600** will be given with reference to FIG. 6.

The image display apparatus **100** of FIG. 1 may be a monitor, TV, Tablet PC, or other types of image display apparatus.

FIG. 2 is an internal block diagram illustrating the image display apparatus of FIG. 1.

Referring to FIG. 2, the image display apparatus **100** according to an embodiment may include a broadcast receiver **105**, an external device interface unit **130**, a storage unit **140**, a user input interface unit **150**, a sensor unit, a controller **170**, a display **180**, and an audio output unit **185**.

The broadcast receiver **105** may include a tuner **110**, a demodulator **120**, a network interface unit **135**, and an external device interface unit **130**.

In contrast with the example of the figure, the broadcast receiver **105** may include only the tuner **110**, the demodulator **120**, and the external device interface unit **130**. That is, the network interface unit **135** may not be included.

The tuner **110** selects a channel selected by a user from among radio frequency (RF) broadcast signals received through an antenna or an RF broadcast signal corresponding to all pre-stored channels. In addition, the tuner **110** converts the selected RF broadcast signal into a middle-frequency signal, a base band image, or a voice signal.

For example, if the selected RF broadcast signal is a digital broadcast signal, the signal is converted into a digital IF (DIF) signal. If the selected RF broadcast signal is an analog broadcast signal, the signal is converted into a baseband image or a voice signal (CVBS/SIF). That is, the tuner **110** may process a digital broadcast signal or an analog broadcast signal. The analog baseband image or voice signal (CVBS/SIF) output from the tuner **110** may be directly input to the controller **170**.

In this embodiment, the tuner **110** may sequentially select an RF broadcast signal for all stored broadcast channels from among RF broadcast signals received through the antenna through the channel memorization function, and convert the same into a middle-frequency signal, baseband image, or voice signal.

To receive broadcast signals of two or more channels, two or more tuners **110** may be provided. Alternatively, a single tuner to receive two or more channels simultaneously may be provided.

The demodulator **120** receives and demodulates the DIF signal converted by the tuner.

After performing demodulation and channel decoding, the demodulator **120** may output a stream signal (TS). Herein, the stream signal may be a signal obtained by multiplexing an image signal, voice signal or data signal.

The stream signal output from the demodulator **120** may be input to the controller **170**. After performing demultiplexing and image/voice signal processing, the controller **170** outputs an image to the display **180** and voice to the audio output unit **185**.

The external device interface unit **130** may transmit or receive data to or from a connected external device, e.g., a set-top box **50**. Further, the external device interface unit **130** may include an A/V input/output unit.

The external device interface unit **130** may be connected to external devices such as a DVD (digital versatile disk), a Blu-ray, a gaming device, a camera, a camcorder, a computer (laptop), and a set-top box in a wired/wireless manner, and perform input/output operations with external devices.

The A/V input/output unit may receive image and voice signals input from an external device. A wireless communication unit may perform short-range wireless communication with other electronic devices.

The external device interface unit **130** may exchange data with a neighboring mobile terminal **600** via the wireless communication unit. In particular, in the mirroring mode, the external device interface unit **130** may receive device information, information about an executed application and an application image from the mobile terminal **600**.

The network interface unit **135** provides an interface for connection with a wired/wireless network including the Internet. For example, the network interface unit **135** may receive content or data provided by a content provider or a network operator over a network.

The network interface unit **135** may include a wireless communication unit.

The storage unit **140** may store programs for processing and control of signals in the controller **170**, and also store a signal-processed image, voice signal or data signal.

The storage unit **140** may function to temporarily store an image signal, a voice signal or a data signal input through the

external device interface unit **130**. In addition, the storage unit **140** may store information about a predetermined broadcast channel through the channel memorization function such as a channel map.

While it is illustrated in FIG. 2 that the storage unit **140** is provided separately from the controller **170**, embodiments of the present invention are not limited thereto. The storage unit **140** may be provided in the controller **170**.

The user input interface unit **150** may transmit a signal input by the user to the controller **170** or transmit a signal from the controller **170** to the user.

For example, the user input interface unit **150** may transmit/receive user input signals such as power on/off, channel selection, and screen window setting to/from the remote control device **200**, deliver, to the controller **170**, user input signals input through local keys such as a power key, a channel key, a volume key, or a setting key, deliver, to the controller **170**, user input signals input through a sensor unit configured to sense gesture of the user, or transmit a signal from the controller **170** to the sensor unit.

The controller **170** may demultiplex streams input through the tuner **110**, demodulator **120**, network interface unit **135** or external device interface unit **130**, or process demultiplexed signals. Thereby, the controller **170** may generate an output signal for outputting an image or voice.

An image signal image-processed by the controller **170** may be input to the display **180** and an image corresponding to the image signal may be displayed. In addition, the image signal which is image-processed by the controller **170** may be input to an external output device through the external device interface unit **130**.

A voice signal processed by the controller **170** may be output to the audio output unit **185** in the form of sound. In addition, the voice signal processed by the controller **170** may be input to an external output device through the external device interface unit **130**.

In FIG. 2, the controller **170** may include a demultiplexer and an image processor, which will be described with reference to FIG. 3 later.

Additionally, the controller **170** may control overall operation of the image display apparatus **100**. For example, the controller **170** may control the tuner **110** to tune in RF broadcasting corresponding to a channel selected by the user or a pre-stored channel.

The controller **170** may control the image display apparatus **100** according to a user command input through the user input interface unit **150** or an internal program.

The controller **170** may control the display **180** to display an image. Herein, the image displayed on the display **180** may be a still image, a moving image, a 2D image, or a 3D image.

The controller **170** may perform a control operation to display the predetermined 2D object in an image displayed on the display **180**. For example, the object may be at least one of an accessed web page (a newspaper, a magazine, etc.), an EPG (electronic program guide), various menus, a widget, an icon, a still image, a moving image and a text.

The controller **170** may recognize the location of the user based on an image captured by a capture unit. For example, the controller **170** may recognize the distance between the user and the image display apparatus **100** (i.e., a z-axis coordinate). Additionally, the controller **170** may recognize an x-axis coordinate and y-axis coordinate corresponding to the location of the user in the display **180**.

The display **180** generates drive signals by converting an image signal, data signal, OSD signal, and control signal

processed by the controller 170 or an image signal, data signal and control signal received from the external device interface unit 130.

The display 180 may be a PDP, A LCD display, OLED display, a flexible display, or a 3D display. The 3D display 180 may be divided into a non-glasses type and a glasses type.

The display 180 may be configured by a touchscreen to be used not only as an output device but also as an input device.

The audio output unit 185 receives a voice signal processed by the controller 170 and outputs voice.

The capture unit captures an image of the user. The capture unit (not shown) may be implemented using one camera. However, embodiments of the present invention are not limited thereto. The capture unit may be implemented using two or more cameras. The capture unit may be buried in the upper portion of the display 180 of the image display apparatus or may be separately disposed. Image information captured by the capture unit may be input to the controller 170.

The controller 170 may sense gesture of the user based on an image captured by the capture unit, a sensed signal from the sensor unit, or a combination thereof.

The power supply 190 supplies power to overall parts of the image display apparatus 100. In particular, the power supply 190 may supply power to the controller 170, which may be implemented in the form of system on chip (SOC), the display 180 for display of images, and the audio output unit 185 for outputting audio signals.

Specifically, the power supply 190 may include a converter to convert alternating current (AC) power into direct current (DC) power and a DC-DC converter to change the level of the DC power.

The remote control device 200 transmits a user input to the user input interface unit 150. Further, the remote control device 200 may employ Bluetooth, radio frequency (RF) communication, infrared (IR) communication, ultra-wideband (UWB), or ZigBee. In addition, the remote control device 200 may receive an image signal, a voice signal or a data signal from the user input interface 150, and display or output the same.

The image display apparatus 100 may be a fixed or mobile digital broadcast receiver capable of receiving digital broadcast services.

The block diagram of the image display apparatus 100 shown in FIG. 2 is simply illustrative. Constituents of the block diagram may be integrated, added or omitted according to the specification of the image display apparatus 100 which is implemented in reality. That is, two or more constituents may be combined into one constituent, or one constituent may be subdivided into two or more constituents, when necessary. In addition, the function performed in each block is simply illustrative, and it should be noted that specific operations or devices of the blocks do not limit the scope of the present invention.

FIG. 3 is an internal block diagram illustrating the controller of FIG. 2.

Referring to FIG. 3, the controller 170 according to an embodiment of the present invention may include a demultiplexer 310, an image processor 320, a processor 330, an OSD generator 340, a mixer 345, a frame rate converter 350, and a formatter 360.

The demultiplexer 310 demultiplexes an input stream. For example, when MPEG-2 TS is input, the demultiplexer 310 may demultiplex the same to separate the stream into an image signal, a voice signal and a data signal. Herein, the stream signal input to the demultiplexer 310 may be a stream

signal output from the tuner 110, the demodulator 120 or the external device interface unit 130.

The image processor 320 may perform image processing on a demultiplexed image signal. Further, the image processor 320 may include an image decoder 325 and a scaler 335.

The image decoder 325 decodes the demultiplexed image signal, and the scaler 335 scales the resolution of the decoded image signal such that the image signal can be output through the display 180.

The image decoder 325 may include decoders of various standards. For example, the image decoder 325 may include an MPEG-2, an H.264 decoder, a 3D image decoder for color images and depth images, and a decoder for multi-viewpoint images.

The processor 330 may control overall operation of the image display apparatus 100 or the controller 170. For example, the processor 330 may control the tuner 110 to tune in RF broadcasting corresponding to a channel selected by the user or a pre-stored channel.

In addition, the processor 330 may control the image display apparatus 100 according to a user command input through the user input interface unit 150 or an internal program.

The processor 330 may control data transmission with the network interface unit 135 or the external device interface unit 130.

The processor 330 may control operations of the demultiplexer 310, image processor 320 and OSD generator 340 in the controller 170.

The OSD generator 340 generates an OSD signal automatically or according to user input. For example, the OSD generator 340 may generate a signal for display of various kinds of information in the form of graphic images or texts on the screen of the display 180 based on a user input signal. The generated OSD signal may include various data including the user interface screen window of the image display apparatus 100, various menu screen windows, widget, and icons. The generated OSD signal may also include a 2D object or a 3D object.

The OSD generator 340 may generate a pointer which can be displayed on the display, based on a pointing signal input from the remote control device 200. In particular, the pointer may be generated by a pointing signal processor, and the OSD generator 340 may include the pointing signal generator. Of course, it is possible to provide the pointing signal processor separately from the OSD generator 340.

The mixer 345 may mix the OSD signal generated by the OSD generator 340 with an image signal processed and decoded by the image processor 320. The mixed image signal is provided to the frame rate converter 350.

The frame rate converter (FRC) 350 may convert the frame rate of an input image. The FRC 350 may output the frame rate without performing separate frame rate conversion.

The formatter 360 may arrange a left image frame and right image frame of a 3D image produced through frame rate conversion. The formatter 360 may output a synchronization signal Vsync to open the left eye glass or right eye glass of a 3D view apparatus.

The formatter 360 may change the format of an input image signal to a format in which the corresponding image can be displayed on the display.

The formatter 360 may change the format of a 3D image signal. For example, the formatter 360 may change the format of the 3D image signal to one of various 3D formats

including a side-by-side format, a top/down format, a frame sequential format, an interlaced format, and a checker box format.

The formatter **360** may convert a 2D image signal into a 3D image signal. For example, the formatter **360** may detect an edge or a selectable object in a 2D image signal, and separate and generate the object according to the detected edge of the selectable object as a 3D image signal. In this instance, the generated 3D image signal may be separated into a left image signal L and a right image signal R to be aligned.

In FIG. 3, a 3D processor for 3-dimensional effect signal processing may be further disposed after the formatter **360**. The 3D processor may perform processing such as adjustment of brightness, tint and color of an image signal to improve the 3D effect. For example, signal processing of making parts at a close distance clear and making parts at a far distance blurred may be performed. Such function of the 3D processor may be integrated into the formatter **360** or the image processor **320**.

An audio processor in the controller **170** may process a demultiplexed voice signal. Further, the audio processor may include various decoders.

The audio processor in the controller **170** may perform processing such as adjustment of bass, treble, and volume.

The data processor in the controller **170** may perform data processing on a demultiplexed data signal. For example, if the demultiplexed data signal is a coded data signal, the data processor may decode the data signal. The coded data signal may be electronic program guide information including broadcast information such as a start time and end time of a broadcast program broadcast on each channel.

The block diagram of the controller **170** shown in FIG. 3 is illustrative. Constituents of the block diagram may be integrated, added or omitted according to the specification of the controller **170** which is implemented.

In particular, the frame rate converter **350** and the formatter **360** may not be provided in the controller **170**. Instead, they may be provided individually or provided as one separate module.

FIG. 4 illustrates a method for controlling the remote control device of FIG. 2.

As shown in (a) of FIG. 4A, a pointer **205** corresponding to the remote control device **200** may be displayed on the display **180**.

The user may move the remote control device **200** up and down, left and right ((b) of FIG. 4A), or back and forth ((c) of FIG. 4A) or rotate the same. The pointer **205** displayed on the display **180** of the image display apparatus corresponds to movement of the remote control device **200**. As shown in the figure, because the pointer **205** moves according to movement of the remote control device **200** in the 3D space, the remote control device **200** may be referred to as a spatial remote control or a 3D pointing device.

(b) of FIG. 4A illustrates where the pointer **205** displayed on the display **180** moves to the left when the user moves the remote control device **200** to the left.

Information about movement of the remote control device **200** sensed through a sensor of the remote control device **200** is transmitted to the image display apparatus. The image display apparatus may calculate coordinates of the pointer **205** based on the information about the movement of the remote control device **200**. The image display apparatus may display the pointer **205** such that the pointer **205** corresponds to the calculated coordinates.

(c) of FIG. 4A illustrates where the user moves the controller **170** away from display **180** while pressing down

a specific button in the remote control device. In this instance, a selected area on the display **180** corresponding to the pointer **205** may be zoomed in and displayed with the size thereof increased. On the other hand, when the user moves the remote control device **200** closer to the display **180**, the selected area may be zoomed out and displayed with the size thereof reduced. Alternatively, the selected area may be zoomed out when the remote control device **200** moves away from the display **180**, and may be zoomed in when the remote control device **200** moves closer to the display **180**.

Vertical and lateral movement of the remote control device **200** may not be recognized while the specific button in the remote control device **200** is pressed down. That is, when the remote control device **200** approaches or moves away from the display **180**, vertical and lateral movements thereof may not be recognized, but only back-and-forth movement thereof may be recognized. If the specific button in the remote control device **200** is not pressed down, the pointer **205** only moves according to vertical and lateral movements of the remote control device **200**.

The speed and direction of movement of the pointer **205** may correspond to the speed and direction of movement of the remote control device **200**.

FIG. 4B is an internal block diagram illustrating the remote control device of FIG. 2.

Referring to FIG. 4B, the remote control device **200** may include a wireless communication unit **425**, a user input unit **430**, a sensor unit **440**, an output unit **450**, a power supply **460**, a storage unit **470**, and a controller **480**.

The wireless communication unit **425** transmits and receives signals to and from one of the image display apparatuses according to embodiments of the present invention described above. Hereinafter, one image display apparatus **100** according to an embodiment of the present invention will be described.

In this embodiment, the remote control device **200** may include an RF module **421** capable of transmitting and receiving signals to and from the image display apparatus **100** according to an RF communication standard. The remote control device **200** may further include an IR module **423** capable of transmitting and receiving signals to and from the image display apparatus **100** according to an IR communication standard.

In this embodiment, the remote control device **200** transmits a signal including information about movement of the remote control device **200** to the image display apparatus **100** via the RF module **421**.

In addition, the remote control device **200** may receive a signal from the image display apparatus **100** via the RF module **421**. When necessary, the remote control device **200** may transmit commands related to power on/off, channel change, and volume change to the image display apparatus **100** via the IR module **423**.

The user input unit **430** may include a keypad, a button, a touchpad, or a touchscreen. The user may input a command related to the display apparatus **100** with the remote control device **200** by manipulating the user input unit **430**. If the user input unit **430** includes a hard key button, the user may input a command related to the image display apparatus **100** with the remote control device **200** by pressing the hard key button. If the user input unit **430** includes a touchscreen, the user may input a command related to the image display apparatus **100** with the remote control device **200** by touching a soft key on the touchscreen. The user input unit **430** may include various kinds of input means such as a scroll key and a jog key which are manipulatable by the user, but

it should be noted that this embodiment does not limit the scope of the present invention.

The sensor unit **440** may include a gyro sensor **441** or an acceleration sensor **443**. The gyro sensor **441** may sense information about movement of the remote control device **200**.

For example, the gyro sensor **441** may sense information about movement of the remote control device **200** with respect to the X, Y and Z axes. The acceleration sensor **443** may sense information about the movement speed of the remote control device **200**. The sensor unit **440** may further include a distance measurement sensor to sense a distance to the display **180**.

The output unit **450** may output an image signal or voice signal corresponding to manipulation of the user input unit **430** or a signal transmitted from the image display apparatus **100**. The user may recognize, via the output unit **450**, whether the user input unit **430** is manipulated or the image display apparatus **100** is controlled.

For example, the output unit **450** may include an LED module **451** configured to be turned on when signals are transmitted to and received from the image display apparatus **100** via the wireless communication unit **425**, a vibration module **453** configured to generate vibration, a sound output module **455** configured to output sound, or a display module **457** configured to output an image.

The power supply **460** supplies power to the remote control device **200**. If the remote control device **200** does not move for a predetermined time, the power supply **460** may stop supplying power to save power. The power supply **460** may resume supply of power when the predetermined key provided to the remote control device **200** is manipulated.

The storage unit **470** may store various kinds of programs and application data necessary for control or operation of the remote control device **200**. When the remote control device **200** wirelessly transmits and receives signals to and from the image display apparatus **100** via the RF module **421**, the remote control device **200** and the image display apparatus **100** may transmit and receive signals in a predetermined frequency band. The controller **480** of the remote control device **200** may store, in the storage unit **470**, information about, for example, a frequency band enabling wireless transmission and reception of signals to and from the image display apparatus **100** which is paired with the remote control device **200**, and reference the same.

The controller **480** controls overall operation related to control of the remote control device **200**. The controller **480** may transmit, via the wireless communication unit **425**, a signal corresponding to manipulation of a predetermined key in the user input unit **430** or a signal corresponding to movement of the remote control device **200** sensed by the sensor unit **440** to the image display apparatus **100**.

The user input interface unit **150** of the image display apparatus **100** may include a wireless communication unit **151** capable of wirelessly transmitting and receiving signals to and from the remote control device and a coordinate calculator **415** capable of calculating coordinates of the pointer corresponding to operation of the remote control device **200**.

The user input interface unit **150** may wirelessly transmit and receive signals to and from the remote control device **200** via an RF module **412**. In addition, the user input interface unit **150** may receive, via an IR module **413**, a signal transmitted from the remote control device **200** according to an IR communication standard.

The coordinate calculator **415** may calculate coordinates (x, y) of the pointer **205** to be displayed on the display **180**,

by correcting the unstable position of a hand or an error in a signal corresponding to operation of the remote control device **200** which is received via the wireless communication unit **151**.

The transmitted signal of the remote control device **200** input to the image display apparatus **100** via the user input interface unit **150** is transmitted to the controller **170** of the image display apparatus **100**. The controller **170** may determine information about an operation of the remote control device **200** or manipulation of a key from the signal transmitted from the remote control device **200**, and control the image display apparatus **100** according to the information.

As another example, the remote control device **200** may calculate coordinates of the pointer corresponding to movement thereof and output the same to the user input interface unit **150** of the image display apparatus **100**. In this instance, the user input interface unit **150** of the image display apparatus **100** may transmit, to the controller **170**, information about the received coordinates of the pointer without separately correcting the unstable position of the hand or error.

As another example, in contrast with the example of the figure, the coordinate calculator **415** may be provided in the controller **170** rather than in the user input interface unit **150**.

FIG. **5** is an internal block diagram illustrating the mobile terminal of FIG. **1**.

Referring to FIG. **5**, the mobile terminal **600** may include a wireless communication unit **610**, an audio/video (A/V) input unit **620**, a user input unit **630**, a sensing unit **640**, and an output unit **650**, a memory **660**, an interface unit **625**, a controller **670** and a power supply **690**.

The wireless communication unit **610** may include a broadcast reception module **611**, a mobile communication module **613**, a wireless communication module **615**, a sound communication unit **617**, and a GPS module **619**.

The broadcast reception module **611** may receive at least one of a broadcast signal and broadcast-related information from an external broadcast management server over a broadcast channel. Herein, the broadcast channel may include a satellite channel and a terrestrial channel.

The broadcast signal and/or broadcast-related information received through the broadcaster reception module **611** may be stored in the memory **660**.

The mobile communication module **613** transmits and receives a radio signal to and from at least one of a base station, an external terminal and a server over a mobile communication network. Herein, the wireless signal may include a voice call signal, a video call signal, or various kinds of data according to transmission and reception of a text/multimedia message.

The wireless communication module **615**, which refers to a module for wireless Internet access, may be installed inside or outside the mobile terminal **600**. For example, the wireless communication module **615** may perform Wi-Fi-based wireless communication or Wi-Fi Direct-based wireless communication.

The sound communication unit **617** may perform sound communication. In the sound communication mode, the sound communication unit **617** may add data of predetermined information to audio data which is to be output and output sound. In addition, in the sound communication mode, the sound communication unit **617** may extract data of predetermined information from received sound.

Available short-range communication technologies may include Bluetooth, RFID (radio frequency identification), IrDA (Infrared Data Association), UWB (Ultra Wideband) and ZigBee.



The GPS module **619** may receive location information from two or more GPS satellites.

The A/V input unit **620** is used for input of an audio signal or a video signal and may include a camera **621** and a microphone **623**.

The user input unit **630** generates key input data input by the user to control operation of a terminal of the user. Further, the user input unit **630** may include a keypad, a dome switch, and a touchpad (resistive touchpad/capacitive touchpad). In particular, the touchpad may form a layered architecture together with the display **180**, thereby realizing a touchscreen.

The sensing unit **640** may generate a sensing signal for controlling operation of the mobile terminal **600** by sensing the current state of the mobile terminal **600**, for example by sensing whether the mobile terminal **600** is in the open or closed position, where the mobile terminal **600** is located, and whether the user contacts the mobile terminal **600**.

The sensing unit **640** may include a proximity sensor **641**, a pressure sensor **643** and a motion sensor **645**. The motion sensor **645** may employ an acceleration sensor, a gyro sensor, a gravity sensor and an other types of motion sensors to sense movement or location of the mobile terminal. In particular, the gyro sensor, which is used to measure an angular speed, may sense orientation (angle) of the mobile terminal with respect to a reference direction.

The output unit **650** may include a display **680**, an audio output unit **653**, a notification unit **655**, and a haptic module **657**.

The display **680** outputs and displays information processed by the mobile terminal **600**.

As described above, if the display **680** forms a layered architecture with the touchpad to implement a touchscreen, the display **680** may be used not only as an output device but also as an input device for input of information according to a touch from the user.

The audio output unit **653** outputs audio data received from the wireless communication unit **610** or stored in the memory **660**. The audio output unit **653** may include a speaker and a buzzer.

The notification unit **655** outputs a signal for reporting occurrence of an event in the mobile terminal **600**. For example, the notification unit **655** may output a signal in the form of vibration.

The haptic module **657** generates various haptic effects which may be felt by the user. A typical example of the haptic effects generated by the haptic module **657** is vibration.

The memory **660** may store a program for processing and control of the controller **670**, and functions to temporarily store input data or output data (e.g., a phonebook, a message, a still image, a moving image, etc.).

The interface unit **625** serves as an interface for all devices connected to the mobile terminal **600**. The interface unit **625** may receive data or power from external devices and transfer the same to the internal constituents of the mobile terminal **600** and to transmit data from the mobile terminal **600** to external devices.

The controller **670** typically controls operations of the aforementioned respective elements, thereby controlling overall operation of the mobile terminal. For example, the controller **670** may perform control or processing related to voice communication, data communication, video communication, and other types of communication. The controller **670** may also include a multimedia playback module **681** to reproduce multimedia. The multimedia playback module

**681** may be provided in the controller **670** as hardware or may be configured separately from the controller **670**.

The power supply **690** supplies power necessary for operations of the respective constituents according to control of the controller **670** when external power or internal power is applied thereto.

The block diagram of the mobile terminal **600** shown in FIG. **5** is simply illustrative. The respective constituents of the block diagram may be integrated, added or omitted according to the specification of the mobile terminal **600** which is implemented in reality. That is, two or more constituents may be combined into one constituent, or one constituent may be subdivided into two or more constituents, when necessary. In addition, the function performed in each block is simply illustrative, and it should be noted that specified operations or devices of the blocks do not limit the scope of the present invention.

FIG. **6** is a flowchart illustrating operation of an image display apparatus and mobile terminal according to an embodiment of the present invention, and FIGS. **7A** to **11K** illustrate the operation method of FIG. **6**.

Referring to FIG. **6**, the controller **170** of the image display apparatus **100** determines whether there is a mirroring execution input (S**505**).

The mirroring execution input may include input for selection of a mirroring application displayed on the image display apparatus **100** or input for selection of a mirroring application displayed on the mobile terminal **600**.

When a mirroring execution input is provided, the controller **170** of the image display apparatus **100** determines whether pairing has been performed (S**507**).

If the distance between the image display apparatus **100** and the mobile terminal **600** is within a predetermined distance, pairing may be automatically performed based on a Bluetooth low energy (BLE)-based pairing signal output from the image display apparatus **100** and a pairing response signal from the mobile terminal **600**.

If mirroring has not been performed, the controller **170** of the image display apparatus **100** controls pairing to be performed (S**509**).

For example, if there is a mirroring execution input, the controller **170** of the image display apparatus **100** may perform a control operation to output a pairing signal and to receive a pairing response signal from the mobile terminal **600** even if the distance between the image display apparatus **100** and the mobile terminal **600** is not within a predetermined distance.

The output level of a pairing signal that is output when the distance between the image display apparatus **100** and the mobile terminal **600** is beyond the predetermined distance is higher than the output level of a pairing signal that is output when the distance between the image display apparatus **100** and the mobile terminal **600** is within the predetermined distance.

If pairing is not performed when the distance between the image display apparatus **100** and the mobile terminal **600** is within the predetermined distance, pairing may be controlled to be performed according to the aforementioned procedure.

Next, when pairing is completed, the controller **170** of the image display apparatus **100** performs a control operation to display a mirroring-related (S**510**).

For example, when pairing is completed, the controller **170** of the image display apparatus **100** may perform a control operation to display an application list including a mirroring application item.

As another example, when pairing is completed, the controller 170 of the image display apparatus 100 may perform a control operation to display an execution icon indicating the user of a mobile terminal or the mobile terminal.

Then, if the execution icon is selected, the controller 170 of the image display apparatus 100 may perform a control operation to display an application list including a mirroring application item.

Next, if a predetermined application item is selected from the application list, particularly, if the mirroring application item is selected, the controller 170 of the image display apparatus 100 performs a control operation to transmit, via the network interface unit 135, a request for transmission of a mirroring image for the selected application item to the mobile terminal 600 (S615).

Then, the controller 670 of the mobile terminal 600 receives the request for transmission of the mirroring image via the communication unit 610 in response (S517).

Next, the controller 670 of the mobile terminal 600 performs a control operation to execute a corresponding application according to the request for transmission of the mirroring image. Then, the controller 670 performs a control operation to transmit the image of the executed application to the image display apparatus 100 via the communication unit 610 (S520). The image of the executed application is transmitted as a mirroring image.

Next, the controller 670 of the mobile terminal 600 performs a control operation to receive the mirroring image from the mobile terminal 600 and display the moved mirroring image via the network interface unit 135 (S522).

The controller 670 of the mobile terminal 600 determines whether a pointer displayed based on the pointing signal from the remote control device 200 is located in a blank area other than the display area for the mirroring image (S525).

If the pointer is located in the blank area, the controller 170 of the image display apparatus 100 performs a control operation to display additional information related to the mobile terminal or the mirroring image in at least one part of the blank area (S530). As the mirroring image and the additional information related to the mirroring image are displayed together, user convenience may be enhanced.

Examples of the additional information will be described with reference to FIGS. 7A to 11K.

FIG. 7A illustrates where the mobile terminal 600 and the image display apparatus 100 remain connected to each other.

When the mobile terminal 600 and the image display apparatus 100 are wirelessly connected to each other, the controller 170 of the image display apparatus 100 may perform a control operation to display an object 962 indicating a paired mobile terminal on the display 180, as shown in FIG. 7A.

In particular, the controller 170 of the image display apparatus 100 may perform a control operation to display the object 962 indicating the paired mobile terminal on a displayed image 960 on the display 180. Thereby, the user of the mobile terminal or another user who is viewing the image 960 of the image display apparatus 100 may recognize that the mobile terminal is connected and paired with the image display apparatus.

In FIG. 7A, if the object 962 indicating the paired mobile terminal is selected, the controller 170 of the image display apparatus 100 may perform a control operation to display an application list 970 and a wish list 975 which are related to the paired mobile terminal, as shown in FIG. 7B.

The application list 970 related to the paired mobile terminal may include application items for which mirroring

can be performed between the mobile terminal 600 and the image display apparatus 100 and an Add item 966.

In the figure, an App Store item, moving image playback item, map item, image viewer item and Internet item are provided as examples of application items for which mirroring can be performed.

If the gallery application item is selected in the application list 970 displayed as shown in FIG. 7B, the controller 170 of the image display apparatus 100 may transmit, to the mobile terminal 600, an application execution request Saib related to the gallery application item. Then, when an application of the mobile terminal 600 related to the gallery application item is executed, the controller 170 may perform mirroring.

Then, in receiving a mirroring image, the controller 170 of the image display apparatus 100 may perform a control operation to display, on the display 180, a screen window 840b of the gallery application which is being displayed as a screen window 840a and executed in the mobile terminal 600, as shown in FIG. 7C.

If a predetermined image item is selected on the displayed screen window 840b of the gallery application, the controller 170 of the image display apparatus 100 transmits selection information to the mobile terminal 600, as shown in FIG. 7C.

The controller 170 of the image display apparatus 100 may receive a mirroring image for the selected image item in response, and perform a control operation to display the mirroring image 1710 in a first area Ara of the display 180, as shown in FIG. 7D.

Typically, the size or resolution of the display 180 of the image display apparatus 100 is greater than the size or resolution of the display 680 of the mobile terminal 600. Accordingly, when the mirroring image is received, the controller 170 of the image display apparatus 100 may perform a control operation to scale up the mirroring image and display the scaled-up mirroring image.

If the screen display position of the mobile terminal 600 is a vertical view position, the display area of the image is limited on the display 180 of the image display apparatus 100, and blank areas Arb and Arc where the image is not displayed are produced.

In this embodiment, additional information related to the mirroring image is displayed in the blank areas.

Herein, the additional information may be automatically displayed in relation to the mirroring image, or optionally displayed according to the location of the pointer 205.

FIG. 7D illustrates disposing a second area Arb and a third area Arc corresponding to blank areas on the left and right sides of the first area Ara of the display 180 in which the mirroring image 1710 is displayed.

The controller 170 of the image display apparatus 100 may receive a pointing signal from the remote control device 200 via the user input interface unit 150, and perform a control operation to display the pointer 205 based on the pointing signal.

In the example of FIG. 7D, the pointer 205 is displayed in the first area Ara of the display 180 in which the mirroring image 1710 is display.

The controller 170 of the image display apparatus 100 may perform a control operation to display the pointer on the display based on the pointing signal. If the pointer is located in the second area corresponding to a blank area, the back key of the remote control device 200 operates, or the pointer 205 flicks to the left in displaying a mirroring image, the controller 170 of the image display apparatus 100 may perform a control operation to display additional informa-

tion related to the mirroring image in the second area. If the pointer is located in the third area corresponding to a blank area in displaying the mirroring image, the controller 170 may perform a control operation to display additional information related to the mirroring image in the third area. More details will be described with reference to FIGS. 7E and 7F.

When the pointer 205 moves to the second area Arb which is a blank area, the controller 170 of the image display apparatus 100 may perform a control operation to display additional information related to the mirroring image 1710.

In the example of FIG. 7E, an image adjustment item 1722 is displayed in the second area Arb, which is a blank area, as the additional information.

The mirroring adjustment item may include items such as brightness, contrast, and temperature.

If the pointer moves from the second area Arb to the third area Arc in displaying a mirroring image, the controller 170 of the image display apparatus 100 may perform a control operation to display second additional information 1724 in the second area with the first additional information 1722 displayed in the second area Arb, as shown in FIG. 7F.

The second additional information 1724 may include items such as color balance, shadows and highlights as the image adjustment items for the mirroring image 1710.

In contrast with the example of FIG. 7F, if the pointer 205 moves from the second area Arb to the third area Arc in displaying the mirroring image 1710, the controller 170 of the image display apparatus 100 may control the additional information displayed in the second area Arb to disappear, and perform a control operation to display the additional information in the third area.

The additional information displayed in a blank area may include at least one of an image adjustment item for the mirroring image, a Share item for sharing the image, a previous image for the mirroring image, a next image for the mirroring image, an image list related to the mirroring image, an application item related to the mirroring image and detailed information about the mirroring image.

FIG. 8A illustrates display of the mirroring image 1710 in the display area Ara, as illustrated in FIG. 7D.

If the pointer 205 moves to the second area Arb which is a blank area, the controller 170 of the image display apparatus 100 may perform a control operation to display additional information 1810 related to the mirroring image 1710, as shown in FIG. 8B.

In FIG. 8B, the additional information displayed in the second area Arb may include a Share item for sharing images or an application item for sharing images.

When the pointer 205 moves to the third area Arc which is a blank area, the controller 170 of the image display apparatus 100 may perform a control operation to display additional information related to the mirroring image 1710, as shown in FIG. 8C.

In FIG. 8C, the controller 170 of the image display apparatus 100 may perform a control operation to display a previous image 1730 related to the mirroring image 1720 in the second area Arb and a next image 1740 related to the mirroring image 1720 in the third area Arc.

Further, the controller 170 of the image display apparatus 100 may transmit a request for transmission of a previous image or next image related to the mirroring image to the mobile terminal 600 according to the location of the pointer 205. Then, the controller 170 may receive the previous image or next image related to the mirroring image from the mobile terminal 600.

In FIG. 8D, the pointer 205 moves to the second area Arb which is a blank area, the controller 170 of the image display

apparatus 100 may perform a control operation to display an image list 1750 related to the mirroring image 1710 as additional information related to the mirroring image 1710.

Further, the controller 170 of the image display apparatus 100 may transmit a request for transmission of the image list 1750 related to the mirroring image to the mobile terminal 600 according to the location of the pointer 205. Then, the controller 170 may receive the image list 1750 related to the mirroring image from the mobile terminal 600.

As the image list is displayed, an image desired by the user may be easily selected, and the selected image item may be transmitted to the mobile terminal 600. Thereby, the selected mirroring image may be easily received from the mobile terminal 600 and displayed.

In displaying additional information related to the mirroring image in a blank area, if the amount of data of the additional information is large or the size of the image indicating the additional information is greater than that of the blank area, the controller 170 of the image display apparatus 100 may perform a control operation to move and display the mirroring image or to display the mirroring image with the image reduced in size.

FIG. 8E illustrates where a mirroring image is moved to the right side such that the mirroring image 1720 is displayed in area Ar1, and the image list 1750 is displayed in area Ar2 as additional information related to the mirroring image.

FIG. 8F illustrates where a mirroring image 1725 which is the mirroring image 1720 reduced in size is displayed in the area Ara without change in the position of the displayed mirroring image, while the mirroring image list 1750 is displayed in the second area Arb which is a blank area.

If the mirroring image is a home screen window of the mobile terminal, the controller 170 of the image display apparatus 100 may perform a control operation to display a second home screen window or third home screen window in the blank area. This operation will be described with reference to FIGS. 9A to 9C.

FIG. 9A illustrates where a main home screen window 1910 of the mobile terminal 600 is displayed in the display area Ara as a mirroring image 1920.

If the pointer 205 moves to the second area Arb which is a blank area, the back key of the remote control device 200 operates, or the pointer 205 flicks to the left, the controller 170 of the image display apparatus 100 may perform a control operation to display a second home screen window 1922 related to the main home screen window 1910 of the mobile terminal 600 as additional information related to the mirroring image 1920, as shown in FIG. 9B.

Further, the controller 170 of the image display apparatus 100 may transmit a request for transmission of the second home screen window related to the mirroring image to the mobile terminal 600 according to the location of the pointer 205. Then, the controller 170 may receive the second home screen window related to the mirroring image from the mobile terminal 600.

As the main home screen window 1920 and the second home screen window 1922 are displayed simultaneously, an application may be easily selected through the image display apparatus 100, contrary to the display 680 of the mobile terminal 600 which is restricted, and the mirroring image for the selected application may be readily received from the mobile terminal 600 and displayed. Thereby, user convenience may be enhanced.

If the pointer 205 moves to the third area Arc which is a blank area, or the pointer 205 flicks to the right, the controller 170 of the image display apparatus 100 may

perform a control operation to display, in the third area Arc, the third home screen window **1924** related to the main home screen window **1920** of the mobile terminal **600** as additional information related to the mirroring image **1920**, as shown in FIG. **9C**.

The second home screen window may be a previous home screen window of the main home screen window, and the third home screen window may be the next home screen window of the main home screen window.

If the pointer **205** moves to the third area Arc which is a blank area, the controller **170** of the image display apparatus **100** may perform a control operation such that the third home screen window **1924** is displayed in the third area Arc while the second home screen window **1922** remains displayed in the second area Arb which is an blank area, as shown in FIG. **9C**.

In contrast with FIG. **9C**, the controller **170** of the image display apparatus **100** may perform a control operation such that the second home screen window **1922** is not displayed in the second area Arb which is a blank area, while the main home screen window **1920** is displayed in the display area Ara, and the third home screen window **1924** is displayed in the third area.

If the displayed mirroring image is a map image **2020** associated with map image **2010** as shown in FIG. **10A**, the controller **170** of the image display apparatus **100** may perform a control operation to display additional information according to the location of the pointer **205**.

Particularly, if the pointer **205** moves to the second area Arb which is a blank area, the back key of the remote control device **200** operates, or the pointer **205** flicks to the left, the controller **170** of the image display apparatus **100** may perform a control operation to display an additional map image **2022** in the second region Arb which is a blank area as additional information related to the mirroring image **2020**, as shown in FIG. **10B**.

Herein, the additional map image may be received from the mobile terminal **600** or may be separately created based on data received from the server **500** to which the image display apparatus **100** is connected.

If the pointer **205** moves to the third area Arc which is a blank area or the pointer **205** flicks to the right, the controller **170** of the image display apparatus **100** may perform a control operation to display an additional map image **2024** in the third area Arc as additional information related to the mirroring image **2020**, as shown in FIG. **10C**.

Herein, the controller **170** of the image display apparatus **100** may perform a control operation to display the map image in the display area Ara, the additional map image **2022** in the second area Arb and the additional map image **2024** in the third area Arc.

In contrast with the example of FIG. **10C**, the controller **170** of the image display apparatus **100** may perform a control operation to display the map image in the display area Ara and the additional map image **2024** in the third area Arc. That is, the controller **170** of the image display apparatus **100** may perform a control operation not to display the additional map image **2022** in the second area Arb.

In addition, if the pointer **205** is located in the display area Ara, the controller **170** of the image display apparatus **100** may perform a control operation such that detailed information which is not displayed on the mobile terminal **600** is displayed in the mirroring image **2020**, as shown in FIG. **10D**.

For example, the controller **170** of the image display apparatus **100** may analyze the mirroring image, collect data of detailed information which may be displayed in the

mirroring image, and perform a control operation to generate and display an object or OSD based on the data of the detailed information.

For example, as shown in FIG. **10D**, if the pointer **205** is located in the display area Ara, the controller **170** of the image display apparatus **100** may perform a control operation to display location information **2027** or shop name information **2028** in the map image as additional information or detailed information.

In particular, the controller **170** of the image display apparatus **100** may perform a control operation to display detailed information related to items in which the user is interested.

In the example of the figure, the shop location information **2027** and the shop name information **2028** are displayed as items in which the user is interested.

FIG. **10E**, which is similar to FIG. **10D**, illustrates mirroring according to horizontal display which corresponds to a display position of the mobile terminal **600**.

In performing mirroring, the image display apparatus **100** receives an image and displays the same according to the display position of the mobile terminal **600**.

In FIG. **10E**, the mobile terminal **600** is in the horizontal display position, and a map image **2030** is displayed thereon.

The controller **170** of the image display apparatus **100** may perform a control operation to display a map image **2040** on the display **180** as a mirroring image.

Similar to FIG. **10D**, the controller **170** of the image display apparatus **100** may perform a control operation to display additional information or detailed information on the map image **2040**.

If the display mode of the mobile terminal **600** is the horizontal display mode, the controller **170** of the image display apparatus **100** may perform a control operation to display additional information or detailed information, regardless of the pointer **205**.

In the figure, the location information **2047** or shop name information **2048** is displayed in the map image **2040** as the additional information or detailed information. Thereby, more detailed information may be viewed through the image display apparatus **100** which has a larger display **180**.

If the mirroring image is the home screen window or idle screen window of the mobile terminal, the controller **170** of the image display apparatus **100** may perform a control operation to display at least one of an object corresponding to a camera manipulation button attached to the mobile terminal, an object corresponding to a power button, an object corresponding to a volume adjustment button and an object corresponding to a zooming adjustment button in a blank area.

If the mirroring image is the home screen window or idle screen window of the mobile terminal, the controller **170** of the image display apparatus **100** may perform a control operation to display at least one of an object indicating a first connector for connection with an external device and an object indicating a second connector for connection with an additional detachable memory in the blank area.

Providing a button object or connector object of a mobile terminal as additional information will be described with reference to FIGS. **11A** to **11K**.

In the example of FIG. **11A**, an idle screen window **2120** is displayed in a display area Ara of the display **180** of the image display apparatus **100** as a mirroring image of idle screen window **2110**.

In the example of FIG. **11B**, if the pointer **205** of the remote control device **200** is located in the third area Arc which is a blank area, the controller **170** of the image display

apparatus **100** may perform a control operation to display an object **2122** corresponding to a manipulation button for, for example, manipulation of a camera.

For example, the controller **170** of the image display apparatus **100** may determine the manufacturer and product name of the mobile terminal **600**, using the device information about the mobile terminal received through pairing with the mobile terminal **600**.

Then, the controller **170** of the image display apparatus **100** may connect to the server **500** to receive an image related to the mobile terminal **600**.

Specifically, the controller **170** of the image display apparatus **100** may perform a control operation to receive an image of the mobile terminal including a manipulation button. Alternatively, the controller **170** of the image display apparatus **100** may perform a control operation to receive an image of the mobile terminal including an external terminal.

As another example, in performing pairing with the mobile terminal **600**, the controller **170** of the image display apparatus **100** may receive an image including the device information about the mobile terminal and the manipulation button of the mobile terminal **600** or receive an image of the mobile terminal **600** including the external terminal.

Thereby, the controller **170** of the image display apparatus **100** may perform a control operation to create an object **2122** corresponding to the manipulation button enabling manipulation of a camera and display the object **2122**, based on the received image including the manipulation button.

Alternatively, the controller **170** of the image display apparatus **100** may transmit, to the server **500**, the device information about the mobile terminal **600** received in performing pairing with the mobile terminal **600**, thereby receiving, from the server **500**, a control menu related to the manipulation button and terminal of the mobile terminal.

Herein, the control menu may include an object related to a manipulation button of the mobile terminal or an object related to the external terminal of the mobile terminal.

Then, the controller **170** of the image display apparatus **100** may perform a control operation to display the object **2122** related to the manipulation button of the mobile terminal in the received control menu according to predetermined input.

When an object **2122** corresponding to the camera manipulation button is selected by the pointer **205**, the controller **170** of the image display apparatus **100** may perform a control operation to transmit a camera manipulation button operation signal to the mobile terminal **600** such that a camera **621** operates in the mobile terminal **600**. Thereby, the camera of the mobile terminal **600** may be manipulated through the image display apparatus **100**.

Where the pointer **205** of the remote control device **200** is located in the third area Arc which is a blank area, the controller **170** of the image display apparatus **100** may perform a control operation to display objects corresponding to various buttons of the mobile terminal **600** in addition to the object **2122** corresponding to the camera manipulation button.

In FIG. **11C**, compared to FIG. **11B**, an object **2123** for a USB item, which is a first item for connection with an external device, a micro SD item, which is a second item for connection with an additional detachable memory, a speaker item, a microphone item, a flash item, a volume adjustment button item, a power button item and other types of button items may be additionally displayed in the third area Arc. Thereby, various manipulation operations of the mobile terminal **600** may be performed through the image display apparatus **100**.

For example, when the USB item, which is the first item for connection with an external device, is selected using the pointer **205**, the controller **170** of the image display apparatus **100** may perform a control operation through a USB terminal to display, on the display **180** of the image display apparatus **100**, an image displayed on the mobile terminal **600** as a mirroring image. Thereby, content from the external device connected to the mobile terminal **600** may be conveniently viewed.

As another example, when the micro SD item which is the second item for connection with an additional detachable memory is selected using the pointer **205**, the controller **170** of the image display apparatus **100** may perform a control operation through a micro SD terminal to display, on the display **180** of the image display apparatus **100**, an image displayed on the mobile terminal **600** as a mirroring image. Thereby, content from the additional memory attached to the mobile terminal **600** may be conveniently viewed.

As another example, when the flash item is selected using the pointer **205**, the controller **170** of the image display apparatus **100** may perform a control operation to transmit a control signal to turn on a flash device of the mobile terminal **600**.

If the flash item is selected again using the pointer **205**, the controller **170** of the image display apparatus **100** may perform a control operation to transmit a control signal to turn off the flash device of the mobile terminal **600**.

Similarly, when the speaker item, microphone item, volume adjustment button item, or power button item is selected, the controller **170** of the image display apparatus **100** may perform a control operation to turn on/off the speaker, the microphone, or the power, or turn up/down the volume.

FIG. **11D** illustrates where the speaker item in the object **2123** is selected by the pointer **205**.

When the speaker item in the object **2123** is selected, the controller **170** of the image display apparatus **100** may perform a control operation such the sound Sou is not output from the speaker of the mobile terminal **600**, as shown in FIG. **11D**. Specifically, the controller **170** of the image display apparatus **100** may perform a control operation to transmit, to the mobile terminal **600**, a control signal for causing the speaker of the mobile terminal **600** to be mute **2203**.

Thereby, as shown FIG. **11D**, sound is not output from the speaker of the mobile terminal **600**.

If the speaker item in the object **2123** is selected, the controller **170** of the image display apparatus **100** may perform a control operation to toggle and alternately output sound between the image display apparatus **100** and the mobile terminal **600**. This operation will be described with reference to FIGS. **11E** and **11F**.

To distinguish the example of FIGS. **11E** and **11F** from the above example, when the speaker item in the object **2123** is selected through a long press, the speaker of the mobile terminal **600** may be controlled to be turned on/off as shown in FIG. **11D**. When the speaker item in the object **2123** is selected through short press, sound output may be controlled to be toggled between the mobile terminal **600** and the image display apparatus **100**.

FIG. **11E** illustrates where sound Sout is output through the speaker of the image display apparatus **100** rather than through the mobile terminal **600** when the speaker item in the object **2123** is selected by the pointer **205**.

When the speaker item in the object **2123** is selected, the controller **170** of the image display apparatus **100** may perform a control operation to transmit a control signal to the

mobile terminal **600** such that a sound signal is not output from the mobile terminal **600**, and perform a control operation to receive an audio signal reproduced in the mobile terminal **600** such that the audio signal is output from the speaker of the image display apparatus **100**.

FIG. **11F** illustrates where sound Sout is output through the speaker of the mobile terminal **600** rather than through the image display apparatus **100** when the speaker item in the object **2123** is selected again by the pointer **205**.

When the speaker item in the object **2123** is selected again, the controller **170** of the image display apparatus **100** may perform a control operation to transmit a control signal to the mobile terminal **600** such that a sound signal is output from the mobile terminal **600** and sound is not output from the speaker of the image display apparatus **100**.

When the pointer **205** located in the blank area is shifted to the display area Ara of the mirroring image, the controller **170** of the image display apparatus **100** may perform a control operation such that an object corresponding to additional information displayed in the blank area is shifted and displayed.

FIG. **11G** illustrates displaying the object **2122** corresponding to the camera manipulation button on a mirroring image **2120** in an overlaying manner as the pointer **205** moves from the blank area to the display area Ara for the mirroring image.

The controller **170** of the display apparatus **100** may perform a control operation to display the object **2122** corresponding to the camera manipulation button at the actual location of the camera manipulation button. In this instance, to distinguish the object **2122** from the mirroring image **2120**, the controller **170** of the image display apparatus **100** may perform a control operation to highlight the object **2122** or make the object **2122** transparent. Thereby, the effect obtained when the camera manipulation button is actually manipulated may be achieved.

In contrast with FIG. **11G**, if the pointer **205** is located at the display area Ara for the mirroring image, the controller **170** of the display apparatus **100** may perform a control operation to display objects corresponding to various terminals disposed on the mobile terminal **600**, as shown in FIG. **11H**.

FIG. **11H** illustrates where a power charge terminal object **2135**, volume adjustment button objects **2133** and **2134**, a camera object **2132**, an earphone jack terminal object **2131**, an object **2136** indicating an LED, and other objects are displayed on the mirroring image **2120**. Thereby, the effect as obtained when the mobile terminal **600** is actually manipulated may be achieved.

Operations of some of the objects of FIG. **11H** may be controlled using the pointer **205**.

For example, when the volume adjustment button objects **2133** and **2134** are selected using the pointer **205**, the controller **170** of the image display apparatus **100** may transmit a volume adjustment signal to the mobile terminal **600**. Thereby, the mobile terminal **600** may be easily controlled.

As another example, when the earphone jack terminal object **2131** is selected using the pointer **205**, the controller **170** of the image display apparatus **100** may perform a control operation to establish Bluetooth connection with the mobile terminal **600**, as shown in FIG. **11H**.

Specifically, when the earphone jack terminal object **2131** is selected, the controller **170** of the image display apparatus **100** may perform a control operation to display a screen window **2210** for Bluetooth connection with the mobile

terminal **600** in an area Arc separate from the area for the mirroring image **2120**, as shown in FIG. **11I**.

When a connection item **2212** in the screen window **2210** for Bluetooth connection is selected, the controller **170** of the image display apparatus **100** may transmit a pairing signal for Bluetooth connection to the mobile terminal **600**, and receive a pairing response signal from the mobile terminal **600**. The pairing signal or pairing response signal may include frequency hopping information for Bluetooth connection.

When Bluetooth connection is completed, the controller **170** of the image display apparatus **100** may perform a control operation to display an object **2214** indicating completion of connection with the mobile terminal or an object **2216** indicating display of a music playback screen window, as shown in FIG. **11J**.

In particular, when the object **2216** indicating display of the music playback screen window is selected by the pointer, the controller **170** of the image display apparatus **100** may perform a control operation to transmit a control signal for execution of the music playback application to the mobile terminal **600**.

Thereby, the mobile terminal **600** may execute the music playback application, and display a music playback application screen window **2220a**, as shown in FIG. **11K**.

The controller **170** of the image display apparatus **100** may receive the music playback application screen window **2220a** displayed in the mobile terminal **600** according to mirroring, and perform a control operation to display a music playback application screen window **2220** in the area Ara as a mirroring screen window, as shown in FIG. **11K**.

As shown in FIG. **11K**, the music playback application screen window **2220** may include an object **2224** indicating a file list, a playback time and other playback information items and a Pause/Play object **2226**.

When the first music item **2222** in the file list is selected by the pointer **205**, the controller **170** of the image display apparatus **100** performs a control operation to play back the first music item **2222**. That is, the controller **170** of the image display apparatus **100** performs a control operation to transmit a control signal for playback of the first music item **2222** to the mobile terminal **600**.

Thereby, the mobile terminal **600** may play the first music item **2222**, and transmit a reproduced audio signal to the image display apparatus **100**. Herein, because the Bluetooth connection is established, the mobile terminal **600** may not output sound for the first music item **2222** through the speaker thereof.

The controller **170** of the image display apparatus **100** may receive an audio signal corresponding to a first music item which is played back, and perform a control operation to output sound Sout3 corresponding to the audio signal through the speaker. Thereby, a music file stored in the mobile terminal **600** may be conveniently played back through the image display apparatus **100** such that the music can be listened to. In particular, sound with a quality higher than the quality of sound provided by the mobile terminal **600** may be listened to through the speaker of the image display apparatus **100**.

Hereinafter, a description will be given of operations of an image display apparatus and mobile terminal for mirroring.

FIG. **12** is a flowchart illustrating operation of an image display apparatus and mobile terminal according to another embodiment of the present invention, and FIGS. **13A** to **15T** illustrate the operation method of FIG. **12**.

Referring to FIG. **12**, the controller **170** of the image display apparatus **100** may perform a control operation

based on user input to display mirroring-related server information or content related to the server information (S1610).

For example, when an input is provided through a specific key of the remote control device 200, the controller 170 of the image display apparatus 100 may perform a control operation to display a mirroring-related menu including content related to mirroring-related server information or content related to the server information.

For example, the content related to the server information may include a code image including the server information. More specifically, the content may include a QR code image including the server information.

As another example, the content related to the server information may be output as predetermined sound.

Next, the controller 670 of the mobile terminal 600 may acquire the mirroring-related server information or the content related to the server information displayed on the image display apparatus 100 (S1620). Then, the controller 670 of the mobile terminal 600 may recognize the mirroring-related server information (S1625).

For example, the mobile terminal 600 may capture a code image displayed on the image display apparatus 100 through the camera 621 of the mobile terminal 600. Then, the controller 670 of the mobile terminal 600 may extract server information from the captured code image and recognize the extracted server information (S1622).

As another example, the mobile terminal 600 may extract server information from sound received through the microphone 623 and recognize the extracted server information.

Next, the controller 670 of the mobile terminal 600 may control the mobile terminal 600 to be connected to the corresponding server based on the recognized mirroring-related server information (S1623). The server 500 may be connected with the mobile terminal 600 in response (S1624).

For example, the server 500 may be a server operated by the manufacturer of the image display apparatus 100. The server 500 may be a server corresponding to mirroring-related server information installed when the image display apparatus 100 was manufactured.

The user of the mobile terminal 600 may easily access the server 500 through the content related to the mirroring-related server information or content related to the server information displayed on the image display apparatus 100.

The server 500 may transmit a mirroring-related application to the mobile terminal 600 when connected with the mobile terminal 600 (S1625).

The controller 670 of the mobile terminal 600 may receive the mirroring-related application from the server 500 through the communication unit 610 (S1626), and install the mirroring-related application. Then, the controller 170 may execute the mirroring-related application (S1628).

Thereby, the mirroring-related application may be easily installed on and executed by the mobile terminal 600.

Next, the controller 670 of the mobile terminal 600 may determine whether an application item for which mirroring is to be performed selected (S1632). When the application item for which mirroring is to be performed is selected, the controller 670 may perform a control operation to transmit the selected application item to the image display apparatus 100 (S1645).

For example, the controller 670 of the mobile terminal 600 may select an application item for which mirroring is to be performed with the image display apparatus 100 among two or more applications installed in the mobile terminal 600, through the mirroring-related application.

At least one of application items may be selected, and the controller 670 of the mobile terminal 600 may transmit information about the selected application item to the image display apparatus 100.

In particular, the controller 670 of the mobile terminal 600 may transmit name information, application image information, user information, and application version information about the selected application item to the image display apparatus 100.

Next, the controller 170 of the image display apparatus 100 may receive the selected mirroring application item from the mobile terminal 600 via the network interface unit 135 or 145 (S1650).

Then, the controller 170 of the image display apparatus 100 may install the received mirroring application item in the image display apparatus 100, and particularly, performs a control operation to display the received mirroring application item in a mirroring-related menu (S1660). Thereby, the mirroring application item from the mobile terminal may be easily installed in and displayed on the image display apparatus 100.

Hereinafter, the operation method of FIG. 12 will be described with reference to FIGS. 13A to 15T.

The controller 170 of the image display apparatus 100 may perform a control operation to display, on the display 180, a broadcast image 700 based on a broadcast signal received by a broadcast receiver 105, as shown in FIG. 13A.

Herein, when an input is provided through of a specific key of the remote control device 200 or a predetermined item in a displayed menu is selected, the controller 170 of the image display apparatus 100 may perform a control operation to display a broadcast image 701 corresponding to a broadcast signal and an application list 710, as shown in FIG. 13B.

The controller 170 of the image display apparatus 100 may perform a control operation to display the application list 710 and the broadcast image 701 in an overlapping manner, as shown in FIG. 13B.

The application list 710 may include various application items including a device connection application item 715a. Additionally, the application list 710 may include an additional view item for viewing an additional application.

The device connection application item 715a may be referred to as a mirroring application item.

When the device connection application item 715a is focused on by the pointer of the remote control device 200, the controller 170 of the image display apparatus 100 may control the device connection application item 715a to be highlighted in contrast with the other items when the device connection application item 715a is displayed, as shown in FIG. 13B.

In the example of the figure, the size of the device connection application item 715a is increased over the other application items.

If the device connection application item 715a is selected by the pointer of the remote control device 200, the controller 170 of the image display apparatus 100 may perform a control operation to display a device list screen window 711 including two or more device items for mirroring connection on the display 180, as shown in FIG. 13C.

In the example of FIG. 13C, the displayed image 701 is caused to disappear, and the device list screen window 711 is displayed. Alternatively, the device list screen window 711 may be displayed on the displayed image 701 in an overlaying manner.

The device list screen window 711 may include a set-top box item, a Blu-ray/DVD player item, a home theater item,

a sound bar item, a speaker/headphone item, a game console item, a mobile terminal item, a computer item, an external storage device item such as a USB item, and other device items.

When the mobile terminal item **719a** in the device list screen window **711** is selected by, for example, the pointer of the remote control device **200**, the controller **170** of the image display apparatus **100** may perform a control operation to display, on the display **180**, a device control list screen window **712** including two or more items to be controlled through the mobile terminal, as shown in FIG. **13D**.

The device control list screen window **712** may include a remote control item from remotely controlling the image display apparatus **100** using the mobile terminal **600**, a Share Content item for sharing content between the mobile terminal **600** and the image display apparatus **100**, and a mirroring item for mirroring between the mobile terminal **600** and the image display apparatus **100**.

When a mirroring item **712a** in the device control list screen window **712** is selected by, for example, the pointer of the remote control device **200**, the controller **170** of the image display apparatus **100** may perform a control operation to display the device control list screen window **712** including two or more items to be controlled through the mobile terminal and a device connection method screen window **700** indicating a device connection method, as shown in FIG. **13E**.

The device connection method screen window **700** may include a code image **714a** including server information and relevant information **713**.

For example, the code image **714a** including the server information may include a QR code image including the server information, as shown in FIG. **13F**.

While the code image **714a** including the server information is displayed on the image display apparatus **100**, the camera **621** of the mobile terminal **600** may capture the code image **714a** including the server information, as shown in FIG. **13F**.

Then, the controller **670** of the mobile terminal **600** may receive and recognize the captured image **720b**. In this instance, the controller **670** of the mobile terminal **600** may perform a control operation to display the image **720b** related to the captured server information on the display **180**.

The controller **670** of the mobile terminal **600** may extract server information from the captured image **720b**.

Then, the controller **670** of the mobile terminal **600** may control connection to the server **500** based on the extracted server information **725**.

For example, the controller **670** of the mobile terminal **600** may transmit a connection request signal Sreg1 to the server **500** to connect to the server **500**, and receive a connection response signal Sreg1 from the server **500**, as shown in FIG. **13G**.

Next, the controller **670** of the mobile terminal **600** may receive a mirroring-related application from the server **500**, as shown in FIG. **13H**.

More specifically, the controller **670** of the mobile terminal **600** may perform a control operation to display a screen window **732** for downloading a mirroring application, as shown in (a) of FIG. **13H**.

In this instance, when the download item **732** is selected by, for example, touch input from the user, the controller **670** of the mobile terminal **600** may download a mirroring application. When downloading is completed, the controller **670** of the mobile terminal **600** may perform a control

operation to display a download complete screen window **734**, as shown in (b) of FIG. **13H**.

Next, the controller **670** of the mobile terminal **600** may install the downloaded mirroring setting application. In this instance, the controller **670** of the mobile terminal **600** may perform a control operation to display an installation screen window **736** as shown in (c) of FIG. **13H**.

When the installation is completed, the controller **670** of the mobile terminal **600** may perform a control operation to display an installation completed screen window **738** as shown in (d) of FIG. **13H**.

Next, the controller **670** of the mobile terminal **600** may execute the installed mirroring setting application.

This operation will be described with reference to FIGS. **14A** to **14K** or FIGS. **15A** to **15T**.

FIG. **14A** illustrates an idle screen window **810** or home screen window **810** of the mobile terminal **600**. The idle screen window **810** or the home screen window **810** may be displayed on the display **680**. Two or more application items may be displayed at the lower end of the screen window. In the figure, the mirroring application item **812** is displayed among two or more application items.

When the mirroring application item **812** is selected in the idle screen window **810** or home screen window **810** of the mobile terminal **600** of FIG. **14A**, or downloading of the mirroring application of FIG. **13H** is completed, the mirroring application may be automatically executed.

In executing the mirroring application, the controller **670** of the mobile terminal **600** may perform a control operation to display a mirroring setting application screen window **820**, as shown in FIG. **14B**.

The mirroring setting application screen window **820** may include a Enable item **822**, a TV Select item **824**, an Application Register item **826**, an Edit User Profile item **823**, a Set Orientation item **813**, and a Set Password item **814**.

When the Enable item **822** is selected and activated, the controller **670** of the mobile terminal **600** may perform a control operation to activate and display the TV Select item **824**, the Application Register item **826**, the Edit User Profile item **823**, the Set Orientation item **813**, and the Set Password item **814**, as shown in FIG. **14C**. Thereby, various kinds of settings may be implemented.

When the TV Select item **824** is selected, the controller **670** of the mobile terminal **600** may search for a TV around the mobile terminal **600**. When the search is terminated, the controller **670** may perform a control operation to display a TV list screen window **830** including at least one TV item, as shown in FIG. **14D**. In the illustrated example, two TV items are listed.

When a first TV item **832** of the two TV items is selected, the controller **670** of the mobile terminal **600** may complete setting for mirroring with the selected first TV item **832**. After the setting is completed, the controller **670** of the mobile terminal **600** may perform a control operation to display the mirroring setting application screen window **820** again, as shown in FIG. **14E**.

Next, when the Application Register item **826** is selected in the mirroring setting application screen window **820** displayed as shown in FIG. **14F**, the controller **670** of the mobile terminal **600** may perform a control operation to display an application list **850** including application items installed in the mobile terminal **600**, as shown in FIG. **14G**.

For example, when an Internet application item **852** and a camera application item **854** are selected from among two or more application items in the application list **850**, the controller **670** of the mobile terminal **600** may perform a



control operation to highlight the Internet application item **852** and the camera application item **854**, as shown in FIG. **14H**.

Then, when a Save item is selected, for example, the controller **670** of the mobile terminal **600** may perform a control operation to display the mirroring setting application screen window **820** again as shown in FIG. **14I**. Herein, the Application Register item **826b** may include information **827** related to the two selected applications.

Next, the controller **670** of the mobile terminal **600** may perform a control operation to transmit information related to the two selected application items to the image display apparatus **100** as shown in FIG. **14J**. In this instance, the controller **670** of the mobile terminal **600** may perform a control operation to display the transmitted information about the applications on the display **680**.

The image display apparatus **100** may receive, through the interface unit **130** or **135**, the information related to the two applications for which mirroring is to be performed.

The controller **170** of the image display apparatus **100** may perform a control operation to install the received mirroring application items on the image display apparatus **100**. In particular, the controller **170** of the image display apparatus **100** may perform a control operation to display the mirroring application items **711**, **712**, **716**, **719** in the mirroring-related menu **717**, as shown in FIG. **14K**.

The controller **170** of the image display apparatus **100** may select a first mirroring application item **711** of the mirroring application items **711**, **712**, **716**, **719** displayed in the mirroring-related menu **717**.

For example, the controller **170** may select the first mirroring application item **711** using an arrow key and an OK key of the remote control device **200**.

As another example, a pointer may be displayed based on a pointing signal included in an RF signal of the remote control device **200**, and the first mirroring application item may be selected by the pointer.

When the first mirroring application item is selected from among the mirroring application items displayed in the mirroring-related menu **717**, the controller **170** of the image display apparatus **100** may perform a control operation to transmit, to the mobile terminal **600**, pairing information or information for request for execution of the first mirroring application, to receive a first mirroring application execution image from the mobile terminal **600** through the network interface unit **135** or **135**, and to display the received first mirroring application execution image on the display **180**.

FIGS. **15A** to **15T** illustrate a method for executing a mirroring application different from the mirroring applications of FIGS. **14A** to **14K**.

FIG. **15A** illustrates the idle screen window **810** or home screen window **810** of the mobile terminal **600**. The idle screen window **810** or the home screen window **810** may be displayed on the display **680**. Two or more application items **910** may be displayed at the lower end of the screen.

In FIG. **15A**, a TV-related application item **905** is displayed in the home screen window **810** of the mobile terminal **600**. The TV-related application may be referred to as an image display apparatus-related application.

The TV-related application item **905** may be installed as illustrated in FIGS. **13A** to **13H**. The TV-related application may conceptually include a TV remote control application and a mirroring application.

When the TV-related application item **905** is executed for the first time, the controller **670** of the mobile terminal **600** may perform a control operation to display the TV-related application item **920** as shown in FIG. **15B**.

The TV-related application item may include a remote control item and a mirroring item **922**.

When the mirroring item **922** is selected, the controller **670** of the mobile terminal **600** may perform a control operation to display a screen window **925** for installation of a mirroring application as shown in FIG. **15C**.

When the "Agree" item **927** in the screen window **925** for installation of the mirroring application is selected, the controller **670** of the mobile terminal **600** may connect to the server **500** to request transmission of the mirroring application, download the mirroring application from the server **500** and install the same.

If an execution input is provided automatically or separately after installation of the mirroring application is completed, the controller **670** of the mobile terminal **600** may perform a control operation to display a mirroring application setting screen window **930** as shown in FIG. **15D**.

In particular, the mirroring application setting screen window **930** may include a list **935** including an image display apparatus item for an image display apparatus which is in the same AP device or located around the mobile terminal **600**.

While it is illustrated in the figure that only one image display apparatus item is displayed, it is also possible to display image display apparatus items for two or more image display apparatuses located around the mobile terminal.

When an image display apparatus item in the list **935** is selected, the controller **670** of the mobile terminal **600** may perform a control operation to transmit a relevant signal for the selected image display apparatus.

For example, the controller **670** of the mobile terminal **600** may perform a control operation to transmit a signal for display of code information related to the mirroring application.

The controller **170** of the image display apparatus **100** may receive, through the network interface unit **135**, a signal for display of the code information related to the mirroring application, and perform a control operation to display the code information **942** on the display **180**.

The displayed code information may be a random code generated by the controller **170** of the image display apparatus **100**.

In this instance, the controller **170** of the image display apparatus **100** may perform a control operation to display the code information **942** in addition to the displayed image **940**, as shown in FIG. **15E**.

When an image display apparatus item in the list **935** is selected, the controller **670** of the mobile terminal **600** may perform a control operation to display, on the display **680** of the mobile terminal **600**, an input window **948** for the code information displayed on the image display apparatus and a keyboard **949**, as shown in FIG. **15F**.

If a code corresponding to the code information displayed on the image display apparatus is input through the keyboard **949**, the controller **670** of the mobile terminal **600** may perform a control operation to transmit the code information to the image display apparatus **100**. Then, the controller **670** of the mobile terminal **600** may receive the authentication complete information from the image display apparatus **100**.

After authentication is completed, the controller **670** of the mobile terminal **600** may perform a control operation to display an authentication complete screen window **950**, as shown in FIG. **15G**.

Through the steps of FIG. **15A** to **15G**, setting for mirroring between the mobile terminal **600** and the image display apparatus **100** may be completed.

When setting for mirroring between the mobile terminal 600 and the image display apparatus 100 is completed in the mobile terminal 600 through the steps of FIG. 15A to 15G, information related to a server connected with the mobile terminal 600 may be transmitted to the image display apparatus 100, and thus a mirroring application may be received by and installed on the image display apparatus 100.

Alternatively, the steps of FIG. 15A to 15G may be performed in the mobile terminal 600 with the mirroring application pre-installed on the image display apparatus 100.

Once setting for mirroring between the mobile terminal 600 and the image display apparatus 100 is completed through the steps of FIG. 15A to 15G, the mobile terminal 600 and the image display apparatus 100 will remain connected to each other.

When the mobile terminal 600 and the image display apparatus 100 are wirelessly connected to each other, the controller 170 of the image display apparatus 100 may perform a control operation to display an object 962 indicating the paired mobile terminal on the display 180.

In particular, the controller 170 of the image display apparatus 100 may perform a control operation to display the object 962 indicating the paired mobile terminal on the displayed image 960. Thereby, while viewing the image 960 of the image display apparatus 100, the user of the mobile terminal or another user may recognize that the mobile terminal is paired and connected with the image display apparatus.

The object 962 indicating the paired mobile terminal may include name information and image information. The image information may be edited through user selection of the paired mobile terminal. The name information may also be edited through user selection of the paired mobile terminal.

FIG. 15H illustrates display of an application list 910 and a setting object 963 in addition to the image 960 and the object 962 indicating the paired mobile terminal.

Where two or more mobile terminals is paired and connected with the image display apparatus, the controller 170 of the image display apparatus 100 may perform a control operation to display objects 962 and 964 indicating the two or more mobile terminals as shown in FIG. 15I.

FIG. 15I illustrates an object 962 indicating the paired mobile terminal and a second object 964 indicating a second paired mobile terminal on an image 965.

If the number of displayed objects is greater than an allowed number of objects, the controller 170 of the display apparatus 100 may perform a control operation to delete objects from the oldest object and display objects corresponding to the most recently connected mobile terminals.

In FIG. 15H or 15I, when the object 962 indicating a paired mobile terminal is selected, the controller 170 of the display apparatus 100 may perform a control operation to display an application list 970 and a wish list 975 related to the paired mobile terminal, as shown in FIG. 15J.

The application list 970 related to the paired mobile terminal may include an application item which can be subjected to mirroring between the mobile terminal 600 and the image display apparatus 100 and an Add item 966.

In the figure, an App Store item, a moving image playback item, a map item, an image viewer item and an Internet item are provided as examples of application items which can be subjected to mirroring.

If the Add item 966 is selected in the application list 970 related to the paired mobile terminal as shown in FIG. 15K, the controller 170 of the image display apparatus 100 may

perform a control operation to display a list 977 of applications to be added as shown in FIG. 15L.

The list 977 of applications to be added may be a mirrored image identical to the image displayed on the mobile terminal 600.

That is, when the Add item 966 is selected in the application list 970 related to the paired mobile terminal as shown in FIG. 15K, the controller 170 of the image display apparatus 100 may transmit an application list execution request to the mobile terminal 600. Then, the controller 170 of the image display apparatus 100 may perform a control operation to receive and display a list of applications which are being executed on the mobile terminal 600.

When predetermined items 977a, 977b and 977c are selected, by, for example, the remote control device 200, in the list 977 of applications to be added which is displayed in FIG. 15M, the controller 170 of the image display apparatus 100 may transmit information related to the selected items to the mobile terminal 600, receive applications related to the selected items from the mobile terminal 600 or the server 500, and install the same.

Thereby, the controller 170 of the image display apparatus 100 may perform a control operation to display a new application list 970 including the added application items 978a, 978b and 978c, as shown in FIG. 15N.

When a moving image playback item 971a is selected in the application list 970 as shown in FIG. 15L, the controller 170 of the image display apparatus 100 may perform a control operation to display an object 971 indicating that connection to the mobile terminal is being executed, and attempt to connect to the mobile terminal 600.

That is, the controller 170 of the image display apparatus 100 may transmit, to the mobile terminal 600, an application execution request related to the moving image playback item. Then, when the application related to the moving image playback item of the mobile terminal 600 is executed, the controller 170 of the image display apparatus 100 may perform a control operation to implement mirroring.

Then, when mirroring connection is completed, the controller 170 of the image display apparatus 100 may perform a control operation to display, on the display 180, a screen window 981 of a moving image playback application which is being executed in the mobile terminal 600, as shown in FIG. 15O.

When the Internet item of FIG. 15N is selected, the controller 170 of the image display apparatus 100 may perform a control operation to display, on the display 180, an Internet screen window 982 displayed on the mobile terminal 600, as shown in FIG. 15P.

When the second object 964 indicating the second paired mobile terminal is selected with the object 962 and the second object 964 displayed as shown in FIG. 15Q, the controller 170 of the image display apparatus 100 may perform a control operation to display an application list 990 related to the second paired mobile terminal as shown in FIG. 15R.

Although FIGS. 15Q and 15R illustrate change of users, addition of a user may also be implemented using a screen division technique.

When the second object 964 indicating the second paired mobile terminal is selected by the back key after the controller 170 of the image display apparatus 100 displays the application list 970 related to the paired mobile terminal according to selection of the object 962 indicating the paired mobile terminal through the steps of FIGS. 15I and 15J, the controller 170 of the image display apparatus 100 may

perform a control operation to display a Change User object **991** and an Add User object **992**, as shown in FIG. 15S.

If the Change User object **991** is selected, the controller **170** of the image display apparatus **100** may perform a control operation to display an application list **990** related to the second paired mobile terminal as shown in FIG. 15R.

When the Add User object **992** is selected, the controller **170** of the image display apparatus **100** may perform a control operation to display an application list **996** related to the paired mobile terminal and an application list **997** related to the second paired mobile terminal on the display **180**, as shown in FIG. 15T.

That is, as shown in FIG. 15T, the screen may be divided to display the application list **996** related to the paired mobile terminal and the application list **997** related to the second paired mobile terminal together on the display **180**. Thereby, mirroring may be implemented using two or more mobile terminals.

The name information and image information about the object indicating the paired mobile terminal may be edited through the mobile terminal **600**.

FIG. 16 is a flowchart illustrating operation of an image display apparatus and mobile terminal according to another embodiment of the present invention, and FIGS. 17A to 17H illustrate the operation method of FIG. 16.

Referring to FIG. 16, after being turned on, the controller **170** of the image display apparatus **100** may periodically transmit a pairing signal.

If the mobile terminal **600** approaches the image display apparatus **100** within a predetermined distance, the mobile terminal **600** may receive the pairing signal (S1503). Then, when the mobile terminal **600** is within the predetermined distance from the image display apparatus **100**, the mobile terminal **600** may transmit a pairing response signal in response to reception of the pairing signal.

Thereby, the image display apparatus **100** may receive the pairing response signal and perform pairing based on the pairing response signal (S1505).

The pairing signal may include device information about the image display apparatus **100**, network information, and frequency channel information for wireless communication.

The pairing response signal may include device information about the mobile terminal **600**, network information, and frequency channel information for wireless communication.

The controller **170** of the image display apparatus **100** may perform a control operation to display a mirroring-related menu when pairing with the mobile terminal **600** is completed (S1510).

The mirroring-related menu may be the mirroring-related menu **717** as shown in FIG. 14K.

In addition, the mirroring-related menu may be an object indicating the paired mobile terminal as shown in FIG. 15H. Hereinafter, description will be given focusing on the object **962** indicating the paired mobile terminal.

FIG. 17A illustrates where the distance between the image display apparatus **100** in the mobile terminal **600** is  $D_a$  at which pairing cannot be performed.

In this instance, the controller **170** of the image display apparatus **100** controls a menu related to the mobile terminal not to be displayed. In FIG. 17A, only the image **960** and the application list **910** are displayed.

FIG. 17B illustrates where the distance between the image display apparatus **100** and the mobile terminal **600** is  $D_b$  at which pairing can be performed.

In this instance, the controller **170** of the image display apparatus **100** receives a pairing signal or a pairing response

signal from the mobile terminal **600** as described above (S1503), and performs pairing based on the signal.

When pairing is completed, the controller **170** of the image display apparatus **100** may perform a control operation to display an object **962** indicating the paired mobile terminal in addition to the image **960** and the application list **910**, as shown in FIG. 17C. Thereby, it may be recognized that connection is being performed as pairing with the mobile terminal is completed.

When a first user item is selected in the menu (S1520), namely when the object **962** indicating the paired mobile terminal is selected, the controller **170** of the image display apparatus **100** may perform a control operation to display an application list **970** related to the paired mobile terminal and a wish list **975** (S1525), as shown in FIG. 17D.

Next, when a first application is selected in the application list **970** related to the paired mobile terminal (S1530), the controller **170** of the image display apparatus **100** may perform a control operation to transmit a request for transmission of a screen window related to the first application to the mobile terminal **600** (S1535).

Thereby, the controller **670** of the mobile terminal **600** may receive the request for transmission of a screen window related to the first application through a communication unit (S1540), and perform a control operation to execute and display the first application on the display **680** and to transmit the screen window of the first application to the image display apparatus **100** (S1545).

The controller **170** of the image display apparatus **100** may receive the first application screen window via the network interface unit (S1550), and perform a control operation to display the moved mirroring image on the display **180** (S1560).

When the image viewer application is selected in the application list **970** related to the paired mobile terminal as shown in FIG. 17D, the controller **170** of the image display apparatus **100** may perform a control operation to receive the image of the image viewer application from the paired mobile terminal **600** and to display the image **701** of the image viewer application, as shown in FIG. 17E.

While it is illustrated in the figure that the image viewer application image **701** and the application list **710** are displayed together, the image viewer application image **701** may be displayed alone.

If another mobile terminal approaches the image display apparatus **100** within a predetermined distance with the paired mobile terminal **600** located within the predetermined distance, the controller **170** of the image display apparatus **100** may perform a control operation to implement additional pairing.

As shown in FIG. 17F, if a second mobile terminal **600b** approaches the image display apparatus **100** within the predetermined distance and is located at distance  $D_c$  from the image display apparatus **100**, the controller **170** of the image display apparatus **100** may perform a control operation to receive a pairing response signal from the second mobile terminal **600b** and implement additional pairing.

After the additional pairing is implemented, the controller **170** of the image display apparatus **100** may perform a control operation to display objects **962** and **964** indicating the two or more mobile terminals as shown in FIG. 17G.

FIG. 17G illustrates where the object **962** indicating the paired mobile terminal and a second object **964** indicating a second paired mobile terminal are displayed on an image **965**.

As shown in FIG. 17H, when the second object **964** indicating the second paired mobile terminal is selected

between the objects 962 and 964, the controller 170 of the image display apparatus 100 may perform a control operation to display an application list 996 related to the paired mobile terminal and an application list 997 related to the second mobile terminal on the display 180 together.

Alternatively, the controller 170 of the image display apparatus 100 may perform a control operation to display only the application list related to the second paired mobile terminal.

An operation method for the image display apparatus or mobile terminal according to the present invention is implementable by code which can be read by the processor on a recording medium which can be read by a processor provided to autonomous driving apparatus or vehicle. The recording medium readable by the processor includes all kinds of recording devices for storing data which can be read by the processor. Examples of the recording medium readable by the processor include ROM, RAM, CD-ROM, magnetic tape, floppy disk, and optical data storage. The method is also implementable in the form of a carrier wave such as transmission over the Internet. In addition, the recording medium readable by the processor may be distributed to computer systems connected over a network, and code which can be read by the processor in a distributed manner may be stored in the recording medium and executed.

As is apparent from the above description, according to an embodiment of the present invention, an image display apparatus includes a display, an interface unit to exchange data with a mobile terminal, and a controller to perform a control operation to display a mirroring image received from the mobile terminal and to perform a control operation to display additional information related to the mirroring image in a blank area other than the display area for display of the mirroring image. Thereby, in performing mirroring between the mobile terminal and the display apparatus, the mirroring image and various kinds of information may be viewed simultaneously.

In addition, the controller performs a control operation to display a pointer on the display based on a pointing signal of a remote control device, and if the pointer is located in the blank area when the mirroring image is displayed, the controller performs a control operation to display the additional information related to the mirroring image. Thereby, display of additional information based on the pointer is enabled. Accordingly, user convenience may be enhanced.

By displaying different information in the blank area according to movement of the pointer, various kinds of information may be provided to the user.

When additional information related to a mirroring image is displayed, the controller performs a control operation to move and display the mirroring image. Thereby, location of the mirroring image may be varied according to the amount of the additional information.

If the mirroring image is a home screen window or idle screen window of the mobile terminal, the controller performs a control operation to display at least one of an object corresponding to a camera manipulation button attached to a mobile terminal, an object corresponding to a power button, an object corresponding to a volume adjustment button and an object corresponding to a zooming adjustment button in the blank area. Thereby, remote control of the mobile terminal may be enabled.

If the mirroring image is the home screen window or idle screen window, the controller performs a control operation to display at least one of an object indicating a first connector for connection with an external device and an object

indicating a second connector for connection with a detachable additional memory in the blank area. Thereby, external input to the mobile terminal may be easily viewed.

According to an embodiment of the present invention, an image display apparatus includes a display, an interface unit to exchange data with a mobile terminal, and a controller to perform a control operation to display a mirroring image received from the mobile terminal and to perform a control operation to display additional information related to the mirroring image in a display area for display of the mirroring image. Thereby, when mirroring is performed between the mobile terminal and the image display apparatus, the mirroring image and various kinds of information may be viewed simultaneously.

In addition, when an object indicating a paired mobile terminal is selected, a list of applications which can be subjected to mirroring is displayed. Thereby, mirroring with the mobile terminal may easily performed.

Further, when a mobile terminal approaches the image display apparatus within a predetermined distance allowing pairing, the image display apparatus performs pairing. Thereby, pairing may be easily performed.

Although embodiments of the present invention have been disclosed for illustrative purposes, those skilled in the art will appreciate that various modifications, additions and substitutions are possible, without departing from the scope and spirit of the invention as disclosed in the accompanying claims.

The present invention encompasses various modifications to each of the examples and embodiments discussed herein. According to the invention, one or more features described above in one embodiment or example can be equally applied to another embodiment or example described above. The features of one or more embodiments or examples described above can be combined into each of the embodiments or examples described above. Any full or partial combination of one or more embodiment or examples of the invention is also part of the invention.

What is claimed is:

1. An image display apparatus comprising:

a display;  
an interface to exchange data with a mobile terminal; and  
a controller electrically connected to the display and the interface,

wherein, when a first distance between the mobile terminal and the image display apparatus is a predetermined distance, pairing is performed with the mobile terminal, wherein, when the pairing with the mobile terminal is completed, the display displays a first object indicating that the mobile terminal is paired with the image display apparatus,

wherein, when the first object is selected, the display displays an application list including a first application corresponding to the paired mobile terminal,

wherein, when the first application is selected, the interface wirelessly transmits a request for transmission of a mirroring image to the mobile terminal, and

wherein the display displays the mirroring image received from the mobile terminal and displays additional information related to the mirroring image in a blank area other than a display area for display of the mirroring image.

2. The image display apparatus according to claim 1, further comprising:

a second interface to receive a signal from a remote control device,

39

wherein the display displays a pointer on the display, based on a pointing signal of the remote control device, and

wherein, when the pointer is located in the display area displaying the mirroring image, the display displays the additional information related to the mirroring image in the blank area.

3. The image display apparatus according to claim 2, wherein, when the additional information related to the mirroring image is displayed, the mirroring image is moved to the blank area and the display displays the moved mirroring image in the blank area.

4. The image display apparatus according to claim 1, further comprising:

a second interface to receive a signal from a remote control device,

wherein the display displays a pointer based on a pointing signal of the remote control device,

wherein, when the pointer is located in a second area corresponding to the blank area, a back key of the remote control device operates, or the pointer flicks to the left in displaying the mirroring image, the display displays the additional information related to the mirroring image in the second area, and

wherein, when the pointer is located in a third area corresponding to the blank area, or the pointer flicks to the right in displaying the mirroring image, the display displays the additional information related to the mirroring image in the third area.

5. The image display apparatus according to claim 4, wherein, when the pointer located in the second area moves to the third area in displaying the mirroring image, the display displays second additional information in the third area with first additional information displayed in the second area.

6. The image display apparatus according to claim 4, wherein, when the pointer located in the second area moves to the third area in displaying the mirroring image, the additional information displayed in the second area disappears and the display displays the additional information in the third area.

7. The image display apparatus according to claim 1, wherein the additional information includes at least one of an image adjustment item for the mirroring image, a share item for sharing the image, a previous image for the mirroring image, a next image for the mirroring image, an image list related to the mirroring image, an application item related to the mirroring image, and detailed information about the mirroring image.

40

8. The image display apparatus according to claim 1, wherein, when the mirroring image is a home screen window or idle screen window of the mobile terminal, the display displays, in the blank area, at least one of an object corresponding to a camera manipulation button attached to the mobile terminal, an object corresponding to a power button, an object corresponding to a volume adjustment button and a zooming adjustment button.

9. The image display apparatus according to claim 1, wherein, when the mirroring image is a home screen window or idle screen window of the mobile terminal, the display displays, in the blank area, at least one of an object indicating a first connector for connection with an external device and an object indicating a second connector for connection with an additional detachable memory.

10. The image display apparatus according to claim 1, wherein the additional information related to the mirroring image is changed according to an attribute of the mirroring the image.

11. The image display apparatus according to claim 1, wherein the mirroring image received from the mobile terminal is scaled and the display displays the scaled mirroring image in a first area of the display and displays the additional information related to the mirroring image in a second area, the second area being the blank area.

12. The image display apparatus according to claim 1, wherein, when the first application in the application list is selected, the interface receives, from the mobile terminal, the mirroring image in response to the request for transmission of the mirroring image.

13. The image display apparatus according to claim 1, wherein, when pairing with a second mobile terminal is additionally performed while the object indicating the paired mobile terminal is displayed, the display displays the object indicating the paired mobile terminal and a second object indicating the second mobile terminal.

14. The image display apparatus according to claim 1, wherein the mirroring image received from the mobile terminal comprises an application execution image of an application executed in the mobile terminal.

15. The image display apparatus according to claim 1, wherein, when the mobile terminal receives the request for transmission of the mirroring image, the mobile terminal performs an application corresponding to the first application, displays an image of the performed application, and transmits the mirroring image corresponding to the image of the performed application.

\* \* \* \* \*