



US010647488B2

(12) **United States Patent**
Ours et al.

(10) **Patent No.:** **US 10,647,488 B2**

(45) **Date of Patent:** **May 12, 2020**

(54) **SYSTEM FOR PRODUCING A
TRANSPORTABLE CONTAINER FOR
FLOWABLE BULK GOODS**

53/02 (2013.01); *B65D 19/44* (2013.01);
B65D 71/08 (2013.01); *B65D 2571/0003*
(2013.01);

(Continued)

(71) Applicant: **Kellogg Company**, Battle Creek, MI
(US)

(58) **Field of Classification Search**

CPC B65B 1/02;
B65B 1/36; B65B 11/025; B65B 11/045;
B65B 11/58; B65B 53/02; B65B 43/58;
B65B 43/59; B65B 43/62; B65D
71/0096; B65D 71/08; B65D 71/10;
B65D 75/002; B65D 2571/00018;

(Continued)

(72) Inventors: **Dave Ours**, Marshall, MI (US); **Sharon
Juntunen**, Portage, MI (US)

(73) Assignee: **KELLOGG COMPANY**, Battle Creek,
MI (US)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 477 days.

U.S. PATENT DOCUMENTS

1,474,625 A * 11/1923 Eckert A47J 19/005
100/123
1,649,362 A * 11/1927 Nagel B65B 1/22
100/151

(Continued)

Primary Examiner — Stephen F. Gerrity

(21) Appl. No.: **15/432,306**

(74) *Attorney, Agent, or Firm* — Honigman LLP; Kathryn
D. Doyle, Esq.; Jonathan P. O'Brien

(22) Filed: **Feb. 14, 2017**

(65) **Prior Publication Data**

US 2017/0152090 A1 Jun. 1, 2017

Related U.S. Application Data

(60) Continuation of application No. 13/593,762, filed on
Aug. 24, 2012, now abandoned, which is a division of
(Continued)

(51) **Int. Cl.**
B65D 71/00 (2006.01)
B65B 1/02 (2006.01)


(Continued)

(52) **U.S. Cl.**
CPC *B65D 71/0096* (2013.01); *B65B 1/02*
(2013.01); *B65B 1/36* (2013.01); *B65B 11/025*
(2013.01); *B65B 11/045* (2013.01); *B65B*

(57) **ABSTRACT**

A transportable container for flowable bulk goods includes
a bottom support and a stretch wrap spirally wrapped around
the bottom support and extending vertically in relationship
to the bottom support. Bulk goods are disposed within the
stretch wrap and at least of portion of the bulk goods are
disposed in direct contact with the stretch wrap to squeeze
the bulk goods together and generate hoop forces for stabi-
lizing the bulk goods in the transportable container. The
transportable container has a shape that varies radially in
vertical relationship to the bottom support for adjusting the
hoop forces vertically along the transportable container. The
varied shape of the transportable container can be, for
example, tapered, hour-glass shaped, or pumpkin shaped.

16 Claims, 6 Drawing Sheets



Related U.S. Application Data

application No. 13/466,166, filed on May 8, 2012, now Pat. No. 8,276,347, which is a division of application No. 12/553,406, filed on Sep. 3, 2009, now Pat. No. 8,191,341.

(60) Provisional application No. 61/093,798, filed on Sep. 3, 2008.

(51) **Int. Cl.**

B65B 11/04 (2006.01)
B65B 11/02 (2006.01)
B65B 1/36 (2006.01)
B65B 53/02 (2006.01)
B65D 19/44 (2006.01)
B65D 71/08 (2006.01)

(52) **U.S. Cl.**

CPC *B65D 2571/00018* (2013.01); *B65D 2571/00024* (2013.01); *B65D 2571/00055* (2013.01)

(58) **Field of Classification Search**

CPC .. *B65D 2571/00024*; *B65D 2571/0003*; *B65D 2571/00055*; *B65D 2571/00111*
 USPC 53/399, 436, 441, 442, 449, 459, 469, 53/526, 528, 139.1, 173, 176, 556, 557, 53/570, 574, 575, 576, 577, 587, 284.7
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,730,295 A * 10/1929 Reuther B65B 1/22
 141/75
 4,546,598 A * 10/1985 Karpisek B65B 9/135
 53/390
 4,553,374 A * 11/1985 Lancaster et al. B65B 11/008
 53/210

5,117,750 A * 6/1992 Mosier, II et al. ... B30B 9/3082
 100/155 R
 5,203,671 A * 4/1993 Cawley et al. B65B 11/008
 414/791.6
 5,566,530 A * 10/1996 Johnstone et al. B65B 11/045
 53/441
 5,701,722 A * 12/1997 Franklin et al. B65B 11/025
 53/399
 6,494,324 B2 * 12/2002 Ours et al. B65B 1/02
 206/527
 6,594,970 B1 * 7/2003 Hyne et al. B65B 11/025
 53/399
 6,647,701 B2 * 11/2003 Rettich B30B 9/3082
 53/528
 6,892,768 B1 * 5/2005 Ours et al. B65B 9/14
 141/10
 6,918,225 B2 * 7/2005 Ours et al. B65B 1/02
 53/139.1
 6,935,385 B2 * 8/2005 Ours et al. B65B 9/14
 141/10
 6,945,015 B2 * 9/2005 Ours et al. B65B 1/06
 53/442
 7,055,293 B2 * 6/2006 Ours et al. B65B 1/02
 53/399
 7,174,924 B2 * 2/2007 Ours et al. B65B 1/02
 141/10
 7,267,145 B2 * 9/2007 Nyhof et al. B65B 1/04
 141/114
 7,284,360 B2 * 10/2007 Cary et al. B65B 9/13
 53/173
 7,536,840 B2 * 5/2009 Ours et al. B65D 71/0088
 53/173
 7,921,624 B2 * 2/2011 Ours et al. B65B 1/02
 53/399
 2001/0029722 A1 * 10/2001 Ours et al. B65B 1/02
 53/399
 2004/0026292 A1 * 2/2004 Ours et al. B65B 1/02
 206/527
 2009/0223179 A1 * 9/2009 Johnstone A01F 15/071
 53/562

* cited by examiner




Fig-1




Fig-2




Fig-3





Fig-5






Fig-7







Fig-8





1

**SYSTEM FOR PRODUCING A
TRANSPORTABLE CONTAINER FOR
FLOWABLE BULK GOODS**

CROSS REFERENCE TO RELATED
APPLICATION

This application is a Continuation of U.S. patent application Ser. No. 13/593,762, filed Aug. 24, 2012, which is a division of U.S. patent application Ser. No. 13/466,166, now U.S. Pat. No. 8,276,347, for a METHOD FOR FORMING A TRANSPORTABLE CONTAINER FOR BULK GOODS, filed May 8, 2012, which is a division of U.S. patent application Ser. No. 12/553,406, now U.S. Pat. No. 8,191,341 for a METHOD FOR FORMING A TRANSPORTABLE CONTAINER FOR BULK GOODS AND METHOD FOR FORMING THE SAME, filed on Sep. 3, 2008, which are hereby incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The subject invention relates to a transportable container for flowable bulk goods.

2. Description of the Prior Art

Typical containers utilized for transport of bulk goods are inefficient, do not have a very large volume, and often require a large amount of manual labor to be used in filling and handling of the container. Also these containers are typically stacked on top of each other during handling and transport, because the containers are not stabilized, this results in damage to the material. It is known in the art of stretch wrapping to stack loads onto a pallet and then shrink wrap the load placed upon the pallet to secure it.

An example of one such system is shown in U.S. Pat. No. 6,594,970 to Hyne et al. The Hyne patent discloses a method and apparatus for wrapping an outer wrap around a stack of products on a bottom support. The system uses a guide which acts as a barrier between the stack of product and the outer wrap. To begin the bottom support is placed at a location adjacent the guide and layers of product are added to the pallet to form the stack. As the layers of products are added to the pallet, the pallet begins to move downwardly from the guide to allow for the outer wrap to be applied to the product to secure and stabilize it. The outer wrap is applied to the guide prior to being received by the layers of products so that the layers of products are not crushed or displaced by the outer wrap.

Another example of one such system is shown in U.S. Pat. No. 4,607,476 to Fulton Jr. The Fulton patent discloses a system for applying an outer wrap to unstable stacks of product on a pallet. The system includes a confinement container having a bottom support or pallet placed on a lift. Layers of unstable product are placed on the pallet to form a stack within the confinement container. A top cap is placed on the top of the unstable layers and the outer wrap is initially applied around the top cap and the upper edge of the confinement container. The lift moves the pallet of unstable products upward and the outer wrap slides off the edge of the

2

confinement container to contact the layers of product for stabilizing the stacks of product.

SUMMARY OF THE INVENTION AND
ADVANTAGES

A transportable container for flowable bulk goods includes a bottom support and a stretch wrap spirally wrapped around the bottom support and extending vertically in relationship to the bottom support. Bulk goods are disposed within the stretch wrap, and at least a portion of the bulk goods are in direct contact with the stretch wrap to squeeze the bulk goods together and create hoop forces for stabilizing the bulk goods in the transportable container. The direct contact between the stretch wrap and a portion of bulk goods is advantageous because the hoop forces created allow for a very compact and rigid transportable container which does not allow the bulk goods to shift or get crushed within the transportable container. The hoop forces promote bridging between the bulk foods thereby reducing the relative motion between the pieces and immobilize the bulk goods within the transportable container.

BRIEF DESCRIPTION OF THE DRAWINGS

Other advantages of the present invention will be readily appreciated, as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings wherein:

FIG. 1 is perspective view of a first exemplary embodiment of a transportable container formed from a packaging system according to the subject invention;

FIG. 2 is perspective view of a second exemplary embodiment of a transportable container formed from a packaging system according to the subject invention;

FIG. 3 is perspective view of a third exemplary embodiment of a transportable container formed from a packaging system according to the subject invention;

FIG. 4 is perspective view of a first exemplary transportable container being circular in cross section and formed according to the subject invention;

FIG. 5 is perspective view of a second exemplary transportable container being square in cross section and formed according to the subject invention;

FIG. 6 is front view of a third exemplary transportable container being hour glass shaped and formed according to the subject invention;

FIG. 7 is perspective view of a fourth exemplary transportable container being tapered and formed according to the subject invention;

FIG. 8 is perspective view of a fifth exemplary transportable container being pumpkin shaped and formed according to the subject invention;

FIG. 9 is side view of a fourth exemplary embodiment of a transportable container formed from a packaging system according to the subject invention; and

FIG. 10 is side view of a fifth exemplary embodiment of a transportable container formed from a packaging system according to the subject invention.

DETAILED DESCRIPTION OF THE
EXEMPLARY EMBODIMENTS

Referring to the Figures, wherein like numerals indicate corresponding parts throughout the several views, a trans-

portable container **20** of bulk goods and a method of making the same are generally shown.

Throughout the present specification and claims the phrase “bulk goods” is used as a shorthand version of the wide range of products that can be packaged utilizing the present invention. The present invention finds utilization in packaging any material that can be bulk packaged. These items can encompass large bulk packaged pieces as well as very small bulk packaged pieces. Examples of smaller bulk goods include, but are not limited to, the following: agricultural products like seeds, rice, grains, vegetables, fruits, chemical products like fine chemicals, pharmaceuticals, raw chemicals, fertilizers, plastics like plastic resin pellets, plastic parts, rejected plastic parts, machined plastic parts, cereals and cereal products such as wheat, a variety of machined parts of all sorts, wood products like wood chips, landscaping material, peat moss, dirt, sand, gravel, rocks and cement. The present invention also finds utilization in bulk packaging of larger bulk goods including, but not limited to: prepared foods, partially processed foods like frozen fish, frozen chicken, other frozen meats and meat products, manufactured items like textiles, clothing, footwear, toys like plastic toys, plastic half parts, metallic parts, soft toys, stuffed animals, and other toys and toy products. All of these types of materials and similar bulk packaged materials are intended to be encompassed in the present specification and claims by this phrase.

While the present invention may be adapted to work with any number of packaging systems **26**, the exemplary embodiment of the present invention will be explained in reference to the exemplary packaging system **26** discussed below.

In the exemplary embodiment, the packaging system **26** includes a frame having an upper support **28** spaced from a frame base **30**. At least one support column **32** extends between the frame base **30** and upper support **28**. The upper support **28**, the frame base **30**, or both may be vertically movable along the support column **32**.

The packaging system **26** may include an upper turntable **34** that is mounted within the upper support **28** of the packaging system **26** and a lower turntable **36** that is mounted within the frame base **30** of the packaging system **26**. The lower turntable **36** and upper turntable **34** may be stationary or rotatable. When the upper turntable **34** and lower turntable **36** are rotatable, it is preferred that the rotation of the lower turntable **36** and upper turntable **34** are synchronized such that they rotate in unison. The synchronized rotation of the upper and lower turntables **34**, **36** allow for the even distribution of bulk goods in the transportable container **20**.

The packaging system **26** comprises a conventional stretch wrapping device **38** such as, for example, a Lantech Q series semi-automatic wrapper. The stretch wrapping device **38** further includes a wrap head having a roll of outer wrap secured on a wrap head base. In the preferred embodiment, the outer wrap is a stretch wrap **40** having a high cling factor and a width between 10 and 30 inches, but the stretch wrap **40** may be any of a variety of stretch wrap **40** films known in the art. The stretch wrap **40** may have a high coefficient of friction, which may lead to delaminating problems. Delaminating may be reduced by applying a glue between layers of stretch wrap **40**, welding the stretch wrap **40** layers or any other method of reducing delaminating known in the art. Welding the stretch wrap **40** may include, but is not limited to, heat or sonic welding.

When the upper turntable **34** and lower turntable **36** are rotatable, the wrap head is vertically moveable along a guide

rod **42** that runs parallel to the support column **32**, and is moved up and down the guide rod **42** by a motor. As the transportable container **20** rotates between the upper turntable **34** and lower turntable **36**, stretch wrap **40** is pulled from the wrap head to create the transportable container **20**. When the upper turntable **34** and lower turntable **36** are stationary the wrap head is rotatable about the stationary transportable container **20** in addition to being vertically moveable along the guide rod **42** to apply the stretch wrap **40** and create the transportable container **20**.

The stretch wrap **40** generates hoop forces which apply a gentle squeeze to the bulk goods, helping to stabilize the bulk goods. The hoop forces stabilize the bulk goods by promoting controllable contact between the elements of the bulk goods being loaded into the transportable container **20** of the transportable container **20**, thereby promoting bridging between the components of the bulk goods. For example, when the bulk goods being loaded are a bulk cereal in puff or flake form, hoop forces promote bridging between cereal pieces, thereby reducing the relative motion between the pieces and immobilizing the cereal within the transportable container **20**. By adjusting the extent to which the outer wrap is applied to the transportable container **20**, hoop forces can be tailored to the type of bulk goods being inserted in the transportable container **20**. Hoop forces allow for a very compact and rigid transportable container **20**, which does not allow the bulk goods to shift or get crushed within the transportable container **20**.

The transportable container **20** includes a bottom support **72** that is placed on the frame base **30**. The bottom support **72** includes, but is not limited to a transporter base **22**, slip sheet **52**, pallet **54** or any other bottom support **72** known in the art. The slip sheet **52** is typically a folded sheet of cardboard, but may be any other material known in the art, including but not limited to plastic. The pallet **54** may be wood, plastic or any other material known in the art. Typically, the pallet **54** and the slip sheet **52** are used together.

In the preferred embodiment, a transporter base **22** is used and begins the initial forming of the transportable container **20**. The transporter base **22** is made of molded plastic, but may be manufactured by any process known in the art and made of any other material known in the art. In an exemplary embodiment, as shown in FIGS. **3** and **4**, the transporter base **22** is round, but the transporter base **22** may be square or any other shape known in the art. A round transporter base **22** is utilized to produce a round transportable container **20** while a square transporter base **22** is utilized to produce a square transportable container **20**. The square transporter base **22**, which results in a square transportable container **20**, is the preferred shape. The square transportable container **20** allows for the greatest amount of space to be utilized when a plurality of transportable containers **20** are placed next to one another in a shipping truck. The round transporter base **22**, which results in a round transportable container **20**, will lead to a void or wasted space being present when the round transportable containers **20** are placed next to one another in a shipping truck.

The transporter base **22** initially forms the bulk goods or particulates disposed in the transportable container **20** and further allows for the transportation of the transportable container **20**. The transporter base **22** includes a bottom **44** and a wall **46** extending peripherally from the bottom **44** to a wall end **48**. A plurality of ears extend radially outward from the wall end **48**. In the exemplary embodiment, the bottom **44** of the round transporter base **22** has a diameter of 48 inches and the wall **46** has a height of 8 inches. These

dimensions are the preferred dimensions, but the base diameter and wall 46 height may be adjusted. The wall 46 assists in the initial shaping of the transportable container 20.

The transporter base 22 includes at least one pair of recesses 50 that extend upwardly from the bottom 44 of the transporter base 22 so that the tines of a transporting device can pickup and move the transportable container 20 of bulks goods. The transporter base 22 may further include a plurality of inwardly extending notches so the bulk goods will not conform directly to the inner surface of the transporter base 22, which may be problematic in removing the bulk goods from the transporter base 22.

The subject invention includes a slip frame former 24 to shape and form the transportable container 20. The slip frame former 24 may be round, square or any other shape known in the art. The shape of the slip frame former 24 is chosen based on the desired shape of the transportable container 20. The shape of the transportable container 20 is determined by the shape of the slip frame former 24. For example, a round slip frame former 24 will produce a round transportable container 20 while a square slip frame former 24 will produce a square transportable container 20.

In the exemplary embodiment, the slip frame former 24 includes at least one former wall 56 having an outer surface that defines a frame opening 78. The former walls 56 are from about 6 to 15 inches in height and may be made from metal, plastic, or any other material known in the art. The former walls 56 are configured such that the frame opening 78 is the desired shape in which the transportable container 20 will be formed into. For example, when a square shaped transportable base is desired, the slip frame former 24 includes former walls 56 that are secured to one another to define the square shaped frame opening 78. When a circular shaped transportable base is desired, the slip frame former 24 includes a continuous former wall 56 that is shaped to define a circular shaped frame opening 78. In the exemplary embodiment, the former walls 56 have a continuous outer surface that extends from the bottom 44 of the slip frame former 24 to the top of the slip frame former 24. When the slip frame former 24 is used in addition to the transporter base 22, the slip frame former 24 will typically be the same shape as the transporter base 22 so as to hold the desired shape of the transporter base 22. The slip frame former 24 may be a solid shape having former walls 56 or consist of a former base 58 having former arms 60 extending downwardly from the former base 58. In some embodiments, the slip frame former includes four former walls defining the frame opening. In other embodiments, the four former walls define a monolithic structure.

The method of producing a transportable container 20 for flowable bulk goods begins by vertically spacing a slip frame former 24 from a bottom support 72. A first portion of outer wrap is disposed around the bottom support 72 and a portion of the at least one former wall 56 to initially form the transportable container 20. The transportable container 20 is initially formed prior to the addition of the plurality of bulk goods into the transportable container 20. The plurality of bulk goods are then fed into the transportable container 20 through a frame opening 78 defined by the slip frame former 24 to establish a fill level 62. At least one of the slip frame former 24 and the bottom support 72 moves vertically relative to other of the slip frame former 24 and the bottom support 72 in response to the fill level 62 of the bulk goods as determined by the fill sensor 76. During filling, the slip frame former 24 is maintained at a position to surround the fill level 62 of the bulk goods in the transportable container 20. As the fill level 62 increases in the transportable con-

tainer 20, previously disposed portions of outer wrap are disengaged from the slip frame former 24 to squeeze the filled portions of the transportable container 20 and lock together the bulk goods disposed in the transportable container 20. Additional portions of outer wrap are disposed around a portion of the at least one wall 46 of the slip frame former 24 to maintain the transportable container 20 for receiving bulk goods as the previously disposed portions of stretch wrap 40 are disengaged from the at least one wall 46 of the slip frame former 24.

In the exemplary embodiment, the outer wrap is a stretch wrap 40 that is disposed from a wrap head. The stretch wrap 40 is disposed spirally about the bottom support 72 and a portion of the at least one former wall 56 of the slip frame former 24 to initially form the transportable container 20. Additional portions of stretch wrap 40 are spirally disposed about a portion of the at least one wall 46 of the slip frame former 24 to maintain the transportable container 20 for receiving bulk goods as previously disposed portions of outer wrap disengage the at least one wall 46 of the slip frame former 24.

In an exemplary embodiment, the slip frame former 24 is moved vertically upwardly relative to the stationary bottom support 72 in response to the fill level 62 of the bulk goods in the transportable container 20. The slip frame former 24 is maintained in a position to surround the fill level 62 of the bulk goods in the transportable container 20. The slip frame former 24 is secured to the upper support 28. With the slip frame former 24 in a lowered position, the stretch wrap 40 from the stretch wrapping device 38 is wrapped around the bottom support 72 and the slip frame former 24 to initially form the transportable container 20. The slip frame former 24 moves upwardly with upper support 28 as a fill level 62 of bulk goods moves upwardly during filling of the transportable container 20. The slip frame former 24 moves relative to the bottom support 72 to disengage the previously disposed portions of the stretch wrap 40 from the slip frame former 24 as the level of bulk goods rises in the transportable container 20. The system can be adjusted to provide overlapping layers of outer wrap spaced apart from 0.5 to 15 inches. The stretch wrap 40 that is used to secure the transportable container 20 overlaps the slip frame former 24 so as to maintain the shape of the slip frame former 24. The slip frame former 24 may include a Teflon coating or dimpled surface, particularly on the corners of the former walls 56 or the downwardly extending former arms 60. The Teflon coating allows for the slip frame former 24 to be easily pulled away from the stretch wrap 40 as the slip frame former 24 moves in response the level of bulk goods.

In an alternative embodiment, the bottom support 72 is moved vertically downwardly relative to the stationary slip frame former 24 in response to the fill level 62 of the bulk goods in the transportable container 20. The slip frame former 24 is maintained in a position to surround the fill level 62 of the bulk goods in the transportable container 20. The lower turntable 36 and frame base 30 may vertically movable. With the slip frame former 24 in a lowered position, the stretch wrap 40 from the stretch wrapping device 38 is wrapped around the bottom support 72 and the slip frame former 24 to initially form the transportable container 20. As the transportable container 20 disposed on the frame base 30 is filled, the frame base 30 is moved in a downward direction to accommodate additional bulk goods in the transportable container 20. Movement of the lower turntable 36 can be accomplished by any of a variety of mechanisms including scissors platform legs, hydraulic pistons, pneumatic pistons, or a geared mechanism. The slip

frame former 24 moves relative to the bottom support 72 to disengage the previously disposed portions of the stretch wrap 40 from the slip frame former 24 as the level of bulk goods rises in the transportable container 20. Again, the slip frame former 24 may include a Teflon coating to allow the stretch wrap 40 to be easily pulled away from the slip frame former 24 as the frame base 30 and stretch wrapping device 38 move downwardly from the slip frame former 24.

The method forms a transportable container 20 for flowable bulk goods having a bottom support 72 and stretch wrap 40 spirally wrapped around the bottom support 72. The stretch wrap 40 extends vertically from the bottom support 72 to form the transportable container 20. The transportable container 20 includes a plurality of flowable bulk goods that are disposed within the stretch wrap 40. The stretch wrap 40 contacts at least a portion of the plurality of bulk goods to squeeze and lock together the plurality of bulk goods disposed in the transportable container 20. No bag 68 is needed between the bulk goods and outer wrap.

In an alternative embodiment as seen in FIG. 3, the former walls 56 of the slip frame former 24 may move radially inward and outward as the slip frame former 24 moves upwardly with upper support 28. The radial position of the at least one former wall 56 is adjusted radially to modify the shape of the transportable container 20. The radial movement of the former walls 56 of the slip frame former 24 may be controlled by hydraulic pistons, pneumatic pistons, a geared mechanism or any other method known in the art. In the exemplary embodiment, slip frame former 24 is segmented or made of fingers or rods. Each segment is movable independently or on a linkage such that when a command is received to move the slip frame former 24 radially inward or outward, the segments move in two directions, thus enabling the sides to move closer together or farther apart. This motion is controlled based on the particular shape desired. The radial movement of the slip frame former 24 results in the transportable container 20 having a shape that varies radially in vertical relationship to the bottom support 72. For example, the shape of the transportable container 20 could be hour glass shaped as shown in FIG. 6, tapered as shown in FIG. 7, pumpkin shaped as shown in FIG. 8 or any other desired shape known in the art. In addition, the radial movement of the slip frame former 24, as the fill level 62 of bulk goods rises, provides the benefit of increasing the effective hoop force on the bulk goods that are more difficult to lock up, resulting in a transportable container 20 having a corrugated shape in vertical relationship to the bottom support 72.

In an alternative embodiment as shown in FIG. 9, the outer wrap is a stretch tube or stretch bag 68. The stretch bag 68 may be used in place of the stretch wrapping device 38 to form the transportable container 20. A predetermined length of the stretch bag 68 is released with respect to the transportable container 20. During the filling process, the predetermined length of the stretch bag 68 can be selected based on the filling rate. For example, a greater length of the stretch bag 68 can be released in response to a high fill rate. Alternatively, the length can be selected based on the density of the material. For example, a greater length of the stretch bag 68 can be released in response to a higher density fill material. The stretch bag 68 can be incrementally released from the bunched orientation or continuously released.

The slip frame former 24 is initially disposed adjacent the bottom support 72. A first portion of the radially flexible stretch bag 68 is disposed around the bottom support 72 and a portion of the slip frame former 24 to initially form the transportable container 20.

The transportable container 20 is then filled with a plurality of bulk goods through an opening in the stretch bag 68. The opening of the radially flexible stretch bag 68 is reduced to a smaller fill diameter substantially at the slip frame former 24 as the fill level 62 rises during filling of the transportable container 20. As discussed above, the slip frame former 24 may include a Teflon coating or dimpled surface, particularly on the corners of the former walls 56 or the downwardly extending arms. The Teflon coating allows for the slip frame former 24 to be easily pulled away from the stretch bag 68 as the slip frame former 24 moves upwardly in response to the level of bulk goods. The large diameter is reduced by radially stretching the stretch bag 68 prior to filling and, after filling substantially to the fill level 62, releasing a stretched portion of the transportable container 20 substantially adjacent the slip frame former 24. In other words, the transportable container 20 can be expanded to define the opening for receiving bulk goods. The packaging system 26 can include a stretching device 90 to radially stretch the stretch bag 68 prior to filling. The stretch bag 68 may be formed from any food grade material, such as for example, low density polyethylene, high density polyethylene, a food grade polymer, or nylon.

The slip frame former 24 moves relative to the bottom support 72 to disengage the previously disposed portions of the stretch bag 68 from the slip frame former 24 as the level of bulk goods rises in the transportable container 20. Additional portions of the stretch bag 68 are disposed around a portion of the slip frame former 24 to maintain the transportable container 20 for receiving bulk goods as previously disposed portions of the stretch bag 68 disengage the slip frame former 24.

The reduction of the stretch bag 68 at the slip frame former 24 by releasing a stretched portion of the stretch bag 68 at the fill level 62 generates hoop forces which apply a gentle squeeze to the bulk goods, helping to support and firm it. The hoop forces stabilize the bulk goods by promoting controllable contact between the elements of the bulk goods being loaded into the stretch bag 68, thereby promoting bridging between the components of the bulk goods. For example, when the bulk goods being loaded are a bulk cereal in puff or flake form, hoop forces promote bridging between cereal pieces, thereby reducing the relative motion between the pieces and immobilizing the cereal within the stretch bag 68. By adjusting the extent of shrinkage, hoop forces can be tailored to the type of bulk goods being inserted in the transportable container 20. Hoop forces allow for a very compact and rigid transportable container 20, which does not allow the bulk goods to shift or get crushed within the transportable container 20.

In an alternative embodiment as shown in FIG. 10, the outer wrap is a heat shrink film 70. The heat shrink film 70 may be used in place of the stretch wrapping device 38 or stretch bag 68 to initially form the transportable container 20. The slip frame former 24 is disposed adjacent the bottom support 72. A first portion of the heat shrink film 70 is disposed around the bottom support 72 and a portion of the slip frame former 24 to initially form a transportable container 20.

The transportable container 20 is filled with a plurality of bulk goods through an opening in the heat shrink film 70. The opening of the radially flexible heat shrink film 70 is reduced to a smaller fill diameter substantially at the slip frame former 24 as the fill level 62 rises during filling of the flexible heat shrink film 70. As discussed above, the slip frame former 24 may include a Teflon coating or dimpled surface, particularly on the corners of the former walls 56 or

the downwardly extending arms. The Teflon coating allows for the slip frame former 24 to be easily pulled away from the heat shrink film 70 as the slip frame former 24 moves upwardly in response to the level of bulk goods. The large diameter is reduced by shrinking the heat shrink film 70 5 prior to filling and, after filling substantially to the fill level 62, shrinking a portion of the heat shrink film 70 substantially adjacent the slip frame former 24. In other words, the transportable container 20 can be expanded to define the opening for receiving bulk goods. The packaging system 26 10 provided by the invention includes a shrinking device to shrink the large diameter. The shrinking device can include a heater 92 to direct heat at transportable container 20 adjacent the slip frame former 24 to shrink the large diameter to the fill diameter. Preferably, the shrinking device is 15 kept within plus or minus twelve inches of the fill level 62.

The slip frame former 24 moves relative to the bottom support 72 to disengage the previously disposed portions of the heat shrink film 70 from the slip frame former 24 as the level of bulk goods rises in the transportable container 20. 20 Additional portions of the heat shrink film 70 are disposed around a portion of the slip frame former 24 to maintain the transportable container 20 for receiving bulk goods as previously disposed portions of the heat shrink film 70 disengage the slip frame former 24.

The reduction of the heat shrink film 70 at the slip frame former 24 by shrinking the heat shrink film 70 to form the transportable container 20 at the fill level 62 generates hoop forces which apply a gentle squeeze to the bulk goods, helping to support and firm it. The hoop forces stabilize the bulk goods by promoting controllable contact between the elements of the bulk goods being loaded into transportable container 20, thereby promoting bridging between the components of the bulk goods. For example, when the bulk goods being loaded are a bulk cereal in puff or flake form, hoop forces promote bridging between cereal pieces, thereby reducing the relative motion between the pieces and immobilizing the cereal within the transportable container 20. By adjusting the extent of shrinkage, hoop forces can be tailored to the type of bulk goods being inserted in the transportable container 20. Hoop forces allow for a very compact and rigid container, which does not allow the bulk goods to shift or get crushed within the transportable container 20.

The transportable container 20 can be closed or left open depending on bulk goods. For example, certain bulk goods such as wood chips, sand, gravel, and other bulk goods, may not require that transportable container 20 be closed. In such instances, the stretch wrap 40 stretch bag 68 or heat shrink film 70 would be applied around the bulk goods in an upward direction to secure bulk goods and create the transportable container 20. Alternatively, the transportable container 20 may be closed in any of a variety of manners known in the art including, but not limited to: sonic or heat welding of the top of the transportable container 20, closure of the top of the transportable container 20 with a plastic pull tie, closure of the top of the transportable container 20 with wire or rope, closure of the top of the transportable container 20 with a clamp, and other closure means known in the art.

The subject invention may further include a second stretch wrapping device 64 for closing the transportable container 20. The second stretch wrapping device 64 includes a wrap head having a roll of secondary wrap 66 secured on a wrap head base. The secondary wrap 66 is preferably a heat sealable polyethylene or other flexible poly or plastic film, but the secondary wrap 66 may be any of a variety of secondary wrap 66 films known in the art. When

the fill level 62 has reached its desired level, the slip frame former 24 is pulled away from the transportable container 20 and the secondary wrap 66 is applied to transportable container 20. The secondary wrap 66 extends upwardly from the transportable container 20 and can be used to create a top flap. The top flap is folded over and stretch wrap 40 is applied over the folded top flap to seal the transportable container 20. In addition, the secondary wrap 66 may be welded or heat sealed. A heater (not shown) can be used to direct heat at excess material of secondary wrap 66 at the top of the transportable container 20 to seal the transportable container 20. Additionally, a heater can be used to direct heat at excess material of stretch wrap 40, secondary wrap 66, stretch bag 68 or heat shrink film 70 at the top of the transportable container 20 to seal the transportable container 20.

Further, the transportable container 20 may be closed by placing a top support 80 upon the filled transportable container 20. The top support 80 is vertically spaced from the bottom support 72 and wrapped within the stretch wrap 40 to form a cover or top for the transportable container 20. The top support 80 may be a transporter base 22 as seen in FIG. 4, a slip sheet 52 as seen in FIG. 5, or a flat sheet of cardboard or plastic on the top of the transportable container 20. After placement of the transporter base 22, slip sheet 52 or flat sheet on the top of the transportable container 20, the transportable container 20 is wrapped with additional stretch wrap 40 to secure the transporter base 22, slip sheet 52 or flat sheet on the top of the transportable container 20.

The system preferably includes a control panel to permit an operator to control various functions such as stop, start, rotation speed and wrap head movement speed. Such controls are known in the art. The system further includes controls to maintain proper fill level 62, outer wrap force and sequencing. The relationship of these parameters is constantly monitored and automatically adjusted by means known in the art.

The foregoing invention has been described in accordance with the relevant legal standards, thus the description is exemplary rather than limiting in nature. Variations and modifications to the disclosed embodiment may become apparent to those skilled in the art and do come within the scope of the invention. Accordingly, the scope of legal protection afforded this invention can only be determined by studying the following claims.

What is claimed is:

1. A system for producing a transportable container for flowable bulk goods, the system comprising:
 - a slip frame former having at least one former wall defining a frame opening;
 - a bottom support vertically spaced from the slip frame former, the bottom support having a bottom and a wall extending peripherally from the bottom to a wall end; wherein the at least one former wall and the wall of the bottom support are in engagement with a first portion of outer wrap to form a portion of the transportable container;
 - wherein at least one of the slip frame former and the bottom support is vertically moveable relative to the other of the slip frame former and the bottom support to maintain a position of the slip frame former relative to a fill level of bulk goods in the transportable container;
 - wherein the slip frame former is configured to disengage previously received portions of outer wrap therefrom to squeeze filled portions of the transportable container and lock together the flowable bulk goods disposed in

11

the transportable container as the at least one of the slip frame former and the bottom support moves relative to the other of the slip frame former and the bottom support; and

wherein a portion of the at least one former wall is configured to receive additional portions of outer wrap to maintain the transportable container and continue to form the transportable container as previously disposed portions of outer wrap disengage the at least one former wall.

2. The system as set forth in claim 1, further comprising a first wrap head operable to spirally apply the first portion of outer wrap about the wall of the bottom support and the portion of the at least one former wall to initially form the transportable container, and wherein the first wrap head is operable to spirally apply the additional portions of outer wrap about the portion of the at least one former wall to maintain the transportable container as previously disposed portions of outer wrap disengage the at least one former wall.

3. The system as set forth in claim 2, further comprising a second wrap head operable to apply a secondary wrap defining a top flap of the transportable container.

4. The system as set forth in claim 1, wherein the outer wrap includes a stretch bag, the system further comprising a stretching device to radially stretch the stretch bag prior to filling the transportable container.

5. The system as set forth in claim 1, wherein the outer wrap includes a heat shrink film, the system further comprising a shrinking device including a heater to direct heat at the heat shrink film adjacent the slip frame former to shrink the heat shrink film from a large diameter to a smaller fill diameter.

6. The system as set forth in claim 1, wherein the at least one former wall includes four former walls defining the frame opening.

7. The system as set forth in claim 6, wherein the four former walls define a monolithic construct.

8. The system as set forth in claim 1, wherein the frame opening is configured to receive the flowable bulk goods therethrough.

9. The system as set forth in claim 1, further comprising an upper support, a frame base, and a support column extending between the upper support and the frame base, wherein the slip frame former is disposed between the upper support and the frame base.

10. The system as set forth in claim 9, wherein at least one of the upper support and the frame base is vertically moveable along the support column.

12

11. The system as set forth in claim 10, wherein the slip frame former is vertically moveable with the upper support.

12. The system as set forth in claim 10, wherein the slip frame former is secured to the upper support.

13. The system as set forth in claim 1, wherein a position of the at least one former wall is radially adjustable as the at least one of the slip frame former and the bottom support moves relative to the other of the slip frame former and the bottom support to modify a shape of the transportable container.

14. The system as set forth in claim 1, wherein the bottom support includes a transporter base or slip sheet.

15. The system as set forth in claim 1, wherein the bottom and the wall of the bottom support define a volume for containing a portion of the flowable bulk goods.

16. A system for producing a transportable container for flowable bulk goods, the system comprising:

a slip frame former having at least one former wall defining a frame opening;

a bottom support vertically spaced from the slip frame former;

wherein the at least one former wall and the bottom support are configured to receive a first portion of outer wrap to form a portion of the transportable container; wherein at least one of the slip frame former and the bottom support is vertically moveable relative to the other of the slip frame former and the bottom support to maintain a position of the slip frame former relative to a fill level of bulk goods in the transportable container;

wherein the slip frame former is configured to disengage previously received portions of outer wrap therefrom to squeeze filled portions of the transportable container and lock together the flowable bulk goods disposed in the transportable container as the at least one of the slip frame former and the bottom support moves relative to the other of the slip frame former and the bottom support;

wherein a portion of the at least one former wall is configured to receive additional portions of outer wrap to maintain the transportable container and continue to form the transportable container as previously disposed portions of outer wrap disengage the at least one former wall; and

wherein a position of the at least one former wall is radially adjustable as the at least one of the slip frame former and the bottom support moves relative to the other of the slip frame former and the bottom support to modify a shape of the transportable container.

* * * * *