

US010662087B2

(12) **United States Patent**
Rigby

(10) **Patent No.:** **US 10,662,087 B2**
(45) **Date of Patent:** **May 26, 2020**

(54) **ELECTROCHEMICAL SYSTEM AND METHOD FOR THE TREATMENT OF WATER AND WASTEWATER**

(71) Applicant: **David J. Rigby**, Fairfax, VA (US)

(72) Inventor: **David J. Rigby**, Fairfax, VA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 304 days.

(21) Appl. No.: **15/626,873**

(22) Filed: **Jun. 19, 2017**

(65) **Prior Publication Data**

US 2017/0283283 A1 Oct. 5, 2017

Related U.S. Application Data

(60) Division of application No. 13/800,903, filed on Mar. 13, 2013, now Pat. No. 9,682,875, which is a (Continued)

(51) **Int. Cl.**
C02F 1/46 (2006.01)
C02F 1/461 (2006.01)

(52) **U.S. Cl.**
CPC **C02F 1/46104** (2013.01); **C02F 1/4602** (2013.01); **C02F 1/46109** (2013.01); **C02F 2001/46119** (2013.01); **C02F 2001/46152** (2013.01); **C02F 2201/008** (2013.01); **C02F 2201/4611** (2013.01);

(Continued)

(58) **Field of Classification Search**
CPC C02F 1/4602; C02F 1/46114; C02F 2001/46119; C02F 2001/46152; C02F 2201/46105; C02F 2201/4611; C02F 2201/4613; C02F 2201/4617;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,032,426 A 6/1977 de Nora et al.
4,872,959 A 10/1989 Herbst et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 201247460 U * 3/2008 C02F 1/4602
JP 09029259 A 2/1997

(Continued)

OTHER PUBLICATIONS

CN201247460U Translation, Mar. 2008 (Year: 2008).*

(Continued)


Primary Examiner — Cameron J Allen

(74) *Attorney, Agent, or Firm* — Carlos R. Villamar; The Villamar Firm PLLC

(57) **ABSTRACT**

Contaminants are removed from untreated raw water or discharge water by applying direct current through an array of spaced, alternately charged electrodes positioned within and electrically isolated from a housing to eliminate or minimize clogging of the electrodes with precipitated contaminants. The housing is surrounded with container structure that cooperates with the housing to define an inlet chamber positioned between the source of untreated water and the housing containing the spaced array of electrodes. The container structure further includes an outlet chamber defined between the housing and the container structure for accumulating and draining water treated by the spaced electrode array.

25 Claims, 13 Drawing Sheets



Related U.S. Application Data

continuation-in-part of application No. 12/492,367, filed on Jun. 26, 2009, now Pat. No. 8,460,520.

(60) Provisional application No. 61/725,861, filed on Nov. 13, 2012, provisional application No. 61/610,053, filed on Mar. 13, 2012, provisional application No. 61/075,842, filed on Jun. 26, 2008.

(52) **U.S. Cl.**
CPC C02F 2201/4613 (2013.01); C02F 2201/4617 (2013.01); C02F 2201/46105 (2013.01); Y02W 10/37 (2015.05)

(58) **Field of Classification Search**
CPC C02F 2201/008; C02F 1/46; C02F 1/72; C02F 1/76; Y02W 10/37
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,034,110	A	7/1991	Glore et al.	
5,271,814	A	12/1993	Metzler	
5,364,512	A	11/1994	Earl	
6,309,532	B1	10/2001	Tran et al.	
6,663,783	B2	4/2003	Stephenson et al.	
6,793,801	B2	9/2004	Holland	
6,800,206	B2	10/2004	Robinson et al.	
6,860,990	B2	3/2005	Bartl et al.	
6,866,757	B2	3/2005	Gilmore	
6,960,301	B2	11/2005	Bradley	
7,018,522	B2	3/2006	Holland	
8,226,813	B2*	7/2012	Nakano	C02F 1/4602 204/228.6
8,460,520	B2	6/2013	Rigby	
2002/0043462	A1	4/2002	Ivory et al.	
2003/0106854	A1	6/2003	Robinson	
2004/0035798	A1	2/2004	Holland	
2005/0029199	A1	2/2005	Holland	
2008/0223731	A1*	9/2008	Lee	C02F 1/463 205/761
2009/0127194	A1	5/2009	Joo	
2009/0321251	A1	12/2009	Rigby	
2011/0308938	A1	12/2011	Gilmore et al.	

FOREIGN PATENT DOCUMENTS

KR	100421515	B1	3/2004
KR	100687095	B1	2/2007
WO	2008018837	A2	2/2008
WO	2008026462	A1	3/2008
WO	2011159941	A1	12/2011

OTHER PUBLICATIONS

International Search Report and Written Opinion from corresponding Application No. PCT/US2013/030936 dated May 31, 2013.
International Preliminary Report on Patentability for PCT/US2009/048812 dated Jan. 5, 2011.
English Translation Abstract for JP09029259A dated Jul. 24, 1995.
Abu-Orf, M. et al., "Electric Avenue—Pretreating solids with electric arc treatment enhances dewaterability," W, E, and T, Jul. 2000, pp. 64-68.
Adhoum, N. et al., "Decolourization and removal of phenolic compounds from olive mill wastewater by electrocoagulation," Chemical Engineering and Processing, 2004, vol. 43, No. 10, pp. 1281-1287, Abstract.
Andreev, S. et al., "Upgrading of wastewater treatment facilitates of the Mokshansk dairy plant," Vodosnabzhenie I Sanitarnaya Tekhnika, 1995, vol. 6, pp. 26-27, Abstract.

Andreev, S. et al., "Upgrading of wastewater treatment facilitates of the Mokshansk dairy plant," Vodosnabzhenie I Sanitarnaya Tekhnika, 1995, vol. 6, pp. 26-27.
Bayramoglu, M. et al., "Operating cost analysis of electrocoagulation of textile dye wastewater," Separation and Purification Technology, 2004, vol. 37, No. 2, pp. 117-125, Abstract.
Bayramoglu, M. et al., "Operating cost analysis of electrocoagulation of textile dye wastewater," Separation and Purification Technology, 2004, vol. 37, No. 2, pp. 117-125.
Beck, E. C. et al., "Electroagulation clarifies food wastewater," Food Technology, 1974, vol. 28, No. 2, pp. 18-19, Abstract.
Beck, E. C. et al., "Electroagulation clarifies food wastewater," Food Technology, 1974, vol. 28, No. 2, pp. 18-19.
Bejankiwar, R. S. et al., "Electrochemical treatment of cigarette industry wastewater: feasibility study," Water Research, 2002, vol. 36, No. 17, pp. 4386-4390, Abstract.
Bejankiwar, R. S. et al., "Electrochemical treatment of cigarette industry wastewater: feasibility study," Water Research, 2002, vol. 36, pp. 4386-4390.
Bektas, N. et al., "Removal of phosphate from aqueous solutions by electro-coagulation," Journal of Hazardous Materials, 2004, vol. 106, No. 2-3, pp. 101-105, Abstract.
Bektas, N. et al., "Removal of phosphate from aqueous solutions by electro-coagulation," Journal of Hazardous Materials, 2004, vol. 106, No. 2-3, pp. 101-105.
Belov, L. P. et al., "Electroagulation treatment of wastewater of hydrolysis-yeast production," Khim. Pererab. Drev., 1983, pp. 56-60, Abstract.
Belov, L. P. et al., "Possible Improvement of an electrocoagulator," Khim. Pererab. Drev. Syr'ya, 1984, pp. 45-49, Abstract.
Belov, L. P. et al., "Possible Improvement of an electrocoagulator," Khim. Pererab. Drev. Syr'ya, 1984, pp. 45-49.
Bilyk, A., "Electrocoagulation of biologically treated wastewater," Mater. Miedzynar. Konf. Nauk, 1978, vol. 1, pp. 235-255, Abstract.
Bilyk, A., "Electrocoagulation of biologically treated wastewater," Mater. Miedzynar. Konf. Nauk, 1978, vol. 1, pp. 235-255.
Biwyk, A. et al., "Electrocoagulation of biologically treated sewage," Proceedings of the Industrial Waste Conference, 1981, vol. 35, pp. 541-549, Abstract.
Biwyk, A. et al., "Electrocoagulation of biologically treated sewage," Proceedings of the Industrial Waste Conference, 1981, vol. 35, pp. 541-549.
Buso, A. et al., "Electrochemical removal of tannins from aqueous solutions," Industrial and Engineering Chemistry Research, 2000, vol. 39, No. 2, pp. 494-499, Abstract.
Buso, A. et al., "Electrochemical removal of tannins from aqueous solutions," Industrial and Engineering Chemistry Research, 2000, vol. 39, No. 2, pp. 494-499.
Bustamante, H. A. et al., "Innovative techniques for the handling and reuse of water treatment plant sludges," Water Supply, 1995, vol. 13, pp. 233-238, Abstract.
Bustamante, H. A. et al., "Innovative techniques for the handling and reuse of water treatment plant sludges," Water Supply, 1995, vol. 13, pp. 233-238.
Carstadt, U. et al., "Conditioning of sewage sludge by electrocoagulation," ATV-Schriftenreihe, 1999, Abstract.
Chen, G. et al., "Electrocoagulation and electroflotation of restaurant wastewater," Journal of Environmental Engineering, 2000, vol. 126, No. 9, pp. 858-863, Abstract.
Chen, G. et al., "Electrocoagulation and electroflotation of restaurant wastewater," Journal of Environmental Engineering, 2000, vol. 126, No. 9, pp. 858-863.
Chen, X. et al., "Analysis of electrocoagulation energy consumption and measures of enegery saving," Shuichuli Jishu, 1997, vol. 23, No. 3, pp. 165-168, Abstract.
Chen, X. et al., "Investigation on the electrolysis voltage of electrocoagulation," Chemical Engineering Science, 2002, vol. 57, No. 13, pp. 2449-2455, Abstract.
Chowwanapoonpohn, S. et al., "Electrocoagulation of certain organic substance," ACGC Chemical Research Communications, 2002, vol. 14, pp. 70-75, Abstract.

(56)

References Cited

OTHER PUBLICATIONS

- Chowwanapoonpohn, S. et al., "Electrocoagulation of certain organic substance," ACGC Chemical Research Communications, 2002, vol. 14, pp. 70-75.
- Ciorba, G. A. et al., "Correlation between organic component and electrode material: consequences on removal of surfactants from wastewater," *Electrochimica Acta*, 2000, vol. 46, pp. 297-303.
- Daily, J. et al., "Alternatives matrix," Technical Memorandum No. 2, Jan. 5, 2007.
- Daily, J. et al., "Wastewater characterization, treatment objectives and existing system assets," Technical Memorandum No. 1, Dec. 21, 2006.
- Dalrymple, C. W. et al., "Electrocoagulation of Industrial wastewaters," Proceedings Annual Meeting—Air & Waste Management Association, 1997, Abstract.
- Dalrymple, C. W. et al., "Electrocoagulation of Industrial wastewaters," Proceedings Annual Meeting—Air & Waste Management Association, 1997.
- Donini, J. C. et al., "Electrocoagulation," *Emerging Sep. Technol. Met. Fuels, Proc. Symp.*, 1993, pp. 409-424, Abstract.
- Donini, J. C. et al., "Electrocoagulation," *Emerging Sep. Technol. Met. Fuels, Proc. Symp.*, 1993, pp. 409-424.
- Donini, J. C. et al., "The operating cost of electrocoagulation," *Canadian Journal of Chemical Engineering*, 1994, vol. 72, No. 6, pp. 1007-1012, Abstract.
- Donini, J. C. et al., "The operating cost of electrocoagulation," *Canadian Journal of Chemical Engineering*, 1994, vol. 72, No. 6, pp. 1007-1012.
- Farrell, J. M., "Electrochemical methods for wastewater and potable water treatment," 2002, vol. 42, No. 2, pp. 501-507, Abstract.
- Feng, C. et al., "Performance of Two New Electrochemical Treatment Systems for Wastewaters," *Journal of Environmental Science and Health*, 2004, Abstract.
- Feng, C. et al., "Performance of Two New Electrochemical Treatment Systems for Wastewaters," *Journal of Environmental Science and Health*, 2004.
- Feng, S. et al., "Electro-coagulation process for phosphorus removal from secondary effluent," *Zhongguo Jishul Paishui*, 2003, vol. 19, No. 1, pp. 52-54, Abstract.
- Ganin, B. A. et al., "Study of methods of treating run-off water from thickeners of fermented sludge," *Trudy-Mosvodkokanalniiproekt*, 1977, vol. 1, pp. 63-73, Abstract.
- Gega, J. et al., "Radical clarifiers and thickeners with lamella modules," *Environmental Science Research*, 1991, vol. 42, pp. 465-473, Abstract.
- Gega, J. et al., "Radical clarifiers and thickeners with lamella modules," *Environmental Science Research*, 1991, vol. 42, pp. 465-473.
- Grechko, A. V. et al., "Removal of pesticides from greenhouse drainage wastewater," *Khimiya I Tekhnologiya Vody*, 1982, vol. 4, No. 1, pp. 56-58, Abstract.
- Grechko, A. V. et al., "Removal of pesticides from greenhouse drainage wastewater," *Khimiya I Tekhnologiya Vody*, 1982, vol. 4, No. 1, pp. 56-58.
- Pouet, M. F. et al., "Electrocoagulation-flotation as pretreatment in tangential microfiltration in water treatment," *Recents Progres en Genie des Procedes*, 1991, vol. 5, No. 12, pp. 195-200, English Abstract.
- Pouet, M. F. et al., "Urban wastewater treatment by electrocoagulation and flotation," *Water Science and Technology*, 1995, vol. 31, No. 3-4, pp. 275-83, Abstract.
- Pouet, M. F. et al., "Urban wastewater treatment by electrocoagulation and flotation," *Water Science and Technology*, 1995, vol. 31, No. 3-4, pp. 275-283.
- Renk, R., "Treatment of Hazardous Wastewaters by Electrocoagulation," 1989.
- Rogov, V. M. et al., "Use of electrocoagulation-flotation in the technology of water treatment," *Elektronnaya Obrabotka Materialov*, 1978, vol. 6, pp. 80-83, Abstract.
- Rogov, V. M. et al., "Use of electrocoagulation-flotation in the technology of water treatment," *Elektronnaya Obrabotka Materialov*, 1978, vol. 6, pp. 80-83.
- Sakakibara, Y. et al., "Phosphate removal and recovery by a novel electrolytic process," *Water Science and Technology*, 2002, vol. 46, No. 11-12, pp. 147-152, Abstract.
- Sakakibara, Y. et al., "Phosphate removal and recovery by a novel electrolytic process," *Water Science and Technology*, 2002, vol. 46, No. 11-12, pp. 147-152.
- Sims, R. C. et al., "Electrocoagulation Removes Metals from Wastewater," *Tech Trends*, Sep. 1996.
- Solids Recovery From Seafood Processing Stick Water Using Electrocoagulation, Feb. 1996.
- Strokatova, S. F. et al., "Removal of protein-fat fractions from concentrated wastewater," *Khimicheskaya Promyshlennost*, 2000, vol. 11, pp. 581-583, Abstract.
- Strokatova, S. F. et al., "Removal of protein-fat fractions from concentrated wastewater," *Khimicheskaya Promyshlennost*, 2000, vol. 11, pp. 581-583.
- Tabakov, D. et al., "Influence of material of electrode system on the effect of treatment of dairy sewage by electrocoagulation and flotation," *Woda I Technika Sanitarna*, 1982, vol. 56, No. 9-10, pp. 197-198, Abstract.
- Tabakov, D. et al., "Influence of material of electrode system on the effect of treatment of dairy sewage by electrocoagulation and flotation," *Woda I Technika Sanitarna*, 1982, vol. 56, No. 9-10, pp. 197-198.
- Tabakov, D. et al., "Purification of dairy industry wastewater," *Khramitelna Promishlennost*, 1984, vol. 33, No. 7, pp. 22-23, Abstract.
- Tabakov, D. et al., "Purification of dairy industry wastewater," *Khramitelna Promishlennost*, 1984, vol. 33, No. 7, pp. 22-23.
- Tabakov, D. et al., "Treatment and utilization of wastewater from the dairy industry," *Molochnaya Promyshlennost*, 1984, vol. 11, pp. 43-45, Abstract.
- Tabakov, D. et al., "Treatment and utilization of wastewater from the dairy industry," *Molochnaya Promyshlennost*, 1984, vol. 11, pp. 43-45.
- Tamarin, S. et al., "Method and apparatus for industrial wastewater treatment," Abstract of US-5 658 450, Publication Date: Aug. 19, 1997.
- Tipton, G. et al., "New Life for an Old Process," *Heavy Metals Removal, Environmental Technology*, Jan./Feb. 1999, pp. 28-30.
- Wang, F. et al., "Treatment of wastewater from antiseptic agent production," *Shanghai Huanjing Kexue*, 1990, vol. 9, No. 10, pp. 37-38, Abstract.
- Xu, L. J. et al., "Recovery and utilization of useful by-products from egg processing wastewater by electrocoagulation," *Poultry Science*, 2002, vol. 81, No. 6, pp. 785-792, Abstract.
- Xu, L. J. et al., "Recovery and utilization of useful by-products from egg processing wastewater by electrocoagulation," *Poultry Science*, 2002, vol. 81, No. 6, pp. 785-792.
- SciFinder Scholar, Oct. 26, 2004.
- Chiou, J. et al., "Study on removing organic matter from swine wastewater by the electrocoagulation method," *Journal of the Environmental Protection Society of the Republic of China*, Jun. 1993, vol. 16, No. 1.
- Alvarado, J. H. et al., "Evaluation of Electrocoagulation Technology for the Removal of Chromium, Silver, Zinc, and Nickel," George Washington University—Civil and Environmental Engineering Department, 2003.
- Barkley, N. P. et al., "Emerging Technology Summary—Electro-Pure Alternating Current Electrocoagulation," United States Environmental Protection Agency, Sep. 1993.
- Cocke, D. L. et al., "Electrocoagulation an evolving electrochemical technology for wastewater treatment," Preprints of Extended Abstracts presented at the ACS National Meeting, American Chemical Society, Division of Environmental Chemistry, 2002, vol. 42, No. 2, pp. 501-507, Abstract.
- Cora-Hernandez et al., "Electrocoagulation/flotation (ECF) technology used in the treatment of wastewater containing variable concentrations of heavy metals and organic pollutants," *Diss. Abstr. Int.*, 2003, vol. 63, No. 12.

(56)

References Cited

OTHER PUBLICATIONS

- Current Water Technology Industrial Wastewater Treatment Equipment, Feb. 25, 2002.
- General Environmental Corporation, Cure Electrocoagulation Technology, Innovative Technology Evaluation Report, Sep. 1998.
- Gilmore, F. W. et al., "Electrocoagulation—A technical analysis," Oct. 2001.
- Louisiana Sugarcane Research, <http://www.agctr.lsu.edu/Subjects/sugarcane/clarification.asp>, Feb. 25, 2002.
- Kaselco by Kaspar, Wastewater Treatment Utilizing Electrocoagulation, <http://www.kaselco.com/>, Oct. 22, 2003.
- Matsumoto, M. R. et al., "Physicochemical Processes," Water Environment Research, 1996, vol. 68, No. 4, pp. 431-460.
- New Electrocoagulation process treats emulsified oily wastewater at Vancouver Shipyards, <http://www.esemag.com/0103/electro.html>, Jan. 2003.
- Electrocoagulation: An Innovative Waste-Water Treatment Technology, <http://www.parsenviro.com/electro.html>, Oct. 22, 2003.
- Phutdhawong, W. et al., "Electrocoagulation and subsequent recovery of phenolic compounds," Analytical Sciences, Oct. 2000, vol. 16, pp. 1083-1084.
- Powell Water Systems, Inc., "Electrocoagulation and Wastewater Treatment Systems," <http://www.powellwater.com>, Oct. 22, 2003.
- RECRA Environmental, Inc., <http://www.clu-in.org/products/site/complete/rcraenvi.htm>, Feb. 25, 2002.
- Smith, J., Clean Water, Inc., 1993.
- Specializing in the Treatment of Industrial Wastewater Using Advanced Non-Chemical Wastewater Treatment Technology, Advanced Scientific Water Systems, Feb. 25, 2002.
- The Stormwater Management Electrocoagulation System, 2002.
- Vorontsova, L. V. et al., "Removal of fine mineral particles from wastewaters," 2002.
- Ionic Electrocoagulation for cleanup of Heavy Metals, Hexavalent Chrome, etc., <http://www.wee-engineer.com/ionic.htm>, Feb. 25, 2002.
- Wmrc Factsheet, Electrocoagulation Technology Ace Plating, Part II, Dec. 2001.
- Greene, H. W., "Waste Water Treatment by Electric Arc," Scientific Utilization Inc., Aug. 10, 1994.
- Groeterud, O. et al., "Phosphorus removal from water by means of electrolysis," Water Research, 1986, vol. 20, No. 5, pp. 667-669, Abstract.
- Groeterud, O. et al., "Phosphorus removal from water by means of electrolysis," Water Research, 1986, vol. 20, No. 5, pp. 667-669.
- Haba, A. et al., "Research on a possibility of using electroflotation process for waste treatment from fish proceedings," Environment Protection Engineering, 1994, vol. 18, No. 3-4, pp. 19-27, Abstract.
- Haba, a. et al., "Research on a possibility of using electroflotation process for waste treatment from fish proceedings," Environment Protection Engineering, 1994, vol. 18, No. 3-4, pp. 19-27.
- Ibanez, J. G. et al., "Laboratory Experiments on electrochemical remediation of the environment: electrocoagulation of oily wastewater," Journal of Chemical Education, 1995, vol. 72, No. 11, pp. 1050-1052, Abstract.
- Ibanez, J. G. et al., "Laboratory Experiments on electrochemical remediation of the environment: electrocoagulation of oily wastewater," Journal of Chemical Education, 1995, vol. 72, No. 11, pp. 1050-1052.
- Inan, H. et al., "Olive oil mill wastewater treatment by means of electro-coagulation," Separation and Purification Technology, 2004, vol. 36, No. 1, pp. 23-31, Abstract.
- Inan, H. et al., "Olive oil mill wastewater treatment by means of electro-coagulation," Separation and Purification Technology, 2004, vol. 36, No. 1, pp. 23-31.
- Ionenko, V. I. et al., "Mathematical modeling of electrocoagulation," *Gidrotekh. Sooruzhenii Inzh. Gidrogeol.* 1973, vol. 40, No. 1, pp. 103-107, Abstract.
- Jaouani, A. et al., "Proposal of a treatment flowchart for the olive oil mill wastewaters," Universiteit Gent, 2000, vol. 65, No. 3a, pp. 111-113, Abstract.
- Jaouani, A. et al., "Proposal of a treatment flowchart for the olive oil mill wastewaters," Universiteit Gent, 2000, vol. 65, No. 3a, pp. 111-113.
- Joffe, L. et al., "Electrocoagulation," Industrial Wastewater, 2000, Abstract.
- Joffe, L. et al., "Electrocoagulation," Industrial Wastewater, 2000.
- Karpuzcu, M. et al., "Purification of agro-industrial wastewater from the grease-protein mixture by means of electroflotocoagulation," Water Science and Technology, 2002, vol. 45, No. 12, pp. 233-240, Abstract.
- Karpuzcu, M. et al., "Purification of agro-industrial wastewater from the grease-protein mixture by means of electroflotocoagulation," Water Science and Technology, 2002, vol. 45, No. 12, pp. 233-240.
- Khristoskova, S. et al., "Possibility of purification and decoloring wastewaters from the yeast industry by electrocoagulation," Nauchni Trudove—Plovdivski Universitet Paisil Khilendarski, 1984, Abstract.
- Khristova, S. et al., "Study of the possibility of treating and decolorizing yeast production wastewater by electrocoagulation," Tseluloza I Khartiya, 1984, vol. 15, No. 6, pp. 24-25, Abstract.
- Khristova, S. et al., "Study of the possibility of treating and decolorizing yeast production wastewater by electrocoagulation," Tseluloza I Khartiya, 1984, vol. 15, No. 6, pp. 24-25.
- Kozyura, A. S. et al., "Electrocoagulation of synthetic latex in waste waters," *Gidrotekhnicheskie Sooruzheniya*, 1974, vol. 17, pp. 81-84, Abstract.
- Kozyura, A. S. et al., "Electrocoagulation of synthetic latex in waste waters," *Gidrotekhnicheskie Sooruzheniya*, 1974, vol. 17, pp. 81-84.
- Lai, J. et al., "Study on removing organic matter from swine wastewater by the electrocoagulation method," Huanjing Baohu (Taipei, Taiwan), 1993, vol. 16, No. 1, pp. 18-34, Abstract.
- Matveenko, A. P. et al., "Technology of treating wastewater to remove organomineral matter suspended in concentrated aqueous solutions from wastewaters," *Zhurnal Prikladnoi khimii*, 1985, vol. 58, No. 1, pp. 122-126, Abstract.
- Matveenko, A. P. et al., "Technology of treating wastewater to remove organomineral matter suspended in concentrated aqueous solutions from wastewaters," *Zhurnal Prikladnoi khimii*, 1985, vol. 58, No. 1, pp. 122-126.
- Mejbaum, Z. et al., "Removal of emulsified oils from effluents by electrocoagulation," *Przemysl Chemiczny*, 1978, vol. 57, No. 8, pp. 407-410, Abstract.
- Mejbaum, Z. et al., "Removal of emulsified oils from effluents by electrocoagulation," *Przemysl Chemiczny*, 1978, vol. 57, No. 8, pp. 407-410.
- Merkvirt, R. K. et al., "Results of studies on electric treatment of petroleum-containing wastewaters from tankers," 1982, Abstract.
- Metzler, D. M. A. et al., "Thin film electrocoagulation for removal for containments from liquid media," Abstract of U.S. Pat. No. 5,271,814, Publication Date: Dec. 21, 1993.
- Mills, D. et al., "A new process for electrocoagulation," American Water Works Association, 2000, vol. 92, No. 6, pp. 34-43, Abstract.
- Mills, D. et al., "A new process for electrocoagulation," American Water Works Association, 2000, vol. 92, No. 6, pp. 34-43.
- Min, K. et al., "Removal of ammonium from tannery wastewater by electrochemical treatment," Journal of Environmental Science and Health, 2004, Abstract.
- Min, K. et al., "Removal of ammonium from tannery wastewater by electrochemical treatment," Journal of Environmental Science and Health, 2004.
- Mollah, M. Y. A. et al., "Electrocoagulation (EC)—Science and applications," Journal of Hazardous Materials, 2001, vol. 84, No. 1, pp. 29-41, Abstract.
- Mollah, M. Y. A. et al., "Electrocoagulation (EC)—Science and applications," Journal of Hazardous Materials, 2001, vol. 84, No. 1, pp. 29-41.
- Nanescu, V. et al., "Water cleaning and treating by electrocoagulation," *Industria Usoara*, 1984, vol. 31, No. 8, pp. 348-351, Abstract.
- Parekh, B. K. et al., "The alternating current electro-coagulation process," *Advances in Filtration and Separation Technology*, 1990, pp. 548-554, Abstract.

(56)

References Cited

OTHER PUBLICATIONS

Parekh, B. K. et al., "The alternating current electro-coagulation process," *Advances in Filtration and Separation Technology*, 1990, pp. 548-554.

Paul, A. B. et al., "Electrolytic treatment of turbid water in package plant," *Reaching the Unreached: Challenges for the 21st Century*, 1996, pp. 286-288.

Peters, R. W. et al., "Wastewater treatment—physical and chemical methods," *Journal—Water Pollution Control Federation*, 1986, vol. 58, No. 6, pp. 481-490, Abstract.

Peters, R. W. et al., "Wastewater treatment—physical and chemical methods," *Journal—Water Pollution Control Federation*, 1986, vol. 58, No. 6, pp. 481-490.

Piatrik, M. et al., "Pretreatment of wastewater from production of starch by electroflotation," *Vodni Hospodarstvi*, 1991, vol. 41, No. 9, pp. 328-330, Abstract.

Pikaev, A. K. et al., "Combined electron-beam and coagulation purification of molasses distillery slops. Features of the method, technical, and economic evaluation of large-scale facility," *Radiation Physics and Chemistry*, 2001, vol. 61, No. 1, pp. 81-87, Abstract.

Pikaev, A. K. et al., "Combined electron-beam and coagulation purification of molasses distillery slops. Features of the method, technical and economic evaluation of large-scale facility," *Radiation Physics and Chemistry*, 2001, vol. 61, pp. 81-87.

Pillay, G. et al., "Electrochemical treatment and minimization of defense-related wastes," *Proceedings—Electrochemical Society*, 2000, Abstract.

Pillay, G. et al., "Electrochemical treatment and minimization of defense-related wastes," *Proceedings—Electrochemical Society*, 2000.

Pogrebnyaya, V. L. et al., "Purification of wastewater of food factories containing proteins," *Pishchevaya Tekhnologiya*, 1994, Abstract.

Pogrebnyaya, V. L. et al., "Purification of wastewater of food factories containing proteins," *Pishchevaya Tekhnologiya*, 1994.

Polunina, E. et al., "Electrocoagulation treatment of sewage in antibiotic production," *Antibiotiki I Khimioterapiya*, 1995, vol. 40, No. 11-12, pp. 10-15, Abstract.

Polunina, E. et al., "Electrocoagulation treatment of sewage in antibiotic production," *Antibiotiki I Khimioterapiya*, 1995, vol. 40, No. 11-12, pp. 10-15.

Pouet, M. F. et al., "Couplage Electrocoagulation-Flottation: Application comme Pretraitement a la microfiltration tangentielle en traitement des eaux," *Recents Progres en Genie des Procedes*, 1991, vol. 5, No. 12, pp. 195-200.

* cited by examiner




FIG. 1




FIG. 2




FIG.3




FIG. 4




FIG. 5




FIG.6




FIG. 7




FIG. 9




FIG. 8




FIG. 10




FIG. 11A




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG.15




FIG.16

ELECTROCHEMICAL SYSTEM AND METHOD FOR THE TREATMENT OF WATER AND WASTEWATER

RELATED APPLICATIONS

This application is a divisional of U.S. patent application Ser. No. 13/800,903, filed on Mar. 13, 2013, now allowed, which claims benefit of priority to U.S. Provisional Patent Application Nos. 61/725,861, filed on Nov. 13, 2012, and 61/610,053, filed on Mar. 13, 2012, and which is a continuation-in-part of U.S. patent application Ser. No. 12/492,367, filed on Jun. 26, 2009, now U.S. Pat. No. 8,460,520, which claims benefit of priority to U.S. Provisional Patent Application No. 61/075,842, filed on Jun. 26, 2008, the entire disclosures of all of which are hereby incorporated by reference herein.

FIELD OF THE INVENTION

This invention, relates to water and wastewater treatment, and more particularly, but not limited to, treatment of surface water, groundwater, domestic sewage, industrial feed water, industrial process wastewater, hazardous and toxic wastes, liquid waste byproducts, the byproducts including, but not limited to, waste biosolids and membrane reject water, as well as but not limited to bilge water and waste water from ships.

BACKGROUND OF THE INVENTION

A variety of methods have been used to treat and remove contaminants from water and wastewater. The procedures and techniques actually used by municipal utilities for the treatment of drinking water and sanitary sewage have remained largely unchanged for at least 40 years.

Municipal drinking water treatment typically involves pumping surface (river or reservoir) water to a high energy mixing tank where alum and/or lime is added. The water then flows into a low energy mixing tank where chemically bound sediment floc is formed. From the flocculation tank the water flows into a gravity clarification tank, then on to a granular media filter and finally the water is disinfected with chlorine prior to distribution.

Municipal treatment of groundwater (wells) tends typically to involve the addition of a strong oxidant such as chlorine or potassium permanganate to oxidize a variety of dissolved pollutants such as iron, manganese, trace organics, heavy metals, radionuclides and bacteria. The chemically treated groundwater is then filtered and disinfected prior to distribution.

Municipal treatment of sanitary sewage typically includes screening to remove large solids, treatment of dissolved organics through a process generically referred to as activated sludge, gravity settling (clarification), then filtration and finally disinfection. In the past chlorine was commonly used for the disinfection of both water and wastewater, but as a result of recognition by the US EPA that byproducts of chlorine may be potentially carcinogenic, new regulations have been passed limiting the widespread use of chlorine and requiring the reduction or elimination of disinfection byproducts. Consequently, ultraviolet light has emerged as the disinfectant of choice.

Because procedures and techniques for treating water and wastewater have advanced little over the past 40 years, there is a glaring need for new methods and systems for treating

water and wastewater that is efficient, effective and reliable and which produces minimal waste byproducts (sludge).

Prior art attempts to improve systems and electrochemical treatment methods for wastewater treatment have not been satisfactory. Those reported in the literature have utilized either parallel electrified plates made of iron or aluminum as electrodes, or a single rod within a cylinder made of iron or aluminum as electrodes. In the case of the parallel plates, the electrical charge density on the plates is insufficient to properly treat the water or wastewater unless the plate spacing is minimal (less than 1/4"; 0.365 cm). This typically results in rapid plugging or clogging of the treatment unit. In the case of a single rod within a cylinder, often the spacing between the central rod and the perimeter wall is so great as to be ineffective in creating a sufficiently strong charge density to completely treat water or wastewater.

Classically, the efforts of the past have focused on the use of either parallel plates or center rods inside a tube as the positively and negatively charged electrodes. Due to the inefficiency of the plate designs, it was considered necessary to minimize plate spacings which quickly resulted in fouling of treatment units. The center rod and tube designs experienced similar problems and attempted to use high voltage potentials to overcome ineffectiveness. In one approach, using electrochemical cells in series with varying electrode materials was tried to achieve the desired treatment effectiveness. In every case, treatment technologies proved to be physically self-limiting and scaling factors (enlarging the units) became problematic. Furthermore, these approaches were typically characterized by high energy consumption as attempts to reach intended treatment levels were explored. This fact became a significant barrier to practical commercialization. Previous attempts to develop effective electrochemical technologies for treatment of water and wastewater resulted in processes that were very expensive to operate and not effective.

SUMMARY OF THE INVENTION

A system is provided for removing contaminants from raw water or waste water. The system includes at least one electrochemical treatment module comprising a housing having an inlet for untreated water and an outlet for treated water that has been treated within the housing. An array of electrodes is positioned within the housing to provide electrically conductive grills. The electrodes have spaces therebetween of a selected distance, the spaces being greater than about 0.25 inch (0.635 cm). A source is provided for applying direct current the electrodes to charge one portion of the array positively and another portion of the array negatively so as to create an electrical gradient between portions of the array, the direct current being sufficient to ionize contaminants, but not large enough to clog the spaces between electrodes with precipitated contaminants. A container structure disposed adjacent to the housing. The container structure has an inlet chamber and an outlet chamber, wherein the inlet chamber accumulates untreated water received and delivers the untreated water to the inlet of the housing. The housing has an outlet that is connected to the outlet chamber of the container and the outlet chamber has an outlet line that drains treated water from the outlet chamber.

In an aspect of the invention, the container structure has an inner wall. The housing is polygonal with at least two pairs of vertically extending corners, each of which corners engaging the inner wall to provide first and second housing

3

walls that cooperate with the inner wall of the container structure to define the inlet and outlet chambers.

In an aspect of the invention, the first housing wall defines an inlet opening at the bottom thereof and the second wall defines an outlet opening at the top thereof with the outlet opening being larger in area than the inlet opening.

In an aspect of the invention, the inlet opening extends horizontally with respect to a lower edge of the first wall of the housing and the outlet extends horizontally with respect to the second wall of the housing.

In an aspect of the invention, the inlet opening is an undercut of the first wall and the outlet opening is an overcut of the second wall.

In an aspect of the invention, the housing containing the array of electrodes is square and the container defines a cylindrical inner wall.

In an aspect of the invention, two side chambers are formed in addition to the inlet and outlet chambers.

In an aspect of the invention, the two side chambers are filled with solid foam.

In a further aspect of the invention, a plurality of cells each defined by a module within a container are arranged in parallel to treat contaminated water flowing to each of the cells through a feed line from the source of contaminated water.

In still a further aspect of the invention, the housing and the container structure are both made of dielectric material. To prevent substantial leakage of electric charge from the electrically conductive grills to the housing and container structure, an air gap is disposed between the top surface of the untreated water accumulated in the inlet chamber and the inlet line connected to the inlet line. An additional air gap occurs between the outlet of the housing and treated water accumulated in the outlet chamber.

The present invention described herein relates to systems for efficiently and effectively removing a broad range of contaminants from water and wastewater including, but not limited to, surface water, groundwater, industrial process water, sanitary sewage, industrial wastewater, water containing hazardous or toxic materials, stormwater runoff containing a variety of organic and inorganic pollutants and contaminants and fluid streams containing byproducts of conventional water treatment and waste activated sludge treatment from domestic wastewater treatment plants.

The systems described herein achieve treatment and removal of dissolved and particulate, organic and inorganic contaminants by means of a variety of treatment and removal processes. The processes include, but are not limited to, electro-coagulation, electro-flocculation, electro-flocculation, electrochemical oxidation, electrochemical reduction, electrolysis of water and other molecules, dissociation of water and other molecules and both organic and inorganic ions, production of free radicals in the aqueous solution, electrical charge neutralization, decrease of Zeta potential, electroplating, and electrical voltage potential resulting in the destruction of bacteria and viruses.

The systems described herein effectively treat, oxidize, remove or destroy a broad range of contaminants including but not limited to the following:

heavy metals such as chromium, lead, mercury, cadmium, copper and zinc,

arsenic from groundwater.

petroleum oils in the form of refinery wastes, well drilling spoils, runoff from transportation activities including truck and vehicle washing and airport fueling operations,

4

contaminants generated by marine vessels including military ships, merchant marine vessels, cruise ships and pleasure crafts, including the treatment of bilge water, fats, oils and grease (FOGs) from a variety of sources including food production facilities such as slaughtering plants, dairies, mayonnaise, vegetable oil and salad dressing plants, bakeries, fish processing plants, rendering plants, and further processing and finished product plants,

aquatic nuisance nutrients such as nitrogen in the form of nitrates and phosphates,

organic and inorganic acid wastes,

organic wastes high in biochemical oxygen demand (BOD) and high chemical oxygen demand (COD),

organic wastes with long chain and complex organic compounds,

pharmaceutical wastes,

pharmaceuticals in urine and feces,

wastes contaminated with phenolic compounds,

wastes with high concentrations of organic and inorganic suspended or colloidal solids,

wastes with high concentrations of toxic organics including cyanide,

colloidal solids, sediment and algae from surface water,

iron, manganese and nitrate from groundwater and

organics, solids, nitrogen, phosphorous and bacteria from domestic sanitary sewage,

waste water from tracking practiced in the production of natural gas and petroleum,

gray water from laundry operations both domestic and industrial,

nuclear waste and water contaminated with transuranic material and/or radon.

The systems described herein effectively achieve, but are not limited to, the following:

improvement of dewaterability of water and wastewater treatment plant sludges,

achievement of drier solids cakes during de-watering,

achievement of the condition of Class A solids,

economical reduction the amount of polymer used for chemical precipitation,

economical reduction of the amount of inorganic salts used for chemical precipitation,

effective destruction of bacteria and viruses and

achievement of "secondary" levels of treatment of raw domestic sewage,

The systems described herein effectively treat raw water or generated domestic sanitary sewage from such applications as remote oil and gas exploration camps, oil drilling rigs, military base camps and improves of drinking water and sanitary conditions in third world countries.

The systems described herein utilize electrochemical treatment with direct electrical current to an electrochemical cell consisting of specially designed parallel rods situated parallel with the direction of flow. The design of the selective electrode materials and electrode spacing includes integrating the system's operating variables into an individual design which is then applied for the removal of a specific contaminant or a combination of contaminants that are present at specific concentrations within an aqueous stream for a specific application or industry. The cells may be single or plural in parallel or series arrays.

The systems described herein take advantage of selective electrode materials which offer advantages one over the other for the removal of a specific contaminant or a combination of contaminants that may be present in an aqueous stream, or to achieve a specific byproduct chemistry based

5

on either the further intended treatment steps or the ultimate fate of the byproducts of which are to be disposed. Selective electrode materials may include, but are not limited to, iron, aluminum, titanium, carbon fiber, stainless steel or any other effective electrode material.

The systems described herein utilize specific electrode materials and configuration selection designed to achieve specific levels of treatment based on the specific contaminant or a combination of contaminants that are present at specific concentrations within the aqueous stream and the desired degree of treatment or removal. The variables which effect selective electrode material and configuration design include contaminants or the combination of contaminants to be removed, the concentrations of those contaminants, rates of flow, the pH of the aqueous streams and fluid conductivities. A resultant design is specifically developed to include selection of electrode material, electrode design configuration, electrode type, spacing between the electrodes, power to be applied and retention time in the electrochemical treatment unit selected. The resultant combination of variables results in both a specific electrical charge density or range and a specific ionic charge density or range.

SUMMARY OF THE ELECTROCHEMICAL TREATMENT METHOD

A first step of overall electrochemical treatment methods involves the capture and transfer of the water or wastewater to an electrochemical treatment unit. This step includes pumping surface water, groundwater or wastewater to the electrochemical treatment unit.

A second step in overall electrochemical treatment methods involves passing the water or wastewater through an electrochemical treatment unit described in this application. In this step direct electrical current is applied and the rate of flow is adjusted to achieve a desired level of treatment based on the concentration of the contaminant or contaminants to be removed. Hydraulic residence time within the electrochemical treatment unit is in a range of about 15 seconds to about 2 minutes, depending on the concentration of the contaminant or contaminants to be removed.

A third step in overall electrochemical treatment methods involves passing effluent from the treatment unit through either a clarifier or filter for removal of any oxidized and/or precipitated solid particles remaining in the water.

SUMMARY OF THE ELECTROCHEMICAL TREATMENT APPARATUS

Multiple pairs of small diameter rods are employed to develop a strong charge density on electrodes to achieve effective treatment. By using multiple rods with a high charge density, the electrode spacing is greater than 1/4" (0.635 cm), for example up to about one inch (2.54 cm) which allows for smooth and efficient flow through the treatment unit without a propensity of clogging.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features which are believed to be characteristic of the present invention, as to its structure, organization, use and method of operation, together with further objectives and advantages thereof, will be better understood from the following drawings in which presently preferred embodiment(s) of the invention are now illustrated by way of example. It is expressly understood, however, that the draw-

6

ings are for the purpose of illustration and description only and are not intended as a definition of the limits of the invention. Embodiments of this invention are described by way of example in association with the accompanying drawings in which:

FIG. 1 is a schematic view of an electrochemical water and wastewater treatment system in accordance with the systems, apparatus and methods of the present invention;

FIG. 2 is a side view of an electrochemical treatment cell according to an initial embodiment of the invention oriented horizontally;

FIG. 3 is a side view partially in elevation taken along lines 3-3 of FIG. 2 showing an array of electrodes within the electrochemical treatment cell;

FIG. 4 is an end view, partially in elevation, taken along lines 4-4 showing of FIG. 3 a charge distribution on the array of electrodes shown in FIG. 3;

FIG. 5 is an end view similar to FIG. 4 showing a reversed charge distribution on the array of electrodes of FIGS. 3 and 4;

FIG. 6 is a side elevational view of the electrochemical treatment cell of FIGS. 2-5 with the housing removed showing details of an arrangement for mounting the electrodes;

FIG. 7 is a side view of an electrochemical treatment cell similar to that of FIG. 2 but oriented vertically;

FIG. 8 is a perspective, exploded view of a second embodiment of an electrochemical treatment cell, according to the invention, shown partially in section;

FIG. 9 is a top view of the treatment cell of FIG. 8;

FIG. 10 is a side elevation of the electrochemical cell of FIG. 9, taken along lines 10-10;

FIG. 11 is a perspective view of an electrode rod sheet used with the electrochemical treatment cell of FIGS. 8-10;

FIG. 11A is a front view of another embodiment of the electrode sheet of FIG. 11;

FIG. 12 is an enlarged view of a connector used with the electro rod sheet of FIG. 11;

FIG. 13 is a perspective view, partially in section, of a reaction chamber formed of the electrochemical cell of FIGS. 8-12 inserted into a container;

FIG. 14 is a top view of the reaction chamber of FIG. 13;

FIG. 15 is a side elevation of the reaction chamber taken along lines 15-15 of FIG. 14, and


FIG. 16 is a schematic view of a plurality of reaction chamber cells arranged in parallel to treat a source of untreated water.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

A variety of organic and inorganic contaminants in water or wastewater are capable of undergoing direct electrochemical oxidation or reduction without the involvement of other substances or catalysts, except for the possible release of electrode material. A general understanding of this phenomenon is available from the following considerations of chemical equations and unbalanced portions of chemical equations.



60 Electrolysis of Water

In addition to organic and inorganic contaminants, water itself is also capable of undergoing electrochemical transformation including electrolysis and dissociation as follows:




The reaction at the cathode results in the production of both hydrogen gas and an abundance of free hydroxyl radicals. Conveniently, the hydrogen gas becomes useful for the ultimate flotation of and separation of precipitated chemical flocs, suspended and colloidal solids and fats, oils and grease from the aqueous solution. Conveniently, the free hydroxyl radicals serve as reducing agents for removal of such contaminants as heavy metals and to raise the pH of the water. This reaction is below to be helpful for:

Precipitation of Phosphorous
 Precipitation of Heavy Metals
 Oxidation of Nitrate and Nitrogen Compounds
 Bacterial Kill
 Oxidation of Iron







Oxidation of Organic Compounds (General)

Electrochemical oxidation of organic compounds occurs within an electrochemical cell when sufficient electrical potential differences (voltage) are applied to the anode and cathode electrodes. Due to the fact that organic compounds usually contain one of more high strength ionic and covalent bonds their oxidation proceeds simultaneously with the production of O₂ from the electrochemical oxidation of H₂O. The following formula provide a generic form of oxidation of organic compounds.




Oxidation of Arsenic

Arsenic in groundwater is usually in the form of arsenite (As⁻³). In the electrochemical cell fitted with iron electrodes the arsenite undergoes oxidation to arsenate (As⁻⁵). In addition the iron released from the anodes combines with the arsenate to form the insoluble precipitate ferric arsenate as follows.




Carbonates

Two major contaminants which cause water hardness are calcium bicarbonate, Ca(HCO₃)₂, and magnesium bicarbonate, Mg(HCO₃)₂. In a first electrochemical cell according to the invention, the bicarbonates are broken down by oxidation into the corresponding carbonate, water and carbon dioxide.



The calcium, carbonate is insoluble and will be captured by a filter. As the carbonates are strongly electronegative, some may plate out onto the anodes in the electrochemical cells. However, most of the carbonates do not adhere to the anodes. The carbonate acid, H₂CO₃, reacts with any calcium carbonate scaling in the downstream pipes re-dissolving it to soluble calcium bicarbonate. Over a period of time, scale will be removed.



As a result, the water undergoes a softening process and the downstream scaling is slowly dissolved.

Nitrogen Oxides

As nitrogen oxides such as NO₃, NO₂ and NO undergo reduction in the electrochemical cells, the nitrogen oxides undergo the following reactions:



These reactions are simplified versions of a multi-step process in which the nitrogen oxides are reduced. The nitrogen oxides are converted to nitrogen gas. In cases where contamination of the treated water is severely high, the amount of gas formed may be high enough to require evacuation from the system. In such cases, the gases are trapped in the head of the filter vessel onto which an air vent connected to the outdoors may be mounted.

In a further alternative, the iron anode may be replaced with an aluminum anode. When the current is applied to the electrochemical cell, the aluminum anode releases activated alumina into the solution. The activated alumina reacts with the arsenate to form aluminum arsenate. Aluminum arsenate is insoluble and will be captured in a downstream filter.

The foregoing discussion provides a theoretical basis as for the success of the method and system, described herein.

In the present invention the laws of physics, chemistry, electricity, thermodynamics and hydraulics are applied in a cost effective way to treat water and wastewater electrochemically while avoiding the problems and pitfalls of the past. The key to successful electrochemical treatment of water and wastewater at atomic and molecular levels is properly applying combinations of voltage, amperage, hydraulic retention time and electrode material to provide effective electrical charge densities on electrodes and electrical potential between the electrodes to then produce desired electrochemical reactions. The system described herein utilizes parallel or substantially parallel electrode array configurations for incorporating the individual treatment units into a horizontal or vertical manifold to achieve both redundancy and provide for greater system capacity.

FIGS. 1-7

FIG. 1 is a schematic overall view of a water or wastewater electrochemical treatment system 20 configured in accordance with the present invention. Water 21 from a raw water source 22, or from a wastewater source 23, is screened at a screening station 24 to remove large solids which could damage downstream apparatus. The raw water source 22 can be a drilled or dug well or a body of water, such as but not limited to, a river, stream, lake, reservoir or any other source of potentially potable water. If the water 21 is from a wastewater source 23, the water can be from, a sewage plant, an industrial wastewater site or from any other source of accumulated or flowing wastewater.

After the screening station 24 has removed large solids from the water 21 to prevent downstream damage, the water is pulled by a flow regulating pump 26 and conveyed to an electrochemical treatment unit 28 configured in accordance with the principles of the present invention. A monitor and control module 27 attached to the flow regulating pump 26 determines the hydraulic residence time within the electrochemical treatment unit 28, and thus depending upon applied electrical parameters, helps determine electrical charge density within the electrochemical treatment unit. A DC power unit 30 controlled by a controller 33 converts AC line current to DC and applies DC to the electrochemical treatment unit 28 while a polarity reverser 32 allows the DC

to be reversed periodically in order to minimize the possibility of clogging in the electrochemical unit 28. A selected contaminate or multiple contaminants are removed from the water stream 21 by the electrochemical treatment unit 28 while an uncontaminated water stream 21A flows to a clarification/filtration station 36. If a gas, such as nitrogen (N₂), is separated from the water stream 21 in the electrochemical treatment unit 28, the gas may be vented by a vent 34.

If the treated water stream 21A still contains suspended solid particulates precipitated by the electrochemical treatment unit 28, the suspended solid particulates are removed by a clarification/filtration station 36, which comprises either a gravitational or centrifugal separation unit 37, or a filtration unit 38. In some situations it may be necessary to use both gravitational or centrifugal separation, as well as filtration in order to provide an uncontaminated water stream 21B which may be for initial use or reuse, or for disposal back into the environment.

FIGS. 2-6 illustrate an initial embodiment of an electrochemical module 40 for use as the electrochemical treatment unit 28, or for use as a stand alone electrochemical treatment unit. The module 40 is an initial prototype of an electrochemical treatment unit formed as a cell, which may be combined with other similar cells when practicing the invention. The module 40 has a horizontal orientation in FIG. 2 and has successfully demonstrated that dissolved nitrogen and dissolved phosphorous compounds are removed from a water stream contaminated therewith when mechanical parameters such as electrode spacing, speed of the pump 26 and volume of the module 40 are considered in combination with electrical parameters, such as potential, amperage and rates of polarity change. Using the module 40, Applicant was able to decontaminate a water flow 21 without clogging of the module, a drawback that has prevented current commercial use of electrochemical decontamination for water treatment.

As is seen in FIG. 2, module 40 is aligned, or substantially aligned, with a horizontal axis 41. The module 40 comprises a cylindrical chamber 42 made of a dielectric material such as polyvinylchloride (PVC) and having at a first end portion 43 an inlet 44 that receives an influent in the form of the water stream 21. At a second end portion 45, an outlet 46 releases an effluent stream in the form of the water stream 21A in which previously dissolved contaminants have been separated from the water and exist in the form of relatively small particulates that are subsequently filtered, or in the form of gas that is subsequently vented. The first and second ends 43 and 45 of the chamber 42 are closed by end caps 50 and 52, respectively, made of a dielectric material such as PVC. The end caps 50 and 52 are bolted by bolts 54 to inverting rings 56 and 58, respectfully, that are received around the first and second ends 43 to 45 of the chamber 42 and are positioned in abutment with end sleeves 60 and 61 fixed to the cylindrical chamber 42. Positively charged and negatively charged leads 64 extend from the second end cap 52 on the cylindrical chamber 42 and are attached to electrodes within the chamber.

Referring now to FIGS. 3-5, it is seen that within the chamber 42 an array 66 of electrodes 68, configured as rods, are imbedded in a separator 70 of insulating material adjacent to the first end cap 50, and imbedded in an insulator 72 of insulating material, at the second end cap 52 so that the electrodes 68 are electrically isolated from one another. In order to ionize and remove dissolved contaminants, it is necessary to set up electrical charge gradients within the chamber 42 by negatively charging one portion of the array 66 of electrodes 68 and positively charging another portion of the array 66 of electrodes 68.

As is seen in the end views of FIGS. 4 and 5, one array of electrodes 68A has a negative charge (-) while another

array of electrodes 68B has a positive charge (+). This creates ionization within the water 21 being treated. In order to prevent clogging of electrodes 68B attracting negatively charged ions, the polarity of the arrays 66A and 66B are periodically reversed, as is shown by comparing FIGS. 4 and 5. By applying DC current at low voltage and keeping the influent water 21 moving through the chamber 42 at a selected speed so that hydraulic retention time is sufficient to obtain, ionization of contaminants suspended in particulate form in the water 21 being treated, and by periodically reversing the polarity of the electrode arrays, clogging of the space between electrodes array 66A and 66B is avoided. Since the particulate contaminants remain suspended, the particulates can be removed by settlement and filtration at station 36 of FIG. 1.

Further with respect to the embodiment of FIGS. 2-6, FIG. 6 shows a practical way in which to install the electrode array 66 wherein the electrodes 68 are retained by the first insulator 70 located at end cap 50 using bushings 80 and retained by the second insulator 72 at second end cap 52' by bushings 82. In the arrangement of FIG. 6, the end caps 50 and 52' are made of an insulating material such as PVC.

While the module 40 is shown aligned with a horizontal axis in FIG. 2, the module 40 is oriented with a vertical axis 41' in the second embodiment of the invention shown in FIG. 7. This takes advantage of the tendency of gas to flow upwardly allowing gas to vent via a vent 34 now disposed proximate the upper end 43 of the chamber 42 of the module 40.

The key to successful electrochemical treatment of waste and raw water at atomic and molecular levels is effective application of voltage, amperage, hydraulic retention time and electrode material in combination to provide electrical charge densities on the electrodes and electrical potential between the electrodes to produce a desired electrochemical reaction. The power applied is determined according to the mass of material to be removed, i.e., watts/pounds removed.

The following Charts A, B and C cite test data from testing the prototype illustrated in FIGS. 2-7 of the drawings. The parameters used occur within testing ranges initially selected by the inventor, which ranges do not limit the scope of the inventor's invention. The test data establish that the inventor has eliminated, or at least minimized, clogging of spaces between electrodes 68 by contaminants when electrochemically removing contaminants from water within the module 40.

As is evident from the charts, preferred test ranges are as follows;

DC Voltage: about 10 volts to about 50 volts.

DC Amperage: about 15 amps to about 35 amps,

Hydraulic retention time: about 2 minutes to about 5 minutes.

Spacing between electrodes; about 0.75 inch (1.90 cm), and

Polarity switching cycle: performed manually at intervals of about 5 minutes,

The ranges and specific parameter values recited in the Charts A, B and C are within larger contemplated ranges as follows:

DC Voltage: about 10.0 volts to about 60 volts,

DC Current: about 5.0 amps to about 50.0 amps.

Hydraulic Retention Time: about 30 seconds to 5 minutes, about 2 minutes, 30 seconds being preferred

Electrode Diameters: about 0.25 inch (0.635 cm) is preferred, but the electrodes may be effective at other diameters

Electrode Spacing: preferably >0.25 inch (0.635 cm)

Electrode Materials: iron, copper, aluminum.

11

Electrode Shape: The electrodes may have any shape effective to accomplish the invention, such as but not limited to: cylindrical rods, perforated or imperforated flat plates, undulating plates or rods.

Polarity Change Cycle: about 1 minute to 15 minutes.

While the cylindrical module 40 used to demonstrate the effectiveness of the invention has a length of 25 inches (63.5 cm) and a diameter of 6 inches (15.24 cm), a module used to practice the invention may have any dimensional configuration that achieves similar useful results. The electrodes 68 of the illustrated electrode array 66 are iron rods that are circular in cross section and have a diameter of 3/4 inch (2.54 centimeters). The cylindrical module 40 has dimensions which are suitable for intermittent flow wherein the water being treated remains in the module for a time sufficient to apply various voltages and amperages to achieve a range of test results such as those of the Charts A, B and C.

A preferable practice is to have an array of modules, configured to achieve results similar to the module 40, wherein individual modules can be readily replaced if necessary. The module can be arranged with other modules in parallel or serial arrays, or unparallel and serial arrays, to accomplish removal of contaminants from waste water or raw water. In order to increase hydraulic retention time, recycling of partially decontaminated water can be performed in order to further decontaminate already treated water.

Module construction can be scaled up to a much, larger individual size, for example, a size suitable to decontaminate waste water discharged from sewerage plants. Also, module construction can be scaled much smaller, for example to decontaminate tap water or water entering a home or a community, so as to remove endocrine disrupting compounds and personal care products from potable water. Modules scaled even smaller and using DC current from batteries and/or solar cells are usable to decontaminate raw water for drinking by campers, hunters and hikers, as well as to decontaminate raw water for military personnel.

The principles of the present invention, as exemplified in by the module 40 of FIGS. 2-7, can be used, to treat waste water and/or bilge water prior to discharge from ships and pleasure boats to remove contaminants. It is also contemplated that these principles are applicable to removing salt from sea water when sea water is used as a source of raw water for ships or perhaps agriculture, and for removing urea from urine recirculated to provide drinking water for astronauts.

Charts A, B and C are test results establishing the effectiveness of the method and system in removing various contaminants from water and aqueous solutions.

CHART A

Electrochemical Treatment of Municipal Wastewater Plant 1			
	Contaminant		
	Raw BOD ¹	Raw Phos	Raw TKN ²
Electrode Material	Iron	Iron	Iron
Electrode Spacing (inches; centimeters)	0.75; 1.905	0.75; 1.905	0.75; 1.905
Power Supplied to the System	120 Volt AC	120 Volt AC	120 Volt AC
DC Voltage Applied			
Low	10	10	10
Medium	30	30	30
High	50	50	50

12

CHART A-continued

Electrochemical Treatment of Municipal Wastewater Plant 1			
	Contaminant		
	Effluent Nitrate	Effluent E Coli	Primary Phos
Amperage Applied			
Low	15	15	15
Medium	25	25	10
High	35	35	15
Hydraulic Retention Time (minutes)			
Low	1	1	1
Medium	3	3	3
High	5	5	5
Untreated Concentration (mg/l)	350	6.9	62
EC Treated Concentration (mg/l)			
Percent Removal			
Low	85	36	29
Medium	90	81	37
High	93	88	50
Contaminant			
Electrode Material	Iron	Iron	Iron
Electrode Spacing (inches; centimeters)	0.75; 1.905	0.75; 1.905	0.75; 1.905
Power Supplied the System	120 Volt AC	120 Volt AC	120 Volt AC
DC Voltage Applied			
Low	10	10	10
Medium	30	30	30
High	50	50	50
Amperage Applied			
Low	15	15	5
Medium	25	25	10
High	35	35	15
Hydraulic Retention Time (minutes)			
Low	1	1	1
Medium	3	3	3
High	5	5	5
Untreated Concentration (mg/l)	16.8	>1,600	2.3
EC Treated Concentration (mg/l)			
Percent Removal			
Low	99	99+	65
Medium	99	99+	87
High	99	99+	87

¹BOD—Biochemical Oxygen Demand

²TKN—Total Kjeldahl Nitrogen (sum of organic nitrogen, ammonia and ammonium)

CHART B

Electrochemical Treatment of Municipal Wastewater Plant 2			
	Contaminant		
	Filter Eff BOD ¹	Filter Eff TOC ³	Effluent Ph
Electrode Material	Iron	Iron	Iron
Electrode Spacing (inches; centimeters)	0.75; 1.905	0.75; 1.905	0.75; 1.905
Power Supplied to the System	120 Volt AC	120 Volt AC	120 Volt AC

13
CHART B-continued

Electrochemical Treatment of Municipal Wastewater Plant 2			
DC Voltage Applied			
Low	10	10	10
Medium	30	30	30
High	50	50	50
Amperage Applied			
Low	15	15	15
Medium	25	25	10
High	35	35	15
Hydraulic Retention Time (minutes)			
Low	1	1	1
Medium	3	3	3
High	5	5	5
Untreated Concentration (mg/l)	4	34	6.4
EC Treated Concentration (mg/l)			
Low	<2	28	6.9
Medium	<2	27	8.0
High	<2		8.3
Percent Removal			
Low	50+	18	NA
Medium	50+	21	NA
High	50+		NA
Contaminant			
	Effluent Nitrate	Effluent <i>E Coli</i>	Primary Phos
Electrode Material			
	Tron	Tron	Tron
Electrode Spacing (inches, centimeters)			
	0.75; 1.905	0.75; 1.905	0.75; 1.905
Power Supplied to the System			
	120 Volt AC	120 Volt AC	120 Volt AC
DC Voltage Applied			
Low	10	10	10
Medium	30	30	30
High	50	50	50
Amperage Applied			
Low	20	15	5
Medium	30	25	10
high	40	35	15
Hydraulic Retention Time (minutes)			
Low	1	1	1
Medium	3	3	3
High	5	5	5
Untreated Concentration (mg/l)	16.7	>1,600	3.5
EC Treated Concentration (mg/l)			
Low	10.1	0	0.6
Medium	0.1	0	0.3
High	0.3	0	0.2
Percent Removal			
Low	40	99+	83
Medium	99	99+	91
High	98	99+	94

¹BOD—Biochemical Oxygen Demand

³TOC—Total Organic Carbon (includes, but is not limited to, pharmaceutical products, such as antibiotics and endocrine disrupting compounds exemplified estrogen compounds, and to personal and household care products, such as cosmetics and deodorant sprays).

14
CHART C

Electrochemical Treatment of Beverage Plant Wastewater			
	Contaminant		
	Phosphorous	Copper	pH
Electrode Material			
	Iron	Iron	Iron
Electrode Spacing (inches, centimeters)			
	0.75; 1.905	0.75; 1.905	0.75; 1.905
Power Supplied to the System			
	240 Volt AC	240 Volt AC	240 Volt AC
DC Voltage Applied			
Low	10	10	10
Medium	30	30	30
High	50	50	50
Amperage Applied			
Low	5	10	10
Medium	20	20	20
High	35	30	30
Hydraulic Retention Time (minutes)			
Low	1	1	2
Medium	3	3	3
High	5	5	5
Untreated Concentration (mg/l)	3.50	0.075	6.3
EC Treated Concentration(mgl)			
Low	1.64	ND	7.0
Medium	1.04	ND	8.3
High	0.62	ND	8.9
Percent Removal			
Low	53	99+	NA
Medium	70	99+	NA
High	82	99+	NA

The electrodes **66** used to develop the data of charts A, B, and C are circular iron electrodes having a diameter of 1/4 inch (0.635 cm). For purposes of this invention the electrodes have a preferable range of 1/8 inch (0.317 cm) to 5/16 inch (0.794 cm), however, the diameter may be substantially smaller wherein the electrodes have diameters which are measured in terms of wire gauge.

FIGS. 8-12

Referring now to FIGS. 8-12 there is shown another embodiment of an electrochemical cell, but configured as a polygonal, preferably rectangular, conductive module **100** having an increased water treatment capacity over that of FIGS. 2-7. The conductive module **100** is within a dielectric housing **102**, which is preferably square in cross section and made of a dielectric material such as fiberglass. Influent, such as but not limited to, untreated water **21** from a raw water source **22** or a waste water source **23** (see FIG. 1) is introduced by an inlet **103** provided at the bottom end **104** of the dielectric housing **102** of the conductive module **100**. Treated effluent **21A** exits the conductive module **100** through an outlet **105** provided by the open top end of the dielectric housing **102**.

The untreated water **21** flows upwardly through a bank **110** of individual electrode rod sheets **112** having individual rods **113** which are preferably circular in cross section. (See FIG. 11). The electrode rod sheets **112** are connected to eyelets **116** along one bus bar **118** of each electrode rod sheet **112**. The bus bars **118** establish an electrical connection with buses **120** and **122**, buses having threaded posts **124** and **126** thereon. The electrode rod sheet **112** has buses **118** and **119** which provide either a positive (+) or a negative (-) polarity to the rods **113** that extend therebetween. The rods **113** are

15

preferably circular and have a spacing of about $\frac{3}{4}$ inch (1.905 cm). The buses **120** and **122** have opposite electrical charges (+ and -) thereon so that all electrode rod sheets **112** connected to the bus bar **120** have a positive charge and all electrode rod sheets **112** connected to the bus bar **122** have a negative bias. Periodically, the polarity reverser **32** (see FIG. 1) reverses polarity on the buses **120** and **122** in order to minimize the possibility of clogging within the electrode rod sheet bank **110**. Within the dielectric housing **102**, the electrode rod sheets **112** are electrically insulated from one another by dielectric spacers **130** (see FIGS. 8 and 9) while adjacent electrode rod sheets **112** have electrical connections **124** and **126** of different polarities so that adjacent electrode rod sheets have opposite polarities. If over time, the individual rods **113** comprising the rod sheets **112** degrade, the electrode rod sheets or panels **112** as seen in FIGS. 11 and 12 may be readily withdrawn from the dielectric housing **102** and replaced.

The conductive module **300** of FIGS. 8-12 has a preferred processing rate in a range of about 35-60+ gallons per minute and has a width in a range of about 2 to 5 feet. In practicing this invention to remove remaining contaminants from untreated discharge water **21**, numerous electrochemical modules, such as the conductive module **100**, are connected in parallel. For example, at a rate of about 50 gallons per minute one hundred electrochemical conductive modules **100** are expected to decontaminate about seven million gallons of water per day.

FIG. 11A is a perspective view of another embodiment of the invention wherein the electrode rod sheets **112** are configured as grates **127**, each grate **127** has rod portions **128** separated by elongated voids **129**. The grates **127** may be formed by stamping metal plates, such as aluminum or aluminum alloy plates, to remove metal so as to create the voids **129**. In the illustrated embodiment, the plate **127** is at least substantially flat. In another embodiment, the grates **127** are made of iron or iron alloys such as steel.

FIGS. 13-16

Referring now to FIGS. 13, 14 and 15, the conductive module **100** and dielectric housing **102** are inserted into a dielectric container structure **130**, which in a preferred embodiment is cylindrical, to form with the dielectric container structure **130** a reaction chamber **132**. The dielectric housing **102** of the conductive module **100** has vertically extending corners **134** which engage an inner cylindrical wall **136** of the container structure **130** so as to provide an inlet chamber **140** and an outlet chamber **142**. The inlet chamber **140** is connected to an inlet pipe **144** for delivering untreated water **21** to the inlet chamber of the reaction chamber **132** and the outlet chamber **142** is connected to an outlet pipe **148** connected to an outlet line for discharging treated water **21A** from the reaction chamber **132**. A floor **149** is integral with the bottom of the cylindrical wall **136** of the dielectric container **130**. In the illustrated embodiment the conductive module **100** is square in cross section and has four vertically extending corners.

In order to facilitate entry of untreated structure water **21** into the conductive module **100** the dielectric housing **102** directly support the conductive module **100** has a first wall **160** having an undercut **162** defining an inlet opening **163** allowing untreated water **21** to flow from the inlet chamber **140** into the dielectric housing **102**. Hydraulic pressure in the inlet chamber **140** forces the untreated water **21** to rise in the dielectric housing **102** so that the untreated water **21** is exposed to the electrode rod panels **112** for a time

16

sufficient to remove contaminants from the untreated water **21** to produce the treated water **21A**. In one example of the illustrated embodiment, the undercut **162** has a height of about 1 inch providing a 1 inch inlet opening in the dielectric housing **102** communicating with the inlet **104** of the conductive module **100**.

The treated water **21A** then flows over a top edge **166** of a second wall **168** of the housing **102**, which top edge **166** is an overcut which is lower than the top edges of the first wall **160** and two side walls **170** and **172** of the dielectric housing **102**. From the top edge **166**, the treated water **21A** flows downward in the outlet chamber **142**, and out of the outlet pipe **148** to the clarification/filtration station **36** (FIG. 1). The overcut reducing the height of the top edge **166** is substantially greater than the undercut **162**. For example, the overcut over the top edge **166** is about 6 inches while the undercut **162** through the first wall **160** is about 1 inch.

As is seen in FIGS. 13 and 15, there are pair of side chambers **176** and **178** which are preferably filled with foam. In this illustrated embodiment, the dielectric container structure **130** is preferably made of fiberglass and the dielectric housing **102** within the container structure **130** is preferably made of Polyvinyl Chloride (PVC) forming a dielectric support structure for the conductive module **100**.

As is seen in FIG. 15, there is an air gap **170** between the outlet end **171** of the inlet pipe **144** and the top surface **173** of the untreated water **21** accumulated in the inlet chamber **140**. The air gap **170** electrically isolates the untreated water **21** from the upstream portion of the treatment system **20** illustrated in FIG. 1. Similarly, there is an air gap **175** between the outlet of the dielectric housing **102** formed by the over cut **166** and the top surface **177** of the treated water **21A** accumulating in the outlet chamber **142**. There are vents **178** and **178a** through the first wall **160** and dielectric container **130** adjacent the inlet pipe **144** and a vent **179** at the top of the outlet chamber **142**.

As is seen in FIGS. 14 and 15, the inlet pipe **144** includes a PVC ball valve **180** and the outlet pipe **148** includes a PVC ball valve **182**. The inlet pipe **144** has a diameter (for example 3 inches) which is larger than that of the outlet pipe **148** (for example 2 inches). A PVC drain valve **186** is placed in a portion of the floor **149** at the bottom of inlet chamber **140**. Preferably, the outlet pipe **348** is beneath the portion of the floor **149** located at the outlet chamber **142**. The top of the housing **102** is preferably open, to the atmosphere in order to let gases such as nitrogen vent from the water **21** being treated by the electrode rod sheets or panels **112**.

In order to process about 40 gallons/min of contaminated water, the reaction chamber **132** has a dielectric housing **102** with a width of about 24 inches and a height of about 30 inches, which reaction chamber **132** is contained within a dielectric container structure **130** having a diameter of about 36 inches. In a preferred embodiment, only a single input pump **26** (see FIG. 1) is connected to the inlet pipe **180**; however as is seen in FIG. 15, a pump **178** may be placed on the outlet pipe **148** that provides an outlet line for drainage of the treated water **21A** from, the outlet chamber **142**.

The inlet and outlet valves **180** and **182** are adjusted so that the level of the treated water **21A** emerging from the module **100** and flowing over the overcut edge **166** does not rise above the top of the container structure **130** and overflow the container structures.

A cap **185** covers the reaction chamber **132** and has a dog house vent **186**.

Referring now to FIG. 16, a plurality of reaction chambers **132 (a-n)**, each of which is as illustrated in FIGS. 13-15, are

17

arranged in parallel (a-n) connection with a feed pipe **190** feeding a parallel array of inlet pipes **144**. The inlet pump **26** (also see FIG. **1**), pumps untreated wafer to each of the reaction chambers which drain through outlet pipes **148** (a-n) to a drain line **192**, The drain line **192** connects to a final processing station **36** (FIG. **1**) where additional clarification and/or filtration occurs before clear treated water **21B** (FIG. **1**) is released back into the environment or collected in holding ponds or containers for recycling.

Examples

a) When using the module **100** within the dielectric container structure **130** of FIGS. **13-16**, a maximum power level of about 15 Kw per module is sufficient for various applications. The actual power level applied depends on the chemical make-up of the water being treated. Preferably, the 15 Kw power supply is capable of producing direct current at 500 amps and 30 volts, or any other combination of amperage or voltage within the 15 Kw envelope.

b) In a specific example, laundry water was treated at a DC power level of 400 amps and 9 volts with satisfactory results, however a higher amperage is thought to achieve better results. The satisfactory results were achieved at a pump speed of 16.5 U.S. gallons per minute (62.46 liters per minute) with a hydraulic retention time of about 2 minutes. Specifically, removal of contaminants was observed at 95 watts/gallon [9 volts×400 amps/38 gallons (94.74 liters)].

c) Experiments on synthetic soapy samples using the module of FIGS. **2-7** used voltages in the range of 10 v to 20 v with amperages remaining under 40 amps arrange for this purpose and utilizes a maximum voltage of 50 volts and maximum amperage of about 47 amps.

d) For acidic mine drainage it was calculated that about 1 Kw per gallon (3.785 liters) is suitable.

These examples are indicative of results achieved by this invention thus far. The selected ratio of voltage/amperage depends on the contaminant being removed from the water.

Other variations of the above principles will be apparent to those who are knowledgeable in the field of the invention, and such variations are considered to be within the scope of the present invention. Other modifications and/or alterations may be used in the configuration and/or manufacture of the apparatus of the present invention, or in methods of practicing the present invention, without departing from the spirit and scope of the accompanying claims.

Moreover, the word “substantially” when used with an adjective or adverb is intended to enhance the scope of a particular characteristic.

Without further elaboration, it is believed that one skilled in the art can, using the preceding description, utilize the present invention to its fullest extent. The preceding preferred specific embodiments are, therefore, to be construed as merely illustrative, and not limitative of the remainder of the disclosure in any way whatsoever.

In the foregoing and in the examples, all temperatures are set forth uncorrected in degrees Celsius and, all parts and percentages are by weight, unless otherwise indicated.

The entire disclosures of all applications, patents and publications, cited herein and of pending U.S. application Ser. No. 12/492,367, filed Jun. 26, 2009, are incorporated in their entirety by reference herein.

The preceding examples can be repeated with similar success by substituting the genetically or specifically described reactants and/or operating conditions of this invention for those used in the preceding examples.

18

From the foregoing description, one skilled in the art can easily ascertain the essential characteristics of this invention and, without departing from the spirit and scope thereof, can make various changes and modifications of the invention to adapt it to various usages and conditions.

The invention claimed is:

1. A system for removing contaminants from raw water or waste water, the system including at least one electrochemical treatment module comprising:

a housing having an inlet for untreated water and an outlet for treated water that has been treated within the housing;

an array of electrodes within the housing, the electrodes having space therebetween of a selected distance, the space being greater than about 0.25 inch (0.635 cm);

a source for applying direct current the electrodes to charge one portion of the array positively and another portion of the array negatively so as to create an electrical gradient between the portions of the array, the direct current being sufficient to oxidize and to neutralize small particle surface charges in an aqueous solution, and

container structure adjacent the housing, the container structure having an inlet chamber and an outlet chamber, the inlet chamber accumulating untreated water and delivering the untreated water to the inlet of the housing, an outlet of the housing being connected to the outlet chamber of the container and an outlet line being connected to the outlet chamber to drain away the treated water,

wherein the housing and container structure are both made of dielectric material with air gaps disposed between the inlet line for untreated water and untreated water accumulated in the inlet chamber and between the outlet of the housing and treated water accumulated in the outlet chamber.

2. The system of claim **1** wherein the container structure has an inner wall and the housing is polygonal with at least two pairs of vertically extending corners, each of which corners engage the inner wall to provide first and second housing walls that cooperate with the inner wall of the container structure to define the inlet and outlet chambers.

3. The system of claim **1** wherein the inlet opening extends horizontally with respect to a lower edge of the first wall of the housing and the outlet extends horizontally with respect to the second wall of the housing.

4. The system of claim **3** wherein two side chambers are formed in addition to the inlet and outlet chambers.

5. The system of claim **3** wherein a plurality of cells each defined by a module within a container are arranged in parallel to treat contaminated water flowing to each of the cells through a feed line from the source of contaminated water.

6. The system of claim **1** wherein a plurality of cells each defined by a module within a container are arranged in parallel to treat contaminated water flowing to each of the cells through a feed line from the source of contaminated water.

7. The system of claim **1** wherein a plurality of cells each defined by a module within a container are arranged in parallel to treat contaminated water flowing to each of the cells through a feed line from the source of contaminated water.

8. The system of claim **2** wherein a plurality of cells each defined by a module within a container are arranged in

19

parallel to treat contaminated water flowing to each of the cells through a feed line from the source of contaminated water.

9. The system of claim 1 wherein the arrays of the electrodes are formed by rod sheets.

10. The system of claim 9 wherein the rod sheets are configured as a grate and wherein the grate has rod portions separated by voids.

11. The system of claim 10 wherein the voids in the grate are arranged in rows and columns.

12. The system of claim 11 wherein there are at least two rows each containing at least two voids and at least two columns each containing at least two voids.

13. The system of claim 10 wherein the voids occupy at least 50% of the area of the grate.

14. The system of claim 10 wherein the voids are in the shape of regular polygons, circles, or ovals.

15. The system of claim 10 wherein there are multiple grates.

16. A system for removing contaminants from raw water or waste water, the system including at least one electrochemical treatment module comprising:

a housing having an inlet for untreated water and an outlet for treated water that has been treated within the housing;

an array of electrodes within the housing, the electrodes having space therebetween of a selected distance, the space being greater than about 0.25 inch (0.635 cm);

a source for applying direct current the electrodes to charge one portion of the array positively and another portion of the array negatively so as to create an electrical gradient between the portions of the array, the direct current being sufficient to oxidize and to neutralize small particle surface charges in an aqueous solution, and

container structure adjacent the housing, the container structure having an inlet chamber and an outlet chamber, the inlet chamber accumulating untreated water and delivering the untreated water to the inlet of the housing, an outlet of the housing being connected to the outlet chamber of the container and an outlet line being connected to the outlet chamber to drain away the treated water,

wherein the first housing wall defines an inlet opening at the bottom thereof and the second wall defines an outlet

20

opening at the top thereof with the outlet opening being larger in area than the inlet opening.

17. The system of claim 16 wherein the housing and container structure are both made of dielectric material with air gaps disposed between the inlet line for untreated water and untreated water accumulated in the inlet chamber and between the outlet of the housing and treated water accumulated in the outlet chamber.

18. The system of claim 16 wherein the inlet opening is an undercut of the first wall and the outlet opening is an overcut of the second wall.

19. The system of claim 18 wherein the housing and container structure are both made of dielectric material with air gaps disposed between the inlet line for untreated water and untreated water accumulated in the inlet chamber and between the outlet of the housing and treated water accumulated in the outlet chamber.

20. The system of claim 18 wherein the two side chambers are filled with solid foam.

21. The system of claim 20 wherein the housing and container structure are both made of dielectric material with air gaps disposed between the inlet line for untreated water and untreated water accumulated in the inlet chamber and between the outlet of the housing and treated water accumulated in the outlet chamber.

22. The system of claim 18 wherein a plurality of cells each defined by a module within a container are arranged in parallel to treat contaminated water flowing to each of the cells through a feed line from the source of contaminated water.

23. The system of claim 17 wherein the housing containing the array of electrodes is square and the container defines a cylindrical inner wall.

24. The system of claim 17 wherein a plurality of cells each defined by a module within a container are arranged in parallel to treat contaminated water flowing to each of the cells through a feed line from the source of contaminated water.

25. The system of claim 16 wherein a plurality of cells each defined by a module within a container are arranged in parallel to treat contaminated water flowing to each of the cells through a feed line from the source of contaminated water.

* * * * *