



US010679181B1

(12) **United States Patent**  
**Prater et al.**

(10) **Patent No.:** **US 10,679,181 B1**  
(45) **Date of Patent:** **Jun. 9, 2020**

(54) **INVENTORY MANAGEMENT USING WEIGHT SENSORS AND PHYSICAL LAYOUT DATA**

(71) Applicant: **AMAZON TECHNOLOGIES, INC.**,  
Seattle, WA (US)

(72) Inventors: **Alexander Clark Prater**, Seattle, WA (US); **Ivan Avramov**, Sammamish, WA (US); **Ismael Medrano**, Seattle, WA (US); **Benjamin Lloyd Shapiro**, Seattle, WA (US); **Navid Shiee**, Seattle, WA (US); **Brett Allen Skaloud**, Seattle, WA (US)

(73) Assignee: **AMAZON TECHNOLOGIES, INC.**,  
Seattle, WA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/383,391**

(22) Filed: **Apr. 12, 2019**

**Related U.S. Application Data**

(63) Continuation of application No. 14/747,553, filed on Jun. 23, 2015, now Pat. No. 10,262,293.

(51) **Int. Cl.**  
**G06Q 10/08** (2012.01)  
**G06N 5/04** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G06Q 10/087** (2013.01); **G06N 5/04** (2013.01)

(58) **Field of Classification Search**  
CPC ..... G06Q 20/00; G06Q 20/208; G06Q 20/20;  
G06Q 90/00; G06K 7/14; G06K 9/98;  
G06K 7/10861  
USPC ..... 705/14.64, 23, 323; 235/375, 462.08;  
702/150; 384/150; 382/100  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,891,755 A *	1/1990	Asher .....	G01G 19/414 177/210 R
7,225,980 B2	6/2007	Ku et al.	
7,949,568 B2	5/2011	Fano et al.	
8,009,864 B2	8/2011	Linaker et al.	
8,189,855 B2	5/2012	Opalach et al.	
8,442,878 B2	5/2013	Henry	
8,447,069 B2	5/2013	Huang et al.	
8,630,924 B2	1/2014	Groenevelt et al.	

(Continued)

OTHER PUBLICATIONS

Asthana, "An Indoor Wireless System for Personalized Shopping Assistance", CiteSeerX, In Proceedings of IEEE Workshop on Mobile Computing Systems and Applications, 1994, 6 pages. Retrieved from the Internet: URL:<http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.127.3303>.

(Continued)


*Primary Examiner* — Olusegun Goyea

(74) *Attorney, Agent, or Firm* — Linauer Law, PLLC

(57) **ABSTRACT**

An inventory location, such as a shelf, may be used to stow different items. The shelf is divided into a plurality of adjacent lanes, some of which may be grouped into a cluster. Items are placed upon the lanes of the cluster. Each lane includes one or more weight sensors to obtain weight data about a load on the lane. Based on the weight data and physical layout data for the shelf, one or more hypotheses may be determined for describing interactions, such as a pick or place of an item, occurring at the lanes of a cluster. One of the hypotheses may be selected as a solution for describing the interaction and used to maintain inventory quantities of items at the shelf.

**20 Claims, 10 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS

9,235,928 B2 1/2016 Medioni et al.  
 9,813,605 B2 11/2017 Peterson et al.  
 2003/0078693 A1 4/2003 Chavez et al.  
 2003/0179294 A1 9/2003 Martins  
 2005/0060246 A1 3/2005 Lastinger et al.  
 2005/0073585 A1 4/2005 Ettinger et al.  
 2005/0190072 A1 9/2005 Brown et al.  
 2006/0071774 A1 4/2006 Brown et al.  
 2007/0050271 A1\* 3/2007 Ufford ..... G06Q 10/087  
 705/28  
 2009/0222359 A1 9/2009 Henry  
 2011/0011936 A1 1/2011 Morandi et al.  
 2012/0284132 A1 11/2012 Kim et al.  
 2013/0223673 A1\* 8/2013 Davis ..... G06K 9/78  
 382/100  
 2013/0284806 A1 10/2013 Margalit  
 2013/0290106 A1\* 10/2013 Bradley ..... G06Q 90/20  
 705/14.64  
 2014/0052555 A1\* 2/2014 MacIntosh ..... G07G 1/0036  
 705/23  
 2014/0074762 A1\* 3/2014 Campbell ..... G06Q 40/00  
 706/46

2014/0379296 A1\* 12/2014 Nathan ..... G06Q 10/08  
 702/150  
 2015/0086107 A1 3/2015 Dedeoglu et al.  
 2015/0178654 A1 6/2015 Glasgow et al.  
 2015/0310601 A1\* 10/2015 Rodriguez ..... G06K 9/209  
 348/150  
 2016/0026032 A1\* 1/2016 Moore ..... G06K 7/10316  
 382/103

OTHER PUBLICATIONS

Kalnikaite, et al., "How to Nudge In Situ: Designing Lambert Devices to Deliver Information Salience in Supermarkets", ACM, In proceeding of: UbiComp 2011: Ubiquitous Computing, 13th International Conference, UbiComp 2011, Beijing, China, Sep. 17-21, 2011, 10 pages. Retrieved from the Internet: [http://www.researchgate.net/publication/221568350\\_How\\_to\\_nudge\\_in\\_Situ\\_designing\\_lambent\\_devices\\_to\\_deliver\\_salient\\_information\\_in\\_supermarkets](http://www.researchgate.net/publication/221568350_How_to_nudge_in_Situ_designing_lambent_devices_to_deliver_salient_information_in_supermarkets).  
 Pop, Cristian, "Introduction to the BodyCom Technology" AN1391, DS01391A, Microchip Technology, Inc., May 2, 2011. Retrieved from the Internet: <http://www.microchip.com/wwwAppNotes/AppNotes.aspx?appnote=en555156>.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3

400




FIG. 4

500




FIG. 5




FIG. 6






FIG. 7




FIG. 8

900




FIG. 9

1000




FIG. 10

## 1

## INVENTORY MANAGEMENT USING WEIGHT SENSORS AND PHYSICAL LAYOUT DATA

### PRIORITY

This application is a continuation of, and claims priority to, U.S. patent application Ser. No. 14/747,553, filed on Jun. 23, 2015 entitled “Item Management System Using Multiple Scales”, which is hereby incorporated by reference in its entirety.

### BACKGROUND

Retailers, wholesalers, and other product distributors typically maintain an inventory of various items that may be ordered, purchased, leased, borrowed, rented, viewed, and so forth, by clients or customers. For example, an e-commerce website may maintain inventory in a fulfillment center. When a customer orders an item, the item is picked from inventory, routed to a packing station, packed, and shipped to the customer. Likewise, physical stores maintain inventory in customer accessible areas, such as in a shopping area, and customers can pick items from inventory and take them to a cashier for purchase, rental, and so forth.

Many physical stores also maintain inventory in a storage area, fulfillment center, or other facility that can be used to replenish inventory located in the shopping areas or to satisfy orders for items that are placed through other channels (e.g., e-commerce). Other examples of entities that maintain facilities holding inventory include libraries, museums, rental centers, and so forth. In each instance, for an item to be moved from one location to another, it is picked from its current location and transitioned to a new location. It is often desirable to monitor quantity of inventory within the facility.

### BRIEF DESCRIPTION OF FIGURES

The detailed description is set forth with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different figures indicates similar or identical items or features. The figures are not necessarily drawn to scale, and in some figures, the proportions or other aspects may be exaggerated to facilitate comprehension of particular aspects.

FIG. 1 illustrates several views of an inventory location comprising a shelf with multiple lanes, each lane having a weight sensor to generate weight sensor data, according to some implementations.

FIG. 2 is a block diagram illustrating a materials handling facility (facility) having weight sensors, according to some implementations.

FIG. 3 is a block diagram illustrating additional details of the facility, according to some implementations.

FIG. 4 is a block diagram of a server to support operation of the facility, according to some implementations.

FIG. 5 is a block diagram of additional data that may be used by the server to support operation of the facility, according to some implementations.

FIG. 6 illustrates a side view of an inventory location that includes various sensors, according to some implementations.

FIG. 7 illustrates a side view of the shelf, according to some implementations.

## 2

FIG. 8 illustrates an overhead schematic view of the shelf, according to some implementations.

FIG. 9 depicts a flow diagram of a process for determining an interaction with a particular item based on weight sensor data, according to some implementations.

FIG. 10 depicts a flow diagram of a process for determining an interaction with a particular item based on weight sensor data, according to some implementations.

While implementations are described herein by way of example, those skilled in the art will recognize that the implementations are not limited to the examples or figures described. It should be understood that the figures and detailed description thereto are not intended to limit implementations to the particular form disclosed but, on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope as defined by the appended claims. The headings used herein are for organizational purposes only and are not meant to be used to limit the scope of the description or the claims. As used throughout this application, the word “may” is used in a permissive sense (i.e., meaning having the potential to), rather than the mandatory sense (i.e., meaning must). Similarly, the words “include,” “including,” and “includes” mean including, but not limited to.

### DETAILED DESCRIPTION

This disclosure describes systems and techniques for determining interactions with items stowed in inventory locations in a materials handling facility (facility) or other settings. For example, interactions may comprise the user picking an item from an inventory location, placing an item at an inventory location, touching an item, and so forth.

The facility may include, or have access to, an inventory management system. The inventory management system may be configured to maintain information about items, users, condition of the facility, and so forth. For example, the inventory management system may maintain data indicative of a number of items at a particular inventory location, what items a particular user is ordered to pick, how many items have been picked or placed at the inventory location, requests for assistance, environmental status of the facility, and so forth.

Operation of the facility may be facilitated by using one or more sensors to acquire information about interactions in the facility. The inventory management system may process the sensor data from the one or more sensors to determine interaction data. For example, the inventory management system may use the interaction data to determine a type of item a user picked from a particular inventory location, to adjust the count of inventory stowed at the particular inventory location, and so forth.

Described are devices and techniques for gathering and processing weight sensor data from one or more weight sensors. The weight sensors may be used to gather weight sensor data about items stowed at an inventory location, such as a shelf.

Each shelf may comprise a plurality of lanes that are arranged adjacent to one another. Each lane is coupled to a weight sensor that provides information about the weight of a load on that particular lane. The load may comprise any object that imposes a weight onto at least a portion of the particular lane, such as items, support structure, and so forth. One or more types of items may be arranged on the shelf. Items may span two or more lanes. For example, the shelf may have a total width of about 48 inches wide, and may include 16 lanes, with each lane about 3 inches wide. Items

may rest on the shelf, supported by two or more lanes. For example, an item 2 inches wide may be resting half on one lane, half on another lane. In another example, an item 10 inches wide may be supported by 4 lanes.

Items may be arranged in columns on the shelf, with the columns running front to back. Each column may store a different type of item. For example, one column may be Brand A dog food, another column may be Brand X cat food, and so forth. During use of the facility, items may be added to or removed from the shelf. For example, some users may pick items from the shelf while other users may place items on the shelf to restock.

As items are added to or removed from the shelf, the weight at the different lanes on that shelf may change. For example, addition or removal of an item may cause a change in weight across several lanes. The amount of weight change may vary depending upon how much support a particular lane provided to the item. For example, removal of an item that weights 300 grams and rests halfway on a first lane and halfway on a second lane will result in a weight change of -150 grams on the first lane and -150 grams on the second lane.

The weight sensor data may be processed to generate weight characteristic data. The processing may include utilizing one or more filters or analysis techniques. For example, the weight sensor data may be processed with an exponential moving average function to generate filtered weight sensor data. The filtered weight sensor data may be processed to generate weight characteristic data. The weight characteristic data may include one or more of a measured weight at a lane at a particular time, measured weight change data at a lane from a first time to a second time, weight distribution indicative of an arrangement of weight across a plurality of lanes, and so forth.

The inventory management system may generate or access hypotheses that describe various predicted combinations of types of items, quantity changes, location on the shelf, and so forth. The hypotheses may be based on item data, physical layout data, one or more constraints, and so forth. Item data may indicate the items that are expected to be stored at that particular shelf, weight of those items, and the location on the shelf where the column is arranged. The physical layout data may provide information indicative of where an inventory location is located in the facility, physical configuration of the inventory location, and so forth. For example, the physical layout data may indicate which lanes are adjacent to one another at a particular shelf, and relative positions thereof such as which lane is on the left and which lane is on the right.

These hypotheses may be compared with measured weight characteristic data to determine if one or more of the hypotheses are a solution indicative of what happened during an interaction. In some implementations, the correspondence of the predicted values of the hypotheses to the measured values may be used to generate a score. Various techniques may be used to generate the score such as an expected weight scorer, edge penalty scorer, penalized weight scorer, transaction count scorer, and so forth. The solution may then be determined based on the score. Once the solution has been determined, the predicted values described in that hypotheses may be deemed to accurately reflect the interaction and may be used to generate the interaction data. For example, if the solution describes a prediction that 2 cans of dog food were removed from the shelf, the interaction may be deemed to involve removal of 2 cans of dog food from the shelf.

The inventory management system may use the interaction data to maintain item data about the items in the facility. For example, the interaction data may indicate that a quantity of one can of Brand A dog food was removed from the shelf. Responsive to this, the inventory management system may decrease the quantity of Brand A dog food on hand at that shelf by one.

By using the devices and techniques described herein, operation of the facility may be improved. Details about interactions between users and items in the facility may be quickly and accurately determined. For example, as items are picked, placed, touched, and so forth, information such as inventory levels or metrics about touch may be readily determined. As a result, the inventory management system may be able to quickly track what item a user has interacted with, maintain up-to-date item data, and so forth.

#### Illustrative System

FIG. 1 illustrates several overhead views **100** of an inventory location. A first view **102** depicts a shelf **104** while an enlarged view **106** depicts a portion of the shelf **104**. With respect to the first view **102**, the shelf **104** is depicted as having 16 lanes **108**. In other implementations, a larger or smaller number of lanes **108** may be implemented. For ease of illustration, and not necessarily by way of limitation, each lane **108** is assigned a lane ID **110**, numbered 1-16 and ordered left to right. The lanes **108** are adjacent to one another, such that one lane **108** is next to at least one other lane **108**. For example, lane 1 is adjacent to lane 2.

The lane **108** may be constructed to provide a relatively flat surface upon which one or more items **112** may rest. As depicted in the enlarged view **106**, one or more weight sensors **114(6)** may be arranged beneath the lane **108**. In this illustration, a pair of weight sensors **114(6)** may be arranged at each end of the lane **108**. In other implementations, the placement of the weight sensor **114(6)** may change, and so forth. The weight sensors **114(6)** generate weight sensor data indicative of a load on that particular lane **108**. The load may include the items **112**, a support structure, and so forth. Items **112** may span or extend across two or more lanes **108**. A group of the same type of item **112** may be arranged as depicted in columns along the lanes **108**. For example, a group of the type of items **112(1)** includes items **112** that span lanes 2 and 3, while a group of the type of items **112(2)** spans lanes 5, 6, 7, and 8.

While the shelf **104** is depicted as having a rectangular shape when viewed from above, in other implementations, the shelf **104** may be arranged with lanes **108** in other configurations. In one implementation the shelf **104** may describe an arc or an angle. For example, the shelf **104** may be configured to extend around a corner, such as on a curved end-cap of the aisle. In another implementation the shelf **104** may be arranged to form a square corner.

The surface of the shelf **104** allows a user **116** to place items **112** on the shelf **104** in whatever arrangement is desired. For example, a planogram provided by an operator of a facility may set forth a particular arrangement of the items **112** on the shelf **104**. Without regard to the location of the underlying lanes **108**, the user **116** may configure the items **112** on the shelf **104** in accord with the planogram. As illustrated here, items **112** need not be constrained to a single lane **108**. Even though a particular item **112** may have a geometry allowing it to fit within a single lane **108**, the item **112** may not be constrained to placement within a single lane **108**. For example, the items **112(5)** are arranged such that they span lanes 14 and 15. Once configured, information about the ultimate arrangement of the items **112** on the shelf **104** may be stored as item data for use as described herein.

An implementation of a materials handling system **200** configured to store and manage inventory items is illustrated in FIG. 2. A materials handling facility **202** (facility) comprises one or more physical structures or areas within which one or more items **112(1)**, **112(2)**, . . . , **112(Q)** may be held. As used in this disclosure, letters in parenthesis such as “(Q)” indicate an integer value greater than or equal to zero. The items **112** comprise physical goods, such as books, pharmaceuticals, repair parts, electronic gear, and so forth.

The facility **202** may include one or more areas designated for different functions with regard to inventory handling. In this illustration, the facility **202** includes a receiving area **204**, a storage area **206**, and a transition area **208**.

The receiving area **204** may be configured to accept items **112**, such as from suppliers, for intake into the facility **202**. For example, the receiving area **204** may include a loading dock at which trucks or other freight conveyances unload the items **112**.

The storage area **206** is configured to store the items **112**. The storage area **206** may be arranged in various physical configurations. In one implementation, the storage area **206** may include one or more aisles **210**. The aisle **210** may be configured with, or defined by, inventory locations **212** on one or both sides of the aisle **210**. The inventory locations **212** may include one or more of a shelf **104**, a rack, a case, a cabinet, a bin, a floor location, or other suitable storage mechanisms for holding, supporting, or storing the items **112**. The inventory locations **212** may be affixed to the floor or another portion of the facility’s **202** structure. The inventory locations **212** may also be movable such that the arrangement of aisles **210** may be reconfigurable. In some implementations, the inventory locations **212** may be configured to move independently of an outside operator. For example, the inventory locations **212** may comprise a rack with a power source and a motor, operable by a computing device to allow the rack to move from one location within the facility **202** to another.

One or more users **116(1)**, **116(2)**, . . . , **116(U)** and totes **214(1)**, **214(2)**, . . . , **214(T)** or other material handling apparatus may move within the facility **202**. For example, the user **116** may move about within the facility **202** to pick or place the items **112** in various inventory locations **212**, placing them on the tote **214** for ease of transport. The tote **214** is configured to carry or otherwise transport one or more items **112**. For example, the tote **214** may include a basket, cart, bag, bin, and so forth. In other implementations, other material handling apparatuses such as robots, forklifts, cranes, aerial drones, and so forth, may move about the facility **202** picking, placing, or otherwise moving the items **112**. For example, a robot may pick an item **112** from a first inventory location **212(1)** and move the item **112** to a second inventory location **212(2)**.

One or more sensors **114** may be configured to acquire information in the facility **202**. The sensors **114** may include, but are not limited to, cameras **114(1)**, three-dimensional (3D) sensors **114(2)**, weight sensors **114(6)**, optical sensor arrays **114(13)**, proximity sensors **114(14)**, and so forth. The sensors **114** may be stationary or mobile, relative to the facility **202**. For example, the inventory locations **212** may contain weight sensors **114(6)** to acquire weight sensor data of items **112** stowed therein, cameras **114(1)** to acquire images of picking or placement of items **112** on shelves, optical sensor arrays **114(13)** to detect shadows of the user’s **116** hands at the inventory locations **212**, and so forth. In another example, the facility **202** may include cameras to

obtain images of the user **116** or other objects in the facility **202**. The sensors **114** are discussed in more detail below with regard to FIG. 3.

While the storage area **206** is depicted as having one or more aisles **210**, inventory locations **212** storing the items **112**, sensors **114**, and so forth, it is understood that the receiving area **204**, the transition area **208**, or other areas of the facility **202** may be similarly equipped. Furthermore, the arrangement of the various areas within the facility **202** is depicted functionally rather than schematically. For example, in some implementations, multiple different receiving areas **204**, storage areas **206**, and transition areas **208** may be interspersed rather than segregated in the facility **202**.

The facility **202** may include, or be coupled to, an inventory management system **216**. The inventory management system **216** is configured to interact with users **116** or devices such as sensors **114**, robots, material handling equipment, computing devices, and so forth, in one or more of the receiving area **204**, the storage area **206**, or the transition area **208**.

During operation of the facility **202**, the sensors **114** may be configured to provide sensor data **218**, or information based on the sensor data **218**, to the inventory management system **216**. The sensor data **218** may include weight sensor data **220** obtained from weight sensors **114(6)**, non-weight sensor data **222** obtained from other sensors **114** such as cameras **114(1)**, 3D sensors **114(2)**, optical sensor arrays **114(13)**, proximity sensors **114(14)**, and so forth. The sensors **114** are described in more detail below.

The weight sensor data **220** comprises data generated by one or more weight sensors **114(6)**. The weight sensors **114(6)** may be incorporated into an inventory location **212** that stows the items **112**. For example, the inventory location **212** may comprise one or more shelves **104**. Each shelf **104** may, in turn, comprise a plurality of adjacent lanes **108** or platforms, with each lane **108** having one or more weight sensors **114(6)**. By reading one or more characteristics of a load cell, the weight of the load on a particular lane may be determined. The load cell uses electronic, optical, acoustic, or other effects to determine the magnitude of a load applied thereto. For example, an electronic load cell may utilize changes in electrical resistance, capacitance, or inductance to determine weight. In another example, an optical load cell may use changes in the transmittance of light, such as in an optical fiber or other waveguide, to determine weight. Continuing the example, the optical fiber may be affixed to a support structure, and the deformation of the structure and corresponding movement of the fiber responsive to a change in the weight of a load on that support structure may be used to generate weight data based on measurement of the Fiber Bragg Grating effect. In another example, acoustic measurement may utilize one or more transducers to introduce sound waves into at least a portion of the load cell and then read out how the transmission of that sound is changed. For example, a change in the phase or amplitude of the received sound may be used to determine weight on the load cell. In other implementations the weight sensor **114(6)** may comprise a force sensitive resistor (FSR) or other material. The FSR may comprise a resilient material, such as foam, that exhibits changes in one or more electrical characteristics when compressed. The FSR may be utilized in a variety of configurations. For example, the FSR may be used as a load cell, or may be arranged across the entire surface of the lane.

The weight sensor data **220** from each lane may be processed by the inventory management system **216** to determine what items **112** have been picked or placed,

quantities involved, and so forth. Features of the shelf **104** are discussed in more detail below with regard to FIGS. **6-8**.

The non-weight sensor data **222** may comprise data generated by the non-weight sensors **114**, such as cameras **114(1)**, 3D sensors **114(2)**, buttons **114(3)**, touch sensors **114(4)**, microphones **114(5)**, optical sensors **114(7)**, RFID readers **114(8)**, RF receivers **114(9)**, accelerometers **114(10)**, gyroscopes **114(11)**, magnetometers **114(12)**, optical sensor arrays **114(13)**, proximity sensors **114(14)**, and so forth. For example, cameras **114(1)** may be arranged to have a field of view (FOV) **224** that includes at least a portion of the inventory location **212**. Continuing the example, the camera **114(1)** may be mounted above the inventory location **212** with the FOV **224** oriented to where the items **112** may be stowed during use of the inventory location **212**.

The inventory management system **216** or other systems may use the sensor data **218** to track the location of objects within the facility **202**, movement of the objects, or provide other functionality. Objects may include, but are not limited to, items **112**, users **116**, totes **214**, and so forth. For example, a series of images acquired by the camera **114(1)** may indicate removal by the user **116** of an item **112** from a particular location on the inventory location **212** and placement of the item **112** on or at least partially within the tote **214**.

The facility **202** may be configured to receive different kinds of items **112** from various suppliers and to store them until a customer orders or retrieves one or more of the items **112**. A general flow of items **112** through the facility **202** is indicated by the arrows of FIG. **2**. Specifically, as illustrated in this example, items **112** may be received from one or more suppliers, such as manufacturers, distributors, wholesalers, and so forth, at the receiving area **204**. In various implementations, the items **112** may include merchandise, commodities, perishables, or any suitable type of item **112**, depending on the nature of the enterprise that operates the facility **202**.

Upon being received from a supplier at the receiving area **204**, the items **112** may be prepared for storage in the storage area **206**. For example, in some implementations, items **112** may be unpacked or otherwise rearranged. The inventory management system **216** may include one or more software applications executing on a computer system to provide inventory management functions. These inventory management functions may include maintaining information indicative of the type, quantity, condition, cost, location, weight, or any other suitable parameters with respect to the items **112**. The items **112** may be stocked, managed, or dispensed in terms of countable units, individual units, or multiple units, such as packages, cartons, crates, pallets, or other suitable aggregations. Alternatively, some items **112**, such as bulk products, commodities, and so forth, may be stored in continuous or arbitrarily divisible amounts that may not be inherently organized into countable units. Such items **112** may be managed in terms of a measurable quantity such as units of length, area, volume, weight, time, duration, or other dimensional properties characterized by units of measurement. Generally speaking, a quantity of an item **112** may refer to either a countable number of individual or aggregate units of an item **112** or a measurable amount of an item **112**, as appropriate.

After arriving through the receiving area **204**, items **112** may be stored within the storage area **206**. In some implementations, like items **112** may be stored or displayed together in the inventory locations **212** such as in bins, on shelves, hanging from pegboards, and so forth. In this implementation, all items **112** of a given kind are stored in

one inventory location **212**. In other implementations, like items **112** may be stored in different inventory locations **212**. For example, to optimize retrieval of certain items **112** having frequent turnover within a large physical facility **202**, those items **112** may be stored in several different inventory locations **212** to reduce congestion that might occur at a single inventory location **212**.

When a customer order specifying one or more items **112** is received, or as a user **116** progresses through the facility **202**, the corresponding items **112** may be selected or “picked” from the inventory locations **212** containing those items **112**. In various implementations, item picking may range from manual to completely automated picking. For example, in one implementation, a user **116** may have a list of items **112** they desire and may progress through the facility **202** picking items **112** from inventory locations **212** within the storage area **206** and placing those items **112** into a tote **214**. In other implementations, employees of the facility **202** may pick items **112** using written or electronic pick lists derived from customer orders. These picked items **112** may be placed into the tote **214** as the employee progresses through the facility **202**.

After items **112** have been picked, the items **112** may be processed at a transition area **208**. The transition area **208** may be any designated area within the facility **202** where items **112** are transitioned from one location to another or from one entity to another. For example, the transition area **208** may be a packing station within the facility **202**. When the item **112** arrives at the transition area **208**, the items **112** may be transitioned from the storage area **206** to the packing station. Information about the transition may be maintained by the inventory management system **216**.

In another example, if the items **112** are departing the facility **202**, a list of the items **112** may be obtained and used by the inventory management system **216** to transition responsibility for, or custody of, the items **112** from the facility **202** to another entity. For example, a carrier may accept the items **112** for transport with that carrier accepting responsibility for the items **112** indicated in the list. In another example, a user **116** may purchase or rent the items **112** and remove the items **112** from the facility **202**. During use of the facility **202**, the user **116** may move about the facility **202** to perform various tasks, such as picking or placing the items **112** in the inventory locations **212**.

To facilitate operation of the facility **202**, the inventory management system **216** is configured to use the sensor data **218**, item data **226**, physical layout data **228**, and so forth, to generate interaction data **230**. The item data **226** provides information about a particular item **112**, characteristics of that type of item **112**, where that type of item **112** is located in the facility **202**, and so forth. For example, the item data **226** may indicate the types and quantities of items **112** that are expected to be stored at that particular inventory location **212** such as a shelf **104**, the location on the shelf **104** where the column is stowed, weight of those items **112** individually or in aggregate, and so forth. The item data **226** may include information such as an item identifier, item weight data, weight distribution, geometry data, shelf location identifiers, quantity data, and so forth. The item data **226** is described in more detail below with regard to FIG. **5**.

The physical layout data **228** may provide information indicative of where an inventory location **212** is located in the facility **202**, physical configuration of the inventory location **212**, and so forth. For example, the physical layout data **228** may indicate that inventory location **212(37)** comprises a shelf **104** with 16 lanes **108**, the lanes **108** ordered



1 to 16 as viewed left to right, and so forth. The physical layout data 228 is described in more detail below with regard to FIG. 5.

The interaction data 230 may provide information about an interaction, such as a pick of an item 112 from the inventory location 212, a place of an item 112 to the inventory location 212, a touch made to an item 112 at the inventory location 212, a gesture associated with an item 112 at the inventory location 212, and so forth. The interaction data 230 may include one or more of the type of interaction, inventory location identifier indicative of where from the inventory location 212 the interaction took place, item identifier, quantity change to the item 112, user identifier, and so forth. The interaction data 230 may then be used to further update the item data 226. For example, the quantity of items 112 on hand at a particular location on the shelf 104 may be changed based on an interaction that picks or places one or more items 112.

The inventory management system 216 may use the sensor data 218 to determine the interaction. Weight characteristics about an interaction may be determined using the weight sensor data 220 obtained from weight sensors 114(6) of the lanes 108 in the shelf 104. These weight characteristics may include weight before an interaction, weight after an interaction, weight change during a period of time, change in distribution of weight, and so forth.

In some implementations, a single inventory location 212 such as a shelf 104 may stow several different types of items 112, with each type of item 112 arranged in columns on the shelf 104. The inventory management system 216 may use the weight sensor data 220 to determine weight characteristics, and use those weight characteristics to identify the item 112 that was picked or placed. The weight characteristics may include the change in measured weight at several different lanes 108 during a particular period of time. The item data 226 may be retrieved that indicates weight of individual items 112, width of an item 112, where the item 112 is supposed to be stowed on at the inventory location 212, and so forth. The physical layout data 228 may be used to determine which lanes 108 and corresponding weight sensors 114(6) are under the location where the item 112 is to be stowed.

Based on the item data 226, the physical layout data 228, and so forth, hypotheses may be generated that describe different or particular combinations of predicted actions. In some implementations, these hypotheses may be precomputed or otherwise generated in advance. These hypotheses may include predicted weight characteristic data for these different or particular combinations. The measured weight characteristics may be compared with the predicted weight characteristics of the hypotheses and used to determine a solution. Once a solution is determined, the predicted identity of the item(s) 112 involved, quantities, and so forth, may be determined to be indicative of the actual interaction that took place. The predicted values of the solution may then be used to change item data 226 such as a quantity on hand at a particular inventory location 212 or position therein. For example, if the hypothesis selected as a solution indicates three cans of dog food were picked from the inventory location 212, the quantity on hand for dog food at that inventory location 212 may be decreased by a quantity of three.

In some implementations, other non-weight sensor data 222 may be processed and used to select a particular hypothesis. For example, non-weight sensor data 222 such as images acquired from cameras may be processed and used to determine motion at particular inventory locations

212 or portions of the inventory locations 212. This motion data may then be used to select or discard hypotheses.

In some implementations, the hypotheses may be selected based at least in part on a score. The scores may be determined by the degree of correspondence between the sensor data 218, or information based thereon, and the predicted values of the hypotheses. A higher score may be indicative of a closer correspondence between the predicted values and the measured data. For example, a high scoring hypothesis may predict values of a change in one or more weight characteristics that are within 5% of the measured weight sensor data 220, while a lower scoring hypothesis may have values that are within 20% of the measured weight sensor data 220.

The process of using the weight sensor data 220 to generate interaction data 230 is discussed in more detail below. For example, FIGS. 8-10 describe various processes for determining a hypothesis based on information derived from weight sensor data 220.

In some implementations, items 112 may be processed, such as at the receiving area 204, to generate at least a portion of the item data 226. For example, an item 112 not previously stored by the inventory management system 216 may be measured to determine geometry such as external dimensions, assigned to a particular inventory location 212, and so forth, as part of a process to receive the item 112 into the facility 202. Continuing the example, the item data 226 generated may include acquiring the weight of a single item 112, information about weight distribution of the item 112, and so forth.

By using the weight sensor data 220 obtained from the various weight sensors 114(6) in the lanes 108 of the shelf 104, and in some implementations, in conjunction with the non-weight sensor data 222, the inventory management system 216 is able to maintain item data 226 such as inventory levels of a particular item 112 at a particular inventory location 212, generate billing information without manual intervention by a user 116, or provide other functions. For example, the user 116 may pick an item 112 from the inventory location 212. Using the interaction data 230 based on the sensor data 218 and in conjunction with the item data 226, the inventory management system 216 may correctly determine that a quantity of one can of dog food has been picked, and bill the user 116 accordingly for the sale price of the item 112.

FIG. 3 is a block diagram 300 illustrating additional details of the facility 202, according to some implementations. The facility 202 may be connected to one or more networks 302, which in turn connect to one or more servers 304. The network 302 may include private networks such as an institutional or personal intranet, public networks such as the Internet, or a combination thereof. The network 302 may utilize wired technologies (e.g., wires, fiber optic cables, and so forth), wireless technologies (e.g., radio frequency, infrared, acoustic, optical, and so forth), or other connection technologies. The network 302 is representative of any type of communication network, including one or more of data networks or voice networks. The network 302 may be implemented using wired infrastructure (e.g., copper cable, fiber optic cable, and so forth), a wireless infrastructure (e.g., cellular, microwave, satellite, and so forth), or other connection technologies.

The servers 304 may be configured to execute one or more modules or software applications associated with the inventory management system 216 or other systems. While the servers 304 are illustrated as being in a location outside of the facility 202, in other implementations, at least a portion

## 11

of the servers **304** may be located at the facility **202**. The servers **304** are discussed in more detail below with regard to FIG. **4**.

The users **116**, the totes **214**, or other objects in the facility **202** may be equipped with one or more tags **306**. The tags **306** may be configured to emit a signal **308**. In one implementation, the tag **306** may be a radio frequency identification (RFID) tag configured to emit a RF signal **308** upon activation by an external signal. For example, the external signal may comprise a radio frequency signal or a magnetic field configured to energize or activate the RFID tag **306**. In another implementation, the tag **306** may comprise a transmitter and a power source configured to power the transmitter. For example, the tag **306** may comprise a Bluetooth Low Energy (BLE) transmitter and battery. In other implementations, the tag **306** may use other techniques to indicate presence of the tag **306**. For example, an acoustic tag **306** may be configured to generate an ultrasonic signal **308**, which is detected by corresponding acoustic receivers. In yet another implementation, the tag **306** may be configured to emit an optical signal **308**.

The inventory management system **216** may be configured to use the tags **306** for one or more of identification of the object, determining a location of the object, and so forth. For example, the users **116** may wear tags **306**, the totes **214** may have tags **306** affixed, and so forth, which may be read and, based at least in part on signal strength, used to determine identity and location.

Generally, the inventory management system **216** or other systems associated with the facility **202** may include any number and combination of input components, output components, and servers **304**.

The one or more sensors **114** may be arranged at one or more locations within the facility **202**. For example, the sensors **114** may be mounted on or within a floor, wall, at a ceiling, at an inventory location **212**, on a tote **214**, may be carried or worn by a user **116**, and so forth.

The sensors **114** may include one or more cameras **114(1)** or other imaging sensors. The one or more cameras **114(1)** may include imaging sensors configured to acquire images of a scene. The cameras **114(1)** are configured to detect light in one or more wavelengths including, but not limited to, terahertz, infrared, visible, ultraviolet, and so forth. The cameras **114(1)** may comprise charge coupled devices (CCD), complementary metal oxide semiconductor (CMOS) devices, microbolometers, and so forth. The inventory management system **216** may use image data acquired by the cameras **114(1)** during operation of the facility **202**. For example, the inventory management system **216** may identify items **112**, users **116**, totes **214**, and so forth, based at least in part on their appearance within the image data acquired by the cameras **114(1)**. The cameras **114(1)** may be mounted in various locations within the facility **202**. For example, cameras **114(1)** may be mounted overhead, on inventory locations **212**, may be worn or carried by users **116**, may be affixed to totes **214**, and so forth.

One or more 3D sensors **114(2)** may also be included in the sensors **114**. The 3D sensors **114(2)** are configured to acquire spatial or 3D data, such as depth information, about objects within a FOV **224** of a sensor **114**. The 3D sensors **114(2)** may include range cameras, lidar systems, sonar systems, radar systems, structured light systems, stereo vision systems, optical interferometry systems, and so forth. The inventory management system **216** may use the 3D data acquired by the 3D sensors **114(2)** to identify objects, determine a location of an object in 3D real space, and so forth.

## 12

One or more buttons **114(3)** may be configured to accept input from the user **116**. The buttons **114(3)** may comprise mechanical, capacitive, optical, or other mechanisms. For example, the buttons **114(3)** may comprise mechanical switches configured to accept an applied force from a touch of the user **116** to generate an input signal. The inventory management system **216** may use data from the buttons **114(3)** to receive information from the user **116**. For example, the tote **214** may be configured with a button **114(3)** to accept input from the user **116** and send information indicative of the input to the inventory management system **216**.

The sensors **114** may include one or more touch sensors **114(4)**. The touch sensors **114(4)** may use resistive, capacitive, surface capacitance, projected capacitance, mutual capacitance, optical, Interpolating Force-Sensitive Resistance (IFSR), or other mechanisms to determine the position of a touch or near-touch. For example, the IFSR may comprise a material configured to change electrical resistance responsive to an applied force. The location within the material of that change in electrical resistance may indicate the position of the touch. The inventory management system **216** may use data from the touch sensors **114(4)** to receive information from the user **116**. For example, the touch sensor **114(4)** may be integrated with the tote **214** to provide a touchscreen with which the user **116** may select from a menu one or more particular items **112** for picking, enter a manual count of items **112** at an inventory location **212**, and so forth.

One or more microphones **114(5)** may be configured to acquire information indicative of sound present in the environment. In some implementations, arrays of microphones **114(5)** may be used. These arrays may implement beam-forming techniques to provide for directionality of gain. The inventory management system **216** may use the one or more microphones **114(5)** to acquire information from acoustic tags **306**, accept voice input from the users **116**, determine ambient noise level, and so forth.

One or more weight sensors **114(6)** are configured to measure the weight of a load, such as the item **112**, the user **116**, the tote **214**, and so forth. The weight sensors **114(6)** may be configured to measure the weight of the load at one or more of the inventory locations **212**, the tote **214**, on the floor of the facility **202**, and so forth. For example, the shelf **104** may include a plurality of lanes **108** or platforms, with one or more weight sensors **114(6)** beneath each one to provide weight sensor data **220** about an individual lane **108**. The weight sensors **114(6)** may include one or more sensing mechanisms to determine the weight of a load. These sensing mechanisms may include piezoresistive devices, piezoelectric devices, capacitive devices, electromagnetic devices, optical devices, potentiometric devices, microelectromechanical devices, and so forth. The sensing mechanisms of weight sensors **114(6)** may operate as transducers that generate one or more signals based on an applied force, such as that of the load due to gravity. For example, the weight sensor **114(6)** may comprise a load cell having a strain gauge and a structural member that deforms slightly when weight is applied. By measuring a change in the electrical characteristic of the strain gauge, such as capacitance or resistance, the weight may be determined. In another example, the weight sensor **114(6)** may comprise a force sensing resistor (FSR). The FSR may comprise a resilient material that changes one or more electrical characteristics when compressed. For example, the electrical resistance of a particular portion of the FSR may decrease as the particular portion is compressed. The inventory man-

## 13

agement system **216** may use the data acquired by the weight sensors **114(6)** to identify an object, determine a change in the quantity of objects, determine a location of an object, maintain shipping records, and so forth.

The sensors **114** may include one or more optical sensors **114(7)**. The optical sensors **114(7)** may be configured to provide data indicative of one or more of color or intensity of light impinging thereupon. For example, the optical sensor **114(7)** may comprise a photodiode and associated circuitry configured to generate a signal or data indicative of an incident flux of photons. As described below, the optical sensor array **114(13)** may comprise a plurality of the optical sensors **114(7)**. For example, the optical sensor **114(7)** may comprise an array of ambient light sensors such as the ISL76683 as provided by Intersil Corporation of Milpitas, Calif., USA, or the MAX44009 as provided by Maxim Integrated of San Jose, Calif., USA. In other implementations, other optical sensors **114(7)** may be used. The optical sensors **114(7)** may be sensitive to one or more of infrared light, visible light, or ultraviolet light. For example, the optical sensors **114(7)** may be sensitive to infrared light, and infrared light sources such as LEDs may provide illumination.

The optical sensors **114(7)** may include photodiodes, photoresistors, photovoltaic cells, quantum dot photoconductors, bolometers, pyroelectric infrared detectors, and so forth. For example, the optical sensor **114(7)** may use germanium photodiodes to detect infrared light.

One or more radio frequency identification (RFID) readers **114(8)**, near field communication (NFC) systems, and so forth, may be included as sensors **114**. For example, the RFID readers **114(8)** may be configured to read the RF tags **306**. Information acquired by the RFID reader **114(8)** may be used by the inventory management system **216** to identify an object associated with the RF tag **306** such as the item **112**, the user **116**, the tote **214**, and so forth. For example, based on information from the RFID readers **114(8)** detecting the RF tag **306** at different times and RFID readers **114(8)** having different locations in the facility **202**, a velocity of the RF tag **306** may be determined.

One or more RF receivers **114(9)** may also be included as sensors **114**. In some implementations, the RF receivers **114(9)** may be part of transceiver assemblies. The RF receivers **114(9)** may be configured to acquire RF signals **308** associated with Wi-Fi, Bluetooth, ZigBee, 3G, 4G, LTE, or other wireless data transmission technologies. The RF receivers **114(9)** may provide information associated with data transmitted via radio frequencies, signal strength of RF signals **308**, and so forth. For example, information from the RF receivers **114(9)** may be used by the inventory management system **216** to determine a location of an RF source, such as a communication interface onboard the tote **214**.

The sensors **114** may include one or more accelerometers **114(10)**, which may be worn or carried by the user **116**, mounted to the tote **214**, and so forth. The accelerometers **114(10)** may provide information such as the direction and magnitude of an imposed acceleration. Data such as rate of acceleration, determination of changes in direction, speed, and so forth, may be determined using the accelerometers **114(10)**.

A gyroscope **114(11)** may provide information indicative of rotation of an object affixed thereto. For example, the tote **214** or other objects may be equipped with a gyroscope **114(11)** to provide data indicative of a change in orientation of the object.

A magnetometer **114(12)** may be used to determine an orientation by measuring ambient magnetic fields, such as

## 14

the terrestrial magnetic field. The magnetometer **114(12)** may be worn or carried by the user **116**, mounted to the tote **214**, and so forth. For example, the magnetometer **114(12)** mounted to the tote **214** may act as a compass and provide information indicative of which direction the tote **214** is oriented.

An optical sensor array **114(13)** may comprise one or more optical sensors **114(7)**. The optical sensors **114(7)** may be arranged in a regular, repeating, or periodic two-dimensional arrangement such as a grid. The optical sensor array **114(13)** may generate image data. For example, the optical sensor array **114(13)** may be arranged within or below an inventory location **212** and obtain information about shadows of items **112**, hand of the user **116**, and so forth.

The sensors **114** may include proximity sensors **114(14)** used to determine presence of an object, such as the user **116**, the tote **214**, and so forth. The proximity sensors **114(14)** may use optical, electrical, ultrasonic, electromagnetic, or other techniques to determine a presence of an object. In some implementations, the proximity sensors **114(14)** may use an optical emitter and an optical detector to determine proximity. For example, an optical emitter may emit light, a portion of which may then be reflected by the object back to the optical detector to provide an indication that the object is proximate to the proximity sensor **114(14)**. In other implementations, the proximity sensors **114(14)** may comprise a capacitive proximity sensor **114(14)** configured to provide an electrical field and determine a change in electrical capacitance due to presence or absence of an object within the electrical field.

The proximity sensors **114(14)** may be configured to provide sensor data indicative of one or more of a presence or absence of an object, a distance to the object, or characteristics of the object. An optical proximity sensor **114(14)** may use time-of-flight (ToF), structured light, interferometry, or other techniques to generate the distance data. For example, ToF determines a propagation time (or “round-trip” time) of a pulse of emitted light from an optical emitter or illuminator that is reflected or otherwise returned to an optical detector. By dividing the propagation time in half and multiplying the result by the speed of light in air, the distance to an object may be determined. In another implementation, a structured light pattern may be provided by the optical emitter. A portion of the structured light pattern may then be detected on the object using an imaging sensor **114(1)** such as a camera. Based on an apparent distance between the features of the structured light pattern, the distance to the object may be calculated. Other techniques may also be used to determine distance to the object. In another example, the color of the reflected light may be used to characterize the object, such as skin, clothing, tote **214**, and so forth.

In some implementations, a proximity sensor **114(14)** may be installed at the inventory location **212**. The non-weight sensor data **222** generated by the proximity sensor **114(14)** may be used in conjunction with the weight sensor data **220** as described in this disclosure. For example, the optical proximity sensor **114(14)** may determine that the user **116** is within a threshold distance of an inventory location **212**. Based on this non-weight sensor data **222**, the inventory management system **216** may generate activity data indicative of that presence. By using the activity data, the inventory management system **216** may determine that the weight sensor data **220** is reliable and subsequently use changes in the weight sensor data **220** to change the item data **226** indicative of a quantity on hand.

The sensors **114** may include other sensors **114(S)** as well. For example, the other sensors **114(S)** may include light curtains, ultrasonic rangefinders, thermometers, barometric sensors, hygrometers, and so forth. For example, the inventory management system **216** may use information acquired from thermometers and hygrometers in the facility **202** to direct the user **116** to check on delicate items **112** stored in a particular inventory location **212**, which is overheating, too dry, too damp, and so forth.

In one implementation, the light curtain may utilize a linear array of light emitters and a corresponding linear array of light detectors. For example, the light emitters may comprise a line of infrared light emitting diodes (LEDs) or vertical cavity surface emitting lasers (VCSELs) that are arranged above a top shelf in front of the inventory location **212**, while the light detectors comprise a line of photodiodes sensitive to infrared light arranged below the light emitters. The light emitters produce a “lightplane” or sheet of infrared light that is then detected by the light detectors. An object passing through the lightplane may decrease the amount of light falling upon the light detectors. For example, the user’s **116** hand would prevent at least some of the light from light emitters from reaching a corresponding light detector. As a result, a position along the linear array of the object may be determined that is indicative of a touchpoint. This position may be expressed as touchpoint data, with the touchpoint being indicative of the intersection between the hand of the user **116** and the sheet of infrared light. In some implementations, a pair of light curtains may be arranged at right angles relative to one another to provide two-dimensional touchpoint data indicative of a position of touch in a plane.

The other sensors **114(S)** may also include an instrumented auto-facing unit (AFU). The instrumented AFU may comprise a position sensor configured to provide data indicative of displacement of a pusher. As an item **112** is removed from the auto-facing unit, the pusher moves, such as under the influence of a spring, and pushes the remaining items **112** in the auto-facing unit to the front of the inventory location **212**. By using data from the position sensor, and given item data **226** such as a depth of an individual item **112**, a count may be determined, based on a change in position data. For example, if each item **112** is 1 inch deep, and the position data indicates a change of 3 inches, the quantity held by the AFU may have changed by 3 items **112**.

In some implementations, the camera **114(1)** or other sensors **114** may include hardware processors, memory, and other elements configured to perform various functions. For example, the cameras **114(1)** may be configured to generate image data, send the image data to another device such as the server **304**, and so forth.

The facility **202** may include one or more access points **310** configured to establish one or more wireless networks. The access points **310** may use Wi-Fi, NFC, Bluetooth, or other technologies to establish wireless communications between a device and the network **302**. The wireless networks allow the devices to communicate with one or more of the sensors **114**, the inventory management system **216**, the optical sensor arrays **114(13)**, the tag **306**, a communication device of the tote **214**, or other devices.

Audio output devices **312** may also be provided in the facility **202**. The audio output devices **312** are configured to generate signals, which may be perceived by the user **116** or detected by the sensors **114**. In some implementations, the audio output devices **312** may be used to provide illumination of the optical sensor array **114(13)**.

Haptic output devices **312(1)** are configured to provide a signal that results in a tactile sensation to the user **116**. The

haptic output devices **312(1)** may use one or more mechanisms such as electrical stimulation or mechanical displacement to provide the signal. For example, the haptic output devices **312(1)** may be configured to generate a modulated electrical signal, which produces an apparent tactile sensation in one or more fingers of the user **116**. In another example, the haptic output devices **312(1)** may comprise piezoelectric or rotary motor devices configured to provide a vibration, which may be felt by the user **116**.

One or more audio output devices **312(2)** may be configured to provide acoustic output. The acoustic output includes one or more of infrasonic sound, audible sound, or ultrasonic sound. The audio output devices **312(2)** may use one or more mechanisms to generate the acoustic output. These mechanisms may include, but are not limited to, the following: voice coils, piezoelectric elements, magnetostrictive elements, electrostatic elements, and so forth. For example, a piezoelectric buzzer or a speaker may be used to provide acoustic output.

The display devices **312(3)** may be configured to provide output, which may be seen by the user **116** or detected by a light-sensitive sensor such as a camera **114(1)** or an optical sensor **114(7)**. In some implementations, the display devices **312(3)** may be configured to produce output in one or more of infrared, visible, or ultraviolet light. The output may be monochrome or color.

The display devices **312(3)** may be emissive, reflective, or both. An emissive display device **312(3)**, such as using LEDs, is configured to emit light during operation. In comparison, a reflective display device **312(3)**, such as using an electrophoretic element, relies on ambient light to present an image. Backlights or front lights may be used to illuminate non-emissive display devices **312(3)** to provide visibility of the output in conditions where the ambient light levels are low.

The display devices **312(3)** may include, but are not limited to, microelectromechanical systems (MEMS), spatial light modulators, electroluminescent displays, quantum dot displays, liquid crystal on silicon (LCOS) displays, cholesteric displays, interferometric displays, liquid crystal displays (LCDs), electrophoretic displays, and so forth. For example, the display device **312(3)** may use a light source and an array of MEMS-controlled mirrors to selectively direct light from the light source to produce an image. These display mechanisms may be configured to emit light, modulate incident light emitted from another source, or both. The display devices **312(3)** may operate as panels, projectors, and so forth.

The display devices **312(3)** may be configured to present images. For example, the display device **312(3)** may comprise an addressable display **312(3)(1)**. The addressable display **312(3)(1)** may comprise elements that may be independently addressable to produce output, such as pixels. For example, the addressable display **312(3)(1)** may produce an image using a two-dimensional array of pixels.

In some implementations, the display devices **312(3)** may be configured to provide non-image data, such as text characters, colors, and so forth. For example, an addressable display **312(3)(1)** may comprise a segmented electrophoretic display device **312(3)**, segmented LED, and so forth, and may be used to present information such as a stock keeping unit (SKU) number, quantity on hand, and so forth. The display devices **312(3)** may also be configurable to vary the color of the segment, such as using multicolor/multi-wavelength LED segments.

The display devices **312(3)** may include image projectors **312(3)(2)**. For example, the image projector **312(3)(2)** may

be configured to project an image onto objects, illuminate at least a portion of an optical sensor array **114(13)**, and so forth. The image may be generated using MEMS, LCOS, and so forth.

The display devices **312(3)** may include a light array **312(3)(3)**. The light array **312(3)(3)** may comprise a plurality of discrete emissive elements configurable to emit light. The discrete emissive elements (or assemblies thereof) may be separated from one another by a distance such that, when image data of the light array **312(3)(3)** is acquired, one emissive element may be distinguished from another. For example, the light array **312(3)(3)** may comprise a plurality of infrared LEDs separated by at least 0.5 centimeters.

Other display devices **312(3)(D)** may also be used in the facility **202**. The display devices **312(3)** may be located at various points within the facility **202**. For example, the addressable displays **312(3)(1)** or the light arrays **312(3)(3)** may be located on inventory locations **212**, totes **214**, in or on the floor of the facility **202**, and so forth.

Other output devices **312(P)** may also be present. For example, the other output devices **312(P)** may include scent/odor dispensers, document printers, 3D printers or fabrication equipment, and so forth.

FIG. 4 illustrates a block diagram **400** of a server **304** configured to support operation of the facility **202**, according to some implementations. The server **304** may be physically present at the facility **202**, may be accessible by the network **302**, or a combination of both. The server **304** does not require end-user knowledge of the physical location and configuration of the system that delivers the services. Common expressions associated with the server **304** may include “on-demand computing”, “software as a service (SaaS)”, “platform computing”, “network-accessible platform”, “cloud services”, “data centers”, and so forth. Services provided by the server **304** may be distributed across one or more physical or virtual devices.

One or more power supplies **402** may be configured to provide electrical power suitable for operating the components in the server **304**. The one or more power supplies **402** may comprise batteries, capacitors, fuel cells, photovoltaic cells, wireless power receivers, conductive couplings suitable for attachment to an external power source such as provided by an electric utility, and so forth. The server **304** may include one or more hardware processors **404** (processors) configured to execute one or more stored instructions. The processors **404** may comprise one or more cores. One or more clocks **406** may provide information indicative of date, time, ticks, and so forth. For example, the processor **404** may use data from the clock **406** to associate a particular interaction with a particular point in time.

The server **304** may include one or more communication interfaces **408** such as input/output (I/O) interfaces **410**, network interfaces **412**, and so forth. The communication interfaces **408** enable the server **304**, or components thereof, to communicate with other devices or components. The communication interfaces **408** may include one or more I/O interfaces **410**. The I/O interfaces **410** may comprise Inter-Integrated Circuit (I2C), Serial Peripheral Interface bus (SPI), Universal Serial Bus (USB) as promulgated by the USB Implementers Forum, RS-232, and so forth.

The I/O interface(s) **410** may couple to one or more I/O devices **414**. The I/O devices **414** may include input devices such as one or more of a sensor **114**, keyboard, mouse, scanner, and so forth. The I/O devices **414** may also include output devices **312** such as one or more of a display device **312(3)**, printer, audio speakers, and so forth. In some

embodiments, the I/O devices **414** may be physically incorporated with the server **304** or may be externally placed.

The network interfaces **412** may be configured to provide communications between the server **304** and other devices, such as the totes **214**, routers, access points **310**, and so forth. The network interfaces **412** may include devices configured to couple to personal area networks (PANs), local area networks (LANs), wide area networks (WANs), and so forth. For example, the network interfaces **412** may include devices compatible with Ethernet, Wi-Fi, Bluetooth, Zig-Bee, and so forth.

The server **304** may also include one or more busses or other internal communications hardware or software that allow for the transfer of data between the various modules and components of the server **304**.

As shown in FIG. 4, the server **304** includes one or more memories **416**. The memory **416** may comprise one or more non-transitory computer-readable storage media (CRSM). The CRSM may be any one or more of an electronic storage medium, a magnetic storage medium, an optical storage medium, a quantum storage medium, a mechanical computer storage medium, and so forth. The memory **416** provides storage of computer-readable instructions, data structures, program modules, and other data for the operation of the server **304**. A few example functional modules are shown stored in the memory **416**, although the same functionality may alternatively be implemented in hardware, firmware, or as a system on a chip (SOC).

The memory **416** may include at least one operating system (OS) module **418**. The OS module **418** is configured to manage hardware resource devices such as the I/O interfaces **410**, the I/O devices **414**, the communication interfaces **408**, and provide various services to applications or modules executing on the processors **404**. The OS module **418** may implement a variant of the FreeBSD operating system as promulgated by the FreeBSD Project; other UNIX or UNIX-like variants; a variation of the Linux operating system as promulgated by Linus Torvalds; the Windows operating system from Microsoft Corporation of Redmond, Wash., USA; and so forth.

Also stored in the memory **416** may be a data store **420** and one or more of the following modules. These modules may be executed as foreground applications, background tasks, daemons, and so forth. The data store **420** may use a flat file, database, linked list, tree, executable code, script, or other data structure to store information. In some implementations, the data store **420** or a portion of the data store **420** may be distributed across one or more other devices including the servers **304**, network attached storage devices, and so forth.

A communication module **422** may be configured to establish communications with one or more of the totes **214**, sensors **114**, display devices **312(3)**, other servers **304**, or other devices. The communications may be authenticated, encrypted, and so forth.

The memory **416** may store an inventory management module **424**. The inventory management module **424** is configured to provide the inventory functions as described herein with regard to the inventory management system **216**. For example, the inventory management module **424** may track items **112** between different inventory locations **212**, to and from the totes **214**, and so forth.

The inventory management module **424** may include one or more of a data acquisition module **426** or a processing module **428**. The data acquisition module **426** may be configured to acquire and access information associated with operation of the facility **202**. For example, the data acqui-

sition module 426 may be configured to acquire sensor data 218 from one or more of the sensors 114. This information may be stored in the data store 420 as part of the sensor data.

The processing module 428 may be configured to use one or more of sensor data 218, item data 226, physical layout data 228, threshold data 430, or other information to generate intermediate data 432. The intermediate data 432 may comprise information such as measured weight characteristics, cluster data indicative of clusters of lanes, gap lane data indicative of gaps between lanes on the shelf 104, and so forth. The intermediate data 432 may be dynamic in that it changes over time.

The processing module 428 may generate hypotheses data 434 or may access previously generated hypotheses data 434. The processing module 428 may then use one or more of the sensor data 218, the intermediate data 432, or the hypotheses data 434 to generate the interaction data 230.

The threshold data 430 may comprise one or more thresholds associated with operation of the processing module 428. For example, the threshold data 430 may specify a tolerance or an accepted extent of deviation permitted between a predicted value of a hypothesis and the measured sensor data 218. In another example, the threshold data 430 may include a threshold indicating a minimum count of pixels that, if different, designate a change has occurred in image data. The threshold data 430 may include other thresholds, such as an interaction threshold period, minimum weight change deemed significant, and so forth. In some implementations, the threshold data 430 may include constraint data, such as described below that may be used to constrain the hypotheses data 434.

The hypotheses data 434 may comprise the predicted values for weight characteristics for particular combinations of variables that may affect weight characteristic data. The variables may include quantities of items 112, position at the particular inventory location 212, and so forth. In some implementations, the hypotheses data 434 may be at least partially precomputed based on the item data 226 and the physical layout data 228. A hypothesis in the hypotheses data 434 may include combinations of items 112 that are adjacent to one another.

The hypotheses data 434 may comprise a data structure with information such as:

Hypothesis 1=Quantity of 3 cans of pet food SKU #12345 removed from a position on the shelf 104 that spans lanes 13 and 14, exhibits a total weight change of 910 grams, with a weight change of -455 grams on lane 13 and -455 grams lane 14.

Hypothesis 3=Quantity of 0 cans of pet food SKU #12345 removed from a position on the shelf 104 that spans lanes 13 and 14 on the shelf 104 and quantity of 3 cans of pet food SKU #67890 removed from a position on the shelf 104 that spans lanes 14 and 15, exhibits a total weight change of 905 grams, with a weight change of -320 grams on lane 14 and -585 grams on lane 15.

In some implementations, the hypotheses data 434 may be constrained. For example, the hypotheses data 434 may exclude situations such as a simultaneous pick and place in the same interaction, simultaneous removal of different types of items 112 from different positions on the shelf 104, interactions involving a minimum or maximum number of items 112, and so forth. In another example, the hypotheses data 434 may exclude hypotheses that include different types of items within a single lane. For example, two different types of lipstick designated by different item identifiers may not be supported by the same single lane on the shelf 104. These exclusions may be specified due to operator prefer-

ence, based on usage patterns of the users 116, and so forth. Continuing the example, constraint data may be provided that limits the hypotheses data 434 to those hypotheses that do not have predicted quantities exceeding the stowage capacity of the inventory location 212, a particular number of lanes, and so forth. For example, the constraint data may be used to limit the hypotheses that are generated or included in the hypotheses data 434. In other implementations, the constraint data may be used to disregard particular hypotheses present in the hypotheses data 434 from further consideration. For example, a hypothesis having a predicted value or a value based on a predicated value that exceeds a threshold specified by the constraint data may be disregarded and not used to determine a solution.

By using the sensor data 218, a particular hypothesis may be selected from the hypotheses data 434 and deemed to be true or accurate given the information available. The information from the selected hypothesis may then be used to generate the interaction data 230. This interaction data 230 may be used to change item data 226 (such as quantity on hand), track objects, and so forth. For example, based on the weight sensor data 220 indicating a measured change in weight of -455 g at lane 13 and -447 g at lane 14, and a weight change of 902 g, hypotheses 1 may be determined to be correct, within the tolerance of error specified by the threshold data 430. The other hypotheses may be disregarded as the weight changes measured by the lanes differ from those presented in hypotheses beyond the tolerance of error. In some implementations, the hypotheses may be scored with a score indicative of deviation or variance from the predicted values of the hypothesis as compared to the measured values. In other implementations, selection of the solution from among hypotheses that describe similar weight characteristics may be disambiguated using the non-weight sensor data 222.

Continuing the example, with hypothesis 1 being deemed the solution, the interaction data 230 generated may indicate that 3 cans of pet food having SKU #12345 were removed from the particular location on the shelf 104. The quantity on hand at that location may be decreased accordingly, and the quantity determined to be in possession of the user 116 may be increased accordingly.

Operation of the processing module 428 and the various data involved including the intermediate data 432, the hypotheses data 434, the interaction data 230, and so forth, is discussed in more detail below.

Processing of the sensor data 218, intermediate data 432, or other data may be performed by the processing module 428 or other modules implementing, at least in part, one or more of the following tools or techniques. In one implementation, processing of the non-weight sensor data 222 such as images acquired by the cameras 114(1) may be performed, at least in part, using one or more tools available in the OpenCV library as developed by Intel Corporation of Santa Clara, Calif., USA; Willow Garage of Menlo Park, Calif., USA; and Itseez of Nizhny Novgorod, Russia, with information available at [www.opencv.org](http://www.opencv.org). In another implementation, functions available in the OKAO machine vision library as promulgated by Omron Corporation of Kyoto, Japan, may be used to process the sensor data 218.

Techniques such as artificial neural networks (ANN), active appearance models (AAM), active shape models (ASM), principal component analysis (PCA), cascade classifiers, and so forth, may also be used to process the sensor data 218 or other data. For example, the ANN may be a trained using a supervised learning algorithm such that object identifiers are associated with images of particular

objects within training images provided to the ANN. Once trained, the ANN may be provided with the sensor data **218** such as the non-weight sensor data **222** comprising image data from a camera **114(1)**, and so forth, and may provide, as output, the object identifier. Likewise, the ANN may be used to process the weight sensor data **220**.

The processing module **428** may also process the non-weight sensor data **222**, such as the images, using one or more machine vision counting techniques to determine a count of the items **112**. For example, machine vision counting techniques may be configured to identify a top portion of the items **112** as acquired from a camera **114(1)** that is looking down on the shelf **104** holding the items **112**. This determination may be based on item data **226**, such as previously acquired images of a sampled item **112**. Each of the tops of the type of item **112** appearing in a frame may be identified, and a count made. A change in count may be determined based on image data obtained at a first time and image data obtained at a second time.

Other modules **436** may also be present in the memory **416** as well as other data **438** in the data store **420**. For example, the other modules **436** may include an accounting module while the other data **438** may include billing data. The accounting module may be configured to assess charges to accounts associated with particular users **116** or other entities, while the billing data may include information such as payment account numbers.

FIG. **5** is a block diagram **500** of additional data that may be used by the server **304** to support operation of the facility **202**, according to some implementations. This data may be stored at least in part by the data store **420**. As described above with regard to FIG. **4**, the inventory management module **424** may use the sensor data **218** to generate other information such as interaction data **230** indicative of what item **112** a user **116** has interacted with.

The processing module **428** may access the item data **226**. The item data **226** may include an item identifier **502**. The item identifier **502** may be used to distinguish one item **112** from another. For example, the item identifier **502** may include a SKU, Universal Product Code (UPC) number, and so forth. The items **112** that are of the same type may be referred to by the same item identifier **502**. For example, 550 grams cans of beef flavor Brand X dog food may be represented by the item identifier **502** value of "9811901181". In other implementations, non-fungible items **112** may each be provided with a unique item identifier **502** allowing each to be distinguished from one another.

The item data **226** may include one or more of item weight data **504**, item weight distribution **506**, and so forth. The item weight data **504** comprises information indicative of a weight of a single item **112**, or a package, kit, or other grouping considered to be a single item **112**. The item weight distribution **506** may indicate a relative position of a center-of-mass (COM) of the item **112**. For example, the item weight distribution **506** data may indicate the item **112** is heavier on the left than on the right.

The item data **226** may also include geometry data **508** such as size and shape of the item **112**. For example, the geometry data **508** may include the overall shape of an item **112**, such as a cuboid, sphere, cylinder, and so forth. The geometry data **508** may also include information such as length, width, depth, and so forth, of the item **112**. Dimensional information in the geometry data **508** may be measured in pixels, centimeters, inches, arbitrary units such as number of lanes, and so forth. The geometry data **508** may be for a single item **112**, or a package, kit, or other grouping considered to be a single item **112**.

The item data **226** may include one or more shelf location identifiers (IDs) **510**. The shelf location ID **510** is indicative of a particular area or volume of an inventory location **212** that is designated for stowage of the item **112**. For example, a single shelf **104** may be designated as several shelf locations, each with a different shelf location ID **510**. Each of the different shelf location IDs **510** may be associated with a particular area on the shelf **104** designated for storage of a particular type of item **112**. A single type of item **112** may be associated with a particular shelf location ID **510**, or in other implementations, more than one type of item **112** may be associated with the particular shelf location ID **510**.

The item data **226** may also include quantity data **512**. The quantity data **512** may comprise a count or value indicative of a number of items **112**. The count may be a measured or estimated value. The quantity data **512** may be associated with a particular shelf location ID **510**. For example, the same type of item **112** may be stored at different shelves **104** within the facility. In other implementations, the item data **226** may include other data, such as an image of the item **112**, point cloud data for the item **112**, and so forth.

The physical layout data **228** may provide information about how the facility **202** is physically configured, location of sensors **114** and fixtures in the facility **202**, and so forth. For example, physical layout data **228** may comprise information representative of a map or floor plan of the facility **202** with relative positions of inventory locations **212**, planogram data indicative of how items **112** are to be arranged at the inventory locations **212**, and so forth.

The physical layout data **228** may associate a particular shelf location ID **510** with other information such as physical location data **514**, lane identifiers **516**, sensor identifiers **518**, and so forth. The physical location data **514** provides information about where in the facility **202** the inventory location **212** is. For example, the physical location data **514** may specify a particular shelf **104** is located on a particular rack within a particular aisle **210**.

The lane identifier **516** is indicative of one or more lanes that are associated with the shelf location ID **510**. For example, the inventory location **212** where a particular type of item **112** is stowed may span lanes 5, 6, and 7. The physical layout data **228** may be used to determine the particular lane identifiers **516** associated with a particular location where a certain type of item **112** is stowed.

The physical layout data **228** may include sensor identifier **518** data. The sensor identifier **518** may be used to associate a particular sensor **114** with a particular location within the facility **202** or fixtures such as an inventory location **212**. For example, the physical layout data **228** may associate a weight sensor **114(6)** serial number 05182000 with lane identifier **516(16)** of shelf **104(47)** on aisle **210(3)**.

The sensor data **218** may also be stored in the data store **420**. The sensor data **218** may include a sensor identifier **518** comprising data indicative of a particular sensor **114**, such as a certain camera **114(1)**, weight sensor **114(6)**, and so forth. The sensor identifier **518** may be unique in the context of a particular inventory location **212**, aisle **210**, facility **202**, or globally across multiple facilities **202**.

The sensor data **218** may be generated or acquired by one or more of the sensors **114**. The sensor data **218** may include one or more of the sensor identifiers **518**, a timestamp **520**, weight sensor data **220**, non-weight sensor data **222**, or other data **522**. The timestamp **520** may comprise information indicative of a time when the sensor data **218** was acquired. For example, the timestamp **520** may be based at least in part on time data obtained from a clock onboard the sensor **114**, by the clock **406** on the server **304**, and so forth. The

inventory management module **424** may use the timestamp **520** to determine the interaction data **230**. For example, the weight sensor data **220** from different weight sensors **114(6)** may be processed to determine weight sensor data **220** that occurred contemporaneously, which may then be processed to determine the weight characteristic data **524** associated with an interaction.

As described above, the sensor data **218** may be broadly categorized as comprising weight sensor data **220** and non-weight sensor data **222**. For example, the weight sensor data **220** may comprise information obtained from one or more the weight sensors **114(6)**. Conversely, the non-weight sensor data **222** may comprise information obtained from the sensors **114** other than the weight sensors **114(6)**.

In some implementations, the non-weight sensor data **222** may comprise image data. The image data may be obtained from one or more sensors **114**, such as a camera **114(1)**, a 3D sensor **114(2)**, or an optical sensor array **114(13)**. The image data may comprise one or more pixels.

The sensor data **218** may include other data **522**. For example, other data **522** may comprise information indicative of operational status of the sensor **114**, error messages associated with the sensor **114**, and so forth.

As described above, the intermediate data **432** may be generated by the processing module **428** or by other modules. The intermediate data **432** may include weight characteristic data **524**. The weight characteristic data **524** may be predicted or measured. Predicted weight characteristic data **524** may be based on hypotheses data **434**. In comparison, measured weight characteristic data **524** may be generated based on the weight sensor data **220**. The inventory management module **424** may determine the weight characteristic data **524**. Alternatively, the determination of the weight characteristic data **524** may be performed at least partially on board the weight sensor **114(6)** or an associated device such as a controller.

The weight characteristic data **524** may include one or more of weight data **526**, weight change data **528**, weight distribution data **530**, and so forth. The weight data **526** is indicative of the weight of the load given a particular set of conditions or at a particular time. For example, predicted weight data **526** may be based on the conditions specified by the hypotheses data **434**, such as a predicted quantity and item weight data **504**. In another example, measured weight data **526** may indicate the weight at a particular lane at a particular time.

The weight change data **528** indicates a change in weight from a first condition to a second condition, or from a first time to a second time. For example, the first condition and the second condition may be specified in hypotheses data **434**, such as a predicted addition or removal of a particular type of item **112**. In another example, the weight change data **528** may be a net change in weight from the first time to the second time. The weight change data **528** may be determined on a per-lane basis, providing measured or predicted lane weight change data **528**.

The weight distribution data **530** provides information indicative of a distribution in weight as measured across two or more weight sensors **114(6)**. The weight distribution data **530** may be expressed as a measured weight at a particular weight sensor **114(6)**, a ratio or percentage of weight on a weight sensor **114(6)**, and so forth. For example, the weight distribution data **530** may be expressed as “3213 g left, 3214 g right”, as a dimensionless ratio such as “0.59 left, 0.41 right”, and so forth. The weight distribution data **530** may be predicted or measured. The weight distribution data **530** may provide data indicative of weight distribution as predicted or

measured by one or more of the weight sensors **114(6)**. For example, the weight distribution data **530** for a configuration in which a rectangular shelf **104** has a weight sensor **114(6)** at each of the four corners may have weight distribution data **530** corresponding to each of the corners. In another implementation, the weight distribution data **530** may indicate weight distribution across two or more adjacent lanes.

The weight distribution data **530** may provide data indicative of COM at a particular time or condition such as predicted by a hypothesis. For example, the weight distribution data **530** may indicate a COM, change in the COM from a first time to a second time, and so forth. A variety of techniques may be used to calculate the COM or center-of-gravity. The COM may be described as the point in space at which weighted position vectors relative to this point sum to zero. For example, the COM of a sphere is a point in the center of the sphere. In another example, the COM of a toroid is a point in the center of the toroid.

The intermediate data **432** may include other information such as cluster data **532**, gap lane data **534**, and so forth. The cluster data **532** comprises information indicative of a cluster of lanes. The cluster of lanes may include one or more lanes of the shelf **104** that are adjacent to one another and that experience a common change in one or more weight characteristic data **524**. For example, during a particular time, if lane 1 and lane 3 both exhibit weight change data **528** that exceeds the threshold value, the lanes may be deemed to be part of the same cluster. Clusters are described in more detail below with regard to FIG. 8. The gap lane data **534** provides information about lanes that separate two or more clusters. For example, a gap lane may comprise a lane that experienced no measured or predicted weight change that exceeded a threshold value. Gap lanes are described in more detail below with regard to FIG. 8.

The processing module **428** may access one or more of the sensor data **218**, the item data **226**, the physical layout data **228**, the intermediate data **432**, or other data to determine the interaction data **230**.

During operation, the weight sensor data **220** may be “tared” or zeroed out while the load on the lane measured by the weight sensors **114(6)** is in a stable state. Subsequent changes in the weight sensor data **220** may be used to produce the weight characteristic data **524**. For example, the weight change data **528** may be based on changes following a tare.

The processing module **428** or other modules may transform the weight characteristic data **524** from one form to another. For example, the weight data **526** from a plurality of lanes in the shelf **104** may be used to determine the weight distribution data **530**.

The processing module **428** may generate interaction data **230** using one or more of the sensor data **218**, the item data **226**, the physical layout data **228**, the intermediate data **432**, and so forth. The interaction data **230** may comprise one or more of an interaction type **536**, a shelf location ID **510**, an item identifier **502**, a quantity change **538**, and so forth.

The interaction type **536** may provide information about whether the interaction is determined to be a pick, place, touch, pick and place, and so forth. The processing module **428** may use the intermediate data **432** or other information such as the sensor data **218** to determine the interaction type **536**.

As described above, shelf location ID **510** provides information about where the interaction took place. For example, the shelf location ID **510** may indicate a particular area on a particular shelf **104** on a particular rack in a particular aisle **210**.



The item identifier **502** specifies the item **112** implicated by the interaction. For example, the item identifier **502** may indicate the item **112** that was picked, placed, touched, and so forth. In some implementations, the item identifier **502** may be determined at least in part by the weight sensor data **220**. For example, based on the weight characteristic data **524**, the particular item **112** may be identified, the quantity change **538** of the items **112** at the inventory location **212** resulting from the interaction may be determined, and so forth.

The quantity change **538** provides information indicative of a change in the quantity of the item **112** resulting from the interaction. For example, the quantity change **538** may indicate a value of “-1” when a single item **112** is picked from the inventory location **212**, or value of “+3” when three items **112** are placed into the inventory location **212**.

The item data **226** may provide information about an individual item **112**, while the interaction data **230** may comprise information about one or more of the items **112** that may be undergoing some change, such as movement from the inventory location **212** to the tote **214**.

In one implementation, the processing module **428** may generate other information about the items **112** stowed at the inventory location **212**. For example, the interaction data **230** may be analyzed to determine if a user **116** such as a person tasked with restocking the inventory location **212** is rotating stock such that old stock is brought to the front while new stock is placed behind.

FIG. 6 illustrates a side view **600** of an inventory location **212** that includes various sensors **114**, according to some implementations. In this illustration, the inventory location **212** comprises a shelf **104** mounted to a rack. In other implementations, the shelf **104** may be mounted on a surface, such as a table or counter.

One or more weight sensors **114(6)** may be used to obtain weight sensor data **220** from one or more lanes at the shelf **104**. The configuration of the shelf **104** is described in more detail below with regard to FIGS. 7-8.

One or more cameras **114(1)** may also be positioned at one or more of on, in the, or around the inventory locations **212**. For example, cameras **114(1)** may be arranged such that their FOV **224** looks on a shelf **104**. The cameras **114(1)** may be arranged at a front edge of the inventory location **212** such as closest to the aisle **210** during operation, at the back edge of the inventory location **212**, both at the front and back edges, overhead, and so forth. The cameras **114(1)**, weight sensors **114(6)**, and other sensors **114** may provide sensor data **218** to the inventory management module **424**.

FIG. 7 illustrates side views **700** of the shelf **104** of FIG. 6, according to some implementations. A first implementation **702** depicts a single weight sensor **114(6)** in the center of a lane **108**. A second implementation **704** depicts a single weight sensor **114(6)** at one end of a lane **108**. A third implementation **704** depicts a first weight sensor **114(6)(1)** at a first end of a lane **108** and a second weight sensor **114(6)(2)** at a second end of the lane **108**, such as depicted in FIG. 6. In the first implementation **702**, the single weight sensor **114(6)** may be arranged in a center of the lane **108**. In another implementation, such as that depicted in the second implementation **704**, the weight sensor data **220** may be obtained from a single weight sensor **114(6)** located at one end of the lane **108**, such as the front of the lane or the back of the lane **108**. In yet another implementation. In the third implementation **706**, the weight sensor data **220** obtained from a plurality of weight sensors **114(6)** coupled to a single lane **108** may be used to generate weight distribution data **530**.

In some situations, two or more weight sensors **114(6)** may be used in conjunction with one another at the same position along the support structure **710** between the front and the back of the lane **108**. For example, a pair of weight sensors **114(6)(1)** and **114(6)(2)** may be side-by-side on one end of the lane **108**.

The shelf **104** may comprise a resilient layer **708** upon which one or more of the items **112** may rest. The resilient layer **708** may comprise one or more of the foam, gel, elastomer, or other material or structure. The resilient layer **708** may allow for some mechanical deformation upon application of a force, such as the weight of an item **112**, and resumes substantially the same original shape after removal of the force. The resilient layer **708** may facilitate operation of the shelf **104** by accommodating the slight movement between adjacent lanes **108**. For example, as depicted in FIG. 6, weight of the larger and heavier items **112(4)** may deflect lanes 13 and 14 relative to lanes 12 and 15. The resilient layer **708** may help maintain stability of the items **112(5)** that have an edge resting on part of lane 14.

Support structure **710** provides underlying rigidity and a mechanical element to support the resilient layer **708** and the items **112** loaded thereon. The resilient layer **708** may be applied to, affixed to, integral with, or otherwise associated with the support structure **710**. For example, the support structure **710** may comprise a sheet of steel, a composite material, and so forth. The support structure **710** may incorporate one or more features to provide mechanical rigidity, such as ribs formed into or affixed to the sheet of steel.

The support structure **710** is in turn supported by one or more weight sensors **114(6)**, or structures coupled thereto. The one or more weight sensors **114(6)** are in turn supported by a shelf support **712**. The shelf support **712** may be coupled to another structure, such as a rack, backplane, countertop, and so forth.

Other types of weight sensors **114(6)** may be used instead of, or in addition to, the load cells described. For example, a force sensitive resistor (FSR) **114(6)** or other sensor **114** may be arranged atop the support structure **710**. In one implementation each of the lanes **108** may have a separate FSR **114(6)**. In another implementation, a single FSR **114(6)** may be divided into sections, with one or more sections covering a different lane **108**. For example, a single FSR **114(6)** covering the shelf **104** depicted in FIG. 1 may have 16 different sections, each section in a different lane **108**. In another example, each lane **108** may have two or more sections of the FSR **114(6)**.

FIG. 8 illustrates an overhead schematic view **800** of the shelf **104**, according to some implementations. To facilitate the discussion of FIGS. 9-10, FIG. 8 illustrates various elements.

As described above with regard to FIG. 6, the shelf **104** comprises 16 lanes **108** that are adjacent to one another. The lanes **108** number 1 through 16, left to right, with each lane **108** adjacent to at least one other lane **108**. Adjacent lanes **802** are two or more lanes **108** that are proximate to one another. For example, lane 1 and lane 3 are proximate to one another. Edges of adjacent lanes **802** may, but need not, be in contact with one another. For example, a gap or space may exist between the proximate edges of adjacent lanes **802**.

The shelf **104** may be subdivided into one or more shelf locations **804**. Each shelf location **804** may be associated with a particular shelf location ID **510**. In this illustration there are five shelf locations **804(1)-(5)**. Each shelf location **804** is an area designated for stowage of a particular type of item **112**. For example, the shelf location **804(1)** is desig-

nated for stowage of items **112(1)**, the shelf location **804(2)** is designated for stowage of items **112(2)**, the shelf location **804(3)** is designated for stowage of items **112(3)**, the shelf location **804(4)** is designated for stowage of items **112(4)**, and the shelf location **804(5)** is designated for stowage of items **112(5)**. The shelf locations **804** may not be defined by or separated using physical partitions. For example, in the configuration illustrated here, no partitions exist between the different types of items **112**. However, in other configurations, physical partitions or walls may be used on the shelf **104** to maintain a tidy arrangement of the items **112** on the shelf **104**.

During operation of the facility, items **112** may be added to or removed from the shelf locations **804** by interactions. These interactions may result in changes in the weight sensor data **220** generated by the weight sensors **114(6)**. One or more adjacent lanes **802** that exhibit measured weight changes that exceed a threshold may be designated as forming a cluster **806**. In the interaction depicted in this illustration, a quantity of one each of items **112(2)**, **112(3)**, and **112(5)** have been removed from the shelf **104** during an interaction. The corresponding lanes **108** supporting these items **112** exhibited changes in weight that exceed the threshold. Adjacent lanes **802** undergoing those changes are designated as clusters **806(2)**, **806(3)**, and **806(5)**, respectively. For example, lanes 5-8 form cluster **806(2)**, lane 10 forms a single-lane cluster **806(3)**, and lanes 14 and 15 form cluster **806(5)**. A shelf location **804** may encompass an area that is less than or equal to an area of the lanes **108** in a cluster **806**. For example, a shelf location **804** may use up less than all of a lane **108**.

The clusters **806** are separated from one another by one or more gap lanes **808**. In one implementation, gap lanes **808** may be based on measured weight characteristic data **524**. For example, those lanes **108** that have measured weight change data **528** that is less than the threshold may be designated as gap lanes **808**. In another implementation, the gap lanes **808** may be determined based on item data **226** and physical layout data **228**. For example, the gap lane **808** may be designated as an entire lane **108** that separates two lanes **108** that are designated as occupied at least in part by an item **112** based on the physical layout data **228**.

Each shelf location **804** has one or more edge lanes **810**. The edge lanes **810** comprise those outermost lanes **108** associated with the shelf location **804**, such as the extreme leftmost and extreme rightmost lanes **108** that are occupied by at least a portion of an item **112**. For lanes **108** located at either end of the shelf **104**, such as lane 1 or lane 16 in this illustration, a shelf location **804** may have only a single edge lane **810** that is toward the middle of the shelf **104**, such as lane 3 and lane 15, respectively. In other implementations, the edge lanes **810** may be relative to the cluster **806**. The edge lanes **810** may be determined for the shelf locations **804** associated with the items **112** present in particular hypotheses of the hypotheses data **434**.

Adjacent to each edge lane **810** may be a neighboring lane **812**. In some implementations neighboring lanes **812** may also be gap lanes **808**. The neighboring lane **812** may be designated as the lane **108** adjacent to the edge lane **810** but which is not associated with a particular item **112** or hypothesis. For example, relative to the group of items **112(2)** at the shelf location **804(2)**, lanes 5-8 are the cluster **806(2)**, lanes 5 and 8 are the edge lanes **810**, and the neighboring lanes **812** are 5 and 9.

A hypothesis in the hypotheses data **434** may include combinations of items **112** that are adjacent to one another. For example, a hypothesis in the hypotheses data **434** may

include predicted changes to quantities for each of the five different types of items **112** depicted on the shelf **104** at FIG. **8**, including those items **112** that did not show a change in weight characteristic data **524**, such as items **112(1)** and **112(4)**. However, various hypotheses may include different or particular combinations of changes in the predicted quantity of items **112(4)** and **112(5)** because they both are supported at least in part by lane 14. In some implementations, the cluster **806** may be extended to include a lane **108** that exhibited no change but for which an item **112** spans onto. For example, the cluster **806(5)** may include lanes 13-15, even though lane 13 reported no change in measured weight characteristic data **524**. Lane 13 may be included in the cluster **806(6)** because lane 13 provides support to an item **112(4)** that is also supported by lane 14 which did experience a change in measured weight characteristic data **524**. The predicted quantity change in hypotheses data **434** for these items **112** for which no change in measured weight characteristic data **524** was detected for the corresponding lanes may be zero. For example, the hypotheses data **434** may indicate a predicted quantity change of 0 for the item **112(4)** as no measured weight change data **528** was observed in lane 13.

By processing the sensor data **218** as described in FIGS. **9** and **10**, and assessing with respect to predicted values in one or more hypotheses of the hypotheses data **434**, the inventory management module **424** may be able to generate interaction data **230**. The interaction data **230** may then be used to update other information, such as the quantity data **512**.

#### Illustrative Processes

FIG. **9** depicts a flow diagram **900** of a process for determining interaction data **230** based on weight sensor data **220**, according to some implementations. The process may be implemented at least in part by the inventory management module **424**. In different implementations, one or more of the blocks described below may be omitted, the sequence of the process using these blocks may vary from that depicted, and so forth.

Block **902** accesses weight sensor data **220** acquired by a first weight sensor **114(6)** of a first lane **108(1)** and a second weight sensor **114(6)** of a second lane **108(2)**. For example, the shelf **104** may have two lanes **108(1)** and **108(2)**.

Block **904** determines weight characteristic data **524** for each of the lanes **108**. For example, measured lane weight change data **528** for the first lane **108(1)** and the second lane **108(2)** that is indicative of a change in weight from a first time to a second time may be determined. The measured change in weight may be determined by subtracting the measured weight data **526** obtained at the first time from the second time, or vice versa.

Block **906** determines a cluster **806** based on the measured weight change for each of the first lane **108(1)** and the second lane **108(2)**. For example, the cluster **806** may comprise any one or more adjacent lanes **108** that exhibit a measured lane weight change that exceeds a threshold. The determined cluster **806** may be stored as cluster data **532**. In some implementations, gap lane data **534** may also be determined.

Block **908** determines, using the weight sensor data **220**, a measured total weight change of the cluster **806**. For example, the measured lane weight change data **528** for the first lane **108(1)** and the second lane **108(2)** may be summed to determine the measured total weight change of the cluster **806**.

Block **910** determines item data **226** for each type of item **112** stowed at the cluster **806**. As described above, the item

data 226 may include one or more of an individual weight for each type of item 112 or a shelf location 804 of each type of item 112. As described above, the shelf location 804 is indicative of placement of the type of item 112 with respect to one or more of the first lane 108(1) or the second lane 108(2). For example, the shelf location 804 may indicate an area that is equally distributed across both lanes 108(1) and 108(2).

Block 912 determines a plurality of hypotheses. For example, previously computed hypotheses data 434 may be accessed, hypotheses data 434 may be generated on demand, or a combination of the two. Each hypothesis may be indicative of different combinations of one or more of a predicted quantity change for the one or more types of items 112 located at the cluster 806, predicted lane weight change data 528 for each of the lanes 108 at the cluster 806, and predicted total weight change data 528 of all lanes 108 in the cluster 806. The predicted lane weight change data 528, the predicted total weight change data 528, and so forth, may be based on parameters specified by a particular hypothesis. For example, the hypothesis may specify a predicted quantity change of one or more particular types of items 112. Based on information such as the item data 226 indicating the individual weight for each of the types of items 112 located at the cluster 806 and the physical layout data 228 providing information about shelf location 804 of each of the types of item 112, the predicted lane weight change data 528 and the predicted total weight change data 528 may be calculated. For example, if the shelf location 804 indicates that the items 112 are arranged 80% on the first lane 108(1) and 20% on the second lane 108(2), the predicted weight on each of the lanes 806 may be determined.

In some implementations, the plurality of hypotheses may be constrained to remove or disregard from consideration those hypotheses that are considered too different from the measured values. For example, for each of the hypotheses, a difference between the predicted total weight change and the measured total weight change may be determined. Those hypotheses having differences that exceed a threshold may be disregarded from further consideration. For example, the threshold may specify a difference between the predicted total weight change and the measured total weight change of less than 50 grams. Those hypotheses having a predicted total weight change greater than 50 grams may be disregarded from further consideration during the remainder of the process.

The plurality of hypotheses to be considered as potential solutions may be constrained in other ways as well. In one implementation, the hypotheses data 434 may be constrained such that predicted quantity changes for one or more types of items 112 located at the cluster 806 are less than or equal to a maximum storage capacity of the items 112 for the cluster 806. For example, the shelf location 804 that is at the cluster 806 may be designated as holding a maximum of 30 of the items 112. The maximum quantity may be specified as a default or calculated based on information such as the area available and the geometry data 508 of the item 112.

Block 914 determines, for each of the hypotheses in the hypotheses data 434 and for each of the lanes 108 in the cluster 806, a difference between the predicted lane weight change data 528 and the measured lane weight change data 528. For example, the predicted lane weight change data 528 may be subtracted from the measured lane weight change data 528.

Block 916 determines a score for each of the hypotheses based on a sum of the differences associated with that

hypothesis. For example, the differences for each of the lanes 108 in the cluster 806 may be summed together to determine the score for that hypothesis. In some implementations, other operations may be performed to produce the score. For example, a reciprocal of the summed value may be used to generate the score, such that a greater score is indicative of less deviation between the predicted and measured values.

Block 918 determine, based on the score for each hypothesis in the plurality of hypotheses, a change to quantity of the one or more items 112. Continuing the previous example, the hypothesis from the hypotheses data 434 that has the greatest score may be selected at the solution. The predicted values for the solution may then be designated indicative of the interaction. For example, the solution may comprise a hypothesis that indicates that 3 cans of pet food SKU #12345 were removed from a particular shelf location 804. The quantity data 512 in the item data 226 associated with that shelf location ID 510 may then be changed to decrease the quantity on hand at that shelf location 804 by 3.

FIG. 10 depicts a flow diagram 1000 of a process for determining an interaction with a particular item 112 based on weight sensor data, according to some implementations. The process may be implemented at least in part by the inventory management module 424. In different implementations, one or more of the blocks described below may be omitted, the sequence of the process using these blocks may vary from that depicted, and so forth.

Block 1002 accesses weight sensor data 220 acquired by a shelf 104 comprising a plurality of physically adjacent lanes 802 with weight sensors 114(6). As described above, each lane 108 may have one or more weight sensors 114(6).

A block may process the weight sensor data 220 to decrease noise in the weight sensor data 220. For example, "raw" or otherwise unprocessed or minimally processed weight sensor data 220 for a lane 108 may be filtered using an exponential moving average function to determine filtered weight sensor data 220. A block accesses a window length indicative of an interval of time. A block may access a portion of the filtered weight sensor data 220 having associated time values within a range of time values delineated by the window length. A block may use a linear regression to fit a straight line to the portion of the filtered weight sensor data 220. A block may determine a slope value of the line. A block may then determine one or more residuals, each residual comprising a difference between the filtered weight sensor data 220 at a particular time and the value of the straight line at the particular time. A block determines, based at least in part on one or more of the slope value of the line or the one or more residuals, a change in state of the weight of the lane 108. For example, the change in state may indicate a transition from an unperturbed state to a perturbed state, and vice versa.

Block 1004 determines measured weight characteristic data 524 for one or more of the lanes 108. As described above, the weight characteristic data 524 may include measured weight data 526, measured weight change data 528, measured weight distribution data 530, and so forth. In some implementations, the measured weight characteristic data 524 may be based on the weight sensor data 220 that has been processed and is thus filtered weight sensor data 220.

In implementations where each lane 108 includes a plurality of weight sensors 114(6), output from those sensors 114 may be aggregated to produce output representative of the entire lane 108. For example, the weight sensors 114(6)

(1) and 114(6)(2) that are in the same lane 108 may be summed to provide weight characteristic data 524 for that lane 108.

Block 1006 determines the lanes that are included in a cluster 806. For example, the processing module 428 may generate cluster data 532 indicative of those lanes that are included in the cluster 806 based on the measured lane weight change data 528. The cluster 806 may comprise any one or more adjacent lanes 802 that exhibit measured lane weight change data 528 that exceeds a threshold during a specified time period. For example, the threshold data 430 may specify that any measured lane weight change data 528 during a window of 300 milliseconds that is less than 10 grams is disregarded. The threshold may be fixed or dynamically adjustable. For example, the fixed threshold may be specified by an operator. In another example, a dynamically adjustable threshold may be time-dependent, such that a slowly accumulating change in measured lane weight change data 528 over several seconds may be disregarded, while the same measured lane weight change data 528 over 500 milliseconds may be considered. The determination of the cluster 806 may be omitted in some implementations. In other implementations, the determination of the cluster 806 may be based on previously stored data rather than measured lane weight change data 528.

In one implementation, the measured lane weight change data 528 for each of the lanes 108 in the cluster 806 may be summed to determine a measured total cluster weight change. The measured total cluster weight change may then be compared to a predicted total cluster weight change.

To improve accuracy of the system, the process may operate using weight sensor data 220 that is stable. For example, the measured weight characteristic data 524 may be determined based on weight sensor data 220 that is determined to be stable. In some implementations, stable weight sensor data 220 may be designated as weight sensor data 220 having values that exhibit changes below a threshold value over a specified time period. Changing weight sensor data 220 may result in the determination of the cluster 806 as described above. Detection of changes used to determine the cluster 806 may be at the level of individual lanes 108. In some implementations, the readings from a particular lane 108 may not be deemed to be stable until all of the lanes 108 within the same cluster 806 are stable. By determining stability for the cluster 806 as a whole, accuracy of the system may be improved to account for additional picks or places of items 112 that may occur at the facility 202.

Clusters 806 may change size. For example, a lane 108 may be added to an existing cluster 806 or may be designated as a new cluster 806. When an additional lane 108 is added to an existing cluster 806, the processing module 428 may check to determine if this additional lane 108 will link or connect to clusters 806 that were previously separated by one or more gap lanes 808. Two clusters 806 may thus merge into a single cluster 806. Similarly, one cluster 806 may be split into two separate clusters 806, or may be pruned into a smaller cluster 806 having fewer lanes 108 by removing one or more lanes 108.

By utilizing clusters 806, the processing module 428 is able to determine separate interactions occurring on the same shelf 104 but which occur contemporaneously in time. For example, a pick of the items 112(2) from cluster 806(2) may be determined independently of a pick of the items 112(5) from the cluster 806(5). The lanes 108 may require different times to settle due to different weights of the respective loads, geometry of the items 112 thereon, and so

forth. For example, as depicted in FIG. 8 the measured weight characteristic data 524 for lanes 14 and 15 may stabilize more quickly than the way characteristic data 524 for lanes 5-8. As a result, the interaction data 230 for the cluster 806(5) may be determined and available more quickly than that for the cluster 806(2).

Block 1008 determines item data 226 for one or more items 112 associated with the shelf 104. For example, the physical layout data 228 may be accessed, and the lane IDs 516 at the cluster 806 may be used to determine physical location data 514 that is at the cluster 806. Continuing the example, the physical location data 514 may then be used to determine the shelf location ID 510, which in turn may be used to access item data 226 about a particular type of item 112 that is stowed at the shelf 104. As described above in FIG. 8, in some implementations, one or more of the items 112 may be supported by two or more of the lanes 108. For example, the item 112(2) as illustrated in FIG. 8 is supported by lanes 5-8.

Block 1010 determines one or more hypotheses. For example, the hypotheses data 434 may be accessed from the data store 420. In one implementation, each hypothesis may be indicative of one or more of the following: different combinations of one or more types of items 112 at the cluster 806; different combinations of predicted quantity of each of the one or more types of items 112 at the cluster 806; a predicted total cluster weight that differs from the measured total cluster weight change by less than a second threshold; or a predicted lane weight change for each lane 108 at the cluster 806. The total cluster weight comprises a sum of the weights of individual lanes 108 at the cluster 806.

The hypotheses data 434 may be generated or retrieved subject to one or more constraints. In one implementation, constraint data may be accessed, and the plurality of hypotheses may be generated in accordance with the one or more constraints. For example, the constraints may specify a minimum and a maximum number of items 112 that may be assumed to be interacted with. The hypotheses data 434 may thus be limited to those predicted values corresponding to interactions involving the number of items 112 between the minimum and maximum. Other constraints may include, but are not limited to, situations such as a simultaneous pick and place in the same interaction, simultaneous removal from different shelf locations 804, and so forth. Hypotheses in the hypotheses data 434 that do not comply with the constraint data may be disregarded or removed.

In some implementations, the hypotheses data 434 that is undergoing consideration as possible solutions may be limited to hypotheses that describe changes to the items 112 at the cluster 806. For example, the hypotheses data 434 associated with the cluster 806(2) may include only changes in predicted quantities of items 112(2). In another example, the hypotheses data 434 associated with the cluster 806(5) may be limited to changes in predicted quantities of items 112(4) and 112(5).

Block 1012 determines a score for one or more of the one or more hypotheses. One or more of the following scoring modules may be implemented individually, or in combination, to determine the score.

A first scoring module may determine, for at least some of the hypotheses, a difference between the predicted lane weight change and the measured lane weight change for each lane 108 in the cluster 806. For each of the hypotheses, a score may be determined based on a sum of the differences associated with that hypothesis.

An edge penalty scorer module may be used to assist in determining scores to differentiate several potential hypoth-

eses. The edge penalty scorer module may perform one or more of the following actions.

A block determines the score for a plurality of the hypotheses is above a threshold. For example, the threshold may specify a minimum score, with that score for some of the hypotheses generated using the first scoring module described above may be used to make this assessment.

For each of the hypotheses with a score above the threshold, a block determines a first edge lane **810(1)** located at a first end of the cluster **806** and a second edge lane **810(2)** located at a second end of the cluster **806**.

A block determines a first neighboring lane **812(1)** adjacent to the first edge lane **810(1)** that is outside of the cluster **806**. A block determines a second neighboring lane **812(2)** adjacent to the second edge lane **810(2)** that is outside of the cluster **806**.

A block may then change the score for each of the hypotheses that appears to involve a situation where a neighboring lane **812** was involved in an interaction or a change was predicted but not measured. The block may change the score for each of the hypotheses that satisfy one or more of the following conditions: a measured lane weight of the first neighboring lane **812(1)** exceeds a fourth threshold; a measured lane weight of the second neighboring lane **812(2)** exceeds the fourth threshold; the predicted lane change weight for the first edge lane **810(1)** is greater than a fifth threshold and the measured lane weight of the first edge lane **810(1)** is below a sixth threshold; or the predicted lane change weight for the second edge lane **810(2)** is greater than the fifth threshold and the measured lane weight of the second edge lane **810(2)** is below the sixth threshold. The first two conditions address the situation where a change in a measured weight characteristic data **524** of a neighboring lane **812** is considered to be significant. The fourth, fifth, and sixth thresholds may specify a particular absolute value of weight, a percentage variance, and so forth. The latter two conditions address the situation where a significant change was predicted, but was not measured.

A penalized weight scorer module may be used to assist in determining scores to differentiate several potential hypotheses. For example, the scores may be indicative of a low confidence. The penalized weight scorer module may perform one or more of the following actions.

For each of the hypotheses, a block may determine a first set of one or more lanes **108** for which a predicted lane weight exceeds a threshold. A block determines a first sum of the measured lane weight changes for the lanes **108** in the first set. A block determines a difference between the first sum and the predicted total cluster weight. A block determines a second set of one or more lanes **108** that are part of the cluster **806** and not part of the first set. A block determines a second sum of the measured lane weight changes for the lanes **108** in the second set. A block determines a third sum of the difference and the second sum. A block determines a score for one or more of the hypotheses based on the third sum.

The penalized weight scorer module may not be used in some situations. For example, if a solution includes both picks and places, the penalized weight scorer may not be used. In another example, if the scores produced by the penalized weight scorer module are within a threshold difference of one another, scores produced by the penalized weight scorer module may be omitted.

In some implementations, the score may be based at least in part on the number of transactions that a particular hypothesis involves. In one implementation, a transaction may comprise one or more of a pick to decrease a quantity

of one of the one or more items **112** supported by the shelf **104**, or a place to increase the quantity. A block may determine, for each of the hypotheses, a number of transactions and a count of the number of transactions. The score may then be based on the count. For example, the larger the count of transactions, the lower the score.

Block **1014** determines a solution from the one or more hypotheses. For example, the hypothesis having a score indicative of a best match or closest correspondence between the predicted and the measured values may be designated as the solution.

Determination of the solution may be based on other factors. For example, other sensor data **218** such as the non-weight sensor data **222** may be processed to determine a quantity of one or more of addition or removal of an item **112** to the inventory location **212**. The determination of the solution may be based on the one of the selected hypotheses having a predicted quantity that is consistent with the determined one or more of addition or removal of an item **112**. Continuing the example, where the non-weight sensor data **222** indicates removal of an item **112**, the solution would be one of the selected hypotheses that represented a pick of the item **112**.

Block **1016** determines interaction data **230** based on the solution. In some implementations, the determination of the interaction data **230** may be responsive to detection of the change in state in the weight sensor data **220**, such as described above. For example, the interaction data **230** may be determined following a sequence of stable-unstable-stable for weight sensor data **220** provided by the shelf **104** or a portion thereof.

In one implementation, the interaction data **230** may be based on the solution. As described above, the interaction data **230** may be indicative of one or more of pick, place, touch, and so forth, of a particular quantity of an item **112** at the shelf **104** as described by the solution. For example, the interaction data **230** may be indicative of a change in quantity of one or more items **112** on the shelf **104**, based on the weight characteristic data **524** and the item data **226**.

The processes discussed herein may be implemented in hardware, software, or a combination thereof. In the context of software, the described operations represent computer-executable instructions stored on one or more non-transitory computer-readable storage media that, when executed by one or more processors, perform the recited operations. Generally, computer-executable instructions include routines, programs, objects, components, data structures, and the like that perform particular functions or implement particular abstract data types. Those having ordinary skill in the art will readily recognize that certain steps or operations illustrated in the figures above may be eliminated, combined, or performed in an alternate order. Any steps or operations may be performed serially or in parallel. Furthermore, the order in which the operations are described is not intended to be construed as a limitation.

Embodiments may be provided as a software program or computer program product including a non-transitory computer-readable storage medium having stored thereon instructions (in compressed or uncompressed form) that may be used to program a computer (or other electronic device) to perform processes or methods described herein. The computer-readable storage medium may be one or more of an electronic storage medium, a magnetic storage medium, an optical storage medium, a quantum storage medium, and so forth. For example, the computer-readable storage media may include, but is not limited to, hard drives, floppy diskettes, optical disks, read-only memories (ROMs), ran-

35

dom access memories (RAMs), erasable programmable ROMs (EPROMs), electrically erasable programmable ROMs (EEPROMs), flash memory, magnetic or optical cards, solid-state memory devices, or other types of physical media suitable for storing electronic instructions. Further, 5 embodiments may also be provided as a computer program product including a transitory machine-readable signal (in compressed or uncompressed form). Examples of transitory machine-readable signals, whether modulated using a carrier or unmodulated, include, but are not limited to, signals that 10 a computer system or machine hosting or running a computer program can be configured to access, including signals transferred by one or more networks. For example, the transitory machine-readable signal may comprise transmission of software by the Internet.

Separate instances of these programs can be executed on or distributed across any number of separate computer systems. Thus, although certain steps have been described as being performed by certain devices, software programs, processes, or entities, this need not be the case, and a variety of alternative implementations will be understood by those 15 having ordinary skill in the art.

Additionally, those having ordinary skill in the art readily recognize that the techniques described above can be utilized in a variety of devices, environments, and situations. 25 Although the subject matter has been described in language specific to structural features or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as illustrative forms of implementing the claims.

What is claimed is:

1. A system comprising:

a first lane and a second lane that are adjacent to one another, each lane comprising: 35

a support structure to hold one or more items, and  
a weight sensor to generate weight data of a load on the support structure;

a computing device comprising: 40

a memory, storing computer-executable instructions;  
and

a hardware processor to execute the computer-executable instructions to:

access physical layout data associated with the first and second lanes; 45

determine, based on the physical layout data, a cluster comprising the first lane and the second lane;

determine a measured lane weight change for each of the first and second lanes; 50

determine a measured total weight change of the cluster;

determine a plurality of hypotheses, each hypothesis comprising: 55

a predicted quantity change of the one or more items stowed at the cluster,

a predicted lane weight change for each of the first and second lanes in the cluster, and

a predicted total weight change of the cluster; 60

determine, for each hypothesis in the plurality of hypotheses and for each of the first and second lanes in the cluster, a difference between the predicted lane weight change and the measured lane weight change; 65

determine a score for the each hypothesis based on a sum of the differences;

36

determine, based on the score for the each hypothesis, a change in quantity of the one or more items; and

assess charges to an account associated with a user proximate to one or more of the first lane or the second lane based on the change in quantity of the one or more items.

2. The system of claim 1, wherein the physical layout data comprises one or more of:

location information of the first and second lanes and the weight sensor;

item data indicative of items stowed on the support structure of the first and second lanes,

information indicative of an arrangement of the items on the support structure of the first and second lanes,

a lane identifier for each of the first and second lanes, or an identifier for the weight sensor.

3. The system of claim 1, further comprising computer-executable instructions to:

limit the plurality of hypotheses based on one or more constraints, the one or more constraints comprising:

a difference threshold between the predicted total weight change of the cluster and the measured total weight change of the cluster; and

a maximum storage capacity for the one or more items on the first and second lanes of the cluster.

4. The system of claim 1, further comprising:

an imaging sensor; and

wherein the computer-executable instructions are further executable to:

determine, using the imaging sensor, that the user is proximate to one or more of the first lane or the second lane.

5. A system comprising:

a shelf comprising a plurality of lanes that are adjacent to one another, each lane comprising:

a weight sensor to generate weight data of a load on the each lane; and

a computing device comprising:

a memory, storing computer-executable instructions;  
and

a hardware processor to execute the computer-executable instructions to:

access layout data associated with the shelf;

determine, based on the layout data, a cluster comprising adjacent lanes from the plurality of lanes;

determine a measured lane weight change for each of the adjacent lanes in the cluster;

determine a measured total weight change for the cluster;

determine one or more hypotheses for one or more items associated with the adjacent lanes in the cluster, each hypothesis indicative of one or more of:

a predicted quantity of the one or more items,

a predicted lane weight change for the each of the adjacent lanes in the cluster, or

a predicted total weight change for the cluster;

determine a score for one or more of the one or more hypotheses;

determine a solution based on the score for the one or more of the one or more hypotheses;

determine interaction data based on the solution; and assess charges to an account associated with a user based on the interaction data.

37

6. The system of claim 5, wherein the layout data comprises one or more of:

location information of the shelf within a facility,  
information indicative of a physical configuration of the  
shelf,

item data for items stowed at the shelf,  
information indicative of an arrangement of the items on  
the shelf,

a lane identifier for each of the plurality of lanes, or  
an identifier for each sensor associated with the shelf.

7. The system of claim 5, wherein the layout data comprises a planogram indicative of an arrangement of items on different lanes of the shelf.

8. The system of claim 5, further comprising computer-executable instructions to:

determine, based on the layout data, one or more edge  
lanes on the shelf, wherein the one or more edge lanes  
comprise outermost lanes of the shelf and outermost  
lanes of the cluster;

determine, based on the layout data, one or more neighboring  
lanes on the shelf, wherein the one or more  
neighboring lanes comprise lanes adjacent to the one or  
more edge lanes that are not associated with an item;

determine, based on the layout data, one or more gap  
lanes, wherein the one or more gap lanes represent an  
entire lane that separates lanes occupied at least in part  
by an item; and

wherein the adjacent lanes of the cluster include one or  
more of the edge lanes and exclude the one or more  
neighboring lanes and the one or more gap lanes.

9. The system of claim 5, further comprising computer-executable instructions to:

determine a shelf location identifier from the layout data;  
and

retrieve item data for the one or more items associated  
with the adjacent lanes in the cluster, based on the shelf  
location identifier.

10. The system of claim 5, further comprising computer-executable instructions to:

sum the measured lane weight change for the each of the  
adjacent lanes in the cluster to determine the measured  
total weight change for the cluster.

11. The system of claim 10, further comprising computer-executable instructions to:

determine, for the each hypothesis, a difference between  
the predicted lane weight change and the measured lane  
weight change for the each of the adjacent lanes in the  
cluster;

wherein the score is determined based on a sum of the  
differences associated with the each hypothesis.

12. The system of claim 10, further comprising computer-executable instructions to:

determine, for the each hypothesis, a first set of one or  
more lanes for which the predicted lane weight change  
exceeds a threshold;

determine a first sum of the measured lane weight changes  
for the one or more lanes in the first set;

determine a difference between the first sum and the  
predicted total weight change for the cluster;

determine a second set of one or more lanes that are part  
of the cluster and not part of the first set;

determine a second sum of the measured lane weight  
changes for the one or more lanes in the second set;

determine a third sum of the difference and the second  
sum; and

determine the score for the one or more of the one or more  
hypotheses based on the third sum.

38

13. The system of claim 10, further comprising computer-executable instructions to:

determine, for the each hypothesis, a number of transactions,  
wherein a transaction comprises one or more of  
a pick to decrease a quantity of one of the one or more  
items supported by the shelf or a place to increase the  
quantity;

determine a count of the number of transactions for the  
each hypothesis; and

wherein the solution is further based at least in part on the  
count.

14. The system of claim 5, wherein:

the interaction data indicates a change in quantity of the  
one or more items on the adjacent lanes in the cluster;  
and

the charges to the account associated with the user are  
assessed based on the change in quantity of the one or  
more items on the adjacent lanes in the cluster.

15. The system of claim 5, further comprising:

an image sensor to generate image data associated with  
the shelf; and

wherein the computer-executable instructions are further  
executable to:

determine, using the image data, that the user is proximate  
to the shelf.

16. A method comprising:

accessing layout data associated with a shelf;

determining, based on the layout data, a cluster comprising  
adjacent lanes from a plurality of lanes on a shelf;

accessing weight data indicative of a weight as measured  
at each of the adjacent lanes of the cluster;

determining a measured total weight change of the cluster;

accessing one or more hypotheses associated with one or  
more items stowed at the cluster, each hypothesis  
comprising:

a predicted total weight change of the cluster that  
differs from the measured total weight change of the  
cluster by a threshold value;

determining, for one or more of the one or more hypotheses,  
a difference between the measured total weight  
change of the cluster and the predicted total weight  
change of the cluster;

determining a solution from the one or more hypotheses;  
generating interaction data based on the solution; and  
generating billing information for an account associated  
with a user based on the interaction data.

17. The method of claim 16, wherein the layout data comprises a planogram indicative of an arrangement of items on different lanes of the shelf.

18. The method of claim 16, further comprising:

determining measured weight characteristic data for the  
plurality of lanes of the shelf, the measured weight  
characteristic data comprising one or more of:

a measured weight for each of the plurality of lanes;  
a measured weight change at the each of the plurality  
of lanes from a first time to a second time; and  
a weight distribution between two or more of the  
plurality of lanes of the shelf; and

wherein the one or more hypotheses further include:

a predicted quantity of the one or more items, and  
a predicted weight characteristic at each of the adjacent  
lanes of the cluster.

19. The method of claim 16, further comprising:

summing a measured weight change at each of the adjacent  
lanes of the cluster to determine the measured total  
weight change of the cluster.

20. The method of claim 16, further comprising:  
detecting that the user is proximate to a shelf, using an  
imaging sensor;  
determining a quantity of the one or more items removed  
from the cluster; and  
wherein the billing information for the account associated  
with the user is generated based on the quantity of the  
one or more items removed from the shelf.

5

\* \* \* \* \*



UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 10,679,181 B1  
APPLICATION NO. : 16/383391  
DATED : June 9, 2020  
INVENTOR(S) : Alexander Clark Prater et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

Column 37, Claim 11, Line 48:

Currently reads: "cluster;".


Where it should read: --cluster; and--.

Column 38, Claim 16, Line 29:

Currently reads: "adjacent lanes from a plurality of lanes on a shelf;".

Where it should read: --adjacent lanes from a plurality of lanes on the shelf;--.

Signed and Sealed this  
Fourteenth Day of July, 2020



Andrei Iancu  
*Director of the United States Patent and Trademark Office*