

US010681450B2

(12) **United States Patent**
Boesen et al.

(10) **Patent No.:** **US 10,681,450 B2**
(45) **Date of Patent:** ***Jun. 9, 2020**

(54) **EARPIECE WITH SOURCE SELECTION
WITHIN AMBIENT ENVIRONMENT**

(71) Applicant: **BRAGI GmbH**, München (DE)

(72) Inventors: **Peter Vincent Boesen**, München (DE);
Darko Dragicevic, München (DE)

(73) Assignee: **BRAGI GmbH**, München (DE)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **16/048,671**

(22) Filed: **Jul. 30, 2018**

(65) **Prior Publication Data**
US 2018/0338199 A1 Nov. 22, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/804,137, filed on
Nov. 6, 2017, now Pat. No. 10,063,957.
(Continued)

(51) **Int. Cl.**
H04R 29/00 (2006.01)
H04R 1/10 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04R 1/1041** (2013.01); **G06F 3/017**
(2013.01); **G06F 3/167** (2013.01); **H04R**
1/1016 (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04R 29/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,325,590 A 8/1943 Carlisle et al.
2,430,229 A 11/1947 Kelsey
(Continued)

FOREIGN PATENT DOCUMENTS

CN 204244472 U 4/2015
CN 104683519 A 6/2015
(Continued)

OTHER PUBLICATIONS

Akkermans, "Acoustic Ear Recognition for Person Identification",
Automatic Identification Advanced Technologies, 2005 pp. 219-
223.

(Continued)


Primary Examiner — Olisa Anwah

(74) *Attorney, Agent, or Firm* — Goodhue, Coleman &
Owens, P.C.

(57) **ABSTRACT**

A wireless earpiece includes a wireless earpiece housing, at
least one microphone for detecting ambient environment
sound, and a processor disposed within the wireless earpiece
housing, the processor configured to distinguish between
two or more sources of sound within the ambient environ-
ment sound. The wireless earpiece further includes a user
interface operatively connected to the processor. The pro-
cessor is configured to receive user input through the user
interface to select one of the sources of sound within the
ambient environment sound and wherein the processor is
configured to process the ambient environment sound to
emphasize portions of the ambient environment sound gen-
erated by the one of the sources of the ambient environment
sound selected by the user to produce a modified sound. The
earpiece may further include a speaker operatively con-
nected to the processor to reproduce the modified sound.

10 Claims, 5 Drawing Sheets



Related U.S. Application Data						
(60)	Provisional application No. 62/417,373, filed on Nov. 4, 2016.		6,185,152	B1	2/2001	Shen
			6,208,372	B1	3/2001	Barracclough
			6,230,029	B1	5/2001	Yegiazaryan et al.
			6,275,789	B1	8/2001	Moser et al.
			6,339,754	B1	1/2002	Flanagan et al.
			D455,835	S	4/2002	Anderson et al.
(51)	Int. Cl.		6,408,081	B1	6/2002	Boesen
	G06F 3/01 (2006.01)		6,424,820	B1	7/2002	Burdick et al.
	G06F 3/16 (2006.01)		D464,039	S	10/2002	Boesen
(52)	U.S. Cl.		6,470,893	B1	10/2002	Boesen
	CPC H04R 1/1083 (2013.01); H04R 1/1091 (2013.01); H04R 2420/07 (2013.01)		D468,299	S	1/2003	Boesen
			D468,300	S	1/2003	Boesen
			6,522,266	B1	2/2003	Soehren et al.
			6,542,721	B2	4/2003	Boesen
			6,560,468	B1	5/2003	Boesen
			6,563,301	B2	5/2003	Gventer
(56)	References Cited		6,654,721	B2	11/2003	Handelman
	U.S. PATENT DOCUMENTS		6,664,713	B2	12/2003	Boesen
			6,681,176	B2	1/2004	Funk et al.
			6,690,807	B1	2/2004	Meyer
			6,694,180	B1	2/2004	Boesen
			6,718,043	B1	4/2004	Boesen
			6,721,657	B2	4/2004	Ford et al.
			6,738,485	B1	5/2004	Boesen
			6,748,095	B1	6/2004	Goss
			6,754,358	B1	6/2004	Boesen et al.
			6,784,873	B1	8/2004	Boesen et al.
			6,823,195	B1	11/2004	Boesen
			6,852,084	B1	2/2005	Boesen
			6,879,698	B2	4/2005	Boesen
			6,892,082	B2	5/2005	Boesen
			6,920,229	B2	7/2005	Boesen
			6,952,483	B2	10/2005	Boesen et al.
			6,987,986	B2	1/2006	Boesen
			7,010,137	B1	3/2006	Leedom et al.
			7,113,611	B2	9/2006	Leedom et al.
			D532,520	S	11/2006	Kampmeier et al.
			7,136,282	B1	11/2006	Rebeske
			7,203,331	B2	4/2007	Boesen
			7,209,569	B2	4/2007	Boesen
			7,215,790	B2	5/2007	Boesen et al.
			D549,222	S	8/2007	Huang
			D554,756	S	11/2007	Sjursen et al.
			7,403,629	B1	7/2008	Aceti et al.
			D579,006	S	10/2008	Kim et al.
			7,463,902	B2	12/2008	Boesen
			7,508,411	B2	3/2009	Boesen
			7,532,901	B1	5/2009	LaFranchise et al.
			D601,134	S	9/2009	Elabidi et al.
			7,668,652	B2	2/2010	Spencer et al.
			7,825,626	B2	11/2010	Kozisek
			7,859,469	B1	12/2010	Rosener et al.
			7,965,855	B1	6/2011	Ham
			7,979,035	B2	7/2011	Griffin et al.
			7,983,628	B2	7/2011	Boesen
			D647,491	S	10/2011	Chen et al.
			8,095,188	B2	1/2012	Shi
			8,108,143	B1	1/2012	Tester
			8,140,357	B1	3/2012	Boesen
			8,238,967	B1	8/2012	Arnold et al.
			8,253,589	B2	8/2012	Grimm et al.
			D666,581	S	9/2012	Perez
			8,300,864	B2	10/2012	Müllenborn et al.
			8,406,448	B2	3/2013	Lin et al.
			8,430,817	B1	4/2013	Al-Ali et al.
			8,436,780	B2	5/2013	Schantz et al.
			D687,021	S	7/2013	Yuen
			8,679,012	B1	3/2014	Kayyali
			8,719,877	B2	5/2014	VonDoenhoff et al.
			8,774,434	B2	7/2014	Zhao et al.
			8,831,266	B1	9/2014	Huang
			8,891,800	B1	11/2014	Shaffer
			8,994,498	B2	3/2015	Agrafioti et al.
			D728,107	S	4/2015	Martin et al.
			9,013,145	B2	4/2015	Castillo et al.
			9,037,125	B1	5/2015	Kadous
			D733,103	S	6/2015	Jeong et al.
			9,081,944	B2	7/2015	Camacho et al.
			9,229,227	B2	1/2016	Border et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,317,241 B2	4/2016	Tranchina	2009/0008275 A1	1/2009	Ferrari et al.
9,461,403 B2	10/2016	Gao et al.	2009/0017881 A1	1/2009	Madrigal
9,510,159 B1	11/2016	Cuddihy et al.	2009/0041313 A1	2/2009	Brown
D773,439 S	12/2016	Walker	2009/0073070 A1	3/2009	Rofougaran
D775,158 S	12/2016	Dong et al.	2009/0097689 A1	4/2009	Prest et al.
9,524,631 B1	12/2016	Agrawal et al.	2009/0105548 A1	4/2009	Bart
D777,710 S	1/2017	Palmborg et al.	2009/0154739 A1	6/2009	Zellner
9,544,689 B2	1/2017	Fisher et al.	2009/0182913 A1	7/2009	Rosenblatt et al.
D788,079 S	5/2017	Son et al.	2009/0191920 A1	7/2009	Regen et al.
9,684,778 B2	6/2017	Tharappel et al.	2009/0226017 A1	9/2009	Abolfathi et al.
9,711,062 B2	7/2017	Ellis et al.	2009/0240947 A1	9/2009	Goyal et al.
9,729,979 B2	8/2017	Özden	2009/0245559 A1	10/2009	Boltyenkov et al.
9,767,709 B2	9/2017	Ellis	2009/0261114 A1	10/2009	McGuire et al.
9,818,005 B2	11/2017	Yeager et al.	2009/0296968 A1	12/2009	Wu et al.
9,821,767 B2	11/2017	Nixon	2009/0299215 A1	12/2009	Zhang
9,848,257 B2	12/2017	Ambrose et al.	2009/0303073 A1	12/2009	Gilling et al.
2001/0005197 A1	6/2001	Mishra et al.	2009/0304210 A1	12/2009	Weisman
2001/0027121 A1	10/2001	Boesen	2010/0007805 A1	1/2010	Vitito
2001/0043707 A1	11/2001	Leedom	2010/0033313 A1	2/2010	Keady et al.
2001/0056350 A1	12/2001	Calderone et al.	2010/0075631 A1	3/2010	Black et al.
2002/0002413 A1	1/2002	Tokue	2010/0106356 A1	4/2010	Trepagnier et al.
2002/0007510 A1	1/2002	Mann	2010/0166206 A1	7/2010	Macours
2002/0010590 A1	1/2002	Lee	2010/0168075 A1	7/2010	Dahlstrom et al.
2002/0030637 A1	3/2002	Mann	2010/0203831 A1	8/2010	Muth
2002/0046035 A1	4/2002	Kitahara et al.	2010/0210212 A1	8/2010	Sato
2002/0057810 A1	5/2002	Boesen	2010/0285771 A1	11/2010	Peabody
2002/0076073 A1	6/2002	Taenzer et al.	2010/0290636 A1	11/2010	Mao et al.
2002/0118852 A1	8/2002	Boesen	2010/0320961 A1	12/2010	Castillo et al.
2003/0002705 A1	1/2003	Boesen	2011/0018731 A1	1/2011	Linsky et al.
2003/0065504 A1	4/2003	Kraemer et al.	2011/0103609 A1	5/2011	Pelland et al.
2003/0100331 A1	5/2003	Dress et al.	2011/0137141 A1	6/2011	Razoumov et al.
2003/0104806 A1	6/2003	Ruef et al.	2011/0140844 A1	6/2011	McGuire et al.
2003/0115068 A1	6/2003	Boesen	2011/0140956 A1	6/2011	Henry et al.
2003/0125096 A1	7/2003	Boesen	2011/0239497 A1	10/2011	McGuire et al.
2003/0218064 A1	11/2003	Conner et al.	2011/0286615 A1	11/2011	Olodort et al.
2004/0070564 A1	4/2004	Dawson et al.	2011/0293105 A1	12/2011	Ade et al.
2004/0102931 A1	5/2004	Ellis et al.	2012/0057740 A1	3/2012	Rosal
2004/0160511 A1	8/2004	Boesen	2012/0155670 A1	6/2012	Rutschman
2005/0017842 A1	1/2005	Dematteo	2012/0159617 A1	6/2012	Wu et al.
2005/0043056 A1	2/2005	Boesen	2012/0162891 A1	6/2012	Tranchina et al.
2005/0094839 A1	5/2005	Gwee	2012/0163626 A1	6/2012	Booij et al.
2005/0125320 A1	6/2005	Boesen	2012/0197737 A1	8/2012	LeBoeuf et al.
2005/0148883 A1	7/2005	Boesen	2012/0235883 A1	9/2012	Border et al.
2005/0165663 A1	7/2005	Razumov	2012/0309453 A1	12/2012	Maguire
2005/0196009 A1	9/2005	Boesen	2013/0106454 A1	5/2013	Liu et al.
2005/0197063 A1	9/2005	White	2013/0154826 A1	6/2013	Ratajczyk
2005/0212911 A1	9/2005	Marvit et al.	2013/0178967 A1	7/2013	Mentz
2005/0251455 A1	11/2005	Boesen	2013/0200999 A1	8/2013	Spodak et al.
2005/0266876 A1	12/2005	Boesen	2013/0204617 A1	8/2013	Kuo et al.
2006/0029246 A1	2/2006	Boesen	2013/0293494 A1	11/2013	Reshef
2006/0073787 A1	4/2006	Lair et al.	2013/0316642 A1	11/2013	Newham
2006/0074671 A1	4/2006	Farmaner et al.	2013/0343585 A1	12/2013	Bennett et al.
2006/0074808 A1	4/2006	Boesen	2013/0346168 A1	12/2013	Zhou et al.
2006/0166715 A1	7/2006	Engelen et al.	2014/0002357 A1	1/2014	Pombo et al.
2006/0166716 A1	7/2006	Seshadri et al.	2014/0004912 A1	1/2014	Rajakarunanayake
2006/0220915 A1	10/2006	Bauer	2014/0010391 A1	1/2014	Ek et al.
2006/0258412 A1	11/2006	Liu	2014/0014697 A1	1/2014	Schmierer et al.
2007/0102009 A1	5/2007	Wong et al.	2014/0020089 A1	1/2014	Perini, II
2007/0239225 A1	10/2007	Saringer	2014/0072136 A1	3/2014	Tenenbaum et al.
2007/0242834 A1	10/2007	Coutinho et al.	2014/0072146 A1	3/2014	Itkin et al.
2007/0247800 A1	10/2007	Smith et al.	2014/0073429 A1	3/2014	Meneses et al.
2007/0269785 A1	11/2007	Yamanoi	2014/0079257 A1	3/2014	Ruwe et al.
2008/0013747 A1	1/2008	Tran	2014/0106677 A1	4/2014	Altman
2008/0076972 A1	3/2008	Dorogusker et al.	2014/0122116 A1	5/2014	Smythe
2008/0090622 A1	4/2008	Kim et al.	2014/0146973 A1	5/2014	Liu et al.
2008/0102424 A1	5/2008	Holljes	2014/0153768 A1	6/2014	Hagen et al.
2008/0146890 A1	6/2008	LeBoeuf et al.	2014/0163771 A1	6/2014	Demeniuk
2008/0187163 A1	8/2008	Goldstein et al.	2014/0185828 A1	7/2014	Helbling
2008/0215239 A1	9/2008	Lee	2014/0219467 A1	8/2014	Kurtz
2008/0253583 A1	10/2008	Goldstein et al.	2014/0222462 A1	8/2014	Shakil et al.
2008/0254780 A1	10/2008	Kuhl et al.	2014/0235169 A1	8/2014	Parkinson et al.
2008/0255430 A1	10/2008	Alexandersson et al.	2014/0237518 A1	8/2014	Liu
2008/0298606 A1	12/2008	Johnson et al.	2014/0270227 A1	9/2014	Swanson
2008/0318518 A1	12/2008	Coutinho et al.	2014/0270271 A1	9/2014	Dehe et al.
2009/0003620 A1	1/2009	McKillop et al.	2014/0276227 A1	9/2014	Pérez
			2014/0279889 A1	9/2014	Luna
			2014/0310595 A1	10/2014	Acharya et al.
			2014/0321682 A1	10/2014	Kofod-Hansen et al.
			2014/0335908 A1	11/2014	Krisch et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

2014/0348367	A1	11/2014	Vavrus et al.
2015/0028996	A1	1/2015	Agrafioti et al.
2015/0035643	A1	2/2015	Kursun
2015/0036835	A1	2/2015	Chen
2015/0056584	A1	2/2015	Boulware et al.
2015/0110587	A1	4/2015	Hori
2015/0124058	A1	5/2015	Okpeva et al.
2015/0148989	A1	5/2015	Cooper et al.
2015/0181356	A1	6/2015	Krystek et al.
2015/0230022	A1	8/2015	Sakai et al.
2015/0245127	A1	8/2015	Shaffer
2015/0256949	A1	9/2015	Vanpoucke et al.
2015/0264472	A1	9/2015	Aase
2015/0264501	A1	9/2015	Hu et al.
2015/0310720	A1	10/2015	Gettings et al.
2015/0317565	A1	11/2015	Li et al.
2015/0358751	A1	12/2015	Deng et al.
2015/0359436	A1	12/2015	Shim et al.
2015/0364058	A1	12/2015	Lagree et al.
2015/0373467	A1	12/2015	Gelter
2015/0373474	A1	12/2015	Kraft et al.
2015/0379251	A1	12/2015	Komaki
2016/0033280	A1	2/2016	Moore et al.
2016/0034249	A1	2/2016	Lee et al.
2016/0071526	A1 *	3/2016	Wingate G10L 21/028 704/233
2016/0072558	A1	3/2016	Hirsch et al.
2016/0073189	A1	3/2016	Lindén et al.
2016/0094550	A1	3/2016	Bradley et al.
2016/0100262	A1	4/2016	Inagaki
2016/0119737	A1	4/2016	Mehnert et al.
2016/0124707	A1	5/2016	Ermilov et al.
2016/0125892	A1	5/2016	Bowen et al.
2016/0140870	A1	5/2016	Connor
2016/0142818	A1	5/2016	Park
2016/0162259	A1	6/2016	Zhao et al.
2016/0209691	A1	7/2016	Yang et al.
2016/0226713	A1	8/2016	Dellinger et al.
2016/0253994	A1	9/2016	Panchapagesan et al.
2016/0324478	A1	11/2016	Goldstein
2016/0352818	A1	12/2016	Han et al.
2016/0353196	A1	12/2016	Baker et al.
2016/0360350	A1	12/2016	Watson et al.
2017/0021257	A1	1/2017	Gilbert et al.
2017/0046503	A1	2/2017	Cho et al.
2017/0059152	A1	3/2017	Hirsch et al.
2017/0060262	A1	3/2017	Hviid et al.
2017/0060269	A1	3/2017	Förstner et al.
2017/0061751	A1	3/2017	Loermann et al.
2017/0061817	A1	3/2017	Mettler May
2017/0062913	A1	3/2017	Hirsch et al.
2017/0064426	A1	3/2017	Hviid
2017/0064428	A1	3/2017	Hirsch
2017/0064432	A1	3/2017	Hviid et al.
2017/0064437	A1	3/2017	Hviid et al.
2017/0065228	A1	3/2017	Hirano
2017/0078780	A1	3/2017	Qian et al.
2017/0078785	A1	3/2017	Qian et al.
2017/0096065	A1	4/2017	Katsuno et al.
2017/0100277	A1	4/2017	Ke
2017/0108918	A1	4/2017	Boesen
2017/0109131	A1	4/2017	Boesen
2017/0110124	A1	4/2017	Boesen et al.
2017/0110899	A1	4/2017	Boesen
2017/0111723	A1	4/2017	Boesen
2017/0111725	A1	4/2017	Boesen et al.
2017/0111726	A1	4/2017	Martin et al.
2017/0111740	A1	4/2017	Hviid et al.
2017/0119318	A1	5/2017	Shay et al.
2017/0127168	A1	5/2017	Briggs et al.
2017/0131094	A1	5/2017	Kulik
2017/0142511	A1	5/2017	Dennis
2017/0146801	A1	5/2017	Stempora
2017/0150920	A1	6/2017	Chang et al.
2017/0151085	A1	6/2017	Chang et al.

2017/0151447	A1	6/2017	Boesen
2017/0151668	A1	6/2017	Boesen
2017/0151918	A1	6/2017	Boesen
2017/0151930	A1	6/2017	Boesen
2017/0151957	A1	6/2017	Boesen
2017/0151959	A1	6/2017	Boesen
2017/0153114	A1	6/2017	Boesen
2017/0153636	A1	6/2017	Boesen
2017/0154532	A1	6/2017	Boesen
2017/0155985	A1	6/2017	Boesen
2017/0155992	A1	6/2017	Perianu et al.
2017/0155993	A1	6/2017	Boesen
2017/0155997	A1	6/2017	Boesen
2017/0155998	A1	6/2017	Boesen
2017/0156000	A1	6/2017	Boesen
2017/0164890	A1	6/2017	Leip et al.
2017/0178631	A1	6/2017	Boesen
2017/0180842	A1	6/2017	Boesen
2017/0180843	A1	6/2017	Perianu et al.
2017/0180897	A1	6/2017	Perianu
2017/0188127	A1	6/2017	Perianu et al.
2017/0188132	A1	6/2017	Hirsch et al.
2017/0193978	A1	7/2017	Goldman
2017/0195829	A1	7/2017	Belverato et al.
2017/0208393	A1	7/2017	Boesen
2017/0214987	A1	7/2017	Boesen
2017/0215016	A1	7/2017	Dohmen et al.
2017/0230752	A1	8/2017	Dohmen et al.
2017/0251295	A1	8/2017	Pergament et al.
2017/0251933	A1	9/2017	Braun et al.
2017/0257698	A1	9/2017	Boesen et al.
2017/0258329	A1	9/2017	Marsh
2017/0263236	A1	9/2017	Boesen et al.
2017/0263376	A1	9/2017	Verschueren et al.
2017/0266494	A1	9/2017	Crankson et al.
2017/0273622	A1	9/2017	Boesen
2017/0280257	A1	9/2017	Gordon et al.
2017/0297430	A1	10/2017	Hori et al.
2017/0301337	A1	10/2017	Golani et al.
2017/0361213	A1	12/2017	Goslin et al.
2017/0366233	A1	12/2017	Hviid et al.
2018/0007994	A1	1/2018	Boesen et al.
2018/0008194	A1	1/2018	Boesen
2018/0008198	A1	1/2018	Kingscott
2018/0009447	A1	1/2018	Boesen et al.
2018/0011006	A1	1/2018	Kingscott
2018/0011682	A1	1/2018	Milevski et al.
2018/0011994	A1	1/2018	Boesen
2018/0012228	A1	1/2018	Milevski et al.
2018/0013195	A1	1/2018	Hviid et al.
2018/0014102	A1	1/2018	Hirsch et al.
2018/0014103	A1	1/2018	Martin et al.
2018/0014104	A1	1/2018	Boesen et al.
2018/0014107	A1	1/2018	Razouane et al.
2018/0014108	A1	1/2018	Dragicevic et al.
2018/0014109	A1	1/2018	Boesen
2018/0014113	A1	1/2018	Boesen
2018/0014140	A1	1/2018	Milevski et al.
2018/0014436	A1	1/2018	Milevski
2018/0034951	A1	2/2018	Boesen
2018/0040093	A1	2/2018	Boesen
2018/0042501	A1	2/2018	Adi et al.
2018/0056903	A1	3/2018	Mullett
2018/0063626	A1	3/2018	Pong et al.

FOREIGN PATENT DOCUMENTS

CN	104837094	A	8/2015
EP	1469659	A1	10/2004
EP	1017252	A3	5/2006
EP	2903186	A1	8/2015
GB	2074817		4/1981
GB	2508226	A	5/2014
JP	06292195		10/1998
WO	2008103925	A1	8/2008
WO	2008113053	A1	9/2008
WO	2007034371	A3	11/2008
WO	2011001433	A2	1/2011
WO	2012071127	A1	5/2012

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	2013134956	A1	9/2013
WO	2014046602	A1	3/2014
WO	2014043179	A3	7/2014
WO	2015061633	A2	4/2015
WO	2015110577	A1	7/2015
WO	2015110587	A1	7/2015
WO	2016032990	A1	3/2016
WO	2016187869	A1	12/2016

OTHER PUBLICATIONS

Alzahrani et al: "A Multi-Channel Opto-Electronic Sensor to Accurately Monitor Heart Rate against Motion Artefact during Exercise", *Sensors*, vol. 15, No. 10, Oct. 12, 2015, pp. 25681-25702, XP055334602, DOI: 10.3390/s151025681 the whole document.

Announcing the \$3,333,333 Stretch Goal (Feb. 24, 2014).

Ben Coxworth: "Graphene-based ink could enable low-cost, foldable electronics", "Journal of Physical Chemistry Letters", Northwestern University, (May 22, 2013).

Blain: "World's first graphene speaker already superior to Sennheiser MX400", <http://www.gizmag.com/graphene-speaker-beats-sennheiser-mx400/31660/>, (Apr. 15, 2014).

BMW, "BMW introduces BMW Connected—The personalized digital assistant", "http://bmwblog.com/2016/01/05/bmw-introduces-bmw-connected-the-personalized-digital-assistant", (Jan. 5, 2016).

BRAGI is on Facebook (2014).

BRAGI Update—Arrival of Prototype Chassis Parts—More People—Awesomeness (May 13, 2014).

BRAGI Update—Chinese New Year, Design Verification, Charging Case, More People, Timeline (Mar. 6, 2015).

BRAGI Update—First Sleeves From Prototype Tool—Software Development Kit (Jun. 5, 2014).

BRAGI Update—Let's Get Ready to Rumble, A Lot to Be Done Over Christmas (Dec. 22, 2014).

BRAGI Update—Memories From April—Update on Progress (Sep. 16, 2014).

BRAGI Update—Memories from May—Update on Progress—Sweet (Oct. 13, 2014).

BRAGI Update—Memories From One Month Before Kickstarter—Update on Progress (Jul. 10, 2014).

BRAGI Update—Memories From the First Month of Kickstarter—Update on Progress (Aug. 1, 2014).

BRAGI Update—Memories From the Second Month of Kickstarter—Update on Progress (Aug. 22, 2014).

BRAGI Update—New People @BRAGI—Prototypes (Jun. 26, 2014).

BRAGI Update—Office Tour, Tour to China, Tour to CES (Dec. 11, 2014).

BRAGI Update—Status on Wireless, Bits and Pieces, Testing-Oh Yeah, Timeline (Apr. 24, 2015).

BRAGI Update—The App Preview, The Charger, The SDK, BRAGI Funding and Chinese New Year (Feb. 11, 2015).

BRAGI Update—What We Did Over Christmas, Las Vegas & CES (Jan. 19, 2014).

BRAGI Update—Years of Development, Moments of Utter Joy and Finishing What We Started (Jun. 5, 2015).

BRAGI Update—Alpha 5 and Back to China, Backer Day, on Track (May 16, 2015).

BRAGI Update—Beta2 Production and Factory Line (Aug. 20, 2015).

BRAGI Update—Certifications, Production, Ramping Up (Nov. 13, 2015).

BRAGI Update—Developer Units Shipping and Status (Oct. 5, 2015).

BRAGI Update—Developer Units Started Shipping and Status (Oct. 19, 2015).

BRAGI Update—Developer Units, Investment, Story and Status (Nov. 2, 2015).

BRAGI Update—Getting Close (Aug. 6, 2015).

BRAGI Update—On Track, Design Verification, How It Works and What's Next (Jul. 15, 2015).

BRAGI Update—On Track, On Track and Gems Overview (Jun. 24, 2015).

BRAGI Update—Status on Wireless, Supply, Timeline and Open House@BRAGI (Apr. 1, 2015).

BRAGI Update—Unpacking Video, Reviews on Audio Perform and Boy Are We Getting Close (Sep. 10, 2015).

Farr, Christina: "iPads in Every Hospital: Apple's Plan to Crack The \$3 Trillion Health Care Sector", "https://www.fastcompany.com/3069060/artists-and-scientists-are-teaming-with-businesses-and-non-profits-on-gender-concerns" (Mar. 18, 2017).

Healthcare Risk Management Review, "Nuance updates computer-assisted physician documentation solution" (Oct. 20, 2016).

Hoffman, "How to Use Android Beam to Wirelessly Transfer Content Between Devices", (Feb. 22, 2013).

Hoyt et. al., "Lessons Learned from Implementation of Voice Recognition for Documentation in the Military Electronic Health Record System", The American Health Information Management Association (2017).

Hyundai Motor America, "Hyundai Motor Company Introduces a Health + Mobility Concept for Wellness in Mobility", Fountain Valley, California (2017).

International Search Report & Written Opinion, PCT/EPI6/70245 (dated Nov. 16, 2016).

International Search Report & Written Opinion, PCT/EP2016/070231 (dated Nov. 18, 2016).

International Search Report & Written Opinion, PCT/EP2016/070247 (dated Nov. 18, 2016).

International Search Report & Written Opinion, PCT/EP2016/07216 (dated Oct. 18, 2016).

International Search Report and Written Opinion, PCT/EP2016/070228 (dated Jan. 9, 2017).

Jain A et al: "Score normalization in multimodal biometric systems", *Pattern Recognition*, Elsevier, GB, vol. 38, No. 12, Dec. 31, 2005, pp. 2270-2285, XPO27610849, ISSN: 0031-3203.

Last Push Before the Kickstarter Campaign Ends on Monday 4pm CET (Mar. 28, 2014).

Lovejoy: "Touch ID built into iPhone display one step closer as third-party company announces new tech", "http://9to5mac.com/2015/07/21/virtualhomebutton/" (Jul. 21, 2015).

Nemanja Paunovic et al, "A methodology for testing complex professional electronic systems", *Serbian Journal of Electrical Engineering*, vol. 9, No. 1, Feb. 1, 2012, pp. 71-80, XP055317584, Yu. Nigel Whitfield: "Fake tape detectors, 'from the stands' footie and Ugh? Internet of Things in my set-top box"; http://www.theregister.co.uk/2014/09/24/ibc_round_up_object_audio_dlna_iot/ (Sep. 24, 2014).

Nuance, "ING Netherlands Launches Voice Biometrics Payment System in the Mobile Banking App Powered by Nuance", "https://www.nuance.com/about-us/newsroom/press-releases/ing-netherlands-launches-nuance-voice-biometrics.html", 4 pages (Jul. 28, 2015).

Staab, Wayne J., et al., "A One-Size Disposable Hearing Aid is Introduced", *The Hearing Journal* 53(4):36-41 Apr. 2000.

Stretchgoal—It's Your Dash (Feb. 14, 2014).

Stretchgoal—The Carrying Case for the Dash (Feb. 12, 2014).

Stretchgoal—Windows Phone Support (Feb. 17, 2014).

The Dash + The Charging Case & The BRAGI News (Feb. 21, 2014).

The Dash—A Word From Our Software, Mechanical and Acoustics Team + An Update (Mar. 11, 2014).

Update From BRAGI—\$3,000,000—Yipee (Mar. 22, 2014).

Weisiger, "Conjugated Hyperbilirubinemia", Jan. 5, 2016.

Wertzner et al., "Analysis of fundamental frequency, jitter, shimmer and vocal intensity in children with phonological disorders", V. 71, n.5, 582-588, Sep./Oct. 2005; *Brazilian Journal of Othrinolaryngology*.

Wikipedia, "Gamebook", <https://en.wikipedia.org/wiki/Gamebook>, Sep. 3, 2017, 5 pages.

Wikipedia, "Kinect", "https://en.wikipedia.org/wiki/Kinect", 18 pages, (Sep. 9, 2017).

(56)

References Cited

OTHER PUBLICATIONS

Wikipedia, “Wii Balance Board”, “https://en.wikipedia.org/wiki/Wii_Balance_Board”, 3 pages, (Jul. 20, 2017).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

EARPIECE WITH SOURCE SELECTION WITHIN AMBIENT ENVIRONMENT

PRIORITY STATEMENT

This application claims priority to U.S. patent application Ser. No. 15/804,137 filed on Nov. 6, 2017 which claims priority to U.S. Provisional Patent Application No. 62/417,373 filed on Nov. 4, 2016, both of which are titled Earpiece with Source Selection within Ambient Environment, and all of which are hereby incorporated by reference in their entirety.

FIELD OF THE INVENTION

The present invention relates to wearable devices. Particularly, the present invention relates to wireless earpieces. More particularly, but not exclusively, the present invention relates to wireless earpieces, which allow a user to selectively control the ambient sound level of the wireless earpieces.

BACKGROUND

Several situations exist in which an individual is acoustically isolated from an external environment. One of the issues with earpieces is they may block the external auditory canal thereby preventing a user from hearing ambient sounds. Sometimes, this is desired and beneficial, but sometimes it is not. The isolation often results in inefficiency or inconvenience. One primary isolation situation arises from the use of earpieces. A wide variety of traditional earpieces exist for noise abatement or for listening to an audio source or communication. Earpieces can be utilized for maintaining communication in a high ambient sound environment, such as in an aircraft cockpit, stadium, and so forth.

Therefore, a need exists for the development of methods for controlling acoustic isolation, so important events are not missed, and non-important noises can be properly identified and ignored. What is needed is a system and method of substantially preventing ambient sounds from reaching the user's tympanic membranes while providing the user with the option to permit the ambient sounds the user desires to listen to.

SUMMARY

Therefore, it is a primary object, feature, or advantage of the present invention to improve over the state of the art.

It is a further object, feature, or advantage of the present invention to provide a wireless earpiece which identifies different sound sources and allows the user to select one or more of the sound sources to hear while filtering out or attenuating other sound sources.

One or more of these and/or other objects, features, or advantages of the present invention will become apparent from the specification and claims follow. No single embodiment need provide every object, feature, or advantage. Different embodiments may have different objects, features, or advantages. Therefore, the present invention is not to be limited to or by an objects, features, or advantages stated herein.

According to one aspect, a wireless earpiece is provided. The wireless earpiece includes a wireless earpiece housing, at least one microphone for detecting ambient environment sound, and a processor disposed within the wireless earpiece housing, the processor configured to distinguish between

two or more sources of sound within the ambient environment sound. The wireless earpiece further includes a user interface operatively connected to the processor. The processor is configured to receive user input through the user interface to select one of the sources of sound within the ambient environment sound and wherein the processor is configured to process the ambient environment sound to emphasize portions of the ambient environment sound generated by the one of the sources of the ambient environment sound selected by the user to produce a modified sound. The earpiece may further include a speaker operatively connected to the processor to reproduce the modified sound. The processor may be further configured to identify direction of the two or more sound sources within the ambient environment sound. The user interface may further include an inertial sensor and the user may then select the one of the sources of sound within the ambient environment sound by moving the user's head toward the direction of the one of the sources of sound. The user interface may provide for voice input from the user. The user interface may include a gestural interface. The processor may include one or more digital signal processors. A left wireless earpiece and a right wireless earpiece may in operative communication with one another.

According to another aspect, a method is provided for performing source selection within an ambient environment using a wireless earpiece comprising an earpiece housing, a processor disposed within the earpiece housing, at least one microphone operative connected to the processor, and at least one speaker operatively connected to the processor. The method may include steps of detecting ambient environment sound using the at least one microphone, processing the ambient environment sound at the processor to distinguish between two or more sources of sound within the ambient environment sound, receiving a selection of one of the sources of sound from a user of the earpiece, processing the ambient environment sound to emphasize portions of the ambient environment sound generated by the one of the sources of sound selected by the user to produce a modified sound, and producing the modified sound at the at least one speaker. The wireless earpiece may further include a gestural interface operatively connected to the processor and wherein the step of receiving the selection of one of the sources of sound from the user of the earpiece is performed using the gestural interface. The wireless earpiece may further include an inertial sensor operatively connected to the processor and wherein the step of receiving the selection of one of the sources of sound from the user of the earpiece is performed using the inertial sensor.

BRIEF DESCRIPTION OF THE DRAWINGS

Illustrated embodiments of the disclosure are described in detail below with reference to the attached drawing figures, which are incorporated by reference herein.

FIG. 1 includes a block diagram in accordance with an embodiment of the present invention;

FIG. 2 illustrates a system including a left earpiece and a right earpiece in accordance with an embodiment of the present invention;

FIG. 3 illustrates a right earpiece and its relationship to a user's ear in accordance with an embodiment of the present invention;

FIG. 4 includes an expanded block diagram of the system in accordance with an embodiment of the present invention;

FIG. 5 includes a flowchart of one embodiment of the method in accordance with an embodiment of the present invention;

DETAILED DESCRIPTION

The following discussion is presented to enable a person skilled in the art to make and use the present teachings. Various modifications to the illustrated embodiments will be clear to those skilled in the art, and the generic principles herein may be applied to other embodiments and applications without departing from the present teachings. Thus, the present teachings are not intended to be limited to embodiments shown but are to be accorded the widest scope consistent with the principles and features disclosed herein. The following detailed description is to be read with reference to the figures, in which like elements in different figures have like reference numerals. The figures, which are not necessarily to scale, depict selected embodiments and are not intended to limit the scope of the present teachings. Skilled artisans will recognize the examples provided herein have many useful alternatives and fall within the scope of the present teachings. While embodiments of the present invention are discussed in terms of source selection of ambient sound for wireless earpieces, it is fully contemplated embodiments of the present invention could be used in most any electronic communications device without departing from the spirit of the invention.

In one implementation, a system includes an earpiece having an earpiece housing. A microphone can be mounted onto the earpiece housing and configured to receive ambient sound. A processor can be disposed within the earpiece housing and operatively connected to each microphone. The processor is configured to process one or more ambient sounds. A gesture control interface can be mounted onto the earpiece housing and operatively connected to the processor. The gesture control interface is configured to allow a user to control the processing of one or more ambient sounds received by the processor using a gesture. A speaker can be mounted onto the earpiece housing and operatively connected to the processor. The speaker is configured to communicate one or more ambient sounds received from the processor.

One or more of the following features may be included. The earpiece housing may be composed of soundproof materials. The earpiece may comprise a set of earpieces, which may further comprise a left earpiece and a right earpiece. Each earpiece may be configured to substantially encompass an external auditory canal of a user and may be further configured to substantially fit within the external auditory canal. The gesture control interface may be configured to prompt a user with a menu upon receiving a gesture. The gesture control interface may be further configured to prompt the user with a menu upon receiving a voice command from one or more microphones. Each menu may comprise at least one option selectable by the user using a gesture or a voice command. A mobile device may be operatively connected to the earpiece and may be configured to prompt the user with a menu upon receiving a user input. The gesture control interface may be configured to control one or more ambient sounds received by one or more microphones by instructing one or more microphones to filter out one or more ambient sounds. The gesture control interface may be configured to control one or more ambient sounds received by one or more microphones by instructing one or more processors to communicate one or more ambient sounds to the speaker. One or more gestures may include

one or more taps on the gesture control interface, one or more swipes, or holds, or other gestures. The processor may be configured to communicate an audio signal to the speaker.

In another implementation, a method includes receiving, via one or more microphones, one or more ambient sounds, conveying, via one or more microphones, each ambient sound to a processor, processing the ambient sounds using the processor based on one or more sound sources selected by the user, and communicating the ambient sounds using a speaker.

One or more of the following features may be included. One or more non-ambient sounds may be provided, which may be stored within the earpiece or received from one or more transceivers. The reception of one or more ambient sounds may further include receiving one or more ambient sounds through a bone microphone positioned. Ambient sound processing may be controlled using one or more voice commands.

FIG. 1 illustrates a block diagram of the system 10 having at least one earpiece 12 having an earpiece housing 14. A microphone 16 is positioned to receive ambient sound. One or more processors 18 may be disposed within the earpiece housing 14 and operatively connected to microphone 16. A gesture control interface 20 is operatively connected to the processor 18. The gesture control interface 20 is configured to allow a user to control the processing of the ambient sounds such as by selecting a source of ambient sounds which the user wishes to listen to. An inertial sensor 36 is also shown which is operatively connected to the one or more processors. One or more speakers 22 may be positioned within the earpiece housing 14 and configured to communicate the ambient sounds desired by the user. The earpiece housing 14 may be composed of soundproof materials to improve audio transparency or any material resistant to shear and strain and may also have a sheath attached to improve comfort, sound transmission or reduce the likelihood of skin or ear allergies. In addition, the earpiece housing 14 may also substantially encompass the external auditory canal of the user to substantially reduce or eliminate external sounds to further improve audio transparency. The housing 14 of each wearable earpiece 12 may be composed of any material or combination of materials, such as metals, metal alloys, plastics, or other polymers having substantial deformation resistance.

One or more microphones 16 may be positioned to receive one or more ambient sounds. The ambient sounds may originate from the user, a third party, a machine, an animal, another earpiece, another electronic device or even nature itself. The types of ambient sounds received by the microphones 16 may include words, combination of words, sounds, combinations of sounds or any combination. The ambient sounds may be of any frequency and need not necessarily be audible to the user.

The processor 18 is the logic controls for the operation and functionality of the earpiece(s) 12. The processor 18 may include circuitry, chips, and other digital logic. The processor 18 may also include programs, scripts and instructions, which may be implemented to operate the processor 18. The processor 18 may represent hardware, software, firmware or any combination thereof. In one embodiment, the processor 18 may include one or more processors. The processor 18 may also represent an application specific integrated circuit (ASIC), system-on-a-chip (SOC) or field programmable gate array (FPGA).

The processor 18 may also process gestures to determine commands or selections implemented by the earpiece 12. Gestures such as taps, double taps, triple taps, swipes, or

5

holds may be received. The processor **18** may also process movements by the inertial sensor **36**. The inertial sensor **36** may be a 9-axis inertial sensor which may include a 3-axis accelerometer, 3-axis gyroscope, and 3-axis magnetometer. The inertial sensor **36** may serve as a user interface. For example, a user may move their head and the inertial sensor may detect the head movements. In one embodiment, a user may select which sound source they wish to listen to by directing their head to point at the desired sound source.

In one embodiment, the processor **18** is circuitry or logic enabled to control execution of a set of instructions. The processor **18** may be one or more microprocessors, digital signal processors, application-specific integrated circuits (ASIC), central processing units or other devices suitable for controlling an electronic device including one or more hardware and software elements, executing software, instructions, programs, and applications, converting and processing signals and information and performing other related tasks. The processor may be a single chip or integrated with other computing or communications components.

A gesture control interface **20** is mounted onto the earpiece housing **14** and operatively connected to the processor **18** and configured to allow a user to select one or more sound sources using a gesture. The gesture control interface **20** may be located anywhere on the earpiece housing **14** conducive to receiving a gesture and may be configured to receive tapping gestures, swiping gestures, or gestures which do not contact either the gesture control interface **20** or another part of the earpiece **12**. FIG. 2 illustrates a pair of earpieces which includes a left earpiece **12A** and a right earpiece **12B**. The left earpiece **12A** has a left earpiece housing **14A**. The right earpiece **12B** has a right earpiece housing **14B**. A microphone **16A** is shown on the left earpiece **12A** and a microphone **16B** is shown on the right earpiece **12B**. The microphones **16A** and **16B** may be positioned to receive ambient sounds. Additional microphones may also be present. Speakers **22A** and **22B** are configured to communicate modified sounds **46A** and **46B** after processing. The modified sounds **46A** and **46B** may be communicated to the user.

FIG. 3 illustrates a side view of the right earpiece **12B** and its relationship to a user's ear. The right earpiece **12B** may be configured to isolate the user's ear canal **48** from the environment so the user does not hear the environment directly but may hear a reproduction of the environmental sounds as modified by the earpiece **12B** which is directed towards the tympanic membrane **50** of the user. There is a gesture control interface **20** shown on the exterior of the earpiece. FIG. 4 is a block diagram of an earpiece **12** having an earpiece housing **14**, and a plurality of sensors **24** operatively connected to one or more processors **18**. The one or more sensors may include one or more bone microphones **32** which may be used for detecting speech of a user. The sensors **24** may further include one or more biometric sensors **34** which may be used for monitoring physiological conditions of a user. The sensors **24** may include one or more microphones **16** which may be used for detecting sound within the ambient environment of the user. The sensors **24** may include one or more inertial sensors **36** which may be used for determining movement of the user such as head motion of the user used to select one or more sound sources within the ambient environment. A gesture control interface **20** is also operatively connected to the one or more processors **18**. The gesture control interface **20** may be implemented in various ways including through capacitive touch or through optical sensing. The gesture control interface **20**

6

may include one or more emitters **42** and one or more detectors **44**. Thus, for example, in one embodiment, light may be emitted at the one or more emitters **42** and detected at the one or more detectors **44** and interpreted to indicate one or more gestures being performed by a user. One or more speakers **22** are also operatively connected to the processor **18**. A radio transceiver **26** may be operatively connected to the one or more processors **18**. The radio transceiver may be a BLUETOOTH transceiver, a BLE transceiver, a Wi-Fi transceiver, or other type of radio transceiver. A transceiver **28** may also be present. The transceiver **28** may be a magnetic induction transceiver such as a near field magnetic induction (NFMI) transceiver. Where multiple earpieces are present, the transceiver **28** may be used to communicate between the left and the right earpieces. A memory **37** is operatively connected to the processor and may be used to store instructions regarding sound processing, user settings regarding selections, or other information. One or more LEDs **38** may also be operatively connected to the one or more processors **18** and may be used to provide visual feedback regarding operations of the wireless earpiece.

FIG. 5 illustrates one example of a method **100**. In step **102**, ambient environment sound is detected such as by using one or more microphones of a single earpiece or using one or more microphones of each earpiece within a set of earpieces which includes both a left earpiece and a right earpiece. In step **104**, the ambient environment sound is processed to distinguish between two or more sources of sound. This processing may occur in various ways using any number of different types of algorithms. For example, a segmentation algorithm may be used to segment the ambient environment sound into different sources. Feature extraction algorithms may be applied to extract different features of the ambient environment sound associated with different sources. Where more than one earpiece is used or where more than one microphone is used on a single wireless earpiece, additional algorithms may be used to determine the direction a sound source is coming from. The sound source may be one of any number of different types of sound source. The sound source may be another individual who is talking. The sound source may be a television, radio, or computer. The sound source may be any person, animal, or object emitting sounds.

In step **106**, a selection of one of the sources of sound may be received. This process may occur in any number of different ways. For example, where the user interface of the wireless earpiece includes an inertial sensor, a user may turn their head to the source of sound the user wishes to listen to. The processor may then select one or more sounds emanating from the direction to which the user is facing by emphasizing the selected one or more sounds or deemphasizing one or more non-selected sounds. A sound source may be emphasized in various ways including increasing amplitude or volume of a sound source or decreasing the amplitude or volume of other sound sources, or otherwise attenuating or suppressing other sound sources. In some cases, other sound sources may be filtered out in other ways such as based on frequency of the sounds. Indeed, any number of filters may be applied by the processor to emphasize one or more selected sounds. In another embodiment, a user may select one of the sound sources through use of the gestural interface. For example, after identifying different sources of sound, the processor may automatically select one of the sources of sound, modify the ambient sound to emphasize the selection and reproduce it and then the user may confirm the selection or deny the selection through use of the gestural

interface. If the user denies the selection of the source of sound, the earpiece may select a different one of the sources of sound and generate the modified sound for the user for the source and repeat the process until the user has agreed upon the selected sound source. Once a selection of one of the sources of sound has been made in step 106, in step 108 the ambient sound is processed based upon the selection to produce modified sound. The modified sound produced is a modified ambient environment sound emphasizing a sound source selection made by the user such as by treating sounds from other sources as background sounds and filtering those sounds out, by increasing the amplitude of sound from the selected sound source or otherwise. In step 110, the modified sound may then be produced at the one or more speakers of the earpiece. Thus, in this manner the earpiece may be used to provide for a source selection within the ambient environment sound.

Therefore, various methods, systems, and apparatus have been shown and described. Although various embodiments or examples have been set forth herein, it is to be understood the present invention contemplates numerous options, variations, and alternatives as may be appropriate in an application or environment.

What is claimed is:

1. A method for performing source selection within an ambient environment using a set of wireless earpieces comprising:

a first earpiece housing and a second earpiece housing;
a first processor disposed within the first earpiece housing and a second processor disposed with the second earpiece housing;

at least one microphone operatively connected to the first processor and at least one microphone operatively connected to the second processor; and

and at least one speaker operatively connected to the first processor and at least one speaker operatively connected to the second processor;

the method comprising steps of:

detecting ambient environment sound using the at least one microphone of a first or a second wireless earpiece;

processing the ambient environment sound at the first or second processor to distinguish between two or more sources of sound within the ambient environment sound;

presenting audibly a plurality of menu selections to a user, each of the plurality of different menu selections corresponding with a different one of the two or more sources of sound with the ambient environment;

receiving a selection of one of the sources of sound from the user of the set of wireless earpieces via a user interface operatively connected to the first or second processor;

processing the ambient environment sound to emphasize portions of the ambient environment sound generated by the one of the sources of sound selected by the user to produce a modified sound; and

producing the modified sound at the at least one speaker of the first and or second wireless earpiece.

2. The method of claim 1, wherein the processing of the ambient environment sound at the first or second processor to distinguish between two or more sources of sound is performed using a feature extraction algorithm for extracting different features of the ambient environment sound.

3. The method of claim 1, wherein the set of wireless earpieces further comprises an inertial sensor operatively connected to the first or second processor and wherein the

step of receiving the selection of one of the sources of sound from the user of the set of wireless earpieces is performed using the inertial sensor.

4. The method of claim 1, wherein the processing of the ambient environment sound at the first or second processor to distinguish between two or more sources of sound within the ambient environment sound comprises segmenting the ambient environment sound into different sources using a segmentation algorithm.

5. The method of claim 1, wherein the selection of one of the sources of sound from the user comprises a non-contact gesture.

6. A set of wireless earpieces for performing source selection within an ambient environment, comprising:

a first earpiece housing and a second earpiece housing;
at least one microphone operatively connected to the first housing and at least one microphone operatively connected to the second housing, wherein the at least one microphone of a first or a second wireless earpiece detects ambient environment sound;

a first processor disposed within the first earpiece housing and a second processor disposed with the second earpiece housing, wherein the first or second processor distinguish between two or more sources of sound within the ambient environment sound, wherein the first or second processor present audibly a plurality of menu selections to a user where each of the plurality of different menu selections corresponds with a different one of the two or more sources of sound with the ambient environment;

a user interface operatively connected to the first or second processor, wherein the user interface receives a selection of one of the sources of sound from the user of the set of wireless earpieces, wherein the first or second processor process the ambient environment sound to emphasize portions of the ambient environment sound generated by the one of the sources of sound selected by the user to produce a modified sound; and

at least one speaker operatively connected to the first processor and at least one speaker operatively connected to the second processor, the at least one speaker of the first or second wireless earpiece producing the modified sound.

7. The set of wireless earpieces of claim 6, further comprising a feature extraction algorithm for extracting different features of the ambient environment sound to distinguish between two or more sources of sound.

8. The set of wireless earpieces of claim 6, further comprising an inertial sensor operatively connected to the first or second processor, wherein the inertial sensor receives the selection of one of the sources of sound from the user of the set of wireless earpieces.

9. The set of wireless earpieces of claim 6, wherein the processing of the ambient environment sound at the first or second processor to distinguish between two or more sources of sound within the ambient environment sound comprises segmenting the ambient environment sound into different sources using a segmentation algorithm.

10. The set of wireless earpieces of claim 6, wherein the selection of one of the sources of sound from the user comprises a non-contact gesture.