



US010684069B2

(12) **United States Patent**  
**Ryu et al.**

(10) **Patent No.:** **US 10,684,069 B2**  
(45) **Date of Patent:** **Jun. 16, 2020**

(54) **REFRIGERATOR**

(71) Applicant: **LG ELECTRONICS INC.**, Seoul (KR)

(72) Inventors: **Inhwan Ryu**, Seoul (KR); **Minjoo Cha**, Seoul (KR); **Hyein Yang**, Seoul (KR)

(73) Assignee: **LG ELECTRONICS INC.**, Seoul (KR)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/453,495**

(22) Filed: **Jun. 26, 2019**

(65) **Prior Publication Data**  
US 2019/0316838 A1 Oct. 17, 2019

**Related U.S. Application Data**

(63) Continuation of application No. 15/792,912, filed on Oct. 25, 2017, now Pat. No. 10,386,116, which is a (Continued)

(30) **Foreign Application Priority Data**

Mar. 27, 2013 (KR) ..... 10-2013-0032525

(51) **Int. Cl.**  
**H04N 7/18** (2006.01)  
**F25D 29/00** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **F25D 29/00** (2013.01); **F25D 23/028** (2013.01); **F25D 23/04** (2013.01); **F25D 23/062** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... F25D 29/00; F25D 23/028; F25D 23/04; F25D 23/062; F25D 2400/06;  
(Continued)

(56) **References Cited**  
U.S. PATENT DOCUMENTS

9,285,162 B2 3/2016 Ryu et al.  
9,503,635 B2 11/2016 Ryu  
(Continued)

FOREIGN PATENT DOCUMENTS

JP 2001-317858 11/2001  
JP 2002-243335 8/2002  
(Continued)


OTHER PUBLICATIONS

European Search Report dated Jul. 22, 2014, issued in Application No. 14152587.3.  
(Continued)

*Primary Examiner* — Eileen M Adams  
(74) *Attorney, Agent, or Firm* — KED & Associates LLP

(57) **ABSTRACT**  
A refrigerator is provided. The refrigerator may include a main body having a storage compartment, a first door rotatably installed at a first side of the main body to open and close a first portion of the storage compartment, and a second door rotatably installed at a second side of the main body to open and close a second portion of the storage compartment. A first camera may be installed at the first door to take a picture of an interior of the first storage compartment during rotation of the first door, and a second camera may be installed at the second door to take a picture of the interior of the first storage compartment during rotation of the second door. A controller may combine plural pictures taken by the first camera and the second camera into a single corrected image of a region of the first compartment spanning from the first door to the second door.

**14 Claims, 18 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 15/298,520, filed on Oct. 20, 2016, now Pat. No. 9,829,243, which is a continuation of application No. 15/040,333, filed on Feb. 10, 2016, now Pat. No. 9,503,635, which is a continuation of application No. 14/190,450, filed on Feb. 26, 2014, now Pat. No. 9,285,162.

2003/0164754	A1	9/2003	Roseen
2006/0096303	A1	5/2006	Kavounas
2010/0170289	A1	7/2010	Graziano
2011/0266275	A1	11/2011	Rateiczak
2012/0285089	A1	11/2012	Artwohl
2013/0056477	A1	3/2013	Go
2014/0168396	A1	6/2014	Kempiak et al.

**FOREIGN PATENT DOCUMENTS**

- (51) **Int. Cl.**  
*H04N 5/225* (2006.01)  
*F25D 23/02* (2006.01)  
*F25D 23/06* (2006.01)  
*G06Q 10/08* (2012.01)  
*G06T 11/60* (2006.01)  
*H04N 5/232* (2006.01)  
*F25D 23/04* (2006.01)

JP	2003-004366	1/2003
JP	2003-090661	3/2003
JP	2003-207258	7/2003
JP	2004-183987	7/2004
JP	2004-286355	10/2004
JP	2006-084132	3/2006
KR	10-2006-0099985	9/2006
KR	10-2010-0059621	6/2014

- (52) **U.S. Cl.**  
 CPC ..... *G06Q 10/087* (2013.01); *G06T 11/60* (2013.01); *H04N 5/2252* (2013.01); *H04N 5/23222* (2013.01); *H04N 7/181* (2013.01); *F25D 2400/06* (2013.01); *F25D 2500/06* (2013.01); *F25D 2600/00* (2013.01); *F25D 2700/02* (2013.01); *F25D 2700/06* (2013.01); *F25D 2700/08* (2013.01)

**OTHER PUBLICATIONS**

- (58) **Field of Classification Search**  
 CPC ..... F25D 2500/06; F25D 2600/00; F25D 2700/02; F25D 2700/06; F25D 2700/08; G06Q 10/087; G06T 11/60; H04N 5/2252; H04N 5/23222; H04N 7/181  
 See application file for complete search history.

Notice of Allowance dated Nov. 6, 2015 issued in U.S. Appl. No. 14/190,450.  
 Office Action dated Mar. 24, 2016 issued in U.S. Appl. No. 15/040,333.  
 Notice of Allowance dated Jul. 22, 2016 issued in U.S. Appl. No. 15/040,333.  
 Chinese Office Action dated Jan. 11, 2017 issued in Application 201410119615.6 (English Translation).  
 Office Action dated Dec. 1, 2016 issued in U.S. Appl. No. 15/298,520.  
 Notice of Allowance dated Jul. 25, 2017 issued in U.S. Appl. No. 15/298,520.  
 Final Office Action dated Jul. 20, 2018 issued in parent U.S. Appl. No. 15/792,912.  
 Korean Notice of Allowance dated Apr. 15, 2019 issued in Application 10-2013-0032525.  
 Korean Office Action dated Apr. 1, 2020 issued in Application 10-2020-0010447.

- (56) **References Cited**  
 U.S. PATENT DOCUMENTS

2002/0066279 A1 6/2002 Kiyomatsu

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15






FIG. 16




FIG. 17




FIG. 18





FIG. 19



**1****REFRIGERATOR**CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a Continuation Application of U.S. patent application Ser. No. 15/792,912 filed Oct. 25, 2017, which is a Continuation Application of U.S. patent application Ser. No. 15/298,520, filed Oct. 20, 2016, now U.S. Pat. No. 9,829,243 which is a Continuation Application of U.S. patent application Ser. No. 15/040,333, filed Feb. 10, 2016, now U.S. Pat. No. 9,503,635, which is a Continuation Application of U.S. application Ser. No. 14/190,450, filed Feb. 26, 2014, now U.S. Pat. No. 9,285,162, which claims priority under 35 U.S.C. § 119 to Korean Application 10-2013-0032525 filed in Korea on Mar. 27, 2013, whose entire disclosures are hereby incorporated by reference

## BACKGROUND

## 1. Field

This relates to a refrigerator, and more particularly to a refrigerator which may provide information related to items stored therein.

## 2. Background

A refrigerator may supply cold air generated via driving of a refrigeration cycle to store items in a low temperature state. A user may open a door of the refrigerator in order to view an interior of the refrigerator and contents of the interior of the refrigerator. Not knowing quantities and types of items stored in the refrigerator may cause inconvenience when purchasing replenishment items.

## BRIEF DESCRIPTION OF THE DRAWINGS

The embodiments will be described in detail with reference to the following drawings in which like reference numerals refer to like elements wherein:

FIG. 1 is a perspective view of a refrigerator in accordance with an embodiment as broadly described herein;

FIG. 2 is a block diagram of a terminal, in accordance with an embodiment as broadly described herein;

FIG. 3 is a front view of a refrigerator, in accordance with an embodiment as broadly described herein;

FIG. 4 is a control block diagram for the refrigerator shown in FIG. 3;

FIG. 5 is an exploded perspective view of a door rotation drive device of the refrigerator shown in FIG. 3;

FIG. 6 is a schematic view of rotation of one or more doors of the refrigerator shown in FIG. 3;

FIG. 7 illustrates an exemplary plurality of pictures of an interior of the refrigerator shown in FIG. 3;

FIG. 8 illustrates the pictures of FIG. 7 corrected and transmitted to a terminal;

FIG. 9 is an exemplary implementation of the combined picture shown in FIG. 8;

FIG. 10 is a flowchart of a picture taking process based on an elapsed open time of a door, in accordance with an embodiment as broadly described herein;

FIG. 11 is a flowchart of a picture taking process based on a rotation position of a door when the door is open, in accordance with an embodiment as broadly described herein;

**2**

FIG. 12 is a flowchart of a picture taking process based on an elapsed time when a door is closed, in accordance with an embodiment as broadly described herein;

FIG. 13 is a flowchart of a picture taking process based on a rotation position of a door when the door is closed, in accordance with an embodiment as broadly described herein;

FIG. 14 is a perspective view of a refrigerator, in accordance with another embodiment as broadly described herein;

FIG. 15 is a control block diagram for the refrigerator shown in FIG. 14;

FIG. 16 illustrates a plurality of pictures corrected into a single picture and transmitted to a terminal, in accordance with another embodiment as broadly described herein;

FIG. 17 is a flowchart, in accordance with another embodiment as broadly described herein;

FIG. 18 is a front view of a refrigerator, in accordance with another embodiment as broadly described herein; and

FIG. 19 is a control block diagram of the refrigerator shown in FIG. 18.

## DETAILED DESCRIPTION

Hereinafter, exemplary embodiments will be described with reference to the accompanying drawings. In the drawings, the shape, size, and the like of components may be exaggerated for clarity and convenience. In addition, the terms particularly defined in consideration of configurations and operations of embodiments as broadly described herein may be replaced by other terms by those skilled in the art. The meanings of these terms may be construed based on the overall content as broadly described herein.

In a refrigerator as embodied and broadly described herein, a camera may be installed at or near a door that is a movable component of the refrigerator, whereby information related to the interior of a storage compartment of the refrigerator may be acquired via the camera. That is, although the interior of the storage compartment is in a stationary state, the camera may be moved along with the door, and thus a region that may be imaged by the camera is variable. As a result, pictures of various positions in the interior of the storage compartment may be acquired via a single camera.

As shown in FIG. 1, a refrigerator **100** as embodied and broadly described herein may include a main body **100a**, a door **101b** coupled at a front surface of the main body **100a**, and a handle **100c** mounted on the door **101b**. A dispenser **110** that dispenses cold water or ice may be provided on the door **101b**, and a display **120** that provides the user with various information related to, e.g., food stored in the refrigerator **100**, may also be provided on the door **101b**. The display **120** may also transmit user input information to other devices.

The display **120** may have various forms so long as it may display prescribed information and enable touch input of a prescribed instruction. In one example, the display **120** may take the form of a touchscreen that may provide for simultaneous input and display. The display **120** may be separably coupled to a front surface of the door **101b**. Thus, the user may attach or detach the display **120** to or from the refrigerator **100** as needed.

Information displayed on the display **120** may be transmitted to a terminal **200** that is connected to the refrigerator **100** through a network. The terminal **200** may be, for example, a smart-phone that is independent of the refrigerator **100** to allow the user to have the terminal **200** remote from the refrigerator **100**. Accordingly, a user viewing the

terminal **200** may recognize information related to the interior of the refrigerator **100** even if the user does not have physical access to the refrigerator **100**.

With reference to FIG. 2, a terminal **200** as embodied and broadly described herein may include a terminal communication device **210**, an Audio/Video (NV) input device **220**, a user input device **230**, a terminal output device **240**, a memory **250**, an interface device **260**, a Radio Frequency Identification (RFID) reader **270**, a terminal controller **280**, and a power supply device **290**, for example. Not all of the components shown in FIG. 2 are essential, and the terminal **200** may include a greater or lesser number of components.

The terminal communication device **210** may include one or more modules to enable use of the Internet between the terminal **200** and a wireless communication system or in an Internet protocol network in which the terminal **200** is located. For example, the terminal communication device **210** may include a broadcast reception module **211**, a mobile communication module **212**, an Internet module **213**, and a short-range communication module **214**.

The broadcast reception module **211** may receive broadcast signals and/or broadcast information from an external broadcast management server through a broadcast channel under control of the terminal controller **280**, and may play back the same on a display module **241**.

The mobile communication module **212** may transmit/receive wireless signals with at least one of a base station, an external terminal, or a server through a mobile communication network. The wireless signals may include voice signals, video call signals, or various other data based on transmission/reception of text/multimedia messages.

The Internet module **213** may provide for wired/wireless Internet connection. Wireless Internet technologies may include Wireless LAN (WLAN) (Wi-Fi), wireless broadband (WiBro), World Interoperability for Microwave Access (WiMAX), High Speed Downlink Packet Access (HSDPA), and the like.

The short-range communication module **214** may provide for short-range communication. Short-range communication technologies may include Bluetooth, Radio Frequency Identification (RFID), Infrared Data Association (IrDA), Ultra Wideband (UWB), ZigBee, and the like.

The A/V input device **220** may receive audio signals and video signals, and may include a camera module **221** and a microphone **222**, for example.

The camera module **221** may process image information including, e.g. a still image or a moving image captured by an image sensor in a video call mode or an image capture mode. The processed image information may be displayed on the display module **241**. Image data processed in the camera module **221** may be stored in the memory **250**, or may be transmitted to, e.g., an external terminal through the terminal communication device **210**. Two or more camera modules **221** may be provided, depending on a particular usage environment.

The microphone **222** may receive an external sound signal, e.g., in a call mode, a recording mode or a voice recognition mode, and may process the sound signal into electrical voice data.

The user input device **230** may receive input data to allow the user to control operation of the terminal **200**. The user input device **230** may include a keypad, a direction key, a dome switch, a touchpad (constant-pressure/capacitive), a jog wheel, a jog switch, and the like.

The terminal output device **240** may generate visual or auditory output, and may include the display module **241** and a sound output module **242**, for example.

The display module **241** may display (output) information processed in the terminal **200**. For example, when displaying information related to the terminal **200** and the refrigerator **100**, the display module **241** of the terminal **200** may display the interior state of the refrigerator **100**. The display module **241** may include at least one of a Liquid Crystal Display (LCD), a Thin Film Transistor Liquid Crystal Display (TFT LCD), an Organic Light Emitting Diode (OLED), a flexible display, and a 3D display.

In certain embodiments, the display module **241** may include a sensor to sense a touch motion (hereinafter referred to as 'a touch sensor') constructed in a layered structure (hereinafter referred to as 'a touchscreen'), so that the display module **241** may be used as an input device as well as an output device.

The touch sensor may take the form of a touch film, a touch sheet, or a touch pad, for example. The touch sensor may be configured to convert, e.g., a pressure applied to a specific portion of the display module **241** or a variation of capacitance generated from the specific portion of the display module **241** into an electrical input signal. The touch sensor may be configured to detect a touch pressure applied to the display module **241** as well as a touched location and an area of the touched location.

When a touch input is generated with respect to the touch sensor, the signal(s) corresponding to the touch input may be transmitted to a touch controller which processes the signal(s), and transmits data corresponding to the signal(s) to the terminal controller **280**. In this manner, the terminal controller **280** may recognize a touch to a particular region of the display module **241**.

The sound output module **242** may output data containing audio stored in the memory **250**, or may output sound informing the user of an operational state of the refrigerator **100**. The sound output module **242** may include, for example, a receiver, a speaker, or a buzzer.

The memory **250** may store a program for processing and control of the terminal controller **280**, and may contain information related to food stored in the refrigerator **100**. In addition, the memory **250** may store graphic data to provide the user with various messages and information via various visual effects.

The above-described memory **250** may include a storage medium having at least one type among a flash memory type, a hard disk type, a multimedia card micro type, a card type of a memory (for example, an SD or XD memory), a Random Access Memory (RAM), a Static Random Access Memory (SRAM), a Read-Only Memory (ROM), an Electrically Erasable Programmable Read-Only Memory (EEPROM), a Programmable Read-Only Memory (PROM), a magnetic memory, a magnetic disc, and an optical disc.

The interface device **260** may connect various external devices to the refrigerator terminal **200**. The interface device **260** may receive data or power from an external device, and transfer the data or power to each component in the terminal **200**, or transmit internal data of the terminal **200** to an external device. For example, the interface device **260** may include a wired/wireless headset port, an external charger port, a wired/wireless data port, a memory card port, a port for connection of a device having an identification module, an audio Input/Output (I/O) port, a video I/O port, and an earphone port.

The terminal controller **280** may control an overall operation of the terminal **200**.

The power supply **290** may receive power from an external power source through the interface device **260** and

## 5

may supply the power to operate each component under control of the terminal controller **280**.

Various exemplary embodiments described herein may be implemented in a recording medium capable of being read by a computer or a similar device using, e.g., software, hardware, or a combination thereof.

According to hardware implementation, exemplary embodiments described herein may be realized using at least one of Application Specific Integrated Circuits (ASICs), digital signal processors (DSPs), digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), processors, controllers, micro-controllers, microprocessors, and an electric unit for performing other functions.

In some cases, exemplary embodiments described in the specification may be implemented by the terminal controller **280**.

According to software implementation, exemplary embodiments with regard to procedures and functions described in the specification may be realized by separate software modules. Each of the software modules may perform at least one function and operation described in the specification.

Software code may be embodied as a software application that is written in an appropriate programming language. The software code may be stored in the memory **250**, and may be executed by the terminal controller **280**.

As shown in FIG. **3**, a refrigerator **100** according to one embodiment may have a first storage compartment **20** and a second storage compartment **90** in which items may be stored, a right door **30** installed at a right side of the main body **100a**, and a left door **50** installed at a left side of the main body **100a**, both the right and left doors **30** and **50** opening and closing the first storage compartment **20**.

The right door **30** may be pivotally rotated about the right side of the first storage compartment **20** to open and close a corresponding portion of the first storage compartment **20**, and the left door **50** may be pivotally rotated about the left side of the first storage compartment **20** to open and close a corresponding portion of the first storage compartment **20**. The user may fully open the first storage compartment **20** by pivotally rotating both the right door **30** and the left door **50** to check, e.g., a type and quantity of food stored in the first storage compartment **20** and to access the food.

According to one embodiment, the refrigerator **100** may include a first camera **40** installed at the right door **30** and a second camera **60** installed at the left door **50**.

Among the various components of a refrigerator, a door is a movable component. In this exemplary embodiment, the door may open or close a storage compartment by being rotated about a single rotation axis. The door has a prescribed trajectory through this rotation, and therefore has less possibility of abnormal movement.

In the present embodiment, the first camera **40** may be installed at an inner surface of the right door **30**, i.e. a surface of the right door **30** facing the first storage compartment **20**. Similarly, the second camera **60** may be installed at an inner surface of the left door **50**, i.e. a surface of the left door **50** facing the first storage compartment **20**. Since the first camera **40** and the second camera **60** are installed respectively on the right door **30** and the left door **50**, the first camera **40** and the second camera **60** are pivotally rotated when the right door **30** and the left door **50** are pivotally rotated relative to the main body **100a**. As the first camera **40** and/or the second camera **60** rotates with the respective door in this manner, the first camera **40** and the second

## 6

camera **60** may take pictures plural times, thereby acquiring a plurality of pictures of the interior of the refrigerator **100**.

More specifically, the first camera **40** and the second camera **60** may be installed on racks **32** on which food is received. In certain embodiments, a cover **31** may enclose the top of the rack **32** so as to isolate food on the rack **32** from the interior of the first storage compartment **20**. The cover **31** may, for example, rotate about one side of the rack **32** to provide access to food received inside the cover **31**, on the rack **32**.

The rack **32** may include a decorative portion **34** at a front surface thereof. The decorative portion **34** may be formed of an opaque material, and a transparent window **36** may be provided at the decorative portion **34** to allow the first camera **40** or the second camera **60** to take a picture through the transparent window **36**.

To drive the first camera **40** or the second camera **60**, an electric wire for transmission of power and a control signal may be necessary. Accordingly, the decorative portion **34** may be formed of an opaque material so that the interior of the rack **32** is not visible. That is, the decorative portion **34** may ensure that the electric wire extending from the main body **100a** to the first camera **40** or the second camera **60** is connected to the rack **32** without being exposed and visible to the user. As the first camera **40** or the second camera **60** is installed to take a picture through the transparent window **36**, distortion due to the decorative portion **34** may be avoided.

Although FIG. **3** shows a state in which each of the first camera **40** and the second camera **60** is installed on a single rack **32** of each door **30** and **50**, the first camera **40** and/or the second camera **60** may be installed on a plurality of racks of each door **30** and/or **50**. More specifically, each of the right door **30** and the left door **50** includes a plurality of racks **32**, and therefore a plurality of first cameras **40** and second cameras **60** may be provided at each door **30** and **50**.

The plurality of racks **32** installed within the first storage compartment **20** may be full of food. Therefore, providing the plurality of first cameras **40** and/or second cameras **60** may allow the first cameras **40** and/or the second cameras **60** to take pictures at various heights, which may ensure more clear transmission of information related to the stored food in the refrigerator **100**.

In addition, in the case in which the plurality of first cameras **40** and/or second cameras **60** is provided, the first cameras **40** and/or the second cameras **60** may be aligned in a single line. In this case, the single line may extend in a vertical direction confronting the main body **100a**.

In certain embodiments, the first camera **40** and the second camera **60** may be installed at different heights. The right door **30** and the left door **50** may respectively include the racks **32** installed at different heights. Accordingly, to ensure that the first camera **40** and the second camera **60** installed at different heights take desired pictures, an installation direction or a zoom-in or zoom-out function of each camera **40** and **60** may be controlled.

According to one embodiment, the first storage compartment **20** and the second storage compartment **90** may define separate storage spaces. That is, the first storage compartment **20** and the second storage compartment **90** may be opened and closed by different doors.

If the first storage compartment **20** is a refrigerating compartment, the second storage compartment **90** may be a freezing compartment. On the contrary, if the first storage compartment **20** is a freezing compartment, the second storage compartment **90** may be a refrigerating compartment. Alternatively, if the first storage compartment **20** and

the second storage compartment **90** define separate spaces, both the first storage compartment **20** and the second storage compartment **90** may equally serve as refrigerating compartments or freezing compartments.

Each of the right door **30** and the left door **50** may include a door rotation drive device **10** configured to open and close the first storage compartment **20**. That is, two door rotation drive devices **10** may be provided to rotate the right door **30** and the left door **50**, respectively.

The first storage compartment **20** may be open as one or both of the door rotation drive devices **10** rotates the right door **30** and/or the left door **50** in a specific direction. On the other hand, the first storage compartment **20** may be closed as each of the door rotation drive devices **10** rotates the right door **30** and/or the left door **50** for the in an opposite direction.

FIG. **4** is a control block diagram associated with the refrigerator shown in FIG. **3**.

A controller **80** may combine a plurality of pictures taken by the first camera **40** and the second camera **60** with one another, and may correct the pictures into a single image of an interior region of the first storage compartment **20**, from the right door **30** to the left door **50**. The controller **80** may combine a plurality of pictures taken by the first camera **40** and the second camera **60**, thereby providing the user with an image that the user may easily and intuitively recognize. The controller **80** may combine the plurality of pictures with one another, and correct the respective pictures. Alternatively, combination of the plurality of pictures may be implemented by an external control device provided external to the refrigerator **100**, rather than being implemented by the controller **80**.

According to one embodiment of the present invention, a door rotation position sensor **130** may be provided to sense a rotation position of the right door **30** and/or a rotation position of the left door **50**. The door rotation position sensor **130** may be integrated with the door rotation drive device **10**, and may sense whether or not the right door **30** and/or the left door **50** for the first storage compartment reaches a predetermined rotation position.

When the right door **30** and/or the left door **50** for the first storage compartment reaches a predetermined rotation position, the door rotation position sensor **130** may transmit a related signal to the controller **80** to instruct the first camera **40** and/or the second camera **60** to take a picture.

In certain embodiments, a plurality of rotation positions may be predetermined with respect to each of the right door **30** and the left door **50**. This allows the first camera **40** and the second camera **60** to take pictures plural times.

The door rotation position sensor **130** may include a Hall sensor using Hall effects. The Hall sensor may find the magnitude and direction of a magnetic field using Hall effects in which a potential difference is produced across a conductor carrying an electric current when a magnetic field is applied in a direction perpendicular to that of the current flow.

According to one embodiment, a timer **140** may measure passage of time. In addition to general passage of time, the timer **140** may measure, in particular, moving time of the right door **30** and/or the left door **50**. When moving time measured by the timer **140** exceeds a predetermined time, the timer **140** may transmit a related signal to the controller **80** to allow the controller **80** to instruct the first camera **40** and/or the second camera **60** to take a picture.

According to one embodiment, a door opening/closing sensor **150** may sense opening or closing of the right door **30** and/or the left door **50**. The door opening/closing sensor **150**

may sense whether or not the right door **30** and/or the left door **50** is released from contact with the main body **100a**, for example, thereby sensing whether the right door **30** and/or the left door **50** opens or closes the first storage compartment **20**. The door opening/closing sensor **150** may transmit information related to opening or closing of the right door **30** and/or the left door **50** to the controller **80**.

According to one embodiment, a door rotation direction sensor **160** may sense a rotation direction of the right door **30** and/or a rotation direction of the left door **50**. The door rotation direction sensor **160** may include a plurality of Hall sensors to sense a rotation position of the right door **30** and/or the left door **50** based on a position of the sequentially affected hall sensors.

The door rotation direction sensor **160** may sense a rotation direction of the right door **30** and/or the left door **50**, and transmit a related signal to the controller **80**. That is, the controller **80** may detect a rotation direction of the right door **30** and/or the left door **50** with assistance from the door rotation direction sensor **160**.

When each of the right door **30** and the left door **50** is rotated in a specific direction, the controller **80** may determine that each of the right door **30** and the left door **50** is rotated to open the first storage compartment **20**. On the other hand, when each of the right door **30** and the left door **50** is rotated in a direction opposite to the specific direction, the controller **80** may determine that each of the right door **30** and the left door **50** is rotated to close the first storage compartment **20**.

According to one embodiment, a storage device **82** may be provided to store an image corrected by the controller **80**. The storage device **82** may store all images corrected by the controller **80** including the most recently corrected image as well as previously corrected images. The image(s) stored in the storage device **82** may be transmitted to the terminal **200** or the display **120**, and the user may recognize information related to the interior of the refrigerator **100** via the terminal **200** or the display **120**.

According to one embodiment, the door rotation drive device **10** may drive the right door **30** and/or the left door **50**. For example, the door rotation drive device **10** may be driven in response to a signal input by the user via the input device **122**, thereby opening or closing the right door **30** and/or the left door **50**, depending on the input and corresponding signal. That is, the door rotation drive device **10** may open or close the first storage compartment **20** by rotating the right door **30** and/or the left door **50** forward or in reverse.

The door rotation drive device **10** may include a stepper motor which may be rotated by an angle proportional to a given pulse number based on the sequence of step pulses. That is, a rotation angle of the right door **30** and/or the left door **50** may be precisely controlled by applying a predetermined pulse to the stepper motor.

Through use of the door rotation drive device **10** including the stepper motor, the door rotation drive device **10** may sense a rotation direction and a rotation position of the right door **30** and/or the left door **50**. That is, through use of the door rotation drive device **10** including the stepper motor, the door rotation position sensor **130** and the door rotation direction sensor **160** of FIG. **4** may be omitted.

According to one embodiment, a communication device **84** may be provided to transmit an image corrected by the controller **80** to an external device. In this case, the communication device **84** may transmit a corrected image to the terminal communication device **210** as shown in FIG. **2**. In particular, the communication device **84** may transmit, e.g.,



an image stored in the storage device **82** or an image corrected by the controller **80** to an external device provided outside of the refrigerator **100**.

FIG. **5** is an exploded perspective view of the door rotation drive device shown in FIG. **3**.

The door rotation drive device **10** may include a bracket **12**, one side of which is coupled to the main body **100a**, and a motor **18** connected to the bracket **12**.

The motor **18** may be embedded in the door **30, 50** and may be mounted at the center of rotation, about which the door **30, 50** is rotated relative to the main body **100a**. As such, the motor **18** may be rotated along with the door **30, 50**.

The bracket **12** may have a cylindrical receiving groove **14**, and a link crank **16** may be received in the receiving groove **14**. A rotating shaft **19** of the motor **18** may be inserted into the link crank **16**. The link crank **16** may be fixed in the receiving groove **14** so that it is not rotatable relative to the receiving groove **14**. Since the bracket **12** is fixed to the main body **100a**, consequently, the link crank **16** is fixed to the main body **100a**, and thus is not rotated relative to the main body **100a**. That is, since the link crank **16** is kept stationary even if the rotating shaft **19** of the motor **18** is rotated, the motor **18** is rotated, and consequently the door **30, 50** is rotated. The motor **18** may be a stepper motor. That is, the motor **18** may rotate the right door **30** and/or the left door **50** by a predetermined angle, thereby controlling an opening degree of the first storage compartment **20**.

As shown in FIG. **6**, the right door **30** and/or the left door **50** is pivotally rotatable relative to the main body **100a**, and the first camera **40** and/or the second camera **60** may take pictures a plurality of times as the doors **30, 50** rotate.

As shown in FIG. **6**, a region imaged by the first camera **40** and/or the second camera **60** may vary as the right door **30** and/or the left door **50** is rotated. However, since the right door **30** and the left door **50** both rotate about a vertical axis of the main body **100a**, each of the first camera **40** and the second camera **60** has a constant picture taking height even if the doors **30, 50** are rotated.

The first camera **40** may take a picture one or more times when the right door **30** is rotated relative to the main body **100a** by an angle less than 90 degrees. This is because the first camera **40** may take a picture of the interior of the first storage compartment **20** or the interior of the left door **50** when the right door **30** is rotated relative to the main body **100a** by an angle less than 90 degrees.

For example, the first camera **40** may take pictures when the right door **30** is rotated relative to the main body **100a** by angles of, for example, 40 degrees, 65 degrees, and 90 degrees. At these positions of the right door **30**, the first camera **40** may take a picture of a region of the first storage compartment **20** proximate to the left door **50** and a picture of the interior of the left door **50**.

The second camera **60** may take a picture one or more times when the left door **50** is rotated relative to the main body **100a** by an angle less than 90 degrees. This is because the second camera **60** may take a picture of the interior of the first storage compartment **20** or the interior of the right door **30** when the left door **50** is rotated relative to the main body **100a** by an angle less than 90 degrees.

In particular, the second camera **60** may take pictures when the left door **50** is rotated relative to the main body **100a** by angles of, for example, 40 degrees, 65 degrees, and 90 degrees. At these positions of the left door **50**, the second camera **60** may take a picture of a region of the first storage compartment **20** proximate to the right door **30** and a picture of the interior of the right door **30**.

Although each of the first camera **40** and the second camera **60** is fixed to its respective door **30, 50**, the first camera **40** and the second camera **60** may take pictures of various regions because the right door **30** and the left door **50** are rotated. That is, it is possible to take pictures of several regions in which food is stored in the first storage compartment using the single first camera **40** and the single second camera **60**.

In addition, the first camera **40** and the second camera **60** may take a plurality of pictures based on a rotation duration of the right door **30** and the left door **50**.

More specifically, the opening of the right door **30** and the left door **50** may be sensed by the door opening/closing sensor **150**. Then, when a prescribed time has elapsed after the door opening/closing sensor **150** senses opening of the right door **30** and/or the left door **50**, the first camera **40** and the second camera **60** may take a picture.

In this case, the right door **30** and the left door **50** may be pivotally rotated by the door rotation drive device **10**. That is, the door rotation drive device **10**, which is driven by the motor **18**, may have a predetermined angular velocity, and the first camera **40** and the second camera **60** may take pictures at desired positions based on a time interval measured by the timer **140**.

The time interval measured by the timer **140** may be set in such a manner that a rotation angle of the right door **30** and/or the left door **50** with respect to the main body **100a** is approximately 40 degrees, 65 degrees, and 90 degrees. That is, when the right door **30** and/or the left door **50** is rotated by the door rotation drive device **10**, the timer **140** may set a point in time when each of the first camera **40** and the second camera **60** takes a picture.

When the door opening/closing sensor **150** senses opening of the right door **30** or the left door **50**, the first camera **40** and the second camera **60** take a picture as the right door **30** and/or the left door **50** opens the first storage compartment **20**. In this case, the first camera **40** and the second camera **60** may take pictures at door rotation angles of, for example, 40 degrees, 65 degrees, and 90 degrees in sequence.

In the above-described case, the door rotation direction sensor **160** may sense whether or not the right door **30** and/or the left door **50** is rotated in a direction to open the first storage compartment **20** based on a rotation direction of the right door **30** and/or the left door **50**.

Alternatively, the first camera **40** and the second camera **60** may take a picture when the right door **30** and/or the left door **50** is rotated in a direction to close the first storage compartment **20**.

Typically, the user opens the right door **30** and/or the left door **50**, introduces food into or retrieves food from the first storage compartment **20**, the right door **30** or the left door **50**, and then closes the right door **30** and/or the left door **50**. That is, the latest information related to food stored in the first storage compartment **20**, the right door **30** and/or the left door **50** may be acquired when the user closes the right door **30** and/or the left door **50**.

If information related to food received in the first storage compartment **20**, the right door **30** and/or the left door **50** is acquired when the right door **30** and the left door **50** is first opened, there is high likelihood of the corresponding information being changed.

In contrast, in the present embodiment, as the door rotation direction sensor **160** senses that the right door **30** and/or the left door **50** is rotated to close the first storage compartment **20**, the first camera **40** and/or the second camera **60** may take a picture.

## 11

The door rotation direction sensor **160** may allow the first camera **40** and the second camera **60** to take pictures at the door rotation angles of, for example, 90 degrees, 65 degrees, and 40 degrees in sequence when the right door **30** and/or the left door **50** is rotated to close the first storage compartment **20**. In this case, the first camera **40** and the second camera **60** takes pictures in a sequence opposite to the sequence of taking pictures when the doors **30**, **50** are rotated to open the first storage compartment **20**.

Even when the right door **30** and/or the left door **50** is rotated in a direction to close the first storage compartment **20**, the timer **140** may begin to measure time when doors **30**, **50** are at an angle of 90 degrees with respect to the main body **100a**.

After a prescribed time has passed from time when the doors **30**, **50** are at an angle of 90 degrees with respect to the main body **100a**, it may be determined that the right door **30** and/or the left door **50** is at an angle of 65 degrees or 40 degrees, and at this time the first camera **40** and/or the second camera **60** may take a picture. In this case, the right door **30** and/or the left door **50** may be rotated at a constant angular velocity by the door rotation drive device **10**. That is, when the right door **30** and/or the left door **50** is rotated at a constant angular velocity, a rotation angle of the right door **30** and/or the left door **50** may be easily determined based on a time measured by the timer **140**.

FIG. **7** illustrates a plurality of pictures taken by the first camera **40** and the second camera **60** as the doors **30**, **50** rotate. For example, in FIG. **7**, the three left pictures may be taken by the first camera **40** and three right pictures may be taken by the second camera **60**, and the six pictures taken by the first camera **40** and the second camera **60** may be combined with one another by the controller **80**.

Alternatively, instead of three pictures, each of the first camera **40** and the second camera **60** may take four or more pictures, or one or two pictures. That is, a number of pictures taken by the first camera **40** and the second camera **60** may be controlled by controlling picture taking positions and the number of picture taking times of the first camera **40** and the second camera **60**.

FIG. **8** is a front view of a terminal **200** displaying the pictures of FIG. **7** which have been corrected and transmitted to the terminal **200**. Although FIG. **8** illustrates the corrected/combined image display on the terminal **200**, the same information may be transmitted to the display **120**.

In this case, the image contains content related to the interior of the first storage compartment **20**. That is, the image may sequentially show, starting from the left side, the interior of the left door **50**, the interior of the first storage compartment **20**, and the interior of the right door **30**. The image may be shown as if the right door **30** and the left door **50** are open and exposed to the user, so that the image displayed on the screen appears as if the user directly opens the right door **30** and the left door **50**, and the user may intuitively and easily recognize information related to food stored in the refrigerator.

The image may be a single panoramic picture. That is, the single picture may prevent an unnecessary increase in photo capacity when the picture is transmitted to the user.

The user may recognize information related to the state, type, and amount of food stored in the first storage compartment **20** by simply viewing the image. Accordingly, it may be unnecessary to frequently open the right door **30** and/or the left door **50** of the refrigerator **100**, and energy consumption may be reduced by preventing leakage from cold air of the first storage compartment **20** due to opening of the right door **30** and/or the left door **50**. In addition, when

## 12

the user is away from home, the user may determine food to be purchased and food not to be purchased using the image. Accordingly, waste of food due to repeated purchase and inconvenience caused when not purchasing necessary food may be prevented.

FIG. **9** illustrates an exemplary implementation example, in which the exemplary image shown in FIG. **8** may be processed to provide the user with a shopping list of items that the user needs to purchase. The shopping list of items may be produced and managed by the user as information related to food is directly extracted from the image, or as the user extracts information related to food and additionally inputs and manages the information.

FIG. **10** is a flowchart of a picture taking process based on an elapsed time when a door is open, according to one embodiment as broadly described herein.

First, the door opening/closing sensor **150** may sense opening or closing of the door (**S10**).

Next, the timer **140** measures movement time of the door, beginning when the door opening/closing sensor **150** senses the opening or closing of the door (**S12**). The timer **140** may measure an elapsed time starting from a moment when the door begins to be opened. Assuming that the door is rotated at a constant angular velocity by the door rotation drive device **10**, a rotation position of the door may be easily determined from the elapsed time.

Even if the door is not driven by the door rotation drive device **10**, a rotation position of the door based on an elapsed time may be predicted by calculating an average angular velocity of the refrigerator door during a typical manual rotation of the door.

The camera takes a picture based on the elapsed time measured by the timer **140** (**S14**). Since the first camera **40** and the second camera **60** are rotated along with the door, positions of the first camera **40** and the second camera **60** vary as time passes. Accordingly, the first camera **40** and the second camera **60** may take different pictures as time passes.

Then, it is determined whether or not a predetermined time, as measured by the timer **140**, has elapsed (**S16**). The predetermined time may be, for example, an amount of time for the door to rotate to a fully open or fully closed position. If the predetermined time has not elapsed and there remains time for the first camera **40** and the second camera **60** to make additional pictures, movement time of the door is continuously measured (**S12**).

On the other hand, if the predetermined time has elapsed, it may be recognized that the first camera **40** and the second camera **60** have taken all pictures necessary. That is, the first camera **40** and the second camera **60** are no longer taking pictures.

Next, the controller **80** combines the pictures taken by the first camera **40** and the second camera **60** (**S18**). FIG. **7** shows one example of the plurality of pictures taken by the first camera **40** and the second camera.

Then, the controller **80** may correct the plurality of combined pictures into an image as shown in FIG. **8**, and transmit the corrected image to the display **120** or to the terminal **200** via the communication device **84** (**S20**).

FIG. **11** is a flowchart of a picture taking process based on a rotation position of the door when the door is open, according to one embodiment as broadly described herein. In FIG. **11**, instead of the time measured by the timer **140**, the first camera **40** and the second camera **60** may take a picture based on a rotation position of the right door **30** and a rotation position of the left door **50**. For convenience of explanation, parts different from those of FIG. **10** will be

## 13

described, and a description related to the same or similar parts will be omitted hereinafter.

When opening of the door is sensed (S10), the door rotation position sensor 130 senses a rotation position of the right door 30 and a rotation position of the left door 50 (S22).

When the right door 30 and the left door 50 reach predetermined rotation positions, the first camera 40 and the second camera 60 take a picture (S24). Since a plurality of rotation positions may be predetermined, the first camera 40 and the second camera 60 may take a plurality of pictures.

Then, it is determined whether or not the right door 30 and the left door 50 reach all predetermined rotation positions (S26). That is, in the case in which the predetermined rotation positions are set to positions where the door is rotated by, for example, 40 degrees, 65 degrees, and 90 degrees with respect to the main body 100a, it may be determined whether or not the doors have reached all positions corresponding to the respective angles.

If it is determined that the right door 30 and the left door 50 have reached all the predetermined rotation positions, the door rotation position sensor 130 may continuously sense a rotation position of the right door 30 and a rotation position of the left door 50.

If it is determined that the right door 30 and the left door 50 have reached all the predetermined rotation positions, the controller 80 may combine a plurality of pictures (S18).

FIG. 12 is a flowchart of a picture taking process based on an elapsed time when the door is closed, according to one embodiment as broadly described herein. In particular, FIG. 12 explains a picture taking process of the first camera 40 and the second camera 60 when the door is rotated in a direction to close the first storage compartment 20, differently from that of FIG. 10. Accordingly, parts different from those of FIG. 10 will be described, and a description related to the same parts will be omitted hereinafter.

First, the door rotation direction sensor 160 may sense a rotation direction of the right door 30 and a rotation direction of the left door 50 (S2).

If it is determined that the right door 30 and the left door 50 are rotated in a direction to close the first storage compartment 20 (S4), movement time of the door may be measured to allow the first camera 40 and the second camera 60 to take a picture.

If it is determined that the right door 30 and the left door 50 are rotated in a direction to open the first storage compartment 20, the first camera 40 and the second camera 60 may take a picture in the same manner as the above description with reference to FIG. 10.

FIG. 13 is a flowchart of a picture taking process based on a rotation position of a door when the door is closed, according to one embodiment as broadly described herein. With reference to FIG. 13, a picture taking method of the first camera 40 and the second camera 60 when the door is rotated in a direction to close the first storage compartment 20 will be described. Accordingly, although the process of FIG. 13 is similar to that of FIG. 12, there is a difference in that the first camera 40 and the second camera 60 take a picture via sensing of a rotation position of the door.

That is, in the same manner as the above description with reference to FIG. 12, the door rotation direction sensor 160 may sense that the right door 30 and the left door 50 are rotated in a direction to close the first storage compartment 20 (S2, S4).

Then, if it is determined that the right door 30 and the left door 50 are closing the first storage compartment 20, the first camera 40 and the second camera 60 may take a picture

## 14

when the right door 30 and the left door 50 reach predetermined rotation positions thereof (S22, S24).

FIG. 14 is a perspective view of a refrigerator according to another embodiment as broadly described herein, and FIG. 15 is a control block diagram of the refrigerator shown in FIG. 14. In this embodiment, the same parts as those of the previously described embodiment are designated by the same reference numerals, and a description related to the same parts will be omitted hereinafter.

In this embodiment, the first storage compartment 20 and the second storage compartment 90 may define separate spaces divided by a barrier 400 which is vertically installed in the main body 100a. In this case, each of the first storage compartment 20 and the second storage compartment 90 may provide a space in which food is stored, and may serve as a refrigerating compartment or a freezing compartment.

The first storage compartment 20 may be open or closed by a first door 330, and the second storage compartment 90 may be open or closed by a second door 350. The first door 330 and the second door 350 may be rotated relative to the main body 100a.

The first storage compartment 20 may be provided with a first storage compartment camera 22, and the second storage compartment 90 may be provided with a second storage compartment camera 92. The first storage compartment camera 22 may take a picture of the interior of the first door 330, and the second storage compartment camera 92 may take a picture of the interior of the second door 350. That is, the first storage compartment camera 22 is arranged to take a picture of food stored in the first door 330, and the second storage compartment camera 92 is arranged to take a picture of food stored in the second door 350.

The first door 330 and the second door 350 may each be provided with door cameras. The first door 330 may be provided with a first door camera 340 and the second door 350 may be provided with a second door camera 360. The first door camera 340 may take a picture of the first storage compartment 20, and the second door camera 360 may take a picture of the second storage compartment 90. That is, the first door camera 340 is arranged to take a picture of food stored in the first storage compartment 20, and the second door camera 360 is arranged to take a picture of food stored in the second storage compartment 90.

The refrigerator 100 may include a light source 300 installed in the main body 100a to emit light. The light source 300 may emit light to allow the user to view food stored in the first storage compartment 20 or the second storage compartment 90 when the user opens the first door 330 or the second door 350. That is, the light source 300 may be driven when the door opening/closing sensor 150 senses opening of the first door 330 and/or the second door 350 and the first door 330 and/or the second door 350 is open.

In addition, the light source 300 may be driven when the user tries to check food stored in the first storage compartment 20 and the second storage compartment 90 as well as food stored in the first door 330 and the second door 350. That is, even in a state in which the first door 330 and the second door 350 close the first storage compartment 20 and the second storage compartment 90, the light source 300 may be driven. Once the light source 300 is driven, the first storage compartment camera 22, the second storage compartment camera 92, the first door camera 340, and the second door camera 360 may take a picture.

The door opening/closing sensor 150 may determine that the first door 330 or the second door 350 closes the first storage compartment 20 or the second storage compartment 90 respectively. In this case, the light source 300 may be

driven, and the first storage compartment camera **22**, the second storage compartment camera **92**, the first door camera **340**, and the second door camera **360** may take a picture.

In a closed state of the first door **330** and the second door **350**, the interior of the first storage compartment **20** and the second storage compartment **90** is dark, and therefore a picture containing information with desired resolution cannot be taken. To solve this problem, the light source **300** may be driven with the first door **330** and the second door **350** closed.

Each of the first storage compartment camera **22**, the second storage compartment camera **92**, the first door camera **340**, and the second door camera **360** may be provided in plurality. In this case, each of the plurality of first storage compartment cameras **22**, the second storage compartment cameras **92**, the first door cameras **340**, and the second door cameras **360** may be arranged in a line or in a plurality of lines to simultaneously take a plurality of pictures.

The controller **80** may combine and correct pictures taken by the first storage compartment camera **22**, the second storage compartment camera **92**, the first door camera **340**, and the second door camera **360**. An image combined and corrected by the controller **80** may be transmitted to the user terminal **200**. For example, an image as shown in FIG. **16** may be transmitted to the user terminal **200**.

The image sequentially shows, starting from the left side, the interior of the second door **350**, the interior of the second storage compartment **90**, the interior of the first storage compartment **20**, and the interior of the first door **330**. That is, the image shows a state in which the first door **330** and the second door **350** are fully open, and therefore the user may intuitively recognize information related to the type, state, and amount of food stored in the refrigerator **100** from the image.

Thus, the user may acquire information related to food stored in the refrigerator **100** without opening the first door **330** and/or the second door **350**. In addition, differently from the previously described embodiment, information related to the interior of the refrigerator **100** may be acquired from pictures taken in a closed state of the first door **330** and the second door **350**.

FIG. **17** is a flowchart according to another embodiment as broadly described herein.

The user may operate the input device **122**, or generation of a signal at a prescribed interval may be set (S**110**). In this case, the user may acquire information related to food stored in the refrigerator by operating the input device **122** or based on periodically generated signals.

In response to a signal to instruct the camera to take a picture, the door opening/closing sensor **150** may sense opening or closing of the first door **330** or the second door **350**.

If it is determined that the first door **330** or the second door **350** is closed, the light source **300** is actuated (S**130**), because the first storage compartment **20** and the second storage compartment **90** are dark when the first door **330** and the second door **350** are closed.

Once the light source **300** is actuated, the first storage compartment **20** and the second storage compartment **90** have sufficient luminance, and the first door camera **340**, the second door camera **360**, the first storage compartment camera **22**, and the second storage compartment camera **92** may be operated to take a picture (S**140**).

Since the first door camera **340**, the second door camera **360**, the first storage compartment camera **22**, and the second storage compartment camera **92** are kept stationary, each camera may take a picture only one time, because the

same picture is acquired in a stationary state of the camera, even if the camera takes a plurality of pictures.

The controller **80** combines pictures taken by the first door camera **340**, the second door camera **360**, the first storage compartment camera **22**, and the second storage compartment camera **92** with one another (S**150**).

Then, the controller **80** may correct the combined pictures into an image, and transmit the corrected image to the display **120** or the terminal **200** via the communication device **84** (S**160**).

The corrected image may be stored in the storage device **82**, which enables history management of respective images.

FIG. **18** is a front view of a refrigerator according to another embodiment as broadly described herein, and FIG. **19** is a control block diagram of the refrigerator shown in FIG. **18**.

This embodiment may be applied to a refrigerator having a configuration as described above with respect to FIG. **13**, and may employ a combined picture taking method including picture taking method described with respect to the embodiment shown in FIG. **3** and the embodiment shown in FIG. **14**. That is, a further embodiment may be applied to the refrigerator having a configuration as shown in FIG. **3**. In addition, information related to food stored in a refrigerating compartment or a freezing compartment may be acquired even in a closed state of the door, similar to that in the embodiment shown in FIG. **14**.

This embodiment is a combination of the embodiment described with respect to FIG. **3** and the embodiment described with respect to FIG. **14**, and thus a detailed description related to respective components will be omitted hereinafter. However, it will be appreciated that the components according to this embodiment perform the same function as the above-described components, and thus the above description may be equally applied.

According to this embodiment, in addition to the first camera **40** installed at the right door **30** and the second camera **60** installed at the left door **50**, a storage compartment camera **420** may be installed to take a picture of the interior of the right door **30** and the interior of the left door **50**. In certain embodiments, a plurality of storage compartment cameras **420** may be arranged in plural lines.

More specifically, as shown in FIG. **6**, the right door **30** and the left door **50** are pivotally rotated to allow the first camera **40** and the second camera **60** to take a picture, which may result in generation of an image as shown in FIG. **8**. In this case, the image may sequentially show, starting from the left side, the interior of the left door **50** for the first storage compartment, the interior of the first storage compartment **20**, and the interior of the right door **30** for the first storage compartment.

In addition, the light source **300** may be actuated as described above with reference to FIG. **16**, and the storage compartment camera **420**, the first camera **40** and the second camera **60** may be driven to take a picture, which may result in generation of an image as shown in FIG. **8**.

In this embodiment, the user may acquire information related to food stored in the refrigerator **100** based on pictures taken via pivotal rotation of the door. In addition, the user may also acquire information related to food stored in the refrigerator **100** even in a state in which the storage compartment is closed by the doors.

In a refrigerator as embodied and broadly described herein, a user may recognize information related to items stored in a refrigerator without opening a door of a storage compartment of the refrigerator.

In a refrigerator as embodied and broadly described herein, even when the user is away from home, the user may recognize information related to items stored in the refrigerator via a portable terminal.

In a refrigerator as embodied and broadly described herein, the user may view a display of an interior of the refrigerator similar to that when a refrigerator door is directly opened, which assists the user in easily recognizing the interior state of the refrigerator.

A refrigerator as embodied and broadly described herein may provide a user with information related to items stored in the refrigerator.

A refrigerator as embodied and broadly described herein may provide a user with an image as if the user opens the refrigerator.

A refrigerator, as embodied and broadly described herein, may include a main body having a first storage compartment in which food is stored, a right door for the first storage compartment, the right door being installed to a right side of the main body to open the first storage compartment via pivotal rotation thereof about the right side of the first storage compartment, a left door for the first storage compartment, the left door being installed to a left side of the main body to open the first storage compartment via pivotal rotation thereof about the left side of the first storage compartment, a first camera installed to the right door for the first storage compartment, the first camera taking a picture during rotation of the right door for the first storage compartment, a second camera installed to the left door for the first storage compartment, the second camera taking a picture during rotation of the left door for the first storage compartment, and a control unit configured to combine a plurality of pictures taken by the first camera and the second camera with one another and correct the pictures into an image showing a region from the right door for the first storage compartment to the left door for the first storage compartment.

The refrigerator may further include a door rotation position sensing unit configured to sense a rotation position of the left door for the first storage compartment or the right door for the first storage compartment.

The control unit may instruct the first camera or the second camera to take a picture when the right door for the first storage compartment or the left door for the first storage compartment reaches a predetermined rotation position.

The first camera or the second camera may take a picture at least one time or more when the right door for the first storage compartment or the left door for the first storage compartment is rotated relative to the main body by an angle less than 90 degrees.

The first camera or the second camera may be installed to an inner side of each door.

The first camera may take a picture of a left region of the first storage compartment and the second camera may take a picture of a right region of the first storage compartment.

The image may sequentially show, starting from the left side, the interior of the left door for the first storage compartment, the interior of the first storage compartment, and the interior of the right door for the first storage compartment.

The refrigerator may further include a door rotation drive unit configured to rotate the right door for the first storage compartment or the left door for the first storage compartment.

The first camera or the second camera may begin to take a picture when the right door for the first storage compartment or the left door for the first storage compartment is rotated in a direction perpendicular to the main body to close the first storage compartment.

The refrigerator may further include a door opening/closing sensing unit configured to sense opening or closing of the right door for the first storage compartment or the left door for the first storage compartment.

The first camera or the second camera may take a picture based on an elapsed time when the right door for the first storage compartment or the left door for the first storage compartment is rotated to open the first storage compartment.

The refrigerator may further include a door rotation direction sensing unit configured to sense a rotation direction of the right door for the first storage compartment or the left door for the first storage compartment.

The first camera or the second camera may take a picture when the door rotation direction sensing unit senses that the right door for the first storage compartment or the left door for the first storage compartment is rotated in a set direction.

The set direction may be a door rotation direction to close the first storage compartment.

The refrigerator may further include a communication unit configured to transmit the image to an external device.

The refrigerator may further include a display unit configured to show the image to the user.

The refrigerator may further include a storage unit configured to store the last image corrected by the control unit, and a communication unit configured to transmit the last image stored in the storage unit to an external device.

In accordance with another embodiment as broadly described herein, a refrigerator may include a main body having a storage compartment in which food is stored, a door configured to open or close the storage compartment, a storage compartment camera installed in the storage compartment, a door camera installed to the door, and a control unit configured to combine a plurality of pictures taken by the storage compartment camera and the door camera with one another and correct the pictures into an image showing the door and the storage compartment.

The refrigerator may further include a door opening/closing sensing unit configured to sense opening or closing of the door.

The storage compartment camera and the door camera may take a picture when the door opening/closing sensing unit senses that the door closes the storage compartment.

Any reference in this specification to "one embodiment," "an embodiment," "example embodiment," etc., means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the invention. The appearances of such phrases in various places in the specification are not necessarily all referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with any embodiment, it is submitted that it is within the purview of one skilled in the art to effect such feature, structure, or characteristic in connection with other ones of the embodiments.

Although embodiments have been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure. More particularly, various variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

19

What is claimed is:

1. A refrigerator, comprising:
  - a main body having a storage compartment;
  - a door rotatably coupled to an end portion of the main body, the door having baskets to store food and to be arranged on an inner surface of the door;
  - a plurality of cameras provided at the baskets and configured to take at least one picture, the cameras arranged in only a row;
  - a light source provided on the storage compartment;
  - a door opening/closing sensor; and
  - a controller configured to actuate the light source and to control the cameras to take the pictures of the storage compartment when the door opening/closing sensor detects that the door closes the storage compartment, wherein the cameras are located on a middle portion of the storage compartment in a width direction, and wherein the cameras take photos simultaneously.
2. The refrigerator according to claim 1, wherein the cameras have one of cameras arranged on an upper portion and the other of cameras arranged on a lower portion.
3. The refrigerator according to claim 1, wherein the cameras takes photos when the light source is operated.
4. The refrigerator according to claim 1, wherein the controller combines a plurality of pictures taken by the cameras simultaneously.
5. The refrigerator according to claim 1, further comprising:
  - a decorative portion provided on the door, wherein the camera is arranged to the decorative portion.

20

6. The refrigerator according to claim 5, wherein the decorative portion is formed of an opaque material, and the decorative portion has a transparent window at the middle portion of the decorative portion.
7. The refrigerator according to claim 1, further comprising:
  - a storage device configured to store the pictures taken by the cameras; and
  - a communication device configured to transmit the pictures stored in the storage device to an external device.
8. The refrigerator according to claim 7, wherein the storage device stores the picture combined by the controller.
9. The refrigerator according to claim 7, wherein the communication device transmits the last pictures taken by the cameras to the external device.
10. The refrigerator according to claim 7, wherein the communication device transmits the pictures when the controller receives a user's request signal.
11. The refrigerator according to claim 7, wherein the external device includes a terminal having a display that displays the picture.
12. The refrigerator according to claim 11, wherein the terminal is connected to the refrigerator through a network.
13. The refrigerator according to claim 1, wherein the storage compartment includes a refrigerating compartment, and wherein the door opens and closes the refrigerating compartment.
14. The refrigerator according to claim 1, wherein a plurality of racks is provided in the storage compartment.

\* \* \* \* \*