

US010691710B2

(12) **United States Patent**
Reynolds et al.

(10) **Patent No.:** **US 10,691,710 B2**
(45) **Date of Patent:** **Jun. 23, 2020**

(54) **INTERACTIVE INTERFACES AS
COMPUTERIZED TOOLS TO PRESENT
SUMMARIZATION DATA OF DATASET
ATTRIBUTES FOR COLLABORATIVE
DATASETS**

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,144,962 A 11/2000 Weinberg et al.
6,317,752 B1 11/2001 Lee et al.

(Continued)

FOREIGN PATENT DOCUMENTS

WO 2012054860 A1 4/2012
WO 2017190153 A1 11/2017

(Continued)

OTHER PUBLICATIONS

Article entitled "Data.World Comes out of Stealth to Make Open Data Easier", by Austininno, dated Jul. 11, 2016.*

(Continued)

Primary Examiner — Mahesh H Dwivedi

(74) *Attorney, Agent, or Firm* — Kokka & Backus, PC

(71) Applicants: **Shad William Reynolds**, Austin, TX (US); **David Lee Griffith**, Austin, TX (US); **Jon Loyens**, Austin, TX (US); **Bryon Kristen Jacob**, Austin, TX (US)

(72) Inventors: **Shad William Reynolds**, Austin, TX (US); **David Lee Griffith**, Austin, TX (US); **Jon Loyens**, Austin, TX (US); **Bryon Kristen Jacob**, Austin, TX (US)

(73) Assignee: **data.world, Inc.**, Austin, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 665 days.

(21) Appl. No.: **15/454,955**

(22) Filed: **Mar. 9, 2017**

(65) **Prior Publication Data**

US 2017/0364568 A1 Dec. 21, 2017

Related U.S. Application Data

(63) Continuation-in-part of application No. 15/186,514, filed on Jun. 19, 2016, now Pat. No. 10,102,258.

(51) **Int. Cl.**

G06F 16/30 (2019.01)

G06F 16/248 (2019.01)

(Continued)

(52) **U.S. Cl.**

CPC **G06F 16/248** (2019.01); **G06F 3/0482** (2013.01); **G06F 3/0484** (2013.01)

(58) **Field of Classification Search**


CPC **G06F 16/25**

See application file for complete search history.

(57) **ABSTRACT**

Various embodiments relate generally to data science and data analysis, and computer software and systems, to provide an interface between repositories of disparate datasets and computing machine-based entities that seek access to the datasets, and, more specifically, to a computing and data storage platform that facilitates consolidation of one or more datasets, whereby one or more interfaces, such as user interfaces, may be implemented as computerized tools for presenting summarization of dataset attributes to facilitate discovery, formation, and analysis of interrelated collaborative datasets. In some examples, a method may include presenting data representing summary characteristic data in a user interface. This may include user interface elements each specifying a value of a dataset attribute for a collaborative dataset. Also, the method may include presenting aggregated data attributes for a subset of the collaborative dataset associated with the linked atomized datasets. In one example, an interactive overlay window may be activated.

18 Claims, 36 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0053130 A1 2/2017 Hughes et al.
 2017/0075973 A1 3/2017 Miranker
 2017/0132401 A1 5/2017 Gopi et al.
 2017/0161323 A1 6/2017 Simitsis et al.
 2017/0177729 A1 6/2017 Duke et al.
 2017/0228405 A1 8/2017 Ward et al.
 2017/0316070 A1 11/2017 Krishnan et al.
 2017/0357653 A1 12/2017 Bicer et al.
 2017/0364538 A1 12/2017 Jacob et al.
 2017/0364539 A1 12/2017 Jacob et al.
 2017/0364553 A1 12/2017 Jacob et al.
 2017/0364564 A1 12/2017 Jacob et al.
 2017/0364569 A1 12/2017 Jacob et al.
 2017/0364570 A1 12/2017 Jacob et al.
 2017/0364694 A1 12/2017 Jacob et al.
 2017/0364703 A1 12/2017 Jacob et al.
 2017/0371881 A1 12/2017 Reynolds et al.
 2018/0032327 A1 2/2018 Adami et al.
 2018/0210936 A1 7/2018 Reynolds et al.
 2018/0262864 A1 9/2018 Reynolds et al.
 2018/0314705 A1 11/2018 Griffith et al.
 2019/0005104 A1 1/2019 Prabhu et al.
 2019/0034491 A1 1/2019 Griffith et al.
 2019/0042606 A1 2/2019 Griffith et al.
 2019/0050445 A1 2/2019 Griffith et al.
 2019/0050459 A1 2/2019 Griffith et al.
 2019/0065567 A1 2/2019 Griffith et al.
 2019/0065569 A1 2/2019 Boutros et al.
 2019/0066052 A1 2/2019 Boutros et al.
 2019/0079968 A1 3/2019 Griffith et al.
 2019/0095472 A1 3/2019 Griffith
 2019/0121807 A1 4/2019 Boutros et al.

FOREIGN PATENT DOCUMENTS

WO 2017222927 A1 12/2017
 WO 2018156551 A1 8/2018
 WO 2018164971 A1 9/2018

OTHER PUBLICATIONS

Boutros et al., "Computerized Tools to Develop and Manage Data-Driven Projects Collaboratively Via a Networked Computing Platform and Collaborative Datasets," U.S. Appl. No. 15/985,702, filed May 22, 2018.

Boutros et al., "Computerized Tools to Facilitate Data Project Development Via Data Access Layering Logic in a Networked Computing Platform Including Collaborative Datasets," U.S. Appl. No. 15/985,704, filed May 22, 2018.

Boutros et al., "Dynamic Composite Data Dictionary to Facilitate Data Operations Via Computerized Tools Configured to Access Collaborative Datasets in a Networked Computing Platform," U.S. Appl. No. 15/985,705, filed May 22, 2018.

Boutros et al., "Graphical User Interface for a Display Screen or Portion Thereof," U.S. Appl. No. 29/648,465, filed May 22, 2018.

Boutros et al., "Graphical User Interface for a Display Screen or Portion Thereof," U.S. Appl. No. 29/648,466, filed May 22, 2018.

Boutros et al., "Graphical User Interface for a Display Screen or Portion Thereof," U.S. Appl. No. 29/648,467, filed May 22, 2018.

Bullock, Joshua, Non-Final Office Action dated Jun. 28, 2018 for U.S. Appl. No. 15/439,908.

Bullock, Joshua, Non-Final Office Action dated Jun. 28, 2018 for U.S. Appl. No. 15/439,911.

Copenheaver, Blaine R., Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration dated Jul. 5, 2017 for International Patent Application No. PCT/US2017/030474.

Hoang, Hau Hai, Non-Final Office Action dated May 3, 2018 for U.S. Appl. No. 15/186,515.

Joshi, Amit Krishna et al., "Alignment-based Querying of Linked Open Data," Lecture Notes in Computer Science, 7566, 807-824, 2012.

Kahn, Yasar et al., "SAFE: Policy Aware Sparql Query Federation Over RDF Data Cubes," Proceedings of the 7th International Workshop on Semantic Web Applications and Tools for Life Sciences, Berlin, Germany, Dec. 9-11, 2014.

Krishnan et al., U.S. Appl. No. 15/583,966, filed May 1, 2017 and titled "Automatic Generation of Structured Data from Semi-Structured Data."

Martin et al., U.S. Appl. No. 13/457,925, filed Apr. 27, 2012 and titled "Incremental Deployment of Computer Software Program Logic."

Martin et al., U.S. Appl. No. 61/479,621, filed Apr. 27, 2011 and titled "Incremental Deployment of Computer Software Program Logic."

Nguyen, Kim T., Non-Final Office Action dated Jun. 14, 2018 for U.S. Appl. No. 15/186,514.

Parashar et al., U.S. Appl. No. 62/329,982, filed Apr. 29, 2016 and titled "Automatic Parsing of Semi-Structured Data and Identification of Missing Delimiters."

Raab, Christopher J., Non-Final Office Action dated Jun. 28, 2018 for U.S. Appl. No. 15/186,520.

Skevakis, Giannis et al., Metadata management, interoperability and Linked Data publishing support for Natural History Museums, Int J Digit Libr (2014), published online: Apr. 11, 2014; Springer-Verlag Berlin Heidelberg.

Young, Lee W., Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration dated May 29, 2018 for International Patent Application No. PCT/US2018/018906.

Bullock, Joshua, Final Office Action dated Oct. 30, 2018 for U.S. Appl. No. 15/186,517.

Bullock, Joshua, Non-Final Office Action dated Jul. 12, 2018 for U.S. Appl. No. 15/186,517.

Ganti et al., U.S. Appl. No. 14/058,208, filed Oct. 18, 2013 and entitled, "Editable and Searchable Markup Pages Automatically Populated Through User Query Monitoring."

Griffith et al., "Extended Computerized Query Language Syntax for Analyzing Multiple Tabular Data Arrangements in Data-Driven Collaborative Projects," U.S. Appl. No. 16/036,834, filed Jul. 16, 2018.

Griffith et al., "Localized Link Formation to Perform Implicitly Federated Queries Using Extended Computerized Query Language Syntax," U.S. Appl. No. 16/036,836, filed Jul. 16, 2018.

Griffith, David Lee, "Determining a Degree of Similarity of a Subset of Tabular Data Arrangements to Subsets of Graph Data Arrangements at Ingestion Into a Data-Driven Collaborative Dataset Platform," U.S. Appl. No. 16/137,297, filed Sep. 20, 2018.

Griffith, David Lee, "Matching Subsets of Tabular Data Arrangements to Subsets of Graphical Data Arrangements at Ingestion Into Data Driven Collaborative Datasets," U.S. Appl. No. 16/137,292, filed Sep. 20, 2018.

Griffith, David Lee, "Predictive Determination of Constraint Data for Application With Linked Data in Graph-Based Datasets Associated With a Data-Driven Collaborative Dataset Platform," U.S. Appl. No. 16/139,374, filed Sep. 24, 2018.

Haveliwala et al., "Evaluating Strategies for Similarity Search on the Web," Proceedings of the 11th international conference on World Wide Web, May 7-11, 2002, Honolulu, Hawaii, USA (ACM), p. 432-442.

Htay, Lin Lin M., Non-Final Office Action dated Sep. 14, 2018 for U.S. Appl. No. 15/186,516.

Jacob et al., "Collaborative Dataset Consolidation Via Distributed Computer Networks," U.S. Appl. No. 16/120,057, filed Aug. 31, 2018.

Pandit et al., "Using Ontology Design Patterns to Define SHACL Shapes," CEUR Workshop Proceedings, Proceedings of the 9th Workshop on Ontology Design and Patterns (WOP 2018), Monterey, USA, Oct. 9, 2018.

Young, Lee W., International Searching Authority, Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration for International Patent Application No. PCT/US2018/020812, dated Aug. 8, 2018.

(56)

References Cited

OTHER PUBLICATIONS

- Young, Lee W., Invitation to Pay Additional Fees and, Where Applicable, Protest Fee, dated Jun. 14, 2018 for International Application No. PCT/US2018/020812.
- Angles, R., Gutierrez, C., "The Expressive Power of SPARQL," Proceedings of the 7th International Semantic Web Conference (ISWC2008). 2008.
- Arenas, M., et al., "A Direct Mapping of Relational Data to RDF," W3C Recommendation, Sep. 27, 2012, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Beckett, D., Berners-Lee, T., "Turtle—Terse RDF Triple Language," W3C Team Submission, Jan. 14, 2008, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Beckett, D., Broekstra, J., "SPARQL Query Results XML Format," W3C Recommendation, Jan. 15, 2008, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Beckett, Dave, "RDF/XML Syntax Specification (Revised)," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Berners-Lee, Tim, "Notation 3," 2006, Retrieved from the Internet [retrieved on Mar. 7, 2019].
- Berners-Lee, Tim, "Linked Data," 2009, Retrieved from the Internet [retrieved on Mar. 7, 2019].
- Brener et al., "Computerized Tools Configured to Determine Subsets of Graph Data Arrangements for Linking Relevant Data to Enrich Datasets Associated With a Data-Driven Collaborative Dataset Platform," U.S. Appl. No. 16/395,036, filed Apr. 25, 2019.
- Brickley, D., Guha, R.V., "RDF Vocabulary Description Language 1.0: RDF Schema," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Buche et al., "Flexible SPARQL Querying of Web Data Tables Driven by an Ontology," FQAS 2009, LNAI 5822, Springer, 2009, pp. 345-357.
- Bullock, Joshua, Final Office Action dated Jan. 22, 2019 for U.S. Appl. No. 15/439,908.
- Bullock, Joshua, Final Office Action dated Jan. 22, 2019 for U.S. Appl. No. 15/439,911.
- Clark, K., Feigenbaum, L., Torres, E., "SPARQL Protocol for RDF," W3C Recommendation, Jan. 15, 2008, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Czajkowski, K., et al., "Grid Information Services for Distributed Resource Sharing," 10th IEEE International Symposium on High Performance Distributed Computing, pp. 181-184. IEEE Press, New York (2001).
- Dean, M., Schreiber, G., "OWL Web Ontology Language Reference," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Feigenbaum, L., et al., "Semantic Web in Action," Scientific American, pp. 90-97, Dec. 2007.
- Fernandez, J., et al., "Lightweighting the Web of Data through Compact RDF/HDT," Lozano J.A., Moreno J.A. (eds) Advances in Artificial Intelligence. CAEPIA 2011. Lecture Notes in Computer Science, vol. 7023. Springer, Berlin, Heidelberg.
- Foster, I., Kesselman, C., "The Grid: Blueprint for a New Computing Infrastructure," Morgan Kaufmann, San Francisco (1999).
- Foster, I., Kesselman, C., Nick, J., Tuecke, S., "The Physiology of the Grid: An Open Grid Services Architecture for Distributed Systems Integration," Technical Report, Global Grid Forum (2002).
- Ganti et al., U.S. Appl. No. 14/058,184, filed Oct. 18, 2013 and entitled, "Assisted Query Formation, Validation, and Result Pre-viewing in a Database Having a Complex Schema."
- Ganti et al., U.S. Appl. No. 14/058,189, filed Oct. 18, 2013 and entitled, "Assisted Query Formation, Validation, and Result Pre-viewing in a Database Having a Complex Schema."
- Ganti et al., U.S. Appl. No. 14/058,206, filed Oct. 18, 2013 and entitled, "Curated Answers Community Automatically Populated Through User Query Monitoring."
- Ganti et al., U.S. Appl. No. 61/802,716, filed Mar. 17, 2013 and entitled, "Data Profile Driven Query Builder."
- Ganti et al., U.S. Appl. No. 61/802,742, filed Mar. 18, 2013 and entitled, "Developing a Social Data Catalog by Crowd-Sourcing."
- Ganti et al., U.S. Appl. No. 61/802,743, filed Mar. 18, 2013 and entitled, "Creating a Data Catalog by Mining Queries."
- Ganti et al., U.S. Appl. No. 61/802,744, filed Mar. 18, 2013 and entitled, "Auto-Completion of Queries With Data Object Names and Data Profiles."
- Garcia-Molina, H., Ullman, J., Widom, J., Database Systems: The Complete Book. Editorial Pearson Prentice Hall. Second Edition.
- Gawinecki, Maciej, "How schema mapping can help in data integration?—integrating the relational databases with ontologies," ITC School, Computer Science, XXIII Cycle DII, University of Modena and Reggio Emilia, Italy, 2008.
- Girma, Anteneh B., Final Office Action for U.S. Appl. No. 13/278,907, dated Apr. 18, 2013.
- Girma, Anteneh B., Non-Final Office Action for U.S. Appl. No. 13/278,907, dated Jul. 25, 2012.
- Grant, J., Beckett, D., "RDF Test Cases," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Hayes, Patrick, "RDF Semantics," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Heflin, J., "OWL Web Ontology Language Use Cases and Requirements," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Hoang, Hau Hai, Final Office Action dated Nov. 26, 2018 for U.S. Appl. No. 15/186,515.
- Hoang, Hau Hai, Non-Final Office Action dated Apr. 16, 2019 for U.S. Appl. No. 15/186,515.
- Htay, Lin Lin M., Notice of Allowance and Fee(s) Due and Notice of Allowability for U.S. Appl. No. 15/186,516, dated Jan. 25, 2019.
- Hu, Xiaoqin, Final Office Action dated Apr. 5, 2019 for U.S. Appl. No. 15/454,969.
- Hu, Xiaoqin, Final Office Action dated Apr. 5, 2019 for U.S. Appl. No. 15/454,981.
- Hu, Xiaoqin, Non-Final Office Action for U.S. Appl. No. 15/454,969 dated Dec. 7, 2018.
- Hu, Xiaoqin, Non-Final Office Action for U.S. Appl. No. 15/454,981 dated Dec. 12, 2018.
- J. Perez, M. Arenas, C. Gutierrez, "Semantics and Complexity of SPARQL," ACM Transactions on Database Systems (TODS), Vol. 34, No. 3, Article 16, Publication Date: Aug. 2009.
- Jacob et al., "Collaborative Dataset Consolidation Via Distributed Computer Networks," U.S. Appl. No. 16/287,967, filed Feb. 27, 2019.
- Langedgger, Andreas, "XL Wrap—Spreadsheet-to-RDF Wrapper," 2009, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Lee, Mark B., Non-Final Office Action for U.S. Appl. No. 13/180,444 dated Jul. 2, 2012.
- Lenz, H.J., Shoshani, A., "Summarizability in OLAP and Statistical Data Bases," Proceedings of the Ninth International Conference on Scientific and Statistical Database Management, 1997.
- Manola, F., Miller, E., "RDF Primer," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].
- May, P., Ehrlich, H.C., Steinke, T., "ZIB Structure Prediction Pipeline: Composing a Complex Biological Workflow through Web Services," In: Nagel, W.E., Walter, W.V., Lehner, W. (eds.) Euro-Par 2006. LNCS, vol. 4128, pp. 1148-1158. Springer, Heidelberg (2006).
- McGuinness, D., Van Harmelen, F., "OWL Web Ontology Language Overview," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Miranker, Daniel Paul, "Accessing Relational Databases as Resource Description Framework Databases," U.S. Appl. No. 61/406,021, filed Oct. 22, 2010.
- Miranker, Daniel Paul, "Automatic Synthesis and Presentation of OLAP Cubes from Semantically Enriched Data Sources," U.S. Appl. No. 61/362,781, filed Jul. 9, 2010.
- National Center for Biotechnology Information, Website, Retrieved from the Internet [retrieved Mar. 7, 2019].
- Nguyen, Kim T., Non-Final Office Action dated Mar. 20, 2019 for U.S. Appl. No. 15/454,923.
- Niinimäki et al., "An ETL Process for OLAP Using RDF/OWL Ontologies," Journal on Data Semantics XIII, LNCS 5530, Springer, pp. 97-119, Aug. 12, 2009.

(56)

References Cited

OTHER PUBLICATIONS

Patel-Schneider, P., Hayes, P., Horrocks, I., "OWL Web Ontology Language Semantics and Abstract Syntax," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].

Perez, J., Arenas, M., Gutierrez, C., "Semantics and Complexity of SPARQL," In Proceedings of the International Semantic Web Conference (ISWC2006). 2006.

Prud'hommeaux, E., Seaborne, A., "SPARQL Query Language for RDF," W3C Recommendation, Jan. 15, 2008, Retrieved from the Internet [Mar. 7, retrieved 2019].

Raab, Christopher J., Notice of Allowance and Fee(s) Due and Notice of Allowability for U.S. Appl. No. 15/186,520, dated Jan. 2, 2019.

RDB2RDF Working Group Charter, Sep. 2009, Retrieved from the Internet [retrieved Mar. 7, 2019].

Sahoo, S., et al., "A Survey of Current Approaches for Mapping of Relational Databases to RDF," W3C RDB2RDF XG Report, Incubator Group, Published Jan. 8, 2009.

Sequeda, J., Depena, R., Miranker, D., "Ultrawrap: Using SQL Views for RDB2RDF," Poster in the 8th International Semantic Web Conference (ISWC2009), Washington DC, US, 2009.

Sequeda, J., et al., "Direct Mapping SQL Databases to the Semantic Web," Technical Report Sep. 2004. The University of Texas at Austin, Department of Computer Sciences. 2009.

Sequeda, J., et al., "Ultrawrap: SPARQL Execution on Relational Data," Technical Report. The University of Texas at Austin, Department of Computer Sciences. 2012.

Sequeda, J., Tirmizi, S., Miranker, D., "SQL Databases are a Moving Target," Position Paper for W3C Workshop on RDF Access to Relational Databases, Cambridge, MA, USA, 2007.

Smith, M., Welty, C., McGuinness, D., "OWL Web Ontology Language Guide," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].

Smith, T.F., Waterman, M.S., "Identification of Common Molecular Subsequences," J. Mol. Biol. 147, 195-197 (1981).

Tirmizi, S., Sequeda, J., Miranker, D., "Translating SQL Applications to the Semantic Web," In Proceedings of the 19th International Databases and Expert Systems Application Conference (DEXA2008). Turin, Italy. 2008.

U.S. Appl. No. 16/251,408, filed Jan. 18, 2019.

Ultrawrap Mapper, U.S. Appl. No. 62/169,268, filed Jun. 1, 2015 (Expired).

Vy, Hung T., Final Office Action for U.S. Appl. No. 13/180,444 dated Dec. 3, 2014.

Vy, Hung T., Final Office Action for U.S. Appl. No. 13/180,444 dated Dec. 9, 2015.

Vy, Hung T., Final Office Action for U.S. Appl. No. 13/180,444 dated Feb. 22, 2013.

Vy, Hung T., Non-Final Office Action for U.S. Appl. No. 13/180,444 dated Jun. 18, 2015.

Vy, Hung T., Non-Final Office Action for U.S. Appl. No. 13/180,444 dated Mar. 26, 2014.

Vy, Hung T., Non-Final Office Action for U.S. Appl. No. 15/273,930 dated Dec. 20, 2017.

Yen, Syling, Final Office Action dated Apr. 10, 2019 for U.S. Appl. No. 15/186,519.

Yen, Syling, Non-Final Office Action dated Feb. 8, 2019 for U.S. Appl. No. 15/186,519.

Young, Lee W., Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration for International Application No. PCT/US2011/057334, dated Mar. 22, 2012.

Jacob et al., "Dataset Analysis and Dataset Attribute Inferencing to Form Collaborative Datasets," U.S. Appl. No. 16/292,120, filed Mar. 4, 2019.

Jacob et al., "Dataset Analysis and Dataset Attribute Inferencing to Form Collaborative Datasets," U.S. Appl. No. 16/271,263, filed Feb. 8, 2019.

Jacob et al., "Management of Collaborative Datasets Via Distributed Computer Networks," U.S. Appl. No. 16/271,687, filed Feb. 8, 2019.

Jacob et al., "Management of Collaborative Datasets Via Distributed Computer Networks," U.S. Appl. No. 16/292,135, filed Mar. 4, 2019.

Jacob et al., "Query Generation for Collaborative Datasets," U.S. Appl. No. 16/395,043, filed Apr. 25, 2019.

Jacob et al., "Query Generation for Collaborative Datasets," U.S. Appl. No. 16/395,049, filed Apr. 25, 2019.

Khong, Alexander, Non-Final Office Action for U.S. Appl. No. 15/165,775, dated Jun. 14, 2018.

Klyne, G., Carroll, J., "Resource Description Framework (RDF): Concepts and Abstract Syntax," W3C Recommendation, Feb. 10, 2004, Retrieved from the Internet [retrieved Mar. 7, 2019].

Griffith et al., "Aggregation of Ancillary Data Associated With Source Data in a System of Networked Collaborative Datasets," U.S. Appl. No. 15/927,006, filed Mar. 20, 2018.

Griffith et al., "Data Ingestion to Generate Layered Dataset Interrelations to Form a System of Networked Collaborative Datasets," U.S. Appl. No. 15/926,999, filed Mar. 20, 2018.

Griffith et al., "Layered Data Generation and Data Remediation to Facilitate Formation of Interrelated Data in a System of Networked Collaborative Datasets," U.S. Appl. No. 15/927,004, filed Mar. 20, 2018.

Griffith et al., "Link-Formative Auxiliary Queries Applied at Data Ingestion to Facilitate Data Operations in a System of Networked Collaborative Datasets," U.S. Appl. No. 15/943,633, filed Apr. 2, 2018.

Griffith et al., "Transmuting Data Associations Among Data Arrangements to Facilitate Data Operations in a System of Networked Collaborative Datasets," U.S. Appl. No. 15/943,629, filed Apr. 2, 2018.

Jacob et al., "Platform Management of Integrated Access of Public and Privately-Accessible Datasets Utilizing Federated Query Generation and Schema Rewriting Optimization," International Patent Application No. PCT/US2018/018906 filed Feb. 21, 2018.

Reynolds et al., "Computerized Tool Implementation of Layered Data Files to Discover, Form, or Analyze Dataset Interrelations of Networked Collaborative Datasets," U.S. Appl. No. 15/454,981, filed Mar. 9, 2017.

Reynolds et al., "Computerized Tools to Discover, Form, and Analyze Dataset Interrelations Among a System of Networked Collaborative Datasets," International Patent Application No. PCT/US2018/020812 filed Mar. 3, 2018.

Reynolds et al., "Interactive Interfaces to Present Data Arrangement Overviews and Summarized Dataset Attributes for Collaborative Datasets," U.S. Appl. No. 15/454,969, filed Mar. 9, 2017.

Young, Lee W., International Searching Authority, Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration for International Patent Application No. PCT/US2017/037846, dated Nov. 9, 2017.

Hoang, Hau Hai, Final Office Action dated Jul. 30, 2019 for U.S. Appl. No. 15/186,515.


Hu, Xiaoqin, Non-Final Office Action dated Aug. 1, 2019 for U.S. Appl. No. 15/454,981.

Hu, Xiaoqin, Non-Final Office Action dated Jul. 26, 2019 for U.S. Appl. No. 15/454,969.

Nguyen, Kim T., Notice of Allowance and Fee(s) Due, dated May 15, 2019 for U.S. Appl. No. 15/454,923.

Yen, Syling, Non-Final Office Action dated Sep. 12, 2019 for U.S. Appl. No. 15/186,519.

* cited by examiner



200 →




FIG. 2

300 ↘




FIG. 3




FIG. 4

500




FIG. 5A





FIG. 5B






FIG. 7

800 ↘




FIG. 8





FIG. 9

1000

1002




FIG. 10

1100

1102




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15

1600 ↘




FIG. 16

1700




FIG. 17




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 19

2000 →

2002




FIG. 20

2100




FIG. 21

2200




FIG. 22

2300 →






FIG. 23






FIG. 25

2600 →




FIG. 26




FIG. 27

2800 →




FIG. 28

2900




FIG. 29




FIG. 30A




FIG. 30B




FIG. 30C




FIG. 30D




FIG. 30E




FIG. 30F

3100 ↘




FIG. 31




FIG. 32

3300 ↗




FIG. 33




FIG. 34

1

**INTERACTIVE INTERFACES AS
COMPUTERIZED TOOLS TO PRESENT
SUMMARIZATION DATA OF DATASET
ATTRIBUTES FOR COLLABORATIVE
DATASETS**

CROSS-REFERENCE TO APPLICATIONS

This application is a continuation-in-part application of U.S. patent application Ser. No. 15/186,514, filed on Jun. 19, 2016, and titled "COLLABORATIVE DATASET CONSOLIDATION VIA DISTRIBUTED COMPUTER NETWORKS," which is herein incorporated by reference in its entirety for all purposes.

FIELD

Various embodiments relate generally to data science and data analysis, computer software and systems, and wired and wireless network communications to provide an interface between repositories of disparate datasets and computing machine-based entities that seek access to the datasets, and, more specifically, to a computing and data storage platform that facilitates consolidation of one or more datasets, whereby one or more interfaces, such as user interfaces, may be implemented as computerized tools for presenting summarization of dataset attributes to facilitate discovery, formation, and analysis of interrelated collaborative datasets.

BACKGROUND

Advances in computing hardware and software have fueled exponential growth in the generation of vast amounts of data due to increased computations and analyses in numerous areas, such as in the various scientific and engineering disciplines, as well as in the application of data science techniques to endeavors of good-will (e.g., areas of humanitarian, environmental, medical, social, etc.). Also, advances in conventional data storage technologies provide the ability to store the increasing amounts of generated data. Consequently, traditional data storage and computing technologies have given rise to a phenomenon in which numerous disparate datasets have reached sizes and complexities that traditional data-accessing and analytic techniques are generally not well-suited for assessing conventional datasets.

Conventional technologies for implementing datasets typically rely on different computing platforms and systems, different database technologies, and different data formats, such as CSV, TSV, HTML, JSON, XML, etc. Further, known data-distributing technologies are not well-suited to enable interoperability among datasets. Thus, many typical datasets are warehoused in conventional data stores, which are generally "data silos," whereby data in the associated data stores are often difficult to connect to other sources of data. These data silos have inherent barriers that insulate and isolate datasets. Further, conventional data systems and dataset accessing techniques are generally incompatible or inadequate to facilitate data interoperability among the data silos.

Conventional approaches to provide dataset generation and management, while functional, suffer a number of other drawbacks. For example, disparate approaches to gathering, forming, and analyzing datasets typically require different, ad hoc approaches. For example, data scientists and other consumers of data generally undertake significant effort during a variety of steps in which a dataset is downloaded

2

and analyzed. In particular, data practitioners usually perform personalized queries and data analyses, manually, on the downloaded dataset to determine whether the downloaded dataset is of any use. Contextual information for understanding the downloaded dataset is usually absent, due to the ad hoc nature of dataset development, thereby complicating the process by which data practitioners assess the worthiness of a dataset. Further, differently-formatted repositories of data provide further challenges when assessing multiple dataset with multiple versions of ad hoc queries. Hence, these approaches are not typically well-suited to resolve sufficiently the drawbacks of traditional techniques of dataset generation and analysis. Moreover, traditional dataset generation and management are not well-suited to reducing efforts by data scientists and data practitioners in extracting, transforming, and loading data into data stores in a manner that serves their desired objectives.

Thus, what is needed is a solution for facilitating techniques to discover, form, and analyze datasets, without the limitations of conventional techniques.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments or examples ("examples") of the invention are disclosed in the following detailed description and the accompanying drawings:

FIG. 1 is a diagram depicting computerized tools to discover, form, and/or analyze collaborative datasets, according to some embodiments;

FIG. 2 is a diagram depicting an example of programmatic interface, according to some examples;

FIG. 3 is a diagram depicting a flow diagram as an example of collaborative dataset creation, according to some embodiments;

FIG. 4 is a diagram depicting a collaborative dataset consolidation system, according to some embodiments;

FIG. 5A is a diagram depicting an example of an atomized data point, according to some embodiments;

FIG. 5B is a diagram depicting operation an example of a collaborative dataset consolidation system, according to some examples;

FIG. 6 is a diagram depicting an example of a dataset analyzer and an inference engine, according to some embodiments;

FIG. 7 is a diagram depicting operation of an example of an inference engine, according to some embodiments;

FIG. 8 is a diagram depicting a flow diagram as an example of ingesting an enhanced dataset into a collaborative dataset consolidation system, according to some embodiments;

FIG. 9 is a diagram depicting a dataset creation interface, according to some embodiments;

FIG. 10 is a diagram of an example of a user interface depicting progression of phases during creation of a dataset, according to some embodiments;

FIG. 11 is a diagram of an example of a user interface configured to enhance dataset attribute data for a dataset, according to some embodiments;

FIG. 12 is a diagram depicting an example of a data ingestion controller configured to generate a set of layer data files, according to some examples;

FIG. 13 is a diagram depicting a user interface in association with generation and presentation of the derived subset of data, according to some examples;

FIGS. 14 and 15 are diagrams depicting examples of generating and presenting derived columns and derived data, according to some examples;

FIG. 16 is a diagram depicting a flow diagram as an example of enhanced collaborative dataset creation based on a derived dataset attribute, according to some embodiments;

FIG. 17 is a diagram depicting an example of a collaboration manager configured to present collaborative information regarding collaborative datasets, according to some embodiments;

FIG. 18A depicts an example of a dataset attribute manager configured to generate data to enhance datasets, according to some examples;

FIGS. 18B and 18C are diagrams that depict examples of calculators to determine trend data and relevancy data relating to collaborative datasets, according to some examples;

FIG. 19 is a diagram depicting an example of a dataset activity feed to present dataset interaction control elements in a user interface, according to some embodiments;

FIG. 20 is a diagram depicting other examples of dataset activity feeds to present a dataset recommendation feed, according to some embodiments;

FIG. 21 is a diagram depicting examples of trend-related dataset activity feeds to facilitate presentation and interaction with user interface elements, according to some embodiments;

FIG. 22 is a diagram depicting other examples of relevancy-related dataset activity feeds to facilitate presentation and interaction with user interface elements, according to some embodiments;

FIG. 23 is an example of a data entry interface to access atomized datasets, according to some examples;

FIG. 24 is an example of a user interface to present interactive user interface elements to provide a data overview of a dataset, according to some examples;

FIG. 25 is an example of a user interface to present interactive user interface elements for another data preview of a dataset, according to some examples;

FIG. 26 is a diagram depicting a flow diagram to present interactive user interface elements for a data overview of a dataset, according to some embodiments;

FIG. 27 is an example of a user interface to present interactive user interface elements for conveying summary characteristics of a dataset, according to some examples;

FIG. 28 is a diagram depicting a flow diagram to present summary characteristics for a dataset in an interactive overlay window, according to some embodiments;

FIG. 29 is a diagram depicting an example in which a subset of data may be analyzed to determine a graphical representation of the data distribution, according to some examples;

FIGS. 30A to 30F are diagrams depicting examples of interactive overlay windows, according to some examples;

FIG. 31 is a diagram depicting a flow diagram to form various interactive overlay windows, according to some embodiments;

FIG. 32 is a diagram depicting an example of a dataset access interface, according to some examples;

FIG. 33 is a diagram depicting a flow diagram to implement a dataset access interface, according to some embodiments; and

FIG. 34 illustrates examples of various computing platforms configured to provide various functionalities to components of a collaborative dataset consolidation system, according to various embodiments.

DETAILED DESCRIPTION

Various embodiments or examples may be implemented in numerous ways, including as a system, a process, an

apparatus, a user interface, or a series of program instructions on a computer readable medium such as a computer readable storage medium or a computer network where the program instructions are sent over optical, electronic, or wireless communication links. In general, operations of disclosed processes may be performed in an arbitrary order, unless otherwise provided in the claims.

A detailed description of one or more examples is provided below along with accompanying figures. The detailed description is provided in connection with such examples, but is not limited to any particular example. The scope is limited only by the claims, and numerous alternatives, modifications, and equivalents thereof. Numerous specific details are set forth in the following description in order to provide a thorough understanding. These details are provided for the purpose of example and the described techniques may be practiced according to the claims without some or all of these specific details. For clarity, technical material that is known in the technical fields related to the examples has not been described in detail to avoid unnecessarily obscuring the description.

FIG. 1 is a diagram depicting computerized tools to discover, form, and/or analyze collaborative datasets, according to some embodiments. Diagram 100 depicts an example of a subset of user interfaces to facilitate implementation of computerized tools at a computing device 109a (as well as computing devices 102a, 102b, and 102n) or a collaborative dataset consolidation system 110, or both. Computing device 109a may be configured to interoperate via a programmatic interface 190 with collaborative dataset consolidation system 110. Programmatic interface 190 may be configured to facilitate functionalities of user interfaces 102, 122, and 132, and further configured to facilitate data exchanges with collaborative dataset consolidation system 100, and among computing device 109a and computing devices 102a, 102b, and 102n.

A first example of a computerized tool is shown implemented as dataset creation interface 102, which may be configured to create a dataset, according to various embodiments. A collaborative dataset, according to some non-limiting examples, is a set of data that may be configured to facilitate data interoperability over disparate computing system platforms, architectures, and data storage devices, and collaboration between multiple users or agents. Further, a collaborative dataset may also be associated with data configured to establish one or more associations (e.g., metadata) among subsets of dataset attribute data for datasets, whereby attribute data, such as dataset attributes, may be used to determine correlations (e.g., data patterns, trends, rankings per unit time, etc.) among the collaborative datasets. Collaborative datasets, with or without associated dataset attribute data, may be used to facilitate easier collaborative dataset interoperability among sources of data, which may be formatted differently at origination, or may be disposed at disparate data stores (e.g., repositories at different geographical locations). In some examples, the term “collaborative dataset” may be used interchangeably with “consolidated dataset.”

Dataset creation interface 102 may be used to create, or initiate creation of, a collaborative dataset via computing device 109a, which may be associated with a user 108a. As shown, dataset creation interface 102 includes a number of user interface elements to facilitate dataset creation, such as a search field 121, a dataset description field 103, a file upload interface 106, a create dataset activation input 141, and any other type of user interface element that may be used to create a dataset that, in turn, may be transformed into

atomized datasets, such as atomized dataset **142a** stored in repository **140**. According to various examples, user interface elements may constitute a subset of one or more structures and/or functions of computerized tools described herein. “User interface element” may refer to, at least in some examples, a subset of executable instructions that interfaces or interacts with one or more applications or programs to initiate, facilitate, and/or perform execution of instructions in accordance with various implementations set forth herein. In some cases, at least one user interface element and at least one subset of executable instructions (e.g., in applications, modules, software components, etc.) may interoperate in combination to set forth one or more specialized functions or structures described herein.

To illustrate operation of dataset creation interface **102**, consider that user **108a** via computing device **109a** initiates a computer-based action in which a user interface element representing a file **105** is selected and dragged via pointer element **107** (e.g., a pointer device, or any other interface selection tool, including a finger) into file upload interface **106**. Computing device **109a** may detect a data signal generated by the implementation of “create dataset” input **141**, which may initiate creation of the dataset. As an example, consider that file **105** may include data formatted in a particular data arrangement, such as formatted as a CSV file, a TSV, an XLS file, or the like. In one example, a set of data **104** from file **105** may be uploaded, responsive to dragging icon of file **105** to upload interface **106**, into collaborative dataset consolidation system **110**, which, in turn, may generate an atomized dataset **142a**. An atomized dataset **142a** may include a data arrangement in which data is stored as an atomized data point **114** that, for example, may be an irreducible or simplest representation of data that may be linkable to other atomized data points, according to some embodiments. Note that in some examples, atomized dataset **142a** may be linked (e.g., during the dataset creation process) via links **111** to other datasets, such as public datasets **113a** and **113b**, to form a collaborative dataset. Public datasets **113a** and **113b** may originate external to collaborative dataset consolidation system **110**, such as at computing device **102a** and computing device **102b**, respectively. Users **101a** and **101b** are shown to be associated with computing devices **102a** and **102b**, respectively.

Logic in computing device **109a** or collaborative dataset consolidation system **110**, or both, may be configured to identify and/or derive attributes (e.g., dataset attributes) of the collaborative dataset, whereby logic may be implemented in hardware, software, or a combination thereof. In some cases, dataset attributes may be identified in the text description of the information entered into dataset description field **103**. In some cases, the logic may implement natural language processing, or the like, to parse through strings of text to identify key words for implementation as dataset attributes. In other cases, collaborative dataset consolidation system **110** may identify or derive attributes based on annotations or other information related to set of data **104** (e.g., annotations based on column header data, etc.).

In some embodiments, collaborative dataset consolidation system **110** may provide access limited to the dataset attributes associated with the collaborative dataset rather than the data (e.g., atomized data points **114**). Therefore, user **108a** may enter search terms into the search field **121** to search for any relevant datasets that may augment or otherwise supplement a current collaborative dataset. To illustrate, consider that a search via field **121** identifies dataset **113n** as having relevant data attributes. Note, however, that dataset **113n** is shown as a “private dataset” that includes

protected data **131c**. Access to dataset **113n** may be permitted via computing device **102n** by administrative user **101n**. Therefore, user **108a** via computing device **109a** may initiate a request to access protected data **131c** through secured link **119** upon activation of user input (“link”) **143**, or by providing authorized credential data to retrieve data via secured link **119**. Collaborative dataset **142a** then may be supplemented by linking to protected data **131c** to form a larger atomized dataset that includes data from datasets **142a**, **113a**, **113b**, and **113n**. According to various examples, a “private dataset” may have one or more levels of security. For example, a private dataset as well as metadata describing the private dataset may be entirely inaccessible by non-authorized users of collaborative dataset consolidation system **110**. Thus, a private dataset may be shielded or invisible to searches performed via search field **121**. In another example, a private dataset may be classified as “restricted,” or inaccessible (e.g., without authorization), whereby its associated metadata describing dataset attributes of the private dataset may be accessible so the dataset may be discovered via search field **121** or identified by any other mechanism. A restricted dataset may be accessed via authorization credentials, according to some examples.

A second example of a computerized tool is shown implemented as collaborative dataset access interface **122**, which may be configured to access or otherwise query a collaborative database through a data entry interface **124**. According to some examples, data entry interface **124** may be configured to accept commands (e.g., queries) in high-level languages (e.g., high-level programming languages, including object-oriented languages, etc.), such as in Python™ and structured query language (“SQL”), among others. Further, commands in a high-level language may be converted into a graph-level access or query language, such as SPARQL or the like. Thus, a query may be initiated at computing device **109a** via user interface **122** to query data associated with the atomized dataset (e.g., data from datasets **142a**, **113a**, **113b**, and **113n**). In some examples, data entry interface **124** may be configured to accept programming languages for facilitating other data operations, such as statistical and data analysis. Examples of programming languages to perform statistical and data analysis include “R,” which is maintained and controlled by “The R Foundation for Statistical Computing” at [www\(dot\)r-project\(dot\)org](http://www(dot)r-project(dot)org), as well as other like languages or packages, including applications that may be integrated with R (e.g., such as MATLAB™, Mathematica™, etc.).

A third example of a computerized tool is shown as collaborative activity interface **132**, which may be configured to facilitate collaboration of dataset **142a** among other datasets and among other users. In some examples, collaborative dataset consolidation system **110** may determine correlations among datasets and dataset interactions, whereby the correlations may be fed via a dataset activity feed **134** to disseminate dataset-related information via computing device **109a** to user **108a**, as well as via other computing devices **102a**, **102b**, and **102n** to other users **101a**, **101b**, and **101n**. Examples of notifications presented in dataset activity feed **134** may include information describing dataset interactions relating to an event in which a particular dataset (e.g., a relevant dataset of interest) has been queried, modified, shared, accessed, created, etc., or an event in which another user commented on a dataset or received a comment for a dataset, etc. For example, a user, such as user **101b**, may post comments and notes electronically to a user account of user **108a**, as a contributor (e.g., “Hi user **108a**. This is user **101b**—I noticed that a value is

missing in column XX.” Would you like me to correct this as a contributor?). User **101b** may activate a user input (not shown) to generate a “like” data signal or a “bookmarked” data signal in association with user’s **108a** dataset **142a**. The “like” data signals may cause a notification to be generated for presentation in dataset activity feed **134** (e.g., “User **101b** *likes* your dataset **142a**”). Similarly, “bookmarked” data signals may cause another notification to be generated for presentation in dataset activity feed **134** (e.g., “User **101b** *has bookmarked* and saved a link to your dataset **142a**”).

Dataset activity feed **134** may present information describing trending dataset and/or user information, whereby a particular subset of datasets (or dataset users) may be of predominant interest among a community during a period of time. Users of predominant interest may be indicated by relatively high rankings, relatively high numbers of comments, a number of “likes,” etc. As shown, dataset collaboration may be initiated in a collaboration request portion **136** of interface **132**, whereby activation of user input (“collaborate”) **135** may facilitate sharing of datasets or commentary among datasets. For example, user input **135** may be activated to “add a contributor,” who may be invited to assist or collaborate in data collection and analysis. User **108a** may grant certain levels of access or permissions (e.g., “view only” permission, “view and edit” permission, etc.) In the event a certain dataset is protected, then user **108a** may request access upon activation of input (“link”) **137** in dataset access request portion **138**. User interface element **139**, when selected, may generate a request to seek authorization to access the particular dataset. Thus, a community of users **108a**, **101a**, **101b**, and **101n**, as well as any other participating user, may discover and share dataset-related information in real-time (or substantially in real-time) in association with collaborative datasets. According to various embodiments, one or more structural and/or functional elements described in FIG. **1**, as well as below, may be implemented in hardware or software, or both.

In view of the foregoing, the structures and/or functionalities depicted in FIG. **1** illustrate computerized tools configured to discover, form, and analyze, for example, via one or more user interface applications, collaborative datasets and interrelations among a system of networked collaborative datasets, according to some embodiments. User interfaces, and user interface elements therein, may be configured to create collaborative datasets by, for example, causing datasets to link automatically to other datasets. For example, collaborative datasets may be formed by “suggesting” similar or related compatible datasets upon ingesting a dataset and building a model of its metadata or schema. In various examples, creation of a dataset may including forming links among atomized datasets, whereby at least some links can be formed via graph data (e.g., at levels at which graph data arrangements are stored in, for example, graph databases). According to some embodiments, graph data arrangements may facilitate connecting and relating increasing amounts of data relative to other data storage technologies that may be relatively inflexible in adapting to increased amounts of data (e.g., increases in relatively large amounts of data). Also, user interfaces and user interface elements may be configured to provide varying levels of access to one or more datasets. For example, a user interface as a computerized tool may be configured to supplement a collaborative dataset by linking, for example, to protected data **131c** to form a larger atomized dataset including data from datasets **142a**, **113a**, **113b**, and **113n**.

Further, the structures and/or functionalities depicted in FIG. **1** illustrate computerized tools configured to establish

and evaluate whether a particular dataset may be useful or satisfactory in, for example, forming a collaborative dataset that may be used to form data models. The data models may be used to analyze datasets to prove theories set forth by data scientists, statisticians, data practitioners, and the like. In one example, dataset creation interface **102** may be configured to initiate creation of a dataset during which “insight” information may be generated. During dataset creation, a set of data or a dataset may be optionally normalized by, for example, forming a hashed representation of the contents of a file (i.e., a reduced or compressed representation of the data file), whereby a hash value may be used for content addressing.

“Insight information” may refer, in some examples, to information that may automatically convey (e.g., visually in text and/or graphics) dataset attributes of a created dataset, including derived dataset attributes, during or after (e.g., shortly thereafter) the creation of the dataset. In some examples, a user need not further manipulate the data by applying, for example, statistical algorithms against the created dataset to view insight information. Insight information presented in a user interface (e.g., responsive to dataset creation) may describe various aspects of a dataset, in summary form, such as, but not limited to, annotations (e.g., of columns, cells, or any portion of data), data classifications (e.g., a geographical location, such as a zip code, etc.), datatypes (e.g., string, numeric, categorical, Boolean, integer, etc.), a number of data points, a number of columns, a “shape” or distribution of data and/or data values, a number of empty or non-empty cells in a tabular data structure, a number of non-conforming data (e.g., a non-numeric data value in column expecting a numeric data, an image file, etc.) in cells of a tabular data structure, a number of distinct values, etc. According to some embodiments, initiation of the dataset creation process invoked at user input **141** may also perform statistical data analysis during or upon the creation of the dataset. For example, logic disposed in collaborative dataset consolidation system **110** or at a client computing device, or both, may be configured to determine statistical characteristics as dataset attributes of a linked collaborative dataset. For instance, the logic can be configured to calculate a mean of the dataset distribution, a minimum value, maximum value, a value of standard deviation, a value of skewness, a value of kurtosis, etc., among any type of statistic or characteristic. As such, a user, when determining whether to use a dataset, need not download a dataset to perform ad hoc data analysis (e.g., creating and running a Python script against downloaded data to perform a statistical analysis, or the like) to identify characteristics of a distribution of data as well as visualization of the distribution.

Additionally, the structures and/or functionalities depicted in FIG. **1** illustrate computerized tools configured to identify interactions among a set of any number of datasets that may include user datasets, a group of other user datasets, a group of non-user datasets (e.g., datasets external to collaborative dataset consolidation system **110**), and the like. Correlations among datasets and dataset interactions may be calculated and summarized for presentation via, for example, dataset activity feed **134** to provide a user **108a** with dataset-related information, such as whether a particular dataset of has been queried, modified, shared, accessed, created, etc., or an event in which another user commented on a dataset or received a comment for a dataset. Therefore, data practitioners may gain additional insights into whether a particular dataset may be relevant based on electronic social interactions among datasets and users. For example, a

dataset may be associated with a rating (e.g., a number between 1 to 10, as aggregated among numeric rankings voted upon by other users), whereby the rating may be indicative of the “applicability” or “quality” of the dataset. Other examples may include data representations via dataset activity feed **134** that conveys a number of queries associated with a dataset, a number of dataset versions, identities of users (or associated user identifiers) who have analyzed a dataset, a number of user comments related to a dataset, the types of comments, etc.). Thus, at least some implementations described herein may provide for “a network for datasets” (e.g., a “social” network of datasets and dataset interactions). While “a network for datasets” need not be based on electronic social interactions among users, various examples provide for inclusion of users and user interactions (e.g., social network of data practitioners, etc.) to supplement the “network of datasets.” Collaboration among users and formation of collaborative datasets therefore may expedite dataset analysis and hypothesis testing based on up-to-date information provided by dataset activity feed **134**, whereby a user may more readily determine applicability of a dataset to modeling data and/or proving a theory.

FIG. **2** is a diagram depicting an example of programmatic interface, according to some examples. Diagram **200** depicts an example of a programmatic interface **202** that may be configured to facilitate data exchange and execution of instructions among any number of applications disposed in either one or more client computing devices **209** or one or more server computing devices **219**, or any combination thereof. Programmatic interface **202** may include one or more subsets of executable code and, optionally, one or more processors for performing any number of functions by executing the executable code. Programmatic interface **202** may be configured to facilitate data communications and execution over any number of processors and data stores (e.g., hardware), and may provide for execution of instructions at either computing device **209** or computing device **219**, or over both devices **209** and **219** via network **201**. Thus, programmatic interface **202** may facilitate performance of any of one or more functions described herein at either client computing device **209** or server computing device **219**, as well as facilitating collaborative computing via data **229** exchanges over network **201** between client computing device **209** and server computing device **219**.

Further to diagram **200**, client-side executable code **220** may be implemented in association with computing device **209**, and may include, for example, a browser application **222**, one or more APIs **224**, and any other programmatic code **226** for performing functions described herein. Also shown in diagram **200**, server-side executable code **230** may include, for example, a web server application **232**, one or more APIs **234**, and any other programmatic code **236** for performing functions described herein. To illustrate a subset of operations of programmatic interface **202**, consider that data (e.g., raw data in sets of data) may be transmitted over network **201** (e.g., from server computing device **219** or any other source of data) to computing device **209** at which dataset creation (or any other function described herein, such as insight generation) may be initiated and performed by executing client-side executable code **220**. As another example, consider that execution of client-side executable code **220** may cause data to be transferred to server computing device **219** from client computing device **209** or any other source of data. Server-side executable code **230** may be executed to create, for example, datasets and insight information, and to provide access to the created datasets and insight information via data exchanges **229** to client

computing device **209**. Note that these examples are not limiting and that any function (or constituent portion thereof) may be performed at any subset of executable instructions disposed at one or more of computing devices **209** and **219**.

According to some examples, programmatic interface **202** may facilitate data communication and interaction, including instruction execution, among one or more similar or different computer hardware platforms, one or more similar or different operating systems, one or more similar or different programming languages and levels thereof (e.g., from high-level to low-level programming languages), one or more similar or different processes, procedures, and objects, one or more similar or different protocols, and the like. According to some examples, programmatic interface **202** (or a portion thereof) may be implemented as an application programming interface, or “API,” or as any number of APIs.

FIG. **3** is a diagram depicting a flow diagram as an example of collaborative dataset creation, according to some embodiments. Flow **300** may be an example of initiating creation of the dataset, such as a collaborative dataset, based on a set of data. In some examples, flow **300** may be implemented in association with a user interface. At **302**, data to form an input as a user interface element may be received via a user interface. For example, a processor executing instruction data at a client computing device (or any other type of computing device, including a server computing device) may receive data to form a user interface element, which may constitute a user input that may be presented in a user interface as, for example, a “create dataset” user input. In one or more cases, activation of the “create dataset” user input can initiate creation of an atomized dataset based on a set of data, which may include, for example, raw data in data file (e.g., a tabular data file, such as a XLS file, etc.). According to some examples, receiving data to form “create dataset” user input may be subsequent to receiving data to form another input (as another user interface element). In some examples, this other user input that may be presented in a user interface as, for example, a “upload” user input that is configured perform an upload of the set of data from a data source (e.g., external, third-party data source, which may or may not be public). In at least one case, activation of the “upload” user input may initiate transmission of an upload instruction to a server computing system (e.g., implemented as a collaborative dataset consolidation system) to import the set of data prior to the data creation process.

At **304**, a programmatic interface may be activated to facilitate the creation of the dataset responsive to receiving the first input. The programmatic interface may be implemented as either hardware or software, or a combination thereof. The programmatic interface also may be disposed at a client computing device or a server computing device, which may be associated with a collaborative dataset consolidation system, or may distributed over any number of computing devices whether networked together or otherwise. In some examples, the programmatic interface may be distributed as subsets of executable code (e.g., as scripts, etc.) to implement APIs in any number of computing devices. In some embodiments, programmatic interface may be optional and may be omitted.

At **306**, a set of data may be transformed from a first format to an atomized format to form an atomized dataset. The atomized dataset may be stored in a graph data structure, according to some examples. In various examples, the transformation into an atomized dataset may be performed at

a client computing device, a server computing device, or a combination of multiple computing devices. According to various embodiments, the transformation of formats from one to another format may be performed at any process or computing device. For example, the transformation (or portion thereof) may be performed at either a client computing device or a server computing device, or both (e.g., distributed computing).

At **308**, the creation of the dataset may be monitored by, for example, a processor. In various examples, the creation of a dataset may pass through one or more phases. In one phase, for example, the data may be cleaned (e.g., data entry exceptions, such as defective data, may be detected and corrected). In another phase, insight information describing the dataset and its attributes may be generated. And in yet another phase, the dataset may be transformed and linked to other atomized datasets to form a collaborative dataset. One or more of these phases may be visually depicted using user interface elements (e.g., a progress bar or the like) upon commencement of the dataset creation process. Additional user interface elements, such as a “link” user input **137** of FIG. **1**, may be presented on a user interface to facilitate linking of atomized datasets (e.g., responsive to input insight information, dataset activity feed information, etc.). At **310**, data representing a status of at least a portion of the creation of the dataset may be presented on the user interface. The status may depict that the atomized dataset is linked to at least one other dataset.

In one embodiment, the monitoring of dataset creation at **308** may include identifying data to form an insight user interface element. The user interface element may be configured to specify a status of an insight phase for a dataset creation process. During the insight phase, data representing insights of the set of data may be formed, whereby insight information may specify at least one dataset attribute, such as annotations, datatypes, inferred dataset attributes, etc. Further, the monitoring of dataset creation at **308** may include identifying data to form a linking user interface element to specify the status of a linking phase of the dataset creation process. During the linking phase, data representing formation of a link among the atomized dataset and other datasets, which includes at least one other atomized dataset, may be presented to a user interface. Accordingly, at **310**, an insight user interface element and a linking user interface element may be presented at the user interface. Note that any of **302**, **304**, **306**, **308**, and **310** may be performed at any process or computing device, and may be performed at either a client computing device or a server computing device, or both (e.g., distributed computing).

In another embodiment, a number of notifications may be implemented as a subset of user interface elements that constitute a dataset activity feed. A notification may specify type of dataset interaction that may be characterized for a particular dataset or user. Examples of dataset interactions may include data specifying one or more of the following: a new dataset is created, a dataset is queried, a dataset is linked to another dataset, a comment relating to a dataset is associated thereto, a dataset is relevant to another dataset, and other like characterized dataset interactions. The characterization of a dataset interaction may be performed during monitoring of the dataset creation process at **308**. A characterized dataset interaction may be presented as a status of the dataset at **310** as a notification in an activity feed. Moreover, a user input interface element associated with a characterized dataset interaction may be configured to initiate access to a dataset for which the dataset interaction is characterized (e.g., the characterized dataset interaction

may be a modified dataset). Therefore, a user, such as a data practitioner, may interact with one or more user interface elements based on the characterized datasets interactions, which provide information that may be useful to determine whether to use, or to link to, that dataset to form a collaborative dataset. For example, data practitioner interested in gun violence statistics may be interested in learning about, via a dataset activity feed, updates or queries relating to certain law enforcement databases.

According to some examples, characterized datasets interactions may specify relevant dataset data or relevant collaborator data (i.e., relative to a particular user’s dataset or user characteristics). Relevant dataset data may specify a subset of datasets having dataset attributes calculated to be relevant to a particular atomized dataset, whereas relevant collaborator data may specify a subset of user accounts having user account attributes calculated to be relevant to a user account associated with the atomized dataset. According to some additional examples, characterized datasets interactions may specify trending dataset data or trending collaborator data (i.e., relative to a community of datasets or users). Trending dataset data may specify a subset of datasets having dataset attributes calculated to include greater dataset attribute values relative to a superset of datasets. For example, trending dataset data, such as a total number of queries per unit time, may specify, for example, a list of “top ten” datasets relating to a particular topic or discipline (e.g., “top ten” datasets based on locations and cases of Zika virus infections).

Trending collaborator data may specify a subset of user accounts having user account attributes calculated to include greater user account attributes values relative to a superset of user accounts. For example, trending collaborator data, such as users that have datasets with a greatest number of comments per unit time, may specify, for example, a list of “top ten” collaborators relating to the particular topic or discipline. In some examples, “trend” related information may describe changes (e.g., statistical changes) in, or general movement of, data or information about datasets over time to predict or estimate patterns of dataset interactions and usage. In some cases, trend-related information may include ranking data (e.g., rankings of dataset attributes or user attributes) over unit time.

FIG. **4** is a diagram depicting a collaborative dataset consolidation system, according to some embodiments. Diagram **400** depicts an example of collaborative dataset consolidation system **410** that may be configured to consolidate one or more datasets to form collaborative datasets. A collaborative dataset, according to some non-limiting examples, is a set of data that may be configured to facilitate data interoperability over disparate computing system platforms, architectures, and data storage devices. Further, a collaborative dataset may also be associated with data configured to establish one or more associations (e.g., meta-data) among subsets of dataset attribute data for datasets, whereby attribute data may be used to determine correlations (e.g., data patterns, trends, etc.) among the collaborative datasets. Collaborative dataset consolidation system **410** may present the correlations via computing devices **409a** and **409b** to disseminate dataset-related information to one or more users **408a** and **408b**. Thus, a community of users **408**, as well as any other participating user, may discover and share dataset-related information of interest in association with collaborative datasets. Collaborative datasets, with or without associated dataset attribute data, may be used to facilitate easier collaborative dataset interoperability among sources of data that may be differently formatted at origi-

nation or may be disposed at disparate data stores (e.g., repositories at different geographical locations). According to various embodiments, one or more structural and/or functional elements described in FIG. 4, as well as below, may be implemented in hardware or software, or both.

Collaborative dataset consolidation system 410 is depicted as including a dataset ingestion controller 420, a dataset query engine 430, a collaboration manager 460, a collaborative data repository 462, and a data repository 440, according to the example shown. Dataset ingestion controller 420 may be configured to receive data representing a dataset 404a having, for example, a particular data format (e.g., CSV, XML, JSON, XLS, MySQL, binary, etc.), and may be further configured to convert dataset 404a into a collaborative data format for storage in a portion of data arrangement 442a in repository 440. According to some embodiments, a collaborative data format may be configured to, but need not be required to, format data in converted dataset 404a as an atomized dataset. An atomized dataset may include a data arrangement in which data is stored as an atomized data point 414 that, for example, may be an irreducible or simplest representation of data that may be linkable to other atomized data points, according to some embodiments. Atomized data point 414 may be implemented as a triple or any other data relationship that expresses or implements, for example, a smallest irreducible representation for a binary relationship between two data units. As atomized data points may be linked to each other, data arrangement 442a may be represented as a graph, whereby the converted dataset 404a (i.e., atomized dataset 404a) forms a portion of the graph. Atomized data point 414, in some cases, may be expressed in a statement in which one object or entity relates (or links) to another object or entity, whereby the objects and the relationship (e.g., the link) each may be individually addressable. In some cases, an atomized dataset facilitates merging of data irrespective of whether, for example, schemas or applications differ.

Further, dataset ingestion controller 420 may be configured to identify other datasets that may be relevant to dataset 404a. In one implementation, dataset ingestion controller 420 may be configured to identify associations, links, references (e.g., annotations, etc.), pointers, etc. that may indicate, for example, similar subject matter between dataset 404a and a subset of other datasets (e.g., within or without repository 440). In some examples, dataset ingestion controller 420 may be configured to correlate dataset attributes of an atomized dataset with other atomized datasets or non-atomized datasets. Further, dataset ingestion controller 420 also may be configured to correlate dataset attributes of any public data (or atomized dataset) to any other public data (or other atomized datasets), whereby public data and datasets may be accessible (e.g., without credentials). In some examples, dataset ingestion controller 420 may be configured to correlate dataset attributes of private data (or private atomized dataset) to other data (or other atomized datasets), whereby the data in private data and atomized datasets may be accessible, for example, with authorized credentials. Dataset ingestion controller 420 or other any other component of collaborative dataset consolidation system 410 may be configured to format or convert a non-atomized dataset (or any other differently-formatted dataset) into a format similar to that of converted dataset 404a). Therefore, dataset ingestion controller 420 may determine or otherwise use associations to identify datasets with which to consolidate to form, for example, collaborative datasets 432a and collaborative datasets 432b. Thus, dataset ingestion controller 420 may be configured to identify correlated dataset attributes

for “discovery purposes.” That is, correlated dataset attributes (or other representations thereof, such as annotations) may be made “searchable,” whereby any user or participant may search for an attribute and receive search results indicating relevant public or private (i.e., protected) datasets. Note that while dataset ingestion controller 420 may make correlated dataset attributes from private datasets accessible, authorization may be required to access or perform any operation on the private datasets correlated by dataset ingestion controller 420.

As shown in diagram 400, dataset ingestion controller 420 may be configured to extend a dataset (i.e., the converted dataset 404a stored in data arrangement 442a) to include, reference, combine, or consolidate with other datasets within data arrangement 442a or external thereto. Specifically, dataset ingestion controller 420 may extend an atomized dataset 404a to form a larger or enriched dataset, by associating or linking (e.g., via links 411) to other datasets, such as external entity datasets 404b, 404c, and 404n, form one or more collaborative datasets. Note that external entity datasets 404b, 404c, and 404n may be converted (or convertible) to form external datasets atomized datasets 442b, 442c, and 442n, respectively. The term “external dataset,” at least in this case, can refer to a dataset generated externally to system 410 and may or may not be formatted as an atomized dataset.

As shown, different entities 405a, 405b, and 405n may each include a computing device 402 (e.g., representative of one or more servers and/or data processors) and one or more data storage devices 403 (e.g., representative of one or more database and/or data store technologies). Examples of entities 405a, 405b, and 405n include individuals, such as data scientists and statisticians, corporations, universities, governments, etc. A user 401a, 401b, and 401n (and associated user account identifiers) may interact with entities 405a, 405b, and 405n, respectively. Each of entities 405a, 405b, and 405n may be configured to perform one or more of the following: generating datasets, searching data and/or data attributes of datasets, discovering datasets, linking to datasets (e.g., public and/or private datasets), modifying datasets, querying datasets, analyzing datasets, hosting datasets, and the like, whereby one or more entity datasets 404b, 404c, and 404n may be formatted in different data formats. In some cases, these formats may be incompatible for implementation with data stored in repository 440. As shown, differently-formatted datasets 404b, 404c, and 404n may be converted into atomized datasets, each of which is depicted in diagram 400 as being disposed in a dataspace. Namely, atomized datasets 442b, 442c, and 442n are depicted as residing in dataspace 413a, 413b, and 413n, respectively. In some examples, atomized datasets 442b, 442c, and 442n may be represented as graphs.

According to some embodiments, atomized datasets 442b, 442c, and 442n may be imported into collaborative dataset consolidation system 410 for storage in one or more repositories 440. In this case, dataset ingestion controller 420 may be configured to receive entity datasets 404b, 404c, and 404n for conversion into atomized datasets, as depicted in corresponding dataspace 413a, 413b, and 413n. Collaborative data consolidation system 410 may store atomized datasets 442b, 442c, and 442n in repository 440 (i.e., internal to system 410) or may provide the atomized datasets for storage in respective entities 405a, 405b, and 405n (i.e., without or external to system 410). Alternatively, any of entities 405a, 405b, and 405n may be configured to convert entity datasets 404b, 404c, and 404n and store corresponding atomized datasets 442b, 442c, and 442n in one or more

data storage devices **403a**, **403b**, and **430c**. In this case, atomized datasets **442b**, **442c**, and **442n** may be hosted for access by dataset ingestion controller **420** for linking via links **411** to extend datasets with data arrangement **442a**.

Thus, collaborative dataset consolidation system **410** is configured to consolidate datasets from a variety of different sources and in a variety of different data formats to form collaborative datasets **432a** and **432b**. As shown, collaborative dataset **432a** extends a portion of dataset in data arrangement **442a** to include portions of atomized datasets **442b**, **442c**, and **442n** via links **411**, whereas collaborative dataset **432b** extends another portion of a dataset in data arrangement **442a** to include other portions of atomized datasets **442b** and **442c** via links **411**. Note that entity dataset **404n** includes a secured set of protected data **431c** that may require a level of authorization or authentication to access. Without authorization, link **419** cannot be implemented to access protected data **431c**. For example, user **401n** may be a system administrator that may program computing device **402n** to require authorization to gain access to protected data **431c**. In some cases, dataset ingestion controller **420** may or may not provide an indication that link **419** exists based on whether, for example, user **408a** has authorization to form a collaborative dataset **432b** to include protected data **431c**. In some examples, user **401n** may permit access to dataset attributes associated with protected data **431c**, whereby the dataset attributes may be accessed by collaborative dataset consolidation system **410** to enable other users to search for and discover relevant dataset attributes for protected data **431c**. Thereafter, an interested user **401a**, **401b**, or **408a** may request access to the protected data **431c**. Access may be granted for a limited time, for a limited purpose, for pecuniary or charitable reasons, or any other purpose or with any other limitation.

Dataset query engine **430** may be configured to generate one or more queries, responsive to receiving data representing one or more queries via computing device **409a** from user **408a**. Dataset query engine **430** is configured to apply query data to one or more collaborative datasets, such as collaborative dataset **432a** and collaborative dataset **432b**, to access the data therein to generate query response data **412**, which may be presented via computing device **409a** to user **408a**. According to some examples, dataset query engine **430** may be configured to identify one or more collaborative datasets subject to a query to either facilitate an optimized query or determine authorization to access one or more of the datasets, or both. As to the latter, dataset query engine **430** may be configured to determine whether one of users **408a** and **408b** is authorized to include protected data **431c** in a query of collaborative dataset **432b**, whereby the determination may be made at the time (or substantially at the time) dataset query engine **430** identifies one or more datasets subject to a query.

Collaboration manager **460** may be configured to assign or identify one or more attributes associated with a dataset, such as a collaborative dataset, and may be further configured to store dataset attributes as collaborative data in repository **462**. Examples of dataset attributes include, but are not limited to, data representing a user account identifier, a user identity (and associated user attributes, such as a user first name, a user last name, a user residential address, a physical or physiological characteristics of a user, etc.), one or more other datasets linked to a particular dataset, one or more other user account identifiers that may be associated with the one or more datasets, data-related activities associated with a dataset (e.g., identity of a user account identifier associated with creating, searching, discovering, ana-

lyzing, discussing, collaborating with, modifying, querying, etc. a particular dataset), and other similar attributes. Another example of a dataset attribute is a “usage” or type of usage associated with a dataset. For instance, a virus-related dataset (e.g., Zika dataset) may have an attribute describing usage to understand victim characteristics (i.e., to determine a level of susceptibility), an attribute describing usage to identify a vaccine, an attribute describing usage to determine an evolutionary history or origination of the Zika, SARS, MERS, HIV, or other viruses, etc. Further, collaboration manager **460** may be configured to monitor updates to dataset attributes to disseminate the updates to a community of networked users or participants. Therefore, users **408a** and **408b**, as well as any other user or authorized participant, may receive communications (e.g., via user interface) to discover new or recently-modified dataset-related information in real-time (or near real-time).

In view of the foregoing, the structures and/or functionalities depicted in FIG. 4 illustrate a dataset consolidated system that may be configured to consolidate datasets originating in different data formats with different data technologies, whereby the datasets (e.g., as collaborative datasets) may originate external to the system. Collaborative dataset consolidation system **410**, therefore, may be configured to extend a dataset beyond its initial quantity and quality (e.g., types of data, etc.) of data to include data from other datasets (e.g., atomized datasets) linked to the dataset to form a collaborative dataset. Note that while a collaborative dataset may be configured to persist in repository **440** as a contiguous dataset, collaborative dataset consolidation system **410** is configured to store at least one of atomized datasets **442a**, **442b**, **442c**, and **442n** (e.g., one or more of atomized datasets **442a**, **442b**, **442c**, and **442n** may be stored internally or externally) as well data representing links **411**. Hence, at a given point in time (e.g., during a query), the data associated one of atomized datasets **442a**, **442b**, **442c**, and **442n** may be loaded into an atomic data store against which the query can be performed. Therefore, collaborative dataset consolidation system **410** need not be required to generate massive graphs based on numerous datasets, but rather, collaborative dataset consolidation system **410** may create a graph based on a collaborative dataset in one operational state (of a number of operational states), and can be partitioned in another operational state (but can be linked via links **411** to form the graph). In some cases, different graph portions may persist separately and may be linked together when loaded into a data store to provide resources for a query. Further, collaborative dataset consolidation system **410** may be configured to extend a dataset beyond its initial quantity and quality of data based on using atomized datasets that include atomized data points (e.g., as an addressable data unit or fact), which facilitates linking, joining, or merging the data from disparate data formats or data technologies (e.g., different schemas or applications for which a dataset is formatted). Atomized datasets facilitate data interoperability over disparate computing system platforms, architectures, and data storage devices, according to various embodiments.

According to some embodiments, collaborative dataset consolidation system **410** may be configured to provide a granular level of security with which an access to each dataset is determined on a dataset-by-dataset basis (e.g., per-user access or per-user account identifier to establish per-dataset authorization). Therefore, a user may be required to have per-dataset authorization to access a group of datasets less than a total number of datasets (including a single dataset). In some examples, dataset query engine **430** may be configured to assert access-level (e.g., query-level)

authorization or authentication. Note that authorization or credentials may be embedded in or otherwise associated with, for example, addresses referencing individual entities (e.g., via an IRI, or the like). As such, non-users (e.g., participants) without account identifiers (or users without authentication) may access or apply a query (e.g., limited to a query, for example) to repository **440** without receiving authorization to access system **410** generally. Dataset query engine **430** may implement such a query if, for example, the query includes, or is otherwise associated with, authorization data.

Collaboration manager **460** may be configured as, or to implement, a collaborative data layer and associated logic to implement collaborative datasets for facilitating collaboration among consumers of datasets. For example, collaboration manager **460** may be configured to establish one or more associations (e.g., as metadata) among dataset attribute data (for a dataset) and/or other attribute data (for other datasets (e.g., within or without system **410**)). As such, collaboration manager **460** can determine a correlation between data of one dataset to a subset of other datasets. In some cases, collaboration manager **460** may identify and promote a newly-discovered correlation to users associated with a subset of other databases. Or, collaboration manager **460** may disseminate information about activities (e.g., name of a user performing a query, types of data operations performed on a dataset, modifications to a dataset, etc.) for a particular dataset. To illustrate, consider that user **408a** is situated in South America and is accessing a recently-generated dataset (e.g., to analyze, query, etc.), the recently-generated dataset including data about the Zika virus over different age ranges and genders over various population ranges. Further, consider that user **408b** is situated in North America and also has generated or curated datasets directed to the Zika virus. Collaborative dataset consolidation system **410** may be configured to determine a correlation between the datasets of users **408a** and **408b** (i.e., subsets of data may be classified or annotated as Zika-related). System **410** also may optionally determine whether user **408b** has interacted with the newly-generated dataset about the Zika virus (whether the user, for example, viewed, accessed, downloaded data from, analyzed, queried, searched, added data to, etc. the dataset). Regardless, collaboration manager **460** may generate a notification to present in a user interface **418** of computing device **409b**. As shown, user **408b** is informed in an “activity feed” portion **416** of user interface **418** that “Dataset X” has been queried and is recommended to user **408b** (e.g., based on the correlated scientific and research interests related to the Zika virus). User **408b**, in turn, may modify Dataset X to form Dataset XX, thereby enabling a community of researchers to expeditiously access datasets (e.g., previously-unknown or newly-formed datasets) as they are generated to facilitate scientific collaborations, such as developing a vaccine for the Zika virus. Note that users **401a**, **401b**, and **401n** may also receive similar notifications or information, at least some of which present one or more opportunities to collaborate and use, modify, and share datasets in a “viral” fashion. Therefore, collaboration manager **460** and/or other portions of collaborative dataset consolidation system **410** may provide collaborative data and logic layers to implement a “social network” for datasets.

FIG. 5A is a diagram depicting an example of an atomized data point, according to some embodiments. Diagram **500** depicts a portion **501** of an atomized dataset that includes an atomized data point **514**. In some examples, the atomized dataset is formed by converting a data format into a format

associated with the atomized dataset. In some cases, portion **501** of the atomized dataset can describe a portion of a graph that includes one or more subsets of linked data. Further to diagram **500**, one example of atomized data point **514** is shown as a data representation **514a**, which may be represented by data representing two data units **502a** and **502b** (e.g., objects) that may be associated via data representing an association **504** with each other. One or more elements of data representation **514a** may be configured to be individually and uniquely identifiable (e.g., addressable), either locally or globally in a namespace of any size. For example, elements of data representation **514a** may be identified by identifier data **590a**, **590b**, and **590c**.

In some embodiments, atomized data point **514a** may be associated with ancillary data **503** to implement one or more ancillary data functions. For example, consider that association **504** spans over a boundary between an internal dataset, which may include data unit **502a**, and an external dataset (e.g., external to a collaboration dataset consolidation), which may include data unit **502b**. Ancillary data **503** may interrelate via relationship **580** with one or more elements of atomized data point **514a** such that when data operations regarding atomized data point **514a** are implemented, ancillary data **503** may be contemporaneously (or substantially contemporaneously) accessed to influence or control a data operation. In one example, a data operation may be a query and ancillary data **503** may include data representing authorization (e.g., credential data) to access atomized data point **514a** at a query-level data operation (e.g., at a query proxy during a query). Thus, atomized data point **514a** can be accessed if credential data related to ancillary data **503** is valid (otherwise, a request to access atomized data point **514a** (e.g., for forming linked datasets, performing analysis, a query, or the like) without authorization data may be rejected or invalidated). According to some embodiments, credential data (e.g., passcode data), which may or may not be encrypted, may be integrated into or otherwise embedded in one or more of identifier data **590a**, **590b**, and **590c**. Ancillary data **503** may be disposed in other data portion of atomized data point **514a**, or may be linked (e.g., via a pointer) to a data vault that may contain data representing access permissions or credentials.

Atomized data point **514a** may be implemented in accordance with (or be compatible with) a Resource Description Framework (“RDF”) data model and specification, according to some embodiments. An example of an RDF data model and specification is maintained by the World Wide Web Consortium (“W3C”), which is an international standards community of Member organizations. In some examples, atomized data point **514a** may be expressed in accordance with Turtle (e.g., Terse RDF Triple Language), RDF/XML, N-Triples, N3, or other like RDF-related formats. As such, data unit **502a**, association **504**, and data unit **502b** may be referred to as a “subject,” “predicate,” and “object,” respectively, in a “triple” data point. In some examples, one or more of identifier data **590a**, **590b**, and **590c** may be implemented as, for example, a Uniform Resource Identifier (“URI”), the specification of which is maintained by the Internet Engineering Task Force (“IETF”). According to some examples, credential information (e.g., ancillary data **503**) may be embedded in a link or a URI (or in a URL) or an Internationalized Resource Identifier (“IRI”) for purposes of authorizing data access and other data processes. Therefore, an atomized data point **514** may be equivalent to a triple data point of the Resource Description Framework (“RDF”) data model and specification, according to some examples. Note that the term “atom-

ized” may be used to describe a data point or a dataset composed of data points represented by a relatively small unit of data. As such, an “atomized” data point is not intended to be limited to a “triple” or to be compliant with RDF; further, an “atomized” dataset is not intended to be limited to RDF-based datasets or their variants. Also, an “atomized” data store is not intended to be limited to a “triplestore,” but these terms are intended to be broader to encompass other equivalent data representations.

Examples of triplestores suitable to store “triples” and atomized datasets (and portions thereof) include, but are not limited to, any triplestore type architected to function as (or similar to) a BLAZEGRAPH triplestore, which is developed by Systap, LLC of Washington, D.C., U.S.A.), any triplestore type architected to function as (or similar to) a STARDOG triplestore, which is developed by Complexible, Inc. of Washington, D.C., U.S.A.), any triplestore type architected to function as (or similar to) a FUSEKI triplestore, which may be maintained by The Apache Software Foundation of Forest Hill, Md., U.S.A.), and the like.

FIG. 5B is a diagram depicting operation an example of a collaborative dataset consolidation system, according to some examples. Diagram 550 includes a collaborative dataset consolidation system 510, which, in turn, includes a dataset ingestion controller 520, a collaboration manager 560, a dataset query engine 530, and a repository 540, which may represent one or more data stores. In the example shown, consider that a user 508b, which is associated with a user account data 507, may be authorized to access (via networked computing device 509b) collaborative dataset consolidation system to create a dataset and to perform a query. User interface 518a of computing device 509b may receive a user input signal to activate the ingestion of a data file, such as a CSV formatted file (e.g., “XXX.csv”), to create a dataset (e.g., an atomized dataset stored in repository 540). Hence, dataset ingestion controller 520 may receive data 521a representing the CSV file and may analyze the data to determine dataset attributes during, for example, a phase in which “insights” (e.g., statistics, data characterization, etc.) may be performed. Examples of dataset attributes include annotations, data classifications, data types, a number of data points, a number of columns, a “shape” or distribution of data and/or data values, a normative rating (e.g., a number between 1 to 10 (e.g., as provided by other users)) indicative of the “applicability” or “quality” of the dataset, a number of queries associated with a dataset, a number of dataset versions, identities of users (or associated user identifiers) that analyzed a dataset, a number of user comments related to a dataset, etc.). Dataset ingestion controller 520 may also convert the format of data file 521a to an atomized data format to form data representing an atomized dataset 521b that may be stored as dataset 542a in repository 540.

As part of its processing, dataset ingestion controller 520 may determine that an unspecified column of data 521a, which includes five (5) integer digits, may be a column of “zip code” data. As such, dataset ingestion controller 520 may be configured to derive a data classification or data type “zip code” with which each set of 5 digits can be annotated or associated. Further to the example, consider that dataset ingestion controller 520 may determine that, for example, based on dataset attributes associated with data 521a (e.g., zip code as an attribute), both a public dataset 542b in external repositories 540a and a private dataset 542c in external repositories 540b may be determined to be relevant to data file 521a. Individuals 508c, via a networked computing system, may own, maintain, administer, host or

perform other activities in association with public dataset 542b. Individual 508d, via a networked computing system, may also own, maintain, administer, and/or host private dataset 542c, as well as restrict access through a secured boundary 515 to permit authorized usage. In some examples, either public dataset 542b or private dataset 542c, or both, may be omitted (e.g., a user may select to exclude a dataset, such as private dataset 542c, from being inferred or otherwise linked).

Continuing with the example, public dataset 542b and private dataset 542c may include “zip code”-related data (i.e., data identified or annotated as zip codes). Dataset ingestion controller 520 may generate a data message 522a that includes an indication that public dataset 542b and/or private dataset 542c may be relevant to the pending uploaded data file 521a (e.g., datasets 542b and 542c include zip codes). Collaboration manager 560 receive data message 522a, and, in turn, may generate user interface-related data 523a to cause presentation of a notification and user input data configured to accept user input at user interface 518b. According to some examples, user 508b may interact via computing device 509b and user interface 518b to (1) engage other users of collaborative dataset consolidation system 510 (and other non-users), (2) invite others to interact with a dataset, (3) request access to a dataset, (4) provide commentary on datasets via collaboration manager 560, (5) provide query results based on types of queries (and characteristics of such queries), (6) communicate changes and updates to datasets that may be linked across any number of atomized dataset that form a collaborative dataset, and (7) notify others of any other type of collaborative activity relative to datasets.

If user 508b wishes to “enrich” dataset 521a, user 508b may activate a user input (not shown on interface 518b) to generate a user input signal data 523b indicating a request to link to one or more other datasets, including private datasets that may require credentials for access. Collaboration manager 560 may receive user input signal data 523b, and, in turn, may generate instruction data 522b to generate an association (or link 541a) between atomized dataset 542a and public dataset 542b to form a collaborative dataset, thereby extending the dataset of user 508b to include knowledge embodied in external repositories 540a. Therefore, user 508b’s dataset may be generated as a collaborative dataset as it may be based on the collaboration with public dataset 542b, and, to some degree, its creators, individuals 508c. Note that while public dataset 542b may be shown external to system 510, public dataset 542b may be ingested via dataset ingestion controller 520 for storage as another atomized dataset in repository 540. Or, public dataset 542b may be imported into system 510 as an atomized dataset in repository 540 (e.g., link 511a is disposed within system 510). Similarly, if user 508b wishes to “enrich” atomized dataset 521b with private dataset 542c, user 508b may extend its dataset 542a by forming a link 511b to private dataset 542c to form a collaborative dataset. In particular, dataset 542a and private dataset 542c may consolidate to form a collaborative dataset (e.g., dataset 542a and private dataset 542c are linked to facilitate collaboration between users 508b and 508d). Note that access to private dataset 542c may require credential data 517 to permit authorization to pass through secured boundary 515. Note, too, that while private dataset 542c may be shown external to system 510, private dataset 542c may be ingested via dataset ingestion controller 520 for storage as another atomized dataset in repository 540. Or, private dataset 542c may be imported into system 510 as an atomized dataset in repository 540

(e.g., link **511b** is disposed within system **510**). According to some examples, credential data **517** may be required even if private dataset **542c** is stored in repository **540**. Therefore, user **508d** may maintain dominion (e.g., ownership and control of access rights or privileges, etc.) of an atomized version of private dataset **542c** when stored in repository **540**.

Should user **508b** desire not to link dataset **542a** with other datasets, then upon receiving user input signal data **523b** indicating the same, dataset ingestion controller **520** may store dataset **521b** as atomized dataset **542a** without links (or without active links) to public dataset **542b** or private dataset **542c**. Thereafter, user **508b** may enter query data **524a** via data entry interface **519** (of user interface **518c**) to dataset query engine **530**, which may be configured to apply one or more queries to dataset **542a** to receive query results **524b**. Note that dataset ingestion controller **520** need not be limited to performing the above-described function during creation of a dataset. Rather, dataset ingestion controller **520** may continually (or substantially continuously) identify whether any relevant dataset is added or changed (beyond the creation of dataset **542a**), and initiate a messaging service (e.g., via an activity feed) to notify user **508b** of such events. According to some examples, atomized dataset **542a** may be formed as triples compliant with an RDF specification, and repository **540** may be a database storage device formed as a “triplestore.” While dataset **542a**, public dataset **542b**, and private dataset **542c** may be described above as separately partitioned graphs that may be linked to form collaborative datasets and graphs (e.g., at query time, or during any other data operation, including data access), dataset **542a** may be integrated with either public dataset **542b** or private dataset **542c**, or both, to form a physically contiguous data arrangement or graph (e.g., a unitary graph without links), according to at least one example.

FIG. 6 is a diagram depicting an example of a dataset analyzer and an inference engine, according to some embodiments. Diagram **600** includes a dataset ingestion controller **620**, which, in turn, includes a dataset analyzer **630** and a format converter **640**. As shown, dataset ingestion controller **620** may be configured to receive data file **601a**, which may include a set of data (e.g., a dataset) formatted in any specific format, examples of which include CSV, JSON, XML, XLS, MySQL, binary, RDF, or other similar or suitable data formats. Dataset analyzer **630** may be configured to analyze data file **601a** to detect and resolve data entry exceptions (e.g., whether a cell is empty or includes non-useful data, whether a cell includes non-conforming data, such as a string in a column that otherwise includes numbers, whether an image embedded in a cell of a tabular file, whether there are any missing annotations or column headers, etc.). Dataset analyzer **630** then may be configured to correct or otherwise compensate for such exceptions.

Dataset analyzer **630** also may be configured to classify subsets of data (e.g., each subset of data as a column) in data file **601a** as a particular data classification, such as a particular data type. For example, a column of integers may be classified as “year data,” if the integers are in one of a number of year formats expressed in accordance with a Gregorian calendar schema. Thus, “year data” may be formed as a derived dataset attribute for the particular column. As another example, if a column includes a number of cells that each include five digits, dataset analyzer **630** also may be configured to classify the digits as constituting a “zip code.” Dataset analyzer **630** can be configured to analyze data file **601a** to note the exceptions in the process-

ing pipeline, and to append, embed, associate, or link user interface elements or features to one or more elements of data file **601a** to facilitate collaborative user interface functionality (e.g., at a presentation layer) with respect to a user interface. Further, dataset analyzer **630** may be configured to analyze data file **601a** relative to dataset-related data to determine correlations among dataset attributes of data file **601a** and other datasets **603b** (and attributes, such as meta-data **603a**). Once a subset of correlations has been determined, a dataset formatted in data file **601a** (e.g., as an annotated tabular data file, or as a CSV file) may be enriched, for example, by associating links to the dataset of data file **601a** to form the dataset of data file **601b**, which, in some cases, may have a similar data format as data file **601a** (e.g., with data enhancements, corrections, and/or enrichments). Note that while format converter **640** may be configured to convert any CSV, JSON, XML, XLS, RDF, etc. into RDF-related data formats, format converter **640** may also be configured to convert RDF and non-RDF data formats into any of CSV, JSON, XML, XLS, MySQL, binary, XLS, RDF, etc. Note that the operations of dataset analyzer **630** and format converter **640** may be configured to operate in any order serially as well as in parallel (or substantially in parallel). For example, dataset analyzer **630** may analyze datasets to classify portions thereof, either prior to format conversion by formatter converter **640** or subsequent to the format conversion. In some cases, at least one portion of format conversion may occur during dataset analysis performed by dataset analyzer **630**.

Format converter **640** may be configured to convert dataset of data file **601b** into an atomized dataset **601c**, which, in turn, may be stored in system repositories **640a** that may include one or more atomized data store (e.g., including at least one triplestore). Examples of functionalities to perform such conversions may include, but are not limited to, CSV2RDF data applications to convert CVS datasets to RDF datasets (e.g., as developed by Rensselaer Polytechnic Institute and referenced by the World Wide Web Consortium (“W3C”)), R2RML data applications (e.g., to perform RDB to RDF conversion, as maintained by the World Wide Web Consortium (“W3C”)), and the like.

As shown, dataset analyzer **630** may include an inference engine **632**, which, in turn, may include a data classifier **634** and a dataset enrichment manager **636**. Inference engine **632** may be configured to analyze data in data file **601a** to identify tentative anomalies and to infer corrective actions, and to identify tentative data enrichments (e.g., by joining with, or linking to, other datasets) to extend the data beyond that which is in data file **601a**. Inference engine **632** may receive data from a variety of sources to facilitate operation of inference engine **632** in inferring or interpreting a dataset attribute (e.g., as a derived attribute) based on the analyzed data. Responsive to a request input data via data signal **601d**, for example, a user may enter a correct annotation via a user interface, which may transmit corrective data **601d** as, for example, an annotation or column heading. Thus, the user may correct or otherwise provide for enhanced accuracy in atomized dataset generation “in-situ,” or during the dataset ingestion and/or graph formation processes. As another example, data from a number of sources may include dataset metadata **603a** (e.g., descriptive data or information specifying dataset attributes), dataset data **603b** (e.g., some or all data stored in system repositories **640a**, which may store graph data), schema data **603c** (e.g., sources, such as schema.org, that may provide various types and vocabularies), ontology data **603d** from any suitable ontology (e.g., data compliant with Web Ontology Language (“OWL”)), as main-

tained by the World Wide Web Consortium (“W3C”), and any other suitable types of data sources.

In one example, data classifier **634** may be configured to analyze a column of data to infer a datatype of the data in the column. For instance, data classifier **634** may analyze the column data to infer that the columns include one of the following datatypes: an integer, a string, a Boolean data item, a categorical data item, a time, etc., based on, for example, data from UI data **601d** (e.g., data from a UI representing an annotation), as well as based on data from data **603a** to **603d**. In another example, data classifier **634** may be configured to analyze a column of data to infer a data classification of the data in the column (e.g., where inferring the data classification may be more sophisticated than identifying or inferring a datatype). For example, consider that a column of ten (10) integer digits is associated with an unspecified or unidentified heading. Data classifier **634** may be configured to deduce the data classification by comparing the data to data from data **601d**, and from data **603a** to **603d**. Thus, the column of unknown 10-digit data in data **601a** may be compared to 10-digit columns in other datasets that are associated with an annotation of “phone number.” Thus, data classifier **634** may deduce the unknown 10-digit data in data **601a** includes phone number data.

In the above example, consider that data in the column (e.g., in a CSV or XLS file) may be stored in a system of layer files, whereby raw data items of a dataset is stored at layer zero (e.g., in a layer zero (“L0”) file). The datatype of the column (e.g., string datatype) may be stored at layer one (e.g., in a layer one (“L1”) file, which may be linked to the data item at layer zero in the L0 file). An inferred dataset attribute, such as a “derive annotation,” may indicate a column of ten (10) integer digits can be classified as a “phone number,” which may be stored as annotative description data stored at layer two (e.g., in a layer two (“L2”) file, which may be linked to the classification of “integer” at layer one, which, in turn, may be linked to the 10 digits in a column at layer zero).

While not shown in FIG. 6, the system of layer files may be adaptive to add or remove data items, under control of the dataset ingestion controller **620** (or any of its constituent components), at the various layers as datasets are expanded or modified to include additional data as well as annotations, references, statistics, etc. Another example of a layer system is described in reference to FIG. 12, among other figures herein.

In yet another example, inference engine **632** may receive data (e.g., a datatype or data classification, or both) from an attribute correlator **663**. As shown, attribute correlator **663** may be configured to receive data, including attribute data (e.g., dataset attribute data), from dataset ingestion controller **620**. Also, attribute correlator **663** may be configured to receive data from data sources (e.g., UI-related/user inputted data **601d**, and data **603a** to **603d**), and from system repositories **640a**. Further, attribute correlator **663** may be configured to receive data from one or more of external public repository **640b**, external private repository **640c**, dominion dataset attribute data store **662**, and dominion user account attribute data store **662**, or from any other source of data. In the example shown, dominion dataset attribute data store **662** may be configured to store dataset attribute data for which collaborative dataset consolidation system may have dominion, whereas dominion user account attribute data store **662** may be configured to store user or user account attribute data for data in its domain.

Attribute correlator **663** may be configured to analyze the data to detect patterns that may resolve an issue. For

example, attribute correlator **663** may be configured to analyze the data, including datasets, to “learn” whether unknown 10-digit data is likely a “phone number” rather than another data classification. In this case, a probability may be determined that a phone number is a more reasonable conclusion based on, for example, regression analysis or similar analyses. Further, attribute correlator **663** may be configured to detect patterns or classifications among datasets and other data through the use of Bayesian networks, clustering analysis, as well as other known machine learning techniques or deep-learning techniques (e.g., including any known artificial intelligence techniques). Attribute correlator **663** also may be configured to generate enrichment data **607b** that may include probabilistic or predictive data specifying, for example, a data classification or a link to other datasets to enrich a dataset. According to some examples, attribute correlator **663** may further be configured to analyze data in dataset **601a**, and based on that analysis, attribute correlator **663** may be configured to recommend or implement one or more added columns of data. To illustrate, consider that attribute correlator **663** may be configured to derive a specific correlation based on data **607a** that describe three (3) columns, whereby those three columns are sufficient to add a fourth (4th) column as a derived column. In some cases, the data in the 4th column may be derived mathematically via one or more formulae. One example of a derived column is described in FIG. 13 and elsewhere herein. Therefore, additional data may be used to form, for example, additional “triples” to enrich or augment the initial dataset.

In yet another example, inference engine **632** may receive data (e.g., enrichment data **607b**) from a dataset attribute manager **661**, where enrichment data **607b** may include derived data or link-related data to form collaborative datasets. Consider that attribute correlator **663** can detect patterns in datasets in repositories **640a** to **640c**, among other sources of data, whereby the patterns identify or correlate to a subset of relevant datasets that may be linked with the dataset in data **601a**. The linked datasets may form a collaborative dataset that is enriched with supplemental information from other datasets. In this case, attribute correlator **663** may pass the subset of relevant datasets as enrichment data **607b** to dataset enrichment manager **636**, which, in turn, may be configured to establish the links for a dataset in **601b**. A subset of relevant datasets may be identified as a supplemental subset of supplemental enrichment data **607b**. Thus, converted dataset **601c** (i.e., an atomized dataset) may include links to establish collaborative datasets formed with collaborative datasets.

Dataset attribute manager **661** may be configured to receive correlated attributes derived from attribute correlator **663**. In some cases, correlated attributes may relate to correlated dataset attributes based on data in data store **662** or based on data in data store **664**, among others. Dataset attribute manager **661** also monitors changes in dataset and user account attributes in respective repositories **662** and **664**. When a particular change or update occurs, collaboration manager **660** may be configured to transmit collaborative data **605** to user interfaces of subsets of users that may be associated the attribute change (e.g., users sharing a dataset may receive notification data that the dataset has been created, modified, linked, updated, associated with a comment, associated with a request, queried, or has been associated with any other dataset interactions).

Therefore, dataset enrichment manager **636**, according to some examples, may be configured to identify correlated datasets based on correlated attributes as determined, for

example, by attribute correlator **663**. The correlated attributes, as generated by attribute correlator **663**, may facilitate the use of derived data or link-related data, as attributes, to form associate, combine, join, or merge datasets to form collaborative datasets. A dataset **601b** may be generated by enriching a dataset **601a** using dataset attributes to link to other datasets. For example, dataset **601a** may be enriched with data extracted from (or linked to) other datasets identified by (or sharing similar) dataset attributes, such as data representing a user account identifier, user characteristics, similarities to other datasets, one or more other user account identifiers that may be associated with a dataset, data-related activities associated with a dataset (e.g., identity of a user account identifier associated with creating, modifying, querying, etc. a particular dataset), as well as other attributes, such as a “usage” or type of usage associated with a dataset. For instance, a virus-related dataset (e.g., Zika dataset) may have an attribute describing a context or usage of dataset, such as a usage to characterize susceptible victims, usage to identify a vaccine, usage to determine an evolutionary history of a virus, etc. So, attribute correlator **663** may be configured to correlate datasets via attributes to enrich a particular dataset.

According to some embodiments, one or more users or administrators of a collaborative dataset consolidation system may facilitate curation of datasets, as well as assisting in classifying and tagging data with relevant datasets attributes to increase the value of the interconnected dominion of collaborative datasets. According to various embodiments, attribute correlator **663** or any other computing device operating to perform statistical analysis or machine learning may be configured to facilitate curation of datasets, as well as assisting in classifying and tagging data with relevant datasets attributes. In some cases, dataset ingestion controller **620** may be configured to implement third-party connectors to, for example, provide connections through which third-party analytic software and platforms (e.g., R, SAS, Mathematica, etc.) may operate upon an atomized dataset in the dominion of collaborative datasets. For instance, dataset ingestion controller **620** may be configured to implement API endpoints to provide or access functionalities provided by analytic software and platforms, such as R, SAS, Mathematica, etc.

FIG. 7 is a diagram depicting operation of an example of an inference engine, according to some embodiments. Diagram **700** depicts an inference engine **780** including a data classifier **781** and a dataset enrichment manager **783**, whereby inference engine **780** is shown to operate on data **706** (e.g., one or more types of data described in FIG. 6), and further operates on annotated tabular data representations of dataset **702**, dataset **722**, dataset **742**, and dataset **762**. Dataset **702** includes rows **710** to **716** that relate each population number **704** to a city **702**. Dataset **722** includes rows **730** to **736** that relate each city **721** to both a geo-location described with a latitude coordinate (“lat”) **724** and a longitude coordinate (“long”) **726**. Dataset **742** includes rows **750** to **756** that relate each name **741** to a number **744**, whereby column **744** omits an annotative description of the values within column **744**. Dataset **762** includes rows, such as row **770**, that relate a pair of geo-coordinates (e.g., latitude coordinate (“lat”) **761** and a longitude coordinate (“long”) **764**) to a time **766** at which a magnitude **768** occurred during an earthquake.

Inference engine **780** may be configured to detect a pattern in the data of column **704** in dataset **702**. For example, column **704** may be determined to relate to cities in Illinois based on the cities shown (or based on additional

cities in column **704** that are not shown, such as Skokie, Cicero, etc.). Based on a determination by inference engine **780** that cities **704** likely are within Illinois, then row **716** may be annotated to include annotative portion (“IL”) **790** (e.g., as derived supplemental data) so that Springfield in row **716** can be uniquely identified as “Springfield, Ill.” rather than, for example, “Springfield, Nebr.” or “Springfield, Mass.” Further, inference engine **780** may correlate columns **704** and **721** of datasets **702** and **722**, respectively. As such, each population number in rows **710** to **716** may be correlated to corresponding latitude **724** and longitude **726** coordinates in rows **730** to **734** of dataset **722**. Thus, dataset **702** may be enriched by including latitude **724** and longitude **726** coordinates as a supplemental subset of data. In the event that dataset **762** (and latitude **724** and longitude **726** data) are formatted differently than dataset **702**, then latitude **724** and longitude **726** data may be converted to an atomized data format (e.g., compatible with RDF). Thereafter, a supplemental atomized dataset can be formed by linking or integrating atomized latitude **724** and longitude **726** data with atomized population **704** data in an atomized version of dataset **702**. Similarly, inference engine **780** may correlate columns **724** and **726** of dataset **722** to columns **761** and **764**. As such, earthquake data in row **770** of dataset **762** may be correlated to the city in row **734** (“Springfield, Ill.”) of dataset **722** (or correlated to the city in row **716** of dataset **702** via the linking between columns **704** and **721**). The earthquake data may be derived via latitude and longitude coordinate-to-earthquake correlations as supplemental data for dataset **702**. Thus, new links (or triples) may be formed to supplement population data **704** with earthquake magnitude data **768**.

Inference engine **780** also may be configured to detect a pattern in the data of column **741** in dataset **742**. For example, inference engine **780** may identify data in rows **750** to **756** as “names” without an indication of the data classification for column **744**. Inference engine **780** can analyze other datasets to determine or learn patterns associated with data, for example, in column **741**. In this example, inference engine **780** may determine that names **741** relate to the names of “baseball players.” Therefore, inference engine **780** determines (e.g., predicts or deduces) that numbers in column **744** may describe “batting averages.” As such, a correction request **796** may be transmitted to a user interface to request corrective information or to confirm that column **744** does include batting averages. Correction data **798** may include an annotation (e.g., batting averages) to insert as annotation **794**, or may include an acknowledgment to confirm “batting averages” in correction request data **796** is valid. Note that the functionality of inference engine **780** is not limited to the examples describe in FIG. 7 and is more expansive than as described in the number of examples. In some examples, determination of a column header, such as column header **744**, may be associated with an annotation that may be automatically determined (e.g., based on inferred data that determines an annotative description of data for a column), or may be entered semi-automatically or manually.

FIG. 8 is a diagram depicting a flow diagram as an example of ingesting an enhanced dataset into a collaborative dataset consolidation system, according to some embodiments. Diagram **800** depicts a flow for an example of inferring dataset attributes and generating an atomized dataset in a collaborative dataset consolidation system. At **802**, data representing a dataset having a data format may be received into a collaborative dataset consolidation system. The dataset may be associated with an identifier or other

dataset attributes with which to correlate the dataset. At **804**, a subset of data of the dataset is interpreted against subsets of data (e.g., columns of data) for one or more data classifications (e.g., datatypes) to infer or derive at least an inferred attribute for a subset of data (e.g., a column of data). In some examples, the subset of data may relate to a columnar representation of data in a tabular data format, or CSV file, with, for example, columns annotated. Annotations may include descriptions of a data type (e.g., string, numeric, categorical, etc.), a data classification (e.g., a location, such as a zip code, etc.), or any other data or metadata that may be used to locate in a search or to link with other datasets.

To illustrate, consider that a subset of data attributes (e.g., dataset attributes) may be identified with a request to create a dataset (e.g., to create a linked dataset), or to perform any other operation (e.g., analysis, data insight generation, dataset atomization, etc.). The subset of dataset attributes may include a description of the dataset and/or one or more annotations the subset of dataset attributes. Further, the subset of dataset attributes may include or refer to data types or classifications that may be association with, for example, a column in a tabular data format (e.g., prior to atomization or as an alternate view). Note that in some examples, one or more data attributes may be stored in one or more layer files that include references or pointers to one or more columns in a table for a set of data. In response to a request for a search or creation of a dataset, the collaborative dataset consolidation system may retrieve a subset of atomized datasets that include data equivalent to (or associated with) one or more of the dataset attributes.

So if a subset of dataset attributes includes alphanumeric characters (e.g., two-letter codes, such as “AF” for Afghanistan), then a column can be identified as including country code data (e.g., a column includes data cells with AF, BR, CA, CN, DE, JP, MX, UK, US, etc.). Based on the country codes as a “data classification,” the collaborative dataset consolidation system may correlate country code data in other atomized datasets to a dataset of interest (e.g., a newly-created dataset, an analyzed dataset, a modified dataset (e.g., with added linked data), a queried dataset, etc.). Then, the system may retrieve additional atomized datasets that include country codes to form a collaborative dataset. The consolidation may be performed automatically, semi-automatically (e.g., with at least one user input), or manually. Thus, these datasets may be linked together by country codes. Note that in some cases, the system may implement logic to “infer” that two letters in a “column of data” of a tabular, pre-atomized dataset includes country codes. As such, the system may “derive” an annotation (e.g., a data type or classification) as a “country code.” Therefore, the derived classification of “country code” may be referred to as a derived attribute, which, for example, may be stored in a layer two (2) data file, examples of which are described herein (e.g., FIGS. 6 and 12, among others). A dataset ingestion controller may be configured to analyze data and/or dataset attributes to correlate the same over multiple datasets, the dataset ingestion controller being further configured to infer a data type or classification of a grouping of data (e.g., data disposed in a column or any other data arrangement), according to some embodiments.

At **806**, the subset of the data may be associated with annotative data identifying the inferred attribute. Examples of an inferred attribute include the inferred “baseball player” names annotation and the inferred “batting averages” annotation, as described in FIG. 7. At **808**, the dataset may be converted from the data format to an atomized dataset

having a specific format, such as an RDF-related data format. The atomized dataset may include a set of atomized data points, whereby each data point may be represented as an RDF triple. According to some embodiments, inferred dataset attributes may be used to identify subsets of data in other dataset, which may be used to extend or enrich a dataset. An enriched dataset may be stored as data representing “an enriched graph” in, for example, a triplestore or an RDF store (e.g., based on a graph-based RDF model). In other cases, enriched graphs formed in accordance with the above, and any implementation herein, may be stored in any type of data store or with any database management system.

FIG. 9 is a diagram depicting a dataset creation interface, according to some embodiments. Diagram **900** depicts a dataset creation interface **902** as an example of a computerized tool to form collaborative datasets. Diagram **900** also depicts a collaborative dataset consolidation system **910**, which is shown to include a repository **940**, a user interface (“UI”) element generator **980**, a programmatic interface **990**, and a processor **999**. User interface (“UI”) element generator **980** may be configured to generate data to form user interface elements, and may be further configured to cause presentation of user interface elements on a user interface to facilitate data signal detection to initiate a dataset creation process, according to various examples. In one or more implementations, elements depicted in diagram **900** of FIG. 9 may include structures and/or functions as similarly-named or similarly-numbered elements depicted in other drawings.

Dataset creation interface **902** may be used to create, or initiate creation of, a collaborative dataset via a computing device (not shown). In the example shown, dataset creation interface **902** includes a descriptive title **901**, a number of user interface elements to facilitate dataset creation, such as a search field **921**, a dataset title **903**, a file upload interface **906**, a “create dataset” activation input **904**, an “open” activation input **941**, a “private” activation input **942**, a “restricted” activation input **944**, and any other type of user interface element that may be used to create datasets that, in turn, may be transformed into atomized datasets, such as an atomized dataset stored in repository **940**.

In this example, consider that dataset creation interface **902** is configured to create a dataset directed to earthquake-related data. Text entered into dataset title field **903** may be parsed, analyzed and associated with the created dataset to identify the dataset and to make at least some of the text in the title entered in field **903** searchable (e.g., in search field **921**). Thus, the term “earthquake” may enable the created dataset to be returned in search results responsive to a search of “earthquake data” in search field **921**. “Open” activation input **941** may be configured to activate, if selected, logic to classify the dataset as “publicly available data” such that anyone may access (e.g., search, view, query, download, modify, etc.) the earthquake dataset created using dataset creation interface **902**. “Private” activation input **942** may be configured to activate, if selected, logic to classify the dataset as “private data” such that no other dataset may link to the “earthquake dataset” and no one may access the dataset, unless authorization is granted to do so. “Restricted” activation input **944** may be configured to activate, if selected, logic to classify the dataset as “restricted data.” In some examples, metadata, such as search terms, annotations, etc., may be publicly exposed or searchable, whereas the data of the “earthquake” dataset may be inaccessible. Consequently, a data practitioner that owns a particular dataset may allow others to find the dataset, and if there is interest by another user, the data practitioner may provide authori-

zation the interested user to access the dataset with restrictions (e.g., usage limitations, time limitations, etc.). In some cases, authorization may be made in exchange for remuneration. “Restricted” activation input **944** may be also configured to modify different levels of restricted access.

An owner of the “earthquake” dataset may offer various levels of permissions for a dataset or a particular user. For example, permissions may be selectably configured to enable or disable an ability to be identified in a search, enable or disable viewing of the dataset, enable or disable an ability to query, enable or disable an ability to download the dataset, enable or disable ability to modify the dataset, ability to modify time intervals during which the dataset is accessible, etc.

According to some embodiments, user interface element generator **980** may be configured to cause the generation of a user interface element for dataset creation interface **902** or any other interface, such as those described herein. A user interface element may be generated by user interface element generator **980** as a graphical control element to provide a visual component for presentation to a user. The visual component may be configured to convey data stored in a computing device or functionality of a computing device to, for example, render specialized functionalities described herein. According to some examples, user interface element generator **980** may be configured to generate at least one user interface element and/or at least one subset of executable instructions for implementation at either a client computing device or a server computing device, or a combination thereof. Thus, user interface elements may be configured to facilitate client-side computations or server-side computations, as well as distributed computing among one or more client computing devices, one or more server computing devices, and one or more other computing devices. Examples of user interface elements include, but are not limited to, subsets of executable instructions (e.g., software components, modules, etc., such as “widgets,” APIs, etc.) that facilitate implementations of (1) data signals for user input controls (e.g., initiation of actions and processes via buttons, menus, text fields, hypertext links, etc.) within an interface, (2) data signals for navigation to access one or more computing devices via links, tabs, scrollbars, etc., (3) data signals for modifying (via computations) or manipulating data values (e.g., using labels, check boxes, radio buttons, sliders, etc.), (4) data signals for displaying and manipulating computational results or data outputs, (5) data signals for implementing a data entry interface for accessing data, querying data, etc. (e.g., via a modal window, etc.), and (6) any other action or process configurable to create a collaborative dataset or otherwise implement a collaborative dataset (e.g., analyzing, sharing, and querying a dataset, among other implementations).

Further to the example shown, a processor **999** may be configured, in accordance with executing program code, to facilitate selection of an icon **905** representing a set of data. The selection may be implemented via a pointer **907** (and associated data signals), which enables a set of data **105** to enter an uploading process. Icon **905** and pointer **907** are examples of user interface elements generated by user interface element generator **980**. Processor **999** may detect a data signal originating from dataset creation interface **902**, responsive to activation of “create dataset” user interface **904**. Processor **999** may initiate dataset creation process or may perform one or more portions thereof (e.g., including the process of creating a dataset). According to some embodiments, processor **999** and/or its functionalities may be disposed and/or performed at either a client computing

device or a remote computing device (e.g., a server), or may be disposed or performed at multiple computing devices, including networked or non-networked computing devices. Similarly, collaborative dataset consolidation system **910** may be include logic that may be implemented either at one or more client computing devices or one or more remote computing devices, or may be implemented at multiple computing devices. Either one of user interface element generator **980** and a programmatic interface **990** or both, may be implemented at a client computing device, at a remote computing device, or at multiple computing devices. Further, the functionalities of user interface element generator **980** and a programmatic interface **990** may be performed in series, in parallel, or in any order. The above-described examples of structures and functionalities in diagram **900** are not intended to be limiting, and such structures and functionalities may be implemented with additional breadth.

FIG. **10** is a diagram of an example of a user interface depicting progression of phases during creation of a dataset, according to some embodiments. Diagram **1000** depicts an interface **1002**, which depicts progression of phases during creation of a dataset. For example, progression user interface element **1020** is configured to present the phases of creating a dataset including an uploading user interface element **1022** to depict the process of uploading data, such as a raw data file, initiated by activating a “create dataset” input **904**. Progression user interface element **1020** also is shown to include an insight user interface element **1024** to specify a status for an insight phase of the dataset creation process (e.g., identifying dataset attributes, including derived or inferred dataset attributes), a linking user interface element **1026** to specify the status of a linking phase during atomized datasets are linked (e.g., including links to protected datasets), and a “complete” user interface element **1028**, which specifies the completion of the data creation process.

According to some examples, interface **1002** may also include user interface elements that provide additional guidance or enhance the progression of the data creation process. User interface element **1012** may be configured as a user input to generate data signals to initiate association of summary data to the dataset, such as adding a data file representing a logo, or other graphical imagery of interest, as well as any other summary information (e.g., hyperlinks to sites from which raw data files were sourced, etc.), including text, as well as uploading code or programmatic instructions, among other things. User interface element **1012** also can facilitate uploading non-dataset data, such as any data or files that may provide context for a dataset to enrich understanding of the data. User interface element **1030** may be configured to convey information as to the user or owner of the dataset, and may be further configured to operate as a user input to generate data signals, which may initiate a transition to an interface that presents user account information (not shown). User interface element **1040** may be configured to convey information regarding one or more original files that are used in the dataset creation process. As shown, user interface element **1040** conveys the type of data file (e.g., .XLS file), a data file title (e.g., “Earthquake M4_5 and higher”), a file size (e.g., 168.5 KB), and an age (e.g., when the data file was last uploaded, such as 10 days or seconds ago, etc.), and the like.

User interface element **1014** may be configured as a user input to generate data signals to initiate inclusion of another set of data for creating a new dataset. In turn, the new dataset may be linked automatically to the previously-created dataset. Automatically-generated links may be formed among datasets, such as atomized datasets, based on inferred or

derived dataset attributes, authorized access to protected datasets, etc. In some instances, a user interface may provide a user input (not shown) to facilitate manual linking among datasets. Further, interface **1002** also may include user interface elements **1001**, **1003**, **1005**, **1007**, and **1009**, each of which may be configured as a user input to generate data signals to initiate a particular function. For example, user interface element **1001** may be configured to generate data signals to associate a short description to the dataset, and user interface element **1003** may be configured to generate data signals to associate “tags” (e.g., key words or symbols) to the dataset so that tags may be used for identifying the subset during, for example, a keyword search. User interface element **1005** may be configured to generate data signals to add files (e.g., .CSV, .XLS, .PDF, etc.), or portions thereof, to creation of a collaborative dataset, whereby added files may automatically linked to a dataset. In some cases, user input **1005** performs similar functions as user input **1014**. User interface element **1007** may be configured to generate data signals to associate a narrative to the dataset, whereby the narrative may be of sufficient size to convey sufficient detail to those potential collaborators that may be interested in using the dataset for their own or different purposes. In at least one example, user interface element **1007** may be configured to generate an overlay window (over interface **1002**), the overlay window including an interface (not shown) to enter text or other symbols into the interface. In some cases, the interface of the overlay window may include a text-to-HTML conversion too, such as MARKDOWN™ developed by John Gruber. User interface element **1009** may be configured to generate data signals to associate data representing a license, and, thus, optional legal requirements to the dataset. In some examples, selection of user interface elements **1001**, **1003**, and **1009** may cause transition to another interface, such as interface **1102** of FIG. **11**.

FIG. **11** is a diagram of an example of a user interface configured to enhance dataset attribute data for a dataset, according to some embodiments. Diagram **1100** depicts an interface **1102**, which depicts various user interface elements with which to add or modify dataset attributes, which, in turn, may be implemented as metadata. As shown, a dataset title field **1103a** may be configured to accept text inputs to associate “earthquake” and “data” to a dataset identified as dataset (“/Earthquake data”) **1101**. User interface **1102** may also include the following user interface elements: (1) a description field **1103b** to enter a description of the dataset, (2) a tag field **1105** to add any number of tags, and (3) a pull-down menu **1107** to select an applicable license type for accessing and using the data of dataset **1101**. In some examples, user interface elements **1001**, **1003**, and **1009** of FIG. **10** may cause a transition to a user interface **1102** of FIG. **11** to enter data in description field **1103b**, tag field **1105**, and pull-down menu **1107**, respectively. According to some examples, activation of pull-down menu **1107** may expose any of the following license types for selection, and, thus association to dataset **1101**: Public Domain Dedication Statement, Open Data Commons Public Domain Dedication and License (“PDDL”), Public Domain Dedication License (“CC0 1.0 Universal”), Attribution 2.0 Generic License (“CC BY 2.0”), Open Data Commons Attribution License (“ODC-BY”), Attribution-ShareAlike 3.0 Unported (“CC BY-SA 3.0”), Open Data Commons Open Database License (“ODbL”), Attribution-NonCommercial-ShareAlike (“CC BY-NC-SA”), among other license types.

FIG. **12** is a diagram depicting an example of a data ingestion controller configured to generate a set of layer data files, according to some examples. Diagram **1200** depicts a

dataset ingestion controller **1220** communicatively coupled to a dataset attribution manager **1261**, and is further coupled communicatively to one or both of a user interface (“UP”) element generator **1280** and a programmatic interface **1290** to exchange data and/or commands (e.g., executable instructions) with a user interface, such as a collaborative dataset interface **1202**. According to various examples, dataset ingestion controller **1220** and its constituent elements may be configured to detect exceptions or anomalies among subsets of data (e.g., columns of data) of an imported or uploaded set of data, and to facilitate corrective actions to negate data anomalies, whether automatically, semi-automatically (e.g., one or more calculated or predicted solutions from which a user may select), and manually (e.g., the user may annotate or otherwise correct exceptions). Further, dataset ingestion controller **1220** may be configured to identify, infer, and/or derive dataset attributes with which to: (1) associate with a dataset via, for example, annotations (e.g., column headers), (2) determine a datatype (e.g., as a dataset attribute) for a subset of data in the dataset, (3) determine an inferred datatype for the subset of data (e.g., as an inferred dataset attribute), (4) determine a data classification for a subset of data in the dataset, (5), determine an inferred data classification, (6) derive one or more data structures, such as the creation of an additional column of data (e.g., temperature data expressed in degrees Fahrenheit) based on a column of temperature data expressed in degrees Celsius, (7) identify similar or equivalent dataset attributes associated with previously-uploaded or previously-accessed datasets to “enrich” the dataset by linking the dataset via the dataset attributes to other datasets, and (8) perform other data actions.

Dataset attribution manager **1261** and its constituent elements may be configured to manage dataset attributes over any number of datasets, including correlating data in a dataset against any number of datasets to, for example, determine a pattern that may be predictive of a dataset attribute. For example, dataset attribution manager **1261** may analyze a column that includes a number of cells that each includes five digits and matches a pattern of valid zip codes. Thus, dataset attribution manager **1261** may classify the column as containing zip code data, which may be used to annotate, for example, a column header as well as forming links to other datasets with zip code data. One or more elements depicted in diagram **1200** of FIG. **12** may include structures and/or functions as similarly-named or similarly-numbered elements depicted in other drawings, or as otherwise described herein, in accordance with one or more examples. Note, too, that while data structures described in this example, as well as in other examples described herein, may refer to a tabular data format, various implementation herein may be described in the context of any type of data arrangement. The descriptions of using a tabular data structure are illustrative and are not intended to be limiting. Therefore, the various implementations described herein may be applied to many other data structures.

Dataset ingestion controller **1220**, at least in some embodiments, may be configured to generate layer file data **1250**, which may include a number of data arrangements that each may constitute a layer file. Notably, a layer file may be used to enhance, modify or annotate data associated with a dataset, and may be implemented as a function of contextual data, which includes data specifying one or more characteristics of the context or usage of the data. Data and datasets may be enhanced, modified or annotated based on contextual data, such as data-related characteristics (e.g., type of data, qualities and quantities of data accesses,

including queries, purpose or objective of datasets, such as deriving vaccines for Zika virus, etc.), time of day, user-related characteristics (e.g., type of user, demographics of user, citizenship of user, location of user, etc.), and other contextually-related characteristics that may guide creation of a dataset or the linking thereof. Note, too, that the use of layer files need not modify the underlying data. Further to the example shown, a layer file may include a link or pointer that references a location (directly or indirectly) at which related dataset data persists or may be accessed. Arrowheads are used in this example to depict references to layered data. A layer file may include layer property information describing how to treat (i.e., use) the data in the dataset (e.g., functionally, visually, etc.). In some instances, “layer files” may be layered upon (e.g., in reference to) another layer, whereby layers may be added, for example, to sequentially augment underlying data of the dataset. Therefore, layer files may provide enhanced information regarding an atomized dataset, and adaptability to present data or consume data based on the context (e.g., based on a user or data practitioner viewing or querying the data, a time of day, a location of the user, the dataset attributes associated with linked datasets, etc.). A system of layer files may be adaptive to add or remove data items, under control of the dataset ingestion controller **1220** (or any of its constituent components), at the various layers responsive to expansions and modifications of datasets (e.g., responsive to additional data, such as annotations, references, statistics, etc.).

To illustrate generation of layer file data **1250**, consider the following example. Dataset ingestion controller **1220** is configured to receive data from data file **1201a**, which may be arranged in a tabular format including columns and rows (e.g., based on .XLS file format). In this example, the tabular data is depicted at layer (“0”) **1251**. In this example, layer (“0”) **1251** includes a data structure including subsets of data **1255**, **1256**, and **1257**. As shown, subset of data **1255** is shown to be a column of numeric data associated with “Foo” as column header **1255a**. Subset of data **1256** is shown to be a column of categorical data (e.g., text strings representing colors) associated with “Bar” as column header **1256a**. And subset of data **1257** is a column of string data that may be of numeric datatype and is without an annotated column header (“???”) **1257a**.

Next, consider operation of dataset ingestion controller **1220** in relation to ingested data (“layer ‘0’”) **1251**. Dataset ingestion controller **1220** includes a dataset analyzer **1230**, which may be configured to analyze data **1251** to detect data entry exceptions and irregularities (e.g., whether a cell is empty or includes non-useful data, whether a cell includes non-conforming data, whether there are any missing annotations or column headers, etc.). In this example, dataset analyzer **1230** may analyze data in columns of data **1255**, **1256**, and **1257** to detect that column **1257** is without descriptive data representing a column header **1257a**. As shown, dataset analyzer **1230** includes an inference engine **1232** that may be configured to infer or interpret a dataset attribute (e.g., as a derived attribute) based on analyzed data. Further, inference engine **1232** may be configured to infer corrective actions to resolve or compensate for the exceptions and irregularities, and to identify tentative data enrichments (e.g., by joining with, or linking to, other datasets) to extend the data beyond that which is in data file **1201a**. So in this example, dataset analyzer **1230** may instruct inference engine **1232** to participate in correcting the absence of the column description.

Inference engine **1232** is shown to include a data classifier **1234**, which may be configured to classify subsets of data

(e.g., each subset of data as a column) in data file **1201a** as a particular data classification, such as a particular data type, a particular annotation, etc. According to some examples, data classifier **1234** may be configured to analyze a column of data to infer a datatype of the data in the column. For instance, data classifier **1234** may analyze the column data to automatically infer that the columns include one of the following datatypes: an integer, a string, a Boolean data item, a categorical data item, a time, etc. In the example shown, data classifier **1234** may determine or infer, automatically or otherwise, that data in columns **1255** and **1256** are a numeric datatype and categorical data type, respectively, and such information may be stored as dataset attribute (“numeric”) **1252a** and dataset attribute (“categorical”) **1252b** at layer (“1”) **1252** (e.g., in a layer file). Similarly, data classifier **1234** may determine or infer data in column **1257** is a numeric datatype and may be stored as dataset attribute (“numeric”) **1252c** at layer **1252**. The dataset attributes in layer **1252** are shown to reference respective columns via, for example, pointers.

Data classifier **1234** may be configured to analyze a column of data to infer or derive a data classification for the data in the column. In some examples, a datatype, a data classification, etc., as well any dataset attribute, may be derived based on known data or information (e.g., annotations), or based on predictive inferences using patterns in data **1203a** to **1203d**. As an example of the former, consider that data classifier **1234** may determine data in columns **1255** and **1256** can be classified as a “date” (e.g., MM/DD/YYYY) and a “color,” respectively. “Foo” **1255a**, as an annotation, may represent the word “date,” which can replace “Foo” (not shown). Similarly, “Bar” **1256a** may be an annotation that represents the word “color,” which can replace “Bar” (not shown). Using text-based annotations, data classifier **1234** may be configured to classify the data in columns **1255** and **1256** as “date information” and “color information,” respectively. Data classifier **1234** may generate data representing as dataset attributes (“date”) **1253a** and (“color”) **1252b** for storage as at layer (“2”) **1253** of a layer file, or in any other layer file that references dataset attributes **1252a** and **1252b** at layer **1252**. As to the latter, a datatype, a data classification, etc., as well any dataset attribute, may be derived based on predictive inferences (e.g., via machine learning, etc.) using patterns in data **1203a** to **1203d**. In this case, inference engine **1232** and/or data classifier **1234** may detect an absence of annotations for column header **1257a**, and may infer that the numeric values in column **1257** each includes five digits, and match patterns of number indicative of valid zip codes. Thus, dataset classifier **1234** may be configured to classify (e.g., automatically) the digits as constituting a “zip code,” and to generate, for example, an annotation “postal code” to store as dataset attribute **1253c**. While not shown in FIG. 12, consider another illustrative example. Data classifier **1234** may be configured to “infer” that two letters in a “column of data” (not shown) of a tabular, pre-atomized dataset includes country codes. As such, data classifier **1234** may “derive” an annotation (e.g., representing a data type, data classification, etc.) as a “country code,” such country codes AF, BR, CA, CN, DE, JP, MX, UK, US, etc. Therefore, the derived classification of “country code” may be referred to as a derived attribute, which, for example, may be stored in one or more layer files in layer file data **1250**.

Also, a dataset attribute, datatype, a data classification, etc. may be derived based on, for example, data from user interface data **1292** (e.g., based on data representing an annotation entered via user interface **1202**). As shown,

collaborative dataset interface **1202** is configured to present a data preview **1204** of the set of data **1201a** (or dataset thereof), with “???” indicating that a description or annotation is not included. A user may move a cursor, a pointing device, such as pointer **1279**, or any other instrument (e.g., including a finger on a touch-sensitive display) to hover or select the column header cell. An overlay interface **1210** may be presented over collaborative dataset interface **1202**, with a proposed derived dataset attribute “Zip Code.” If the inference or prediction is adequate, then an annotation directed to “zip code” may be generated (e.g., semi-automatically) upon accepting the derived dataset attribute at input **1271**. Or, should the proposed derived dataset attribute be undesired, then a replacement annotation may be entered into annotate field **1275** (e.g., manually), along with entry of a datatype in type field **1277**. To implement, the replacement annotation will be applied as dataset attribute **1253c** upon activation of user input **1273**. Thus, the “postal code” may be an inferred dataset attribute (e.g., a “derived annotation”) and may indicate a column of 5 integer digits that can be classified as a “zip code,” which may be stored as annotative description data stored at layer two **1253** (e.g., in a layer two (“L2”) file). Thus, the “postal code,” as a “derived annotation,” may be linked to the classification of “numeric” at layer one **1252**. In turn, layer one **1252** data may be linked to 5 digits in a column at layer zero **1251**). Therefore, an annotation, such as a column header (or any metadata associated with a subset of data in a dataset), may be derived based on inferred or derived dataset attributes, as described herein.

Further to the example in diagram **1200**, additional layers (“n”) **1254** may be added to supplement the use of the dataset based on “context.” For example, dataset attributes **1254a** and **1254b** may indicate a date to be expressed in U.S. format (e.g., MMDDYYYY) or U.K. format (e.g., DDM-MYYYY). Expressing the date in either the US or UK format may be based on context, such as detecting a computing mobile device is in either the United States or the United Kingdom. In some examples, data enrichment manager **1236** may include logic to determine the applicability of a specific one of dataset attributes **1254a** and **1254b** based on the context. In another example, dataset attributes **1254c** and **1254d** may indicate a text label for the postal code ought to be expressed in either English or in Japanese. Expressing the text in either English or Japanese may be based on context, such as detecting a computing mobile device is in either the United States or Japan. Note that a “context” with which to invoke different data usages or presentations may be based on any number of dataset attributes and their values, among other things.

In yet another example, data classifier **1234** may classify a column of numbers as either a latitudinal or longitudinal coordinate and may be formed as a derived dataset attribute for a particular column, which, in turn, may provide for an annotation describing geographic location information (e.g., as a dataset attribute). For instance, consider dataset attributes **1252d** and **1252e** describe numeric datatypes for columns **1255** and **1257**, respectively, and dataset attributes **1253d** and **1253e** are classified as latitudinal coordinates in column **1255** and longitudinal coordinates in column **1257**. Dataset attribute **1254e**, which identifies a “country” that references dataset attributes **1253d** and **1253e**, is shown associated with a dataset attribute **1254f**, which is an annotation as a name of the country and references dataset attribute **1254e**. Similarly, dataset attribute **1254g**, which identifies a “distance to a nearest city” (e.g., a city having a threshold least a certain population level), may reference

dataset attributes **1253d** and **1253e**. Further, a dataset attribute **1254h**, which is an annotation as a name of the city for dataset attribute **1254g**, is also shown stored in a layer file at layer **1254**.

Dataset attribution manager **1261** may include an attribute correlator **1263** and a data derivation calculator **1265**. Attribute correlator **1263** may be configured to receive data, including attribute data (e.g., dataset attribute data), from dataset ingestion controller **1220**, as well as data from data sources (e.g., UI-related/user inputted data **1292**, and data **1203a** to **1203d**), and from system repositories (not shown). Attribute correlator **1263** may be configured to analyze the data to detect patterns or data classifications that may resolve an issue, by “learning” or probabilistically predicting a dataset attribute through the use of Bayesian networks, clustering analysis, as well as other known machine learning techniques or deep-learning techniques (e.g., including any known artificial intelligence techniques). Attribute correlator **1263** may further be configured to analyze data in dataset **1201a**, and based on that analysis, attribute correlator **1263** may be configured to recommend or implement one or more added or modified columns of data. To illustrate, consider that attribute correlator **1263** may be configured to derive a specific correlation based on data **1207a** that describe two (2) columns **1255** and **1257**, whereby those two columns are sufficient to add a new column as a derived column.

In some cases, data derivation calculator **1265** may be configured to derive the data in a new column mathematically via one or more formulae, or by performing any computational calculation. First, consider that dataset attribute manager **1261**, or any of its constituent elements, may be configured to generate a new derived column including the “name” **1254f** of the “country” **1254e** associated with a geolocation indicated by latitudinal and longitudinal coordinates in columns **1255** and **1257**. This new column may be added to layer **1251** data, or it can optionally replace columns **1255** and **1257**. Second, consider that dataset attribute manager **1261**, or any of its constituent elements, may be configured to generate a new derived column including the “distance to city” **1254g** (e.g., a distance between the geolocation and the city). In some examples, data derivation calculator **1265** may be configured to compute a linear distance between a geolocation of, for example, an earthquake and a nearest city of a population over 100,000 denizens. Data derivation calculator **1265** may also be configured to convert or modify units (e.g., from kilometers to miles) to form modified units based on the context, such as the user of the data practitioner. The new column may be added to layer **1251** data. One example of a derived column is described in FIG. **13** and elsewhere herein. Therefore, additional data may be used to form, for example, additional “triples” to enrich or augment the initial dataset.

Inference engine **1232** is shown to also include a dataset enrichment manager **1236**. Data enrichment manager **1236** may be configured to analyze data file **1201a** relative to dataset-related data to determine correlations among dataset attributes of data file **1201a** and other datasets **1203b** (and attributes, such as dataset metadata **1203a**), as well as schema data **1203c**, ontology data **1203d**, and other sources of data. In some examples, data enrichment manager **1236** may be configured to identify correlated datasets based on correlated attributes as determined, for example, by attribute correlator **1263** via enrichment data **1207b** that may include probabilistic or predictive data specifying, for example, a data classification or a link to other datasets to enrich a dataset. The correlated attributes, as generated by attribute correlator **1263**, may facilitate the use of derived data or

link-related data, as attributes, to form associate, combine, join, or merge datasets to form collaborative datasets. To illustrate, consider that a subset of separately-uploaded datasets are included in dataset data **1203b**, whereby each of these datasets in the subset include at least one similar or common dataset attribute that may be correlatable among datasets. For instance, each of datasets in the subset may include a column of data specifying “zip code” data. Thus, each of datasets may be “linked” together via the zip code data. A subsequently-uploaded set of data into dataset ingestion controller **1220** that is determined to include zip code data may be linked via this dataset attribute to the subset of datasets **1203b**. Therefore, a dataset formatted based on data file **1201a** (e.g., as an annotated tabular data file, or as a CSV file) may be “enriched,” for example, by associating links between the dataset of data file **1201a** and other datasets **1203b** to form a collaborative dataset having, for example, and atomized data format.

FIG. **13** is a diagram depicting a user interface in association with generation and presentation of the derived subset of data, according to some examples. Diagram **1300** depicts a user interface **1302** as an example of a computerized tool to modify collaborative datasets and to present such modified datasets automatically, semi-automatically, or manually. User interface **1302** presents the data preview of a dataset that includes earthquake data and is entitled “Earthquake Data over 30 Day Period” **1310**. Data preview mode **1313** indicates that rows 1-10 of set of data **1304**, which includes 355 rows and 22 columns of data, are available to preview via a user interface element **1314** (e.g., via “scroll bar”). The dataset originates from a set of data **1304**, which is entitled “Earthquakes M4_5 and higher” and includes data describing geolocations, among other things (e.g., earthquake magnitudes, etc.), related to earthquakes having a magnitude 4.5 or higher.

Diagram **1300** depicts a dataset ingestion controller **1320**, a dataset attribute manager **1360**, a user interface generator **1380**, and a programmatic interface **1390** configured to generate a derived column **1392** and to present user interface elements **1312** to determine data signals to control modification of the dataset. One or more elements depicted in diagram **1300** of FIG. **13** may include structures and/or functions as similarly-named or similarly-numbered elements depicted in other drawings, or as otherwise described herein, in accordance with one or more examples. As shown, the dataset may be presented in a tabular format arranged in rows of data in accordance with a specific time (e.g., column **1303** data). The dataset is shown to include column data **1306a** (i.e., latitude coordinates), column data **1306b** (i.e., longitude coordinates), a column including depth data (e.g., depth of earthquake in kilometers from surface), a column **1308** including magnitude data (e.g., size of earthquake), a column including a type of magnitude of the earthquake (e.g., magnitude type “mb” refers to an earthquake magnitude based on a short period body wave to compute the amplitude of a P body-wave).

Logic in one or more of dataset ingestion controller **1320**, dataset attribute manager **1360**, user interface generator **1380**, and programmatic interface **1390** may be configured to analyze columns of data, such as latitude column data **1306a** and longitude column data **1306b**, to determine whether to derive one or more dataset attributes that may represent a derived column of data. In the example shown, the logic is configured to generate a derived column **1392**, which may be presented automatically in portion **1307** of user interface **1302** as an additionally-derived column. As shown, derived column **1392** may include an annotated

column heading “place,” which may be determined automatically or otherwise. Hence, the “place” of an earthquake can be calculated (e.g., using a data derivation calculator or other logic) to determine a geographic location based on latitude and longitude data of an earthquake event (e.g., column data **1306a** and **1306b**) at a distance **1319** from a location of a nearest city. For example, an earthquake event and its data in row **1305** may include derived distance data of “16 km,” as a distance **1319**, from a nearest city “Kaikoura, New Zealand” in derived row portion **1305a**. According to some examples, a data derivation calculator or other logic may perform computations to convert 16 km into units of miles and store that data in a layer file. Data in derived column **1392** may be stored in a layer file that references the underlying data of the dataset.

Further to user interface elements **1312**, a number of user inputs may be activated to guide the generation of a modify dataset. For example, input **1371** may be activated to add derived column **1392** to the dataset. Input **1373** may be activated to substitute and replace columns **1306a** and **1306b** with derived column **1392**. Input **1375** may be activated to reject the implementation of derived column **1392**. In some examples, input **1377** may be activated to manually convert units of distance from kilometers to miles. The generation of the derived column **1392** is but one example, and various numbers and types of derived columns (and data thereof) may be determined.

FIGS. **14** and **15** are diagrams depicting examples of generating derived columns and derived data, according to some examples. Diagram **1400** of FIG. **14** and diagram **1500** of FIG. **15** depict a dataset ingestion controller **1420**, a dataset attribute manager **1460**, a user interface generator **1480**, and a programmatic interface **1490**, one or more of which includes logic configured to each generate one or more derived columns. One or more elements depicted in diagrams **1400** and **1500** may include structures and/or functions as similarly-named or similarly-numbered elements depicted in other drawings, or as otherwise described herein, in accordance with one or more examples.

In diagram **1400**, the logic may be configured to generate derived column **1422** (e.g., automatically) based on aggregating data in column **1404**, which includes data representing a month, data in column **1406**, which includes data representing a day, and data in column **1408**, which includes data representing a year. Column **1422** may be viewed as a collapsed version of columns **1404**, **1406**, and **1408**, according to some examples. Therefore, the logic can generate derived column **1422** that can be presented in user interface **1402** in a particular date format. Note, too, that column annotations, such as “month,” “day,” “year,” and “quantity,” can be used for linking and searching datasets as described herein. Further, diagram **1400** depicts that a user interface **1402** may optionally include user interface elements **1471**, **1473**, and **1475** to determine data signals to control modification of the dataset for respectively “adding,” “substituting,” or “rejecting,” mentation of derived column data.

In diagram **1500**, the logic may be configured to generate derived columns **1504**, **1506**, and **1508** based on data in column **1522** and related data characteristics. Derived columns **1504**, **1506**, and **1508** may also be presented in user interface **1502**. Derived columns **1504**, **1506**, and **1508** may be viewed as expanded versions of column **1522**, according to some examples. Therefore, the logic can extract data with which to, for example, infer additional or separate datatypes or data classifications. For example, the logic may be configured to split or otherwise transform (e.g., automatically) data in column **1522**, which represents a “total

amount,” into derived column **1504**, which represents a quantity, derived column **1506**, which represents an amount, and derived column **1508**, which includes data representing a unit type (e.g., milliliter, or “ml”). Note, too, that column annotations, such as “total amount,” “quantity,” “amount,” and “units,” can be used for linking and searching datasets as described herein. Further, diagram **1500** depicts that a user interface **1502** may optionally include user interface elements **1571**, **1573**, and **1575** to determine data signals to control modification of the dataset for respectively “adding,” “substituting,” or “rejecting,” implementation of derived column data.

FIG. **16** is a diagram depicting a flow diagram as an example of enhanced collaborative dataset creation based on a derived dataset attribute, according to some embodiments. Flow **1600** may be an example of initiating creation of the dataset, such as a collaborative dataset, based on a derived dataset attribute that is derived from a set of data. In some examples, flow **1600** may be implemented in association with a user interface. At **1602**, data to form an input (as a user interface element) may be received via a user interface. For example, a processor executing instruction data at a client computing device (or any other type of computing device, including a server computing device) may receive data to form a user interface element, which may constitute a user input that may be presented in a user interface as, for example, a “create dataset” user input. In one or more cases, activation of a “create dataset” user input can initiate creation of an atomized dataset based on the set of data, which, for example, may be raw data in data file (e.g., a tabular data file, such as a XLS file, etc.). According to some examples, a data preview of subsets of data may be presented in the user interface, the data preview showing portions of a dataset or set of data. A data preview may be generated (e.g., by a user interface element generator) to depict each subset of data as a column of data. In one example, a data view of a column of data may be presented with an unknown dataset attribute, whereby data may be received to annotate a column header to form an annotation to resolve the unknown dataset attribute. The annotation may refer to a datatype, a data classification, or the like. An example of an unknown dataset attribute is depicted as unknown column header (“???”) **1257a** of FIG. **12**.

Referring back to FIG. **16**, a programmatic interface may be activated at **1604** to facilitate the derivation of the dataset attribute that may be used in the creation of a dataset responsive to receiving the first input. The programmatic interface may be implemented as either hardware or software, or a combination thereof. In some examples, the programmatic interface may be distributed as subsets of executable code (e.g., as scripts, etc.) to implement APIs in any number of computing devices. In some embodiments, programmatic interface may be optional and may be omitted.

At **1606**, the set of data may be transformed from a first format to an atomized format to form an atomized dataset. In some examples, a request to initiate creation of the dataset may cause transformation of a dataset by, for example, deriving a dataset attribute based a subset of data. The derived dataset attribute may be used to form an annotation (e.g., derived annotation), or to form a derived column of data in which data is derived from one or more other subsets of data in a dataset, or from any other source of data. As such, an atomized dataset may be generated to include data points associated with derived data. The atomized dataset may be stored in a graph data structure, according to some examples. In various examples, the transformation into an

atomized dataset, which includes one or more derived dataset attributes, may be performed at a client computing device, a server computing device, or a combination of multiple computing devices.

At **1608**, data representing an annotation may be presented at the user interface, the annotation being based on the derived dataset attribute for the subset of data. Therefore, one or more various examples of logic, as described herein, may be implemented to form derived subsets of data, such as derived columns, which may be used to visually convey an enhanced dataset that can be analyzed in relation to an objective or theory. Further, a user interface may be used to manipulate the dataset and its subsets of data, including derived subsets of data. Derived dataset attributes, derived data, and derived data arrangements (e.g., derived columns) may be used to facilitate linking to other datasets, including protected datasets. Additional user interface elements, such as a “link” user input **137** of FIG. **1**, may be presented on a user interface to facilitate linking of atomized datasets based on annotations associated with derived dataset attributes (e.g., responsive to input from a data practitioner in view of insight information, dataset activity feed information, etc.).

At **1610**, a second input may be accepted via the user interface (e.g., in association with a processor) using a second user interface element to create an atomized dataset. In some cases, the second user interface element may be presented as the annotation, which, in turn, may be associated with a column of data. Thus, activation of the second input may be configured to cause linking between the atomized dataset and to another dataset based on the annotation. In other examples, the second input may be configured to invoke, upon activation, other data operations and functions.

FIG. **17** is a diagram depicting an example of a collaboration manager configured to present collaborative information regarding collaborative datasets, according to some embodiments. Diagram **1700** depicts a collaboration manager **1760** including a dataset attribute manager **1761**, and coupled to a collaborative activity repository **1736**. In this example, dataset attribute manager **1761** is configured to monitor updates and changes to various subsets of data representing dataset attribute data **1734a** and various subsets of data representing user attribute data **1734b**, and to identify such updates and changes. Further, dataset attribute manager **1761** can be configured to determine which users, such as user **1708**, ought to be presented with activity data for presentation via a computing device **1709** in a user interface **1718**. In some examples, dataset attribute manager **1761** can be configured to manage dataset attributes associated with one or more atomized datasets. For example, dataset attribute manager **1761** can be configured to analyzing atomized datasets and, for instance, identify a number of queries associated with a atomized dataset, or a subset of account identifiers (e.g., of other users) that include descriptive data that may be correlated to the atomized dataset. To illustrate, consider that other users associated with other account identifiers have generated their own datasets (and metadata), whereby the metadata may include descriptive data (e.g., attribute data) that may be used to generate notifications to interested users of changes, modifications, or activities related to a particular dataset. The notifications may be generated as part of an activity feed presented in a user interface, in some examples.

Collaboration manager **1760** receives the information to be presented to a user **1708** and causes it to be presented at computing device **1709**. As an example, the information presented may include a recommendation to a user to review

a particular dataset based on, for example, similarities in dataset attribute data (e.g., users interested in Zika-based datasets generated in Brazil may receive recommendation to access a dataset with the latest dataset for Zika cases in Sao Paulo, Brazil). Note the listed types of attribute data monitored by dataset attribute manager **1761** are not intended to be limiting. Therefore, collaborative activity repository **1736** may store other attribute types and attribute-related than is shown.

FIG. **18A** depicts an example of a dataset attribute manager configured to generate data to enhance datasets, according to some examples. Diagram **1800** depicts a dataset attribute manager **1861** and one or more of its constituent elements may be configured to correlate, identify, analyze, and summarize datasets and dataset interactions, including correlating, identifying, analyzing, and summarizing user datasets, groups of other user datasets, groups of non-user datasets (e.g., datasets external to collaborative dataset consolidation system), etc. Correlations and dataset interaction summary data may be fed via a dataset activity feed to disseminate dataset-related information via computing device **1802a** to user **1801a**, as well as via other computing devices (not shown) to other users (not shown). Examples of dataset interaction summary data include trending dataset information, trending user information, relevant dataset information, relevant collaborator, dataset tracking information, collaborator tracking information, and the like. Dataset attribute manager **1861** may be configured to calculate correlations among datasets and dataset interactions and may be further configured to summarize the interactions for presentation via, for example, a dataset activity feed. Dataset interactions may be represented as data specifying whether a particular dataset of has been queried, modified, shared, accessed, created, etc., or an event in which another user commented on a dataset or received a comment for a dataset. Other examples may include data representations via a user interface that conveys a number of queries associated with a dataset, a number of dataset versions, identities of users (or associated user identifiers) who have analyzed a dataset, a number of user comments related to a dataset, the types of data practitioners, therefore, may gain additional insights into whether a particular dataset may be relevant based on electronic social interactions among datasets and users. Thus, at least some implementations may be described as “a network for datasets” (e.g., a “social” network of datasets and dataset interactions).

Dataset attribute manager **1861** is configured to identify user dataset attribute data **1804** and user attribute data **1806** associated with a user **1801a** via computing device **1802a**. Further, dataset attribute manager **1861** may be configured to receive, identify, derive or determine global dataset attribute data **1810** from a pool of dataset data, which may include data representing a community of datasets, a subset of dataset, a superset of datasets (e.g., including all or substantially all datasets identifiable or accessible by dataset attribute manager **1861**), as well as interactions therebetween. Also, dataset attribute manager **1861** may be configured to receive, identify, derive or determine global user attribute data **1820** for any number of users, user accounts, etc. Global user attribute data **1820** includes user-related and user account-related data over a community of users.

According to some embodiments, user attribute data **1806** may include user-related characteristics describing a user, a user account, a user computer device system, and other user-related characteristics specifying user interactions with any aspect of a collaborative dataset consolidation system or external thereto. Examples of user attribute data **1806**

include, but are not limited to, a geographic location (e.g., of a user, a user computing device, etc.); a user identifier (e.g., a user name, a user account number identifier, etc.); demographic information; a field of interest and/or scientific discipline (e.g., applied mathematics or engineering, chemistry, physics, earth sciences, astronomy, biology, social science, etc.); a profession and/or title; ranking of user **1801a** by others (e.g., others in a subset of users, such as user in an organization, a scientific discipline, a country, etc.), etc. Other examples of user attribute data **1806** include, but are not limited to, data in datasets; dataset-related data (e.g., metadata), such as data representing tags; data representing titles and/or descriptions of datasets; data indicating whether the dataset is open, private, or restricted; types and amounts of queries against datasets owned by user **1801a**; types and amounts of queries by user **1801a** against other datasets; types and amounts of accesses of datasets owned by user **1801a**; types and amounts of accesses by user **1801a** against other datasets; types of users other datasets with whom user **1801a** collaborates; a number or type of users monitoring (e.g., “following”) datasets interactions by user **1801a**; a number or type of user or dataset interactions that user **1801a** follows or monitors; a number or type of comments associated with datasets owned by user **1801a**; a number or type of comments applied to datasets owned or managed by user **1801a**; a number of citations of one or more datasets owned or managed by user **1801a**; a number of citations to one or more other datasets by user **1801a**, and the like. Note that the above-identified user attribute data **1806** are examples are not intended to be limiting. Note, too, one or more of the above-identified user attribute data **1806** may be used to determine a “context” of dataset usage, and may be referred to, or implemented as, dataset attributes.

Global dataset attribute data **1810** includes any number of datasets and subsets of dataset attributes **1828a**, **1828b**, **1828c**, and **1828n**, one or more of which may be associated with at least one dataset. Subsets of dataset attributes **1828a**, **1828b**, **1828c**, and **1828n** may be uniquely-identifiable and accessible via, for example, a collaborative dataset consolidation system. Hence, data representing dataset attributes for subsets of dataset attributes **1828a**, **1828b**, **1828c**, and **1828n** may be similar to those included in user dataset attribute data **1804**, such as described above.

According to some embodiments, user dataset attribute data **1804** may include dataset-related characteristics describing data of a dataset, metadata or other data associated with a dataset, and other dataset-related characteristics specifying dataset interactions with any aspect of a collaborative dataset consolidation system or external thereto. Examples of user dataset attribute data **1804** include, but are not limited to, data representing quantities or types of links from datasets to a dataset of user **1801a**; data representing quantities or types of links from a dataset of user **1801a** to multiple datasets; data representing context and/or usage of a dataset (e.g., categorical and numeric descriptions thereof); data representing a number of accesses in association with a dataset (including views or any data interaction with a dataset); data representing a quantity of copies, downloads, modifications, or versions of a dataset; data representing types and quantities of comments associated with the dataset; data representing quantity of votes or ranking for one or more datasets; and the like. Additional examples of user dataset attribute data **1804** include, but are not limited to, a number of distinct data points in a column of data, a number of non-empty cells, a mean value, a minimum value, a maximum value, a standard deviation value, a value of skewness, a value of kurtosis, as well as any

other statistical or characteristic data. Note that the above-identified user dataset attribute data **1806** are examples are not intended to be limiting. Note, too, one or more of the above-identified user dataset attribute data **1806** may be used to determine a “context” of dataset usage, and may be referred to, or implemented as, dataset attributes.

Global user attribute data **1820** may include any number of subsets of user attributes **1838a**, **1838b**, **1838c**, and **1838n**, one or more of which may be associated with at least one user or user account. Subsets of user attributes **1838a**, **1838b**, **1838c**, and **1838n** may be accessible via, for example, a collaborative dataset consolidation system. Hence, data representing user attributes in user attributes **1838a**, **1838b**, **1838c**, and **1838n** may be processed similar to those included in user attribute data **1806**, such as described above.

Dataset attribute manager **1861** is shown to include a trend dataset calculator **1862**, a relevant dataset calculator **1864**, and a dataset tracker **1866**. Trend dataset calculator **1862** may be configured to determine values (e.g., normalized values, such as standardized values, including z-score determination, or the like) of aggregated dataset attributes (e.g., over a large number of subsets of dataset attributes) with which to compare to a subset of dataset attributes for a dataset to determine, for example, trending information or a rank for the dataset. For example, a particular dataset may have one or more dataset attributes with the following values or representations: a tag “Zika” as a data attribute, a number of 15,891 queries per unit time, and a number of 389 requests to access the dataset. Thus, trend dataset calculator **1862** may be configured to compare these values against, for example, “average” values, which may be calculated by trend dataset calculator **1862**. Further, trend dataset calculator **1862** may be configured to compare “Zika” tags, “15,891” queries, and “369” requests to the average values of the aggregated dataset attributes to determine a comparative ranking and/or trend information of the dataset. The comparative ranking and/or trend information may be transmitted via notifications to user interfaces and activity feed portions thereof to disseminate dataset-related updates in real time (or substantially in real-time). Note that trend dataset calculator **1862** (as well as other calculators and logic of dataset attribute manager **1861**) is not limited to implementing an “average value” as a comparative value for aggregated dataset attributes, but rather, any other representation, metric (e.g., mean value, etc.), or technique (e.g., use of k-NN algorithms, regression, Bayesian inferences and the like, classification algorithms, including Naïve Bayes classifiers, or any other statistical or empirical technique) to measure or rank a dataset attribute relative to a predominated number of datasets may be implemented, according to various examples. Trend dataset calculator **1862** may generate trending dataset data **1812** to initiate presentation of trending or ranking information on a user interface.

A superset of datasets associated with a superset of users, such as user **1801a**, may be associated with global dataset attribute data **1810**, which may include aggregated values or indicative values of a predominant number of datasets. For example, each subset **1828a**, **1828b**, **1828c**, and **1828n** of dataset attributes may include data representative of an aggregated value (e.g., a normalized value) or representation of a dataset attribute for the superset of datasets (e.g., large numbers of datasets associated with large numbers of users, including, but not limited to all accessible datasets, etc.). As an example, consider that subset **1828a** of dataset attributes includes attribute data describing “an average number of links” to other datasets, subset **1828b** of dataset attributes

includes attribute data describing “an average number of times datasets are returned as a result” of a search, subset **1828c** of dataset attributes includes attribute data describing “an average number comments received” in association with datasets, and subset **1828n** of dataset attributes includes attribute data describing “an average number of times datasets are queried.” Based on these “average” values, which may be generated by trend dataset calculator **1862**, dataset attributes values of associated one or more datasets may be compared to the average values of the one or more datasets to determine a comparative ranking and/or trend information, as determined by trend dataset calculator **1862**. According to some embodiments, subsets **1828a**, **1828b**, **1828c**, and **1828n** of dataset attributes that are identified as corresponding to a superset of users may be used to determine a trend for, or a ranking of, a dataset for a particular user, such as user **1801a** relative to the aggregated values or representations of dataset attributes associated with the superset of datasets.

Relevant dataset calculator **1864** of dataset attribute manager **1861** may be configured to determine values of dataset attributes of a particular dataset in global dataset attribute data **1810**. Those attributes then can be compared to corresponding similar dataset attributes of user dataset attribute data **1804** to determine, for example, a degree of relevancy between two datasets. By determining a degree of relevancy between a dataset of user **1801a** and another dataset associated with global dataset attribute data **1810**, relevant dataset calculator **1864** can generate relevant dataset data **1814** that represents a list of datasets **1810** that may be most relevant to user **1801a**. Additionally, relevant dataset calculator **1864** may be configured to determine degrees of relevancy for any number of different datasets, whereby the most relevant datasets may be included in an activity feed for a user who may be interested in such datasets. Therefore, user **1801a** may identify or learn of a dataset of interest in an expedited manner than otherwise might be the case.

In at least one other example, a user **1801a** (or a group of collaborators including user **1801a**) may correspond in association with subsets **1828a**, **1828b**, **1828c**, and **1828n** of dataset attributes. As a variation of a previous example, consider that the following is relevant to a dataset: subset **1828a** of dataset attributes includes attribute data describing “a number of links” to other datasets, subset **1828b** of dataset attributes includes attribute data describing “a number of times a dataset is returned as a result” of a search, subset **1828c** of dataset attributes includes attribute data describing “a number comments received” in association with a dataset, and subset **1828n** of dataset attributes includes attribute data describing “a number of times a dataset has been queried.” According to some embodiments, subsets **1828a**, **1828b**, **1828c**, and **1828n** of dataset attributes may be identified to determine a degree of relevancy to, for example, user dataset attribute data **1804** to determine whether dataset attributes **1828a**, **1828b**, **1828c**, and **1828n** may be relevant to the interests of user **1801a**.

Dataset tracker **1866** of dataset attribute manager **1861** maybe configured to monitor and track new, updated, modified, deleted, etc. values of dataset attributes of global dataset attribute data **1810**, as well as user dataset attribute data **1804**. Thus, dataset tracker **1866** may be configured to determine updates for disseminating via dataset update data **1816** to relevant datasets, users, user accounts, etc. Thus, user **1801a** may be notified to identify or learn of a particular dataset interaction that facilitates the update to a dataset of interest. User **1801a** then can explore the updates in an expedited manner than otherwise might be the case

Dataset attribute manager **1861** also is shown to include a trend user calculator **1863**, a relevant collaborator calculator **1865**, and a collaborator tracker **1867** that are configured to generate trending user data **1811**, relevant collaborator data **1813**, and collaborator update data **1815**, respectively. According to some examples, trend user calculator **1863**, relevant collaborator calculator **1865**, and collaborator tracker **1867** may be configured to perform similar or equivalent functions as trend dataset calculator **1862**, relevant dataset calculator **1864**, and dataset tracker **1866**, respectively, but using user attribute data **1806** and global user attribute data **1820**. Therefore, trend user calculator **1863** may be configured to determine values of aggregated user attributes (e.g., over a large number of subsets of user attributes) with which to compare to a subset of user attributes for a dataset to determine, for example, trending information or a rank for a user based on global user attribute data **1820**. As such, trend user calculator **1863** may be configured to determine, for example, a subset of the most highly-ranked users for a unit of time. An electronic notification may be transmitted via trending user data **1811** to a user interface of computing device **1802a** to notify user **1801a** of trending users.

Relevant collaborator calculator **1865** may be configured to determine values of user attributes of a particular dataset in global user attribute data **1820** with which to compare to corresponding similar user attributes of user attribute data **1804** to determine, for example, a degree of relevancy between two users or user accounts, or the like. By determining a degree of relevancy between user **1801a** and another user associated with global user attribute data **1820**, relevant collaborator calculator **1865** can generate relevant collaborator data **1813** for presentation as a notification in a user interface of computing device **1802a**. Relevant collaborator data **1813** may present to user **1801a** the most relevant collaborators (e.g., a top 10 list of relevant users) so that user **1801a** may determine whether to collaborate, or otherwise exchange data electronically with another user to facilitate improvements in the datasets or efforts of user **1801a**. Collaborator tracker **1867** may be configured to determine updates to changes in user attributes for disseminating via collaborator update data **1815** to relevant datasets, users, user accounts, etc. (including user **1801a**) to alert interested entities of user interactions that may be of interest.

FIGS. **18B** and **18C** are diagrams that depict examples of calculators to determine trend and relevancy data relating to collaborative datasets, according to some examples. Diagram **1850** of FIG. **18B** depicts a trend user calculator **1863** configured to receive user attributes **1830** of a particular user **1840**. Trend user calculator **1863** also is configured to receive aggregated user attributes **1834** associated with a pool of users **1842**, and data representing a number of weighting factors **1832** to influence operations of trend user calculator **1863**. While in some cases, aggregated user attributes **1834** may represent average or mean values for respective attributes, this need not be required. Thus, the values of aggregated user attributes **1834** can be any value for comparing dataset or user attributes to each other. Regardless, each of aggregated user attributes (e.g., UA1, UA2, . . . , UAn) may have a value with which to compare with values of user attributes **1830** to determine a relative ranking of user **1840** in view of pool of users **1842**. Values of weighting factors **1832** are configurable to emphasize or deemphasize one or more user attributes in determining trending user data **1811**. For example, user attributes asso-

ciated with any of “tags,” scientific discipline (“Sci Displ”), and “country” may be emphasized or deemphasized based on weighting factors **1832**.

Trend user calculator **1863** is shown to also include differential modules **1831** configured to detect a value of a user attribute **1830** and determine, for example, a “distance” to a value of an aggregated user attribute **1834**. In cases in which the value of user attribute **1830** closely matches, or is near to, a value of an aggregated user attribute **1834**, the value of user attribute **1830** is less notable, and, therefore, less likely to be indicative of a trend beyond, for example, the norm. But in cases in which the value of user attribute **1830** diverts relatively significantly from an aggregated user attribute **1834**, then user attribute **1830** and the associated dataset may be of greater interest to certain users and datasets. For example, if the value of user attribute **1830**, such as a number of “followers,” diverges from an average value of “followers,” then trending data may indicate that an increased number of other users have requested to “follow” dataset interactions associated with a particular user or dataset. Such increases may indicate that the highly-followed dataset may be perceived as being of high-value to a community of data practitioners. Trend user calculator **1863** can transmit trending user data **1811** to notify potentially interested users in activity feeds. Therefore, potentially interested users may learn quickly of new developments in data science management analytics in real-time or near real-time.

Diagram **1870** of FIG. **18C** depicts a relevant collaborator calculator **1865** configured to receive user attributes **1880** of a particular user **1890**. Relevant collaborator calculator **1865** also is configured to receive user attributes **1884** associated with a user under analysis **1892** (e.g., a user being analyzed to determine whether the user is relevant to user **1890**), and data representing a number of weighting factors **1882** to influence operations of relevant collaborator calculator **1865**. While in some cases, user attributes **1884** may represent average or mean values for respective attributes, this need not be required. Thus, the values of user attributes **1884** can be any value for comparing dataset or user attributes to each other. So, each of user attributes **1884** may have a value with which to compare with values of user attributes **1880** to determine a relative relevancy of user under analysis **1892** to user **1890**. Values of weighting factors **1882** are configurable to emphasize or deemphasize one or more user attributes in determining relevant collaborator data **1813**.

Relevant collaborator calculator **1865** is shown to also include differential modules **1881** configured to detect a value of a user attribute **1880** and determine, for example, a “distance” to a value of user attribute **1884**. Unlike the above-described operation of differential modules, when a value of user attribute **1880** closely matches, or is near to, a value of a user attribute **1884**, the value of user attribute **1884** is indicative that user attribute **1880** and user attribute **1884** are similar (i.e., relevant) to each other relative to others. For example, if the value of user attributes **1884** include a “tag” (e.g., Zika), a scientific discipline (“Sci Displ”) (e.g., biology, including serology and vaccine development), and a “country” (e.g., U.S.A.), that closely match those of user attributes **1880**, then a dataset associated with user under analysis **1892** may be relevant to the efforts to user **1890**. Relevant collaborator calculator **1865** can transmit relevant collaborator data **1813** to notify potentially interested users in activity feeds. Therefore, potentially interested users may learn quickly of new developments in

data science management analytics in real-time or near real-time and can contact or collaborate with newly-found datasets.

FIG. 19 is a diagram depicting an example of a dataset activity feed to present dataset interaction control elements in a user interface, according to some embodiments. Diagram 1900 depicts a user interface 1902 presenting one or more user interface elements constituting user account information 1910, user datasets 1920, 1922, and 1924, and a dataset activity feed 1950. One or more text strings depicted in user interface 1902 may be configured as control elements (e.g., user inputs) that, in response to user interaction via activation of the user input, cause presentation of dataset interaction information. Activation may be triggered by, for example, selecting or hovering over a user input using a pointer element 1990 (or other things, such as a finger on a touch-sensitive display).

User account information 1910 may include user interface elements 1972a and 1972b that relate to “a number of followers” and “a number following,” respectively. The “number of followers” may indicate a number of other datasets or other user accounts that monitor dataset interactions relating to datasets 1920, 1922, and 1924, as well as updates to user attributes associated with user account information 1920. For example, each of at least eleven (11) datasets may be indicated as a “follower” that may cause notifications to be received into dataset activity feed 1950 of the user interfaces (not shown) associated with the eleven datasets (and other 11 users) if, for example, dataset 1920 is modified, queried, or any other data interaction are performed, or any other action is performed by a user associated with user account 1910. By contrast, the “number following” may indicate a number of other datasets or other user accounts that user account 1910 and datasets 1920, 1922, and 1924 are following, and may receive notifications in dataset activity feed 1950. For example, pointer element 1990a may select or hover over user interface element 1972b to cause presentation (not shown) of identities and other information describing twelve (12) datasets being followed by datasets 1920, 1922, or 1924 and/or user “Sherman” of user account 1910. Further, user interface elements associated with corresponding user datasets 1920, 1922, or 1924, if activated, may be configured to display or otherwise cause dataset-related information, including dataset attributes, to be presented via user interface 1902 or any other user interface.

Dataset activity feed 1950, in this example, are shown to include a number of notifications 1951, 1952, 1953, 1954, 1955, 1956, and 1957, each having user interface elements to cause activation and/or presentation of dataset-related interaction functions and/or information. Each of notifications 1951, 1952, 1953, 1954, 1955, 1956, and 1957 may be generated (e.g., remotely) in response to one of a number of dataset interactions associated with a corresponding dataset. In at least some notifications, such as notification 1951, a type of dataset interaction 1951a may be identified in view of a user identifier 1970 and a dataset 1972. Here, notification 1951 indicates that a user “Adam” associated with user identifier 1970 has caused a dataset interaction 1951a of “creating a dataset,” with a dataset identifier (“Open Food Fact”) 1972 for a dataset. Notifications 1952, 1953, 1954, 1955, 1956, and 1957 may be provide indications, respectively, of dataset interaction 1952a (e.g., dataset “Age-CAP” is queried by user “Beth”), 1953a (e.g., dataset “Age-CAP” has access granted to Becky user “Adam”), 1954a (e.g., dataset “Dementia Survey Data” is queried by user “Mo”), 1955a (e.g., dataset “Historical Trading Data” is corre-

sponds, or is linked to, dataset “Historical GPD” by user “JohnQ”), 1956a (e.g., dataset “Historical GPD” is added or uploaded by user “JohnQ”), and 1957a (e.g., dataset “Student Loan Data” has been associated with a comment added by user “Sid”). Other dataset interactions are possible.

Further, user interface elements of notifications 1951 to 1957 may be activated to at least present related information. For example, pointer element 1990b may select user identifier 1970 (e.g., a hyperlink or control input) that may cause presentation of user account-related information for user “Adam” (not shown). As another example, pointer element 1990c may be activated to select data interaction 1957a to cause generation of an overlay window to present, for example, text 1992 of a comment. Therefore, a user may determine another user, a comment, and a dataset “in a view” (e.g., single user interface view), whereby a user may expedite data collection and collaboration.

In view of the foregoing, collaboration among users and formation of collaborative datasets may be expedited based on the dissemination up-to-date information provided by dataset activity feed 1950. Thus, user “Sherman” 1910 more readily may be able to determine applicability of other datasets, such as dataset “Dementia Survey Data” of notification 1954, to one of user datasets 1920, 1922, and 1924. Consequently, user “Sherman” 1910 may expedite modeling data and/or theory testing, among other things.

FIG. 20 is a diagram depicting other examples of dataset activity feeds to present a dataset recommendation feed in a user interface, according to some embodiments. Diagram 2000 depicts a user interface 2002 presenting one or more user interface elements of one or more dataset recommendation feeds based on dataset interactions and dataset attributes. User interface 2002 is shown to include a dataset recommendation feed 2020 that presents a number of higher-ranked “tags” 2010 that may be of interest (and relevant) to a dataset and user account. Also, user interface 2002 may include a dataset recommendation feed 2022 that presents a number of users as “who to follow,” each of whom may be of interest (and relevant) to a dataset and user account. A user may be follow another user (e.g., initiate receipt of notifications) by selecting a corresponding user input 2012. Further, user interface 2002 may include a dataset recommendation feed 2024 that presents a number of discussions regarding, for example, a dataset 2014, such as dataset “Hate Crime Laws and Statistics.” One or more text strings depicted in user interface 2002 may be configured as control elements (e.g., user inputs) that, in response to user interaction via activation of the user input, cause presentation of respective dataset recommendation information.

FIG. 21 is a diagram depicting examples of trend-related dataset activity feeds to facilitate presentation and interaction with user interface elements, according to some embodiments. Diagram 2100 depicts a user interface 2102 configured to present user interface elements, which may be interactive (e.g., control user inputs), that constitute trending information. Trending dataset-related information 2120 is shown to include trending datasets 2130 and trending users 2140.

Trending datasets 2130 may be disposed in a portion of user interface 2102 that presents user interface elements including, for example, a ranking 2132 (e.g., ranking of 1, 2, 3, . . . , n). Rankings 2132 are each associated with data representing a trending dataset 2150, which may include other user interface elements, such as text information 2152 describing trending dataset 2150. An exemplary description may include a purpose of the dataset, a source of the dataset, a field of applicability (e.g., biological, such as serological

applications to test vaccines, etc.), and the like. Trending datasets **2150** may also include an indication **2156** whether the dataset is open, restricted, or private. Further, trending datasets **2150** may also include user interface element **2158**, which may be a control element (e.g., a user input). On activation, such as by a pointer element, user interface element **2107** may be configured to generate an overlay window **2110** (over interface **2102**). Overlay window **2110** may include an interface to initiate a request to access trending datasets **2150** via user input **2171**, or to reject linking trending dataset **2150** to a dataset **2104**. As trending dataset **2150** is a private dataset, a username field **2175** and passcode field **2177** may be presented in overlay window **2110** to facilitate authentication for accessing or linking to trending dataset **2150**.

Trending users **2140** may be disposed in another portion of user interface **2102** and may present user interface elements including, for example, a ranking **2142** (e.g., ranking of 1, 2, 3, . . . , n). Trending user **2160** may have similar user interface elements as trending dataset **2150**, such as a text description **2162** and a user interface element **2168** configured to form a link between user **2105** and trending user **2160**. In some examples, activation of link element **2168** may cause, for example, data to be exchanged (e.g., notifications) among users, as well as may enable a number of permissions when accessing a dataset associated with trending user **2160**. Permissions include, but are not limited to, authorization to copy a dataset, authorization to modify a dataset, authorization to query a dataset, etc.

FIG. **22** is a diagram depicting other examples of relevancy-related dataset activity feeds to facilitate presentation and interaction with user interface elements, according to some embodiments. Diagram **2200** depicts a user interface **2202** configured to present user interface elements, which may be interactive (e.g., via control user inputs), that constitute relevancy information. Relevant dataset-related information **2220** is shown to include relevant datasets **2230** and relevant users **2240**, which may include user interface elements similar to trending datasets **2130** and trending users **2140**, respectively, of FIG. **21**. A portion of user interface **2202** that includes relevant datasets **2230** may be configured to present, for example, highest ranked user datasets **2250** that rank in accordance with their degree of relevancy to dataset **2204** (e.g., ranking “1” of rankings **2232** indicates the most relevant other user dataset). Relevant datasets **2230** may include user interface elements, such as “private” indication **2256**, and a user interface element **2258** (e.g., a control element as a user input) configured to activate an overlay interface (not shown) to link relevant dataset **2250** to dataset **2204**. Relevant users **2240** may include a user interface element **2268** configured to establish a link between relevant dataset **2250** and user **2205**. Another portion of user interface **2202** includes relevant users **2240** that is configured to present, for example, highest ranked users **2260** that rank in accordance with their degree of relevancy to user **2205** (e.g., ranking “1” of rankings **2242** indicates the most relevant other user). In some examples, user interface **2202** may include user interface elements, such as user input **2295**, for voting or otherwise expressing usefulness of dataset **2204**. For example, user input **2295** may indicate a number of users or viewers that “like” dataset **2204**. User input **2297** may be implemented to cause information regarding dataset **2204** to be transmitted (i.e., communicated) to third party social networking systems, such as Facebook™, Twitter™, and the like. According to some examples, elements depicted in diagram **2200** of FIG. **22**

may include structures and/or functions as similarly-named or similarly-numbered elements depicted in other drawings.

FIG. **23** is an example of a data entry interface to access atomized datasets, according to some examples. Diagram **2300** depicts a collaborative dataset access interface **2322**, which operates as a computerized tool to access a collaborative dataset (e.g., an atomized dataset) or perform other operations, such as a query. Also shown is a user interface element generator **2380**, a programmatic interface **2390**, and a collaborative dataset, consolidation system **2310**, which, in turn, includes a dataset attribute manager **2361** and a repository **2340**. According to some examples, elements depicted in diagram **2300** of FIG. **23** may include structures and/or functions as similarly-named or similarly-numbered elements depicted in other drawings. Collaborative dataset access interface **2322** includes a data entry interface **2350** to enter, for example, commands to access a graph data structure (e.g., an atomized dataset). A graph-level access or query language, such as SPARQL, or the like, may be used to enter a query into data entry interface **2350**. When SPARQL is used, a “SPARQL” indicator **2303** may be presented. In this example, a query having a title (“First 100 Data Points”) **2305** is entered into data entry interface **2350** for querying against a linked dataset **2301**. The query may be executed upon activation of user input (“run query”) **2390**. Further, collaborative dataset consolidation system **2310** may generate collaborator update data **2305** to propagate or disseminate notifications that a user has performed a query against a dataset **2301**. Also, collaborative dataset consolidation system **2310** may generate dataset update data **2370** to alert other datasets or users that a particular dataset has been queried. User input **2375** may cause a query to be published, which enables the query and results to become visible and shareable from, for example, a dataset homepage (not shown). Therefore, a community of data practitioners may be able keep informed about developments or dataset interactions regarding datasets in which they are interested.

FIG. **24** is an example of a user interface to present interactive user interface elements to provide a data overview of a dataset, according to some examples. Diagram **2400** depicts a user interface **2402** as an example of a computerized tool to provide access to summarized data, information and aspects of a dataset (e.g., an atomized dataset), including schema information, or to perform other operations. In some examples, “insight information” may be calculated and presented via user interface **2402**, which may be generated during a dataset creation process, or subsequently thereafter, to present user interface elements that may include, for example, characterizations of the data in summary form shown in diagram **2400**. For example, user interface elements may present information, (e.g., textually, statistically, graphically, etc.) that may convey characteristics of the data distribution and “shape,” among other things. Diagram **2400** also depicts a user interface element generator **2480**, a programmatic interface **2490**, and a collaborative dataset consolidation system **2410**, and a data derivation calculator **2465**. According to some examples, elements depicted in diagram **2400** of FIG. **24** may include structures and/or functions as similarly-named or similarly-numbered elements depicted in other drawings.

Insight information may be generated during at one or more phases of a dataset creation process, or subsequently. “Insight information” may refer, in some examples, to information that may automatically convey (e.g., visually in text and/or graphics) dataset attributes of a created dataset, including derived dataset attributes, during or after (e.g., shortly thereafter) the creation of the dataset. Insight infor-

mation presented in a user interface (e.g., responsive to dataset creation) may describe various aspects of a dataset, in summary form, such as, but not limited to, annotations (e.g., of columns, cells, or any portion of data), data classifications (e.g., a geographical location, such as a zip code, etc.), datatypes (e.g., a string data type, a numeric data type, a categorical data type, a Boolean data type, a derived classification data type, a date data type, a time data type, a geolocation data type, etc.), a number of data points, a number of columns, a “shape” or distribution of data and/or data values, a number of empty or non-empty cells in a data structure, a number of non-conforming data (e.g., a non-numeric data value in column expecting a numeric data, an image file, such as an image file embedded in a cell, etc., or some other erroneous or unexpected data) in cells of a data structure, a number of distinct values, etc. According to some embodiments, initiation of the dataset creation process invoked at a user input of user interface **2402** (not shown) may also perform statistical data analysis during or upon the creation of the dataset.

In view of the foregoing, algorithms (e.g., statistical algorithms or other analytic algorithms) may be applied against the dataset, during or subsequent to the creation of the dataset, to access insight information. A user need not download the data from a dataset to perform some sort of ad hoc data analysis (e.g., creating and running a Python script, or the like, against downloaded data to perform a statistical analysis) to identify characteristics of a distribution of data as well as visualization of the distribution. Therefore, insight information presented in user interface **2402** may provide (e.g., automatically) dataset attributes (and characteristics thereof) in a “snapshot view” so that data practitioners and users may readily determine whether a dataset may be of a quality or of a form that serves a desired purpose or objective. Further, user interface **2402** may automatically calculate and present dataset attributes of a “linked” dataset in which a link is established with, for example, an atomized dataset. In some examples, user interface **2402** may automatically convey dataset attributes, in summary form, for collaborative datasets that include links to protected (e.g., secured) atomized datasets that require authentication or permission to access in a collaborative dataset.

In the example shown, user interface **2402** is configured to present insight information for a dataset **2404**. User interface **2402** is configured to convey insight information for a subset of data arrangements in a data arrangement overview interface **2411**. In the example shown, data arrangement overview interface **2411** is configured to provide an overview (e.g., summary) or aggregation of, for instance, columnar data from a tabular data arrangement, such as an XLS file. As shown, each data arrangement, or column, of a set of data **2405**, which is depicted as file “Earthquakes M4_5 and higher (30 Day Interval).xls,” may be presented as a row in data arrangement overview interface **2411**, with each row depicting an aggregation (e.g., summarization) of data attributes and thereof values.

As shown, a number of columns are depicted in orthogonal data arrangements (e.g., as rows) wherein a column header (or annotation) is provided in column (“column name”) **2420**, which describes a dataset attribute of the data disposed therein. In this example, an index **2421**, or ranking, is depicted adjacent to text describing a column annotation. Indices **2421** for columns 1 (“time”) to 6 (“magType”) are shown in data arrangement overview interface **2411**. Note that in this example, data preview mode **2413** indicates that there are twenty-two (“22”) columns and 355 rows that may be summarized and viewed with, for example, the use of

scroll bar **2414**. Further, each column may include a datatype **2421** indicating a datatype for the column, a number **2422** (e.g., in percentage) of empty cells, and a number **2423** of distinct values for the columnar data, among many other types of data. In the example shown, a subset of column headers are disposed at **2420a**, **2420b**, **2420c**, **2420d**, **2420e**, and **2420f**, each having column headers (e.g., annotations) “time,” “latitude,” “longitude,” “depth,” magnitude (“mag”), and magnitude type (“magType”), respectively. Therefore, in this example, orthogonal arrangements of data associated with **2420a**, **2420b**, **2420c**, **2420d**, **2420e**, and **2420f** may be configured to display, respectively, aggregate or summary information regarding the “time” of an earthquake, the latitude and longitude of an earthquake, a depth at which an earthquake originates, a magnitude of the earthquake and a magnitude type of earthquake (e.g., “mb,” or measured body-wave magnitude), among other dataset attributes (some of which are not shown and viewable via **2414**).

Data arrangement overview interface **2411** also may include a column **2424** to present graphically a “shape” of the data for subsets of data ingested during uploading of file **2405**. The shape and presentation of the data may be presented as a histogram, a line graph, a percentage, a top number of categorical values, or in any other visualization graphical format to convey summary information, visually, based on values of a subset of the dataset attributes for a column. To illustrate, consider shape data **2424a** associated with a subset **2420a** of data that presents earthquake magnitude (“mag”) summary information. As shown, a histogram **2424a** depicts the frequencies of earthquake magnitude ranging from a minimum magnitude **2492** of 4.5 (on the Richter scale) to a maximum magnitude **2494** of 7.8, with predominant frequencies are shown nearer minimum magnitude **2492**. Also shown, top categories **2424b** depict the most common and next most common categories of earthquake magnitudes. As shown, the most common category **2493**, with 298 occurrences, is the “mb” category, which describes a number of occurrences in which an earthquake magnitude may be categorized as a measured body-wave magnitude. The next common category **2495**, with 26 occurrences, is the “mmw” category, which describes a moment magnitude derived from a centroid moment tensor inversion of a W-phase. The ‘mmw’ category may be a very long period phase (e.g., 100 seconds to 1000 seconds) that may be derived to provide rapid characterization of a seismic source for tsunami warning purposes.

According to some examples, one or more of subsets of column headers disposed at **2420a** (“time”), **2420b** (“latitude”), **2420c** (“longitude”), **2420d** (“depth”), **2420e** (magnitude, or “mag”), and **2420f** (magnitude type, or “magType”) may be derived. For example, any of the columns associated with **2420a** to **2420f** may include one or more derived dataset attributes and associated values. For example, one of subsets of column headers disposed at **2420a** to **2420f** may include “place” (e.g., name of a geographic location or city) derived from data in **2420b** (“latitude”) and **2420c** (“longitude”), as well as associated values (e.g., distances to nearest cities to earthquake epicenters). Another example of a derived column may be depicted in FIG. 13, among others. Any one of the column headers disposed at one of **2420a** to **2024f** may be derived, whereby the column header may be associated with an annotation, which may be automatically provided or by the user. An annotation may be derived based on inferred or derived dataset attributes, and, as such, a column header (or any metadata associated with a subset of data in a dataset),

may be derived or inferred, as described herein. Therefore, insight calculations and user interface elements presented in data arrangement overview interface **2411** may be based on a derived dataset attribute and/or associated values.

Data arrangement overview interface **2411** may be configured to function as an interactive display, whereby a display of graphically-displayed distributions **2424** of data, such as a histogram, may include user interface elements (e.g., control inputs or user inputs) that facilitate interaction with presented data, including some data representing derived or inferred dataset attributes. To illustrate, consider that a pointer element **2447b** may be configured to select or hover over a portion of the histogram associated with the maximum magnitude value. In response, data arrangement overview interface **2411** may present an overlay window (not shown) that provides additional information about earthquake magnitudes at 7.8 on the Richter scale (e.g., the overlay window may provide information as to geographic location, a time, an affected country or city, etc.).

Furthermore, data arrangement overview interface **2411** may include user interface elements **2443** and **2445** to provide enhanced control of at least a portion of a data creation process, as described herein. “Link” user input **2443** may be configured to initiate selection of another dataset with which to link to the present dataset **2404** to form a collaborative dataset. Consequently, logic of one or more of user interface element generator **2480**, a programmatic interface **2490**, and a collaborative dataset consolidation system **2410**, and a data derivation calculator **2465** may be configured to re-calculate insight information based on a combination of data from the other set of data linked to the set of data **2405** to derive updated dataset attributes and associated updated values (e.g., updated aggregated dataset attributes and associated updated values). In some examples, “Link” user input **2443** may be configured to link a protected atomized dataset to present dataset **2404**. Authorization data to access the protected atomized dataset may accompany control signals associated with user input **2443** to facilitate access to the protected atomized dataset to perform recalculations of the insight information. Thus, the values for the insight information may be recalculated and adapted to new versions of collaborative datasets during the linking (e.g., uploading) phase for presentation of an updated shape or distribution information for the combination of data that may be presented in column **2424**.

“Add files” user input **2445** may be activated via pointer element **2447a** to initiate adding (e.g., uploading) files to provide additional datasets or to correct data in set of data **2405**. Thus, a new version of a file **2405** may be uploaded to form a new version of dataset **2404**. For example, “depth” column insight information **2475** indicates that 5 of 355 rows (e.g., 1.4%) include “empty” data cells. A user may download the data file **2405** and address the empty data cells by correcting the data therein or adding appropriate data. Then, the revised file **2405** may be uploaded (e.g., via “add files” input **2445**) so as to initiate re-calculation of the insight information, whereby “depth” column insight information **2475** may be revised to include “zero” empty cells (not shown). The foregoing implementations of presenting insight information are examples and are not intended to be limiting, and there are many variations that fall within the scope of the present disclosure. In some examples, a pointer element **2447c** may be configured to select or hover over a portion **2489** of user interface **2402** to cause a transition to, or display of, a data overview **2511** of FIG. **25**. Portion **2489** may include hyperlinked text “Switch to data preview,” as an example.

FIG. **25** is an example of a user interface to present interactive user interface elements for another data preview of a dataset, according to some examples. Diagram **2500** depicts a user interface **2502** as an example of a computerized tool to provide access to a portion of the dataset to present a data view **2511** as a portion of a dataset. According to some examples, data view **2511** presents the data in a tabular format. Hence, logic (not shown) may be configured to upload and ingest, during a dataset creation process, a set of data **2505** formatted in, for example, a comma separated value, or “CSV,” format. The logic may be configured format the data for presentation via data view **2511** into a tabular format as depicted in diagram **2500**, with cells (e.g., intersections of a row and a column, other than column headers, indices, etc.) including specific values of data. As shown, subsets of dataset data are disposed in columns **2520** (“time”), **2522** (“latitude”), **2523** (“longitude”), **2524** (“depth”), **2525** (magnitude, or “mag”), and **2526** (magnitude type, or “magType”). Diagram **2400** of FIG. **24** is an example of summary information of the data presented in data view **2511**. “See all” text **2580** may be hyperlinked to cause, upon activation, presentation of rows 1-355 and columns 1-22, which is beyond that shown in data view **2511**. Further, user interface elements of user interface **2502** may include a user input **2589** (e.g., a link, or hyperlink) in association with text “Switch to column overview.” Activation of user input **2589** may cause the presentation of data preview **2511** to transition to user interface **2402** or data arrangement overview interface **2411** of FIG. **25**.

FIG. **26** is a diagram depicting a flow diagram to present interactive user interface elements for a data overview of a dataset, according to some embodiments. Flow **2600** may be an example of generating insight formation for a created dataset to present to a user interface based on a set of data. At **2602**, data to form an input as a user interface element may be received via a user interface. For example, a processor executing instruction data at a client computing device (or any other type of computing device, including a server computing device) may receive data to form a user interface element, which, upon activation, may initiate creation of an atomized dataset based on raw data in data file (e.g., a tabular data file, such as an XLS file, etc.). At **2604**, which is optional, a programmatic interface may be activated to facilitate the creation of (or updating or modifying) a dataset responsive to receiving the first input, according to some examples. Insight information may be calculated during a phase, such as during a “Gathering Insights” **1024** phase of FIG. **10**. Referring back to FIG. **26**, a programmatic interface at **2604** may be implemented as either hardware or software, or a combination thereof. The programmatic interface also may be disposed at a client computing device or a server computing device, which may be associated with a collaborative dataset consolidation system, or may be distributed over any number of computing devices whether networked together or otherwise. In some examples, the programmatic interface may be distributed as subsets of executable code (e.g., as scripts, etc.) to implement APIs in any number of computing devices. In some embodiments, programmatic interface may be optional and may be omitted.

At **2606**, data may be received, for example, at a processor, and the data may be a result of insight calculations. Further, the resultant data may describe a portion of insight information regarding dataset attributes of the dataset. In some examples, the insight information may be computed based on, for example, a derived or inferred dataset attribute and/or associated values. At **2608**, a set of data (e.g., a CSV

file) may be transformed during an ingestion process into a particular format, such as into an atomized datasets. At **2610**, a data arrangement overview interface summarizing the data attributes as an aggregation of data attributes in a portion of a user interface. Examples are depicted in FIGS. **24** and **25**, among other drawings. The data arrangement overview interface may include an interactive display of a distribution of a subset of values for a data arrangement associated with a collaborative atomized dataset. In some examples, an interactive display and/or a nested overlay window may include an overlay interface (e.g., including a tool tip) in which summary insight information may be presented responsive to interactions with the user interface.

FIG. **27** is an example of a user interface to present interactive user interface elements for conveying summary characteristics of a dataset, according to some examples. Diagram **2700** depicts a user interface **2702** as an example of a computerized tool to provide access to various levels of detail for summarized data, information and aspects of a dataset (e.g., an atomized dataset). In the example shown, user interface includes a data arrangement overview interface **2711**, which, may, in at least some cases, have structures and/or functionalities similar or equivalent to data arrangement overview interfaces described herein. According to some examples, elements depicted in diagram **2700** of FIG. **27** may include structures and/or functions as similarly-named or similarly-numbered elements depicted in other drawings.

Logic of one or more of a user interface element generator, a programmatic interface, a collaborative dataset consolidation system, and a data derivation calculator, none of which are shown, may be configured to facilitate interactivity of data arrangement overview interface **2711** with a pointer element, including a finger (e.g., for touch-sensitive screens), such as pointer element **2747**. In some examples, logic disposed in a collaborative dataset consolidation system or at a client computing device, or both, may be configured to determine summary characteristics (e.g., statistical characteristics) as dataset attributes of a collaborative dataset. For instance, the logic can be configured to calculate summary characteristics, such as a mean of the dataset distribution, a minimum value, maximum value, a value of standard deviation, a value of skewness, a value of kurtosis, etc., among any type of statistic or characteristic. Summary characteristics and graphical representations of data distributions may be referred to as dataset attributes, according to some examples.

Pointer element **2747** may select or hover over a user interface element, such as user input **2730**. In response, the logic may cause activation of interactive overlay window **2750**. User input (“latitude”) **2730** may be text (or an area thereof) that when selected may activate a subset of the executable code to cause generation of interactive overlay window **2750**. As shown, user input **2730** may be associated with the text “latitude,” which may be a hypertext link or another type of control input for invoking interactive overlay window **2750**. Further, interactive overlay window **2750** may be configured to present data representing summary characteristic data for subsets of data, such as columns of data. As shown, user input (“latitude”) **2730** is associated with a subset of dataset data that relates to a column of latitude data in, for example, a tabular representation of dataset **2704**, which may be an atomized dataset. As pointer element **2747** selects or hovers over user input **2730**, a subset of data relating to “latitude” is identified, interactive overlay window **2750** is activated, thereby presenting summary characteristics for the subset of data, which is shown

to directed to column 2 (“col 2”) having annotation (“latitude”) **2751**. Annotation **2751** may be derived from a column header.

Interactive overlay window **2750** may be configured to present an annotation **2751**, a datatype (“numeric”) **2752** for the subset of data, a graphical representation of a data distribution **2790** (e.g., a histogram), and aggregated data attributes **2755** including summary characteristics. In this example, a column of latitude data may have the following summary characteristics: distinct number of latitude values (“354”) **2760**, a number of non-empty data fields or cells (“355”) **2761**, a number of empty data fields or cells (“0(0%)”) **2762**, a mean of value of the latitude coordinates (“2.146”) **2763**, a minimum value of the latitude coordinates (“-63.586”) **2764**, a maximum value of the latitude coordinates (“85.597”) **2765**, a standard deviation (“32.086”) **2766**, a value of skewness (“0.053”) **2767**, a value of kurtosis (“-0.872”) **2768**, among other statistical characteristics or any other summary characteristics.

According to some embodiments, interactive overlay window **2750** may include user interface elements, as user inputs, to further perform data operations interactively with interactive overlay window **2750** to determine yet another level of details. For example, interactive overlay window **2750** may include an interface to enter text or other symbols into the interface. As shown, interface **2770** is configured to receive user input to recalculate the above-described summary characteristics and graphical representation **2790** based on adding or omitting datasets (or portions thereof). User input **2771** may be activated to add a particular dataset (e.g., add dataset “X”), whereas user input **2773** may be activated to remove a dataset (e.g., remove dataset “Z”).

As another example, interactive overlay window **2750** may include one or more user interface elements to cause presentation of a nested overlay window **2792**. Pointer element **2747** may transition to another position on user interface **2702**, such as to a position depicted as pointer element **2748**. At this position, pointer element **2748** may be configured to cause identification (e.g., through selection or hovering over) of a bar **2753** of graphical representation **2790**, which is shown as a histogram. Responsive to pointer element **2748**, nested overlay window **2792** may be generated to present relevant values of dataset attributes, such as a total number latitude data points (e.g., 22 latitude coordinates) and a range of latitude values (e.g., from 38.356 to 40.842) associated with bar **2753**. As shown, histogram **2790** has a number of bars representing a frequency in which a latitude data value falls within a particular range of latitude data values. The above-described examples are not intended to be limiting, and an interactive overlay window and/or a nested overlay window may include any type of data and/or control inputs (as user inputs). And in view of the foregoing, a user need not download a dataset to perform ad hoc data analysis, such as creating and running a Python script at a client computing device against downloaded data to determine applicability. Therefore, such information may be presented via interactive overlay window **2750**.

FIG. **28** is a diagram depicting a flow diagram to present summary characteristics for a dataset in an interactive overlay window, according to some embodiments. At **2802**, data representing summary characteristic data for subsets of data may be presented in a user interface. A summary characteristic may be a statistic or any other data characteristic or dataset attribute, whereby a subset of data may refer to a column of data in some examples. At **2804**, a user interface element may be selected. An example of the user interface element may be a user input configured to activate presen-

tation of an interactive overlay window. At **2806**, a subset of executable code may be activated, responsive to identification or selection of the user input. When executed, the code causes presentation of an interactive overlay window to convey interactive summary characteristics for a column of data. At **2808**, an interactive overlay window may be configured to include aggregated data attributes (e.g., an aggregation or collection of summary characteristics) for a column of data associated with, for example, an atomized dataset.

FIG. **29** is a diagram depicting an example in which a subset of data may be analyzed to determine a graphical representation of the data distribution, according to some examples. Diagram **2900** depicts a user interface **2902** coupled communicatively to logic embodied in one or more portions of a collaborative dataset consolidation system **2910**, which is shown to include a data derivation calculator **2965** and an inference engine **2908**, a user interface element generator **2980** and a programmatic interface **2990**. According to some examples, elements depicted in diagram **2900** of FIG. **29** may include structures and/or functions as similarly-named or similarly-numbered elements depicted in other drawings.

The logic is configured to acquire data representing annotations **2920** for subsets of data (e.g., column headings), datatypes **2922**, a number of empty cells **2924**, a number of distinct data values **2926**, and any number of other dataset attribute values. According to various embodiments, the logic may be configured to determine (e.g., automatically) a suitable graphical format with which to present summary view data in graphical representations **2928**. In some examples, the graphical format may be selected as a function of a shape of the data and, for example, shape attributes. Further, the graphical format may be selected as a function of one or more inferred dataset attributes (e.g., annotation “Place” in annotations column **2920** may be derived or inferred from other data). Therefore, logic may be configured to present insight data in a tabular format having a graphical representation of the data distribution being optimized based on inferred the dataset attributes and shape attributes.

For graphical representations **2928**, the logic may be configured to determine time-based bar graph **2972** based on, for example, a datatype (e.g., “date”), distinct values **2926** (e.g., “12” distinct values associated with time-related data, such as, per month), an annotation **2920**, as well as shape attributes. Shape attributes include characteristics that describe the amount, quality, and spread of a distribution due to various data values. Examples of shape attributes include symmetry, a number of peaks (e.g., unimodal or bell-shaped, bimodal, etc.), a degree of uniformity (e.g., measure of equal spreading of data), a degree of skewness (e.g., skewed left, skewed right, etc.), etc. Shape attributes may also refer to one or more summary characteristics, such as standard deviation, skewness, kurtosis, etc. The logic may be configured to determine categorical description **2974** based on datatype and a number of categories, as well as other dataset attributes. For example, a “most common” category may be associated with a greatest number of occurrences, whereby “suicide” has a greatest number of occurrences, followed by “homicide,” which is the next common category. Further, logic may be configured to present two (2) values (and percentages thereof) as a graphical representation **2976** for Boolean datatypes, and based on other dataset attributes. Graphical representation **2978** may be presented as a histogram based on, for example, a number of occurrences, a datatype, a spread of data (e.g., standard deviation and

ranges of values), and other data attributes. User interface **2902** may also include user inputs **2971** and **2973** to cause any of graphical representations **2928** to be accepted (as presented), or to be recalculated for presentation into a different graphical representation (e.g., a bar chart may be presented as a pie chart, etc.).

FIGS. **30A** to **30F** are diagrams depicting examples of interactive overlay windows, according to some examples. Interactive overlay windows **3000** and **3015** of FIGS. **30A** and **30B**, respectively, depict summary characteristics (e.g., values of dataset attributes) and graphical representations for subsets of data. For example, interactive overlay window **3000** includes an annotative description **3003** for a subset of data (e.g., column 3, denoted “col 03”), a datatype **3004**, and graphical representations **3006** (e.g., as text) of the different categories and number of occurrences. Additionally, a horizontal bar chart **3008** may also be generated as part of graphical representations **3000**. In some examples, logic may determine a distinct number of categories (e.g., four) and may generate graphical representations **3006** based on a threshold number of categories **3001** (e.g., less than five category types). In particular, with less than five categories, the format of graphical representations **3006** may be implemented.

By contrast, interactive overlay window **3015** includes an annotative description **3021** for a subset of data (e.g., column 7, denoted “col 07”), a datatype **3019**, and graphical representation **3020** (e.g., as text) of the different categories and graphical representation **3022** for more the “five categories.” In some examples, logic may determine a distinct number of categories (e.g., 36) and may generate graphical representation **3020**, as a textual description of top two categories, and **3022**, as a histogram, based on a threshold number **3018** of categories (e.g., greater than five category types).

In FIG. **30C**, interactive overlay window **3000** includes an annotative description (“Police”) **3033** for a subset of data (e.g., column 4, denoted “col 04”), a datatype (“Boolean”) **3034**, and graphical representations **3036** (e.g., as text) of one of two states or characteristics, such as “true” or “false” of the two different categories and percentages of occurrences. Additionally, a horizontal bar chart **3038** may also be generated as part of graphical representation **3036**. In some examples, graphical representations **3036** for Boolean datatypes may include a third category, such as “null” to provide information on, for example, one occurrence of defective or absent data.

FIG. **30D** depicts an example of an interactive overlay window **3045** including an annotative description (“Month”) **3048** for a subset of data (e.g., column 2, denoted “col 02”), a datatype (“date”) **3049**, and a graphical representation **3051** as a bar chart depicting occurrences per month.

FIG. **30E** depicts an example of an interactive overlay window **3060** including an annotative description (“Location”) **3063** for a subset of data (e.g., column 10, denoted “col 10”), a datatype (“zip code”) **3062**, and a graphical representation **3066**. In this example, graphical representation **3066** may include a map of, for example, a geographic location or region spanning multiple zip codes, whereby the map may include graphical representations **3068** of occurrences (e.g., as a function of pixel color values, or varied shades of “gray” using greyscale values) at certain locations (e.g., within a zip code). Thus, “heat maps” **3068** may be implemented to present variable densities of occurrences of “suicides” and “homicides” relative to a location (e.g., a zip code). Other graphical representations including maps are also within the scope of the present disclosure.

FIG. 30F depicts an example of an interactive overlay window 3075 including an annotative description (“Place”) 3077 for a subset of data (e.g., column 8, denoted “col 08”), a datatype (“string”) 3077, and descriptive text implemented as a graphical representation 3081.

FIG. 31 is a diagram depicting a flow diagram to form various interactive overlay windows, according to some embodiments. At 3102, data to form a first input via a user interface may be received as a first user interface element. Activation of the user interface element, such as a user input, may be configured to ingest as set of data to initiate creation of an atomized dataset. A programmatic interface may be activated at 3104 to facilitate creation of a dataset, which may include the derivation of a dataset attribute that may be used in dataset creation. At 3106, a request to generate the dataset having a first format may be transmitted to a server computing system implementing a collaborative dataset consolidation system. The computing system may operate to interpret a subset of data (e.g., a column) of the set of data (e.g., a number of columns) against one or more data classifications at an inference engine to derive an inferred dataset attribute for the subset of data.

In some examples, interpreting a subset of data may include identifying a data type for an inferred dataset attribute, determining shape attributes to form the a graphical representation of a distribution, and selecting a first graphical format based on, for example, a datatype. An example of the first graphical format may be a histogram. Interpreting the subset of data, at least in some cases, may include identifying a data type for an inferred dataset attribute as a numeric data type, forming a histogram user interface element as a distribution (e.g., a graphical representation) for presentation as summary view (e.g., within an interactive overlay window) in a first graphical format based on the numeric data type. Further, interpreting the subset of data may include causing presentation of a histogram user interface element in a user interface.

Interpreting the subset of data may include identifying a data type (for the inferred dataset attribute) as a categorical datatype, according to some examples. The categorical datatype may be associated with a value for data points (e.g., a value representing a number of categories) within a threshold amount (e.g., a threshold number of categories) under which a graphical representation (e.g., histogram) may be implemented. In some examples, interpreting the subset of data may also include forming one or more textual user interface elements as a distribution for presentation in a summary view in a text-based descriptive format based on the categorical datatype and number of categories. Therefore, textual user interface elements may be presented in the user interface, whereby the textual user interface elements may specify one or more categories having greatest values.

By contrast, identifying the datatype as a categorical datatype may further include determining the value of the data points exceeds a threshold amount (e.g., more than 5 distinct categories may trigger a change in format of a graphical representation). That is, when a number of distinct values for the data points exceed a threshold amount, another graphical representation may be implemented. Further, a histogram user interface element may be formed as a distribution for presentation as a summary view based on the categorical data type. The histogram user interface element may be presented in the user interface, whereby the histogram user interface element specifies a distribution of a number of categories.

At 3108, data representing a distribution in a first graphical format may be received for a subset of data. The first

graphical format may convey visually a shape of the data. In some cases, a second input may be implemented to recalculate a second graphical format with which to present the shape of the data for the distribution. Subsequent to activation, the distribution may be presented using the second graphical format. At 3110, data representing a distribution in a summary view may be presented at a user interface for the subset of data. The distribution may be a summary representation that represents a shape of values for one or more dataset attributes associated with an inferred dataset attribute.

FIG. 32 is a diagram depicting an example of a dataset access interface, according to some examples. Diagram 3200 depicts a user interface 3202 coupled communicatively to logic embodied in one or more portions of a collaborative dataset consolidation system 3210, which is shown to include a query engine 3230 and an operations transformation engine 3240, a user interface element generator 3280 and a programmatic interface 3290. According to some examples, elements depicted in diagram 3200 of FIG. 32 may include structures and/or functions as similarly-named or similarly-numbered elements depicted in other drawings.

In this example, user interface 3202 may be implemented as a computerized tool that may be configured to access or otherwise query a collaborative database through a data entry interface 3204. According to some examples, data entry interface 124 may be configured to accept commands (e.g., queries) in high-level language (e.g., high-level programming languages, including object-oriented languages), such as in Python™ and structured query language (“SQL”), as well as dwSQL (i.e., as dialect of SQL developed by Data.world™), among others. Further, commands in a high-level language may be converted into a graph-level access or query language, such as SPARQL, other RDF query languages, or the like. Thus, a query may be initiated via data entry interface 3204 to query data associated with an atomized dataset, including linked collaborative atomized datasets. In some examples, data entry interface 3204 may be configured to accept programming languages for facilitating other data operations, such as statistical and data analysis. Examples of programming languages to perform statistical and data analysis include “R,” among others.

Further to diagram 3200, operations transformation engine 3240 may include a “SQL-to-SPARQL” processing engine 3242, which may be configured to transform SQL-based commands into SPARQL or other RDF query languages. Operations transformation engine 3240 may include an “R-to-RDF” processing engine 3244, which may be configured to transform statistics-based commands (e.g., R) into RDF or other graph-level languages. Further, operations transformation engine 3240 may include a “Python-to-RDF” processing engine 3246, which may be configured to transform Python-based commands into RDF or RDF query languages. Note that other transformations between high-level programming languages and graph-level languages are possible.

In view of the foregoing, a user need not rely on graph-level languages, such as SPARQL, but may implement high-level programming languages that may be more familiar with users and data practitioners. In some examples, an overlay window 3220 (or any other user interface element) may be presented concurrently (or substantially concurrently) with the presentation of data entry interface 3204. Thus, as a query 3272 may be entered in a high-level programming language, a low-level version (e.g., in SPARQL) may be presented in interface 3274 in a mirrored fashion. This is, interface 3274 may be referred to as a

61

“mirrored data entry interface” in user interface **3302**. Mirrored data entry interface **3274** may be configured to detect entry of an operation instruction in data entry interface **3272** and replicate a transformed operation instruction in mirrored data entry **3274** as a graph-related data instruction (e.g., in real-time). Thus, users that are less familiar with low-level languages may begin to learn or adapt queries from entry and the high-level programming language to, for example, SPARQL or the like. By contrast, users that may be familiar with both high- and low-level programs may wish to validate an appropriately crafted query by reviewing interface **3274** while the query is entered via data entry interface **3204**.

FIG. **33** is a diagram depicting a flow diagram to implement a dataset access interface, according to some embodiments. At **3302**, data may be received to form a first input via a user interface as a first user interface element. The first user interface element may be configured to initiate a data operation on an atomized dataset based on a set of data. Examples of a data operation include dataset accesses, dataset queries, statistical operations on a dataset, etc. At **3304**, a data signal indicating selection of the data operation may be received (e.g., initiate “run query”). A programmatic interface may be activated at **3306** to perform a selected data operation responsive to the data signal. At **3308**, a data entry interface may be presented in the user interface to receive operation data instructions. The operation data instructions may transform the data instructions into graph-related data instructions, at **3310**, to access data associated with an atomized dataset stored in, for example, a triplestore repository. At **3312**, graph-related data instructions may be implemented to perform the operation (e.g., at a low-level). At **3314**, data representing results (e.g., query results) may be received responsive to executing the graph-related data instructions.

FIG. **34** illustrates examples of various computing platforms configured to provide various functionalities to components of a collaborative dataset consolidation system, according to various embodiments. In some examples, computing platform **3400** may be used to implement computer programs, applications, methods, processes, algorithms, or other software, as well as any hardware implementation thereof, to perform the above-described techniques.

In some cases, computing platform **3400** or any portion (e.g., any structural or functional portion) can be disposed in any device, such as a computing device **3490a**, mobile computing device **3490b**, and/or a processing circuit in association with initiating the formation of collaborative datasets, as well as analyzing and presenting summary characteristics for the datasets, via user interfaces and user interface elements, according to various examples described herein.

Computing platform **3400** includes a bus **3402** or other communication mechanism for communicating information, which interconnects subsystems and devices, such as processor **3404**, system memory **3406** (e.g., RAM, etc.), storage device **3408** (e.g., ROM, etc.), an in-memory cache (which may be implemented in RAM **3406** or other portions of computing platform **3400**), a communication interface **3413** (e.g., an Ethernet or wireless controller, a Bluetooth controller, NFC logic, etc.) to facilitate communications via a port on communication link **3421** to communicate, for example, with a computing device, including mobile computing and/or communication devices with processors, including database devices (e.g., storage devices configured to store atomized datasets, including, but not limited to triplestores, etc.). Processor **3404** can be implemented as

62

one or more graphics processing units (“GPUs”), as one or more central processing units (“CPUs”), such as those manufactured by Intel® Corporation, or as one or more virtual processors, as well as any combination of CPUs and virtual processors. Computing platform **3400** exchanges data representing inputs and outputs via input-and-output devices **3401**, including, but not limited to, keyboards, mice, audio inputs (e.g., speech-to-text driven devices), user interfaces, displays, monitors, cursors, touch-sensitive displays, LCD or LED displays, and other I/O-related devices.

Note that in some examples, input-and-output devices **3401** may be implemented as, or otherwise substituted with, a user interface in a computing device associated with a user account identifier in accordance with the various examples described herein.

According to some examples, computing platform **3400** performs specific operations by processor **3404** executing one or more sequences of one or more instructions stored in system memory **3406**, and computing platform **3400** can be implemented in a client-server arrangement, peer-to-peer arrangement, or as any mobile computing device, including smart phones and the like. Such instructions or data may be read into system memory **3406** from another computer readable medium, such as storage device **3408**. In some examples, hard-wired circuitry may be used in place of or in combination with software instructions for implementation. Instructions may be embedded in software or firmware. The term “computer readable medium” refers to any tangible medium that participates in providing instructions to processor **3404** for execution. Such a medium may take many forms, including but not limited to, non-volatile media and volatile media. Non-volatile media includes, for example, optical or magnetic disks and the like. Volatile media includes dynamic memory, such as system memory **3406**.

Known forms of computer readable media includes, for example, floppy disk, flexible disk, hard disk, magnetic tape, any other magnetic medium, CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, RAM, PROM, EPROM, FLASH-EPROM, any other memory chip or cartridge, or any other medium from which a computer can access data. Instructions may further be transmitted or received using a transmission medium. The term “transmission medium” may include any tangible or intangible medium that is capable of storing, encoding or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible medium to facilitate communication of such instructions. Transmission media includes coaxial cables, copper wire, and fiber optics, including wires that comprise bus **3402** for transmitting a computer data signal.

In some examples, execution of the sequences of instructions may be performed by computing platform **3400**. According to some examples, computing platform **3400** can be coupled by communication link **3421** (e.g., a wired network, such as LAN, PSTN, or any wireless network, including WiFi of various standards and protocols, Bluetooth®, NFC, Zig-Bee, etc.) to any other processor to perform the sequence of instructions in coordination with (or asynchronous to) one another. Computing platform **3400** may transmit and receive messages, data, and instructions, including program code (e.g., application code) through communication link **3421** and communication interface **3413**. Received program code may be executed by processor **3404** as it is received, and/or stored in memory **3406** or other non-volatile storage for later execution.

In the example shown, system memory **3406** can include various modules that include executable instructions to implement functionalities described herein. System memory **3406** may include an operating system (“O/S”) **3432**, as well as an application **3436** and/or logic module(s) **3459**. In the example shown in FIG. **34**, system memory **3406** may include any number of modules **3459**, any of which, or one or more portions of which, can be configured to facilitate any one or more components of a computing system (e.g., a client computing system, a server computing system, etc.) by implementing one or more functions described herein.

The structures and/or functions of any of the above-described features can be implemented in software, hardware, firmware, circuitry, or a combination thereof. Note that the structures and constituent elements above, as well as their functionality, may be aggregated with one or more other structures or elements. Alternatively, the elements and their functionality may be subdivided into constituent sub-elements, if any. As software, the above-described techniques may be implemented using various types of programming or formatting languages, frameworks, syntax, applications, protocols, objects, or techniques. As hardware and/or firmware, the above-described techniques may be implemented using various types of programming or integrated circuit design languages, including hardware description languages, such as any register transfer language (“RTL”) configured to design field-programmable gate arrays (“FPGAs”), application-specific integrated circuits (“ASICs”), or any other type of integrated circuit. According to some embodiments, the term “module” can refer, for example, to an algorithm or a portion thereof, and/or logic implemented in either hardware circuitry or software, or a combination thereof. These can be varied and are not limited to the examples or descriptions provided.

In some embodiments, modules **3459** of FIG. **34**, or one or more of their components, or any process or device described herein, can be in communication (e.g., wired or wirelessly) with a mobile device, such as a mobile phone or computing device, or can be disposed therein.

In some cases, a mobile device, or any networked computing device (not shown) in communication with one or more modules **3459** or one or more of its/their components (or any process or device described herein), can provide at least some of the structures and/or functions of any of the features described herein. As depicted in the above-described figures, the structures and/or functions of any of the above-described features can be implemented in software, hardware, firmware, circuitry, or any combination thereof. Note that the structures and constituent elements above, as well as their functionality, may be aggregated or combined with one or more other structures or elements. Alternatively, the elements and their functionality may be subdivided into constituent sub-elements, if any. As software, at least some of the above-described techniques may be implemented using various types of programming or formatting languages, frameworks, syntax, applications, protocols, objects, or techniques. For example, at least one of the elements depicted in any of the figures can represent one or more algorithms. Or, at least one of the elements can represent a portion of logic including a portion of hardware configured to provide constituent structures and/or functionalities.

For example, modules **3459** or one or more of its/their components, or any process or device described herein, can be implemented in one or more computing devices (i.e., any mobile computing device, such as a wearable device, such as a hat or headband, or mobile phone, whether worn or

carried) that include one or more processors configured to execute one or more algorithms in memory. Thus, at least some of the elements in the above-described figures can represent one or more algorithms. Or, at least one of the elements can represent a portion of logic including a portion of hardware configured to provide constituent structures and/or functionalities. These can be varied and are not limited to the examples or descriptions provided.

As hardware and/or firmware, the above-described structures and techniques can be implemented using various types of programming or integrated circuit design languages, including hardware description languages, such as any register transfer language (“RTL”) configured to design field-programmable gate arrays (“FPGAs”), application-specific integrated circuits (“ASICs”), multi-chip modules, or any other type of integrated circuit.

For example, modules **3459** or one or more of its/their components, or any process or device described herein, can be implemented in one or more computing devices that include one or more circuits. Thus, at least one of the elements in the above-described figures can represent one or more components of hardware. Or, at least one of the elements can represent a portion of logic including a portion of a circuit configured to provide constituent structures and/or functionalities.

According to some embodiments, the term “circuit” can refer, for example, to any system including a number of components through which current flows to perform one or more functions, the components including discrete and complex components. Examples of discrete components include transistors, resistors, capacitors, inductors, diodes, and the like, and examples of complex components include memory, processors, analog circuits, digital circuits, and the like, including field-programmable gate arrays (“FPGAs”), application-specific integrated circuits (“ASICs”). Therefore, a circuit can include a system of electronic components and logic components (e.g., logic configured to execute instructions, such that a group of executable instructions of an algorithm, for example, and, thus, is a component of a circuit). According to some embodiments, the term “module” can refer, for example, to an algorithm or a portion thereof, and/or logic implemented in either hardware circuitry or software, or a combination thereof (i.e., a module can be implemented as a circuit). In some embodiments, algorithms and/or the memory in which the algorithms are stored are “components” of a circuit. Thus, the term “circuit” can also refer, for example, to a system of components, including algorithms. These can be varied and are not limited to the examples or descriptions provided.

Although the foregoing examples have been described in some detail for purposes of clarity of understanding, the above-described inventive techniques are not limited to the details provided. There are many alternative ways of implementing the above-described invention techniques. The disclosed examples are illustrative and not restrictive.

The invention claimed is:

1. A method comprising:

- presenting data representing summary characteristic data for subsets of data in a user interface, each subset of data being presented to include user interface elements each specifying a value of a dataset attribute for a collaborative dataset including linked atomized datasets;
- determining selection of a first user interface element of the user interface to identify a subset of data to form an identified subset of data from the collaborative dataset;

65

activating a subset of executable code to present in a portion of the user interface an interactive overlay window as a second interface element responsive to identifying the identified subset of the collaborative dataset,

presenting the interactive overlay window to include aggregated data attributes for the subset of the collaborative dataset associated with the linked atomized datasets;

determining selection of a third user interface element of the interactive overlay window to identify a graphical representation of a range of values in a distribution of a plurality of ranges of values for a column of data in a data file for the collaborative dataset;

activating another subset of executable code to present in a portion of the interactive overlay window a nested overlay window as a fourth interface element responsive to identifying the graphical representation of the range of values;

presenting the nested overlay window to include one or more values of dataset attributes for the range of values;

receiving a data signal indicating to either add a linked atomized dataset or omit the linked atomized dataset in generating the aggregated data attributes;

identifying that either the linked atomized data set is either added or omitted;

transmitting an instruction via a programmatic interface to recalculate values of the aggregated data attributes based on adding or omitting the linked atomized data set; and

receiving recalculated values of the aggregated data attributes.

2. The method of claim 1 wherein presenting the data representing the summary characteristic data for the subsets of data comprises:

presenting data that represents the summary characteristic data for columns of data, each column of data including a corresponding subset of data.

3. The method of claim 1 wherein the identified subset of the collaborative dataset comprises:

a column of data in a data file for the collaborative dataset.

4. The method of claim 1 further comprising specifying a quality of the dataset attribute including

presenting data that represents one or more values of the dataset attribute.

5. The method of claim 4 wherein presenting the data that represents the value of the dataset attribute comprises:

presenting as the one or more values as data representing one or more of a string, a number, and a range of values displayed as a graphical representation of a distribution.

6. The method of claim 1 further comprising:

presenting the distribution of the plurality of ranges of values in a histogram data format.

7. The method of claim 1 further comprising:

presenting a number of data points associated with the values in the range of values.

8. The method of claim 1 wherein presenting the interactive overlay window to include the aggregated data attributes further comprises:

identifying a column of data associated with the identified subset of the collaborative dataset; and

presenting a number of distinct data points associated with distinct values of a value of the dataset attribute for the column of data.

66

9. The method of claim 1 wherein presenting the interactive overlay window to include the aggregated data attributes further comprises:

identifying a column of data associated with the identified subset of the collaborative dataset; and

presenting a number of data points associated with non-empty data cells in the column of data; and

presenting another number of data points associated with null values for data in the column of data, wherein a null value represents an empty data cell.

10. The method of claim 1 wherein presenting the interactive overlay window to include the aggregated data attributes further comprises:

identifying a column of data associated with the identified subset of the collaborative dataset; and

presenting values of one or more of a mean value, maximum value, a minimum value and a standard deviation value for the values of the dataset attribute for the column of data.

11. The method of claim 1 wherein presenting the interactive overlay window to include the aggregated data attributes further comprises:

identifying a column of data associated with the identified subset of the collaborative dataset; and

presenting values of a skewness value and a kurtosis value for the values of the dataset attribute for the column of data.

12. The method of claim 1 wherein presenting the interactive overlay window to include the aggregated data attributes further comprises:

identifying a column of data associated with the identified subset of the collaborative dataset; and

presenting values of a textual representation of an annotation for the column of data.

13. The method of claim 1 wherein presenting the interactive overlay window to include the aggregated data attributes further comprises:

identifying a column of data associated with the identified subset of the collaborative dataset; and

presenting values of a textual representation of a data type for the column of data.

14. The method of claim 1 wherein determining the selection of the first user interface element comprises:

detecting selection via a pointer device as a user interface element.

15. The method of claim 1 wherein the atomized dataset and another dataset include subsets of linked data points.

16. The method of claim 15 wherein the linked data points comprise triples.

17. The method of claim 16 wherein at least one triple of the triples are formatted to comply with a Resource Description Framework (“RDF”) data model.

18. An apparatus comprising:

a memory including executable instructions; and

a processor, responsive to executing the instructions, is configured to:

present data representing summary characteristic data for subsets of data in a user interface, each subset of data being presented to include user interface elements each specifying a value of a dataset attribute for a collaborative dataset including linked atomized datasets;

determine selection of a first user interface element of the user interface to identify a subset of data to form an identified subset of data from the collaborative dataset;

67

activate a subset of executable code to present in a portion of the user interface an interactive overlay window as a second interface element responsive to identifying the identified subset of the collaborative dataset; and 5

present the interactive overlay window to include aggregated data attributes for the subset of the collaborative dataset associated with the linked atomized datasets; 10

determine selection of a third user interface element of the interactive overlay window to identify a graphical representation of a range of values in a distribution of a plurality of ranges of values for a column of data in a data file for the collaborative dataset; 15

activate another subset of executable code to present in a portion of the interactive overlay window a nested

68

overlay window as a fourth interface element responsive to identifying the graphical representation of the range of values;

present the nested overlay window to include one or more values of dataset attributes for the range of values;

receive a data signal indicating to either add a linked atomized dataset or omit the linked atomized dataset in generating the aggregated data attributes;

identify that either the linked atomized data set is either added or omitted;

transmit an instruction via a programmatic interface to recalculate values of the aggregated data attributes based on adding or omitting the linked atomized data set; and

receive recalculated values of the aggregated data attributes.

* * * * *