

US010695190B2

(12) **United States Patent**
Liu et al.

(10) **Patent No.:** **US 10,695,190 B2**
(45) **Date of Patent:** **Jun. 30, 2020**

- (54) **BONE EXPANDABLE DEVICE**
- (71) Applicant: **I-Shou University**, Kaohsiung (TW)
- (72) Inventors: **Pao-Hsin Liu**, Kaohsiung (TW);
Shih-Hsuan Shen, Kaohsiung (TW)
- (73) Assignee: **I-SHOU UNIVERSITY**, Kaohsiung (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 151 days.

(21) Appl. No.: **15/954,022**

(22) Filed: **Apr. 16, 2018**

(65) **Prior Publication Data**
US 2018/0311047 A1 Nov. 1, 2018

(30) **Foreign Application Priority Data**
Apr. 26, 2017 (TW) 106113985 A

(51) **Int. Cl.**
A61F 2/44 (2006.01)
A61F 2/46 (2006.01)
A61F 2/30 (2006.01)

(52) **U.S. Cl.**
CPC **A61F 2/4425** (2013.01); **A61F 2/4601** (2013.01); **A61F 2002/30148** (2013.01); **A61F 2002/30471** (2013.01); **A61F 2002/443** (2013.01)

(58) **Field of Classification Search**
CPC **A61F 2/4425**; **A61F 2/443**; **A61F 2/4601**; **A61F 2002/30148**; **A61F 2002/30471**; **A61F 2002/443**; **A61B 17/8858**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,176,882	B1	1/2001	Biedermann et al.
8,012,207	B2	9/2011	Kim
2007/0225807	A1	9/2007	Phan et al.
2011/0319997	A1	12/2011	Glerum et al.
2014/0257484	A1	9/2014	Flower et al.

FOREIGN PATENT DOCUMENTS

CN	104665961	A	6/2015	
CN	204683847	U	10/2015	
WO	WO-2018200507	A1	* 11/2018 A61F 2/4455

* cited by examiner


Primary Examiner — Eric S Gibson

(74) *Attorney, Agent, or Firm* — Muncy, Geissler, Olds & Lowe, P.C.

(57) **ABSTRACT**

A bone expandable device comprises two expanding members, a retractable member and a fastener. The two expanding members are joined together for forming a cavity therebetween, each the expanding member includes two flexible parts and a fixed part. The two flexible parts are connected to the fixed part separately, and each the flexible part can be bent from the fixed part. The retractable member is disposed in the cavity and includes a first part and a second part. The first part is movably sleeved on the second part, and a length of the retractable member can be adjusted by moving the first part or the second part. The fastener is for fastening the two expanding members together. When the length of the retractable member is increasing, the two opposite ends of the retractable member would push against the four flexible parts to expand the flexible parts outwardly from the cavity.

10 Claims, 11 Drawing Sheets






Fig.1A




Fig.1B




Fig.2A




Fig.3A




Fig.3B




Fig.4A




Fig. 4B




Fig. 5




Fig.6




Fig.7

BONE EXPANDABLE DEVICE

RELATED APPLICATIONS

The present application claims the priority of Taiwan Application No. 106113985, filed Apr. 26, 2017.

FIELD OF THE DISCLOSURE

The present invention relates to a bone expandable device, and more particularly to a bone expandable device for expanding the collapsed bones.

BACKGROUND

Osteoporosis usually causes bones collapse, such as the compressive fracture of spine, and the patients with this disease are becoming more and more in recent years. Though the surgeries and the medical instruments nowadays are improved considerably, there are still a lot of issues occurring when these surgeries and instruments are applied clinically, such as the excessive damage to vertebral bones, the secondary collapse of spine, the insufficient angle and height for rebuilding the collapsed vertebral bones, and the leakage of bone cement.

The current surgeries for treating the compressive fracture of spine include Vertebroplasty, Kyphoplasty and Vertebral expandable implant, and the vertebral expandable implant is newer clinical surgery. The vertebral bones are expanded along the direction of spine by using the metal expander and are injected with bone cement for fixing and recovering the collapsed spine.

Though all the above surgery methods can be applied for clinical treatment, there are some failure issues happened after using these surgery methods. For example, the Vertebroplasty method cannot recover the spine height and usually have the severe problems such as bone cement leakage. In Kyphoplasty surgery, there is a risk that the balloon may break during expansion, and the spine could collapse again due to losing the support after removing the balloon. In the surgery of vertebral expandable implant, the metal tools are used to expand the collapsed vertebral bones, however, it is difficult to control the expanding effects and the problems such as insufficient expanding height and insufficient space for injecting the bone cement usually happened, and the worse is that the inaccurate expanding height could result in the spinal curve deformation.

Therefore, a bone expandable device is provided by the present invention for overcoming the above issues.

SUMMARY

One objective of the present invention is to provide a bone expandable device for expanding the collapsed bones or vertebral body firmly and safely, thereby to maintain a space therebetween for injecting the bone cement. The bone expandable device can prevent the bone cement from leaking, can be applied to adjust the required height of rebuilding vertebral bones by the medical therapy unit according to the vertebral collapse degree, and can be applied to perform the angular adjustment for the deformed spine curve. Further, the bone expandable device has a shorter length in the closing state and can be adjusted with continuous or multi-stage heights to provide firmly supports for the vertebral bones.

The present invention provides a bone expandable device comprising two expanding members, a retractable member and a fastener.

The two expanding members are joining together for forming a cavity therebetween, and each the expanding member includes two flexible parts and a fixed part. A middle portion of each the expanding member is the fixed part, and two end portions of each the expanding member are the flexible parts. The two flexible parts are connected to and extending from the fixed part separately, and each the flexible part can be bent from a position adjacent to the fixed part. The fastener is for fastening the fixed parts of the two expanding members together.

The retractable member is disposed in the cavity and includes a first part and a second part. The first part is movably sleeved on the second part, and a length of the retractable member can be adjusted by moving the first part or the second part.

When the length of the retractable member is increasing, the two opposite ends of the retractable member would push against surfaces of four the flexible parts of the two expanding members facing the cavity, to expand the flexible parts outwardly from the cavity.

The retractable member has various modifications. In one embodiment, an inner surface of the first part and an outer surface of the second part are corresponding to each other and are formed with screw threads individually. The first part is sleeved and screwed onto the second part, and the length of the retractable member can be adjusted by rotating the first part or the second part.

When the first part and the second part are made to be screwed together as depicted above, at least one of the first part and the second part is formed with an operation hole, for inserting a tool from outside to rotate the first part or the second part.

In another embodiment of the retractable member, an inner surface of the first part and an outer surface of the second part are corresponding to each other and are formed with ratchet teeth individually, and the length of the retractable member can be adjusted by pulling the first part or the second part.

In a further embodiment of the retractable member, the first part includes at least one sliding chute and the second part includes at least one sliding block corresponding to the at least one sliding chute, and the length of the retractable member can be adjusted by pulling the first part or the second part.

The fastener also has various modifications. In one embodiment, the fastener is a C-type fastener for clamping the two fixed parts elastically.

In another embodiment, the fastener is a double buckle structure including two buckle parts, and at least one end of one the buckle part is hooked up with at least one end of the other buckle part correspondingly.

In a further embodiment, the fastener is a double buckle structure including two buckle parts, and at least one end of one the buckle part is bolted on at least one end of the other buckle part correspondingly.

Therefore, by applying the bone expandable device provided by the present invention, the retractable member can push against and spread the two expanding members for expanding the collapsed bones or vertebral body firmly and safely, thereby to maintain a space therebetween for injecting the bone cement. Besides, the bone expandable device, can prevent the bone cement from leaking effectively, can be applied to adjust the required height of rebuilding vertebral bones by the medical therapy unit according to the vertebral

collapse degree, and can be applied to perform the angular adjustment for the deformed spine curve. Further, the bone expandable device has a shorter length in the closing state and can be adjusted with continuous or multistage heights to provide firmly supports for the vertebral bones.

The present invention will be further described in detail with reference to accompanying drawings and preferred embodiments as follows.

BRIEF DESCRIPTION OF THE DRAWINGS

Accompanying drawings are for providing further understanding of embodiments of the disclosure. The drawings form a part of the disclosure and are for illustrating the principle of the embodiments of the disclosure along with the literal description. Apparently, the drawings in the description below are merely some embodiments of the disclosure, a person skilled in the art can obtain other drawings according to these drawings without creative efforts. In the figures:

FIG. 1A is a schematic view of the bone expandable device in the closing state provided by the present invention;

FIG. 1B is a schematic view of the bone expandable device in the expanding state provided by the present invention;

FIG. 2A is an explosion view of the bone expandable device provided by the present invention;

FIG. 2B is a side view of the bone expandable device in the expanding state provided by the present invention;

FIG. 3A and FIG. 3B are schematic views of the retractable member with ratchet teeth provided by the present invention;

FIG. 4A and FIG. 4B are schematic views of the slide type of retractable member provided by the present invention;

FIG. 5 is a schematic view illustrating another embodiment of the fastener provided by the present invention;

FIG. 6 is a schematic view illustrating further an embodiment of the fastener provided by the present invention; and

FIG. 7 is a schematic view illustrating another embodiment of the fastener provided by the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The specific structural and functional details disclosed herein are only representative and are intended for describing exemplary embodiments of the disclosure. However, the disclosure can be embodied in many forms of substitution and should not be interpreted as merely limited to the embodiments described herein.

Please refer to FIG. 1A, the schematic view of the bone expandable device 10 in the closing state provided by the present invention is shown. The fastener 34 is for fastening the two expanding members 32 stacked up and down, to join the two expanding members 32 together as a capsule for forming a cavity therebetween. The closing state of bone expandable device 10 has a small volume, beneficial for implanting into collapsed bones, for instance, implanting into collapsed vertebral bones.

Please refer to FIG. 1B, the schematic view of the bone expandable device 10 in the expanding state provided by the present invention is shown. The bolt set 36 is stretching to expand the two ends of each the expanding member 32, for extending and supporting the collapsed bones, for instance, extending the collapsed vertebral bones.

Please refer to FIG. 2A and FIG. 2B. FIG. 2A is an explosion view of the bone expandable device 10 provided

by the present invention. FIG. 2B is a side view of the bone expandable device 10 in the expanding state. The bone expandable device 10 provided by the present invention comprises two the expanding members 32, the retractable member such as the bolt set 36 and the fastener 34.

Each the expanding member 32 includes two flexible parts 3202 disposed at two ends and a fixed part 3204. The middle portion of each the expanding member 32 is the fixed part 3204, and the two end portions of each the expanding member 32 are the flexible parts 3202. The two flexible parts 3202 are connected with and extending from the fixed part 3204 separately, and the portion of the flexible part 3202 adjacent to the fixed part 3204 is serving as a deformation part 3206. The deformation part 3206 is thinner or has a weak structural strength, thereby easy to be bent. Therefore, by bending the deformation part 3206 at the position the flexible parts 3202 adjacent to the fixed part 3204, the flexible parts 3202 can be bent and extending outwardly relative to the fixed part 3204.

The surface structure on outside of the fixed part 3204 is serving as a fastening part 3208. The structure shape of the fastening part 3208 is fitting to the inner structure shape of the fastener 34, so the fastener 34 can be fastened stably on the fastening part 3208, thereby to have the two expanding members 32 stacked up and down for forming a capsule-like structure. In a preferred embodiment, the two expanding members 32 are made of thinner steel sheets.

In this embodiment, the retractable member is the bolt set 36, and the bolt set 36 is disposed in the cavity. The first part and the second part are the nut part 3602 and the screw part 3604 individually. Namely, the bolt set 36 includes the nut part 3602 and the screw part 3604. The inner surface of the nut part 3602 and the outer surface of the screw part 3604 are corresponding to each other and are formed with screw threads individually, therefore the nut part 3602 is sleeved and screwed onto the screw part 3604.

The length of the bolt set 36 can be adjusted by rotating the nut part 3602 or the screw part 3604, thereby to elongate or shorten two ends of the bolt set 36 relative to the fixed part 3204 which is served as a center.

In a preferred embodiment, the nut part 3602 or the screw part 3604 is formed with an operation hole 36H on outer end thereof, such as the hexagon hole shown in Figs, for inserting a tool from outside to rotate the nut part 3602 or the screw part 3604, thereby to elongate or shorten the bolt set 36. Besides, the thread surfaces of the nut part 3602 and the screw part 3604 include at least one through hole 36S separately, beneficial for injecting the bone cement into the cavity.

The fastener 34 is applied to clamp firmly the two fixed parts 3204 of the two expanding members 32. Various embodiments of the fastener 34 are illustrated as below. In this embodiment, the fastener 34 is a C-type fastener for clamping the two fixed parts 3204 elastically.

The shape of the cavity in a side view is preferably a diamond shape or likes. When the length of the bolt set 36 is increasing, the two opposite ends 36T of the bolt set 36 would push against the surfaces of four the flexible parts 3202 of the two expanding members 32 facing the cavity, along the diamond shaped bevel surfaces of the cavity separately, thereby to expand the four flexible parts 3202 outwardly from the cavity. A surface of the flexible part 3202 facing the cavity has a guiding chute 32C extending along an elongation direction of the bolt set 36, beneficial for guiding the two opposite ends 36T sliding along a fixed direction. Besides, another surface of the flexible parts 3202 back to the cavity has a flat portion 32P, beneficial for contacting and

5

supporting the collapsed bones with a large contacting area, to prevent the bones from being damaged again by the excessive stress due to the small contacting area.

In the above embodiment, the retractable member is the bolt set **36**, however, the retractable member may be made of other modifications. Please refer to FIG. 3A and FIG. 3B, the retractable member with ratchet teeth provided by the present invention is shown. In this embodiment, the retractable member is made of a ratchet set **46**. The ratchet set **46** is also disposed in the cavity, the first part and the second part are the female ratchet part **4602** and the male ratchet part **4604** individually. Namely, the ratchet set **46** includes the female ratchet part **4602** and the male ratchet part **4604**. The inner surface of the female ratchet part **4602** and the outer surface of the male ratchet part **4604** are corresponding to each other and are formed with circular ratchet teeth individually. The length of the ratchet set **46** can be elongated by pulling the female ratchet part **4602** or the male ratchet part **4604**, and after the length adjustment the female ratchet part **4602** and the male ratchet part **4604** can stuck each other to fix the length of the ratchet set **46**.

Please refer to FIG. 4A and FIG. 4B, the slide type of retractable member provided by the present invention is shown. In this embodiment, the retractable member is a slide set **56** disposed in the cavity, the first part and the second part are a female slide part **5602** and a male slide part **5604** individually. Namely, the slide set **56** includes the female slide part **5602** and the male slide part **5604**. The female slide part **5602** includes at least one sliding chute **60**, the male slide part **5604** includes at least one sliding block **62** corresponding to the sliding chute **60**. As shown in this embodiment, the sliding chute **60** formed on the female slide part **5602** is long spiral-shaped, and the sliding block **62** is fixed on an outer surface of the male slide part **5604**. A portion of the sliding chute **60** is made with zigzag slots for positioning the sliding block **62**. By pulling the female slide part **5602** or the male slide part **5604**, the sliding block **62** may slide in the sliding chute **60** for adjusting the length of the slide set **56** and stuck in the zigzag slot to fix the length of the slide set **56**.

Please refer to FIG. 5, another embodiment of the fastener **34** provided by the present invention is shown. In this embodiment, the bone expandable device **10** includes two C-type fasteners **34** disposed opposite to each other for buckling. Namely, the two C-type fasteners **34** are arranged opposite to each other to clamp the fixed part **3204** of the two expanding members **32** individually. By buckling the two C-type fasteners **34** opposite to each other, the risk that the components of the bone expandable device **10** slipping off to each other or disassembling could be reduced.

Please refer to FIG. 6, another embodiment of the fastener **34** provided by the present invention is shown. The fastener **34** may be a double buckle structure including two buckle parts **3402** and **3404**. In this embodiment, two the buckle parts **3402** and **3404** are disposed on the two fixed parts **3204** of the two expanding members **32** individually. Two ends of the buckle part **3402** are made with hook structures **3402h** separately. Also, two ends of the buckle part **3404** are made with hook structures **3404h** separately. Therefore, two the hook structures **3402h** of the buckle part **3402** are corresponding to and may be hooked up with two the hook structures **3404h** of the buckle part **3404** separately, thereby to fasten the two expanding members **32** together firmly by the buckle parts **3402** and **3404**.

Please refer to FIG. 7, a further embodiment of the fastener **34** provided by the present invention is shown. The fastener **34** may be a double buckle structure including two

6

buckle parts **3402** and **3404**. In this embodiment, two the buckle parts **3402** and **3404** are disposed on the two fixed parts **3204** of the two expanding members **32** individually. Two ends of the buckle part **3402** are made with bolt structures **3402a** separately. Also, two ends of the buckle part **3404** are made with bolt structures **3404a** separately. The bolt structure **3402a** is a convex structure with a first penetration hole, and the bolt structure **3404a** is a concave structure with a second penetration hole. The bolt structure **3402a** and the bolt structure **3404a** are fitting to each other and may be fastened with a bolt inserting the first and second penetration holes. Therefore, two the bolt structures **3402a** of the buckle part **3402** are correspond to and may be bolted on two the bolt structures **3404a** of the buckle part **3404**, thereby to fasten the two expanding members **32** together firmly by the buckle parts **3402** and **3404**.

The bolt illustrated in FIG. 7 may be fixed or pluggable. Besides, the embodiments shown in FIG. 6 and FIG. 7 may be mixed up. Namely, a pair of the corresponding ends of the buckle parts **3402** and **3404** may be made with the hook structures **3402h** and **3404h** individually, and the other pair of the corresponding ends of the buckle parts **3402** and **3404** may be made with the bolt structures **3402a** and **3404a** individually, thereby to have more modifications.

Accordingly, when the bone expandable device **10** provided by the present invention is used, the retractable member can push against and spread the two expanding members for expanding the collapsed bones or vertebral body firmly and safely, thereby to maintain a space therebetween for injecting the bone cement. Besides, the bone expandable device, can prevent effectively the bone cement from leaking, can be applied to adjust the required height for rebuilding vertebral bones by the medical therapy unit according to the vertebral collapse degree, and can be applied to perform the angular adjustment for the deformed spine curve. Further, the bone expandable device has a shorter length in the closing state and can be adjusted with continuous or multistage heights to provide firmly supports for the vertebral bones.

The foregoing contents are detailed description of the disclosure in conjunction with specific preferred embodiments and concrete embodiments of the disclosure are not limited to these descriptions. For the person skilled in the art of the disclosure, without departing from the concept of the disclosure, simple deductions or substitutions can be made and should be included in the protection scope of the application.

What is claimed is:

1. A bone expandable device, comprising:

two expanding members, joined together for forming a cavity therebetween, each of the expanding members including two flexible parts and a fixed part, wherein a middle portion of each of the expanding members is the fixed part and two end portions of each of the expanding members are the flexible parts, the two flexible parts are connected with and extending from the fixed part separately, and each of the flexible parts can be bent from a position adjacent to the fixed part, wherein a portion of each of the flexible parts at a position adjacent to the fixed part is thinner or has a weaker structural strength than other portions of the flexible parts for serving as a deformation part to be bent;

a retractable member, disposed in the cavity, including a first part and a second part, wherein the second part couples to a sleeve of the first part, and a length of the retractable member can be adjusted by moving the first part or the second part; and

7

a fastener, surrounding outsides of the two fixed parts of the two expanding members for clamping the two expanding members together;

wherein, when the length of the retractable member is increasing, two opposite ends of the retractable member would push against surfaces of the four flexible parts of the two expanding members facing the cavity, to expand the flexible parts outwardly from the cavity.

2. The bone expandable device according to claim 1, wherein an inner surface of the first part and an outer surface of the second part are corresponding to each other and are formed with screw threads individually, the second part is screwed into the sleeve of the first part, and the length of the retractable member can be adjusted by rotating the first part or the second part.

3. The bone expandable device according to claim 2, wherein at least one of the first part and the second part is formed with an operation hole on an outer end thereof, for inserting a tool from outside to rotate the first part or the second part.

4. The bone expandable device according to claim 1, wherein an inner surface of the first part and an outer surface of the second part are corresponding to each other and are formed with ratchet teeth individually, and the length of the retractable member can be adjusted by pulling the first part or the second part.

5. The bone expandable device according to claim 1, wherein the first part includes at least one sliding chute and

8

the second part includes at least one sliding block corresponding to the at least one sliding chute, and the length of the retractable member can be adjusted by pulling the first part or the second part.

6. The bone expandable device according to claim 1, wherein a surface of the flexible part facing the cavity has a guiding chute extending along an elongation direction of the retractable member, and another surface of the flexible part has a flat portion opposite of the cavity.

7. The bone expandable device according to claim 1, wherein sidewalls of the first part and the second part both include at least one through hole separately.

8. The bone expandable device according to claim 1, wherein the fastener is a C-type fastener, for clamping the two fixed parts elastically.

9. The bone expandable device according to claim 1, wherein the fastener is a double buckle structure including two buckle parts, and at least one end of one the buckle part is hooked up with at least one end of the other buckle part correspondingly.

10. The bone expandable device according to claim 1, wherein the fastener is a double buckle structure including two buckle parts, and at least one end of one the buckle part is bolted on at least one end of the other buckle part correspondingly.

* * * * *