



US010698587B2

(12) **United States Patent**
Paek et al.

(10) **Patent No.:** **US 10,698,587 B2**
(45) **Date of Patent:** ***Jun. 30, 2020**

- (54) **DISPLAY-EFFICIENT TEXT ENTRY AND EDITING**
- (71) Applicant: **Microsoft Technology Licensing, LLC**, Redmond, WA (US)
- (72) Inventors: **Timothy Paek**, Sammamish, WA (US); **Dmytro Rudchenko**, Bellevue, WA (US); **Vishwas Kulkarni**, Woodinville, WA (US); **Asela Jeevaka Ranaweera Gunawardana**, Seattle, WA (US); **Jason Grieves**, Bellevue, WA (US); **Daniel Ostrowski**, Seattle, WA (US); **Amish Patel**, Seattle, WA (US)
- (73) Assignee: **MICROSOFT TECHNOLOGY LICENSING, LLC**, Redmond, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/381,943**

(22) Filed: **Apr. 11, 2019**

(65) **Prior Publication Data**
US 2019/0286300 A1 Sep. 19, 2019

Related U.S. Application Data
(63) Continuation of application No. 14/555,502, filed on Nov. 26, 2014, now Pat. No. 10,261,674.
(Continued)

(51) **Int. Cl.**
G06F 17/00 (2019.01)
G06F 3/0484 (2013.01)
(Continued)


- (52) **U.S. Cl.**
CPC **G06F 3/04842** (2013.01); **G06F 3/0237** (2013.01); **G06F 3/0482** (2013.01);
(Continued)
- (58) **Field of Classification Search**
CPC .. **G06F 3/04842**; **G06F 3/0237**; **G06F 3/0482**; **G06F 3/0485**
(Continued)

- (56) **References Cited**
U.S. PATENT DOCUMENTS
2011/0296333 A1* 12/2011 Bateman G06F 3/04883
715/773
2014/0143784 A1* 5/2014 Mistry G06F 15/0208
718/102
(Continued)

- OTHER PUBLICATIONS
Funk et al., Using a touch-sensitive Wristband for text Entry on Smart Watches, ACM 2014, pp. 2305-2310. (Year: 2014).*
(Continued)
- Primary Examiner* — Cong-Lac Huynh
(74) *Attorney, Agent, or Firm* — Alleman Hall Creasman & Tuttle LLP

(57) **ABSTRACT**
Embodiments are disclosed for a method of providing a user interface on a computing device. The method includes presenting a virtual keyboard on a display of the computing device, detecting input to the virtual keyboard. The method further includes, for each detected input, determining whether the input selects any of one or more delimiter keys, displaying a placeholder for the input responsive to the input not selecting any of the one or more delimiter keys, and receiving suggested candidate text from a word-level recognizer and replacing all currently displayed placeholders with the suggested candidate text responsive to the input selecting any of the one or more delimiter keys.

20 Claims, 20 Drawing Sheets



Related U.S. Application Data

(60) Provisional application No. 62/046,883, filed on Sep. 5, 2014.

(51) **Int. Cl.**

G06F 3/0488 (2013.01)
G06F 3/0482 (2013.01)
G10L 25/48 (2013.01)
G06F 3/023 (2006.01)
G06F 3/0483 (2013.01)
G06F 3/0485 (2013.01)
H04M 1/725 (2006.01)
G06F 40/232 (2020.01)
G06F 1/16 (2006.01)
G10L 15/26 (2006.01)
G10L 15/00 (2013.01)

(52) **U.S. Cl.**

CPC **G06F 3/0483** (2013.01); **G06F 3/0485** (2013.01); **G06F 3/04883** (2013.01); **G06F 3/04886** (2013.01); **G06F 40/232** (2020.01); **G10L 25/48** (2013.01); **H04M 1/72552** (2013.01); **G06F 1/163** (2013.01); **G10L 15/00** (2013.01); **G10L 15/26** (2013.01); **H04M 1/7253** (2013.01); **H04M 2250/70** (2013.01)

(58) **Field of Classification Search**

USPC 715/773
 See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0222576 A1* 8/2015 Anderson G06F 3/04817
 715/752
 2015/0248235 A1* 9/2015 Offenber G06F 3/017
 715/773
 2015/0323998 A1* 11/2015 Kudekar G06F 1/163
 345/156
 2015/0339100 A1* 11/2015 Miura G06F 1/163
 345/156
 2016/0098086 A1* 4/2016 Li G01P 13/045
 345/173
 2017/0068448 A1* 3/2017 Ghassabian G06F 3/04886
 2017/0315620 A1* 11/2017 Johri G06F 3/014
 2017/0357413 A1* 12/2017 Green G06F 3/04883
 2018/0129897 A1* 5/2018 Hinckley G06K 9/34

OTHER PUBLICATIONS

“Second Office Action Issued in Chinese Patent Application No. 201580047733.3”, dated Mar. 1, 2019, 8 Pages.
 “Third Office Action Issued in Chinese Patent Application No. 201580047733.3”, dated Jul. 23, 2019, 10 Pages.
 “Office Action Issued in European Patent Application No. 15763783.6”, dated Oct. 1, 2019, 8 Pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7





FIG. 8

FIG. 9






FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17

DISPLAY-EFFICIENT TEXT ENTRY AND EDITING

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/555,502, filed Nov. 26, 2014, and entitled “DISPLAY-EFFICIENT TEXT ENTRY AND EDITING”, which claims priority to U.S. Provisional Patent Application No. 62/046,883, filed Sep. 5, 2014, and entitled “DISPLAY-EFFICIENT TEXT ENTRY AND EDITING”, the entirety of each of which are hereby incorporated herein by reference.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 schematically shows a text-entry device in the form of a wrist-wearable computing device.

FIG. 2 shows an example user interface displayed on a touch display of a text-entry device.

FIG. 3 shows an example initialization scenario of a text-entry device.

FIG. 4 shows a text entry scenario of a text-entry device.

FIGS. 5A, 5B, 6, and 7 show keyboard layout selection scenarios of a text-entry device.

FIG. 8 shows a scenario for selecting a numerical keyboard layout on a text-entry device.

FIG. 9 shows a text editor viewing scenario on a text-entry device.

FIGS. 10A-10C show an example sliding ribbon configuration of a text-entry device.

FIGS. 11-14 show text editing scenarios on a text-entry device.

FIG. 15 shows an example text entry and editing scenario that utilizes voice input.

FIG. 16 is a flow chart of an example method of text entry.

FIG. 17 shows an example text-editing computing device.

DETAILED DESCRIPTION

The present disclosure is directed to an intuitive and powerful mechanism for entering and/or editing textual input on a computing device. While the concepts of this disclosure are compatible with text-entry devices that have very small displays, the concepts are not limited to any particular device form factor.

FIG. 1 shows an example text-entry device in the form of a wrist-wearable computing device **100** including a touch display **102**. Wrist-wearable computing device **100** is configured to receive user input and translate the input into text—e.g., letters, numbers, characters, and/or symbols.

As discussed in more detail below, text-entry devices may include touch display sensors that allow a user to input text via a virtual keyboard presented on a display; touch sensors that allow a user to draw text on a display or a non-display touch area; speech recognition systems that allow a user to enter text via spoken words; eye-tracking systems that allow a user to enter text via gaze; gesture recognition systems that allow a user to trace text shapes in air; and/or other text input mechanisms.

When included, a text-entry device’s virtual keyboard may take full advantage of a small display size by filling substantially all of the display. In particular, the virtual keyboard may be presented without a significant portion of the display reserved for showing the user a letter-by-letter reproduction of what is being typed or what has already been

typed. In some implementations, only the last completed word, or a portion thereof, is displayed with the keyboard—letters of an uncompleted word are not displayed until the word is completed, and the penultimate word is not displayed with the last completed word. In some implementations, a last completed word, or a portion thereof, is displayed immediately adjacent the right- or left-most key in a bottom row of the virtual keyboard. The last completed word, or a portion thereof, may additionally or alternatively be displayed (e.g., superimposed) over the keyboard temporarily (e.g., for a set period of time and/or until a suitable input is received). The superimposed word or portion thereof may be partially transparent and/or the appearance of the keyboard may be altered (e.g., dimmed) during display of the superimposed text in some examples. Optionally, a placeholder (e.g., asterisks or bullet) may be displayed in these same areas responsive to each recognized key stroke.

In some implementations, two or more different virtual keyboards may cooperate to provide a user a greater number of text input options. As an example, one keyboard may include 26 lower case letter keys; another keyboard may include 10 numeric keys; another keyboard may include one or more symbols (e.g., @, #, \$, %, &, and/or others) and/or emoticons; another keyboard may include 26 upper case letter keys; and another keyboard may include one or more foreign language letters or symbols (e.g., Hanzi, Kanji, and/or others). In addition to the primary keys of a given keyboard, some keyboards may also include a space key, one or more modifier keys, one or more punctuation keys (e.g., period, comma, question mark), and/or other supplemental keys. When two or more keyboards are included, a user may selectively toggle between the keyboards with a touch swipe, voice command, gesture, gaze, and/or other user command. In some implementations, keys of one keyboard may provide direct links to different keyboards. FIGS. 2-9 show example virtual keyboards.

The computing device may leverage an on-board word-level recognizer **104** or off-board word-level recognizer **106** (e.g., within a remote computing device **108**) that analyzes all input between text delimiters and recommends candidate text based on the word-level analysis. In some embodiments, (e.g., during utilization of keyboards relating to character-based languages), each input character may be processed and words may be determined based on natural word boundaries for that language without inputting specific delimiters. Once a text-delimiter, other user indication, or language-based natural word boundary signals a word completion, the word-level recognizer may determine the word or words that the user most-likely intended to input. Before the user indication signals a word completion, the word-level recognizer need not present any word predictions. By avoiding such predictions, the user will not be distracted by potentially unintended word fragments that are inaccurately predicted based on less than all user input for that word. The word-level recognizer may be trained via supervised or unsupervised machine learning and/or may include personalized training data from the computing device or a cloud-based network.

When an off-board word-level recognizer is utilized, the text-entry device may communicate all user input to the off-board word-level recognizer using one or more local or wide area networks. In some implementations, the off-board word-level recognizer may be a module of a mobile telephone or other portable computing device that is physically near the text-entry computing device. In other implementations, the off-board word-level recognizer may be offered as part of a remote cloud-based service. The local text-entry

device and the off-board, word-level recognizer may communicate using any suitable protocol and/or technology. Non-limiting examples of suitable protocols and technologies are described in APPENDIX A.

When an off-board, word-level recognizer is used in cooperation with a virtual keyboard, the text-entry device optionally may use very light weight communication with the off-board, word-level recognizer. As one example, the text-entry device may communicate the detected touch contact parameters to the off-board, word-level recognizer. This may be less computationally expensive than translating raw sensor measurements on board and then communicating translation of the raw input.

The text-entry device may provide text editing functionality that allows a user to verify and/or change candidate text that has been recognized using any of the device's text input mechanisms. The text editor is displayed independently and is not part of the virtual keyboard's graphical user interface. By temporally separating display of a virtual keyboard and the text editor, both the virtual keyboard and the text editor are allowed to independently take full advantage of whatever display real estate the text-entry device offers. The virtual keyboard does not have to make any compromises for the text editor or vice versa. In some implementations, a user may selectively toggle between a virtual keyboard and the text editor. Such toggling may be initiated by a touch swipe, voice command, gesture, gaze, greater-than-threshold pause, and/or other event or user command. A toggle between a virtual keyboard and a text editor may include an animation where the virtual keyboard appears to be pushed off the display by the text editor, or vice versa.

The text editor may display candidate text translated from user input (e.g., via a word-level recognizer). In some instances, the candidate text may not be the final text that the user wants. As such, the text editor is configured to allow the user to select any word for editing, delete any word, add new words, and/or make other changes. In some examples, the text editor may provide one or more alternate candidate words for each candidate word. FIGS. 9-15 show non-limiting examples of text editors and editing scenarios.

Turning now to FIG. 2, an example user interface 202 displayed on the touch display 102 of the wrist-wearable computing device 100 of FIG. 1 is illustrated. The user interface 202 may include two or more pages, including a menu page, one or more virtual keyboard pages, and/or a text editor page. The menu may enable a user to select a desired keyboard layout from among a plurality of possible layouts and/or may include directional navigation keys (e.g., a back or exit button). A virtual keyboard may comprise letters, numbers, and/or symbols that a user may select using touch input. Text entered by the user may be displayed and/or edited via the text editor. Text entered and edited as described herein may be used in virtually any computing scenario, including text messaging, emailing, word processing, note taking, and/or other writing scenarios.

Due to the relatively small size of the touch display 102, in order to allow a user to effectively visualize and enter touch input to each key of the virtual keyboard, menu option, etc., the user interface 202 may be configured such that only a portion of the user interface is displayed at any given time (e.g., either keyboard page or text editor page). For example, the user interface may be configured as a ribbon, and only a section of the ribbon may be displayed at one time, with each section of the ribbon viewable as a user scrolls through the user interface. Additional information regarding the ribbon configuration of the user interface will be provided below with respect to FIGS. 10A-10C.

FIG. 2 illustrates a virtual keyboard 204 of the user interface 202 including letters arranged in a standard QWERTY keyboard arrangement, one or more text delimiters, including a space key 206 and a period key 208, and a text preview area 210. Due to the relatively small size of the display 102, the virtual keyboard 204 may occupy nearly all of the available display space, and thus the menu and text editor regions of the user interface are not visible in FIG. 2. For example, the display 102 may have a top edge and a bottom edge, and the virtual keyboard may be presented without a text-editing area between the virtual keyboard and the bottom edge. As illustrated, a top row of keys of the virtual keyboard (e.g., the row having letters "QWE . . .") may be displayed in a top third of the display 102, a middle row of keys of the virtual keyboard (e.g., the row having letters "ASD . . .") may be displayed in a middle third of the display 102, and a bottom row of keys of the virtual keyboard (e.g., the row having letters "ZXC . . .") may be displayed in a bottom third of the display 102.

It is to be understood that the illustrated arrangement of the virtual keyboard 204 is one example of possible arrangements, and other configurations are possible. For example, rather than having the letters arranged in the QWERTY arrangement illustrated, the letters may be arranged alphabetically or in virtually any suitable arrangement. Further, additional or alternative text delimiters may be present on virtual keyboard 204, including but not limited to a question mark key, exclamation point key, etc. Further still, while only letters are illustrated in virtual keyboard 204, it is to be understood that other characters, such as numbers or symbols, may be additionally or alternatively displayed, as explained in more detail below.

In order to create a text string, a user may touch the virtual keyboard 204. As such, computing device 100 may include a plurality of touch sensors configured to detect touch input. In some examples, more than one letter, number, or symbol may be mapped to the same touch sensor (i.e., the touch sensing resolution may be less than the number of keys).

In the example illustrated in FIG. 2, a preview area 210 displays placeholder symbols that indicate the number of touch inputs that have currently been entered by the user. The placeholder symbols may comprise suitable symbols, such as asterisks, bullets, or other symbols. In this way, the user may see how many touch inputs (e.g., how many characters) he or she has entered without seeing the actual characters, until a text delimiter key is entered. Once the user makes an input to a text delimiter key (e.g., the space key 206 or the period key 208), a candidate word may be displayed in the preview area.

When the user is entering touch inputs to the user interface 202, in addition to displaying how many touch inputs have been made in the preview area 210, the user interface 202 may also be configured to provide touch input feedback to the user to inform the user where the last touch input occurred. For example, as illustrated in FIG. 2, a user 212 has entered touch input to virtual keyboard 204 at a location near the D, F, X, and C keys. A feedback indicator 214 may be displayed on the user interface 202 to provide a visual indicator to the user of the location of the most recent touch input. The feedback indicator may be a semi-transparent circle, as illustrated in FIG. 2, or may be of another suitable design. Further, the feedback indicator may persist on the display 102 for a duration after the user has ended the current touch input, for example until a subsequent touch input is entered and/or for a predetermined/selected dura-

5

tion. In some examples, the feedback provided to the user may include haptic feedback, audio feedback, or other suitable feedback.

A plurality of example scenarios for interacting with a user interface displayed on the touch display **102** of computing device **100** will now be described with respect to FIGS. **3-16**. It is to be understood that one or more of the user interface examples and states described below may correspond to user interface **202**.

Starting with FIG. **3**, an example initialization scenario illustrating an initialization of a virtual keyboard **302** of a user interface **304** is displayed. The initialization scenario includes a series of user interface states that may be displayed over time. As such, a timeline **306** is depicted in FIG. **3** along the vertical axis. At time T_0 , the user interface **304** displays a connecting notification **305** that notifies the user that the virtual keyboard is being initialized, e.g., that the computing device **100** is connecting to a remote device to enable the identification of candidate words based on user touch inputs to the virtual keyboard, as explained above. During this time, the connecting notification is displayed over the virtual keyboard. In some implementations, a connection period may not be needed.

At time T_1 , the user interface **304** transitions to display a preview of a menu **308**. The menu **308** may allow a user to select a desired keyboard layout, such as a keyboard that displays letters, numbers, or symbols. The preview is displayed as a hint to inform a user that the menu is available to the left of the virtual keyboard **302**. At time T_2 , the user interface **304** further transitions to display a navigation key **310**. The navigation key **310** may allow a user to exit out of the virtual keyboard **302**, return to a previous user interface display, or execute other operations. At times T_3 and T_4 , the user interface **304** slides back to only display virtual keyboard **302**. It is to be understood that the type of keyboard displayed upon initialization of the virtual keyboard may be context-dependent. For example, the keyboard may be initialized responsive to a user input for responding to a received message (e.g., an email, an SMS message, or another suitable message). Accordingly, the keyboard presented responsive to such selection may have a language corresponding to a detected language of the received message. A default type of keyboard may additionally or alternatively be defined by user preference settings.

The initialization animation illustrated in FIG. **3** is a non-limiting example of an animation that may be used to inform a user that functions that typically may be displayed on a same page as a virtual keyboard can be accessed on a different page, thus allowing keys and/or other display real estate associated with such functions to be omitted from the virtual keyboard.

FIG. **4** shows an example text input scenario for entering text input via virtual keyboard **402** of a user interface **404**. Similar to FIG. **3**, a timeline **406** is depicted along a vertical axis and a series of user interface states are illustrated over time. As explained above, a feedback indicator optionally may be displayed each time a user enters a touch input. Thus, at time T_0 , in response to a touch input entered by a user, a feedback indicator **408** is displayed at the location of the touch input, which in this example is in the vicinity of the T, G, F, and R keys. Similarly, at time T_1 , the feedback indicator **408** is displayed at a different location, corresponding to a second touch input entered by the user over the H key. At time T_2 , the feedback indicator **408** is displayed at another location, in response to a subsequent user touch input at the region of the I and U keys. At time T_3 , the feedback indicator is displayed at a further different location

6

corresponding to the location of another touch input over the S key, and at time T_4 , the feedback indicator **408** is displayed at another location in response to an additional touch input at the space key.

When the user enters touch input to the virtual keyboard **402**, a placeholder symbol **410** is displayed in a preview area **412**. For each separate touch input entered between text delimiters, a placeholder symbol is displayed. Accordingly, a first placeholder symbol (in this example, a bullet) is displayed in preview area **412** at time T_0 , indicating that one touch input has been entered. At time T_1 , two placeholder symbols are displayed in preview area **412**, indicating that two touch inputs have been entered. At time T_2 , three placeholder symbols are displayed in preview area **412**, indicating three touch inputs have been entered. At time T_3 , four placeholder symbols are displayed in the preview area **412**, indicating that four touch inputs have been entered.

At time T_4 , the user enters touch input to the space key, which as explained above is a text delimiter. As such, the raw sensor data corresponding to the four touch inputs are processed to determine one or more candidate words. Once at least one candidate word is determined, a candidate word is displayed in the preview area **412**. In one example, the displayed candidate word may be the word that the word-level recognizer has determined is the most likely word represented by the touch inputs received. In the example touch input scenario illustrated in FIG. **4**, the user has entered touch input that the word-level recognizer determines to correspond to the word "THIS."

While providing input to the computing device **100**, the user may access different keyboard layouts in order to expand the number and types of characters that may be entered. FIGS. **5A**, **5B**, **6**, and **7** show example keyboard layout selection scenarios. In the examples illustrated in FIGS. **5A** and **5B**, keyboard layouts may be accessed by performing a swiping or slide gesture input (e.g., moving a finger or other input device across the display) while viewing a virtual keyboard.

At time T_0 in FIG. **5A**, a QWERTY virtual keyboard **502** is displayed, and a user begins a downward vertical swipe gesture (e.g., via finger **506**) to access a different keyboard layout. At time T_1 , the downward swipe is continued, and a portion of a symbol keyboard layout **508** is presented along a top of the viewable user interface **504** as the symbol keyboard is moved into view. A portion of the QWERTY virtual keyboard **502** is no longer displayed, as the QWERTY keyboard is moved out of view for replacement by the symbol keyboard **508**. At time T_2 , the downward swipe is completed, and the symbol keyboard is displayed, replacing the QWERTY keyboard. As illustrated, the symbol keyboard includes a plurality of symbols (e.g., punctuation, symbolic characters, and emoticons), a space delimiter **510**, a delete icon **512**, and a preview area **514** (e.g., for displaying entered symbols). It is to be understood that any suitable symbols may be included in the symbol keyboard.

Turning now to FIG. **5B**, a numerical keyboard layout accessible by an upward vertical swipe is illustrated. At time T_0 in FIG. **5B**, a user begins an upward vertical swipe gesture (e.g., via finger **506**) to access a different keyboard layout. At time T_1 , the upward swipe is continued, and a portion of a numerical keyboard layout **516** is presented along a bottom of the viewable user interface **504** as the numerical keyboard is moved into view. A portion of the QWERTY virtual keyboard **502** is no longer displayed, as the QWERTY keyboard is moved out of view for replacement by the numerical keyboard **516**. At time T_2 , the upward swipe is completed, and the numerical keyboard is dis-

played, replacing the QWERTY keyboard. As illustrated, the numerical keyboard includes numerals 0-9, a space delimiter **518**, a delete icon **520**, and a preview area **522** (e.g., for displaying entered numbers). It is to be understood that any suitable numbers may be included in the numerical keyboard layout for selection. In some implementations, additional or alternative keyboard layouts may be accessed by performing additional or alternative swiping gestures or other user input while a virtual keyboard is displayed.

As described above, FIGS. **5A** and **5B** illustrate examples of accessing additional keyboard layouts via swiping gestures. In other implementations, additional keyboard layouts may be accessed via selection of direct links and/or keys (e.g., a menu item), as illustrated in FIG. **6**. At time T_0 in FIG. **6**, a QWERTY virtual keyboard **602** is included in a user interface **604**. Also at time T_0 , a user begins a horizontal swipe gesture toward the right of the display (e.g., via finger **606**) to access a different keyboard layout. At time T_1 , the QWERTY virtual keyboard is dragged to the right, such that a portion of the keyboard is no longer displayed (e.g., letters on the right side of the keyboard). A portion of a keyboard selection menu **608** is displayed to the left of the QWERTY virtual keyboard **602**. At time T_2 , the horizontal swipe gesture is completed, and a navigation key **610** is displayed to the left of the keyboard selection menu **608**. As described above, the navigation key **610** may include a back button or similar key that enables a user to cancel a current task, exit the keyboard, exit the keyboard selection menu (e.g., return to a display of a virtual keyboard), and/or input any other suitable command. It is to be understood that the placement of the keyboard selection menu illustrated in FIG. **6** is exemplary in nature, and the keyboard selection keys may be displayed with any suitable arrangement or omitted altogether.

FIG. **7** illustrates an example scenario for selecting a symbol keyboard layout via the keyboard selection menu. At time T_0 , a portion of a QWERTY virtual keyboard **702** of a user interface **704** is displayed to the right of a keyboard selection menu **706**. Also at time T_0 , user input is received at a symbol keyboard layout selection key **708** (e.g., as represented by feedback indicator **710**). In response to the user input, a symbol virtual keyboard **712** is selected at time T_1 , as indicated by a highlighting or other visual distinction of the symbol keyboard layout selection key **708**. As also illustrated at time T_1 , a portion of the symbol virtual keyboard is displayed to the right of the keyboard layout selection menu **706**, including a subset of the symbols included in the symbol virtual keyboard. The portion of the symbol virtual keyboard displayed at time T_1 replaces the portion of the QWERTY virtual keyboard **702** displayed at time T_0 .

At time T_2 , a horizontal swiping gesture is being performed, as represented by leftward-moving gesture indicator **714**. As a result of the swiping gesture, the user interface **704** is dragged to the left to transition from the keyboard layout selection menu to the selected virtual keyboard (e.g., the symbol virtual keyboard). As illustrated, the navigational key is no longer displayed, the keyboard selection keys of the keyboard layout menu **706** are displayed on a far left side of the display, and additional symbols (e.g., relative to the symbols displayed at time T_1) are displayed in the virtual keyboard area. At time T_3 , the swiping gesture is concluded, revealing the full symbol keyboard. It is to be understood that the illustrated symbols included in the symbol virtual keyboard are exemplary in nature, and any suitable symbols may be included in any suitable arrangement. In addition to the symbols of the symbol virtual keyboard, a delimiter key

(e.g., space key **716**), a delete key **718**, and a preview area **720** are displayed. As illustrated at time T_4 , selection of a symbol in the symbol virtual keyboard (e.g., as indicated by feedback indicator **722**) results in the display of the selected symbol within preview area **720**. In other words, a symbol may include an implied delimiter. In some implementations, a placeholder may be displayed until a dedicated delimiter key is selected.

FIG. **8** illustrates an example scenario for selecting a numerical keyboard layout via the keyboard selection menu described above. At time T_0 , a portion of a QWERTY virtual keyboard **802** of a user interface **804** is displayed to the right of a keyboard selection menu **806**. Also at time T_0 , user input is received at a numerical keyboard layout selection key **808** (e.g., as represented by feedback indicator **810**). In response to the user input, a numerical virtual keyboard is selected at time T_1 , as indicated by a highlighting or other visual distinction of the symbol keyboard layout selection key **808**. As also illustrated at time T_1 , a portion of a numerical virtual keyboard **809** is displayed to the right of the keyboard layout selection menu **806**, including a subset of the numbers included in the numerical virtual keyboard. The portion of the numerical virtual keyboard **809** displayed at time T_1 replaces the portion of the QWERTY virtual keyboard **802** displayed at time T_0 .

At time T_2 , a horizontal swiping gesture is being performed, as represented by leftward-moving gesture indicator **812**. As a result of the swiping gesture, the user interface **804** is dragged to the left to transition from the keyboard layout selection menu to the selected virtual keyboard (e.g., the numerical virtual keyboard **809**). As illustrated, a navigational key is no longer displayed, the keyboard selection keys are displayed on a far left side of the display, and additional numbers (e.g., relative to the numbers displayed at time T_1) are displayed in the virtual keyboard area. At time T_3 , the swiping gesture is concluded, revealing the full numerical virtual keyboard **809**. It is to be understood that the illustrated numbers included in the numerical virtual keyboard are exemplary in nature, and any suitable numerical values or other related characters (e.g., mathematical symbols, decimal points, and/or other suitable characters) may be included in any suitable arrangement. In addition to the numbers of the numerical virtual keyboard, a delimiter key (e.g., space key **816**), a delete key **818**, and a preview area **820** are displayed. As illustrated at time T_4 , selection of a number (e.g., "9") in the numerical virtual keyboard (e.g., as indicated by feedback indicator **822**) results in the display of the selected number within preview area **820**. In other words, a number may include an implied delimiter. In some implementations, a placeholder may be displayed until a dedicated delimiter key is selected.

As described above, example virtual keyboards may be configured to occupy substantially all of a display, leaving little room for viewing entered text/characters. In order to view input that has already been entered (e.g., candidate text that has been recognized, forming at least a portion of a message), a text editor may be accessed by providing user input to the device (e.g., a touch input such as a tap, swipe, slide, or other gesture, a physical button actuation, a detected eye gaze, a voice input, or any other suitable input). FIG. **9** illustrates an example of a transition from a virtual keyboard page to a text editor page.

At time T_0 in FIG. **9**, a QWERTY virtual keyboard **902** of a user interface **904** is illustrated (e.g., without a text-editing area between the virtual keyboard and a top or bottom edge of a display). As shown in the lower right corner, a preview area **906** may include a portion of the last-recognized

candidate text word. For example, prior to time T_0 , a user may have provided input selecting a plurality of letters and then selected a delimiter (e.g., the period key **908**), resulting in a candidate text “DEVICE” to be recognized based on the input strokes. As the preview area **906** is constrained to a particular region (e.g., the illustrated example shows a region that is large enough to show three characters from the example candidate text), the candidate text may be truncated if the text is larger than the size of the preview area. In this way, only a portion of the candidate text is displayed (e.g., the first three characters) in the preview area at time T_0 .

The preview area is configured to truncate an end portion of the candidate text (e.g., in the event that the candidate text is too large to fit in the preview area) in order to suggest and/or provide a hint to a user as to the location of the remainder of the candidate text. For example, by noting that the candidate text is truncated by a right edge of the display, the user may be encouraged to drag the user interface (e.g., the virtual keyboard) to the left in order to reveal the remaining characters of the candidate text. Accordingly, as illustrated at time T_0 , a show-text-editor input, such as a leftward horizontal swiping or sliding gesture may be initiated, indicated by leftward-moving gesture indicator **910**. In response to the swiping gesture, the user interface **904** may be dragged to the left, as illustrated at time T_1 . For example, only a right portion of the virtual keyboard may be displayed in a left region of the display, as the user interface transitions from a virtual keyboard to a text editor. The text editor may be partially displayed on a right side of the display, as illustrated by a partial string of candidate text **912** (e.g., a message string for a currently-composed message) and an action button (e.g., “SEND” key **914**). It is to be understood that other suitable action buttons may be displayed. In some implementations, the “SEND” key **914** may include text and/or a graphical icon. As also illustrated at time T_1 , the candidate text of a last-recognized word (e.g., “DEVICE”) may be fully displayed, creating a “bleed-over” effect between the virtual keyboard and the text editor.

The swiping gesture is continued at time T_1 , as illustrated by the leftward-moving gesture indicator **916**. In response, at time T_2 , the user interface is fully transitioned to the text editor **918** such that the text editor is displayed without the virtual keyboard. The text editor may display a string of candidate text **912** (e.g., recognized inputs during a current text input session and/or prior to selecting an action button such as a send key). The string of candidate text **912** may include words recognized from input to a QWERTY virtual keyboard, symbols selected from a symbol virtual keyboard, and/or numbers selected from a numerical virtual keyboard. In some implementations, the text editor may include a character counter **920**. For example, some messages (e.g., SMS text messages), may be limited to include a threshold number of characters (e.g., due to bandwidth parameters and/or communication protocols). Character counter **920** may enable a user to keep track of how many characters have been entered during a text input session (e.g., how many characters are included in a message that is currently being composed).

The text editor **918** may also include a slider bar **922**, which illustrates the length of the string of candidate text (e.g., a length of the slider bar may be relative to a length of the string of candidate text) and a currently-viewed location in the string of candidate text. For example, at time T_2 , the beginning of the string may be in view, resulting in the display of the slider bar **922** in a lower far left corner of the display. As the user navigates along the string at time T_3 (e.g., as illustrated by leftward horizontal swiping gesture

represented by leftward-moving gesture indicator **924**), the string is moved along the display such that a different portion of the string is viewable. Accordingly, at time T_3 , some of the text that was viewable at time T_2 is no longer viewable (e.g., is dragged out of the displayable region toward the left side of the display) and additional text that was not viewable at time T_2 is brought into view (e.g., is dragged from the right side of the display into the displayable region). As also illustrated at time T_3 , the slider bar **922** is moved to the right, indicating that a middle portion of the string of candidate text is being viewed.

As the user continues navigating along the string at time T_3 (e.g., as illustrated by leftward horizontal swiping gesture represented by leftward-moving gesture indicator **924**), the string is moved along the display such that a different portion (e.g., an end) of the string is viewable. Accordingly, at time T_4 , some of the text that was viewable at time T_3 is no longer viewable (e.g., is dragged out of the displayable region toward the left side of the display) and additional text that was not viewable at time T_3 is brought into view (e.g., is dragged from the right side of the display into the displayable region). As also illustrated at time T_4 , the slider bar **922** is moved to the right, indicating that an end portion of the string of candidate text is being viewed.

As illustrated in FIG. 9, the action button (e.g., “SEND” key **914**) is presented responsive to displaying a portion of the text editor (e.g., at time T_1). In some implementations, selection of the “SEND” key may result in a sending and/or saving of the message. For example, if the text entry user interface is entered responsive to selecting a compose message or reply to message command, selecting the “SEND” key may result in sending the message to a selected recipient(s). In other implementations, selection of the “SEND” key at times T_1 , T_2 , T_3 and/or any other time in which the end of the candidate text string is not being viewed may result in the user interface automatically (e.g., without further user input) navigating to the end of the string (e.g., simulating an effect of a horizontal swiping gesture). A subsequent selection of the “SEND” key may result in sending and/or saving the message. In still other implementations, the action button may not be displayed until an end of the candidate text string is displayed and selecting the action button may result in the message being sent and/or saved.

FIGS. 10A-10C illustrate a text-entry device **1000** (e.g., a wrist-wearable computing device) presenting a panoramic or ribbon graphical user interface **1002**. For example, ribbon graphical user interface **1002** may correspond to the user interfaces described and illustrated in FIGS. 2-15. It should be understood that while FIGS. 10A-10C show portions of ribbon graphical user interface **1002** extending past the boundaries of the display of the text-entry device, such portions of the ribbon graphical user interface are not visible to a user. FIGS. 10A-10C are intended to show the horizontal portions of the ribbon graphical user interface which are not currently visible to a user, but which may be brought into view.

Text-entry device **1000** includes a display **1004** for presenting ribbon graphical user interface **1002**, other user interfaces, applications, data, media content, and/or other content. Display **1004** has a first dimension along a first axis and a second dimension along a second axis. In the illustrated implementations, the first dimension is a height dimension and the second dimension is a width dimension. In other implementations, a display may be shaped differently. For example, while display **1004** is formatted with a landscape aspect ratio (i.e., width greater than height), a display with a portrait aspect ratio (i.e., height greater than

11

width), a square aspect ratio, or a non-rectangular aspect ratio may be used. Further, while ribbon graphical user interface **1002** is shown as being horizontally-pannable, a vertically-scrollable graphical user interface and/or a graphical interface that is both vertically-scrollable and horizontally-pannable is within the scope of this disclosure. In some implementations, the orientation of a display may automatically rotate responsive to the text-entry device being rotated.

Ribbon graphical user interface **1002** includes a collection of user interface states or input regions anchored over a contiguous background **1006**. The user interface input regions may include a keyboard selection menu, a virtual keyboard, a text editor, and/or any other suitable user interface input region. As used herein, the term anchored means that the user interface input regions move with the contiguous background. In other words, the input regions do not scroll over the background while the background remains stationary. Instead, the input regions and the background move together. It should be understood, however, that some input regions may move relative to the contiguous background (e.g., growing, shrinking, rotating, changing form, and/or exhibiting other suitable relative movements). Furthermore, in some implementations, the background can optionally be scrolled at a different speed than the foreground to give the visual perception of parallax, which may help enforce a three-dimensional metaphor of the user interface.

As shown in FIGS. **10A-10C**, ribbon graphical user interface **1002** is a fixed-height, horizontally-pannable graphical user interface. A height of ribbon graphical user interface **1002** is sized to fit within a first dimension of display **1004**. In contrast, the width of the ribbon graphical user interface is too large to be completely visible at one time using display **1004**. In particular, the contiguous background is sized to extend beyond the second dimension of the display, and at least one of the user interface input regions are arranged to extend beyond the second dimension of the display.

FIG. **10A** shows a first state of the ribbon graphical user interface, in which a first user interface input region is viewable within display **1004** of the text-entry device **1000**. As illustrated, a keyboard selection menu and a portion of a virtual keyboard may be viewable in the state illustrated in FIG. **10A**. In FIG. **10B**, the ribbon graphical user interface **1002** is presented within display **1004** in a second state, in which a second user interface input region (e.g., a virtual keyboard) is viewable. Likewise, in FIG. **10C**, the ribbon graphical user interface **1002** is presented within display **1004** in a third state, in which a third user interface input region (e.g., a text editor) is viewable. In some embodiments, a user may fluidly transition between the illustrated user interface input regions, such that portions of multiple input regions are visible on the display during transitions (e.g., as the user progresses from one input region to another). In some embodiments, the user interface may “snap” or otherwise be biased toward presenting the illustrated user interface input regions discretely, such that simultaneous views of multiple input regions are only presented for a short period of time (e.g., in motion) while the user interface moves between input regions.

As further illustrated in FIG. **10C**, some additional user interface elements (e.g., message counter **1008** and action button **1010**) may only be displayed upon presentation of a particular input region. For example, the user interface elements may not appear when that input region is partially presented or in transition. The user interface elements may not be anchored to a contiguous background of the user

12

interface, such that the elements remain in a particular location(s) of the display while the user interface is presenting an associated input region. For example, the message counter **1008** and action button **1010** may remain in the upper and lower right corners of the display **1004**, respectively, as long as the text editor is viewable, even as the user interface is moved to show different portions of text string **1012**.

FIGS. **11-15** illustrate example text editing scenarios and associated user interface states. Turning first to FIG. **11**, an example scenario of replacing a recognized candidate word with an alternate candidate word is illustrated. At time T_0 , a user interface **1102** includes a portion of a string of candidate text **1104**. For example, the string of candidate text **1104** may include all recognized candidate words entered by a user in a text entry session (e.g., after initiation of the keyboard and prior to sending a message). At time T_1 (or some time period between T_0 and T_1), a selection of one of the candidate words in the string **1104** is input, as indicated by gesture indicator **1106** illustrated over the candidate word “test.” As illustrated at time T_1 , selection of a candidate word causes a plurality of user interface elements to be displayed. For example, an add word key **1108**, a delete word key **1110**, and alternate candidate words **1112** may be displayed. In some embodiments, the selected word may be differentiated from other words in the string by altering the display characteristics of the selected word and/or the other words in the string. For example, the other words in the string may be greyed out, faded, reduced in size, and/or otherwise less prominently displayed relative to the selected word. Additionally or alternatively, opposite effects may be applied to the selected word to increase the prominence of the selected word. For example, the selected word may remain the same color, be changed to a different (e.g., a brighter) color, increased in size, highlighted, and/or otherwise more prominently displayed than the other words in the string.

In the example illustrated in FIG. **11**, alternate candidate words for the selected candidate word are presented above and below the selected candidate word. As shown at time T_2 , a user may scroll through the alternate candidate words (e.g., as indicated by vertically-moving gesture indicator **1114**) to view the alternate candidate words. At time T_3 , the user selects a desired alternate candidate word (e.g., “tear”) to replace the selected candidate word that appears in the string. As a result, at time T_4 , the selected candidate word is replaced by the selected alternate candidate word. As illustrated, the selected alternate candidate word is not prominently displayed (e.g., the additional user interface items are not displayed and the other words in the string are no longer greyed out). In some embodiments, selection of an alternate candidate word may cause the alternate candidate word to swap places with the selected candidate word, such that the additional user interface items are still displayed and the alternate candidate word (now located within the string of candidate text) is prominently displayed relative to the other words in the string.

As described above, alternate candidate words **1112** may be presented above and below a selected candidate word, allowing a user to scroll through the list of alternate candidate words. In some embodiments, the height and/or touch sensing capabilities of a display may hinder the performance of such vertical scrolling gestures. FIG. **12** illustrates another example of presenting alternative candidate words. At time T_0 , a viewable portion of user interface **1202** includes a portion of a string of candidate text **1204**. At time T_1 (or some time between T_0 and T_1), a selection of one of

13

the candidate words in the string **1204** is input, as indicated by feedback indicator **1206** illustrated over the candidate word “test.” As illustrated at time T_1 , selection of a candidate word causes a plurality of user interface elements to be displayed, including an add word key **1208**, a delete word key **1210**, and alternate candidate words **1212**. In the example illustrated in FIG. **12**, the alternate candidate words are displayed horizontally across a top of the selected candidate word. It is to be understood that the placement of the alternate candidate words is exemplary in nature, and the alternate candidate words may be displayed at any suitable location in the user interface.

In some examples, a predetermined number of alternate candidate words (e.g., the second through fourth most-likely alternate candidate words identified by a word-level recognizer) may be displayed. Depending on the modality, the source of the alternate candidate words may vary. For example, if the text was generated by speech recognition, acoustic speech recognition candidates (e.g., from a word confusion network) may be utilized in addition to language model candidates. In other embodiments, all alternate candidate words may be viewable by horizontally scrolling through the displayed list of alternate candidate words (e.g., by providing a horizontal swiping gesture along a top of the display). At time T_2 , a user selects a desired alternate candidate word to replace the selected candidate word (e.g., as indicated by feedback indicator **1214**). In response, at time T_3 , the selected alternate candidate word replaces the selected candidate word.

FIG. **13** illustrates an example scenario of deleting a word in a string of candidate text. At time T_0 , a user interface **1302** includes a string **1304** that is displayed in a text editor **1306**. At time T_1 (or some time between T_0 and T_1), a selection of one of the candidate words in the string **1304** is provided as input, indicated by feedback indicator **1308** illustrated over the candidate word “test.” As illustrated at time T_1 , selection of a candidate word causes a plurality of user interface elements to be displayed. For example, an add word key **1310**, a delete word key **1312**, and alternate candidate words **1314** may be displayed. At time T_2 , delete word key **1312** is selected, as indicated by the feedback indicator **1316**. As a result, at time T_3 , the string of candidate text is presented without the selected candidate word (e.g., the word “test” is deleted). In some embodiments, the add word key **1310** may persist in the location of the deleted word in order to enable a user to quickly insert a word in the location of the deleted word.

FIG. **14** illustrates an example scenario of adding a word in a string of candidate text. At time T_0 , a user interface **1402** includes a string **1404** that is displayed in a text editor **1406**. At time T_1 (or some time period between T_0 and T_1), a selection of one of the candidate words in the string **1404** is provided as input, indicated by feedback indicator **1407** illustrated over the candidate word “test.” As illustrated at time T_1 , selection of a candidate word causes a plurality of user interface elements to be displayed. For example, an add word key **1408**, a delete word key **1410**, and alternate candidate words **1412** may be displayed. At time T_2 , add word key **1408** is selected, as indicated by the feedback indicator **1414**. As a result, at time T_3 , a virtual keyboard **1416** is displayed, enabling a user to begin entering characters to form a word to be inserted in front of the selected candidate word. In some embodiments, a keyboard layout selection or an input method selection may be presented to a user upon selection of the add word key **1408**, enabling the user to select the manner in which the additional word is to be input.

14

Text/character entry may be input via mechanisms other than touch input on virtual keyboards. For example, the text-entry device may include a microphone to capture voice input, which may be processed to generate recognized candidate words locally or remotely (e.g., via an on-board voice recognition/speech-to-text module within the text-entry device and/or via an off-board voice recognition/speech-to-text module within a computing device located remotely from the text-entry device and communicating with the text-entry device over a communication link such as a wireless communication link). In examples where a remote computing device is utilized to perform voice recognition, raw and/or partially processed voice data may be transmitted from the text-entry device and received by the remote computing device. After performing the voice recognition/speech-to-text processing, the remote computing device may transmit candidate word(s) to the text-entry device.

In some examples, the text-entry device may send raw and/or partially processed voice data to an external computing device (e.g., a smartphone or other mobile computing device, which may be within direct communication range of the text-entry device). The external computing device may perform some or no processing on the received voice data prior to sending the received and/or further processed voice data to a remote service via a network (e.g., a cloud computing device located remotely from the text-entry device and the external computing device). The remote service may convert the voice data received from the external computing device to text and/or perform additional processing and then return the text and/or additionally processed voice data to the external computing device. The external computing device may then forward the text and/or additionally processed voice data to the text-entry device.

FIG. **15** illustrates an example of providing voice input. At time T_0 , a user interface **1502** includes a microphone icon **1504** indicating that the user interface is accepting voice input. In a preview area **1506**, a placeholder visually represents voice data that is being captured. At time T_1 , a horizontal swiping gesture (e.g., as indicated by leftward moving feedback indicator **1508**) is performed to transition the user interface from the voice input region/state to a text editor. As described above with respect to FIG. **9**, a text editor of the user interface may be displayed at time T_2 , including a string of recognized candidate text. At time T_3 , the string may be dragged via a horizontal swiping gesture to enable viewing of additional text, and at time T_4 , the end of the string may be viewable responsive to the horizontal swiping gesture. In some implementations, a voice command or another type of user input may be used to transition to the text editor.

The voice input mode of the user interface as described above may be entered from any suitable region of the user interface. For example, the voice input mode may be an additional option in the keyboard layout selection menu described in FIG. **6**. The voice input mode may additionally or alternatively be accessed by swiping up or down while viewing a virtual keyboard, as described with respect to FIGS. **5A** and **5B** or by selecting an icon displayed while viewing a virtual keyboard. The voice input mode may additionally or alternatively be accessed within the text editor. For example, upon selection of a candidate word in a string of recognized candidate words, a key for providing voice input to replace the word may be displayed.

Additionally or alternatively, a handwriting, drawing, or shape-writing input mode may be selected via a displayed icon or menu option. The drawing input mode may enable a user to replace and/or enter characters/words by drawing

directly on the display with a finger, stylus, or other input device. In some embodiments, characters or shapes may be drawn on a display orientation that is different than the display orientation used for the text editor (e.g., text may be drawn in a portrait orientation and the text editor may be in a landscape orientation). The drawing input may include one or more touch inputs (e.g., a series of continuous touch inputs, each continuous touch input forming or representing a character or a portion of a character) to the display. The touch inputs and/or data corresponding to the touch inputs may be analyzed by the computing device that includes the display and/or may be transmitted to a remote computing device for processing to determine characters or words that correspond to the drawing input.

The determined characters or words may be added to a string of entered text and displayed in the text editor upon completing a drawing input session (e.g., responsive to exiting the drawing input mode). In some examples, the drawing input mode may utilize delimiters similarly to the virtual keyboard in order to trigger character or word recognition. For example, lifting a finger, pausing (e.g., not touching the display or maintaining contact with a single point of the display) for a time that exceeds a threshold, selecting a user interface element (e.g., an “end drawing mode” user interface element), or other delimiter input (e.g., a tap, a swipe gesture, and/or another suitable input) may trigger the character or word recognition of touch inputs received since a last delimiter input or the start of the drawing mode.

FIG. 16 shows a method 1600 of recognizing text input. Method 1600 may be performed by wrist-wearable computing device 100 of FIG. 1 or any other text-entry device capable of displaying a virtual keyboard.

At 1602, method 1600 includes presenting a virtual keyboard. As discussed above, the virtual keyboard may be presented to occupy substantially an entire display, thus allowing each key of the virtual keyboard to be as large as the display allows.

At 1604, method 1600 includes recognizing input. Such input may include key strokes (e.g., tap input) on the virtual keyboard, voice input, gaze input, gesture input, hardware button presses, or any other type of input recognizable by the text-entry device.

At 1606, if the recognized input is a command to leave the virtual keyboard, the method ends at 1608. Such a command may be a swipe or other input to toggle to a text editor, open another application, turn the text-entry device off, or perform another operation. If the recognized input is not a command to leave the virtual keyboard, the method advances to 1610.

At 1610, if the recognized input is a delimiter key, the method proceeds to 1612. If the recognized input is not a delimiter key, the method proceeds to 1614, where the detected input is optionally sent to an on-board or off-board word-level recognizer. As discussed below with reference to 1612, instead of sending each input after each input recognition, a plurality of inputs between successive delimiters may be bundled and sent together.

At 1616, method 1600 optionally includes displaying a placeholder with the virtual keyboard. When a placeholder is displayed, it may be an asterisk, bullet, or any other generic symbol that signals that a key has been input, but without distracting the user with a potentially wrong key. In some implementations, an actual letter or other symbol corresponding to the particular input may be used instead. The placeholder may be displayed responsive to the input not selecting any of the delimiter keys.

As indicated at 1618, the placeholder may replace a displayed word that corresponds to input before the last delimiter (i.e., the previous word). As indicated at 1620, a plurality of placeholders may be displayed together, such that each new input before a delimiter will add a new placeholder. In this way, the user can see that each touch input is being recognized. In some implementations, only a threshold number of placeholders will be displayed (e.g., the number of placeholders that will fit on the display without altering the virtual keyboard size or position). In some implementations, the placeholders and/or other aspects of the virtual keyboard page can flash or otherwise visually indicate when touch input is recognized. In some implementations, haptic feedback and/or other mechanisms may be used to signal touch input recognition to the user.

At 1612, method 1600 optionally includes bundling all key inputs between successive delimiter inputs and sending the bundle to an on-board or off-board word-level recognizer. Such bundling may reduce the number of communications necessary to convey the input, for example. Alternatively, as discussed above with reference to 1614, each input may be sent individually.

At 1622, method 1600 includes receiving a suggested candidate text from the word-level recognizer. At 1624, the received suggested candidate text is displayed with the virtual keyboard. This new suggested candidate text replaces any candidate text from a previous word or any placeholder(s) for the current word (e.g., all currently displayed placeholders) responsive to the input selecting one of the delimiter keys. In this way, at most one word is displayed with the keyboard at any given time. As such, the keyboard need not be made smaller to accommodate a larger area for displaying entered text with the virtual keyboard. As indicated at 1626, the displayed candidate text may be truncated so that a portion of a displayed word bleeds off the edge of the display. Alternatively, a size of the candidate text may be reduced so that an entire word fits on the display with the virtual keyboard.

In some examples, in addition to or as an alternative to replacing placeholders with the candidate text, the new suggested candidate text may be temporarily displayed over the keyboard. For example, the new suggested candidate text may be displayed over the keyboard in a semi-transparent manner and/or the keyboard may be faded (e.g., in a similar manner to the fading described above with respect to times T_0 - T_3 in FIG. 3) during display of the new suggested candidate text. The new suggested candidate text may have a uniform size, regardless of the number of characters in the text (e.g., resulting in selective truncation as described above with respect to the text replacing the placeholders) in some examples. In other examples, the candidate text may be zoomed/stretched and/or shrunk to fit the screen size.

The methods and processes described herein are tied to a computing system of one or more computing devices. In particular, such methods and processes may be implemented as a computer-application program or service, an application-programming interface (API), a library, and/or other computer-program product.

FIG. 17 schematically shows a non-limiting embodiment of a computing system 1700 that can enact one or more of the methods and processes described above. Computing system 1700 is shown in simplified form. Computing system 1700 may take the form of one or more text-entry devices and/or cooperating computing devices, which may take the form of wearable computing devices, mobile computing devices, mobile communication devices (e.g., smart phone), personal computers, server computers, tablet computers,

home-entertainment computers, network computing devices, gaming devices, and/or other computing devices.

Computing system **1700** includes a logic machine **1702** and a storage machine **1704**. Computing system **1700** may optionally include a display subsystem **1706**, input subsystem **1708**, communication subsystem **1710**, and/or other components not shown in FIG. **17**.

Logic machine **1702** includes one or more physical devices configured to execute instructions. For example, the logic machine may be configured to execute instructions that are part of one or more applications, services, programs, routines, libraries, objects, components, data structures, or other logical constructs. Such instructions may be implemented to perform a task, implement a data type, transform the state of one or more components, achieve a technical effect, or otherwise arrive at a desired result.

The logic machine may include one or more processors configured to execute software instructions. Additionally or alternatively, the logic machine may include one or more hardware or firmware logic machines configured to execute hardware or firmware instructions. Processors of the logic machine may be single-core or multi-core, and the instructions executed thereon may be configured for sequential, parallel, and/or distributed processing. Individual components of the logic machine optionally may be distributed among two or more separate devices, which may be remotely located and/or configured for coordinated processing. Aspects of the logic machine may be virtualized and executed by remotely accessible, networked computing devices configured in a cloud-computing configuration.

Storage machine **1704** includes one or more physical devices configured to hold instructions executable by the logic machine to implement the methods and processes described herein. When such methods and processes are implemented, the state of storage machine **1704** may be transformed e.g., to hold different data.

Storage machine **1704** may include removable and/or built-in devices. Storage machine **1704** may include optical memory (e.g., CD, DVD, HD-DVD, Blu-Ray Disc, etc.), semiconductor memory (e.g., RAM, EPROM, EEPROM, etc.), and/or magnetic memory (e.g., hard-disk drive, floppy-disk drive, tape drive, MRAM, etc.), among others. Storage machine **1704** may include volatile, nonvolatile, dynamic, static, read/write, read-only, random-access, sequential-access, location-addressable, file-addressable, and/or content-addressable devices.

It will be appreciated that storage machine **1704** includes one or more physical devices. However, aspects of the instructions described herein alternatively may be propagated by a communication medium (e.g., an electromagnetic signal, an optical signal, etc.) that is not held by a physical device for a finite duration.

Aspects of logic machine **1702** and storage machine **1704** may be integrated together into one or more hardware-logic components. Such hardware-logic components may include field-programmable gate arrays (FPGAs), program- and application-specific integrated circuits (ASIC/ASICs), program- and application-specific standard products (PSS/ASSPs), system-on-a-chip (SOC), and complex programmable logic devices (CPLDs), for example.

The terms “module,” “program,” and “engine” may be used to describe an aspect of computing system **1700** implemented to perform a particular function. In some cases, a module, program, or engine may be instantiated via logic machine **1702** executing machine-readable instructions held by storage machine **1704**. It will be understood that different modules, programs, and/or engines may be instantiated from

the same application, service, code block, object, library, routine, API, function, etc. Likewise, the same module, program, and/or engine may be instantiated by different applications, services, code blocks, objects, routines, APIs, functions, etc. The terms “module,” “program,” and “engine” may encompass individual or groups of executable files, data files, libraries, drivers, scripts, database records, etc.

It will be appreciated that a “service”, as used herein, is an application program executable across multiple user sessions. A service may be available to one or more system components, programs, and/or other services. In some implementations, a service may run on one or more server-computing devices.

When included, display subsystem **1706** may be used to present a visual representation of data held by storage machine **1704**. This visual representation may take the form of a graphical user interface (GUI). As the herein described methods and processes change the data held by the storage machine, and thus transform the state of the storage machine, the state of display subsystem **1706** may likewise be transformed to visually represent changes in the underlying data. Display subsystem **1706** may include one or more display devices utilizing virtually any type of technology. Such display devices may be combined with logic machine **1702** and/or storage machine **1704** in a shared enclosure, or such display devices may be peripheral display devices.

When included, input subsystem **1708** may comprise or interface with one or more user-input devices such as a keyboard, mouse, touch screen, or game controller. In some embodiments, the input subsystem may comprise or interface with selected natural user input (NUI) componentry. Such componentry may be integrated or peripheral, and the transduction and/or processing of input actions may be handled on- or off-board. Example NUI componentry may include a microphone for speech and/or voice recognition; an infrared, color, stereoscopic, and/or depth camera for machine vision and/or gesture recognition; a head tracker, eye tracker, accelerometer, and/or gyroscope for motion detection and/or intent recognition; as well as electric-field sensing componentry for assessing brain activity.

When included, communication subsystem **1710** may be configured to communicatively couple computing system **1700** with one or more other computing devices. Communication subsystem **1710** may include wired and/or wireless communication devices compatible with one or more different communication protocols. As non-limiting examples, the communication subsystem may be configured for communication via a wireless telephone network, or a wired or wireless local- or wide-area network. In some embodiments, the communication subsystem may allow computing system **1700** to send and/or receive messages to and/or from other devices via a network such as the Internet.

An example provides a method of providing a user interface on a computing device, the method comprising presenting a virtual keyboard on a display of the computing device, detecting input to the virtual keyboard, and, for each detected input, determining whether the input selects any of one or more delimiter keys, displaying a placeholder for the input responsive to the input not selecting any of the one or more delimiter keys, and receiving suggested candidate text from a word-level recognizer and replacing all currently displayed placeholders with the suggested candidate text responsive to the input selecting any of the one or more delimiter keys. In such an example, each detected input may additionally or alternatively be sent to the word-level rec-

ognizer responsive to detecting the input to the virtual keyboard. In such an example, the computing device may additionally or alternatively be a first computing device, and the word-level recognizer may additionally or alternatively be included in a second computing device, remote from the first computing device and communicating with the first computing device via a wireless communication link. In such an example, displaying the placeholder for the input may additionally or alternatively comprise incrementing a number of placeholders displayed if a maximum number of placeholders are not displayed and maintaining the number of placeholders displayed if the maximum number of placeholders are displayed. In such an example, detecting input to the virtual keyboard may additionally or alternatively comprise detecting tap inputs to the virtual keyboard, and the method may additionally or alternatively comprise detecting a slide input and transitioning from displaying the virtual keyboard to displaying a different portion of the user interface responsive to the slide input. In such an example, displaying the different portion of the user interface may additionally or alternatively comprise displaying a keyboard selection menu. In such an example, displaying the different portion of the user interface may additionally or alternatively comprise displaying a text editor, the text editor presenting a list of previously-received suggested candidate text. In such an example, transitioning from displaying the virtual keyboard to displaying the different portion of the user interface may additionally or alternatively comprise shifting a portion of the virtual keyboard out of a displayable region of the user interface and shifting the different portion of the user interface into the displayable region of the user interface. In such an example, replacing all currently displayed placeholders with the suggested candidate text may additionally or alternatively comprise showing only a portion of the candidate text on a displayable region of the user interface if a length of the candidate text is greater than a threshold. Any or all of the above-described examples may be combined in any suitable manner in various implementations.

Another example provides a computing device comprising a touch display device having a top edge and a bottom edge, a logic machine, and a storage machine. In such an example, the storage machine may hold instructions executable by the logic machine to present a virtual keyboard on the touch display without a previously-entered text-editing area between the virtual keyboard and the top edge and without a text-editing area between the virtual keyboard and the bottom edge, generate recognized words based on input to the virtual keyboard, and, responsive to a show-text-editor input, transition from displaying the virtual keyboard to displaying a text editor without the virtual keyboard, the text editor presenting the recognized words. In such an example, the transition may additionally or alternatively comprise a panning of the user interface, and a portion of the virtual keyboard may additionally or alternatively be displayed alongside a portion of the text editor in a displayable region of the user interface during the transition. In such an example, presenting the virtual keyboard may additionally or alternatively comprise presenting a top row of keys of the virtual keyboard in a top third of the touch display device, presenting a middle row of keys of the virtual keyboard in a middle third of the touch display device, and presenting a bottom row of keys of the virtual keyboard in a bottom third of the touch display device. In such an example, generating recognized words based on input to the virtual keyboard may additionally or alternatively comprise detecting input to the virtual keyboard, and, for each detected input, determin-

ing whether the input selects any of one or more delimiter keys, displaying a placeholder for the input responsive to the input not selecting any of the one or more delimiter keys, and receiving suggested candidate text from a word-level recognizer and replacing all currently displayed placeholders with the suggested candidate text responsive to the input selecting any of the one or more delimiter keys. In such an example, each detected input may additionally or alternatively be sent to the word-level recognizer responsive to detecting the input to the virtual keyboard. In such an example, the word-level recognizer may additionally or alternatively be included in a remote computing device, and the remote computing device may additionally or alternatively communicate with the computing device via a wireless communication link. In such an example, displaying the placeholder for the input may additionally or alternatively comprise incrementing a number of placeholders displayed if a maximum number of placeholders are not displayed and maintaining the number of placeholders displayed if the maximum number of placeholders are displayed. In such an example, the show-text-editor input may additionally or alternatively comprise a slide input. In such an example, the computing device may additionally or alternatively comprise a microphone, and recognized words may additionally or alternatively be generated responsive to voice input detected by the microphone. Any or all of the above-described examples may be combined in any suitable manner in various implementations.

Another example provides a wrist-wearable computing device comprising a touch display device having a top edge and a bottom edge, a logic machine, and a storage machine. The storage machine may hold instructions executable by the logic machine to present a virtual keyboard on the touch display without a previously-entered text-editing area between the virtual keyboard and the bottom edge, detect input to the virtual keyboard, and, for each detected input, determine whether the input selects any of one or more delimiter keys, display a placeholder for the input responsive to the input not selecting any of the one or more delimiter keys, and receive suggested candidate text from a word-level recognizer and replacing all currently displayed placeholders with the suggested candidate text responsive to the input selecting any of the one or more delimiter keys. The storage machine may additionally or alternatively hold instructions executable by the logic machine to, responsive to a show-text-editor input, transition from displaying the virtual keyboard to displaying a text editor without the virtual keyboard, the text editor presenting previously-entered text formed from previously-received suggested candidate text. In such an example, each detected input may additionally or alternatively be sent to the word-level recognizer responsive to detecting the input to the virtual keyboard. Any or all of the above-described examples may be combined in any suitable manner in various implementations.

It will be understood that the configurations and/or approaches described herein are exemplary in nature, and that these specific embodiments or examples are not to be considered in a limiting sense, because numerous variations are possible. The specific routines or methods described herein may represent one or more of any number of processing strategies. As such, various acts illustrated and/or described may be performed in the sequence illustrated and/or described, in other sequences, in parallel, or omitted. Likewise, the order of the above-described processes may be changed.

21

The subject matter of the present disclosure includes all novel and non-obvious combinations and sub-combinations of the various processes, systems and configurations, and other features, functions, acts, and/or properties disclosed herein, as well as any and all equivalents thereof.

The invention claimed is:

1. A wrist-wearable computing device comprising:
a wrist band; and
a compute module attached to the wrist band, the compute module including a touch display, a logic machine, and a storage machine holding instructions executable by the logic machine to:
present a virtual keyboard on the touch display;
receive touch input to the virtual keyboard without presenting a letter-by-letter reproduction of keyboard-entered text in an area between a top of the virtual keyboard and an upper perimeter of the touch display;
recognize a word based on the touch input to the virtual keyboard; and
present the recognized word in a preview area adjacent to the virtual keyboard on the touch display.
2. The wrist-wearable computing device of claim 1, wherein the preview area is adjacent to a right side of the virtual keyboard.
3. The wrist-wearable computing device of claim 1, wherein the preview area is adjacent to a side of the virtual keyboard.
4. The wrist-wearable computing device of claim 1, wherein the preview area is adjacent to a bottom side of the virtual keyboard.
5. The wrist-wearable computing device of claim 1, wherein the recognized word is a candidate word that a word-level recognizer determines to be the most likely word based on the received touch inputs.
6. The wrist-wearable computing device of claim 5, wherein the candidate word replaces a previous candidate word previously presented on the touch display based on previous touch inputs.
7. The wrist-wearable computing device of claim 5, wherein the candidate word is added to a text editor area responsive to touch input to the candidate word.
8. The wrist-wearable computing device of claim 7, wherein the touch input to the virtual keyboard comprises tap inputs to the virtual keyboard, and wherein the storage machine holds instructions executable by the logic machine to receive a slide input to the touch display and transition from presenting the virtual keyboard to presenting the text editor area on the touch display responsive to the slide input.
9. The wrist-wearable computing device of claim 1, wherein the storage machine holds instructions executable by the logic machine to transition from presenting the virtual keyboard to presenting the recognized word without the virtual keyboard.
10. A method of providing a user interface on a wrist-wearable computing device, the method comprising:
presenting a virtual keyboard on a touch display of the wrist-wearable computing device without presenting keyboard-entered text in an area between a top of the virtual keyboard and an upper perimeter of the touch display;

22

- receiving touch input to the virtual keyboard without presenting a letter-by-letter reproduction of keyboard-entered text in the area between the top of the virtual keyboard and the upper perimeter of the touch display;
recognizing a word based on the touch input to the virtual keyboard; and
presenting the recognized word in a preview area adjacent to the virtual keyboard on the touch display.
11. The method of claim 10, wherein the preview area is adjacent to a right side of the virtual keyboard.
 12. The method of claim 10, wherein the preview area is adjacent to a side of the virtual keyboard.
 13. The method of claim 10, wherein the preview area is adjacent to a bottom side of the virtual keyboard.
 14. The method of claim 10, wherein the recognized word is a candidate word that a word-level recognizer determines to be the most likely word based on the received touch inputs.
 15. The method of claim 14, wherein the candidate word replaces a previous candidate word previously presented on the touch display based on previous touch inputs.
 16. The method of claim 14, wherein the candidate word is added to a text editor area responsive to touch input to the candidate word.
 17. The method of claim 16, wherein the touch input to the virtual keyboard comprises tap inputs to the virtual keyboard, and wherein the method further comprising receiving a slide input to the touch display and transitioning from presenting the virtual keyboard to presenting the text editor area on the touch display responsive to the slide input.
 18. The method of claim 10, further comprising transitioning from presenting the virtual keyboard to presenting the recognized word without the virtual keyboard.
 19. A wrist-wearable computing device comprising:
a wrist band; and
a compute module attached to the wrist band, the compute module including a touch display, a logic machine, and a storage machine holding instructions executable by the logic machine to:
present a virtual keyboard on the touch display without presenting keyboard-entered text in an area between a top of the virtual keyboard and an upper perimeter of the touch display;
receive touch input to the virtual keyboard without presenting a letter-by-letter reproduction of keyboard-entered text in the area between the top of the virtual keyboard and the upper perimeter of the touch display;
recognize a word based on the touch input to the virtual keyboard; and
present the recognized word in a preview area positioned to a side of the virtual keyboard on the touch display.
 20. The wrist-wearable computing device of claim 19, wherein the storage machine holds instructions executable by the logic machine to transition from presenting the virtual keyboard to presenting the recognized word without the virtual keyboard.