



US010731793B2

(12) **United States Patent**
Zrim et al.

(10) **Patent No.:** **US 10,731,793 B2**
(45) **Date of Patent:** **Aug. 4, 2020**

(54) **TANK CONTAINER FOR TRANSPORT AND STORAGE OF CRYOGENIC LIQUEFIED GASES**

(71) Applicants: **Aerogel CARD d.o.o.**, Ljubljana (SI);
Aspen Aerogels, Inc., Northborough,
MA (US)

(72) Inventors: **Milan Zrim**, Ljubljana (SI); **Mihael Gruden**, Ljubljana (SI)

(73) Assignees: **Aspen Aerogels, Inc.**, Northborough,
MA (US); **Aerogel CARD d.o.o.**,
Ljubljana (SI)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/992,171**

(22) Filed: **Jan. 11, 2016**

(65) **Prior Publication Data**

US 2016/0123533 A1 May 5, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/377,629, filed as
application No. PCT/EP2013/052559 on Feb. 8,
2013, now Pat. No. 9,488,313.

(30) **Foreign Application Priority Data**

Feb. 10, 2012 (SI) 201200040

(51) **Int. Cl.**

F17C 1/12 (2006.01)

F17C 5/02 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F17C 5/02** (2013.01); **F17C 3/022**
(2013.01); **F17C 3/04** (2013.01); **F17C 13/001**
(2013.01);

(Continued)

(58) **Field of Classification Search**

CPC .. **F17C 5/02**; **F17C 13/001**; **F17C 2205/0192**;
F17C 2201/0109; **F17C 2201/032**;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,188,007 A 1/1940 Kistler
3,101,861 A 8/1963 Mearns et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 1165624 B 3/1964
DE 10302394 A1 12/2004
DE 102008052877 A1 4/2010

Primary Examiner — J. Gregory Pickett


Assistant Examiner — Niki M Eloshway

(74) *Attorney, Agent, or Firm* — Christopher Stow;
Poongunran Muthukumaran

(57) **ABSTRACT**

The invention relates to a tank container (100; 100') for the transport and storage of cryogenic liquefied gas, comprising a framework (120) and a cylindrical vessel (110) connected to the frames work (120), wherein the vessel (110) is covered by a superinsulation arrangement (130) based on an aerogel composition, and the vessel (110) is connected to the framework (120) by a clamping device (30) which is adapted to allow for a relative movement between the framework (120) and the vessel (110) due to thermal expansion or contraction of the vessel (110).

16 Claims, 8 Drawing Sheets



US 10,731,793 B2

Page 2

(51)	Int. Cl.		4,065,019	A	12/1977	Letourneur et al.	
	<i>F17C 13/00</i>	(2006.01)	4,354,612	A *	10/1982	Pelabon B65D 88/128 206/591	
	<i>F17C 3/02</i>	(2006.01)					
	<i>F17C 3/04</i>	(2006.01)	4,363,738	A	12/1982	Kummermehr	
	<i>F17C 1/00</i>	(2006.01)	4,447,345	A	5/1984	Kummermehr et al.	
(52)	U.S. Cl.		4,481,778	A	11/1984	Reinker et al.	
	CPC	<i>F17C 2201/0109</i> (2013.01);	4,619,908	A	10/1986	Cheng et al.	
		<i>F17C 2201/032</i> (2013.01); <i>F17C 2201/035</i>	4,667,417	A	5/1987	Graser et al.	
		(2013.01); <i>F17C 2201/054</i> (2013.01); <i>F17C</i>	4,717,708	A	1/1988	Cheng et al.	
		<i>2203/03</i> (2013.01); <i>F17C 2203/0308</i>	5,124,101	A	6/1992	Hirao et al.	
		(2013.01); <i>F17C 2203/0325</i> (2013.01); <i>F17C</i>	5,275,796	A	1/1994	Tillotson et al.	
		<i>2203/0329</i> (2013.01); <i>F17C 2203/0629</i>	5,306,555	A	4/1994	Ramamurthi et al.	
		(2013.01); <i>F17C 2203/0643</i> (2013.01); <i>F17C</i>	5,464,116	A	11/1995	Aoki et al.	
		<i>2203/0697</i> (2013.01); <i>F17C 2205/013</i>	5,565,142	A	10/1996	Deshpande et al.	
		(2013.01); <i>F17C 2205/0107</i> (2013.01); <i>F17C</i>	5,786,059	A	7/1998	Frank et al.	
		<i>2205/0126</i> (2013.01); <i>F17C 2205/0192</i>	5,789,075	A	8/1998	Frank et al.	
		(2013.01); <i>F17C 2205/0332</i> (2013.01); <i>F17C</i>	5,830,387	A	11/1998	Yokogawa et al.	
		<i>2209/221</i> (2013.01); <i>F17C 2221/011</i>	5,866,027	A	2/1999	Frank et al.	
		(2013.01); <i>F17C 2221/013</i> (2013.01); <i>F17C</i>	5,962,539	A	10/1999	Perrut et al.	
		<i>2221/014</i> (2013.01); <i>F17C 2221/016</i>	5,972,254	A	10/1999	Sander	
		(2013.01); <i>F17C 2221/033</i> (2013.01); <i>F17C</i>	5,973,015	A	10/1999	Coronado et al.	
		<i>2223/0161</i> (2013.01); <i>F17C 2223/033</i>	6,068,882	A	5/2000	Ryu	
		(2013.01); <i>F17C 2250/043</i> (2013.01); <i>F17C</i>	6,080,475	A	6/2000	Frank et al.	
		<i>2250/0408</i> (2013.01); <i>F17C 2250/0626</i>	6,083,619	A	7/2000	Frank et al.	
		(2013.01); <i>F17C 2260/012</i> (2013.01); <i>F17C</i>	6,087,407	A	7/2000	Coronado et al.	
		<i>2260/013</i> (2013.01); <i>F17C 2260/033</i>	6,140,377	A	10/2000	Schwertfeger et al.	
		(2013.01); <i>F17C 2270/0102</i> (2013.01); <i>F17C</i>	6,187,250	B1	2/2001	Champagne	
		<i>2270/0165</i> (2013.01); <i>F17C 2270/0173</i>	6,197,270	B1	3/2001	Sonada et al.	
		(2013.01)	6,479,416	B1	11/2002	Frank et al.	
	(58)	Field of Classification Search		6,620,355	B1	9/2003	Schmidt
		CPC	<i>F17C 2201/035</i> ; <i>F17C 2201/054</i> ; <i>F17C</i>	6,656,527	B1	12/2003	Gessner et al.
			<i>2206/012</i> ; <i>F17C 2260/013</i> ; <i>F17C</i>	6,670,402	B1	12/2003	Lee et al.
			<i>2260/033</i> ; <i>F17C 2270/0102</i> ; <i>F17C</i>	6,770,584	B2	8/2004	Barney et al.
			<i>2270/0135</i> ; <i>F17C 2203/03</i> ; <i>F17C</i>	6,887,563	B2	5/2005	Frank et al.
			<i>2250/0408</i> ; <i>F17C 2250/043</i> ; <i>F17C</i>	6,989,123	B2	1/2006	Lee et al.
			<i>2250/0626</i>	7,078,359	B2	7/2006	Stepanian et al.
		USPC	220/560.12, 592.2, 560.1, 560.05, 562	7,399,439	B2	7/2008	Lee et al.
		See application file for complete search history.		7,504,346	B2	3/2009	Stepanian et al.
				7,780,890	B2	8/2010	Lee et al.
				8,214,980	B2	7/2012	Bullock et al.
			2003/0029877	A1	2/2003	Mathur et al.	
			2006/0096185	A1	5/2006	Dhellemmes et al.	
			2007/0007962	A1	1/2007	Mraz et al.	
(56)		References Cited		2007/0152363	A1	7/2007	Begag et al.
			2007/0228045	A1	10/2007	Goldbach et al.	
			2008/0307798	A1	12/2008	Luo et al.	
			2010/0146992	A1	6/2010	Miller et al.	
			2011/0031861	A1	2/2011	Gentry et al.	
			2012/0097907	A1	4/2012	Bauer et al.	
			2014/0166663	A1	6/2014	Sele et al.	
	U.S. PATENT DOCUMENTS						
		3,583,352	A	6/1971	Alleaume et al.		
		4,038,832	A	8/1977	Lutgen et al.		
						* cited by examiner	




Fig. 1




Fig. 2




Fig. 3




Fig. 4






Fig. 5






Fig. 6c




Fig. 6d




Fig. 7a




Fig. 7b




Fig. 8




Fig. 9




Fig. 10




Fig. 11

TANK CONTAINER FOR TRANSPORT AND STORAGE OF CRYOGENIC LIQUEFIED GASES

CROSS-REFERENCES TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/377,629, filed Aug. 8, 2014; which is a National Stage Application under 35 U.S.C. § 371 of PCT/EP2013/052559 filed on Feb. 8, 2013; which claims priority to the Slovenian International Patent Application SI201200040 filed on Feb. 10, 2012; all of which are hereby incorporated by reference in their entirety as if fully set forth.

DESCRIPTION

The invention relates to the development of cryogenic equipment for transport and storage of liquefied gases where the family of cryogenic equipment for transport and storage consist of horizontal and vertical vessels and transportable-mobile equipment in ISO containers. The invention specifically relates to a tank container for the transport and storage of cryogenic liquefied gas, comprising a framework and a cylindrical vessel connected to the framework.

KNOWN STATE OF DEVELOPMENT

The current existing technological solutions based on technologies of performance of traditional insulation, which are also applicable in other insulation applications, such as the use of vacuum insulated cryogenic vessels with applications to storage and transport containers and expanded foam, expanded glass, perlite and similar inorganic materials. The traditional insulation of cryogenic tanks is considered to still require a significant low vacuum for successful operation. Insulation based on nanostructure gels has already achieved in atmospheric pressure values of insulation, which are better than in comparable existing materials, but the available potential and properties that are not to be found in conventional materials is exploited in this application.

Cryogenic gases are stored in liquid form at extremely low temperatures. Fields of application are expanding along with increased technological possibilities in the industry and energy supply. Of the liquefied gas used most are liquefied natural gas, liquefied nitrogen, liquefied oxygen, argon and CO₂. The temperature of liquefied gas goes down to -196° C. (liquid nitrogen—LIN), oxygen (LOX) and argon (LAR), natural gas (LNG) at -163° C., carbon dioxide (LCO₂) is the warmest with temperatures ranging from -40° C. down to -80° C.

The introduction of the liquefied methane industry in the supply system and group of consumers in some countries of the world (Brazil, Indonesia) achieved a remarkable delivery volume. Expansion of gas pipeline network is capital intensive and is difficult in areas with low consumption population density; the supply of liquefied gas provides the introduction of gas in areas where the supply pipeline is possible only after a long period of growth in consumption. Introducing the use of liquefied natural gas in transport would significantly reduce the pressure on the market of liquid fuels. The presence of such equipment solutions on the market facilitates the development of such means of transport and facilitates the issue of pollution from particulates and pollutant gases in urban and densely populated regions,

where the work force carry out hundreds of kilometers of journeys per day. The supply of natural gas as an energy provider has taken place so far exclusively through primary, secondary and tertiary networks of gas pipelines. Construction of gas pipelines is capital intensive and requires at least a basic supply of gas to enough powerful customers. This condition is unavailable in many locations in a real short time. Alternative in this regard is the introduction of LNG in smaller tanks, which would provide for such monthly consumption at the specified location (a small industry or residential area) for the supply of liquefied gas would need modified mobile containers for the transport of liquefied gas to the local reservoirs.

For storage and transport of liquefied gases have hitherto been used tanks or tank containers with superinsulation features (thermal conductivity of the insulation material below 0.020 W/mK) realized by a double-vessel design wherein the space between the two vessels is vacuumed. Production of such double container and vacuuming of the dead space is technologically very demanding and expensive. Thus, the container must be serviced annually for vacuuming dead space, which can last several weeks, while all the time necessary for restoring the insulation the tank is useless.

The underlying problem of the present invention is therefore to provide a transport or storage tank, specifically a tank container for cryogenic gases like LNG, LOX, LIN or LAR, which allows for a high transport capacity, a low tare weight, a superinsulation arrangement with low maintenance and a simple structural design suitable for a high temperature difference between the tank vessel and the framework.

SUMMARY OF THE INVENTION

This problem is solved by a tank container according to claim 1. Such a tank container for the transport and storage of cryogenic liquefied gas, comprises a framework and a cylindrical vessel connected to the framework, wherein the vessel is covered by a superinsulation arrangement based on an aerogel composition, and the vessel is connected to the framework by an insulating clamping device which is adapted to allow for a relative movement between the framework and the vessel due to thermal expansion or contraction of the vessel.

Further embodiments of the present invention are indicated in the claims 2 to 15, the following description and the drawings.

ADVANTAGES OF THE INVENTION

The equipment based on the invention differs from the current solutions in the technology of insulation: The insulation is improved, the storage time is prolonged, manufacturing times are shortened, reduced material in quantity and the need for vacuum as the traditional technology of insulation is eliminated.

The introduction of new technologic procedures, new materials and new composites contribute to the solution of technological difficulties, which are not satisfactorily resolved (thermal bridges on supports, losses on functional piping and valves, etc.). In the production significant time is saved due to shorter timing between manufacturing operations. The vacuum insulated vessel requires needs two shells—an outer and an inner shell capable of operation under pressure conditions. The result is double quantity of material and at least double mass of the vessel. The manufacture of two complex vessels takes at least double time

(the cryo temperature set due to exquisite complexity range the highest requirements). Also the process of establishing vacuum is slow, and the problem of maintaining vacuum remains. A great portion of time dedicated in the production of vacuum insulated vessels is necessary for the vacuuming process. In addition to this the vacuum through time is lost and regular vacuuming is necessary. The established solutions require repeated vacuuming every 290 to 365 days. The process of vacuuming takes some 250 to 550 hours. The vessel insulated with the solution presented in the innovation can be manufactured in shorter time—a single pressure vessel, lighter—the mechanical protection is one tenth of the vacuum protection, less sensitive to mechanical and fire loads.

The developed procedures allow significant saving in material with the lighter vessel shell, faster installation of the insulation and better control over local deviations, the possibility of insulation of connecting piping all contribute to evaporation rates under 0.38% of full load per day.

The installation of cryogenic vessels in container frames enables multimodal transport within the scope of ADR (road) and RID (rail) and IMDG (sea). Such an implementation can relieve the road transportation and enable access to specific locations.

DESCRIPTION OF THE INVENTION

The cryogenic insulation is suitable for cryo temperatures and also demonstrates in case of flammable gases fire resistance. During the filling the liquefied gas at temperature of gas -186°C . (LIN) to -161°C . (LNG) at ambient pressure. During transport or longer storage the temperature would raise to -135°C ., and the pressure in the vessel rises to 6 bars due to heat transfer from the ambient through the insulation. This is the limited pressure where the safety relief valves start to operate or we need to direct the gas to immediate consumption. The insulation is very important for the function of the tank. For the stationary storage tanks the quantity of evaporated gas in a period of time is limited with losses under 0.38% of full load. The evaporation value is determined based on trial operation.

The insulation of vessels with a modern and innovative insulating material based on nanostructure gels based on aerogel material according to the invention avoids the disadvantages of vacuum insulation. High-tech nano-insulation has extremely good insulating properties. Base material formed aerogel, which has in its structure of nano-size pores, which trap molecules of air, which eliminates nearly three modes of heat transfer-convection, -conduction and -radiation and are also flame-retardant. At the same time the material is mechanically stable at temperatures down to -200°C . These properties in the other traditional insulation materials are not common.

The development of vessels with insulation based on nanostructure gels enables the elimination of vacuum. The advantages are directly in the field of the inner and outer vessel shell, both are significantly lighter in weight that means:

The direct material saving for a CRYOTAINER 34000 LNG/40' example is some 10.000 kg. This results in more freight with one shipment. It allows for faster production procedures for material preparation and shorter time for production.

Prefabrication of insulation material with a specialized work group can reduce the insulation time and the overall finalization of products.

The heat transfer from the ambient to the liquefied gas presents a difficulty, a portion of liquefied gas in the vessel is evaporating, and introduction of efficient insulation is

essential. The introduction of innovative solutions based on nanostructure insulation materials provides also properties other than insulation alone. These required properties are resistance to low temperatures, fire resistance, light weight, water repellence, vapor permeability and adequate handling qualities.

The new technology allows for significant savings on material and time of production, and in addition offers safety. In case of mechanical damage of the outer shell in nanostructure insulation prevents in contrast to conventional vacuum continuous heat shielding and prevents immediate evaporation in case of vacuum collapse and extends by a multiplier the available time for salvage. In vacuum vessels the damage causes immediate rise of pressure in the vacuum to the level of the atmosphere. With the rising pressure the vacuum loses its insulating properties and very fast evaporation of liquefied gas takes place.

In case of direct fire exposure the new technology of insulation prevents any rise of temperature in the media for at least 120 minutes.

The family of cryogenic vessels for transport and storage of liquefied gases is composed of stationary horizontal vessels of 8600 to 27000 liters. In addition to the horizontal there is a family of vertical vessels with 8600 to 15000 liters. The family of transportable (intermodal) vessels in ISO container frames is two models with 16800 and 32600 liter volume.

The pressure vessel is composed of an inner shell and an outer coat. The intermediate space is filled with a combination of insulating materials. The insulation from inside towards outside is composed 5 from four to seven 10 mm thick layers of cryogenic protection (in total from 80 to 140 mm) made of nanostructure insulating material (based on aerogel). Every layer is compressed with bands, so that there is no space for air in between. After four or seven layers there is a thermal shrink foil 10 of 0.038 to 0.12 mm thick. This shrink foil has the role of a vapor barrier. The next four to seven layers of insulation are installed. Every layer is compressed with bands. The next thermo shrink foil 10 is installed. Toward the outer coat of the vessel expanded insulation foam (thickness 30 to 50 mm) has to fill out the voids resulting from the deviations between the outer shape and the piping installations. Directly under the outer coat there is 6 to 18 mm fire protection. The introduction of insulation with at least 120 minute fire resistance presents an additional contribution to fire damage risk.

Existing vacuum insulated tanks have an outer shell made of construction steel 1 Omm thick and reinforced with U profiles in order to prevent the collapse due to outer pressure. In the project developed nanostructure insulated vessels have an outer coat of only 1 mm thickness of stainless steel. The intermodal unit CRYOTAINER 34000LNG/40' is some 10.000 kg lighter than comparable tanks with vacuum insulation. The difference in environmental load in the manufacture is significant it saves 10000 kg of steel and eliminates also the emissions to the environment derived from steel production. In stable units the difference is equal depending on the size of the vessel.

The stationary tanks are intended to replace the liquefied petrol gas (LPG) that is in production directly connected to the available crude oil production. This product enables direct replacement on the market in municipal areas where there are no conditions established for a pipeline connection.

Embodiments, implementation cases, features and further details of the present invention are explained in the following on the basis of the drawings in which:

5

FIG. 1 shows perspective views of a first embodiment of a tank container according to the present invention (Unit CRYOTAINER 34000 LNG/40');

FIG. 2 shows perspective views of a second embodiment of a tank container according to the present invention (Unit CRYOTAINER 16800 LNG/20');

FIG. 3 shows perspective views of an embodiment of a storage container (Vertical stable unit CARD 8600 LNG);

FIG. 4 shows a further embodiment of a storage container (Horizontal stationary unit CARD 15600 LNG);

FIG. 5 shows the tank container of FIG. 2 including the arrangements of supports in the frame without the insulation;

FIG. 6a to d show details of the support structure of the tank container shown in FIGS. 1, 2 and 5;

FIG. 7a, b show in a schematic manner the nanostructure insulation arrangement on the stationary horizontal tank shown in FIG. 3 also realized on the tank container according to the present invention;

FIG. 8 shows a further detail of the insulation arrangement of FIG. 7a, b;

FIG. 9 shows in a schematic manner a further embodiment of a support structure for a tank container according to the present invention;

FIG. 10 shows a perspective view of a support structure according to FIG. 6c; and

FIG. 11 shows a detail of a support structure.

IMPLEMENTATION CASE 1

»Intermodal« tank container unit **100** CRYOTAINER 34000 LNG/40' (FIG. 1) is intended for the long range transportation of liquefied natural gas and is assembled of two horizontal vessels **110** of 16.800 liter clamped into a standard frame **120** for a 40-foot (~12 m long; in the following text as 40') container.

Each pressure vessel **110** is horizontally embedded in the standard ISO 40' container frame **120'**. The pressure vessel **110** is defined of an internal shell **12** which is covered by an external insulation coating formed by a cover sheet **7**. The space between shell **12** and coating **7** is filled with an insulation arrangement **130** comprising a combination of insulating materials. (FIG. 7a, FIG. 7b). The insulation arrangement **130** from the inside towards the outside consists of at least one (two according to FIG. 7b) set **131s** of several (five with a thickness of 10-mm, as indicated in FIG. 7b) nanostructure insulation layers **11** of cryogenic insulation based on an aerogel composition (total 100 mm). In the present case, a composite material which contains homogeneous or heterogeneous aerogel phases with at least one additive incorporated either into the gel matrix (e.g. during synthesis) or added to the gel as a second distinct phase such as fibers, blankets, a fleece or also by a subsequent modification by compounding. The insulation arrangement **130** shown in FIG. 7a in connection with the storage vessel **300** is also applicable to the Tank container unit **100** and **100'**.

FIGS. 1 and 2 show optional insulation casings **135** which completely surround the saddle structures **121** and tank supports **30** described below.

Each layer **11** is particularly well-compressed by means of tapes **14** (see FIG. 8), that the individual layers **11** of insulation are separated by a thin air space. After each five layers of insulation an internally installed thermo-shrink film **10** in the thickness of 0.05 mm is installed. The thermo shrinkable film **10** acts as vapor barrier. Then there are five additional layers **11** of insulation placed to insulate cryogenic temperature range. Each layer is compressed by means

6

of strong bands **14**. After a total of ten layers **11** again the same thermo-shrinkable film **10** is placed. Toward the outer circumference of the vessel coat the insulation is followed by a filling layer **9** based on expanded foam for filling the gaps, which are the result of variations in the circumference of the container **20** and built-in installations. Under the outer coat **7** is a 10 mm fire protection layer **8**.

The outer coat layer **7** is formed from thin metal sheets which form a completely sealed enclosure of the insulation arrangement **130** which serves as an additionally vapor barrier. For this purpose the sheets of the coat layer **7** are welded to each other and/or to a suitable substructure connected to the frame (**120**) or to the vessel **110**. The fire protection layer **8** underneath serves as thermal shield during welding which protects the components of the insulation arrangement **130** underneath the fire protection layer **8**.

The fire protection layer **8** may also be based on an aerogel composition. Also, the filling layer **9** may also be based on an aerogel composition, e.g. finely divided aerogel pieces or crumbs of aerogel with typical diameters below 1 cm for granules and 1 mm for powders which may be provided in 30 suitable bags, filled blankets or flexible hoses.

FIG. 8 shows a further detail of the insulation arrangement **130**. Each insulation layer **11** is provided with a thermal radiation shield layer **16** formed as metallic sheet (e.g. aluminum) which is attached to the insulation layer **11**. Gaps **15** between adjoining insulation layers **11** (and radiation shield layers **16**) are sealed with a sealing tape **18** with self sticking layer **19**. Each gap **15** is also bridged in a radial direction to vessel shell **7** a preceding and/or following insulation layer **11** for improved insulation. The insulation layers **11** are fixed and optionally compressed by surrounding tightening bands or tapes **14**.

The inner shell **12** of the vessel **110** is made of stainless steel. The pressure vessel **110** is equipped with installations for the loading and unloading, pressure indication, level and of the pressure control. The pressure vessel is built with two safety relief valves, which prevent excessive increase in pressure in the tank due to gasification of liquefied gas.

In the frame **120** of 40' tank container unit two pressure vessels **110** of the same size are arranged horizontally along a tank vessel axis **121**. Each of these vessels **110** can be used due to installation that is functioning independently.

Large temperature difference causes some material elongation or in this case shrinkage. Temperature elongations according to the invention of the tank supports formed as clamping devices **30** (see FIGS. 5, 6a to d) are neutralized by using a specially mounted container. The mounting into in a **15** container frame is designed so that it allows the movement of containers vessel due to thermal shrinkage or expansion. The vessel **110** is mounted in a fixed frame **110** of the tank container **100**. The vessel support legs **33** have openings **37** (e.g. formed as elongated holes) that allow the movement—shrinkage of the vessel due to temperature or strain within the frame. Joint elements formed as screws **36** are tightened with a force that does not cause excessive friction. Further suitable joint elements are bolt elements.

A specificity of such a support **30** is the low thermal conductivity, which is achieved by a sandwich structure comprising a (first) steel plate element **34** which is welded to a saddle structure **121** of the frame **120**. Plate element **34** is sandwiched between two (second) steel plate elements **33** welded to the tank vessel shell **12** via a doubler plate **35** (FIGS. 6a and 6c). Between the first plate element **34** and the second plate elements **33** are insulation plate elements **32** arranged formed from suitable material having a low ther-

mal conductivity and a suitable brittle resistance at very low temperatures (e.g. PTFE (Teflon) or reinforced plastic sheet material) which reduce the thermal conductivity between the vessel 110 and the frame 110. Carbon steel (28 W/mK) conductivity is much higher than a typical thermal conductivity of PTFE (0.23 W/mK) panels.

The whole sandwich structure of the clamping device 30 is compressed by the joint elements 36, which penetrate corresponding openings 37 of the plate elements 32, 33, 34.

As shown in FIG. 11 the cross sectional dimension of the opening 37 exceeds in at least one direction the cross sectional dimension of the penetrating joint element 36 to reduce the contact 9 area between the joint element 37 and the inner face of the opening 37. For this purpose the opening 37 can be formed as an elongated hole (dashed outline 37') or with a circular diameter exceeding a smaller diameter of the joint element 36. The openings 37; 37' allow for displacement movements in a longitudinal direction L and in a radial direction R.

In the present case the compressing force is exceeded by the head elements 38 of the joint element 36 formed configured as bolts and the nuts tightened on the thread of the bolt acting as a tie rod. Details of the reduction of thermal bridge is shown in FIGS. 6a and 6b, with the structure containing PTFE insulation panels (formed as insulation plate elements 34) and panels (acting as stabilizing plate elements 31) made of metal (e.g. carbon steel). The insulation plate elements 34 and stabilizing plate elements 31 are optionally provided to improve the insulation capacity of the clamping device 30. Typically, such a pair of an insulation plate element 32 and a stabilizing plate element 31 is arranged between the first 34 and the second plate element 33 or between at least one of the of the head elements 38 and the first 34 and/or the second plate element 33. (see FIG. 6b)

In the arrangement shown in FIGS. 6a and 6d, the first plate elements 34 are part of box shaped saddle piece 39 connected to the saddle structure 121 which is sandwiched between insulation plate elements 34 and the second plate elements 33 connected to the vessel 110.

The plate elements 31, 32, 33 and 34 extend in a longitudinal direction, parallel to a tank vessel axis 112. Depending of the cross sectional design of the openings 37 and the corresponding joint elements 36 a controlled sliding movement between the first plate elements 34 and the second plate elements 33 is possible at least at the supports 30 at one end of the vessel which may occur due to thermal expansion or contraction. As the plate elements 31, 32, 33 and 34 also extend in a radial direction to the vessel axis 112 they also allow for a radial displacement of the first plate element 34 relative to the second plate element 33.

FIG. 9 shows an embodiment in which the thermal insulation between the frame 120 and the vessel 25 is further improved. A connecting plate 39 is sandwiched between insulation plate elements 34 and first plate elements 34 on the vessel side and second plate elements 33 on the frame side. Optional pairs of insulation plate elements 32 and stabilizing plate 31 elements are also provided to improve the insulation capacity of such a support. The connecting plate 39 is fabricated from steel or a different suitable material which meets the structural requirements necessary to transfer all operational (dynamic and static) loads between the vessel and the frame.

IMPLEMENTATION CASE 2

Intermodal unit CRYOTAINER 16800 LNG/20' (FIGS. 2 and 5) is intended for local transport of liquefied natural gas

and is composed of a horizontal vessel 110 of 16.800 liter volume clamped into a standard 20-foot (some 6 m; vas 20' in the following text) frame 120'.

Pressure vessel 110 is horizontally embedded in the standard ISO 40' container frame 120'. All 5 further features and embodiments of the insulation arrangement 130, supports 30 and the saddle structure 121 described above in connection with implementation case 1 also apply to the tank container 100' with a single vessel 110 according to implementation case 2 (FIGS. 2 and 5).

IMPLEMENTATION CASE 3

The vertical stationary pressure vessel 200 CARD 8600 LNG (FIG. 3) is intended for storage and distribution of liquefied natural gas. The volume of the vessel is 8.600 liter (the family extends from 8.600 to 15.000 liter). This vessel presents a cost effective alternative to local supply of customers on low population density areas, where a pipeline solution would prove not feasible due to high capital involvement. The use of liquefied natural gas in supply of medium and small consumers can present an option also for the supply of vehicles in traffic where it is one of the cleanest and environmentally most favorable solutions. All further features and embodiments of the insulation 130 described above in connection with implementation cases 1 and 2 also apply to the vertical stationary vessel 200 according to implementation case 3.

IMPLEMENTATION CASE 4

The horizontal stationary pressure vessel 300 CARD 15600 LNG (FIG. 4) is intended for distribution of liquefied natural gas. The volume of the vessel is 15.600 liter (the family of vessels is in the range from 8.600 to 27.000 liter). This vessel presents a cost effective alternative to local supply of customers on low population density areas, where a pipeline solution would prove not feasible due to high capital involvement. The use of liquefied natural gas in supply of medium and groups of small consumers can present an option also for the supply of vehicles in traffic where it is one of the cleanest and environmentally most favorable solutions.

The vessel is supported by a foundation insulated with foam glass. All further features and embodiments of the insulation 130 described above in connection with implementation cases 1 and 2 also apply to the horizontal stationary vessel 300 according to implementation case 4.

The following features are realized at least partly in the implementation cases described above and specifically in the tank container 100, 100' according to the present invention.

1. The cryogenic equipment or device 100, 100' for transport and storage of liquefied gas is identified with the basic means of insulation the cryogenic insulation is used, predominantly nanostructure insulation based on aerogel and that there is no need for vacuum or below atmospheric pressure.

2. The cryogenic device 100, 100' from point 1 is identified by the insulation between the inner shell 12 and outer coat 7 is composed from the following components:

a. The layer close to the inner vessel shell 7 includes from 7 to 14 layers 11 of cryogenic insulation in a total thickness of 80-40 mm;

b. Optionally a foil 16 enveloping or separating the layers 11 of cryogenic insulation one or more thermo shrink foils 10 are placed 0.038-0.12 mm thick or some other

element that serves as vapor protection and as a separation layer during eventual possible dismantling of the cryogenic insulation;

c. Optionally layers of insulation foam **9**, preferably expanded foam in the thickness of 30-50 mm, that will fill the void to the fire protection (**8**);

d. Optionally a layer **8** of fire protection follows 6-18 mm thick, preferably nanostructure aerogel, which is fixed to the outer coat **7**.

3. The cryogenic device **100, 100'** in point 1-2 is identified with the with evaporation rates of less than 0.36% of full load per day.

4. The cryogenic device **100, 100'** in point 1-3 is identified with the property of fire resistance preventing the temperature to rise, is at least 60 minutes preferably 120 minutes

5. The cryogenic device **100, 100'** in point 1-4 is identified with the volumes of containerized tanks are 16.800 liter and 32.600 liter.

6. The cryogenic device **100, 100'** in point 1-4 is identified with the volumes of storage tanks **30 110** are 8.600 liter in 27.000 liter

7. The cryogenic device **100, 100'** in point 1-5 is identified with the clamping **30** in the ISO container is executed so that it enables free movement of the shrinking.

8. The cryogenic device **100, 100'** in point 7, is identified with the clamping on one side front or back of the vessel **110** to be fixed, on the other end of the vessel **110** is not fixed but the screws **36** have space to allow deviations by means of elongated bores **37** and with screws **36** tightened with low force that prevents most friction.

9. The cryogenic device in point 8, is identified with specific clamping **30** where for maximal effect the clam is insulated with PTFE insulation plates **32** and carbon steel plates **31**.

The method of insulation of cryogenic devices is not based on conventional vacuum insulation but on nanostructure insulation **130**.

10. The procedures to minimize the effect of the fixing of the vessel to the outer coat **7** is designed on the reduction of the heat conductivity of the support **30**,—prolonged heat conduction path,—smaller contact surfaces,—corresponding mechanical resistance and rigidity that is obtained in the following way:

- More blades **31** of thin sheet on the cold side;
- More blades **31** of thin sheet on the warm side;
- Separation—the space between the blades is separated with a layer **32** of fitting PTFE;
- The screw joint **38** is protected against loosening, since the sole function is prevention of separation or dislocation of the joint.

The invention claimed is:

1. A tank container comprising a vessel covered by a thermal insulation arrangement, and a framework; wherein the vessel is connected to the framework by a clamping device which comprises a sandwich structure with at least one first plate element connected to the framework, at least one second plate element connected to the vessel, and at least one thermally insulating plate element arranged between the first and the second plate element, wherein the first, second and thermally insulating plate elements each have at least one opening, and wherein the first, second and thermally insulating plate elements are interconnected by a joint element traversing corresponding openings of the first, second and thermally insulating plate elements, wherein the thermally insulating plate reduces a thermal bridging effect between the vessel and the framework, wherein the sandwich structure comprises at least one stabilizing plate ele-

ment arranged between the first and the second plate element; wherein the stabilizing plate element is not directly connected to either the vessel or the framework.

2. Tank container of claim 1, wherein the dimensions of the openings in the first plate element and/or the second plate element exceed in at least in one direction a cross sectional dimension of the traversing joint element, thereby allowing for a movement between the first plate attached to the framework and the second plate attached to the vessel.

3. Tank container of claim 1, wherein the insulation arrangement comprises at least one insulation layer which comprises aerogel.

4. Tank container of claim 3, further comprising at least one outer cover sheet enclosing the insulation arrangement.

5. Tank container of claim 4, wherein the insulation arrangement comprises at least one insulation layer set comprising at least two insulation layers which comprise aerogel and at least one radiation shield layer between the at least two insulation layers.

6. Tank container of claim 5, wherein the insulation arrangement comprises at least two insulation layer sets comprising aerogel insulation layers and at least one radiation shield layer, and at least one vapor barrier layer between the at least two insulation layer sets.

7. A tank container comprising a vessel covered by an insulation arrangement, and a framework; wherein the vessel is connected to the framework by a clamping device which comprises a sandwich structure with at least one first plate element connected to the framework, at least one second plate element connected to the vessel, and at least one insulating plate element arranged between the first and the second plate element, wherein the first, second and insulating plate elements each have at least one opening, and wherein the first, second and insulating plate elements are interconnected by a joint element traversing corresponding openings of the first, second and insulating plate elements,

wherein the sandwich structure comprises at least one pair of sandwiching plate elements which sandwich the first and second plate elements, at least one head element external to each sandwiching plate element, at least one insulating plate element arranged between at least one of the head elements and the corresponding sandwiching plate element, wherein the joint element secures the sandwich structure by traversing corresponding head elements and sandwiching plate elements.

8. A tank container comprising a vessel covered by an insulation arrangement, and a framework; wherein the vessel is connected to the framework by a clamping device which comprises a sandwich structure with at least one first plate element connected to the framework, at least one second plate element connected to the vessel, and at least one insulating plate element arranged between the first and the second plate element, wherein the first, second and insulating plate elements each have at least one opening, and wherein the first, second and insulating plate elements are interconnected by a joint element traversing corresponding openings of the first, second and insulating plate elements, wherein the insulating plate element is manufactured from a fiber reinforced plastic material comprising a PTFE material.

9. Tank container comprising a vessel covered by an insulation arrangement, and a framework; wherein the vessel is connected to the framework by a clamping device which comprises a first sandwich structure with at least one first plate element connected to the framework, a second sandwich structure with at least one second plate element connected to the vessel, and a load-bearing connecting plate

11

extending in parallel to the first and second plate element and having a first end overlapping the first plate element and a second end overlapping the second plate element; wherein the first sandwich structure comprises the first plate element interconnected to the first end of the load-bearing connecting plate by at least one joint element traversing the first plate element and the load-bearing connecting plate, and at least one insulating plate element arranged between the first plate element and the load-bearing connecting plate; and wherein the second sandwich structure comprises the second plate element interconnected to the second end of the load-bearing connecting plate by at least one joint element traversing the second plate element and the load-bearing connecting plate, and at least one insulating plate element arranged between the second plate element and the load-bearing connecting plate.

10. Tank container of claim **9**, wherein the insulation arrangement comprises at least one insulation layer which comprises aerogel.

11. Tank container of claim **10**, further comprising at least one outer cover sheet enclosing the insulation arrangement.

12. Tank container of claim **11**, wherein the insulation arrangement comprises at least one insulation layer set comprising at least two insulation layers which comprise aerogel and at least one radiation shield layer between the at least two insulation layers.

12

13. Tank container of claim **12**, wherein the insulation arrangement comprises at least two insulation layer sets comprising aerogel insulation layers and at least one radiation shield layer, and at least one vapor barrier layer between the at least two insulation layer sets.

14. Tank container of claim **9**, wherein the first sandwich structure comprises at least two first plate elements, and wherein the first end of the load-bearing connecting plate is arranged between the at least two first plate elements.

15. Tank container of claim **9**, wherein the second sandwich structure comprises at least two second plate elements, and wherein the second end of the load-bearing connecting plate is arranged between the at least two second plate elements.

16. Tank container of claim **9**, wherein the first sandwich structure comprises at least two first plate elements, and wherein the first end of the load-bearing connecting plate is arranged between the at least two first plate elements; and wherein the second sandwich structure comprises at least two second plate elements, and wherein the second end of the load-bearing connecting plate is arranged between the at least two second plate elements.

* * * * *