



US010731915B2

(12) **United States Patent**
Gillette et al.

(10) **Patent No.:** **US 10,731,915 B2**
(45) **Date of Patent:** **Aug. 4, 2020**

(54) **SELF-CONTAINED PANTRY BOX SYSTEM FOR INSERTION INTO AN APPLIANCE**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **WHIRLPOOL CORPORATION**,
Benton Harbor, MI (US)

948,541 A 2/1910 Coleman
1,275,511 A 8/1918 Welch

(Continued)

(72) Inventors: **Thomas A. Gillette**, Shelby Township,
MI (US); **Duane M. Kobos**, Laporte,
IN (US); **Todd Tunzi**, St. Joseph, MI
(US)

FOREIGN PATENT DOCUMENTS

CA 626838 A 5/1961
CA 1320631 7/1993

(Continued)

(73) Assignee: **Whirlpool Corporation**, Benton
Harbor, MI (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 175 days.

Machine Translation of JPO 2010-43823 to Kurita; eSpacenet;
description (Year: 2010).*

(Continued)

(21) Appl. No.: **15/862,150**

Primary Examiner — Filip Zec

(22) Filed: **Jan. 4, 2018**

(74) *Attorney, Agent, or Firm* — Price Heneveld LLP

(65) **Prior Publication Data**

(57) **ABSTRACT**

US 2018/0128541 A1 May 10, 2018

A pantry box system for a refrigerating appliance includes a pantry mullion having an interstitial space defined therein, a pantry wall extending perpendicularly from the pantry mullion, a base positioned substantially parallel with the pantry mullion. The pantry mullion, pantry wall and base define an insertable pantry compartment having an internal pantry volume. A pantry drawer is in operable communication with the internal pantry volume, and is operable through a drawer aperture defined in the pantry wall between open and closed positions. The pantry drawer includes an exterior drawer panel that conceals the drawer aperture when the at least one pantry drawer is in the closed position. A pantry box cooling system is configured to deliver cooling to the insertable pantry compartment from an external location, wherein the pantry box cooling system includes a control that independently controls a pantry temperature of the insertable pantry compartment.

Related U.S. Application Data


(63) Continuation of application No. 14/644,421, filed on
Mar. 11, 2015, now Pat. No. 9,897,370.

(51) **Int. Cl.**
F25B 5/00 (2006.01)
F25D 25/02 (2006.01)

(52) **U.S. Cl.**
CPC **F25D 25/025** (2013.01); **F25B 5/00**
(2013.01); **F25C 2400/10** (2013.01); **F25D**
2317/061 (2013.01)

(58) **Field of Classification Search**
CPC **F25D 2317/061**; **F25D 25/025**
See application file for complete search history.

12 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

1,849,369 A	3/1932	Frost	4,777,154 A	10/1988	Torobin
1,921,576 A	8/1933	Muffly	4,781,968 A	11/1988	Kellerman
2,108,212 A	2/1938	Schellens	4,805,293 A	2/1989	Buchser
2,128,336 A	8/1938	Torstensson	4,865,875 A	9/1989	Kellerman
2,164,143 A	6/1939	Munters	4,870,735 A	10/1989	Jahr et al.
2,191,659 A	2/1940	Hintze	4,914,341 A	4/1990	Weaver et al.
2,318,744 A	5/1943	Brown	4,917,841 A	4/1990	Jenkins
2,356,827 A	8/1944	Coss et al.	5,007,226 A	4/1991	Nelson
2,432,042 A	12/1947	Richard	5,018,328 A	5/1991	Cur et al.
2,439,602 A	4/1948	Heritage	5,033,636 A	7/1991	Jenkins
2,439,603 A	4/1948	Heritage	5,066,437 A	11/1991	Barito et al.
2,451,884 A	10/1948	Stelzer	5,082,335 A	1/1992	Cur et al.
2,538,780 A	1/1951	Hazard	5,084,320 A	1/1992	Barito et al.
2,559,356 A	7/1951	Hedges	5,094,899 A	3/1992	Rusek, Jr.
2,729,863 A	1/1956	Kurtz	5,118,174 A	6/1992	Benford et al.
2,768,046 A	10/1956	Evans	5,121,593 A	6/1992	Forslund
2,817,123 A	12/1957	Jacobs	5,157,893 A	10/1992	Benson et al.
2,942,438 A	6/1960	Schmeling	5,168,674 A	12/1992	Molthen
2,985,075 A	5/1961	Knutsson-Hall	5,171,346 A	12/1992	Hallett
3,075,366 A *	1/1963	Jung F25D 17/065 62/382	5,175,975 A	1/1993	Benson et al.
3,086,830 A	4/1963	Malia	5,212,143 A	5/1993	Torobin
3,125,388 A	3/1964	Constantini et al.	5,221,136 A	6/1993	Hauck et al.
3,137,900 A	6/1964	Carbary	5,227,245 A	7/1993	Brands et al.
3,218,111 A	11/1965	Steiner	5,231,811 A	8/1993	Andrepoint et al.
3,258,883 A	7/1966	Companaro et al.	5,248,196 A	9/1993	Lynn et al.
3,290,893 A	12/1966	Haldopoulos	5,251,455 A	10/1993	Cur et al.
3,338,451 A	8/1967	Kesling	5,252,408 A	10/1993	Bridges et al.
3,353,301 A	11/1967	Heilweil et al.	5,263,773 A	11/1993	Gable et al.
3,353,321 A	11/1967	Heilweil et al.	5,273,801 A	12/1993	Barry et al.
3,358,059 A	12/1967	Snyder	5,318,108 A	6/1994	Benson et al.
3,379,481 A	4/1968	Fisher	5,340,208 A	8/1994	Hauck et al.
3,408,316 A	10/1968	Mueller et al.	5,353,868 A	10/1994	Abbott
3,466,804 A *	9/1969	Swaneck, Jr. F25D 23/087 49/483.1	5,359,795 A	11/1994	Mawby et al.
3,471,416 A	10/1969	Fijal	5,375,428 A	12/1994	LeClear et al.
3,597,850 A	8/1971	Jenkins	5,397,759 A	3/1995	Torobin
3,607,169 A	9/1971	Coxe	5,418,055 A	5/1995	Chen et al.
3,632,012 A	1/1972	Kitson	5,433,056 A	7/1995	Benson et al.
3,633,783 A	1/1972	Aue	5,477,676 A	12/1995	Benson et al.
3,634,971 A	1/1972	Kesling	5,500,287 A	3/1996	Henderson
3,635,536 A	1/1972	Lackey et al.	5,500,305 A	3/1996	Bridges et al.
3,670,521 A	6/1972	Dodge, III et al.	5,505,810 A	4/1996	Kirby et al.
3,688,384 A	9/1972	Mizushima et al.	5,507,999 A	4/1996	Copsey et al.
3,769,770 A	11/1973	Deschamps et al.	5,509,248 A	4/1996	Dellby et al.
3,862,880 A	1/1975	Feldman	5,512,345 A	4/1996	Tsutsumi et al.
3,868,829 A	3/1975	Mann et al.	5,532,034 A	7/1996	Kirby et al.
3,875,683 A	4/1975	Waters	5,533,311 A	7/1996	Tirrell et al.
3,910,658 A	10/1975	Lindenschmidt	5,562,154 A	10/1996	Benson et al.
3,933,398 A	1/1976	Haag	5,562,154 A	12/1996	Dellby et al.
3,935,787 A	2/1976	Fisher	5,586,680 A	2/1997	Revlett et al.
4,005,919 A	2/1977	Hoge et al.	5,599,081 A	2/1997	Valence et al.
4,006,947 A	2/1977	Haag et al.	5,600,966 A	2/1997	Valence et al.
4,043,624 A	8/1977	Lindenschmidt	5,632,543 A	5/1997	McGrath et al.
4,050,145 A	9/1977	Benford	5,640,828 A	6/1997	Reeves et al.
4,067,628 A	1/1978	Sherburn	5,643,485 A	7/1997	Potter et al.
4,170,391 A	10/1979	Bottger	5,652,039 A	7/1997	Tremain et al.
4,242,241 A	12/1980	Rosen et al.	5,694,789 A *	12/1997	Do F25D 23/02 312/405
4,260,876 A	4/1981	Hochheiser	5,716,581 A	2/1998	Tirrell et al.
4,303,730 A	12/1981	Torobin	5,768,837 A	6/1998	Sjoholm
4,303,732 A	12/1981	Torobin	5,792,801 A	8/1998	Tsuda et al.
4,325,734 A	4/1982	Burrage et al.	5,813,454 A	9/1998	Potter
4,330,310 A	5/1982	Tate, Jr. et al.	5,826,780 A	10/1998	Neeser et al.
4,332,429 A	6/1982	Frick et al.	5,827,385 A	10/1998	Meyer et al.
4,396,362 A	8/1983	Thompson et al.	5,834,126 A	11/1998	Sheu
4,417,382 A	11/1983	Schilf	5,843,353 A	12/1998	DeVos et al.
4,492,368 A	1/1985	DeLeeuw et al.	5,866,228 A	2/1999	Awata
4,529,368 A	7/1985	Makansi	5,866,247 A	2/1999	Klatt et al.
4,548,196 A	10/1985	Torobin	5,868,890 A	2/1999	Fredrick
4,583,796 A	4/1986	Nakajima et al.	5,900,299 A	5/1999	Wynne
4,660,271 A	4/1987	Lenhardt	5,918,478 A	7/1999	Bostic et al.
4,671,909 A	6/1987	Torobin	5,924,295 A	7/1999	Park
4,671,985 A	6/1987	Rodrigues et al.	5,950,395 A	9/1999	Takemasa et al.
4,681,788 A	7/1987	Barito et al.	5,952,404 A	9/1999	Simpson et al.
4,745,015 A	5/1988	Cheng et al.	5,966,963 A	10/1999	Kovalaske
			5,985,189 A	11/1999	Lynn et al.
			6,013,700 A	1/2000	Asano et al.
			6,063,471 A	5/2000	Dietrich et al.
			6,094,922 A	8/2000	Ziegler
			6,109,712 A	8/2000	Haworth et al.
			6,128,914 A	10/2000	Tamaoki et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,132,837	A	10/2000	Boes et al.	7,930,892	B1	4/2011	Vonderhaar
6,158,233	A	12/2000	Cohen et al.	7,938,148	B2	5/2011	Carrier et al.
6,163,976	A	12/2000	Tada et al.	7,992,257	B2	8/2011	Kim
6,164,030	A	12/2000	Dietrich	8,049,518	B2	11/2011	Wern et al.
6,164,739	A	12/2000	Schulz et al.	8,074,469	B2	12/2011	Hamel et al.
6,187,256	B1	2/2001	Aslan et al.	8,079,652	B2	12/2011	Laible et al.
6,209,342	B1	4/2001	Banicevic et al.	8,083,985	B2	12/2011	Luisi et al.
6,210,625	B1	4/2001	Matsushita et al.	8,108,972	B2	2/2012	Bae et al.
6,220,473	B1	4/2001	Lehman et al.	8,113,604	B2	2/2012	Olson et al.
6,221,456	B1	4/2001	Pogorski et al.	8,117,865	B2	2/2012	Allard et al.
6,224,179	B1	5/2001	Wenning et al.	8,157,338	B2	4/2012	Seo et al.
6,244,458	B1	6/2001	Frysinger et al.	8,162,415	B2	4/2012	Hagele et al.
6,260,377	B1	7/2001	Tamaoki et al.	8,163,080	B2	4/2012	Meyer et al.
6,266,970	B1	7/2001	Nam et al.	8,176,746	B2	5/2012	Allard et al.
6,294,595	B1	9/2001	Tyagi et al.	8,182,051	B2	5/2012	Laible et al.
6,305,768	B1	10/2001	Nishimoto	8,197,019	B2	6/2012	Kim
6,485,122	B2	1/2002	Wolf et al.	8,202,599	B2	6/2012	Henn
6,390,378	B1	5/2002	Briscoe, Jr. et al.	8,211,523	B2	7/2012	Fujimori et al.
6,406,449	B1	6/2002	Moore et al.	8,266,923	B2	9/2012	Bauer et al.
6,408,841	B1	6/2002	Hirath et al.	8,281,558	B2	10/2012	Hiemeyer et al.
6,415,623	B1	7/2002	Jennings et al.	8,299,545	B2	10/2012	Chen et al.
6,428,130	B1	8/2002	Banicevic et al.	8,299,656	B2	10/2012	Allard et al.
6,430,780	B1	8/2002	Kim et al.	8,343,395	B2	1/2013	Hu et al.
6,460,955	B1	10/2002	Vaughan et al.	8,353,177	B2	1/2013	Adamski et al.
6,519,919	B1	2/2003	Takenouchi et al.	8,382,219	B2	2/2013	Hottmann et al.
6,623,413	B1	9/2003	Wynne	8,434,317	B2	5/2013	Besore
6,629,429	B1	10/2003	Kawamura et al.	8,439,460	B2	5/2013	Laible et al.
6,651,444	B2	11/2003	Morimoto et al.	8,453,476	B2	6/2013	Kendall et al.
6,655,766	B2	12/2003	Hodges	8,456,040	B2	6/2013	Allard et al.
6,689,840	B1	2/2004	Eustace et al.	8,491,070	B2	7/2013	Davis et al.
6,716,501	B2	4/2004	Kovalchuk et al.	8,516,845	B2	8/2013	Wuesthoff et al.
6,736,472	B2	5/2004	Banicevic	8,522,563	B2	9/2013	Allard et al.
6,749,780	B2	6/2004	Tobias	8,528,284	B2	9/2013	Aspenson et al.
6,773,082	B2	8/2004	Lee	8,590,992	B2	11/2013	Lim et al.
6,858,280	B2	2/2005	Allen et al.	8,717,029	B2	5/2014	Chae et al.
6,860,082	B1	3/2005	Yamamoto et al.	8,726,690	B2	5/2014	Cur et al.
6,938,968	B2	9/2005	Tanimoto et al.	8,733,123	B2	5/2014	Adamski et al.
6,997,530	B2	2/2006	Avendano et al.	8,739,567	B2	6/2014	Junge
7,008,032	B2	3/2006	Chekal et al.	8,752,918	B2	6/2014	Allard et al.
7,026,054	B2	4/2006	Ikegawa et al.	8,752,921	B2	6/2014	Kang
7,197,792	B2	4/2007	Moon	8,756,952	B2	6/2014	Gorz et al.
7,197,888	B2	4/2007	LeClear et al.	8,756,952	B2	6/2014	Adamski et al.
7,207,181	B2	4/2007	Murray et al.	8,763,847	B2	7/2014	Mortarotti
7,210,308	B2	5/2007	Tanimoto et al.	8,764,133	B2	7/2014	Park et al.
7,234,247	B2	6/2007	Maguire	8,770,682	B2	7/2014	Lee et al.
7,263,744	B2	9/2007	Kim et al.	8,776,390	B2	7/2014	Hanaoka et al.
7,278,279	B2	10/2007	Hirai et al.	8,790,477	B2	7/2014	Tenra et al.
7,284,390	B2	10/2007	Van Meter et al.	8,840,204	B2	9/2014	Bauer et al.
7,296,432	B2	11/2007	Muller et al.	8,852,708	B2	10/2014	Kim et al.
7,316,125	B2	1/2008	Uekado et al.	8,871,323	B2	10/2014	Kim et al.
7,343,757	B2	3/2008	Egan et al.	8,881,398	B2	10/2014	Hanley et al.
7,360,371	B2	4/2008	Feinauer et al.	8,899,068	B2	12/2014	Jung et al.
7,386,992	B2	6/2008	Adamski et al.	8,905,503	B2	12/2014	Sahasrabudhe et al.
7,449,227	B2	11/2008	Echigoya et al.	8,927,084	B2	1/2015	Jeon et al.
7,475,562	B2	1/2009	Jackovin	8,943,770	B2	2/2015	Sanders et al.
7,517,031	B2	4/2009	Laible	8,944,541	B2	2/2015	Allard et al.
7,517,576	B2	4/2009	Echigoya et al.	8,986,483	B2	3/2015	Cur et al.
7,537,817	B2	5/2009	Tsunetsugu et al.	9,009,969	B2	4/2015	Choi et al.
7,614,244	B2	11/2009	Venkatakrishnan et al.	RE45,501	E	5/2015	Maguire
7,625,622	B2	12/2009	Teckoe et al.	9,056,952	B2	6/2015	Eilbracht et al.
7,641,298	B2	1/2010	Hirath et al.	9,074,811	B2	7/2015	Korkmaz
7,665,326	B2	2/2010	LeClear et al.	9,080,808	B2	7/2015	Choi et al.
7,703,217	B2	4/2010	Tada et al.	9,102,076	B2	8/2015	Doshi et al.
7,703,824	B2	4/2010	Kittelson et al.	9,103,482	B2	8/2015	Fujimori et al.
7,757,511	B2	7/2010	LeClear et al.	9,125,546	B2	9/2015	Kleemann et al.
7,762,634	B2	7/2010	Tenra et al.	9,140,480	B2	9/2015	Kuehl et al.
7,794,805	B2	9/2010	Aumaugher et al.	9,140,481	B2	9/2015	Curr et al.
7,815,269	B2	10/2010	Wenning et al.	9,170,045	B2	10/2015	Oh et al.
7,842,269	B2	11/2010	Schachtely et al.	9,170,046	B2	10/2015	Jung et al.
7,845,745	B2	12/2010	Gorz et al.	9,188,382	B2	11/2015	Kim et al.
7,861,538	B2	1/2011	Welle et al.	8,955,352	B2	12/2015	Lee et al.
7,886,559	B2	2/2011	Hell et al.	9,221,210	B2	12/2015	Wu et al.
7,893,123	B2	2/2011	Luisi	9,228,386	B2	1/2016	Thielmann et al.
7,905,614	B2	3/2011	Aoki	9,252,570	B2	2/2016	Allard et al.
7,908,873	B1	3/2011	Cur et al.	9,267,727	B2	2/2016	Lim et al.
				9,303,915	B2	4/2016	Kim et al.
				9,328,951	B2	5/2016	Shin et al.
				9,353,984	B2	5/2016	Kim et al.
				9,410,732	B2	8/2016	Choi et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,423,171 B2	8/2016	Betto et al.	2011/0215694 A1	9/2011	Fink et al.
9,429,356 B2	8/2016	Kim et al.	2011/0220662 A1	9/2011	Kim et al.
9,448,004 B2	9/2016	Kim et al.	2011/0241513 A1	10/2011	Nomura et al.
9,463,917 B2	10/2016	Wu et al.	2011/0241514 A1	10/2011	Nomura et al.
9,482,463 B2	11/2016	Choi et al.	2011/0260351 A1	10/2011	Corradi et al.
9,506,689 B2	11/2016	Carbajal et al.	2011/0290808 A1	12/2011	Bai et al.
9,518,777 B2	12/2016	Lee et al.	2011/0309732 A1	12/2011	Horil et al.
9,568,238 B2	2/2017	Kim et al.	2011/0315693 A1	12/2011	Cur et al.
D781,641 S	3/2017	Incukur	2012/0000234 A1	1/2012	Adamski et al.
D781,642 S	3/2017	Incukur	2012/0011879 A1	1/2012	Gu
9,605,891 B2	3/2017	Lee et al.	2012/0060544 A1	3/2012	Lee et al.
9,696,085 B2	7/2017	Seo et al.	2012/0073321 A1*	3/2012	Davis F25D 23/028 62/449
9,702,621 B2	7/2017	Cho et al.	2012/0099255 A1	4/2012	Lee et al.
9,759,479 B2	9/2017	Ramm et al.	2012/0103006 A1	5/2012	Jung et al.
9,777,958 B2	10/2017	Choi et al.	2012/0104923 A1	5/2012	Jung et al.
9,791,204 B2	10/2017	Kim et al.	2012/0118002 A1	5/2012	Kim et al.
9,833,942 B2	12/2017	Wu et al.	2012/0137501 A1	6/2012	Allard et al.
2002/0004111 A1	1/2002	Matsubara et al.	2012/0152151 A1	6/2012	Meyer et al.
2002/0114937 A1	8/2002	Albert et al.	2012/0196059 A1	8/2012	Fujimori et al.
2002/0144482 A1	10/2002	Henson et al.	2012/0231204 A1	9/2012	Jeon et al.
2002/0168496 A1	11/2002	Morimoto et al.	2012/0237715 A1	9/2012	McCracken
2003/0008100 A1	1/2003	Horn	2012/0240612 A1	9/2012	Wusthoff et al.
2003/0041612 A1	3/2003	Piloni et al.	2012/0273111 A1	11/2012	Nomura et al.
2003/0056334 A1	3/2003	Finkelstein	2012/0279247 A1	11/2012	Katu et al.
2003/0157284 A1	8/2003	Tanimoto et al.	2012/0280608 A1	11/2012	Park et al.
2003/0167789 A1	9/2003	Tanimoto et al.	2012/0285971 A1	11/2012	Junge et al.
2003/0173883 A1	9/2003	Koons	2012/0297813 A1	11/2012	Hanley et al.
2004/0144130 A1	7/2004	Jung	2012/0324937 A1	12/2012	Adamski et al.
2004/0178707 A1	9/2004	Avendano	2013/0026900 A1	1/2013	Oh et al.
2004/0180176 A1	9/2004	Rusek	2013/0033163 A1	2/2013	Kang
2004/0226141 A1	11/2004	Yates et al.	2013/0043780 A1	2/2013	Ootsuka et al.
2004/0253406 A1	12/2004	Hayashi et al.	2013/0068990 A1	3/2013	Eilbracht et al.
2005/0042247 A1	2/2005	Gomoll et al.	2013/0111941 A1	5/2013	Yu et al.
2005/0229614 A1	10/2005	Ansted	2013/0221819 A1	8/2013	Wing
2005/0235682 A1	10/2005	Hirai et al.	2013/0256318 A1	10/2013	Kuehl et al.
2006/0064846 A1	3/2006	Espindola et al.	2013/0256319 A1	10/2013	Kuehl et al.
2006/0076863 A1	4/2006	Echigoya et al.	2013/0257256 A1	10/2013	Allard et al.
2006/0201189 A1	9/2006	Adamski et al.	2013/0257257 A1	10/2013	Cur et al.
2006/0261718 A1	11/2006	Miseki et al.	2013/0270732 A1	10/2013	Wu et al.
2006/0263571 A1	11/2006	Tsunetsugu et al.	2013/0285527 A1	10/2013	Choi et al.
2006/0266075 A1	11/2006	Itsuki et al.	2013/0293080 A1	11/2013	Kim et al.
2007/0001563 A1	1/2007	Park et al.	2013/0305535 A1	11/2013	Cur et al.
2007/0099502 A1	5/2007	Ferinauer	2013/0328472 A1	12/2013	Shim et al.
2007/0176526 A1	8/2007	Gomoll et al.	2014/0009055 A1	1/2014	Cho et al.
2007/0266654 A1	11/2007	Noale	2014/0097733 A1	4/2014	Seo et al.
2008/0044488 A1	2/2008	Zimmer et al.	2014/0132144 A1	5/2014	Kim et al.
2008/0048540 A1	2/2008	Kim	2014/0166926 A1	6/2014	Lee et al.
2008/0138458 A1	6/2008	Ozasa et al.	2014/0171578 A1	6/2014	Meyer et al.
2008/0196441 A1	8/2008	Ferreira	2014/0190978 A1	7/2014	Bowman et al.
2008/0300356 A1	12/2008	Meyer et al.	2014/0196305 A1	7/2014	Smith
2008/0309210 A1	12/2008	Luisi et al.	2014/0216706 A1	8/2014	Melton et al.
2009/0032541 A1	2/2009	Rogala et al.	2014/0232250 A1	8/2014	Kim et al.
2009/0056367 A1	3/2009	Neumann	2014/0260332 A1	9/2014	Wu
2009/0058244 A1	3/2009	Cho et al.	2014/0346942 A1	11/2014	Kim et al.
2009/0113925 A1	5/2009	Korkmaz	2014/0364527 A1	12/2014	Matthias et al.
2009/0131571 A1	5/2009	Fraser et al.	2015/0011668 A1	1/2015	Kolb et al.
2009/0179541 A1	7/2009	Smith et al.	2015/0015133 A1	1/2015	Carbajal et al.
2009/0205357 A1	8/2009	Lim et al.	2015/0017386 A1	1/2015	Kolb et al.
2009/0302728 A1	12/2009	Rotter et al.	2015/0027628 A1	1/2015	Cravens et al.
2009/0322470 A1	12/2009	Yoo et al.	2015/0059399 A1	3/2015	Hwang et al.
2009/0324871 A1	12/2009	Henn	2015/0115790 A1	4/2015	Ogg
2010/0206464 A1	8/2010	Heo et al.	2015/0147514 A1	5/2015	Shinohara et al.
2010/0218543 A1	9/2010	Duchame	2015/0159936 A1	6/2015	Oh et al.
2010/0231109 A1	9/2010	Matzke et al.	2015/0168050 A1	6/2015	Cur et al.
2010/0287843 A1	11/2010	Oh	2015/0176888 A1	6/2015	Cur et al.
2010/0287974 A1	11/2010	Cur et al.	2015/0184923 A1	7/2015	Jeon
2010/0293984 A1	11/2010	Adamski et al.	2015/0190840 A1	7/2015	Muto et al.
2010/0295435 A1	11/2010	Kendall et al.	2015/0224685 A1	8/2015	Amstutz
2011/0011119 A1	1/2011	Kuehl et al.	2015/0241115 A1	8/2015	Strauss et al.
2011/0023527 A1	2/2011	Kwon et al.	2015/0241118 A1	8/2015	Wu
2011/0030894 A1	2/2011	Tenra et al.	2015/0285551 A1	10/2015	Aiken et al.
2011/0095669 A1	4/2011	Moon et al.	2016/0084567 A1	3/2016	Fernandez et al.
2011/0146325 A1	6/2011	Lee	2016/0116100 A1	4/2016	Thiery et al.
2011/0146335 A1	6/2011	Jung et al.	2016/0123055 A1	5/2016	Ueyama
2011/0165367 A1	7/2011	Kojima et al.	2016/0161175 A1	6/2016	Benold et al.
			2016/0178267 A1	6/2016	Hao et al.
			2016/0178269 A1	6/2016	Hiemeyer et al.
			2016/0235201 A1	8/2016	Soot

(56)

References Cited

U.S. PATENT DOCUMENTS

2016/0240839 A1 8/2016 Umeyama et al.
 2016/0258671 A1 9/2016 Allard et al.
 2016/0290702 A1 10/2016 Sexton et al.
 2016/0348957 A1 12/2016 Hitzelberger et al.
 2017/0038126 A1 2/2017 Lee et al.
 2017/0157809 A1 6/2017 Deka et al.
 2017/0176086 A1 6/2017 Kang
 2017/0184339 A1 6/2017 Liu et al.
 2017/0191746 A1 7/2017 Seo

FOREIGN PATENT DOCUMENTS

CA 2259665 1/1998
 CA 2640006 8/2007
 CN 1158509 7/2004
 CN 1970185 5/2007
 CN 100359272 1/2008
 CN 101437756 5/2009
 CN 201680116 12/2010
 CN 201748744 U 2/2011
 CN 102296714 5/2012
 CN 102452522 5/2012
 CN 102717578 A 10/2012
 CN 102720277 10/2012
 CN 103072321 5/2013
 CN 202973713 U 6/2013
 CN 203331442 12/2013
 CN 104816478 A 8/2015
 CN 105115221 12/2015
 CN 2014963379 U 1/2016
 DE 1150190 6/1963
 DE 4110292 A1 10/1992
 DE 4409091 9/1995
 DE 19818890 11/1999
 DE 19914105 9/2000
 DE 19915311 10/2000
 DE 102008026528 12/2009
 DE 102009046810 5/2011
 DE 102010024951 12/2011
 DE 102011051178 A1 12/2012
 DE 102012223536 6/2014
 DE 102012223541 6/2014
 EP 0260699 3/1988
 EP 0480451 4/1992
 EP 0645576 A1 3/1995
 EP 0691518 1/1996
 EP 0860669 8/1998
 EP 1087186 3/2001
 EP 1200785 5/2002
 EP 1243880 9/2002
 EP 1496322 1/2005
 EP 1505359 2/2005
 EP 1602425 A1 12/2005
 EP 1624263 A2 8/2006
 EP 1484563 10/2008
 EP 2342511 8/2012
 EP 2543942 A2 1/2013
 EP 2607073 6/2013
 EP 2789951 10/2014
 EP 2878427 A1 6/2015
 FR 2980963 4/2013
 FR 2991698 A1 12/2013
 GB 837929 6/1960
 GB 1214548 6/1960
 JP 4828353 8/1973
 JP 51057777 5/1976
 JP 59191588 12/1984
 JP 03013779 1/1991
 JP 404165197 6/1992
 JP 04165197 10/1992
 JP 04309778 A 11/1992
 JP 06159922 6/1994
 JP 7001479 1/1995
 JP H07167377 7/1995
 JP 08300052 11/1996

JP H08303686 11/1996
 JP H09166271 6/1997
 JP 10113983 5/1998
 JP 11159693 A 6/1999
 JP 11311395 11/1999
 JP 11336990 12/1999
 JP 2000097390 4/2000
 JP 2000117334 4/2000
 JP 2000320958 A 11/2000
 JP 2001038188 2/2001
 JP 2001116437 4/2001
 JP 2001336691 12/2001
 JP 2001343176 12/2001
 JP 2002068853 3/2002
 JP 3438948 8/2003
 JP 03478771 12/2003
 JP 2004303695 10/2004
 JP 2005069596 A 3/2005
 JP 2005098637 A 4/2005
 JP 2005114015 4/2005
 JP 2005164193 6/2005
 JP 2005256849 9/2005
 JP 2006077792 3/2006
 JP 2006161834 A 6/2006
 JP 2006161945 6/2006
 JP 03792801 7/2006
 JP 2006200685 A 8/2006
 JP 2007263186 10/2007
 JP 4111096 7/2008
 JP 2008157431 7/2008
 JP 2008190815 8/2008
 JP 2009063064 3/2009
 JP 2009162402 7/2009
 JP 2009524570 7/2009
 JP 2010017437 1/2010
 JP 2010071565 4/2010
 JP 2010108199 5/2010
 JP 2010145002 7/2010
 JP 04545126 B2 9/2010
 JP 2010236770 10/2010
 JP 2010276309 12/2010
 JP 2011002033 1/2011
 JP 2011069612 4/2011
 JP 04779684 9/2011
 JP 2011196644 10/2011
 JP 2012026493 2/2012
 JP 04897473 3/2012
 JP 2012063029 3/2012
 JP 2012087993 5/2012
 JP 2012163258 8/2012
 JP 2012189114 10/2012
 JP 2012242075 12/2012
 JP 2013002484 1/2013
 JP 2013050242 3/2013
 JP 2013050267 A 3/2013
 JP 2013076471 A 4/2013
 JP 2013088036 5/2013
 JP 2013195009 9/2013
 KR 20020057547 7/2002
 KR 20020080938 10/2002
 KR 20030083812 11/2003
 KR 20040000126 1/2004
 KR 20050095357 A 9/2005
 KR 100620025 B1 9/2006
 KR 20070044024 4/2007
 KR 1020070065743 A 6/2007
 KR 1020080103845 11/2008
 KR 20090026045 3/2009
 KR 1017776 2/2011
 KR 20120007241 1/2012
 KR 2012046621 5/2012
 KR 2012051305 5/2012
 KR 20150089495 A 8/2015
 RU 547614 5/1977
 RU 2061925 C1 6/1996
 RU 2077411 C1 4/1997
 RU 2081858 6/1997
 RU 2132522 C1 6/1999
 RU 2162576 C2 1/2001

(56)

References Cited

FOREIGN PATENT DOCUMENTS

RU	2166158	C1	4/2001
RU	2187433	C2	8/2002
RU	2234645	C1	8/2004
RU	2252377		5/2005
RU	2253792	C2	6/2005
RU	2349618	C2	3/2009
RU	2414288	C2	3/2011
RU	2422598		6/2011
RU	142892		7/2014
RU	2529525	C1	9/2014
RU	2571031		12/2015
SU	203707		12/1967
SU	00476407	A1	7/1975
SU	648780	A1	2/1979
SU	01307186	A1	4/1987
WO	9614207	A1	5/1996
WO	9721767		6/1997
WO	1998049506		11/1998
WO	02060576	A1	4/1999
WO	9614207	A1	4/1999
WO	9920961	A1	4/1999
WO	9920964	A1	4/1999
WO	199920964		4/1999
WO	200160598		8/2001
WO	200202987		1/2002
WO	2002052208		4/2002
WO	02060576	A1	8/2002
WO	03072684	A1	9/2003
WO	03089729		10/2003
WO	2004010042	A1	1/2004
WO	2006045694		5/2006
WO	2006073540	A2	7/2006
WO	2007033836	A1	3/2007
WO	2007085511		8/2007
WO	2007106067	A2	9/2007
WO	2008065453		6/2008
WO	2008077741		7/2008
WO	2008118536	A2	10/2008
WO	2008122483	A2	10/2008
WO	2009013106	A2	1/2009
WO	2009112433	A1	9/2009
WO	2009147106		12/2009
WO	2010007783	A1	1/2010
WO	2010029730		3/2010
WO	2010043009		4/2010
WO	2010092627		8/2010
WO	2010127947		11/2010

WO	2010127947	A2	11/2010
WO	2011003711		1/2011
WO	2011058678		5/2011
WO	2011058678	A1	5/2011
WO	2011081498		7/2011
WO	2010007783	A1	1/2012
WO	2012023705		2/2012
WO	2012026715		3/2012
WO	2012031885		3/2012
WO	2012044001		4/2012
WO	2012043990		5/2012
WO	2012085212		6/2012
WO	2012119892		9/2012
WO	2012152646		11/2012
WO	2013116103		8/2013
WO	2013116302		8/2013
WO	2014038150		3/2014
WO	2014038150	A1	3/2014
WO	2014095542		6/2014
WO	2014121893	A1	8/2014
WO	2014184393		11/2014
WO	2014184393	A1	11/2014
WO	2013140816	A1	8/2015
WO	2016082907	A1	6/2016
WO	2017029782	A1	2/2017

OTHER PUBLICATIONS

BASF, "Balindur™ Solutions for fixing Vacuum Insulated Panels," web page, 4 pages, date unknown, <http://performance-materials.basf.us/products/view/family/balindur>, at least as early as Dec. 21, 2015.

BASF, "Balindur™," web page, 2 pages, date unknown, <http://product-finder.basf.com/group/corporate/product-finder/en/brand/BALINDUR>, at least as early as Dec. 21, 2015.

PU Solutions Elastogram, "Balindur™ masters the challenge," web page, 2 pages, date unknown, <http://product-finder.basf.com/group/corporate/product-finder/en/literature-document:/Brand+Balindur+Flyer+Balindur+The+new+VIP+fixation+technology-English.pdf>, Dec. 21, 2014.

Kitchen Aid, "Refrigerator User Instructions," 120 pages, published Sep. 5, 2015.

Cai et al., "Generation of Metal Nanoparticles by Laser Ablation of Microspheres," J. Aerosol Sci., vol. 29, No. 5/6 (1998), pp. 627-636.

Raszewski et al., "Methods for Producing Hollow Glass Microspheres," Powerpoint, cached from Google, Jul. 2009, 6 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 10




FIG. 11




FIG. 12

Method 400 for Installing a Pantry Box System into a Refrigerating Appliance




FIG. 13

1

SELF-CONTAINED PANTRY BOX SYSTEM FOR INSERTION INTO AN APPLIANCE

CROSS REFERENCE TO RELATED APPLICATION

The present application is a continuation of U.S. patent application Ser. No. 14/644,421 filed Mar. 11, 2015, entitled SELF-CONTAINED PANTRY BOX SYSTEM FOR INSERTION INTO AN APPLIANCE, the entire disclosure of which is hereby incorporated herein by reference.

FIELD OF THE INVENTION

The device is in the field of refrigerating appliances, specifically, a self-contained pantry box system for insertion into a refrigerating appliance.

BRIEF SUMMARY OF THE INVENTION

According to at least one aspect, a refrigerating appliance includes a cabinet having a plurality of sidewalls and a rear wall that define an interior volume. An interior mullion typically extends through a portion of the interior volume. The back wall, the sidewalls and the interior mullion define a refrigerator compartment and a freezer compartment, separated by the interior mullion. A refrigerator compartment door selectively covers at least a portion of the refrigerator compartment and a freezer compartment door selectively covers at least a portion of the freezer compartment. A plurality of doors may be used to enclose the refrigerator compartment and the freezer compartment, but typically a single or two doors enclose the compartments. A refrigeration system is also provided and typically includes a compressor, a condenser, an evaporator, an expansion device and a refrigerant. The refrigeration system operates to maintain the refrigerator compartment at a first temperature and maintain the freezer compartment at a second temperature typically lower than the first temperature and typically below freezing. A pantry box system is typically employed. The pantry box system defines a pantry compartment, and is disposed within a portion of the interior volume of the cabinet. The pantry box system includes a pantry wall and a base that define an internal pantry volume. At least one pantry drawer is in operable communication with the internal pantry volume. The at least one drawer is operable between open and closed positions. The at least one drawer includes an exterior drawer panel that conceals at least a portion of the pantry compartment and covers at least a portion of the refrigerator compartment when the at least one pantry drawer is in the closed position. A top mullion of the pantry box system includes an interstitial mullion space, a pantry box cooling system that provides cooled air from at least one of: the refrigerator compartment, the freezer compartment and the refrigeration system. The pantry box cooling system is typically configured to maintain the internal pantry volume at a third temperature and an interface portion defined within one of the sidewalls, back wall and interior mullion of the cabinet. The pantry box system engages the cabinet at the interface portion such that the refrigeration system is placed in communication with the pantry box cooling system.

According to at least another aspect, a pantry box system for installation in a refrigerator compartment of a refrigerating appliance includes a pantry mullion having an interstitial space defined therein. A pantry wall extends perpendicularly from the pantry mullion. A base is positioned

2

proximate the pantry wall and is positioned substantially parallel with the pantry mullion. The pantry mullion, the pantry wall and the base define an insertable pantry compartment having an internal pantry volume. At least one pantry drawer is in operable communication with the internal pantry volume. The at least one pantry drawer is operable through a drawer aperture defined in the pantry wall between open and closed positions. Each at least one pantry drawer includes an exterior drawer panel that conceals the drawer aperture when the at least one pantry drawer is in the closed position. A pantry box cooling system is configured to deliver cooling to the insertable pantry compartment from an external location when the insertable pantry compartment is positioned within an appliance. The pantry box cooling system includes a control that independently controls at least one pantry temperature of the internal pantry volume of the insertable pantry compartment.

At least another aspect of the present disclosure is generally directed to a method for installing a pantry box system into a refrigerating appliance to create a thermally independent pantry compartment includes the step of providing an appliance having a cabinet having a plurality of sidewalls and a rear wall that define an interior volume. The interior volume is divided by an interior mullion to further define a refrigerator compartment and a freezer compartment. According to various steps of the embodiments of the method, an appliance cooling system is provided having a compressor, a condenser, an evaporator, an expansion device and a refrigerant, wherein the appliance cooling system is incorporated within a machine component of the appliance and in communication with the refrigerator and freezer compartments. The appliance cooling system is configured to maintain the refrigerator compartment at a first temperature and maintain the freezer compartment at a second temperature, which is typically less than the first temperature and also typically below freezing. The appliance cooling system is in communication with an interface portion of the cabinet. A pantry box system is provided having a perimeter wall, a base and a pantry mullion that define an insertable pantry compartment, and a pantry box cooling system in communication with the insertable pantry compartment. A pantry ice maker is disposed, within an interstitial mullion space defined within the pantry mullion, and wherein the pantry ice maker is in communication with the pantry box cooling system. The pantry ice maker is configured to deliver ice to a portion of the pantry compartment. The pantry box system is positioned in the refrigerator compartment, wherein the insertable pantry compartment is defined within the refrigerator compartment. The pantry box system is connected to the interface portion of the cabinet such that the pantry box cooling system is in communication with the appliance cooling system, wherein the pantry box cooling system maintains the pantry compartment at a third temperature, and wherein the first, second and third temperatures can be independently modified. At least one pantry drawer is inserted into an aperture defined in the pantry compartment. Each at least one pantry drawer includes an exterior drawer panel that conceals at least a portion of the pantry compartment and covers at least a portion of the refrigerator compartment when the at least one pantry drawer is in the closed position.

These and other features, advantages, and objects of the present invention will be further understood and appreciated by those skilled in the art by reference to the following specification, claims, and appended drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing summary, as well as the following detailed description of the invention, will be better understood when

read in conjunction with the appended drawings. For the purpose of illustrating the invention, there are shown in the drawings, certain embodiment(s) which are presently preferred. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown. Drawings are not necessary to scale. Certain features of the invention may be exaggerated in scale or shown in schematic form in the interest of clarity and conciseness.

FIG. 1 is a front elevational view of a refrigerating appliance incorporating an embodiment of an insertable pantry box system;

FIG. 2 is a front perspective view of the appliance of FIG. 1 with the refrigerator doors and the pantry drawers in an open position;

FIG. 3 is a top perspective view of the insertable pantry box system installed within a refrigerating appliance;

FIG. 4 is another top perspective view of the pantry box system of FIG. 3;

FIG. 5 is a cross-sectional view of the refrigerating appliance of FIG. 1, taken along line V-V in FIG. 1;

FIG. 6 is a partially exploded cross-sectional view of the refrigerating appliance of FIG. 5 with the insertable pantry box system about to be installed into the refrigerator compartment of the refrigerating appliance;

FIG. 7 is a schematic cross-sectional view of the refrigerating appliance of FIG. 1, taken along line VII-VII in FIG. 1;

FIG. 8 is the schematic cross-sectional view of FIG. 7, but illustrating an alternate pantry box cooling system configuration installed in the pantry box system;

FIG. 9 is the schematic cross-sectional view of FIG. 7, but illustrating an alternate pantry box cooling system configuration installed in the pantry box system;

FIG. 10 is a partially exploded top perspective view of another alternate embodiment of the insertable pantry box system with the pantry drawers removed;

FIG. 11 is a partially exploded top perspective view of the insertable pantry box system of FIG. 4, removed from the appliance;

FIG. 12 is an exploded top perspective view of a refrigerating appliance incorporating another embodiment of the insertable pantry box system; and

FIG. 13 is a schematic flow diagram illustrating a method for installing a pantry box system into a refrigerating appliance.

DETAILED DESCRIPTION

Before the subject invention is described further, it is to be understood that the invention is not limited to the particular embodiments of the invention described below, as variations of the particular embodiments may be made and still fall within the scope of the appended claims. It is also to be understood that the terminology employed is for the purpose of describing particular embodiments, and is not intended to be limiting. Instead, the scope of the present invention will be established by the appended claims.

Where a range of values is provided, it is understood that each intervening value, to the tenth of the unit of the lower limit unless the context clearly dictates otherwise, between the upper and lower limit of that range, and any other stated or intervening value in that stated range, is encompassed within the invention. The upper and lower limits of these smaller ranges may independently be included in the smaller ranges, and are also encompassed within the invention, subject to any specifically excluded limit in the stated range.

Where the stated range includes one or both of the limits, ranges excluding either or both of those included limits are also included in the invention.

In this specification and the appended claims, the singular forms "a," "an" and "the" include plural reference unless the context clearly dictates otherwise.

As illustrated in FIGS. 1-7, reference numeral 10 generally refers to an insertable pantry box system configured to be installed within a refrigerator compartment 12 of a refrigerating appliance 14, according to one embodiment. The refrigerating appliance 14 can include a cabinet 16 having a plurality of sidewalls 18 and a rear wall 20 that define an interior volume 22. An interior mullion 24 of the refrigerating appliance 14 extends through a portion of the interior volume 22, where the rear wall 20, sidewalls 18 and the interior mullion 24 define a refrigerator compartment 12 and a freezer compartment 26 separated by the interior mullion 24. A refrigerator compartment door 28 selectively covers at least a portion of the refrigerator compartment 12. Also included is a freezer compartment door 30 that selectively covers the freezer compartment 26.

A refrigeration system 32 of the refrigerating appliance 14 includes a compressor, a condenser, an evaporator, an expansion device and a refrigerant (all not shown) that is moved through the refrigeration system 32. The refrigeration system 32 operates to maintain a refrigerator compartment 12 at a first temperature 34, and also maintain a freezer compartment 26 at a second temperature 36. Generally, the second temperature 36 of the freezer compartment 26 is lower than the first temperature 34 of the refrigerator compartment 12.

The pantry box system 10 defines a pantry compartment 38 and can be disposed within a portion of the interior volume 22 of the cabinet 16. It is contemplated that the pantry box system 10 can be installed within the refrigerator compartment 12 or the freezer compartment 26, as will be described more fully below.

According to the various embodiments, the pantry box system 10 can include a pantry wall 40 and a base 42 that define an internal pantry volume 44. At least one pantry drawer 46 is in operable communication with the internal pantry volume 44, where the at least one pantry drawer 46 is operable between the open position 100 (FIG. 2) and closed position 50 (FIG. 1). The at least one pantry drawer 46 includes an external drawer panel 48 that conceals at least a portion of the pantry compartment 38 and also covers at least a portion of a refrigerator compartment 12 when the at least one pantry drawer 46 is in the closed position 50 and the pantry box system 10 is installed within the refrigerator compartment 12. The pantry box system 10 can also include a top mullion 52 that defines an interstitial mullion space 54. The interstitial mullion space 54 can include a substantially hollow or open region within the top mullion 52. In this manner, the interstitial mullion space 54 is an open area that is capable of housing and allowing for the operation of various water-related, electrical and/or mechanical features of the refrigerating appliance 14, the pantry box system 10, or both.

Referring again to FIGS. 5-7, it is contemplated that a pantry box cooling system 56 of the pantry box system 10 can provide cooled air from at least one of the refrigerator compartment 12 (shown in FIG. 8), the freezer compartment 26, or the refrigeration system 32 of the refrigerating appliance 14 (shown in FIG. 9). The pantry box cooling system 56 is configured to maintain the internal pantry volume 44 at a third temperature 58. It is contemplated that the third temperature 58 of the internal pantry volume 44 can be the

same or different than either or both of the first and second temperatures 34, 36 of the refrigerator compartment 12 and freezer compartment 26, respectively. The cabinet 16 of the refrigerating appliance 14 can include an interface portion 60 that can be defined within one or more of the sidewalls 18, rear wall 20, or interior mullion 24 of the cabinet 16. It is contemplated that the pantry box system 10 can engage the cabinet 16 at the interface portion 60 such that the refrigeration system 32 is placed in communication with the pantry box cooling system 56 in order to maintain the internal pantry volume 44 at the third temperature 58.

Referring again to the embodiment illustrated in FIGS. 1-7, it is contemplated that in addition to the pantry box cooling system 56, the pantry box system 10 can also include a pantry water system 80 that is at least partially disposed within the interstitial mullion space 54 of the top mullion 52 of the pantry box system 10. It is contemplated that when the pantry box system 10 is engaged with the interface portion 60 of the refrigerating appliance 14, the pantry water system 80 is placed in communication with an appliance water system 82 of the refrigerating appliance 14. According to the various embodiments, the appliance water system 82 can provide water to the various functions of the refrigerating appliance 14 that require water, where such functions can include, but are not limited to, forming ice, delivering water, and other similar functions, where such functions can be performed at various and multiple locations within the refrigerating appliance 14. It is contemplated that the appliance water system 82 of the refrigerating appliance 14 can include various water lines 84 that are run through the cabinet 16 into a portion of the interface portion 60 of the refrigerating appliance 14. In this manner, the appliance water system 82 extends to and is in communication with the interface portion 60 of the cabinet 16.

Referring again to the embodiment illustrated in FIGS. 1-10, it is contemplated that the pantry box system 10 can include a pantry ice maker 90 that is disposed at least partially within the interstitial mullion space 54. The pantry ice maker 90 can be placed in communication with the pantry water system 80, such that when the pantry box system 10 is engaged with the interface portion 60 of the cabinet 16, the appliance water system 82 can provide water through the interface portion 60 and into the pantry water system 80 of the pantry box system 10 for delivery of water to the pantry ice maker 90. It is also contemplated that fluid from the appliance water system 82 can be routed directly through the interface portion 60 and directly to the pantry ice maker 90. In such an embodiment, the fluid from the appliance water system 82 can be filtered at a location within the appliance 14 before reaching the interface portion 60. It is also contemplated that the pantry ice maker 90 can be positioned within the interstitial mullion space 54 such that the pantry ice maker 90 is in communication with an ice/food bin 92 disposed within at least one of the pantry drawers 46 of the pantry box system 10. In this manner, the pantry ice maker 90 can be configured to deliver formed ice 94 from the pantry ice maker 90 to the ice/food bin 92 disposed within one of the drawers of the pantry box system 10.

According to the various embodiments, the pantry box system 10 can include at least two drawers, each individually operable within the pantry box system 10 between open and closed positions 100, 50. In this manner, the ice/food bin 92 for the pantry box system 10 can be disposed within one of the two or more pantry drawers 46 for receiving ice from the pantry ice maker 90 when the pantry drawer 46 is in the closed position 50. It is contemplated that the pantry box

system 10 can be configured such that the pantry ice maker 90 is temporarily disengaged from delivering ice when the pantry drawer 46 is moved to an open position 100, to prevent unwanted delivery of ice outside of the ice/food bin 92 disposed within one of the pantry drawers 46 of the pantry box system 10.

Referring again to the embodiment illustrated in FIGS. 1-7, the pantry box system 10 can include a water filter 110 and water tank 112 that are typically disposed within the interstitial mullion space 54, or at least partially within the interstitial mullion space 54. In this manner, the water filter 110 and water tank 112 are placed in communication with the pantry water system 80. According to the various embodiments, it is contemplated that water delivered to the pantry water system 80 through the interface portion 60 and from the appliance water system 82 can be first delivered to the water filter 110 disposed within the interstitial mullion space 54. Once filtered through the water filter 110 within the interstitial mullion space 54, water from the pantry water system 80 can then be delivered through the water utilizing portions of the pantry box system 10 that include, but are not limited to, the pantry ice maker 90, the water tank 112, a water delivery system, and other similar functions. In addition, the water filter 110 disposed within the interstitial mullion space 54 can be used as the water filtration mechanism for the entire refrigerating appliance 14, such that water can be delivered into the pantry water system 80, filtered through the water filter 110 disposed within the interstitial mullion space 54, and then delivered back through the interface portion 60 and into an outgoing portion of the appliance water system 82 for delivery to various functions of the refrigerating appliance 14 that require water and/or filtered water. It is also contemplated that the water tank 112 and the water filter 110 can be disposed in other portions of the pantry box system 10 or the refrigerating appliance 14.

Referring again to the embodiments illustrated in FIGS. 4-6, it is contemplated that the water filter 110 disposed within the interstitial mullion space 54 can be accessed by a user through a portion of the refrigerator compartment 12. Accordingly, an operable access panel 120 can be defined within a wall, such as a top wall 122, of the top mullion 52 of the pantry box system 10. In the various embodiments, when the water filter 110 is to be installed, replaced, maintained, or otherwise accessed by a user, the operable access panel 120 can be removed from the top wall 122 of the top mullion 52, thereby revealing the water filter 110 and allowing the user to directly access the water filter 110. It is contemplated that the operable access panel 120 can be moved from a concealing position 124 where the water filter 110 is concealed by the operable access panel 120 to an access position 126 where the operable access panel 120 is moved such that the water filter 110 is accessible to the user. In order to move the operable access panel 120 to the access position 126, the operable access panel 120 can include various operable mechanisms that can include, but are not limited to, hinge mechanisms, sliding mechanisms, mating tabs for complete removal of the operable access panel 120, combinations of these mechanisms and other similar attachment mechanisms that provide for the movement of the operable access panel 120 between the concealing and access positions 124, 126.

Referring again to the embodiment illustrated in FIGS. 4-6, it is contemplated that the water filter 110 and the operable access panel 120 that provides access to the water filter 110 can be disposed in a front portion 140 of the top mullion 52 in a position near the refrigerator compartment

door 28 of the refrigerating appliance 14. In this manner, the operable access panel 120 can be disposed such that the user is only required to open the refrigerator compartment door 28 in order to access the operable access panel 120 for gaining access to the water filter 110. Such a position of the water filter 110 in the operable access panel 120 can allow the user to access the water filter 110 without manipulating shelves within the refrigerator compartment 12, moving food items or other containers stored within the refrigerator compartment 12, or having to move other various objects that are stored within the refrigerator compartment 12. The positioning of the operable access panel 120 and the water filter 110 in front of the refrigerator compartment 12 provides the user with ready access to the water filter 110. According to the various embodiments, it is contemplated that the operable access panel 120 can include a color and finish that is substantially similar to the surrounding areas of the refrigerator compartment 12 and the top mullion 52 of the pantry box system 10. In this manner, the operable access panel 120 for the water filter 110 can be substantially inconspicuous within the refrigerator compartment 12.

According to the various embodiments, it is also contemplated that the water filter 110 can be disposed in other portions of the pantry box system 10. In an alternate embodiment, the water filter 110 and operable access panel 120 can be positioned at the front portion 140 of the top mullion 52, where the operable access panel 120 can be defined within a front face 150 of the top mullion 52. In another alternate embodiment, the water filter 110 can be accessed through an operable access panel 120 disposed within an area proximate the internal pantry volume 44. In such an embodiment, the movement of one or more of the pantry drawers 46 toward the open position 100 may be required such that the user can reach an underside 152 of the interstitial mullion space 54 to move the operable access panel 120 to the access position 126 and reach the water filter 110. Such a position can be used where greater concealment of the operable access panel 120 is desired.

Referring again to the embodiment illustrated in FIGS. 1-6, it is contemplated that the pantry box system 10 can include a plurality of pantry drawers 46, where the pantry box system 10 can include a first drawer 170 and a second drawer 172 that are separated by a medial wall 174 extending through a portion of the pantry box system 10. In such an embodiment, it is contemplated that the first and second drawers 170, 172 are placed in communication with the pantry box cooling system 56. It is also contemplated that the first drawer 170 can be maintained at the third temperature 58 of the pantry box system 10 and the second drawer 172 of the pantry box system 10 can be maintained at a fourth temperature 176. In such an embodiment, the first temperature 34 of the refrigerator compartment 12, the second temperature 36 of the freezer compartment 26, the third temperature 58 of the first drawer 170 and the fourth temperature 176 of the second drawer 172 can all be independently adjustable and separately controlled to define a plurality of temperatures. Accordingly, the first, second, third and fourth temperatures 34, 36, 58, 176 can be set to the same temperature or can be set four different individual temperatures, or combinations of similar and dissimilar temperatures.

According to the various embodiments, the pantry box system 10 can include one or more insulated panels 190 that are defined by the top mullion 52, the pantry wall 40, the base 42, and the medial wall 174, such that thermal transfer between the various compartments of the refrigerating appliance 14 can be accurately controlled. According to various

embodiments, because of the insulated panels 190 of the pantry box system 10, one or both of the pantry drawers 46 can be maintained at a temperature above or below the refrigerator compartment 12 and/or the freezer compartment 26. Thermal transfer between the first and second drawers 170, 172 and the freezer and refrigerator compartment 26, 12 can be minimized due to the presence of the insulated panels 190 of the pantry box system 10.

Referring again to FIGS. 1-7, it is also contemplated that the pantry box cooling system 56 can include various pantry ducts 270 extending between the refrigerator and/or freezer compartment 12, 26 to deliver chilled air from within the refrigerator and/or freezer compartments 12, 26 for providing cooling to the first and/or second drawers 170, 172. Accordingly, the first drawer 170 can define a refrigerator pantry compartment 12a or a freezer pantry compartment 26a. Similarly, the second drawer 172 can also define a refrigerator pantry compartment 12a or a freezer pantry compartment 26a, regardless of what temperature the first drawer 170 may be set at. Additionally, the medial wall 174 extending between the first and second drawers 170, 172 provides further insulation through the insulated panel 190 to prevent thermal transfer between the first and second drawers 170, 172.

Referring again to the embodiment illustrated in FIGS. 1-7, it is contemplated that one or more of the pantry drawers 46 can include a viewing window 200 disposed within the exterior drawer panel of one or both of the first and second drawers 170, 172. Such a viewing window 200 can be substantially insulated to prevent the substantial escape of cooled air when the first and second drawers 170, 172 are in the closed position 50. Such a viewing window 200 can also provide the user an opportunity to view of the contents of the first and/or second drawers 170, 172 without requiring the user to move the first or second drawers 170, 172 to an open position 100, which may tend to release cooled air to external portions of the refrigerating appliance 14, and thereby require the use of additional energy to bring the first and/or second drawers 170, 172 back to the desired third and fourth temperatures 58, 176, respectively.

Referring again to the embodiments illustrated in FIGS. 3 and 4, it is contemplated that one of the first and second drawers 170, 172 can include the ice/food bin 92 that receives formed ice 94 from the pantry ice maker 90. It is contemplated that the ice/food bin 92 can include first and second ice/food compartments 210, 212 that are independently and selectively removable from the first drawer 170. It is also contemplated that at least one of the first and second ice/food compartments 210, 212 can be viewed through the viewing window 200 disposed within the external drawer panel 48 of the first and/or second drawer 170, 172 that houses the ice/food bin 92 when the particular pantry drawer 46 is in the closed position 50. According to the various embodiments, it is contemplated that the first and second ice/food compartments 210, 212 can take up substantially all of the internal space of the first drawer 170 of the pantry box system 10. In such an embodiment, substantial amounts of ice can be stored within the first drawer 170. Such amounts of ice can be up to ten pounds of ice or more, depending on the size of the first drawer 170.

In various alternate embodiments, it is contemplated that the ice/food bin 92 can include a single compartment, where the single compartment can be slid within the first drawer 170. According to the various embodiments, it is contemplated that the ice/food bin 92 having a single ice/food compartment can be moved between a forward and rearward position 220, 222 within the first drawer 170. When in one

of these positions, the ice/food bin **92** can be placed in communication with the pantry ice maker **90** such that ice can be delivered to the ice/food bin **92**. It is contemplated that once a predetermined amount of ice is disposed within the ice/food bin **92**, the pantry ice maker **90** can be deactivated through the use of various ice monitoring mechanisms. According to various alternate embodiments, it is contemplated that the movement of the ice/food bin **92** between the forward and rearward positions **220**, **222** can serve to activate and deactivate the pantry ice maker **90**. In such an embodiment, the placement of the ice/food bin **92** in one of the forward and rearward positions **220**, **222** can activate the pantry ice maker **90**. It is contemplated that the movement of the ice/food bin **92** to the opposing position can be configured to deactivate the pantry ice maker **90**, such that no ice will be delivered to the ice/food bin **92** or the pantry drawer **46** in the absence of the ice/food bin **92** being in the proper position to activate the pantry ice maker **90**.

According to the various embodiments, the various ice/food bins **92** can be suspended from sidewalls or on a lip of the first drawer **170** and/or the second drawer **172**. It is contemplated that the various ice/food bins **92** can be removed by hand and without the use of tools. Any one or more of the ice/food bins **92** can be adapted to contain ice or food stuffs within the respective ice/food compartment defined therein. It is also contemplated that an ice/food bin in the forward position **220** can be engaged with an ice/food bin in the rearward position **222** to store added amounts of ice, such as for use during a high ice-usage event like a party or other social gathering, or during production of ice cream, or other substantially similar occurrence. It is also contemplated that the various ice/food bins **92** can be supported by the bottom surface of either of the pantry drawers **46**.

Referring again to the embodiment illustrated in FIGS. **5** and **6**, the pantry box system **10** can be manufactured in a separate facility from the remainder of the refrigerating appliance **14**. The pantry box system **10** can include the various mechanisms for providing functionalities for the pantry box system **10**, where such functions can include the pantry ice maker **90**, the water filter **110**, the water tank **112**, the ice/food bin **92**, a water delivery system, combinations of these, and other similar functional mechanisms. Accordingly, the pantry box system **10** can be manufactured as a self-contained unit that can be delivered to the appliance assembly location, which can be in a separate building or manufacturing facility. The remainder of the refrigerating appliance **14**, including the refrigerator compartment **12**, the freezer compartment **26**, the various doors of the refrigerator and freezer compartment **12**, **26** can be manufactured at a separate location, and the pantry box system **10** can be inserted into the refrigerator compartment **12** or the freezer compartment **26** as an entire unit during manufacture of the refrigerating appliance **14**.

Referring now to the embodiments illustrated in FIGS. **5-9**, as the pantry box system **10** is inserted within the refrigerator or freezer compartment **12**, **26**, a pantry box interface **240** disposed upon a portion of the pantry box system **10** can be engaged with the interface portion **60** of the cabinet **16** of the refrigerating appliance **14**. It is contemplated that the engagement between the pantry box interface **240** and the interface portion **60** can be a substantially "plug-and-play" connection, whereby the insertion of the pantry box system **10** into an installed position **242** within the refrigerator and/or freezer compartment **12**, **26** can automatically engage the appliance water system **82** with the pantry water system **80**. It is also contemplated that at least some tightening or manual engagement of connec-

tions between the various portions of the cabinet **16** and the pantry box, using tools or by hand and without the use of tools, can serve to connect the systems together.

By way of explanation, and not limitation, a cabinet connection port **250** of the appliance water system **82** that extends into the area where the pantry box system **10** is to be disposed to define the installed position **242**, can include a nut, weld point, or other fastening mechanism that is installed to a receiving portion of the pantry water system **80** that is configured to engage the appliance water system **82**. These connection points can be fixed together through a mechanical mechanism, such as through a compression fitting, male/female connector, or other similar connection.

As illustrated in the embodiments of FIGS. **5-9**, it is also contemplated that the pantry box cooling system **56** can be engaged with the refrigeration system **32** of the cabinet **16** through the installation of the pantry box system **10** into the installed position **242** within the cabinet **16** of the refrigerating appliance **14**. In various embodiments, the pantry box cooling system **56** can include one or more pantry ducts **270** that engage corresponding appliance ductwork **272** running from at least one of the refrigerator compartment **12** and/or the freezer compartment **26**. The pantry ducts **270** of the pantry box cooling system **56** provide for the delivery of air from the refrigerator and/or freezer compartment **12**, **26** and/or from the cooling tower **370** into the first and second drawers **170**, **172** of the pantry box system **10**. The pantry ducts **270** of the pantry box cooling system **56** can also include various dampers **274** that can be controlled to regulate the amount of cooled air that is delivered to the first and second drawers **170**, **172** from the refrigerator and/or freezer compartments **12**, **26**, and/or from the cooling tower **370**.

According to various alternate embodiments, as illustrated in FIG. **9**, it is contemplated that the pantry box cooling system **56** can include a pantry refrigeration line **276** that connects to one or more pantry evaporators **278**, where the pantry refrigeration line **276** engages an appliance refrigeration line **280** of the refrigeration system **32** of the refrigerating appliance **14**. In this manner, when the pantry box system **10** is placed in the installed position **242**, it is contemplated that the pantry refrigeration line **276** can substantially align with the appliance refrigeration line **280**.

It is contemplated that the pantry refrigeration line **276** can provide refrigerant to a single pantry evaporator **278** configured to provide cooling to the first and second drawers **170**, **172**. Alternatively, the pantry refrigeration line **276** can provide refrigerant to two dedicated pantry evaporators **278** that individually and separately provide cooling to the first and second drawers **170**, **172** to maintain the third and fourth temperatures **58**, **176**, respectively.

Typically, the connection of two refrigeration lines requires bonding, welding, adhesives, or other similar connection method to fully connect the two opposing refrigeration lines together to prevent refrigerant leaks. It is also contemplated that the refrigeration line can incorporate a compression or other mechanical-type fitting to engage the pantry refrigeration line and the appliance refrigeration line to place the pantry box cooling system **56** in communication with the refrigeration system **32** of the refrigerating appliance **14**. During operation of the refrigerating appliance **14** having the pantry box system **10** installed therein, refrigerant from the appliance refrigeration system **32** can be delivered to the one or more evaporators disposed within the pantry box cooling system **56** such that cooling can be delivered to the first and second drawers **170**, **172** of the pantry box system **10**.

According to various alternate embodiments, the pantry box system 10 can include a self-contained pantry box cooling system 56 that includes a separate pantry compressor, pantry condenser, pantry expansion device, and the one or more pantry evaporators, as well as a separate pantry refrigerant that is delivered through the self-contained pantry box cooling system 56. In such an embodiment, installation of the pantry box system 10 into the cabinet 16 of the refrigerating appliance 14 can include connection of the electrical system of the refrigerating appliance 14 with a pantry electrical system for operating the various electrical functions of the pantry box system 10. It is also contemplated that in various embodiments of the pantry box system 10 that do not have a self-contained pantry box cooling system 56, as described above, the insertion of the pantry box system 10 into the installed position 242 within the cabinet 16 of the refrigerating appliance 14 can include connection of the appliance electrical system with the pantry electrical system to provide electrical power for the various electrical functions of the pantry box system 10. Such electrical functions of the pantry box system 10 can include, but are not limited to, lights, a user interface, fog/condensation control mechanisms, heaters, among others.

Referring again to the embodiment illustrated in FIGS. 5 and 6, the interior surface 288 of the cabinet 16 of the refrigerating appliance 14 can include guide surfaces 290 within the refrigerator and/or freezer compartments 12, 26 that serve to substantially align the pantry box system 10 within the cabinet 16 of the refrigerating appliance 14. The guide surfaces 290 defined within the interior surface 288 of the cabinet 16 can also serve to substantially secure the pantry box system 10 within the cabinet 16 of the refrigerating appliance 14 in the installed position 242.

According to the various embodiments, it is contemplated that when the pantry box system 10 is installed within the cabinet 16 of the refrigerating appliance 14, a finished inner liner 350 can be disposed within the cabinet 16 to provide a finished surface for the refrigerator and/or freezer compartment 12, 26 that contains the pantry box system 10. In such an embodiment, the finished liner 350 can provide a surface that substantially conceals the scene that appears between the pantry box system 10 and the refrigerator or freezer compartment 12, 26 within which the pantry box system 10 is installed.

Referring again to FIGS. 1-6, the refrigerator compartment doors 28 can include different configurations that can be incorporated into the refrigerating appliance 14 depending on whether the pantry box system 10 is installed in the refrigerator compartment 12 or not. A set of bottom hinges 300 for the refrigerator compartment doors 28 can be disposed proximate the top mullion 52 of the pantry box system 10. In this manner, the refrigerator compartment doors 28 are configured to extend from the top of the external drawer panels 48 for the pantry drawers 46 to a position proximate the top of the refrigerating appliance 14. Alternatively, where the pantry box system 10 is not installed in the refrigerator compartment 12, the bottom hinges 300 can be installed proximate the interior mullion 24. In this configuration, the refrigerator compartment doors 28 can be longer to extend from the top of the freezer compartment door 30 to the top of the refrigerating appliance 14. This alternate bottom hinge positioning can allow for the manufacture of a base cabinet 310 for a refrigerating appliance 14. This base cabinet 310 can be used for a variety of models of refrigerating appliances 14 that can incorporate varying configurations of pantry compartment 38 (single drawer, multi-drawer, swaying door, etc.), or no pantry

compartment 38 at all. This flexibility of the base cabinet 310 can save time, material, labor and cost by not having to manufacture separate cabinets 16 for each model of refrigerating appliance 14.

Referring now to the embodiment illustrated in FIGS. 10 and 11, the pantry box system 10 can include the pantry mullion, which can correspond to the top mullion 52 discussed above. The pantry mullion includes the interstitial space within. The pantry wall 40 extends perpendicularly from the pantry mullion, and the base 42 is positioned proximate the pantry wall 40 and is substantially parallel with the pantry mullion. In such an embodiment, the pantry mullion, the pantry wall 40 and the base 42 define the insertable pantry compartment 38 having an internal pantry volume 44. It is contemplated that the one or more pantry drawers 46 can be disposed within the insertable pantry compartment 38 so as to be in operable communication with the internal pantry volume 44. The at least one pantry drawer 46 can be operable through a drawer aperture 320 that is defined in the pantry wall 40, where the one or more pantry drawers 46 are operable between the open and closed positions 100, 50. It is also contemplated that the at least one pantry drawer 46 can include the external drawer panel 48 that is configured to conceal the drawer aperture 320 when the at least one pantry drawer 46 is in the closed position 50. Additionally, the pantry box cooling system 56 can be installed within a portion of the insertable pantry compartment 38, wherein the pantry box cooling system 56 is configured to deliver cooling to the insertable pantry compartment 38 from an external location when the insertable pantry compartment 38 is positioned within a refrigerating appliance 14. It is also contemplated that a pantry box cooling system 56 can include a control that independently controls at least one pantry temperature of the internal pantry volume 44 of the insertable pantry compartment 38.

Referring again to the embodiments illustrated in FIGS. 10 and 11, the insertable pantry compartment 38 can include the medial wall 174 that divides the internal pantry volume 44 into first and second pantry compartments 330, 332. In such an embodiment, first and second drawers 170, 172 are slidably engaged with the first and second pantry compartments 330, 332, respectively. Additionally, the medial wall 174 is configured to extend between the pantry mullion and the base 42. According to the various embodiments, the medial wall 174 can include an insulated panel 190 that substantially prevents thermal infiltration between the first and second pantry compartments 330, 332 of the insertable pantry compartment 38.

Referring again to the embodiment illustrated in FIGS. 10 and 11, the first and second pantry compartments 330, 332 are configured to be in communication with the pantry box cooling system 56. In this manner, the first pantry compartment 330 is configured to be maintained at a first compartment temperature, corresponding to the third temperature 58. Additionally, the second pantry compartment 332 can be configured to be maintained at a second compartment temperature, corresponding to the fourth temperature 176, wherein the first and second compartment temperatures are independently adjustable and can define the same or different temperatures. Accordingly, the first pantry compartment 330 can be one of a refrigerator pantry compartment 12a or a freezer compartment 26a. Simultaneously, the second pantry compartment 332 can also define independent of the first pantry compartment 330 either a separate refrigerator pantry compartment 12a or a separate freezer pantry compartment 26a, irrespective of the first compartment temperature of the first pantry compartment 330.

13

According to the various embodiments, it is contemplated that the at least one or both of the first and second pantry compartments **330**, **332** can be placed in communication with a heating mechanism. In such an embodiment, the first and/or second pantry compartments **330**, **332** can be configured to be a heating compartment or warmer/thawing compartment disposed within the refrigerating appliance **14**. In such an embodiment, the various insulated panels **190** disposed within the pantry box system **10** and the refrigerating appliance **14** serve to prevent thermal transfer between the refrigerator compartment **12**, the freezer compartment **26** and the first and second pantry compartments **330**, **332** such that the various compartments can define refrigerator or freezer compartment **12**, **26** or a heating compartment of the refrigerating appliance **14**.

According to the various embodiments, the pantry box system **10** can be installed as a pantry compartment **38** within any one of various appliances. Such appliances can include, but are not limited by, a refrigerating appliance **14**, a freezing appliance, a cooler, a warming appliance or other similar temperature-regulating appliance. It is also contemplated that an appliance can include two or more separate pantry box systems **10** disposed therein that define a plurality of pantry compartments **38**. It is further contemplated that a particular appliance can be filled with only pantry box systems **10**, where all of the various temperature-controlled compartments of the appliance are pantry compartments **38** defined by the various pantry box systems **10** disposed therein.

Referring now to the embodiments illustrated in FIGS. **1-13**, having described various embodiments of the pantry box system **10** that is configured to be disposed within a refrigerating appliance **14**, a method **400** is disclosed for installing a pantry box system **10** into a refrigerating appliance **14** to create a pantry compartment **38** that is thermally independent. According to the method **400**, a refrigerating appliance **14** is provided, where the refrigerating appliance **14** includes a cabinet **16** having a plurality of sidewalls **18** and a rear wall **20** that defines an interior volume **22**. It is contemplated that the interior volume **22** can be divided by an interior mullion **24** to further define the refrigerator compartment **12** and the freezer compartment **26** of the refrigerating appliance **14** (step **402**). An appliance cooling system is also provided, where the appliance cooling system includes a compressor, condenser, evaporator, expansion device, and a refrigerant (step **404**). It is contemplated that the appliance cooling system can be disposed within the cabinet **16** and placed in communication with the refrigerator and freezer compartments **12**, **26**. The appliance cooling system is also configured to maintain the refrigerator compartment **12** at the first temperature **34** and also maintain the freezer compartment **26** at the second temperature **36**. The appliance cooling system is also in communication with an interference portion of the cabinet **16**.

Referring again to FIGS. **1-13**, according to the method **400**, a pantry box system **10** is also provided where the pantry box system **10** includes a pantry wall **40**, a base **42** and a pantry top mullion **52** that cooperate to define an insertable pantry compartment **38**, and a pantry box cooling system **56** that is in communication with the insertable pantry compartment **38** (step **406**). According to the various embodiments, the pantry wall **40** can include a perimetrical pantry wall **40** that extends around the outside of the insertable pantry compartment **38**. It is also contemplated that the pantry wall **40** can include one or more exterior walls that extend between a portion of the pantry top mullion **52** and the base **42**.

14

According to various alternate embodiments, the pantry wall **40** can include a series of supports that extend around a perimeter of the pantry box system **10**. In such an embodiment, the vertical supports can serve to position the pantry mullion relative to the base **42**. When the pantry box system **10** is installed into the cabinet **16** of the refrigerating appliance **14**, the surface of the liner **350** defined within the cabinet **16** cooperates with the insertable pantry compartment **38** to define the walls of the first and second pantry compartments **330**, **332**. Accordingly, the pantry box system **10**, in such an embodiment, is not fully enclosed, but serves to cooperate with the liner **350** of the cabinet **16** to define an enclosed internal pantry volume **44** when the pantry box system **10** is installed within the cabinet **16**. Similarly, the base **42** and/or the pantry mullion, depending upon the location that the pantry box system **10** is installed within the cabinet **16**, can include spaces or gaps that are filled by the bottom or top surface of the interior mullion **24** of the refrigerating appliance **14**, depending upon the location of the pantry box system **10**.

By way of example, and not limitation, where the pantry box system **10** is disposed within the refrigerator compartment **12** and at least partially resting on the interior mullion **24** of the refrigerating appliance **14**, the base **42** of the pantry box system **10** can cooperate with the liner **350** at the top of the interior mullion **24** to fully enclose the internal pantry volume **44** of the pantry box system **10**.

Referring again to the embodiments illustrated in FIGS. **1-13**, the method **400** includes disposing a pantry ice maker **90** within the interstitial mullion space **54** defined within the pantry mullion (step **408**). In such an embodiment, the pantry ice maker **90** is configured to be in communication with a pantry box cooling system **56**. In various embodiments, the pantry ice maker **90** can include a dedicated evaporator that is connected to a refrigerant line extending at least partially through the interstitial mullion space **54** and which is in communication with the refrigeration system **32** of the refrigerating appliance **14**. It is also contemplated that the pantry ice maker **90** is configured to deliver ice to a portion of the pantry compartment **38**. According to the various embodiments, the pantry ice maker **90** can extend at least partially into the first or second pantry compartments **330**, **332**, where a bottom portion of the pantry ice maker **90** includes a sensing mechanism that determines the amount of ice that has been delivered and currently rests within the first and/or second pantry compartment **330**, **332** into which ice has been disposed from the pantry ice maker **90**.

Referring again to FIG. **13**, according to the method **400**, the pantry box system **10** is positioned within the refrigerator compartment **12** (step **410**). Accordingly, the insertable pantry compartment **38** can be incorporated within the refrigerator compartment **12**. Due to the various insulated panels **190**, the pantry compartment **38**, while positioned within the interior volume **22** of the refrigerator compartment **12**, is thermally independent from the refrigerator compartment **12**. It is also contemplated that the pantry box system **10** can be installed within the freezer compartment **26** of the refrigerating appliance **14**, wherein the insertable pantry compartment **38** would, in such an embodiment, be defined within, and thermally separate from, the freezer compartment **26** of the refrigerating appliance **14**.

After being installed within the refrigerator compartment **12** (or freezer compartment **26**), the pantry box system **10** is connected to the interface portion **60** of the cabinet **16**, such that the pantry box cooling system **56** is placed in communication with the appliance cooling system (step **412**). Accordingly, the pantry box cooling system **56** can be

15

configured to maintain the first pantry compartment **330** at the third temperature **58** and the second pantry compartment **332** at the fourth temperature **176**. As discussed earlier herein, it is contemplated that the first, second, third and fourth temperatures **34**, **36**, **58**, **176** of the refrigerating appliance **14** can be separately and independently modified relative to one another.

Referring again to the embodiments illustrated in FIGS. **1-10**, at least one pantry drawer **46**, such as a first and second drawer **170**, **172**, can be inserted into an aperture defined within the insertable pantry compartment **38**. Due to the presence of the medial wall **174** extending through the pantry box system **10**, the insertable pantry compartment **38** can include first and second apertures **360**, **362** for receiving the first drawer **170** within the first pantry compartment **330**, and the second drawer **172** within the second pantry compartment **332**, respectively (step **414**).

According to the various embodiments, when the first and second drawers **170**, **172** are inserted within the first and second apertures **360**, **362** defined within the insertable pantry compartment **38**, the exterior drawer panels of the first and second drawers **170**, **172** serve to conceal at least a portion of the pantry compartment **38** and also cover at least a portion of the refrigerator compartment **12** when the first and/or second drawers **170**, **172** are in the closed position **50**. As discussed above, when the pantry box system **10** is installed within the refrigerator compartment **12** of the refrigerating appliance **14**, additional systems of the pantry box system **10** can be connected with various systems of the refrigerating appliance **14**. Such systems can include, but are not limited to, the pantry water system **80** being connected to the appliance water system **82**, the pantry box cooling system **56** being connected to the appliance refrigeration system **32**, the pantry electrical system being connected to the appliance electrical system and other similar connected pantry/appliance systems. As discussed above, it is contemplated that at least a portion of these systems can be connected by hand and without the use of tools or by inserting the pantry box system **10** into the installed position **242** within the cabinet **16** of the refrigerating appliance **14**. Additionally, the guide surfaces **290** defined within the inside surface of the liner **350** of the cabinet **16** can serve to guide the pantry box interface **240** into connection with the interface portion **60** of the refrigerating appliance **14** such that the installed position **242** of the pantry box system **10** defines the connection between the various systems of the pantry box system **10** and the refrigerating appliance **14**. Alternatively, certain utility systems of the pantry box system **10** can be connected to the corresponding systems of the refrigerating appliance **14** by the use of tools for tightening, adhering, welding or performing some other connection method.

According to the various embodiments, the interface portion **60** of the cabinet **16** can be defined within a rear portion **368** of the refrigerating appliance **14** such as in the cooling tower **370** or similar structure defined within the refrigerator compartment **12**. In such an embodiment, the cooling tower **370** can include various mechanical interfaces that define the interface portion **60** of the refrigerating appliance **14**. Similarly, a corresponding portion of the pantry box interface **240** of the pantry box system **10** can engage a portion of the cooling tower **370** to place the pantry box interface **240** in communication with the interface portion **60** of the refrigerating appliance **14**. It is also contemplated that the interface portion **60** of the refrigerating appliance **14** can be in portions distal from the back wall of the refrigerating appliance **14**, such as in a sidewall **18** of

16

the liner **350**, within a portion of the internal mullion, or other similar position. It is contemplated that whatever the position of the interface portion **60** of the refrigerating appliance **14**, it is a position that is substantially engaged by the pantry box system **10** when the pantry box system **10** is placed in the installed position **242** within the refrigerating appliance **14**.

Referring again to the embodiment illustrated in FIG. **9**, the pantry box system **10** can include a recess portion **380** that cooperates with the geometry of the cooling tower **370** disposed within the backwall **382** of the refrigerator compartment **12**. Accordingly, the pantry wall **40** of the pantry box system **10** can matingly engage the backwall **382** of the refrigerator compartment **12**. It is contemplated that the mating engagement with the pantry wall **40** and the various geometries of the refrigerator compartment **12** can serve to further locate the pantry box system **10** within the refrigerator compartment **12** to further align the pantry box interface **240** with the interface portion **60**.

The invention claimed is:

1. A refrigerating appliance comprising:

- a cabinet having an interior volume, wherein an interior mullion extends through the interior volume to define refrigerator and freezer compartments within the interior volume;
- a refrigeration system that operates to maintain the refrigerator and freezer compartments at first and second temperatures, respectively, the refrigeration system having an interface portion defined within the cabinet;
- an appliance water system disposed within the cabinet, wherein a portion of the appliance water system extends to the interface portion of the cabinet; and
- a pantry box system having a pantry compartment and disposed within the refrigerator compartment, the pantry box system comprising:
 - at least one pantry drawer, wherein each pantry drawer is operable between open and closed positions and includes an exterior drawer panel that conceals at least a portion of the pantry compartment and covers a portion of the refrigerator compartment when each pantry drawer is in the closed position;
 - a top mullion having a bottom panel that defines a lower boundary of an interstitial mullion space of the top mullion and a top boundary of the pantry compartment;
 - a pantry water system at least partially disposed within the interstitial mullion space, wherein a portion of the pantry water system is disposed on top of the bottom panel of the top mullion, wherein engagement of the pantry box system with the interface portion places the pantry water system in communication with the appliance water system, wherein a water filter and water tank are disposed within the interstitial mullion space, wherein the water filter and water tank are in communication with the pantry water system, and wherein the water filter is selectively removable from the interstitial mullion space through an operable access panel defined within a wall of the top mullion, and
 - a pantry box cooling system that provides cooled air to the pantry compartment from at least one of the refrigerator compartment, the freezer compartment and the refrigeration system, wherein the pantry box cooling system is configured to maintain the pantry compartment at a third temperature, wherein the

pantry box cooling system engages the interface portion to communicate with the refrigeration system.

2. The refrigerating appliance of claim 1, wherein the at least one pantry drawer includes first and second drawers that are selectively and independently operable between the open and closed positions.

3. The refrigerating appliance of claim 1, wherein a pantry ice maker is disposed at least partially within the interstitial mullion space, wherein the pantry ice maker is in communication with the pantry water system, and wherein the pantry ice maker is also in communication with an ice bin disposed within the at least one pantry drawer when the at least one pantry drawer is in the closed position, such that the pantry ice maker delivers formed ice to the ice bin.

4. The refrigerating appliance of claim 2, wherein the first and second drawers are separated by a medial wall that extends between the interior mullion and the bottom panel.

5. The refrigerating appliance of claim 4, wherein first and second drawers are in communication with the pantry box cooling system wherein the first drawer is maintained at the third temperature and the second drawer is maintained at a fourth temperature, wherein the first, second, third and fourth temperatures are independently adjustable to define a plurality of temperatures.

6. The refrigerating appliance of claim 4, wherein the at least one pantry drawer includes first and second drawers, and wherein the first drawer includes the ice bin, wherein the ice bin includes first and second ice compartments that are independently and selectively removable from the first drawer, and wherein the first drawer includes a viewing window disposed within the exterior drawer panel that allows the ice bin to be viewed from an exterior of the cabinet when the first drawer is in the closed position.

7. A pantry box system for installation in a compartment of an appliance, the pantry box system comprising:

a pantry mullion having a bottom panel that at least partially defines an interstitial space defined within the pantry mullion, wherein the interstitial space within the pantry mullion includes a pantry water system positioned above the bottom panel;

a pantry wall extending perpendicularly from the pantry mullion, wherein the pantry mullion and the pantry wall define an insertable pantry compartment having an internal pantry volume;

at least one pantry drawer in operable communication with the internal pantry volume, the at least one pantry drawer operable through a drawer aperture defined in the pantry wall between open and closed positions, wherein each at least one pantry drawer includes an exterior drawer panel that conceals the drawer aperture when the at least one pantry drawer is in the closed position, wherein a pantry ice maker is disposed at least partially within the interstitial space, wherein the pantry ice maker is in communication with the pantry water system, and wherein the pantry ice maker is also in

communication with an ice bin disposed within the at least one pantry drawer when the at least one pantry drawer is in the closed position, such that the pantry ice maker delivers former ice to the ice bin;

a pantry box cooling system that is configured to deliver cooling to the insertable pantry compartment from an external location when the insertable pantry compartment is positioned within the appliance; and

a pantry box interface that is configured to engage the appliance wherein the pantry box cooling system is in communication with the pantry box interface, wherein the pantry water system is at least partially disposed within the interstitial space and is in communication with the pantry box interface, and wherein the pantry box interface is positioned on a portion of the insertable pantry compartment.

8. The pantry box system of claim 7, wherein the insertable pantry compartment includes a medial wall that divides the internal pantry volume into first and second pantry compartments, wherein the at least one pantry drawer includes first and second drawers that are slidably engaged with the first and second pantry compartments, respectively, and wherein the medial wall extends between the pantry mullion and a base, the base being substantially parallel with the pantry mullion.

9. The pantry box system of claim 7, wherein a water filter is disposed within the interstitial space and is in communication with the pantry water system, wherein the water filter and water tank are in communication with the pantry water system and an appliance water system, and wherein the water filter is selectively removable from the interstitial space through an operable access panel defined within a wall of the pantry mullion.

10. The pantry box system of claim 8, wherein first and second pantry compartments are in communication with the pantry box cooling system wherein the first pantry compartment is configured to be maintained at a first compartment temperature, and wherein the second pantry compartment is configured to be maintained at a second compartment temperature, wherein the first and second compartment temperatures are independently adjustable.

11. The pantry box system of claim 7, wherein the at least one pantry drawer includes first and second drawers, and wherein the first drawer includes the ice bin, wherein the ice bin includes first and second ice compartments that are independently and selectively removable from the first drawer, and wherein the first drawer includes a viewing window disposed within the exterior drawer panel that allows the ice bin to be viewed from an exterior of an appliance cabinet when the first drawer is in the closed position.

12. The pantry box system of claim 7, wherein the pantry box cooling system includes a control that independently controls at least one pantry temperature of the internal pantry volume of the insertable pantry compartment.

* * * * *