



US010774870B2

(12) **United States Patent**
Kang et al.

(10) **Patent No.:** **US 10,774,870 B2**
(45) **Date of Patent:** **Sep. 15, 2020**

(54) **VACUUM SUCTION DEVICE AND ELECTRONIC DEVICE INCLUDING THE SAME**

(71) Applicant: **Samsung Electronics Co., Ltd.**,
Suwon-si, Gyeonggi-do (KR)

(72) Inventors: **Yoon-Seok Kang**, Seoul (KR);
Min-Hyuk Nam, Seoul (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**,
Suwon-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 140 days.

(21) Appl. No.: **15/806,157**

(22) Filed: **Nov. 7, 2017**

(65) **Prior Publication Data**
US 2018/0135688 A1 May 17, 2018

(30) **Foreign Application Priority Data**
Nov. 16, 2016 (KR) 10-2016-0152514

(51) **Int. Cl.**
F16B 47/00 (2006.01)
H05K 5/02 (2006.01)

(52) **U.S. Cl.**
CPC **F16B 47/00** (2013.01); **H05K 5/0213** (2013.01); **H05K 5/0217** (2013.01)

(58) **Field of Classification Search**
CPC combination set(s) only.
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,593,983 A	7/1971	Csenyi	
4,196,882 A *	4/1980	Rognon F16B 47/00 248/205.9
5,381,990 A *	1/1995	Belokin F16B 47/00 248/205.9
5,511,752 A	4/1996	Trethewey	
5,553,837 A *	9/1996	Kahle B25B 11/005 269/21
6,042,095 A *	3/2000	Kuchta A41H 43/0292 269/21

(Continued)

FOREIGN PATENT DOCUMENTS

CN	1375043 A	10/2002
CN	2558807 Y	7/2003

(Continued)

OTHER PUBLICATIONS

Foreign Communication from Related Counterpart Application; European Patent Application No. 17201649.5; Extended European Search Report and European Search Opinion dated Mar. 26, 2018; 6 pages.


(Continued)

Primary Examiner — Monica E Millner

(57) **ABSTRACT**

A vacuum suction device including a suction pad having a concave inner surface. The vacuum suction device also includes a vent hole penetrating from the concave inner surface of the suction pad to an outer surface of the suction pad. The vacuum suction device also includes a valve member disposed on the outer surface of the suction pad. As a pressure of a space, formed by an inner space of the suction pad, decreases, the valve member closes the vent hole from the outer surface of the suction pad.

12 Claims, 13 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,827,344 B1 12/2004 Ristau
7,690,610 B2* 4/2010 Ristau F16B 47/00
248/205.5
8,783,634 B2* 7/2014 Summers F16B 47/00
248/205.5
9,803,680 B2* 10/2017 Potters A47G 1/17
2012/0112023 A1 5/2012 Tollman
2013/0168523 A1 7/2013 Summers et al.
2015/0377280 A1 12/2015 Potters et al.
2016/0031092 A1 2/2016 Li

FOREIGN PATENT DOCUMENTS

CN 102459933 A 5/2012
CN 203453258 U 2/2014
CN 204729452 U 10/2015
CN 105317816 A 2/2016
DE 8813521 U1 3/1989
DE 29916197 U1 3/2000
JP 2002295441 A 10/2002
KR 10-1514737 B1 4/2015
TW M467755 U 12/2013
WO 2014117766 A2 8/2014

OTHER PUBLICATIONS

The First Office Action in connection with Chinese Application No.
201711141783.5 dated Jun. 24, 2020, 15 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG.3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG.16




FIG.17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG.25




FIG. 26




FIG. 27

1

**VACUUM SUCTION DEVICE AND
ELECTRONIC DEVICE INCLUDING THE
SAME**

CROSS-REFERENCE TO RELATED
APPLICATION(S) AND CLAIM OF PRIORITY

This application is related to and claims priority to Korean Application No. 10-2016-0152514 filed on Nov. 16, 2016, the contents of which are incorporated herein by reference.

TECHNICAL FIELD

The present disclosure relates to a fixing device, for example, a vacuum suction device and an electronic device including the same.

BACKGROUND

A vacuum suction device has a semi-spherical or conical suction pad of synthetic rubber or flexible plastic which is sucked to a tile wall or a glass surface. As the internal pressure of the suction pad decreases, the suction pad may be kept sucked to a plane (for example, a tile wall, a glass surface, or a floor). Such a vacuum suction device may be useful in the bathroom or the kitchen in daily living, and may also be used to carry various parts such as large-sized glass in industrial sites.

A variety of electronic devices or goods are used in households or offices, inclusive of audio or video players, and devices for building a wireless communication environment. For example, a standing screen used along with a projector, multi-channel speakers, a small-sized Bluetooth speaker, a wireless frequency relay (for example, a Wireless Fidelity (WiFi) router), a desktop charger or cradle for a mobile communication terminal, and a small-sized desktop computer are devices commonly used indoors.

Such devices as placed in an indoor space or on a desk may be changed in position or fall down due to contact or collision with other objects. The vacuum suction device may be useful in stably positioning these devices (for example, a standing screen or speaker, a Bluetooth speaker, or a small-sized desktop computer).

Although such a device(s) may be stably placed by means of the vacuum suction device, the use of the vacuum suction device may make it inconvenient to carry the device(s). For example, in order to remove the suction pad from the floor, an edge of the suction pad should be raised up. In certain embodiments the suction pad may be hidden by the device (s). While a part of the edge of the suction pad may be protruded outward from the device(s), this may not be pleasing in outward looks. Moreover, a device such as a Bluetooth speaker may be moved often to the living room or the bedroom even in an indoor space, and when needed, a user may carry the Bluetooth speaker. For example, although a device(s) may be stably placed by means of the vacuum suction device, the vacuum suction device makes it difficult to remove the device placed on a plane, thus causing inconvenience to a user who often moves a device to which the vacuum suction device is mounted.

The above information is presented as background information only to assist with an understanding of the present disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the present disclosure.

SUMMARY

To address the above-discussed deficiencies, it is a primary object to provide at least the advantages described

2

below. Accordingly, an aspect of the present disclosure is to provide a vacuum suction device for enabling staple positioning of various devices including a desktop computer, a Bluetooth speaker, and a desktop charger, and/or an electronic device including the same.

Another aspect of the present disclosure is to provide a vacuum suction device for enabling staple positioning of various devices and facilitating relocation of the devices, and/or an electronic device including the same.

In accordance with an aspect of the present disclosure, there is provided a vacuum suction device and/or an electronic device including the same. The vacuum suction device and/or the electronic device including the same may include a suction pad having a concave inner surface, a vent hole penetrating from the inner surface of the suction pad to an outer surface of the suction pad, and a valve member disposed on the outer surface of the suction pad. As a pressure of a space formed by the inner space of the suction pad decreases, the valve member may close the vent hole from the outer surface of the suction pad.

In accordance with another aspect of the present disclosure, there is provided a vacuum suction device and/or an electronic device including the same. The vacuum suction device and/or the electronic device including the same may include a suction pad having a concave inner surface, at least one first vent hole penetrating from the inner surface of the suction pad to an outer surface of the suction pad, a valve member engaged rotatably with the outer surface of the suction pad, and at least one second vent hole formed in the valve member. As the valve member rotates with respect to the suction pad, the at least one second vent hole may be selectively aligned with the at least one first vent hole.

In the vacuum suction device, the suction pad may be disposed on a bottom surface of the housing. As the space of the inner surface of the suction pad is contacted by the weight of a housing of the electronic device and/or electronic parts contained in the housing of the electronic device, the suction pad may be sucked to a plane (for example, a floor). For example, as the pressure of a space formed on the inner surface of the suction pad decreases, the suction pad may be sucked to the plane.

Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses exemplary embodiments of the disclosure.

Before undertaking the DETAILED DESCRIPTION below, it may be advantageous to set forth definitions of certain words and phrases used throughout this patent document: the terms “include” and “comprise,” as well as derivatives thereof, mean inclusion without limitation; the term “or,” is inclusive, meaning and/or; the phrases “associated with” and “associated therewith,” as well as derivatives thereof, may mean to include, be included within, interconnect with, contain, be contained within, connect to or with, couple to or with, be communicable with, cooperate with, interleave, juxtapose, be proximate to, be bound to or with, have, have a property of, or the like; and the term “controller” means any device, system or part thereof that controls at least one operation, such a device may be implemented in hardware, firmware or software, or some combination of at least two of the same. It should be noted that the functionality associated with any particular controller may be centralized or distributed, whether locally or remotely.

Moreover, various functions described below can be implemented or supported by one or more computer programs, each of which is formed from computer readable

program code and embodied in a computer readable medium. The terms “application” and “program” refer to one or more computer programs, software components, sets of instructions, procedures, functions, objects, classes, instances, related data, or a portion thereof adapted for implementation in a suitable computer readable program code. The phrase “computer readable program code” includes any type of computer code, including source code, object code, and executable code. The phrase “computer readable medium” includes any type of medium capable of being accessed by a computer, such as read only memory (ROM), random access memory (RAM), a hard disk drive, a compact disc (CD), a digital video disc (DVD), or any other type of memory. A “non-transitory” computer readable medium excludes wired, wireless, optical, or other communication links that transport transitory electrical or other signals. A non-transitory computer readable medium includes media where data can be permanently stored and media where data can be stored and later overwritten, such as a rewritable optical disc or an erasable memory device.

Definitions for certain words and phrases are provided throughout this patent document, those of ordinary skill in the art should understand that in many, if not most instances, such definitions apply to prior, as well as future uses of such defined words and phrases.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present disclosure and its advantages, reference is now made to the following description taken in conjunction with the accompanying drawings, in which like reference numerals represent like parts:

The above and other aspects, features and advantages of certain exemplary embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

FIG. 1 illustrates a perspective view of an exemplary electronic device including a vacuum suction device according to various embodiments of the present disclosure;

FIG. 2 illustrates a perspective view of another exemplary electronic device including a vacuum suction device according to various embodiments of the present disclosure;

FIG. 3 illustrates an exploded perspective view of a vacuum suction device according to one of various embodiments of the present disclosure;

FIG. 4 illustrates a perspective view of a suction pad in a vacuum suction device according to one of various embodiments of the present disclosure;

FIG. 5 illustrates an exploded perspective view of a vacuum suction device according to one of various embodiments of the present disclosure;

FIG. 6 illustrates a perspective view of a vacuum suction device according to one of various embodiments of the present disclosure, viewed from a different direction;

FIG. 7 illustrates a sectional view of a vacuum suction device according to one of various embodiments of the present disclosure;

FIGS. 8 and 9 illustrate sectional views of a use example of a vacuum suction device according to one of various embodiments of the present disclosure;

FIG. 10 illustrates a perspective view of a vacuum suction device according to one of various embodiments of the present disclosure;

FIG. 11 illustrates a perspective view of a suction pad in a vacuum suction device according to another of various embodiments of the present disclosure;

FIG. 12 illustrates a perspective view of a rotation rod in a vacuum suction device according to another of various embodiments of the present disclosure;

FIG. 13 illustrates a view of an operation of a valve member in a vacuum suction device according to another of various embodiments of the present disclosure;

FIG. 14 illustrates a view of a holder in a vacuum suction device according to another of various embodiments of the present disclosure;

FIGS. 15 and 16 illustrate sectional views of a use example of a vacuum suction device according to another of various embodiments of the present disclosure;

FIG. 17 illustrates a perspective view of a closed vent hole in a vacuum suction device according to another of various embodiments of the present disclosure;

FIG. 18 illustrates a sectional view of a closed vent hole in a vacuum suction device according to another of various embodiments of the present disclosure;

FIG. 19 illustrates a perspective view of an opened vent hole in a vacuum suction device according to another of various embodiments of the present disclosure;

FIG. 20 illustrates a sectional view of an opened vent hole in a vacuum suction device according to another of various embodiments of the present disclosure;

FIG. 21 illustrates a perspective, partially cut-away view of a vacuum suction device according to another of various embodiments of the present disclosure;

FIG. 22 illustrates a sectional view of a vacuum suction device according to another of various embodiments of the present disclosure;

FIG. 23 illustrates a view of the structure of a valve member in a vacuum suction device according to another of various embodiments of the present disclosure;

FIGS. 24 and 25 illustrate views of an operation of a valve member in a vacuum suction device according to another of various embodiments of the present disclosure; and

FIGS. 26 and 27 illustrate sectional views respectively of opened and closed states of a vent hole in a vacuum suction device according to another of various embodiments of the present disclosure.

Throughout the drawings, like reference numerals will be understood to refer to like parts, components, and structures.

DETAILED DESCRIPTION

FIGS. 1 through 27, discussed below, and the various embodiments used to describe the principles of the present disclosure in this patent document are by way of illustration only and should not be construed in any way to limit the scope of the disclosure. Those skilled in the art will understand that the principles of the present disclosure may be implemented in any suitably arranged device.

The present disclosure may be subjected to various modifications and have various embodiments. Specific embodiments of the present disclosure are described with reference to the accompanying drawings. However, the embodiments are not intended to limit the present disclosure, and it is to be understood that the present disclosure covers various modifications, equivalents, and/or alternatives to the embodiments.

Ordinal terms as used in the present disclosure, such as ‘first’ and ‘second’ may be used to describe various components, not limiting the components. These expressions are used to distinguish one component from another component. For example, a first component may be referred to as a second component and vice versa without departing from

5

the scope of the present disclosure. The term ‘and/or’ includes a combination or any of a plurality of related items.

The relative terms such as ‘front surface’, ‘rear surface’, ‘top surface’, and ‘bottom surface’ described as they are shown in the drawings may be replaced with ordinal terms such as ‘first’, ‘second’, and the like. The sequence of the ordinal numbers such as ‘first’, ‘second’, and the like is determined as mentioned or arbitrarily, and thus may be changed freely when needed.

The terms as used in the present disclosure are provided to describe merely specific embodiments, not intended to limit the scope of the present disclosure. It is to be understood that singular forms include plural referents unless the context clearly dictates otherwise. In the present disclosure, the term ‘have’, ‘may have’, ‘include’, or ‘may include’ signifies the presence of a specific feature, number, step, operation, component, part, or combination thereof, not excluding the presence of one or more other features, numbers, steps, operations, components, parts, or combinations thereof.

Unless otherwise defined, the terms and words including technical or scientific terms used in the following description and claims may have the same meanings as generally understood by those skilled in the art. The terms as generally defined in dictionaries may be interpreted as having the same or similar meanings as or to contextual meanings of related technology. Unless otherwise defined, the terms should not be interpreted as ideally or excessively formal meanings.

According to the present disclosure, an electronic device may be any device equipped with a touch panel, and an electronic device may also be called a terminal, a portable terminal, a mobile terminal, a communication terminal, a portable communication terminal, a portable mobile terminal, a display device, or the like.

For example, an electronic device may be a smart phone, a portable phone, a navigation device, a game console, a television (TV), an in-vehicle head unit, a laptop computer, a tablet computer, a portable multimedia player (PMP), a personal digital assistant (PDA), or the like. An electronic device may be configured as a pocket-size portable communication terminal equipped with a wireless communication function. Further, an electronic device may be a flexible device or a flexible display device.

The electronic device may communicate with an external electronic device such as a server or perform a task through interaction with an external electronic device. For example, the electronic device may transmit an image captured by a camera and/or location information detected by a sensor unit to a server through a network. The network may be, but not limited to, a mobile or cellular communication network, a local area network (LAN), a wireless local area network (WLAN), a wide area network (WAN), the Internet, a small area network (SAN), or the like.

FIG. 1 illustrates a perspective view of an electronic device 10 including a vacuum suction device 13 according to various embodiments of the present disclosure.

Referring to FIG. 1, the electronic device 10 is, for example, a desktop computer in which a speaker device may be provided at the top of a housing 11 and the vacuum suction device 13 may be provided at the bottom of the housing 11. The housing 11 is roughly cylindrical, and may include a main circuit board and/or an auxiliary circuit board, with a processor, a communication module, an audio module, a storage medium, and a power module mounted thereon.

6

The vacuum suction device 13 may include, for example, a suction pad 13a and a cover member 13b. The suction pad 13a may be molded of synthetic rubber or flexible plastic, and may be disposed on the bottom surface of the housing 11 through the cover member 13b. In an embodiment, the cover member 13b may be a part of the housing 11. For example, the suction pad 13a may be mounted directly to the bottom surface of the housing 11.

If the electronic device 10 is placed on a floor, the suction pad 13a may be sucked onto the floor by the weight of the housing 11 and/or parts contained in the housing 11. For example, as an inner space of the suction pad 13a contracts by the weight of the housing 11 and so on and thus the inner pressure of the suction pad 13a decreases, the suction pad 13a may be sucked to the floor. As described later in relation to an embodiment disclosed in FIG. 3, even though the electronic device 10 is tilted with respect to the floor due to interference or impact from an external object, the vacuum suction device 13 may prevent the electronic device 10 from falling down. As described later in relation to an embodiment disclosed in FIG. 3, when the electronic device 10 is to be moved, the electronic device 10 may be easily removed from the floor by raising the electronic device 10 in a predetermined direction (for example, a direction perpendicular to the floor) or rotating the electronic device 10. For example, the motion of raising or rotating the electronic device 10 leads to opening of a vent hole (for example, a vent hole 111 in FIG. 7) formed in the suction pad 13a, and the internal pressure of the suction pad 13a becomes substantially equal to an ambient pressure, thereby facilitating removal of the suction pad 13a from the floor.

FIG. 2 illustrates a perspective view of another exemplary electronic device 20 including a vacuum suction device according to various embodiments of the present disclosure.

Referring to FIG. 2, the electronic device 20 may be, for example, a Bluetooth speaker equipped with a desktop clock functionality, a wireless power transmission functionality, and a wireless frequency relay functionality. A speaker grill 21a may be mounted on a side surface of a housing 21 in the electronic device 20, and a vacuum suction device, for example, suction pads 23 may be disposed on the bottom surface of the housing 21. When the electronic device 20 is placed on a floor, the suction pad may be sucked to the floor by the weight of the housing 21 and the like, thereby stably positioning the electronic device 20. In an embodiment, a pair of suction pads 23 may be arranged on the bottom surface of the housing 21. In some embodiment, if a plurality of suction pads 23 are arranged, the electronic device 20 may be readily removed from the floor by raising the electronic device 20 in a predetermined direction.

A detailed description will be given of the above-described vacuum suction device with reference to FIG. 3.

FIG. 3 illustrates an exploded perspective view of a vacuum suction device 100 according to one of various embodiments of the present disclosure, FIG. 4 illustrates a perspective view of a suction pad 101 in a vacuum suction device according to one of various embodiments of the present disclosure, FIG. 5 illustrates an exploded perspective view of the vacuum suction device 100 according to one of various embodiments of the present disclosure, and FIG. 6 illustrates a perspective view of the vacuum suction device 100 according to one of various embodiments of the present disclosure, viewed from a different direction.

Referring to FIGS. 3 to 6, the vacuum suction device 100 may include the suction pad 101, a vent hole 111 formed in the suction pad 101, and a valve member 102 disposed on an outer surface of the suction pad 101b.

According to various embodiments, the suction pad **101** may be molded of synthetic rubber or flexible plastic into a predetermined shape, and may be deformed by external force. Without an external force, the suction pad **101** may elastically return to the original molded form. For example, the suction pad **101** is shaped so that the inner surface **101a** of suction pad **101** may be concave. If an external force is exerted on an outer surface **101b** of the suction pad **101**, a space defined by the inner surface **101a** may be contracted. With the inner surface **101a** contracted, the pressure of the space defined by the inner surface **101a** may be decreased due to the property of the suction pad **101** to return to the original molded form. For example, as the pressure of the inner space of the suction pad **101** decreases, the suction pad **101** may be sucked to a plane (for example, a wall or a floor), facing the plane.

According to various embodiments, the vent hole **111** may penetrate from the inner surface **101a** to the outer surface **101b** of the suction pad **101**. For example, the vent hole **111** may connect the inner space of the suction pad **101** to an outer space. The valve member **102** may selectively open or close one end portion of the vent hole **111** from the outer surface of the suction pad **101**. For example, in the state where the pressure of the inner space of the suction pad **101** is low, external air may be introduced into the inner space of the suction pad **101** through the vent hole **111**. Herein, as the valve member **102** is brought into close contact with the one end portion of the vent hole **111**, thereby preventing introduction of air into the inner space of the suction pad **101**. When air is discharged from the inner space of the suction pad **101** through the vent hole **111**, the valve member **102** may be apart from the outer surface **101b** of the suction pad **101**. For example, when air is discharged, the valve member **102** may open the one end portion of the vent hole **111**.

According to various embodiments, the vacuum suction device **100** may further include a cover member **103** (the cover member **13b** in FIG. 1). In an embodiment, the cover member **103** may be a part of a housing (for example, the housing **11** in FIG. 1) of an electronic device. In another embodiment, the cover member **103** may include an accommodation recess **131** and a fixing hole **133**. The accommodation recess **131** may be configured to form a closed curve, for example, a circle on the inner surface of the cover member **103**, and the fixing hole **133** may be formed in an area surrounded by the accommodation recess **131**.

According to various embodiments, the suction pad **101** may be movably engaged with the cover member **103**. For example, a catching member **115** to be accommodated in the accommodation recess **131** may be provided on the outer surface **101b** of the suction pad **101**. In an embodiment, the catching member **115** may be circular in correspondence with the accommodation recess **131**. In another embodiment, a plurality of catching members **115** may be arranged along a circle corresponding to the accommodation recess **131**. For example, although the catching member **115** is continuously circular, a plurality of arc catching members may be arranged along a circle.

According to various embodiments, the catching member **115** may include an extension portion **115a** and a flange portion **115b**. The extension portion **115a** may be extended from the outer surface **101b** of the suction pad **101**, and may include the flange portion **115b** curved from an end portion of the extension portion **115a**, while being tilted with respect to the extension portion **115a**. In an embodiment, the extension portion **115a** and the flange portion **115b** may be perpendicular to each other.

According to various embodiments, as a part of the extension portion **115a** and the flange portion **115b** are accommodated in the accommodation recess **131**, the suction pad **101** may be engaged with the cover member **103**. As described later with reference to FIG. 7, since the inner space of the accommodation recess **131** is formed to be large enough, a part of the extension portion **115a** and/or the flange portion **115b** is movable to some extent inside the accommodation recess **131**. For example, the cover member **103** may move within a predetermined range relative to the suction pad **101**.

In some embodiment, the valve member **102** may be engaged in the fixing hole **133**. For example, the valve member **102** may include a curved portion **121** corresponding to one end portion of the vent hole **111** and a fixing portion **123** extended from the curved portion **121**, and the fixing portion **123** may be engaged in the fixing hole **133**. When the fixing portion **123** is engaged in the fixing hole **133**, the curved portion **121** may be disposed protruded from the inner surface of the cover member **103**.

FIG. 7 illustrates a sectional view of the vacuum suction device **100** according to one of various embodiments of the present disclosure, and FIGS. 8 and 9 illustrate sectional views of a use example of the vacuum suction device **100** according to one of various embodiments of the present disclosure.

Referring to FIGS. 7, 8 and 9, the vacuum suction device **100** may further include a mounting recess **113** formed on the outer surface of the suction pad **101**. The mounting recess **113** is shaped to be sunk from the outer surface of the suction pad **101**. For example, as the valve member **102** (for example, the curved portion **121**) is brought into close contact with the mounting recess **113**, the vent hole **111** may be closed. In an embodiment, the mounting recess **113** may be curved with a predetermined curvature. For example, the mounting recess **113** may be a part of a spherical surface.

In an embodiment, the outer circumferential surface of the valve member **102**, for example, the outer circumferential surface of the curved portion **121** may be shaped at least partially in correspondence with the shape of the inner circumferential surface of the mounting recess **113**. In an embodiment, with the vent hole **111** closed by the valve member **102**, a part of the outer circumferential surface of the valve member **102**, for example, a part of the outer circumferential surface of the curved portion **121**, corresponding to the inner circumferential surface of the mounting recess **113** may be exposed outward from the mounting recess **113**. For example, even though the curved portion **121** rotates or rolls inside the mounting recess **113**, in close contact with the mounting recess **113**, the whole inner circumferential surface of the mounting recess **113** may closely contact a part of the outer circumferential surface of the curved portion **121**. For example, as the valve member **102** slidably contacts the inner circumferential surface of the mounting recess **113**, while the outer surface of the valve member **102** (or the curved portion **121**) and/or a part of the outer surface of the valve member **102** (or the curved portion **121**) is kept in close contact with the mounting recess **113**, the valve member **102** may rotate with respect to the suction pad **101**. In some embodiment, if the valve member **102** rotates with respect to the suction pad **101** in the state where the suction pad **101** is fixed on a plane, the cover member **103** may also move within a predetermined range relative to the suction pad **101**. For example, as illustrated in FIGS. 8 and 9, the cover member **103** may move within an angle range of $\pm\theta$ with respect to a plane.

According to various embodiments, if the vacuum suction device **100** is provided in an electronic device (for example, the electronic device **10** in FIG. **1**), the suction pad **101** may be sucked to a plane (for example, a floor) by the weight of the electronic device **10** and/or the housing **11**. In some embodiment, the cover member **103** may be mounted to the housing **11** or may be a part of the housing **11**. For example, with the suction pad **101** sucked to a plane, the electronic device may move together with the cover member **103** within a predetermined range relative to the suction pad **101** and/or the plane, while being kept stably cradled on the plane. Thus, the electronic device including the vacuum suction device **100** may be kept positioned stably without falling down by interference or impact from another object.

If the user wants to move an electronic device (for example, the electronic device **10** in FIG. **1**) including the vacuum suction device **100**, the user may raise the electronic device **10** in a predetermined direction, for example, in a direction perpendicular to the plane to which the suction pad is sucked, thereby readily removing the suction pad **101** from the plane. For example, if the electronic device with the vacuum suction device **100** is raised up, the cover member **103** recedes away from the suction pad **101**, along with the valve member **102**. As a result, the outer circumferential surface of the valve member **102** (for example, the curved portion **121**) becomes apart from the inner circumferential surface of the mounting recess **113**, and thus air may be introduced into the suction pad **101**. Therefore, the inner pressure of the suction pad **101** becomes substantially equal to an ambient pressure, and the suction pad **101** loses a suction force, so that the user may easily remove and move the electronic device from the plane.

FIG. **10** illustrates a perspective view of a vacuum suction device **200** according to one of various embodiments of the present disclosure.

Referring to FIG. **10**, the vacuum suction device **200** may include a suction pad **201**, a first vent hole (**211** in FIG. **11**) formed in the suction pad **201**, a valve member **204** rotatably engaged on the suction pad **201**, and/or a second vent hole **247** formed in the valve member **204**. The valve member **204** may include a rotation rod **241** that rotates in close contact between a part of the outer circumferential surface of the rotation rod **241** and the outer surface of the suction pad **201**. While the valve member **204** (for example, the rotation rod **241**) is rotating, the second vent hole **247** may be selectively aligned with the first vent hole **211**. Thus, external air may be introduced into the suction pad **201**. In some embodiment, the vacuum suction device **200** may further include a cover member **203** engaged with the suction pad **201**, surrounding at least a part of the outer surface of the suction pad **201**, and the valve member **204** may be mounted on the cover member **203**.

According to various embodiments, the suction pad **201** has a concave inner surface, and may be sucked to a plane, with the inner surface of the suction pad **201** facing the plane. For example, if with the inner surface of the suction pad **201** facing the plane, an external surface is applied to the outer surface of the suction pad **201**, an inner space of the suction pad **201** (for example, a space formed by the inner surface of the suction pad **201**) is contracted. If the external force is removed, the inner pressure of the suction pad **201** is decreased due to the property of the suction pad **201** to return to the original molded form of the suction pad **201**, thereby keeping the suction pad **201** sucked to the plane.

FIG. **11** illustrates a perspective view of the suction pad **201** in a vacuum suction device according to another of various embodiments of the present disclosure.

Referring to FIG. **11**, similarly to the suction pad **101** illustrated in FIG. **4**, the suction pad **201** includes a catching member **215**. Thus, the suction pad **201** may be engaged with the cover member **203**, and a part of the suction pad **201** may be exposed from the outer surface of the cover member **203** through an opening **231** formed on the cover member **203**. For example, the suction pad **201** may include a protrusion **213** formed on the outer surface of the suction pad **201**. If the suction pad **201** is engaged with the cover member **203**, the protrusion **213** may be exposed from the outer surface of the cover member **203** through the opening **231**.

The protrusion **213** is shaped into a cone protruded from the outer surface of the suction pad **201**, and one end portion of the first vent hole **211** may be exposed from one end portion, for example, a top end portion of the protrusion **213**. For example, the first vent hole **211** penetrates from the inner surface of the suction pad **201** through the outer surface of the suction pad **201**, and one end portion of the first vent hole **211** may be opened on the top end of the protrusion **213**. In some embodiment, the suction pad **201** may include a mounting recess **217** formed on the top end of the protrusion **213**. The mounting recess **217** is curved in correspondence with a part of the outer circumferential surface of the valve member **204**, for example, the rotation rod **241**. The mounting recess **217** may slidably contact the outer circumferential surface of the valve member **204** in close contact with a part of the outer circumferential surface of the valve member **204**. In another embodiment, one end portion of the first vent hole **211** may be positioned on the mounting recess **217**.

Referring to FIG. **10** again, the rotation rod **241** of the valve member **204** may be disposed in close contact with the inner circumferential surface of the mounting recess **217**, for example, one end portion of the first vent hole **211** from the outer surface of the suction pad **201**. The second vent hole **247** may penetrate in a direction crossing the length direction of the rotation rod **241**. The rotation rod **241** may be installed rotatably with respect to a rotation axis extended along the length direction of the rotation rod **241** on the outer surface of the cover member **203**. Along with the rotation of the rotation rod **241**, the second vent hole **247** may be selectively connected to the first vent hole **211**. For example, the inner space of the suction pad **201** may be connected to an outer space through the first vent hole **211** and the second vent hole **247**.

According to various embodiments, the rotation rod **241** may rotate with respect to the cover member **203**, in engagement with a holder(s) **233a** and **233b** formed on the outer circumferential surface of the cover member **203**. The holder(s) **233a** and **233b** may support both ends of the rotation rod **241** in a manner that allows rotation of the rotation rod **241**. In an embodiment, when seen from a plan view, the rotation rod **241** may be arranged in a diameter direction of the suction pad **201**, and a part of the outer circumferential surface of the rotation rod **241** may closely contact the top end of the protrusion **213**. In some embodiment, the suction pad **201** may be sucked to a plane by a force that presses down the cover member **203**. Herein, the rotation rod **241** may be brought into closer contact with the top end of the protrusion **213**.

FIG. **12** illustrates a perspective view of the rotation rod **241** in a vacuum suction device according to another of various embodiments of the present disclosure, FIG. **13** illustrates a view of an operation of a valve member in a vacuum suction device according to another of various embodiments of the present disclosure, and FIG. **14** illus-

11

trates a view of a holder in a vacuum suction device according to another of various embodiments of the present disclosure.

Referring to FIG. 12, the rotation rod **241** may include a valve portion **241a** extended along the rotation axis A, and supports **241b** extended from both ends of the valve portion **241a** along the rotation axis A. The second vent hole **247** may penetrate through the valve portion **241a** in the rotation rod **241**. Each of the supports **241b** may be rotatably supported by one of the afore-described holder(s) **233a** and **233b**.

Referring to FIGS. 12, 13, and 14 together with FIG. 10, the valve member **204** may further include a cam button **243** and an elastic member **245**.

According to various embodiments, the cam button **243** may be disposed such that the cam button **243** may make a linear reciprocating motion on the outer surface of the suction pad **201**. The cam button **243** may include a first inclined cam surface **243a** at an end thereof. In an embodiment, a second inclined cam surface **241c** interworking with the first inclined cam surface **243a** may be formed at one end portion of the valve portion **241a**. For example, when the cam button **243** makes a linear reciprocating movement, the first inclined cam surface **243a** may be interfered by the second inclined cam surface **241c**, thereby rotating the rotation rod **241**. In some embodiment, if the cam button **243** makes one reciprocating movement in a reciprocating range, the rotation rod **241** may rotate by 90 degrees. For example, if with the second vent hole **247** aligned with the first vent hole **211**, the cam button **243** makes one reciprocating movement, the second vent hole **247** may be aligned vertically with the first vent hole **211**.

The cam button **243** may be installed such to make a linear reciprocating movement inside the first holder **133a**. For example, the first holder **233a** may include an operation hole **235** for accommodating the cam button **243**, and a guide slot **237** formed in the operation hole **235**. The guide slot **237** may be extended in parallel to the length direction of the rotation rod **241** and/or the reciprocating direction of the cam button **243**. A guide protrusion **243b** corresponding to the guide slot **237** may be formed on the outer circumferential surface of the cam button **243**. For example, as the guide protrusion **243b** is accommodated in the guide slot **237**, the cam button **243** may be accommodated in the operation hole **235** in a state where the cam button **243** is capable of making a linear movement but is limited in rotation. With the cam button **243** accommodated in the operation hole **235**, one end portion of the cam button **243** may protrude outward from the cover member **203**. For example, the user may reciprocate the cam button **243** by pressing the cam button **243**, as indicated by reference character P, and along with linear movement of the cam button **243**, the first inclined cam surface **243a** and the second inclined cam surface **241c** are interfered, thereby rotating the rotation rod **241**, as indicated by reference numeral R.

Referring to FIG. 10 again, the elastic member **245** has one end supported by the second holder **233b** and the other end supported by the other end portion of the rotation rod **241**, for example, the valve portion **241a**, and thus may return the cam button to an initial position (the position of the cam button **243** prior to being pressed by the user). For example, if an external force is not applied to the cam button **243**, the cam button **243** may be kept protruded outward from the cover member **203** by an elastic force of the elastic member **245**.

12

FIGS. 15 and 16 illustrate sectional views of a use example of the vacuum suction device **200** according to another of various embodiments of the present disclosure.

Referring to FIGS. 15 and 16, with the first vent hole **211** closed, for example, with one end portion of the first vent hole **211** facing the outer circumferential surface of the rotation rod **241**, the vacuum suction device **200** may be isolated from an outer surface which is the inner surface of the suction pad **201**. If with the inner space of the suction pad **201** isolated, an external force is applied (for example, the electronic device **10** is disposed on a plane and the weight of the housing **11** and so on is applied), the cover member **203** may press down the suction pad **201**, thereby reducing the inner space of the suction pad **201**. In some embodiment, the cover member **203** may be a part of the afore-described housing of the electronic device. If the inner space of the suction pad **201** is reduced, the inner pressure of the suction pad **201** may increase, thus discharging air to the outside. Herein, the air inside the suction pad **201** may be discharged through a part of the edge of the suction pad **201** and/or between the inner circumferential surface of the mounting recess **217** and the outer circumferential surface of the rotation rod **241** through the first vent hole **211**. Along with the discharge of the air inside the suction pad to the outside, the internal pressure of the suction pad **201** may be decreased due to the property of the suction pad **201** to returning to its original molded form (for example, elastic restoring force). If the internal pressure of the suction pad **201** is decreased, the outer circumferential surface of the rotation rod **241** may be brought into close contact with the mounting recess **217**, and the suction pad **201** may be kept sucked to the plane.

According to various embodiments, if the user wants to move the electronic device provided with the vacuum suction device **200**, the user may easily remove the suction pad **201** from the plane by pressing the cam button **243**. For example, if the cam button **243** is pressed, the rotation rod **241** rotates by a predetermined angle (for example, 90 degrees). Thus, the second vent hole **247** is connected to the first vent hole **211**, thereby introducing external air into the suction pad **201**. As a consequence, the suction force of the suction pad **201** is eliminated and the user may readily move the electronic device.

FIG. 17 illustrates a perspective view of a closed vent hole in a vacuum suction device **300** according to another of various embodiments of the present disclosure, and FIG. 18 illustrates a sectional view of a closed vent hole in the vacuum suction device **300** according to another of various embodiments of the present disclosure.

Referring to FIGS. 17 and 18, the vacuum suction device **300** may include a suction pad **301**, and a valve member **304** rotatably engaged with the outer circumferential surface of the suction pad **301**. According to an embodiment, at least one first vent hole(s) **311** is formed in the suction pad **301**, and at least one second vent hole **347** is formed in the valve member **304**. As the valve member **304** rotates, the second vent hole **347** may be aligned with the first vent hole(s) **311**.

The suction pad **301** may be molded of synthetic rubber or flexible plastic, the inner surface of which is concave. The inner space of the suction pad **301** may be contacted by an external force. The first vent hole(s) **311** may penetrate from the inner surface of the suction pad **301** to the outer surface of the suction pad **301**. According to an embodiment, a plurality of first vent holes(s) **311** may be arranged along the circumferential direction of the suction pad **301**, each first vent hole(s) **311** being extended in a radius direction of the suction pad **301**.

The valve member **304** is shaped to surround at least part of the outer surface of the suction pad **301**. With the edge of the valve member **304** surrounded by the suction pad **301**, the valve member **304** may rotate with respect to the suction pad **301**, facing the suction pad **301**. An engagement member **351** may be provided on a top end of the valve member **304**. The engagement member **351** may be mounted, for example, on the bottom surface of a housing (for example, the housing **11** in FIG. **1**) of the electronic device. In some embodiment, the engagement member **351** may be a part of the housing of the electronic device. The valve member **304** may further include an intermediate member **341** provided on the inner surface of the valve member **304**. The intermediate member **341** may be fabricated of synthetic rubber or flexible plastic, and may closely contact with the outer surface of the suction pad **301**. For example, as the intermediate member **341** closes the first vent hole(s) **311**, the inner space of the suction pad **301** may be isolated from an outer space.

According to various embodiments, the second vent hole **347** may be aligned selectively with the first vent hole(s) **311** along with the rotation of the valve member **304**. For example, as the valve member **304** rotates, the first vent hole(s) **311** may be opened or closed. In some embodiment, a plurality of second vent holes **347** may be arranged along a circumferential direction of the valve member **304**, each second vent hole **347** being extended in a radius direction of the valve member **304**.

According to various embodiments, if an external force is applied (for example, the weight of the above-described electronic device is applied) in the state where the suction pad **301** is placed facing a plane and the first vent hole(s) **311** is closed, the inner space of the suction pad **301** is contacted, thereby discharging internal air through a part of the edge of the suction pad **301** and/or a space between the outer surface of the suction pad **301** and the inner surface of the valve member **304** (for example, the inner surface of the intermediate member **341**). With the internal air discharged, the elastic restoring force of the suction pad **301** decreases the internal pressure of the suction pad **301**. As a result, the suction pad **301** may be sucked to the plane. If the internal pressure of the suction pad **301** decreases in the state where the intermediate member **301** has closed the first vent hole(s) **311**, the intermediate member **341** may be brought into closer contact with the outer surface of the suction pad **301**. For example, since external air may not be introduced into the suction pad **301**, the suction force of the suction pad **301** may be kept constant.

FIG. **19** illustrates a perspective view of an opened vent hole in the vacuum suction device **300** according to another of various embodiments of the present disclosure, and FIG. **20** illustrates a sectional view of an opened vent hole in the vacuum suction device **300** according to another of various embodiments of the present disclosure.

Referring to FIGS. **19** and **20**, as the valve member **304** rotates, the second vent holes **347** are aligned respectively with the first vent hole(s) **311**, thereby allowing air to be introduced into the suction pad **301**. For example, as the suction force of the suction pad **301** is eliminated, the suction pad **301** may be readily removed from a plane. According to various embodiments, if an electronic device provided with the vacuum suction device **300** is placed with the first vent hole(s) **311** closed, the suction pad **301** may be sucked to the plane by the weight of the electronic device (or a housing of the electronic device). To move the electronic device placed on the plane, the user may easily raise up the electronic device from the plane by rotating the electronic

device by a predetermined angle. For example, since the engagement member **351** is mounted in the housing of the electronic device, rotation of the electronic device may lead to rotation of the valve member **304**, thereby introducing external air into the suction pad **301**. As the external air is introduced into the suction pad **301**, the suction force of the suction pad **301** is eliminated. Thus, the user may easily remove the electronic device, for example, the suction pad **301** from the plane.

FIG. **21** illustrates a perspective, partially cut-away view of a vacuum suction device **400** according to another of various embodiments of the present disclosure, and FIG. **22** illustrates a sectional view of the vacuum suction device **400** according to another of various embodiments of the present disclosure.

Referring to FIGS. **21** and **22**, the vacuum suction device **400** may include a suction pad **401** and a valve member **402**. As a part (for example, a valve plate **441**) of the valve member **402** rotates on the suction pad **401**, at least one first vent hole(s) **411** formed in the suction pad **401** may be opened or closed. According to an embodiment, the vacuum suction device **400** may include a cover member **404**. The cover member **404** is engaged with the suction pad **401**, surrounding at least a part of the outer circumferential surface of the suction pad **401**, and may constrain a part (for example, the valve plate **441**) of the valve member **402**, rotatably on the outer surface of the suction pad **401**.

The suction pad **401** has a concave inner surface, and a space formed by the inner surface of the suction pad **401** may be contracted by an external force. If the external force is not applied, the suction pad **401** may return to its original molded form. The suction pad **401** may include the at least one first vent hole(s) **411** penetrating from the inner surface of the suction pad **401** to the outer surface of the suction pad **401**. If there are a plurality of first vent hole(s) **411**, the first vent hole(s) **411** may be arranged at a predetermined angle interval along a circumferential direction of the suction pad **401**.

According to various embodiments, the valve member **402** may include the valve plate **441**, a rotary shaft member **403**, and a cam member **451**.

FIG. **23** illustrates a view of the structure of the valve member in the vacuum suction device **400** according to another of various embodiments of the present disclosure.

Referring to FIG. **23**, the valve plate **441** may include a second vent hole(s) **447**, a guide rib **443**, and a guide hole **445**. The valve plate **441** is disposed rotatably, one surface of which faces the outer surface of the suction pad **401**. Along with the rotation of the valve plate **441**, the second vent hole(s) **447** are aligned with the first vent hole(s) **411**, thus connecting the inner space of the suction pad **401** to the outer space. The guide rib **443** may be shaped into a cylinder, extended from the other surface of the valve plate **441**. The guide hole **445** may be formed in the guide rib **443**.

The rotary shaft member **403** may be engaged, penetrating through the suction pad **401** and the valve plate **441**, and may move up and down with respect to the suction pad **401** and/or the valve plate **441**. According to an embodiment, the rotary shaft member **403** may include a guide protrusion **433** formed on the outer circumferential surface thereof. When the rotary shaft member **403** is engaged with the suction pad **401** (and/or the valve plate **441**), the guide protrusion **433** may be accommodated in the guide hole **445**. When the rotary shaft member **403** moves up and down with respect to the suction pad **401** and/or the valve plate **441**, the guide protrusion **433** may move along the guide hole **445**. For example, the guide hole **445** may be extended along a

vertical movement direction of the rotary shaft member 403. As mentioned before, since the valve plate 441 is engaged rotatably with the suction pad 401, and the guide hole 445 and the guide protrusion 433 are engaged with each other, the rotary shaft member 403 may rotate together with the valve plate 441 with respect to the suction pad 401.

The cam member 451 may include inclined cam surfaces 453a facing one end portion of the rotary shaft member 403. When the rotary shaft member 403 moves up and down, the inclined cam surfaces 453a may be interfered by one end portion (for example, a top end portion) of the rotary shaft member 403, thereby rotating the rotary shaft member 403. For example, other inclined cam surfaces 431a corresponding to the inclined cam surfaces 453a may be formed at one end portion of the rotary shaft member 403.

Referring to FIG. 22 again, a spring 455 may be provided between the cam member 451 and the rotary shaft member 403. The spring 455 may maintain the inclined cam surfaces 453a and 431a formed respectively on the cam member 451 and the rotary shaft member 403 apart from each other.

In the foregoing embodiment, while it has been described that 'the rotary shaft member moves up and down', a part of the suction pad 401, the valve plate 441, and/or the cam member 451 may move up and down with respect to the rotation axis member 403, substantially in an environment in which the vacuum suction device 400 is actually used. For example, in the state where the vacuum suction device 400 is placed on a plane, a bottom end of the rotary shaft member 403 is supported by the plane, and the part of the suction pad 401, the valve plate 441, and/or the cam member 451 may move up and down with respect to the rotation shaft member 403.

The above vertical movement will be described in greater detail with reference to FIGS. 24 and 25.

FIGS. 24 and 25 illustrate views of an operation of a valve member in a vacuum suction device according to another of various embodiments of the present disclosure.

Referring to FIGS. 24 and 25, when the vacuum suction device 400 is placed on a plane, the edge of the suction pad 401 may closely contact the plane, and the bottom end portion of the rotary shaft member 403 may also contact the plane. If an external force is applied to the vacuum suction device 400 placed on the plane, for example, if the weight W of the above-described electronic device is applied to the suction pad 401 and/or the cam member 451, a part of the suction pad 401 or the cam member 451 may move down with respect to the rotary shaft member 403. For example, the rotary shaft member 403 may rise relatively, approaching the cam member 451. As the rotary shaft member 403 approaches the cam member 451 (for example, as the cam member 451 descends), the inclined cam surfaces 431a of the rotary shaft member 403 may be interfered with the inclined cam surfaces 453a of the cam member 451, thereby rotating the rotary shaft member 403 in a first direction R. While the cam member 451 is descending, the suction pad 401 has a gradually contracted inner space, in close contact with the plane. Since the suction pad 401 is not capable of rotating, as the edge of the suction pad 401 closely contacts the plane, if the inclined cam surfaces 453a and 431a interfere with each other, the rotary shaft member 403 may rotate in the first direction R. The rotation of the rotary shaft member 403 may lead to rotation of the valve plate 441 together with the rotary shaft member 403 with respect to the suction pad 401, thereby closing the first vent hole(s) 411. Even though the first vent hole(s) 411 are closed, air inside the suction pad 401 may be discharged through a part of the edge of the suction pad 401, and/or between the outer

surface of the suction pad 401 and one surface of the valve plate 441, while the inner space of the suction pad 401 is being contracted. For example, if an external force is applied to the vacuum suction device 400, the cam member 451 rotates the rotary shaft member 403, and the valve plate 441 rotates along with the rotary shaft member 403, thereby closing the first vent hole(s) 411. As the external force applied to the vacuum suction device 400 contracts the inner space of the suction pad 401, air inside the suction pad may be discharged. With the inside air discharged, the elastic restoring force of the suction pad 401 decreases the pressure of the inner space of the suction pad 401. Accordingly, the suction pad 401 may be kept sucked to the plane.

According to various embodiments, when a user wants to move an electronic device with the vacuum suction device 400, the user may easily separate the electronic device from a plane by rotating the electronic device, for example, the cam member 451 in a reverse direction of the first direction R. In an embodiment, the cam member 451 may further include a stopper surface 453b formed between every two adjacent inclined cam surfaces 453a, and the rotary shaft member 403 may also further include a stopper surface 431b formed between every two adjacent inclined cam surfaces 431a. If the cam member 451 rotates in the reverse direction of the first direction R, the stopper surfaces 453b and 431b may interfere with each other, thereby rotating the rotary shaft member 403 in the reverse direction of the first direction R. While the cam member 451 and/or the rotary shaft member 403 are rotating in the reverse direction of the first direction R, the suction pad 401 may be kept suck to the plane. For example, as the valve plate 441 rotates together with the rotary shaft member 403 with respect to the suction pad 401, the first vent hole(s) 411 may be opened, thereby facilitating removal of the suction pad 401 from the plane.

FIGS. 26 and 27 illustrates sectional views respectively of opened and closed states of a first vent hole(s) 411 in the vacuum suction device according to another of various embodiments of the present disclosure.

Referring to FIG. 26, with the first vent hole(s) 411 closed by the valve plate 441, the suction pad 401 may be kept sucked to the plane. If the cam member 451 rotates the rotary shaft member 403 and/or the valve plate 441 in the state where the suction pad 401 is sucked to the plane, the second vent hole(s) 447 may be aligned with the first vent hole(s) 411. Referring to FIG. 27, in the state where the second vent hole(s) 447 are aligned with the first vent hole(s) 411, external air may be introduced into the suction pad 401 through the second vent hole(s) 447 and/or the first vent hole(s) 411, and the suction force of the suction pad 401 may be eliminated. For example, in the state where an electronic device provided with the suction pad 401 is placed on a plane (for example, the suction pad 401 is sucked to the plane), the suction pad 401 and/or the electronic device may be easily removed from the plane by rotating the electronic device and/or the cam member 451.

As described above, according to various embodiments of the present disclosure, a vacuum suction device may include a suction pad having a concave inner surface, a vent hole penetrating from the inner surface of the suction pad to an outer surface of the suction pad, and a valve member disposed on the outer surface of the suction pad. As a pressure of a space formed by the inner space of the suction pad decreases, the valve member may close the vent hole from the outer surface of the suction pad.

According to various embodiments, the vacuum suction device may further include a mounting recess formed on the outer surface of the suction pad and connected to one end

portion of the vent hole. The valve member may close the vent hole by closely contacting the mounting recess.

According to various embodiments, an inner circumferential surface of the mounting recess may be a curved surface having a predetermined curvature, and an outer circumferential surface of the valve member may be shaped at least partially in correspondence with the inner circumferential surface of the mounting recess.

According to various embodiments, with the valve member closing the vent hole, a part of the outer circumferential surface of the valve member corresponding to the inner circumferential surface of the mounting recess may be exposed outward from the mounting recess.

According to various embodiments, the valve member may rotate with respect to the suction pad, with the outer circumferential surface of the valve member slidingly contacting the inner circumferential surface of the mounting recess.

According to various embodiments, the vacuum suction device may further include a cover member engaged with the outer surface of the suction pad, and the valve member may be fixed on an inner surface of the cover member.

According to various embodiments, the vacuum suction device may further include a mounting recess formed at one end portion of the vent hole on the outer surface of the suction pad, and the valve member may close the vent hole by closely contacting the mounting recess.

According to various embodiments, an inner circumferential surface of the mounting recess may be a curved surface having a predetermined curvature, and an outer circumferential surface of the valve member may be shaped at least partially in correspondence with the inner circumferential surface of the mounting recess.

According to various embodiments, the vacuum suction device may further include a catching member extended from the outer surface of the suction pad, and an accommodation recess formed on the inner surface of the cover member, and a part of the catching member may be movably accommodated in the accommodation recess.

According to various embodiments, the accommodation recess may be shaped into a closed curve on the inner surface of the cover member, and the valve member may be fixed in an area surrounded by the accommodation recess.

According to various embodiments, the catching member may include an extension portion extended from the outer surface of the suction pad, and a flange portion curved from an end portion of the extension portion, while being tilted with respect to the extension portion, and at least the flange portion may be accommodated in the accommodation recess.

According to various embodiments, a vacuum suction device may include a suction pad having a concave inner surface, at least one first vent hole penetrating from the inner surface of the suction pad to an outer surface of the suction pad, a valve member engaged rotatably with the outer surface of the suction pad, and at least one second vent hole formed in the valve member. As the valve member rotates with respect to the suction pad, the at least one second vent hole is selectively aligned with the at least one first vent hole.

According to various embodiments, the valve member may include a rotation rod disposed on the outer surface of the suction pad, in close contact with one end portion of the at least one first vent hole, the at least one second vent hole may penetrate through the rotation rod, and as the rotation

rod rotates, one end portion of the at least one second vent hole may be selectively connected to one end portion of the at least one first vent hole.

According to various embodiments, the valve member may further include a cam button for making a linear reciprocating movement on the outer surface of the suction pad, a first inclined cam surface formed at one end of the cam button, and a second inclined cam surface formed at one end of the rotation rod, and as the cam button makes a linear reciprocating movement, the first inclined cam surface and the second inclined cam surface may interfere with each other, thereby rotating the rotation rod.

According to various embodiments, the vacuum suction device may further include a mounting recess formed at one end portion of the at least one first vent hole on the outer surface of the suction pad, the valve member may rotate in close contact with an inner circumferential surface of the mounting recess, and the at least one second vent hole may penetrate through the rotation rod.

According to various embodiments, the valve member may be formed to surround at least a part of an outer circumferential surface of the suction pad.

According to various embodiments, a plurality of first vent holes extended along a radius direction of the suction pad may be arranged along a circumferential direction of the suction pad, and a plurality of second vent holes extended along a radius direction of the valve member may be arranged along a circumferential direction of the valve member.

According to various embodiments, the valve member may include a valve plate engaged rotatably with an outer circumferential surface of the suction pad, facing the outer circumferential surface of the suction pad, a rotary shaft member engaged vertically movably with the suction pad and the valve plate, and a cam member having an inclined cam surface interfering the rotary shaft member along with a vertical movement of the rotary shaft member. As the rotary shaft member moves up and down, the rotary shaft member may be interfered by the inclined cam surface, and rotate together with the valve plate with respect to the suction pad.

According to various embodiments, as the suction pad is sucked to a plane, the rotary shaft member may be interfered by the plane and move up and down with respect to the suction pad.

According to various embodiments, the valve member may further include an elastic member between the cam member and the rotary shaft member.

According to various embodiments, the valve member may further include a guide rib extended on one surface of the valve plate, along a vertical movement direction of the rotary shaft member, a guide hole formed in the guide rib, along the vertical movement direction of the rotary shaft member, and a guide protrusion formed on an outer circumferential surface of the rotary shaft member. The guide protrusion may be accommodated in the guide hole, and rotate the rotary shaft member and the valve plate together, while moving up and down with respect to the valve plate.

According to various embodiments, the at least one second vent hole may be formed in the valve plate.

According to various embodiments, as the rotary shaft member is interfered by the inclined cam surface and rotates together with the valve plate with respect to the suction pad, the at least one first vent hole may be closed by the valve plate.

According to various embodiments, an electronic device including the above vacuum suction device may further

19

include a housing. The suction pad may be disposed on a bottom surface of the housing, and the valve member may be mounted in the housing to be interposed between the housing and the suction pad.

According to various embodiments, the suction pad may be deformed by the weight of at least the housing, and the concave space of the inner surface of the suction pad may be contracted.

As is apparent from the foregoing description, the vacuum suction device and/or the electronic device including the same may easily be moved and relocated because the suction pad is removed from a floor without the need for a user to directly raise up the suction pad. For example, as the electronic device is raised up or rotated, the valve member opens the vent holes, thereby facilitating removal of the vacuum suction device (for example, the suction pad) from the floor. In an embodiment, with the electronic device placed on the floor, the suction pad may be sucked to the floor by the weight of the electronic device. Therefore, the electronic device may be stably positioned and its fall-down may be prevented.

While the disclosure has been shown and described with reference to certain exemplary embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

Although the present disclosure has been described with an exemplary embodiment, various changes and modifications may be suggested to one skilled in the art. It is intended that the present disclosure encompass such changes and modifications as fall within the scope of the appended claims.

What is claimed is:

1. A vacuum suction device comprising:

a suction pad including a concave inner surface;

a catching member extended from an outer surface of the suction pad;

a cover member engaged with the outer surface of the suction pad;

an accommodation recess formed on an inner surface of the cover member;

a vent hole penetrating from the concave inner surface of the suction pad to the outer surface of the suction pad; and

a valve member fixed on the inner surface of the cover member while being disposed on the outer surface of the suction pad,

wherein as a pressure of a space, formed by the concave inner surface of the suction pad, decreases, the valve member closes the vent hole from the outer surface of the suction pad, and

wherein a part of the catching member is movably accommodated in the accommodation recess.

2. The vacuum suction device of claim **1**, further comprising a mounting recess formed on the outer surface of the suction pad and connected to one end portion of the vent hole,

wherein the valve member closes the vent hole by closely contacting the mounting recess.

3. The vacuum suction device of claim **2**, wherein an inner circumferential surface of the mounting recess is a curved surface comprises a predetermined curvature, and an outer circumferential surface of the valve member is shaped at least partially in correspondence with the inner circumferential surface of the mounting recess.

20

4. The vacuum suction device of claim **3**, wherein with the valve member closing the vent hole, a part of the outer circumferential surface of the valve member corresponding to the inner circumferential surface of the mounting recess is exposed outward from the mounting recess.

5. The vacuum suction device of claim **3**, wherein the valve member rotates with respect to the suction pad, with the outer circumferential surface of the valve member slidably contacting the inner circumferential surface of the mounting recess.

6. The vacuum suction device of claim **1**, further comprising a mounting recess formed at one end portion of the vent hole on the outer surface of the suction pad,

wherein the valve member closes the vent hole by closely contacting the mounting recess.

7. The vacuum suction device of claim **6**, wherein an inner circumferential surface of the mounting recess is a curved surface comprises a predetermined curvature, and an outer circumferential surface of the valve member is shaped at least partially in correspondence with the inner circumferential surface of the mounting recess.

8. The vacuum suction device of claim **1**, wherein the accommodation recess is shaped into a closed curve on the inner surface of the cover member, and the valve member is fixed in an area surrounded by the accommodation recess.

9. The vacuum suction device of claim **1**, wherein the catching member comprises:

an extension portion extended from the outer surface of the suction pad; and

a flange portion curved from an end portion of the extension portion, while being tilted with respect to the extension portion, and

wherein at least the flange portion is accommodated in the accommodation recess.

10. An electronic device comprising:

a processor;

a communication unit operatively coupled to the processor; and

a vacuum suction device operatively coupled to the electronic device, wherein the vacuum suction device comprises:

a suction pad including a concave inner surface,

a catching member extended from an outer surface of the suction pad,

a cover member engaged with the outer surface of the suction pad,

an accommodation recess formed on an inner surface of the cover member,

a vent hole penetrating from the concave inner surface of the suction pad to the outer surface of the suction pad, and

a valve member fixed on the inner surface of the cover member while being disposed on the outer surface of the suction pad,

wherein as a pressure of a space, formed by the concave inner surface of the suction pad, decreases, the valve member closes the vent hole from the outer surface of the suction pad, and

wherein a part of the catching member is movably accommodated in the accommodation recess.

11. The electronic device of claim **10**, further comprising a housing,

wherein the suction pad is disposed on a bottom surface of the housing, and the valve member is mounted in the housing to be interposed between the housing and the suction pad.

12. The electronic device of claim 11, wherein the suction pad is deformed by weight of at least the housing, and an inner space of the suction pad is contracted.

* * * * *