

US010791675B1

(12) **United States Patent**
Dixon

(10) **Patent No.:** **US 10,791,675 B1**
(45) **Date of Patent:** **Oct. 6, 2020**

(54) **COMBINE SYSTEM**

2201/042 (2013.01); B65G 2812/02128
(2013.01); B65G 2814/0326 (2013.01)

(71) Applicant: **Carl R. Dixon**, Weiner, AR (US)

(58) **Field of Classification Search**

(72) Inventor: **Carl R. Dixon**, Weiner, AR (US)

CPC combination set(s) only.
See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(56) **References Cited**

(21) Appl. No.: **15/985,603**

U.S. PATENT DOCUMENTS

(22) Filed: **May 21, 2018**

5,888,044 A * 3/1999 Baskerville A01C 15/003
198/311

Related U.S. Application Data

* cited by examiner

(63) Continuation of application No. 14/839,954, filed on Aug. 29, 2015, now Pat. No. 9,974,236.

Primary Examiner — Saul Rodriguez
Assistant Examiner — Willie Berry, Jr.

(60) Provisional application No. 62/044,063, filed on Aug. 29, 2014.

(74) *Attorney, Agent, or Firm* — Schrantz Law Firm, PLLC; Stephen D. Schrantz

(51) **Int. Cl.**

B60P 1/00 (2006.01)
A01D 57/20 (2006.01)
A01F 12/60 (2006.01)
A01D 41/12 (2006.01)
B65G 19/14 (2006.01)
B65G 19/22 (2006.01)
B65G 67/24 (2006.01)
B65G 19/28 (2006.01)


(57) **ABSTRACT**



The combine system provides a motor driven paddle system for the movement of grain from combine storage, such as a hopper, to secondary storage, including but not limited to a grain bin, truck, or grain cart. The paddles are constructed from a somewhat rigid material that enable the paddles to move the grain to the secondary storage. The paddle conveyor may be partially enclosed by a housing that protects users from accidental contact with the paddles and the paddle conveyor.

(52) **U.S. Cl.**

CPC **A01D 57/20** (2013.01); **A01D 41/12** (2013.01); **A01F 12/60** (2013.01); **B65G 19/14** (2013.01); **B65G 19/22** (2013.01); **B65G 19/28** (2013.01); **B65G 67/24** (2013.01); **B65G**

17 Claims, 7 Drawing Sheets











FIG. 3









FIG. 8






FIG. 10

COMBINE SYSTEM**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims priority to and is a continuation of U.S. patent application Ser. No. 14/839,954 filed on Aug. 29, 2015 entitled Combine System which is a continuation in part of U.S. Patent Application No. 62/044,063 filed on Aug. 29, 2014 entitled Combine System.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not Applicable.

REFERENCE TO A MICROFICHE APPENDIX

Not Applicable.

RESERVATION OF RIGHTS

A portion of the disclosure of this patent document contains material which is subject to intellectual property rights such as but not limited to copyright, trademark, and/or trade dress protection. The owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure as it appears in the Patent and Trademark Office patent files or records but otherwise reserves all rights whatsoever.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates generally to moving grain during the harvest. The present invention replaces the screw auger system currently implemented in grain conveyors. The present invention provides a new and safer conveyor system.

II. Description of the Known Art

The combine harvester, or simply combine, is a machine that harvests grain crops. The combine reaps, threshes, and winnows the grain crops to process the grain. Among the crops harvested with a combine are wheat, oats, rye, barley, corn, soybeans and flax. The waste straw left behind on the field is the remaining dried stems and leaves of the crop with limited nutrients which is either chopped and spread on the field or baled for feed and bedding for livestock.

Typically, a combine cuts the crop material, threshes the grain therefrom, separates the grain from the straw, and cleans the grain before storing the grain in an onboard tank. Straw and crop residue is ejected from the rear of the machine.

In conventional combines, the harvested grain is stored in an on-board grain tank. The grain is removed from the grain tank by a main unloading auger positioned within an unloading chute. This unloading chute permits the grain to be transferred into a bulk transport vehicle such as a truck or wagon, which is positioned on the one side of the combine harvester where the exit port of the unloading chute is located. The auger creates an unnecessary hazard as the auger may cause bodily harm to a user. The PTO driving the auger could also cause bodily harm.

Accordingly, it would be desirable to provide an improved device and system for unloading grain from a combine.

Patents and patent applications disclosing relevant information are disclosed below. These patents and patent applications are hereby expressly incorporated by reference in their entirety.

5 U.S. Pat. No. 6,499,930 issued to Dixon (“the ’930 patent”) teaches an unloading system for a grain bin. The unloading system taught by the ’930 patent includes a sweep conveyor for sweeping grain from the interior of the grain bin to a well in the floor of the grain bin. The sweep conveyor taught by the ’930 patent includes an elongated frame, a first sprocket at one end of the frame, a second sprocket at the other end of the frame, an endless chain extending between the first and second sprockets, a plurality of spaced apart paddles attached to the chain, and a motor for causing the chain to rotate whereby the paddles will drag or sweep grain to the well in the floor of the grain bin.

15 U.S. Pat. No. 7,040,980 issued to Ketsel (“the ’980 patent”) teaches a combine harvester for harvesting grain and seed crops that includes a double unloading auger system for unloading in both directions of travel harvested feed grains produced in one round or two lengths of a field to storage area of transport vehicle. The double unloading auger system taught by the ’980 patent has a first main unloading auger assembly being selectively operable for discharging the harvested grain from a first side of the combine harvester to the transport vehicle and a second main unloading auger assembly being selectively operable for discharging the harvested grain from a second side of the combine harvester to the transport vehicle. A pair of transverse auger taught by the ’980 patent is located in a bottom wall of the grain tank and is selectively reversibly driven for delivery of the harvested grain from the grain tank to either the first main unloading auger assembly or the second main unloading auger assembly. As a result, if one unloading auger system is inoperative the combine taught by the ’980 patent can be continued operating at a reduced capacity until the inoperative auger system is repaired.

20 U.S. Pat. No. 5,718,556 issued to Forsyth on Feb. 17, 1998 (“the ’556 patent”) teaches a bulk granular material transport system having multiple compartments with a detachable elevating conveyor to permit the conveyor to assist with unloading as well as loading of the transport device. Each compartment taught by the ’556 patent may be individually discharged onto a horizontal conveyor which delivers the seed to the elevating conveyor when the elevating conveyor is in its first position. The elevating conveyor taught by the ’556 patent is suspended from an adjustable crane which is pivotable on the frame of the transport system. The elevating conveyor taught by the ’556 patent may be released from its first position such that the discharge of the elevating conveyor may be positioned over a compartment of the transport device. All mechanisms taught by the ’556 patent are individually actuable through a remote control device.

SUMMARY OF THE INVENTION

The present invention provides a method and system for moving grain during harvest. A drag-chain sweep system provides a new and safe method for moving grain by a combine tractor in harvesting said grain at the field level. The system replaces the current screw-auger system. The present invention provides a much longer lasting wear factor.

65 Currently, within nearly all grain movement systems, a screw-auger tool is used with much safety precautions to achieve a movement of grain from the field to a proper grain

storage unit for later use. The drag-chain sweep system is a safer, faster alternative to the aforementioned screw auger system. The present invention provides an enclosed belt system with attached rubber paddles at intervals needed for the job to provide a no-limit point to point moving process where safety is key and time is not wasted or misused. The grain is cut and separated from the plant by combine tractor units. With this system, the conveyor, such as a belt system, transfers the grain to the enclosed paddle system. The enclosed paddle system, which is powered by a motor, such as a hydraulic motor, pulls the grain out of the hopper storage through an adjacent arm to unload out of the hopper to secondary storage, such as a grain buggy, bin, cart, or other storage.

By enclosing the paddle belt system, safety is insured as no human contact with moving parts is required. The enclosure reduces an increasing amount of screw-auger related injuries or malfunctions. Current systems are limited in productivity due to safety precautions and the systems' inability to move grain at a rate faster than the augers are able to rotate. By implementing the drag-chain paddle system, the amount of grain moved is only limited to the amount of grain that can be fed to the system and safety is insured by protecting the worker from exposure to the moving parts.

It is an object of the present invention to provide a safer working environment for a farmer.

It is also an object of the present invention to eliminate the need for an auger system inside of the combine.

It is also an object of the present invention to enclose the grain conveying system to provide a safer work environment.

It is also an object of the present invention to move grain at a faster rate.

It is also an object of the present invention to protect the user from exposure to the moving parts

These and other objects and advantages of the present invention, along with features of novelty appurtenant thereto, will appear or become apparent in the course of the following descriptive sections and the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

In the following drawings, which form a part of the specification and which are to be construed in conjunction therewith, and in which like reference numerals have been employed throughout wherever possible to indicate like parts in the various views:

FIG. 1 is a sectional view of a known grain moving system;

FIG. 2 is a sectional view of one embodiment of the present invention;

FIG. 3 is a top perspective view of one embodiment of the paddle conveyor of one embodiment of the present invention;

FIG. 4 is a sectional view thereof;

FIG. 5 is a sectional view thereof;

FIG. 6 is a top perspective view of one embodiment of the present invention;

FIG. 7 is a sectional view thereof;

FIG. 8 is an environmental view of one embodiment of the present invention;

FIG. 9 is a sectional view thereof; and

FIG. 10 is a top view thereof.

DETAILED DESCRIPTION

FIG. 1 shows a sectional view of a known grain system 10 with augers 12, 14, 16. Augers 12, 14, 16 assist with transferring the grain outside of the bin of system 10.

FIG. 2 shows a sectional view of one embodiment of the unloading system 100. The combine processes the grain and transfers the grain to storage 102, such as hopper storage. As the storage 102 fills, the grain must be transferred from storage 102 such that combine can continue to operate.

Conveyor 104, a flat belt conveyor which can be as wide as necessary, moves the grain towards paddle conveyor 108. Opening 106 allows the grain to flow from conveyor 104 to the paddle conveyor 108. Paddles 110 push the grain upwards to secondary storage, such as a transport vehicle, such as a cart or truck, or to a grain bin.

The unloading system 100 is a safer, faster alternative to the aforementioned screw auger system 10. The present invention provides a paddle conveyor 108 with attached rubber paddles 110 at intervals needed for the job. Paddles 110 provide a no-limit point to point moving process where safety is key and time is not wasted or misused. The grain is cut and separated from the plant by combine tractor units.

With this system, the grain is moved by the conveyor 104 to the paddle conveyor 108. The conveyor 104 pushes the grain out of storage 102, the grain storage, of the combine. Conveyor 104 pushes the grain into paddle conveyor 108 to transfer the grain from storage 102. The paddle conveyor 108 and conveyor 104 of one embodiment are powered by hydraulic motors.

The conveyor 104 pushes the grain out of the hopper storage 102 through an adjacent arm to unload the grain from the hopper to the paddle conveyor 108. The paddles 110 push the grain out of the hopper to a different storage, such as a portable storage, grain buggy unit, etc. The grain is then stored in the storage. If the grain is transferred to portable storage, the grain is transported to a proper grain storage unit elsewhere.

By enclosing the paddle conveyor 108 as shown in FIG. 3, safety is insured. The enclosure limits human contact with moving parts to reduce an increasing amount of screw-auger related injuries or malfunctions. Current systems are limited in productivity due to safety precautions and the systems' inability to move grain at a rate faster than the augers are able to rotate. By implementing the drag-chain paddle system, the amount of grain moved is only limited to the amount of grain that can be fed to the system. Safety is insured by protecting the worker from exposure to the moving parts.

The unloading system 100 of the present invention unloads grain from the interior of the combine storage 102. The combine storage 102 may be of any typical construction providing a housing having wall structure and floor or floor structure for supporting a quantity of grain. Thus, for example, the combine storage 102 may be constructed of metal with the wall structure. The combine storage 102 has at least one opening allowing grain to pass through to be unloaded from the interior of the combine storage.

The unloading system 100 includes a conveyor 104 positioned above the floor 112 of the combine storage 102 for conveying grain towards opening 106. At opening 106, conveyor 104 transfers the grain to paddle conveyor 108 and paddles 110.

The conveyor 104 is positioned on the floor 112 of the combine storage 102. The conveyor 104 has a first end 114 for being positioned adjacent a first wall of the combine storage 102. The conveyor 104 has a second end 116 for preferably being positioned adjacent opening 106 of the combine storage 102. The conveyor 104 transfers grain from within the combine storage 102 to opening 106. The con-

5

veyor **104** moves grain from first end **114** to end **116** to transfer the grain stored within combine storage **102** to opening **106**.

The conveyor **104** of one embodiment is a flat belt conveyor powered by a motor, such as a hydraulic motor. The conveyor **104** may be as wide as necessary to cover the floor **112** of the combine storage **102**. The conveyor **104** should extend from one end of the wall to the opening **106** to transport the grain to opening **106**.

The conveyor **104** transfers the grain to the paddle conveyor **108** at opening **106**. The paddle conveyor **108** transports the grain vertically and outward at exit opening **138** where the grain is deposited into a grain cart or other secondary storage. Paddle conveyor **108** implements a first wheel **120**, preferably a first sprocket, rotatably attached to the housing **107** adjacent a first end, and a second wheel **126**, preferably a second sprocket, rotatably attached to the housing **107** adjacent the second end.

As shown in FIGS. 2-5, a first shaft **120** preferably rotatably extends transversely through the first end of the housing **107** (preferably through the first and second side walls) for rotatably attaching the first sprocket **118** to the housing **107**, and a second shaft **128** preferably rotatably extends transversely through the second end of the housing **107** (preferably through the first and second side walls **140**, **142**) for rotatably attaching the second sprocket **126** to the housing **107**. The shafts **120**, **128** may be rotatably mounted to the side walls of the housing **107** via bearings or the like. The sprockets **118**, **126** may be standard, off-the-shelf roller chain drive sprockets or the like, keyed or otherwise fixed to the respective shaft **120**, **128** substantially centered between the side walls **140**, **142**. In one embodiment, the paddles **110** are approximately as wide as the space between walls **140**, **142** such that the paddles will move the grain found between the walls **140**, **142**.

The paddle conveyor **108** includes a belt, preferably a roller chain **144**, passing about the first and second sprockets **118**, **126**. The roller chain **144** is also preferably an off-the-shelf item that acts with the sprockets **118**, **126** to form a chain drive.

A plurality of spaced apart paddles **110** attached to the chain **144** transport the grain. Each paddle **110** may be rectangular shaped and is preferably made of rubber. The paddles **110**, while somewhat flexible, must be rigid enough to push grain without excessive flexing. In one embodiment, the paddles **110** are constructed from a resilient material. The housing **107** is preferably shaped and sized so that the paddles **110** are covered except at the opened ends **106**, **138** to provide a protective cover extending over the top and at least a portion of the sides of the sprockets **118**, **126**, the chain **144**, and the paddles **110** to provide safety and protection. Each paddle **110** is preferably attached to a link of the chain **110** by a rigid connector **146** or the like.

Paddles **130** located towards the bottom of housing **107** push the grain towards opening **138** in direction **122**. These paddles **130** extend downward towards the floor of housing **107** to sweep the grain to opening **138**. Paddles **132** return from opening **138** to opening **106** to begin the process of sweeping the grain to opening **138**. Such an endless loop of paddles **110** enable the paddle conveyor **108** to continue sweeping the grain from opening **106** to opening **138** to second storage, such as a grain cart or bin. Paddles **132** move in direction **124** towards opening **106**. Paddles **130** move in direction **122** toward opening **138**.

Drive **136** of paddle conveyor **108** rotates one of the sprockets **118**, **126** to cause the chain **144** to rotate about the first and second sprockets **118**, **126** and cause the paddles

6

110 to sweep grain from the floor of the housing **107** to opening **138**. The drive **136** preferably includes a motor and a gear box for reducing the speed or revolutions per minute of the drive or output shaft of the motor and changing the axis of rotation of the drive or output shaft of the motor, and a belt drive **148** or the like for transferring power from the gear box to the shaft **128**. The motor and gear box are preferably mounted on the second end of the housing **107**. The motor may be a hydraulic motor or other motor.

As shown in FIG. 7, the belt drive **148** may include a first pulley **150** or sprocket attached to the drive or output shaft of the gear box, a second pulley **152** or sprocket attached to one end of the shaft **128**, and a belt or chain **154** extending between the first and second pulleys **150**, **152**. The belt drive **148** transfers power from the motor to the sprocket **126** to cause the chain **144** and paddles **110** to circle about the sprockets **118**, **126** in the direction of the arrows **122**, **124**. The motor enables movement of paddles **110** thus causing paddles **110** to push grain toward the second end of the housing **107** to exit **138**. A protective cover or housing may be provided over the pulley **150**, **152** and belt **154**.

In another embodiment, the paddle conveyor **108** may be retrofitted on an existing hopper of a combine. The augers found within the combine storage, such as a hopper, transfer the grain from inside the combine storage to the paddle conveyor **108**. The augers transfer the grain outside of the combine storage and deposit the grain to paddle conveyor.

As shown in FIGS. 3-5, the paddle conveyor may be operated within a housing that at least partially encloses the paddles **110**. The housing provides two openings **136**, **138** within the housing to allow the grain to be deposited from the combine storage into the housing and to allow the paddles to transfer the grain into a secondary storage, such as grain cart. In another embodiment shown in FIGS. 6 and 7, the housing may be open in the bottom. The grain may be deposited onto plane **162**. The paddles then push the grain along plane **162**. The plane may provide side walls **158**, **160** to prevent loss of the grain at the sides of the plane.

FIGS. 8-10 show another embodiment of the paddle system **102** placed within storage **164**. In such an embodiment, the grain is transferred from combine storage **102** to storage **164**. A conveyor, such as conveyor **104**, transfers the grain from combine storage **102** to storage **164**. A vertical conveyor may be required to transfer the grain from combine storage **102** to storage **164** depending on the positioning of the storage **164**.

In one embodiment, storage **164** secures to the combine at the grain exit of the combine. In another embodiment, the storage **164** and paddle system **108** secure to the combine at the combine exit. Grain exit of the combine transfers the grain to storage **164**. The paddle system **108** transfers the grain directly from the grain exit. The paddle system **108** rotates in relation to the combine for unloading the grain at multiple storage areas without moving the combine. The rotation of paddle system **108** reduces the requirement of moving the combine to reach other storage areas.

In another embodiment, the clearance of the combine may not be sufficient to allow the storage **164** to secure to the combine at the grain exit of the combine. In such an embodiment, a conveyor may transport the grain to the storage **164**. The paddle system **108** and storage **164** may be pivotally attached to the combine to allow rotation of the paddle system **108** and storage **164**.

Storage **164** provides paddle system **102** with access to the grain. Opening **106** of the paddle system **102** accepts the grain into paddle system **102**. The paddle system **102** pushes the grain towards the secondary storage.

Paddle system **102** secures to storage **164** to allow the paddle system **102** to rotate. Pivot **166** secures the paddle system **102** and storage **164** to each other. Paddle system **102** rotates for transferring grain to different areas. Instead of requiring the user to move the combine, the user simply rotates the paddle system **102** to access other storage areas. Paddle system **102** rotates in relation to the combine storage **102** and combine. In another embodiment, paddle system **102** and storage **164** both rotate in relation to the combine storage **102** and combine.

Paddle system **102** functions similarly to the paddle systems described above. Paddles **110** transfer grain from opening **106** to opening **138**. As discussed above, paddles **110** along the lower section of combine system **108** push the grain to opening **138**. The paddles **110** return from opening **138** to opening **106** along the upper section of combine system **108**.

In one embodiment, the sweep system **108** secures to storage **164** to such that the sweep system **108** is centrally attached to avoid off set rotation of the sweep system **108** with the storage **164**. In such an embodiment in which the sweep system **108** secures to the storage **164**, the sweep system **108** are secured to an attachment arm that attaches the sweep system **108** and storage **164** with the combine. The sweep system **108** and storage **164** can be adjusted between an in use position for use and a transport position for travelling. The attachment arm increases the adjustability of the sweep system **108** and storage **164**. The attachment arm may vary according to the equipment to which the sweep system **108** attaches.

Although the present invention has been described and illustrated with respect to a preferred embodiment and a preferred use therefor, it is not to be so limited since modifications and changes can be made therein which are within the full intended scope of the invention.

From the foregoing, it will be seen that the present invention is one well adapted to obtain all the ends and objects herein set forth, together with other advantages which are inherent to the structure.

It will be understood that certain features and subcombinations are of utility and may be employed without reference to other features and subcombinations. This is contemplated by and is within the scope of the claims.

As many possible embodiments may be made of the invention without departing from the scope thereof, it is to be understood that all matter herein set forth or shown in the accompanying drawings is to be interpreted as illustrative and not in a limiting sense.

What is claimed is:

1. An apparatus for transferring grain from combine storage to a secondary storage, the apparatus comprising:
 a first storage for placement of the grain;
 a housing for transferring the grain to the secondary storage, the housing secured to the first storage;
 a conveyor secured within the housing;
 at least one paddle extending perpendicular from the conveyor;
 an intake opening of the housing wherein the intake opening accepts grain into the housing, the intake opening located within the first storage;
 an exit opening of the housing wherein the grain exits the housing at the exit opening; and
 the paddle transferring grain from the intake opening to the exit opening;
 a sidewall of the first storage wherein the sidewall is separate from the housing, the sidewall located laterally outward from the housing;

a pivot securing both the first storage and the housing to the combine, the pivot securing the housing interior of the sidewall of the first storage, the first storage and the housing rotatable in relation to the combine wherein the pivot secures the intake opening within the first storage.

2. The apparatus of claim 1 wherein the conveyor divides the housing into an upper section and a lower section.

3. The apparatus of claim 2 wherein the exit opening is located within the lower section.

4. The apparatus of claim 3 wherein the paddle travels in the lower section to the exit opening.

5. The apparatus of claim 1 wherein the housing pivotally attaches to the combine.

6. The apparatus of claim 1 wherein the conveyor pivotally attaches to the combine.

7. The apparatus of claim 6 wherein the first storage pivotally attaches to the combine.

8. The apparatus of claim 7 wherein the paddles are constructed from a resilient material.

9. The apparatus of claim 7 wherein the paddle is constructed from rubber.

10. The apparatus of claim 1 wherein the housing passes through a side wall of the first storage.

11. The apparatus of claim 10 wherein the housing transfers grain from inside of the first storage to the secondary storage outside of the first storage.

12. An apparatus for transferring grain from combine storage to a secondary storage, the apparatus comprising:

a first storage for placement of the grain;

a housing for transferring the grain to the secondary storage, the housing secured to the first storage;

a conveyor secured inside of the housing, the conveyor dividing the housing into an upper section and a lower section;

at least one paddle extending perpendicular from the conveyor;

an intake opening of the housing wherein the intake opening accepts grain into the housing, the intake opening located within the first storage;

an exit opening of the housing wherein the grain exits the housing at the exit opening, the exit opening outside of the first storage;

the paddle transferring grain from the intake opening to the exit opening;

a sidewall of the first storage wherein the sidewall is separate from the housing, the sidewall located laterally outward from the housing;

a base of the first storage that extends laterally outward from the housing for collecting the grain from the combine storage;

a pivot securing both the first storage and the housing to the combine, the pivot securing the housing to the base interior of the sidewall of the first storage, the first storage and the housing rotatable in relation to the combine wherein the pivot secures the housing to the first storage.

13. The apparatus of claim 12 wherein the exit opening is located within the lower section.

14. The apparatus of claim 13 wherein the paddle travels in the lower section to the exit opening.

15. The apparatus of claim 12 wherein the paddle is constructed from rubber.

16. The apparatus of claim 15 wherein the housing passes through the side wall of the first storage.

17. An apparatus for transferring grain from combine storage to a secondary storage, the apparatus comprising:
 a first storage for placement of the grain;

9

a housing for transferring the grain to the secondary storage, the housing secured to the first storage, wherein the housing passes through a side wall of the first storage;

a conveyor secured inside of the housing, the conveyor 5 dividing the housing into an upper section and a lower section;

at least one paddle extending perpendicular from the conveyor;

an intake opening of the housing wherein the intake 10 opening accepts grain into the housing, the intake opening located within the first storage;

an exit opening of the housing wherein the grain exits the housing at the exit opening, the exit opening outside of 15 the first storage;

the paddle transferring grain from the intake opening to the exit opening, the paddle traveling in a counterclockwise direction, the paddle travelling from the intake

10

opening to the exit opening in the lower portion of the housing, the paddle returning to the intake opening from the exit opening in the upper portion of the housing;

a sidewall of the first storage wherein the sidewall is separate from the housing, the sidewall located laterally outward from the housing;

a base of the first storage that extends laterally outward from the housing for collecting the grain from the combine storage;

a pivot securing both the first storage and the housing to the combine, the first storage and the housing rotatable in relation to the combine, the pivot securing the housing to the base interior of the sidewall of the first storage, the first storage and the housing rotatable in relation to the combine wherein the pivot secures the intake opening within the first storage.

* * * * *