



US010801757B2

(12) **United States Patent**
Hellmann

(10) **Patent No.:** **US 10,801,757 B2**
(45) **Date of Patent:** **Oct. 13, 2020**

(54) **REFRIGERATION SYSTEM**

(71) Applicants: **Carrier Corporation**, Farmington, CT (US); **Sascha Hellmann**, Mainz-Kostheim (DE)

(72) Inventor: **Sascha Hellmann**, Mainz-Kostheim (DE)

(73) Assignee: **CARRIER CORPORATION**, Palm Beach Gardens, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 571 days.

(21) Appl. No.: **15/324,321**

(22) PCT Filed: **Jul. 9, 2014**

(86) PCT No.: **PCT/EP2014/064706**

§ 371 (c)(1),

(2) Date: **Jan. 6, 2017**

(87) PCT Pub. No.: **WO2016/004988**

PCT Pub. Date: **Jan. 14, 2016**

(65) **Prior Publication Data**

US 2017/0159977 A1 Jun. 8, 2017

(51) **Int. Cl.**

F25B 1/10 (2006.01)

F25B 5/02 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F25B 1/10** (2013.01); **F25B 5/02** (2013.01); **F25B 9/08** (2013.01); **F25B 41/04** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC **F25B 1/10**; **F25B 9/08**; **F25B 5/02**; **F25B 41/04**; **F25B 2400/16**; **F25B 2400/13**;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,324,105 A 4/1982 Cann
6,658,888 B2 12/2003 Manohar et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1265136 C 7/2006
CN 101097100 A 1/2008

(Continued)

OTHER PUBLICATIONS

Chinese First Office Action and Search Report for application CN 20140080513.6, dated Nov. 5, 2018, 8 pages.

(Continued)

Primary Examiner — Len Tran


Assistant Examiner — Melodee Jefferson

(74) *Attorney, Agent, or Firm* — Cantor Colburn LLP

(57) **ABSTRACT**

A refrigeration system (1) has A) an ejector circuit (3) comprising: Aa) a high pressure compressor unit (2) comprising at least one compressor (2a, 2b, 2c, 2d); Ab) a heat rejecting heat exchanger/gas cooler (4); Ac) an ejector (6); Ad) a receiver (8) having a gas outlet (8b) which is connected to an inlet of the high pressure compressor unit (2). B) a normal cooling temperature flowpath (5) comprising in the direction of flow of the refrigerant: Ba) a normal cooling temperature expansion device (10) fluidly connected to a liquid outlet (8c) of the receiver (8); Bb) a normal cooling temperature evaporator (12); Bc) an ejector secondary inlet line (68) with an ejector inlet valve (26) fluidly connecting an outlet (12b) of the normal cooling temperature evaporator (12) to a suction inlet (6b) of the ejector (6); and Bd) a normal cooling temperature flowpath valve unit (22) configured for fluidly connecting the inlet of the high pressure compressor unit (2) selectively either to the gas outlet (8b) of the receiver (8) or to the outlet (12b) of the normal cooling temperature evaporator (12); C) a freezing temperature

(Continued)



flowpath (7) comprising in the direction of flow of the refrigerant: Ca) a freezing temperature expansion device (14) fluidly connected to the liquid outlet (8c) of the receiver (8); Cb) a freezing temperature evaporator (16); Cc) a freezing temperature compressor unit (18) comprising at least one freezing temperature compressor (18a, 18b); and Cd) a freezing temperature flowpath valve unit (20) configured for fluidly connecting the outlet of the freezing temperature compressor unit (18) selectively either to the inlet of the high pressure compressor unit (2) or to the ejector inlet valve (26).

14 Claims, 4 Drawing Sheets

- (51) **Int. Cl.**
F25B 9/08 (2006.01)
F25B 41/04 (2006.01)
- (52) **U.S. Cl.**
 CPC ... *F25B 2341/0012* (2013.01); *F25B 2400/13* (2013.01); *F25B 2400/16* (2013.01)
- (58) **Field of Classification Search**
 CPC *F25B 2341/0012*; *F25B 1/06*; *F25B 9/008*; *F25B 2341/0014*; *F25B 20/05*
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,675,609	B2	1/2004	Takeuchi et al.
6,834,514	B2	12/2004	Takeuchi et al.
7,325,414	B2	2/2008	Taras et al.
8,109,111	B2	2/2012	Yamada
8,375,741	B2	2/2013	Taras et al.

2010/0162751	A1	7/2010	Nishijima et al.
2011/0005268	A1*	1/2011	Oshitani F25B 41/00 62/500
2012/0167601	A1*	7/2012	Cogswell F25B 1/10 62/115
2012/0266618	A1	10/2012	Levy et al.

FOREIGN PATENT DOCUMENTS

CN	101573579	A	11/2009
CN	102272541	A	12/2011
CN	103282730	A	9/2013
CN	103429975	A	12/2013
CN	103597296	A	2/2014
CN	103842745	A	6/2014
DE	102004007932	A1	9/2004
DE	102011100198	A1	11/2011
EP	2221559	A1	8/2010
EP	2450647	A2	5/2012
EP	2532991	A2	12/2012
EP	2594839	A2	5/2013
JP	2005249315	A	9/2005
WO	2008076122	A1	6/2008
WO	2009091094	A1	7/2009
WO	2009091096	A1	7/2009
WO	2012092686	A1	7/2012
WO	WO-2012092686	A1 *	7/2012 F25B 1/10
WO	2012169146	A1	12/2012

OTHER PUBLICATIONS

International Search Report and Written Opinion for application PCT/EP20141064706, dated Mar. 10, 2015, 10 pages.
 Visser, Klaas, "The World's First Multifunction Two Stage Transcritical CO2 Refrigeration System At a Food Processing Plant in Melbourne, Australia", ATMOSphere Oct. 11-12, 2011, Sofitel Brussels, 39 pages.

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4

1

REFRIGERATION SYSTEM

The invention is related to a refrigeration system, in particular to a refrigeration system comprising an ejector and two refrigeration circuits providing different evaporator temperatures.

PRIOR ART

A refrigeration system comprising an ejector is disclosed e.g. by WO 2012/092686 A1. Based on various measured parameters, including ambient air temperature, pressure drop at the expansion valve, etc., the refrigeration system is switched between a base line mode and an ejector mode in order to enhance the energy efficiency of the system in at least some range of ambient temperatures.

It would be beneficial to increase the energy efficiency of a refrigeration system comprising an ejector and two refrigeration circuits providing different evaporator temperatures over a wide range of ambient temperatures.

DISCLOSURE OF THE INVENTION

A refrigeration system according to exemplary embodiments of the invention comprises:

A) an ejector circuit comprising in the direction of flow of a circulating refrigerant:

Aa) a high pressure compressor unit comprising at least one compressor;

Ab) a heat rejecting heat exchanger/gas cooler;

Ac) an ejector having

a primary inlet fluidly connected to the outlet(s) of the heat rejecting heat exchanger/gas cooler;

a secondary inlet; and

an outlet, which is fluidly connected to

Ad) a receiver having a gas outlet which is connected to an inlet of the high pressure compressor unit.

B) a normal cooling temperature flowpath comprising in the direction of flow of the refrigerant:

Ba) a normal cooling temperature expansion device fluidly connected to a liquid outlet of the receiver;

Bb) a normal cooling temperature evaporator;

Bc) an ejector secondary inlet line with a valve fluidly connecting an outlet of the normal cooling temperature evaporator to the secondary inlet of in the ejector; and

Bd) a normal cooling temperature flowpath valve unit configured for fluidly connecting the inlet of the high pressure compressor unit selectively either to the gas outlet of the receiver or to the outlet of the normal cooling temperature evaporator; C) a freezing temperature flowpath comprising in the direction of flow of the refrigerant:

Ca) a freezing temperature expansion device fluidly connected to the liquid outlet of the receiver;

Cb) a freezing temperature evaporator;

Cc) a freezing temperature compressor unit comprising at least one freezing temperature compressor; and

Cd) a freezing temperature flowpath valve unit configured for fluidly connecting the outlet of the freezing temperature compressor unit selectively either to the inlet of the high pressure compressor unit or to the ejector inlet valve.

The skilled person will easily understand that refrigeration systems according to embodiments of the invention may also comprise a plurality of heat rejecting heat exchangers/gas coolers, ejectors, normal cooling temperature expansion devices, normal cooling temperature evaporators, freezing

2

temperature expansion devices and freezing temperature evaporators, respectively connected in parallel.

A refrigeration system according to exemplary embodiments of the invention can be operated in at least four different modes of operation, allowing to adjust the operation of the system to different conditions, which in particular includes the ambient air temperature, for operating the refrigeration system with high efficiency under changing conditions.

A refrigeration system according to exemplary embodiments of the invention in particular can be operated in a first mode of operation, which is called "standard operation mode" and includes the steps of:

circulating a first flow of refrigerant from the high pressure compressor unit via the heat rejecting heat exchanger/gas cooler, the ejector, and the receiver to the inlet side of the high pressure compressor unit;

directing a second flow of refrigerant from the receiver via the normal cooling temperature expansion device and the normal cooling temperature evaporator to inlet side of the high pressure compressor unit; and

directing a third flow of refrigerant from the receiver via the freezing temperature expansion device, the freezing temperature evaporator and the freezing temperature compressor unit to the inlet side of the high pressure compressor unit.

Said "standard operation mode" has shown to be efficient at relatively low ambient temperatures, in particular at ambient temperatures below 10-15° C.

A refrigeration system according to an embodiment of the invention further may be operated in a second mode of operation, which is called "economizer mode" and includes the step of directing refrigerant from the gas outlet of the receiver to the economizer compressor of the high pressure compressor unit.

Said "economizer mode" has shown to be efficient at medium ambient temperatures, in particular at ambient temperatures between 10-15° C. and 18-20° C.

A refrigeration system according to exemplary embodiments of the invention also may be operated in a third mode of operation, which is called "first ejector mode" and includes the steps of

circulating a first flow of refrigerant from the high pressure compressor unit via the heat rejecting heat exchanger/gas cooler; the ejector and the receiver back to the inlet side of the high pressure compressor unit;

directing a second flow of refrigerant from the receiver via the normal cooling temperature expansion device, the normal cooling temperature evaporator and the ejector inlet valve to the secondary inlet of the ejector; and

directing a third flow of refrigerant from the receiver via the freezing temperature expansion device, the freezing temperature evaporator and the freezing temperature compressor unit to the inlet side of the high pressure compressor unit.

Said "first ejector mode" has shown to be efficient at higher ambient temperatures, in particular at ambient temperatures between 18-20° C. and 30-35° C.

A refrigeration system according to exemplary embodiments of the invention further may be operated in a fourth mode of operation, which is called "second ejector mode" and includes the steps of

circulating a first flow of refrigerant from the high pressure compressor unit via the heat rejecting heat exchanger/gas cooler;

3

directing a second flow of refrigerant from the receiver via the normal cooling temperature expansion device, the normal cooling temperature evaporator and the ejector inlet valve to the secondary inlet of the ejector; and

directing a third flow of refrigerant from the receiver via the freezing temperature expansion device, the freezing temperature evaporator, the freezing temperature compressor unit and the ejector inlet valve to the secondary inlet of the ejector.

Thus "second ejector mode" has shown to be efficient at very high ambient temperatures, in particular ambient temperatures above 30-35° C.

By selecting the most appropriate mode of operation, a refrigeration system according to exemplary embodiments of the invention can be operated with high efficiency over a very wide range of ambient temperatures, in particular from ambient temperatures below 10° C. to ambient temperatures above 35° C. Thus, the refrigeration system can be operated efficiently over a wide range of ambient conditions.

In the following a refrigeration system according to exemplary embodiments of the invention will be described with reference to the enclosed figures.

SHORT DESCRIPTION OF THE FIGURES

FIG. 1 shows a refrigeration system according to an exemplary embodiment of the invention operating in a first mode of operation.

FIG. 2 shows refrigeration system according to an exemplary embodiment of the invention operating in a second mode of operation.

FIG. 3 shows refrigeration system according to an exemplary embodiment of the invention operating in a third mode of operation.

FIG. 4 shows refrigeration system according to an exemplary embodiment of the invention operating in a fourth mode of operation.

DETAILED DESCRIPTION OF THE FIGURES

The embodiment of a refrigeration system 1 shown in the figures comprises an ejector circuit 3, a normal cooling temperature flowpath 5, and a freezing temperature flowpath 7 respectively circulating a refrigerant.

In the figures, the flow of the refrigerant in the ejector circuit 3 is indicated by dashed lines, the flow of refrigerant in the normal cooling temperature flowpath 5 is indicated by dotted lines, and the flow of refrigerant in the freezing temperature flowpath 7 is indicated by dash-dotted lines.

FIG. 1 shows a refrigeration system 1 according to an exemplary embodiment of the invention operating in a first mode of operation.

The ejector circuit 3 comprises in the direction of the flow F of the circulating refrigerant a high pressure compressor unit 2 including a plurality of compressors 2a-2d connected in parallel. The compressors 2a-2d in particular include an economizer compressor 2a and a plurality of standard compressors 2b, 2c and 2d.

The high pressure side outlets of the compressors 2a-2d are fluidly connected to an outlet manifold 40, which collects the refrigerant from the compressors 2a-2d and delivers it via a heat rejection heat exchanger/gas cooler inlet line 42 to the inlet 4a of a heat rejecting heat exchanger/gas cooler 4. The heat rejecting heat exchanger/gas cooler 4 is configured for transferring heat from the refrigerant to the environment reducing the temperature of the refrigerant. In the

4

embodiment shown in the figures, the heat rejecting heat exchanger/gas cooler 4 comprises two fans 38 which may be operated for blowing air through the heat rejecting heat exchanger/gas cooler 4 in order to enhance the transfer of heat from the refrigerant to the environment.

The cooled refrigerant leaving the heat rejecting heat exchanger/gas cooler 4 through its outlet 4b is delivered via a heat rejecting heat exchanger/gas cooler outlet line 44 and a successive ejector primary inlet line 46 to a primary inlet 6a of an ejector 6, which is configured for expanding the refrigerant to a reduced pressure. The expanded refrigerant leaves the ejector 6 via an ejector outlet 6c and is delivered by means of an ejector outlet line 48 to an inlet 8a of a receiver 8. Within the receiver 8, the refrigerant is separated by gravity into a liquid portion collecting at the bottom of the receiver 8 and a gas phase portion collecting in an upper portion of the receiver 8.

The gas phase portion of the refrigerant leaves the receiver 8 through a receiver gas outlet 8b, which is arranged in the upper portion of the receiver 8, and is delivered via a receiver gas outlet line 50, 52 to the inlet side of the high pressure compressor unit 2 completing the refrigerant cycle of the ejector circuit 3.

Optionally, a suction line heat exchanger 36 may be arranged in the receiver gas outlet line 50, 52 for allowing a transfer of heat between the refrigerant leaving the heat rejecting heat exchanger/gas cooler 4 and the gaseous refrigerant leaving the receiver 8 through the gas outlet 8b. Such a heat exchange has been found to enhance the efficiency of the refrigeration system 1.

In the first mode of operation ("standard operation mode"), which is illustrated by FIG. 1, gas phase refrigerant from the receiver 8 is delivered via an open economizer valve 24 and a second inlet line 58 downstream of the economizer valve 24 to a normal cooling temperature flowpath valve unit 22, which (in said first mode of operation) delivers the gas phase refrigerant via a high pressure compressor unit inlet line 60 and a high pressure compressor unit inlet manifold 62 to the inlets of the standard compressors 2b, 2c, 2d.

Refrigerant from the liquid phase portion of the refrigerant collecting at the bottom of the receiver 8 exits from the receiver 8 via its liquid outlet 8c and is delivered through a receiver liquid outlet line 64 to a first expansion device 10 ("normal cooling temperature expansion device") and a second expansion device 14 ("freezing temperature expansion device").

After having passed the normal cooling temperature expansion device 10, where it has been expanded further, the refrigerant enters through an inlet 12a into a first evaporator 12 ("normal cooling temperature evaporator"), which is configured for operating at "normal" cooling temperatures, in particular in a temperature range of 0° C. to 15° C. for providing "normal temperature" refrigeration.

In said first mode of operation ("standard operation mode"), the refrigerant, after having left the normal cooling temperature evaporator 12 via its outlet 12b, flows through a normal cooling temperature evaporator outlet line 66 into the second inlet line 58 of the normal cooling temperature flowpath valve unit 22 from where it is delivered to the inlet side of the high pressure compressor unit 2 together with the gas portion of the refrigerant supplied by the receiver 8.

An ejector secondary inlet line 68 branches from the normal cooling temperature evaporator outlet line 66 downstream of the normal cooling temperature evaporator 12 and fluidly connects the normal cooling temperature evaporator outlet line 66 to an inlet side of an ejector inlet valve 26. An

5

outlet side of said ejector inlet valve **26** is fluidly connected to a secondary (suction) inlet **6b** of the ejector **6**. The ejector inlet valve **26**, however, is closed in the standard operation mode, which is illustrated in FIG. **1**, and in consequence no refrigerant is delivered from the outlet **12b** of the normal cooling temperature evaporator **12** via the ejector secondary inlet line **68** into the ejector **6**.

The portion of the liquid refrigerant, which has been expanded by the second (freezing temperature) expansion device **14** enters through an inlet **16a** into a second (“freezing temperature”) evaporator **16**, which is configured for operating at freezing temperatures below 0° C., in particular at temperatures in the range of -15° C. to -5° C. for providing freezing temperature refrigeration. The refrigerant leaves the freezing temperature evaporator **16** through its outlet **16b** and is delivered via a freezing temperature evaporator outlet line **70** to the inlet side of a freezing temperature compressor unit **18**, which comprises one or more freezing temperature compressors **18a**, **18b**.

In operation, the freezing temperature compressor unit **18** compresses the refrigerant supplied by the freezing temperature evaporator outlet line **70** to medium pressure. After said compression, the refrigerant is delivered via a freezing temperature compressor unit outlet line **72** and an optional desuperheater **34** to a freezing temperature flowpath valve unit **20**. Said freezing temperature flowpath valve unit **20** is configured for selectively directing the refrigerant supplied by the freezing temperature compressor unit **18** either via a first outlet line **74** into the high pressure compressor unit inlet line **60**, which is done in the first mode of operation illustrated in FIG. **1**, or via a second outlet line **76** into the second inlet line **58** of the normal cooling temperature flowpath valve unit **22** when the refrigeration system **1** is operated in an alternative mode of operation, which will be discussed further below.

In an embodiment, an oil separator **32** is provided within the ejector secondary inlet line **68**. The oil separator **32** is configured for separating oil comprised in the refrigerant circulating within the normal cooling temperature flowpath **5** from said refrigerant and feeding said separated oil into the freezing temperature evaporator outlet line **70** in order to avoid that the oil collects within the normal cooling temperature flowpath **5** and in consequence the compressors **18a**, **18b**, **2b**, **2c**, **2d** run out of oil. Said oil separation is in particular important when the refrigeration system **1** is operated in the third or fourth mode of operation, which will be discussed below, as in said modes of operation the refrigerant from the normal cooling temperature evaporator **12** is not fed back into the high pressure compressor unit **2**. When the refrigeration system **1** is operated in one of said modes of operation, oil separation is necessary for transferring oil from the normal cooling temperature flowpath **5** back to the compressors **18a**, **18b**, **2b**, **2c**, **2d**.

Pressure and/or temperature sensors **28**, **30** are provided at the normal cooling temperature evaporator outlet line **66** and at the receiver gas outlet line **52**, respectively, for measuring the pressure and/or the temperature of the refrigerant flowing in said lines **66**, **52**. Alternatively or additionally an ambient temperature sensor **78** is provided, which is configured for measuring the ambient temperature.

The sensors **28**, **30**, **78** deliver their outputs to a control unit **80**, which is configured for controlling the operation of the compressor units **2**, **18** and the valve units **20**, **22** based on the outputs of at least some of the sensors **28**, **30**, **78** in order to operate the refrigeration system with optimal efficiency.

6

For transferring the data and the control signals, the control unit **80** may be connected with the sensors **28**, **30**, **78**, the compressor units **2**, **18** and the valve units **20**, **22** by means of electrical and/or hydraulic control lines, which are not shown in the figures, or by means of a wireless connection.

The control unit **80** in particular is configured for switching the operation of the refrigeration system between different modes of operation by driving the valve units **20**, **22** accordingly. Said switching in particular may be controlled and triggered based on the pressure and/or temperature data provided by the sensors **28**, **30**, **78**.

The first mode of operation (“standard operation mode”), which has been described before with reference to FIG. **1**, is typically employed at relatively low ambient temperatures, e.g. at ambient temperatures below 10-15° C.

At higher ambient temperatures, e.g. in the range of 10-15° C. to 18-20° C., which are detected either directly by means of the ambient temperature sensor **78** or indirectly by a change of the refrigerant pressure measured by at least one of the sensors **28**, **30**, the control unit **80** switches the refrigeration system **1** into a second mode of operation (“economized mode”), which is illustrated in FIG. **2**.

In said second mode of operation the economizer valve **24** is shut in order to deliver the gas phase refrigerant supplied by the receiver **8** to the economizer compressor **2a** instead of delivering it to the standard compressors **2b**, **2c**, **2d** as it is done in the first mode of operation.

Thus, when the system is operated in the second mode of operation (“economized mode”), the refrigerant circulating within the ejector circuit **3** is driven and compressed only by means of the economizer compressor **2a**, whereas the refrigerant supplied by the evaporators **12**, **16** is still compressed by the standard compressors **2b**, **2c**, **2d**. As the economizer compressor **2a** is optimized for this kind of operation, this work sharing enhances the efficiency of the system when operated in the medium range of ambient temperatures mentioned before.

At even higher ambient temperatures, e.g. in the range of 18-20° C. to 30-35° C., the system is switched into a third mode of operation called “first ejector mode”, which is illustrated in FIG. **3**.

In said third mode of operation the economizer valve **24** remains closed as in the second mode of operation (FIG. **2**), but the normal cooling temperature flowpath valve unit **22** is switched for fluidly connecting its first inlet line **56**, which is fluidly connected to the evaporator’s **8** gas outlet line **52**, to the high pressure compressor unit inlet line **60**. In consequence, the gas phase refrigerant supplied by the receiver **8** is compressed by a combination of all compressors **2a-2d** of the high pressure compressor unit **2**, in particular including the economizer compressor **2a** and the standard compressors **2b**, **2c**, **2d**.

Further, in said third mode the normal cooling temperature flowpath valve unit **22** is switched to close the fluid connection between its second inlet line **58** fluidly connected to the outlet **12b** of the normal cooling temperature evaporator **12** and the high pressure compressor unit line **60**, and the ejector inlet valve **26** is opened. As a result, the refrigerant from the normal cooling temperature evaporator **12** is sucked by the ejector **6** via the ejector secondary inlet line **68** and the ejector inlet valve **26** into the secondary (suction) inlet **6b** of the ejector **6**.

Thus, when the refrigeration system **1** is operated in the third mode of operation (“first ejector mode”), which is illustrated in FIG. **3**, the refrigerant of the normal cooling temperature flowpath **5** is not delivered to the compressors

2a-2d of the high pressure compressor unit 2 anymore, but it is driven only by means of the ejector 6. In contrast, the refrigerant of the freezing temperature flowpath 7 is still compressed by the freezing temperature compressor unit 18 and the successive high pressure compressor unit 2, as the freezing temperature flowpath valve unit 20 has not been switched with respect to the first and second modes of operation.

Finally, in case the ambient temperature increases even further to very high temperatures above 30-35° C., the refrigeration system 1 is switched into a fourth mode of operation, which is called “second ejector mode” and illustrated in FIG. 4.

For switching the refrigeration system from the third mode of operation (“first ejector mode”), which has been described before with reference to FIG. 3, into the fourth mode of operation (“second ejector mode”) the freezing temperature flowpath valve unit 20 is switched to deliver the refrigerant supplied by the freezing temperature compressor unit 18 via its second outlet line 76 into the second inlet line 58 of the normal cooling temperature flowpath valve unit 22 instead of delivering the refrigerant into the high pressure compressor unit inlet line 60.

When the refrigeration system 2 is operated in said fourth mode of operation (“second ejector mode”), the position of the normal cooling temperature flowpath valve unit 22 remains the same as in the third mode of operation (“first ejector mode”), i.e. the connection between the second inlet line 58 of the normal cooling temperature flowpath valve unit 22 and the high pressure compressor unit inlet line 60 remains closed. In consequence, the refrigerant supplied by the freezing temperature compressor unit 18 is delivered via the second inlet line 58 of the normal cooling temperature flowpath valve unit 22 together with the refrigerant supplied by the normal cooling temperature evaporator 12 into the ejector secondary inlet line 68 from where it is sucked through the open ejector inlet valve 26 into the secondary (suction) inlet 8b of the ejector 6.

Thus, when the refrigeration system 2 is operated in said fourth mode of operation (“second ejector mode”), the refrigerant flow of the normal cooling temperature flowpath 5 as well as the refrigerant flow of the freezing temperature flowpath 7 are both driven only by means of the ejector 6, and the compressors 2a-2d of the high pressure compressor unit 2 are operated only for driving the refrigerant circulating within the ejector circuit 3 driving the ejector 6.

A refrigeration system, as it has been described before, may be operated with high efficiency over a wide range of ambient temperatures, in particular from ambient temperatures below 10° C. to ambient temperatures above 35° C.

Further Embodiments

In an embodiment the high pressure compressor unit comprises an economizer compressor and at least one standard compressor in order to allow an economical compression of the refrigerant by means of the economizer compressor.

In an embodiment the refrigeration system further comprises an economizer valve which is configured for fluidly connecting the gas outlet of the receiver selectively to the inlet(s) of the economizer compressor or to the inlet(s) of the at least one standard compressor. This allows to selectively compress the refrigerant by means of the economizer compressor and/or by means of the standard compressor(s) in order to select the most efficient compression, which may

depend on the actual environmental conditions, in particular including the ambient temperature, and/or the pressure of the refrigerant.

In an embodiment the normal cooling temperature flowpath valve unit comprises: an outlet fluidly connected to the inlet side of the high pressure compressor unit, a first inlet fluidly connected to the gas outlet of the receiver, and a second inlet fluidly connected to an outlet of the normal cooling temperature evaporator. Such a configuration allows to select efficiently between different modes of operation by switching the normal cooling temperature flowpath valve unit.

In an embodiment the freezing temperature flowpath valve unit comprises: an inlet fluidly connected to an outlet side of the freezing temperature compressor unit, a first outlet fluidly connected to the inlet side of the high pressure compressor unit, and a second outlet fluidly connected to the ejector secondary inlet line. Such a configuration allows to select efficiently between different modes of operation by switching the freezing temperature flowpath valve unit.

In an embodiment at least one of the freezing temperature flowpath valve unit and the normal cooling temperature flowpath valve unit comprises a three-way-valve. A three-way-valve provides a compact and cheap valve unit providing the desired functionality. Alternatively, the valve unit(s) may be provided by an appropriate combination of at least two simple two-way-valves.

At least one of the valves may be an adjustable valve, in particular a continuously adjustable valve, for allowing to switch gradually, in particular continuously between the different modes of operation.

In an embodiment a desuperheater is arranged between the freezing temperature compressor unit and the freezing temperature flowpath valve unit, which allows to enhance the efficiency of the freezing temperature flowpath even further.

In an embodiment the refrigeration system further comprises a suction line heat exchanger which is configured for providing heat exchange between refrigerant flowing from the gas outlet of the receiver to the high pressure compressor unit and refrigerant flowing from the heat rejecting heat exchanger/gas cooler to the ejector in order to enhance the efficiency of the ejector circuit.

In an embodiment the refrigeration system further comprises at least one pressure and/or temperature sensor which is configured for measuring the pressure/temperature of the refrigerant circulating within the refrigeration system.

Such a sensor in particular may be provided at the inlet side of the high pressure compressor unit and/or at the outlet side of the normal cooling temperature evaporator.

Providing such sensors allows to switch between the different modes of operation based on the pressure and/or temperature of the refrigerant measured by the sensors. Alternatively or additionally an ambient temperature sensor may be provided allowing to switch between different modes of operation based on the measured ambient temperature.

In an embodiment the refrigeration system further comprises an oil separator for separating oil from the refrigerant, in particular from the refrigerant flowing within the normal temperature flowpath in order to avoid that the compressors run out of oil.

In an embodiment the oil separator is in particular configured to deliver the oil, which has been separated from the refrigerant, to the inlet of the freezing temperature compressor unit in order to ensure a sufficient supply of oil to the compressors of the freezing temperature compressor unit.

While the invention has been described with reference to exemplary embodiments, it will be understood by those skilled in the art that various changes may be made and equivalence may be substitute for elements thereof without departing from the scope of the invention. In particular, modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention is not limited to the particular embodiments disclosed, but that the invention will include all embodiments falling within the scope of the pending claims.

REFERENCE NUMERALS

1 refrigeration system
 2 high pressure compressor unit
 2a economizer compressor
 2b, 2c, 2d standard compressors
 3 ejector circuit
 4 heat rejecting heat exchanger/gas cooler
 4a inlet of the heat rejecting heat exchanger/gas cooler
 4b outlet of the heat rejecting heat exchanger/gas cooler
 5 normal cooling temperature flowpath
 6 ejector
 6a primary inlet of the ejector
 6b secondary inlet of the ejector
 6c outlet of the ejector
 7 freezing temperature flowpath
 8 receiver
 8a inlet of the receiver
 8b gas outlet of the receiver
 8c liquid outlet of the receiver
 10 normal cooling temperature expansion device
 12 normal cooling temperature evaporator
 12a inlet of the normal cooling temperature evaporator
 12b outlet of the normal cooling temperature evaporator
 14 freezing temperature expansion device
 16 freezing temperature evaporator
 16a inlet of the freezing temperature evaporator
 16b outlet of the normal cooling temperature evaporator
 18 freezing temperature compressor unit
 18a, 18b freezing temperature compressors
 20 freezing temperature flowpath valve unit
 22 normal cooling temperature flowpath valve unit
 24 economizer valve
 26 ejector inlet valve
 28, 30 pressure sensors
 32 oil separator
 34 desuperheater
 36 suction line heat exchanger
 38 fan
 40 manifold of the high pressure compressor unit
 42 heat rejecting heat exchanger/gas cooler inlet line
 44 heat rejecting heat exchanger/gas cooler outlet line
 46 ejector primary inlet line
 48 ejector outlet line
 50, 52 receiver gas outlet line
 54 economizer compressor inlet line
 56 first inlet line of the normal cooling temperature flowpath valve unit
 58 second inlet line of the normal cooling temperature flowpath valve unit
 60 high pressure compressor unit inlet line
 62 high pressure compressor unit inlet manifold
 64 receiver liquid outlet line
 66 normal cooling temperature evaporator outlet line
 68 ejector secondary inlet line

70 freezing temperature evaporator outlet line
 72 freezing temperature compressor unit outlet line
 74 first outlet line of the freezing temperature flowpath valve unit
 76 second outlet line of the freezing temperature flowpath valve unit
 78 ambient temperature sensor
 80 control unit

The invention claimed is:

1. A refrigeration system comprising

A) an ejector circuit comprising in the direction of flow of a circulating refrigerant:

Aa) a high pressure compressor unit comprising at least one compressor;

Ab) a heat rejecting heat exchanger/gas cooler;

Ac) an ejector having

a primary inlet fluidly connected to the outlet(s) of the heat rejecting heat exchanger/gas cooler;

a secondary inlet; and

an outlet, which is fluidly connected to

Ad) a receiver having a gas outlet which is connected to an inlet of the high pressure compressor unit;

B) a normal cooling temperature flowpath comprising in the direction of flow of the refrigerant:

Ba) a normal cooling temperature expansion device fluidly connected to a liquid outlet of the receiver;

Bb) a normal cooling temperature evaporator;

Bc) an ejector secondary inlet line with an ejector inlet valve fluidly connecting an outlet of the normal cooling temperature evaporator to the secondary inlet of the ejector; and

Bd) a normal cooling temperature flowpath valve unit configured for fluidly connecting the inlet of the high pressure compressor unit selectively either to the gas outlet of the receiver or to the outlet of the normal cooling temperature evaporator;

C) a freezing temperature flowpath comprising in the direction of flow of the refrigerant:

Ca) a freezing temperature expansion device fluidly connected to the liquid outlet of the receiver;

Cb) a freezing temperature evaporator;

Cc) a freezing temperature compressor unit comprising at least one freezing temperature compressor; and

Cd) a freezing temperature flowpath valve unit configured for fluidly connecting the outlet of the freezing temperature compressor unit selectively either to the inlet of the high pressure compressor unit or to the ejector inlet valve

wherein a desuperheater is arranged between the freezing temperature compressor unit and the freezing temperature flowpath valve unit.

2. The refrigeration system of claim 1, wherein the high pressure compressor unit comprises an economizer compressor and at least one standard compressor.

3. The refrigeration system of claim 2, further comprising an economizer valve, the economizer valve and the normal cooling temperature flowpath valve unit being configured for fluidly connecting the gas outlet of the receiver selectively to the inlet(s) of the economizer compressor or to the inlet(s) of the at least one standard compressor.

4. The refrigeration system of claim 1, wherein the normal cooling temperature flowpath valve unit comprises:

an outlet fluidly connected to the inlet side of the high pressure compressor unit;

a first inlet fluidly connected to the gas outlet of the receiver; and

11

a second inlet fluidly connected to an outlet of the normal cooling temperature evaporator;
and allows to fluidly connect the outlet selectively with the first inlet or the second inlet.

5 **5.** The refrigeration system of claim 1, wherein the freezing temperature flowpath valve unit comprises:

an inlet fluidly connected to an outlet side of the freezing temperature compressor unit;

10 a first outlet fluidly connected to the inlet side of the high pressure compressor unit; and

a second outlet fluidly connected to the ejector secondary inlet line;

and allows to fluidly connect the inlet selectively with the first outlet or the second outlet.

15 **6.** The refrigeration system of claim 1, wherein at least one of the freezing temperature flowpath valve unit and the normal cooling temperature flowpath valve unit comprises a three-way-valve or a combination of at least two valves, wherein at least one of the valves is in particular an adjustable valve.

20 **7.** The refrigeration system of claim 1, comprising a suction line heat exchanger providing heat exchange between refrigerant flowing from the gas outlet of the receiver to the high pressure compressor unit and refrigerant flowing from the heat rejecting heat exchanger/gas cooler to the ejector.

25 **8.** The refrigeration system of claim 1, further comprising at least one of an ambient temperature sensor, which is configured for measuring the ambient temperature, a pressure sensor, which is configured for measuring the pressure of the refrigerant at the inlet side of the high pressure compressor unit, and a pressure sensor, which is configured for measuring the pressure of the refrigerant at the outlet of the normal cooling temperature evaporator.

30 **9.** The refrigeration system of claim 1, further comprising an oil separator for separating oil from the refrigerant, in particular from refrigerant flowing within the normal temperature flowpath.

35 **10.** The refrigeration system of claim 9, wherein the oil separator is configured to deliver the oil, which has been separated from the refrigerant leaving the normal cooling temperature evaporator to the inlet of the freezing temperature compressor unit.

40 **11.** A method of operating a refrigeration system of claim 1 in a standard mode, the method comprising:

45 circulating a first flow of refrigerant from the high pressure compressor unit via the heat rejecting heat exchanger/gas cooler;

12

the ejector and the receiver to the inlet side of the high pressure compressor unit;

directing a second flow of refrigerant from the receiver via the normal cooling temperature expansion device

and the normal cooling temperature evaporator to the inlet side of the high pressure compressor unit; and

directing a third flow of refrigerant from the receiver via the freezing temperature expansion device, the freezing temperature evaporator and the freezing temperature compressor unit to the inlet side of the high pressure compressor unit.

12. A method of operating a refrigeration system of claim 7 in a first ejector mode, the method comprising:

circulating a first flow of refrigerant from the high pressure compressor unit via the heat rejecting heat exchanger/gas cooler; the ejector and the receiver back to the inlet side of the high pressure compressor unit;

directing a second flow of refrigerant from the receiver via the normal cooling temperature expansion device, the normal cooling temperature evaporator and the ejector inlet valve to the secondary inlet of the ejector; and

directing a third flow of refrigerant from the receiver via the freezing temperature expansion device, the freezing temperature evaporator and the freezing temperature compressor unit to the inlet side of the high pressure compressor unit.

13. A method of operating a refrigeration system of claim 1 in a second ejector mode, the method comprising:

circulating a first flow of refrigerant from the high pressure compressor unit via the heat rejecting heat exchanger/gas cooler; the ejector and the receiver to the inlet side of the high pressure compressor unit;

directing a second flow of refrigerant from the receiver via the normal cooling temperature expansion device, the normal cooling temperature evaporator and the ejector inlet valve to the secondary inlet of the ejector; and

directing a third flow of refrigerant from the receiver via the freezing temperature expansion device, the freezing temperature evaporator, the freezing temperature compressor unit and the ejector inlet valve to the secondary inlet of the ejector.

14. A method of operating a refrigeration system according to claim 1 in an economizer mode, wherein the method comprises directing refrigerant from the gas outlet of the receiver to the economizer compressor of the high pressure compressor unit.

* * * * *